

EchoTrack™

Expanded Ambient Temperature Ultrasonic Couplant

EchoTrack is the lowest price, high performance gel ultrasonic couplant.



PRODUCT DESCRIPTION

Available in two viscosities: High and medium to address most ultrasonic applications.

Improved resistance to corrosion salts

Easy removal with water wash, not film-forming.

No formaldehydes, nitrates, nitrites or glycol ethers.

Safety/environmental and operator friendly.

PACKAGING

Carton of (12) 12-oz./340 ml bottles

1 gallon / 3.8 liter cubitainer

5 gallon / 19 liter cubitainer

55 gallon / 208 liter drum*

PRODUCT SPECIFICATIONS

Operating Range:

18° to 180° F (-8° to 82° C)

- **Viscosity:**
Standard (Medium, flowable gel)
High (Stiff gel, stays in place)
- **Halogens & Sulfur:** Less than 50 ppm
- **pH:** 8.0 nominal at 20° C
- **Compliance:**
ASME Boiler & Pressure Vessel Code (T-533)
NAVSHIPS 250-1500
FAA-AC #25-29 (Glycerin-free)
Nuclear Grade (< 50 ppm Halogens & Sulfur)

***Note:** High viscosity requires Echo supplied hand pump for 55 gallon drums.

REMOVAL: Wipe with a rag or water wash.

SDS available at www.echoultrasonics.com

ECHO
ultrasonics



7952 Nieman Road, Lenexa, KS 66214-1560 USA
Phone: 913-685-0675, Fax: 913-685-1125
www.ndtsupply.com, sales@ndtsupply.com

Echo Ultrasonics®, LLC
774 Marine Drive | Bellingham, WA 98225
echoultrasonics.com | sales@echoultrasonics.com
360.671.9121