

DAKOTA ULTRASONICS



PR-8² Sonic Tester

The **PR-82** is the first affordable **Sonic Tester**, utilizing state-of-the-art digital technology to produce fast and accurate readings. It requires no special training to operate.

Unlike calipers, the **PR-82** will measure where there is access to only one side. This makes it valuable when measuring roll cage thickness, cylinder walls (before and after boring) and heads during porting.

The **PR-82** measures in two modes. The first mode takes a measurement at the point you place the probe. The second is

the Scan mode, which is helpful when measuring cylinder walls and roll cages. Place the probe at the bottom of the cylinder and drag it to the top, the gauge will display the thinnest reading measured.

The **PR-82** is a lightweight, rugged tool that is resistant to water and oil. Other features include a backlit LCD and a bar graph to indicate signal stability.

The **5 year warranty** indicates how we feel about the quality of the **PR-82**.

The **PR-82** can go where you go, to do the work you do, saving you time and money, making fast, accurate measurements.

SOUND SOLUTIONS

THE PR-8² SONIC TESTER

With the PR-82, you can make accurate reliable measurements and scan a length of material for the thinnest point.

A partial list of the custom probes for racing applications:

• Chassis Tubing, Roll Cages*	3/16" 10MHz Flat Probe head	
• Cast Iron Cylinder Heads*	1/4" 5MHz with 1" or 9" Wand	0.60" radius
• Cast Iron & Aluminum Heads	1/4" 7.5MHz with 1" or 9" Wand	0.60" radius
• Aluminum Cylinder Heads*	1/4" 10MHz with 1" or 9" Wand	0.60" radius
• Cylinder Blocks*	1/2" 5MHz	2.00" radius

* best performance on stated material

The PR-82 comes complete, ready to use and is protected by Dakota Ultrasonics
5 year limited warranty—a statement of its quality.

Typical automotive applications are:

- Cylinder
- Head Ports
- Roll Cage
- Chassis Tubing
- Body Panels
- Windshields

SPECIFICATIONS

Physical

Weight:

10 ounces (with batteries).

Size:

2.5 W x 4.5 H x 1.24 D inches
(63.5 W x 114.3 H x 31.5 D mm).

Operating Temperature:

-20 to 120F (-30 to 50C).

Case:

Extruded aluminum body
with nickel-plated aluminum
end caps (gasket sealed).

Keypad

Sealed membrane that is
resistant to both water and
petroleum products.

Six tactile-feedback keys.

Transducer

Dual-element (transmit and
receive).

1 to 10 MHz frequency range.

Locking quick disconnect
LEMO connectors.

4 foot cable.

Custom transducers available
for special applications.

Power Source

Two 1.5V alkaline or
1.2V NiCad AA cells.

Typically operates for
80 hours on alkaline and
20 hours on NiCad.

Display flashes when battery is
low. Unit turns off automatically
when battery is too low to
operate reliably.

Display

Multi-function 4.5 digit liquid
crystal display with 0.500 inch
numerals, backlit for use in
poor light conditions.

Backlight is selectable on/off/auto
(illuminates only when taking a
measurement).

Bar graph indicates stability
of reading.

Certification

Factory calibration traceable to NIST
& MIL-STD-45662A.

Warranty

5 year limited.

Measuring

Range:

Measures from 0.025 to 19.999
inches (0.63 to 500 millimeters).
Range dependent on material
and transducer type.

Automotive Applications:

0.050 to 1.500 inches in casted
materials.

Units:

English & Metric

Resolution:

0.001 inches (0.01 millimeters)

Velocity Range:

0.0492 to .5511 in/μs.
(1250 to 14,000 m/sec)

Four readings per second for
single point measurements or 16
per second in SCAN mode.

One or Two point calibration op-
tion.



MADE IN THE USA

Distributed by:



7952 Nieman Road, Lenexa, KS 66214-1560 USA
Phone: 913-685-0675, Fax: 913-685-0675
www.ndtsupply.com, sales@ndtsupply.com



DAKOTA ULTRASONICS

1500 Green Hills Road, #107

Scotts Valley, CA 95066

Ph: (831) 431-9722

Fax: (831) 431-9723

Website: www.dakotaultrasonics.com

Email: info@dakotaultrasonics.com