PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ABL090-6	BLADE PROBE, .090 THICK, 6"L, STRAIGHT, 50-500KHX, MICRODOT. Includes Test Report and Certificate of Conformance.	MP-900.090-60			
AF-5094	CLINCHED FASTENER PROBE 1.0"X1.0" 4FT CABLE TRIAX FISCHER CONNECTOR 2-7 KHZ DIFF	,	,	,	
APN-45-4/6MHZ	45 DEGREE SURFACE PROBE, MICRODOT CONNECTOR 6MHz 4.0" LONG .125"OD TIP	PEN45-4/6M			
APN-925-4.5B	ABSOLUTE SHIELDED EDDY CURRENT PROBE 50-500KHz 90 DEGREES .25" DROP WITH .600" CRANK, MICRODOT CONNECTOR, 4.5" PROBE LENGTH.	313P24F			
APN-95FX	FLEXIBLE COPPER SURFACE PROBE 9.5" LONG STRAIGHT SHAFT WITH MICRODOT CONNECTOR. 50-500KHz	MP-95FX			
APN-4FX	FLEXIBLE SURFACE PROBE 4.0" LONG, .125"Ø TIP MICRODOT CONNECTOR 50-500KHz				
AMHY.187250/500K	ADJUST MANUAL BOLT-HOLE PROBE 1.5"WL, ,MD CONNECTOR, 500K-1M	MHY.187250			
AMHY.125156/2MHZ	ADJUST MANUAL BOLT-HOLE PROBE 1.5 WL MICRODOT CONNECTOR, 1-3MHZ	MHY.1251562MHZ			
AMHY.156187/2MHZ	ADJUST MANUAL BOLT-HOLE PROBE 1.5 WL MICRODOT CONNECTOR, 1-3MHZ	MHY.156187/2MHZ			
AMHY.187250/2MHZ	ADJUST MANUAL BOLT-HOLE PROBE 1.5 WL MICRODOT CONNECTOR, 1-3MHZ	MHY.187250/2MHZ			
AMHY.250312/2MHZ	ADJUST MANUAL BOLT-HOLE PROBE 1.5 WL MICRODOT CONNECTOR, 1-3MHZ	MHY.250312/2MHZ			
AMHY.312375/2MHZ	ADJUST MANUAL BOLT-HOLE PROBE 1.5 WL MICRODOT CONNECTOR, 1-3MHZ	MHY.312375/2MHZ			
AMHY.375437/2MHZ	ADJUST MANUAL BOLT-HOLE PROBE 1.5 WL MICRODOT CONNECTOR, 1-3MHZ	MHY.375437/2MHZ			
AMHY.125156/500K	ADJUST MANUAL BOLT-HOLE PROBE 1.5 WL MICRODOT CONNECTOR, 500K-1M	MHY.125156			
AF-5127750/.875	ADJUSTABLE MANUAL BOLT HOLE PROBE .750875 4 PIN FISCHER CONNECTOR( ABSOLUTE) 1-3MHZ	NEC-3129-48/56			
AF-5127875/1.0	ADJUSTABLE MANUAL BOLT HOLE PROBE .875-1.0" 4 PIN FISCHER CONNECTOR( ABSOLUTE) 1-3MHZ	NEC-3129-56/64			
AURY250312/3WL	ADJUSTABLE UNIVERSAL ROTARY PROBE 3.0" WORKING LENGTH .250"312' 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR				
AMHY.156187/500K	ADJUST MANUAL BOLT-HOLE PROBE 1.5"WL, ,MD CONNECTOR, 500K-1M	MHY.156187			
AMHY.156187	ADJUST MANUAL BOLT-HOLE PROBE 1.5"WL, ,MD CONNECTOR, 50-500KHZ	MHY.156187			
AMHY.500625	ADJUST MANUAL BOLT-HOLE PROBE 1.5"WL, ,MD CONNECTOR, 50-500KHZ	MHY.500625			
AMHY156187/3WL	ADJUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 5/32" OD				
APN-9125-6FX	FLEXIBLE SURFACE PROBE 50-500KHZ				
ATPNU-6FX	FLEXIBLE SURFACE PROBE, .125"Ø TUBING, TAPERED TIP 0.187"TO 0.063" TRIAX FISCHER CONNECTOR, 50-500 KHz, UNSHIELDED	TMTF-187-063-60FX	DO815E1015E2079		
ASDP5-10K-2	LF REFLECTION SPOT PROBE 5- 80KHZ TRIAX FISCHER CONNECTOR	RS10005-2/TF	SDP.5-10K-2		
ASDP44/500HZ	LF REFLECTION SPOT PROBE 500HZ-60KHZ TRIAX FISCHER CONNECTOR				
ASDP420/5K	LF SPOT PROBE DIFFERENTIAL SKHZ-100KHZ, 1.75L, TRIAX				
ASDP4/20K	LOW FFREQUENCY REFLECTION SPOT PROBE, .400 DIA 1-40KHz WITH TOP MOUNT TRIAX FISCHER CONNECTOR.	SDP.4-20K			
ARP60-1.0/100Hz	LOW FREQUENCY REFLECTION RING PROBE .60" ID 1.0" OD 100HZ-3KHZ TRIAX FISCHER CONNECTOR 737 PART 6 57-10-60, pg.2	LFRR.600/1.0			
AF-4032-3	LOW FREQUENCY REFLECTION RING PROBE, 150HZ-1KHz(.600" ID) x (1.0" OD) x (1.25" H) TRIAX FISCHER CONNECTOR	TEK-3006-3	NEC4028-3		
ARP-1.0055-200H	LOW FREQUENCY RING PROBE REFLECTION55" ID 1.00" OD TRIAX FISCHER CONNECTOR 200HZ-2KHZ	RDP1.0055/200H			
ASDP55-1	LOW FREQUENCY SPOT PROBE RIGHT ANGLE REFLECTION TRIAX FISCHER CONNECTOR 1-100KHZ. DIAMETER=.550"	RS055-1TF			
ASDP.50-10K-5	LOW FREQUENCY SPOT PROBE RIGHT ANGLE, .500"Ø, 5-100KHz REFLECTION WITH TRIAX FISCHER CONNECTOR500"	SDP.50-10K-5			
ATP-45-6/5K	LOW FREQUENCY SURFACE PROBE 45 DEG .500 DROP 6.0" LONG .187"OD TUBING DIFFERENTIAL, TRIAX FISCHER CONNECTOR 1-30KHZ				
ATMHD120	MANUAL BOLT HOLE DIFFERENTIAL COIL TRIAX FISCHER CONNECTOR 1.0" WORKING LENGTH 200KHZ-1MHZ	BPMD-8TF			
ATMHD156	MANUAL BOLT HOLE DIFFERENTIAL COIL TRIAX FISCHER CONNECTOR 1.0" WORKING LENGTH 200KHZ-1MHZ	BPMD-10TF			
ATMH156	MANUAL BOLT HOLE DIFFERENTIAL COIL TRIAX FISCHER CONNECTOR 1.1" WORKING LENGTH 200KHZ-1MHZ	BPMD-10TF			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATMHYD.500562	MANUAL BOLT HOLE EDDY CURRENT PROBE 500KHZ-3MHZ, 2"WL. DUAL COIL				
AMH.438	MANUAL BOLT HOLE PROBE 50-500KHZ MICRODOT CONNECTOR 7/16" x 3.0" OVERALL LENGTH WITH COLLAR	•			
ATMHD.281/2WL	MANUAL BOLT HOLEPROBE DIFFERENTIAL COIL TRIAX FISCHER CONNECTOR 2.0" WORKING LENGTH 500KHZ-2MHZ	9216172			
ARR.312SE/1.5WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ. SPLIT END FOR RA SCANNER 1.5"WORKING LENGTH .312375" 4 PIN STEP LEMO CONNECTOR	9217157			
ARP78/1.40	REFL RING PROBE 1.1 OAL .780" ID 1.40" OD TRIAX FISCHER CONNECTOR	RR0114-3-TF			
AURYFBF500562/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .500562 Includes Test Report and Certificate of Conformance	URYFB.500562-2			
AURYFBF562625/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .562625 Includes Test Report and Certificate of Conformance	URYFBF.562-625-2			
ARP7-2K-5	REFLECTION RING PROBE .360" ID .700" OD TRIAX FISCHER CONNECTOR 500HZ-2KHZ	RR207-5TF			
ARP-1.05/50HZ	REFLECTION RING PROBE, SOHZ-3KHZ.500" ID 1.0" OD TRIAX FISCHER CONNECTOR	RDP1.05/50HZ			
AURFX687/6WL	ROTARY FLEX PROBE 100KHZ-2MHZ,6.0" WORKING LONG 4 PIN FISCHER CONNECTOR	EMFLX.156-4			
AURFX.156-4WL/.5"	ROTARY FLEX PROBE 100KHZ-2MHZ, 4"WL .500" TIP LONG 4 PIN FISCHER CONN.	EMFLX.156-4			
AURFX-9/64SS/4WL	ROTARY FLEX SHAFT PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL TIP 4 PIN FISCHER CONNECTOR	•			
AURFX.500-7WL	ROTARY FLEX SHAFT PROBE 100KHZ-2MHZ, FOR MINI MITE 4 PIN FISCHER CONNECTOR 7.0"WL WITH COLLAR				
AURFX.281-7WL	ROTARY FLEX SHAFT PROBE 100KHZ-2MHZ, FOR MINI MITE 4.0" WORKING LENGHT 4 PIN FISCHER CONNECTOR	-			
AURFX.187-7WL	ROTARY FLEX SHAFT PROBE 100KHZ-2MHZ, FOR MINI MITE 7.0" WORKING LENGHT 4 PIN FISCHER CONNECTOR	-			
AURFX.250-7WL	ROTARY FLEX SHAFT PROBE 100KHZ-2MHZ, FOR MINI MITE 7.0" WORKING LENGHT 4 PIN FISCHER CONNECTOR	-			
AURFX.156-6WL	ROTARY FLEX SHAFT PROBE 100KHZ-2MHZ, 6" WORKING LENGTH, 4PIN FISCHER CONNECTOR	EMFLX.156-6			
AURFX.437-7WL	ROTARY FLEX SHAFT PROBE 100KHZ-2MHZ, FOR MINI MITE 7.0" WORKING LENGHT 4 PIN FISCHER CONNECTOR	-			
AURFX312-7WL	ROTARY FLEX SHAFT PROBE 100KHZ-2MHZ, FOR MINI MITE 7.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR	-			
AURFX500SE/200MWL	ROTARY FLEX SHAFT PROBE 100KHZ-2MHZ, FOR MINI MITE SCANNER, 4 PIN FISCHER CONNECTOR, 8.0" (200mm) WORKING LENGTH WITH COLLAR. EXPANDABLE FROM .500"562".				
ARR098	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO .098" OD, 1.1" WORKING LENGTH	-			
ARR187	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO .187" OD, 1.1" WORKING LENGTH	-			
ARR.500	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 1/2" OD3.0" OVERALL LENGTH	-			
ARR.250	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 1/4" OD3.0" OVERALL LENGTH				
ARR.312	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 1/4" OD3.0" OVERALL LENGTH	RA-5/16			
ARR687	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 11/16" OD3.0" OVERALL LENGTH				
ARR.343	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 11/32" OD 3.0" OVERALL LENGTH				
ARR.406	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 13/32" OD 3.0" OVERALL LENGTH	-			
ARR.468	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 15/32" OD 3.0" OVERALL LENGTH	-			
ARR531	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 17/32" OD 3.0" OVERALL LENGTH	•			
ARR.592	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 19/32" OD 3.0" OVERALL LENGTH				
ARR.656	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 21/32" OD 3.0" OVERALL LENGTH	•			
ARR.718	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 23/32" OD 3.0" OVERALL LENGTH				
ARR.750	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 3/4" OD 3.0" OVERALL LENGTH	•			
ARR.375	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 3/8" OD3.0" OVERALL LENGTH				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARR.625	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 5/8" OD 3.0" OVERALL LENGTH	•			
ARR.437	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 7/16" OD 3.0" OVERALL LENGTH				
ARR.218	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 7/32" OD3.0" OVERALL LENGTH				
ARR.562	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 9/16" OD 3.0" OVERALL LENGTH	•			
ARR.281	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 9/32" OD3.0" OVERALL LENGTH				
ARR098SS	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO STAINLESS STEEL .098" OD, 1.1" WORKING LENGTH				
ARR12855	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO STAINLESS STEEL .128" OD, 1.1" WORKING LENGTH				
ARR156SS	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO STAINLESS STEEL.156" OD, 1.1" WORKING LENGTH	•			•
ARR159SS	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO STAINLESS STEEL.159" OD, 1.1" WORKING LENGTH				
ARR18855	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO STAINLESS STEEL.188" OD, 1.1" WORKING LENGTH				•
ARR125SS	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO STAINLESS STEEL1/8"(.125") OD, 1.1" WORKING LENGTH	•			
ARR.156	ROTARY PROBE FOR RA2000 SCANNER 100KHZ-2MHZ 4 PIN STEP LEMO	BPRAF-10 5/32			•
AUR500SS/1.5WL	ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR				
AUR5312SS/1.5WL	ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR				
AUR5626SS/1.5WL	ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR	-			
AUR5937SS/1.5WL	ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR	-			
AUR6406SS/1.5WL	ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR	-			
AUR6718SS/1.5WL	ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR				
ATP-925-1/4-7FX	SRFACE PROBE 50-500KHZ .325"OD 90 DEG .250" DROP FLEX SHAFT TRIAX CONN	VM252RAFX-P325-1/4X7			
ATPN96-7FX/2MHZ	FLEXIBLE SURFACE PROBE 90 DEG .600" DROP 7.0" LONG 1-3MHZ TRIAX FISCHER CONNECTOR	TPENFLX96-7/2M			
ATPN-925-7FX	FLEXIBLE SURFACE PROBE 90DEG .250" DROP 7.0" INCH LONG 50-500KHZHZ , TRIAX FISCHER CONNECTOR	-			
ATPN-5/1MHZ	STRAIGHT SHAFT SURFACE PROBE, TRIAX FISCHER CONNECTOR 5.0" LONG. FREQUENCY= 500KHZ-2MHZ				
ATPN-4/.050/2M	STRAIGHT SURFACE PROBE .050 " TUBING TRIAX FISCHER CONNECTOR 4.0" LONG 1-3MHz	TXPEN-4/2M			
AXSPN45-4	SURFACE PROBE 50-500KHZ, TIP OD .062 , 45° .50 DROP ,4.0" LONG, MICRODOT CONNECTOR	XPEN45-4			
ATPN-4/500K	STRAIGHT SURFACE PROBE, TRIAX FISCHER CONNECTOR 4.0"LONG 500KHZ-1MHZ				
AUR120SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ	•			
AUR130SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR140SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR150SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR160SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR170SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR180SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR190SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				•
AUR200SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ	•			•
AUR210SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				•
AUR220SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR230SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR240SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR260SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR270SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR290SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ	-			
AUR310SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR320SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR340SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ	•			
AUR350SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ	-			
AUR370SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR380SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR400SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR410SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR430SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR440SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR450SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR460SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR470SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR480SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AUR490SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WL SHEILDED4 PIN FISCHER 100KHZ -2MHZ				
AURCS100-11.1MSS/50MWL	100° COUNTER SINK STAINLESS STEEL ROTATING SCANNER PROBE, 100KHZ-2MHZ WITH 4 PIN FISCHER CONNECTOR. 11.1mmØ, 50MM WORKING LENGTH.	-			
AURCS100-5.4MSS/50MWL	100* COUNTER SINK STAINLESS STEEL ROTATING SCANNER PROBE, 100KHZ-2MHZ WITH 4 PIN FISCHER CONNECTOR. 5.4mmØ, 50MM WORKING LENGTH.				
AURCS100-7.1MSS/50MWL	100° COUNTER SINK STAINLESS STEEL ROTATING SCANNER PROBE, 100KHZ-2MHZ WITH 4 PIN FISCHER CONNECTOR. 7.9mmØ, 50MM WORKING LENGTH.				
AURCS100-7.9MSS/50MWL	100° COUNTER SINK STAINLESS STEEL ROTATING SCANNER PROBE, 100KHZ-2MHZ WITH 4 PIN FISCHER CONNECTOR. 7.9mmØ, 50MM WORKING LENGTH.				
ASPN-1012R	10MHZ 90° RIGHT ANGLE PENCIL TRANSDUCER W/ .080 REPLACEABLE TIP	-			
ASPN-1012	10MHZ STRAIGHT PENCIL TRANSDUCER W/.080 REPLACEABLE TIP	•			
AUHF-12	12.0" PROBE EXTENDER UHF MALE TO UHF FEMALE				
AUR928/2WL	13/14" SOLID ROTATING SCANNER PROBE 100KHZ-2MHZ UNSHIELDED, 2WL 4 PIN FISHER CONNECTOR	SPO-5393 (9230212)			
ASPN-1512R	15MHZ 90° RIGHT ANGLE PENCIL TRANSDUCER W/ .080 REPLACEABLE TIP	-			
ASPN-1512	15MHZ STRAIGHT PENCIL TRANSDUCER W/.080 REPLACEABLE TIP	-			
AUR958/2WL	23/24" SOLIDROTATING SCANNER PROBE 100KHZ-2MHZ UNSHIELDED, 2WL 4 PIN FISHER CONNECTOR	SPO-5393 (9230710)			
APN-925-6FX	FLEXIBLE SURFACE PROBE 90 DEG .250" DROP 6.0" LONG MICRODOT CONNECTOR, 50-500KHZ	•			
ASTW-5	5 STEP CLEAR ACRYLIC STEP WEDGE 2"X2" .100500	•			
ASTW-10/.600-1.00	S STEP CLEAR ACRYLIC STEP WEDGE 2"X2" .600-1.00				
ASTW-10/1.100-1.500	5 STEP CLEAR ACRYLIC STEP WEDGE 2"X2" 1.100-1.500				
AWP-B717M	50-500KHz WHEEL PROBE FOR BOEING 717 MAIN WHEEL				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AWP-B717N	S0-S00KHz WHEEL PROBE FOR BOEING 717 NOSE WHEEL				
AUHF-6	6.0" PROBE EXTENDER UHF MALE TO UHF FEMALE				
AFP-7512	7.5MHZ .125" dia. High Resolution focused Straight shaft pencil transducer with a .080" Replaceable tip. Standard microdot connector. (K-PEN style )	389-042-200			
AFP-7512/90	7.5MHZ 90° angle head. High Resolution .125° dia focused pencil transducer with a .080° Replaceable tip. Standard microdot connector. K-PEN Style	389-042-870			
ATPRQ-95-6/1-20K	90 DEGREE LOW FREQUENCY SURFACE PROBE, REFLECTION, .250" DIAMETER TIP .500" DROP 6.0" LONG 1-20KHz TRIAX FISCHER CONNECTOR	RS905-60/1-20KHz			
ATPRQ-95-6/1-40K	90 DEGREE LOW FREQUENCY SURFACE PROBE, REFLECTION, .250" DIAMETER TIP .500" DROP 6.0" LONG 1-40KHz TRIAX FISCHER CONNECTOR	RS905-60/1-40KHz			
ATPRQ-95-6/20-50K	90 DEGREE LOW FREQUENCY SURFACE PROBE, REFLECTION, .250" DIAMETER TIP .500" DROP 6.0" LONG 20-500KHz TRIAX FISCHER CONNECTOR	RS-905-60/20-50KHz			
AFLX90-6	90° ANGLE PROBE EXTENDER, MICRODOT CONNECTOR, FLEX SHAFT 6.0° LENGTH	MFLX90-6			
ATPN-95-9	SURFACE PROBE 90 DEGREE , .500" DROP, TRIAX FISCHER CONNECTOR 50-500KHZ 9.0" LONG .125"OD TIP				
7637987-17	AS3-142 Douglas DC-9 Probe Holding Fixture and alignment 2024-T3 Clad Aluminum. Figure 1, Sheet 4				
ATPN-95-6B/5OOKHZ	90° DEGREE SURFACE PROBE ABSOLUTE SHIELDED, .500° DROP, BENT AT 1.0° FROM TIP TRIAX FISCHER CONNECTOR 500KHz-1MHz.	PA90C605			
ATPN452-6FX	FLEXIBLE SURFACE PROBE 45 DEG .200" DROP 6.0" LONG TRIAX FISCHER CONNECTOR 200KHZ-1MHZ	MTF-452-60FX			
AF-3017-1.120/1.240	ABSOLUTE MANUAL ADJUSTABLE X BOLT HOLE PROBE, 1.120/1.240 25-50KHZ TRIAX FISCHER CONNECTOR	NEC-3112-1.120/1.240	TEK-3012		
AF-3017-1.235/1.355	ABSOLUTE MANUAL ADJUSTABLE X BOLT HOLE PROBE, 1.235/1.355 25-50KHZ TRIAX FISCHER CONNECTOR	NEC-3112-1.235/1.355	TEK-3012		
AF-3017-1.565/1.685	ABSOLUTE MANUAL ADJUSTABLE X BOLT HOLE PROBE, 1.565/1.685 25-50KHZ TRIAX FISCHER CONNECTOR	NEC-3112-1.565/1.685	TEK-3012		
AMH-11M/76MWL/500K	ABSOLUTE MANUAL BOLT HOLE PROBE 50-500KHZ MICRODOT CONNECTOR 11.0mm(.433")Ø x 3.0"(76mm) OVERALL LENGTH WITH COLLAR				
AMH-15M/76MWL/500K	ABSOLUTE MANUAL BOLT HOLE PROBE 50-500KHZ MICRODOT CONNECTOR 15.0mm(.591")Ø x 3.0"(76mm) OVERALL LENGTH WITH COLLAR				
AF-5086/1M	ABSOLUTE PENCIL PROBE .100" TIP OD10DEG TIP ,3.0" LONG DELRIN BODY UNSHEILDED 50KHZ-1.5MHZ MICRODOT CONNECTOR. USE ON TI/SS		NEC-5024		
APR-93-6/50-500K	ABSOLUTE REFLECTION SUFRACE PROBE SHIELDED. 90 DEGREES WITH .300" DROP, TRIAX FISCHER CONNECTORCONNECTOR.	9216204			
APN-903-4FX/2MHZ	FLEXIBLE SURFACE PROBE 1-3MHZ	MP9003-40FX 1-3M			
ASPN-4.5	ABSOLUTE SHIELDED STRAIGHT PENCIL PROBE .092"Ø TUBING 4.5" LONG MICRODOT CONNECTOR 50-500KHz.	105P4XF			
ASDP5/1.5-40KHZ	ABSOLUTE SPOT PROBE ACETAL BODY .500" (13mm)OD, 1.5" LONG STRAIGHT (TOP MOUNT TRIAX FISCHER 1.5-40KHZ				
ASDP5/100HZ-300HZ	ABSOLUTE SPOT PROBE ACETAL BODY .500" (13mm)OD, 1.5" LONG STRAIGHT (TOP MOUNT TRIAX FISCHER 100Hz-300Hz	SPT-007			
ASDP5/50KHZ-4MHZ	ABSOLUTE SPOT PROBE ACETAL BODY .500" (13mm)OD, 1.5" LONG STRAIGHT (TOP MOUNT TRIAX FISCHER 50KHZ-4MHZ			•	
AF-5148/4F	ABSOLUTE SURFACE/SUB-SURFACE CRACK PROBE. PLASTIC TIP OD 4.5mm. RIGHT ANGLE. 8.5mm DROP. 295mm LONG. 1 KHZ-400KHZ	KA-31H-139.02.1			
AURX811875	ADJUSTABLE X (SCREW) ROTARY PROBE 4 PIN FISCHER CONNECTOR WITH RANGE OF 0.811"-0.875", REFLECTION / DIFFERRENTIAL COIL CONFIGURATION 100KHZ-2MHZ. 2.0" WORKING LENGTH				
AURX875937	ADJUSTABLE X (SCREW) ROTARY PROBE 4 PIN FISCHER CONNECTOR WITH RANGE OF 0.875"-0.937", REFLECTION / DIFFERRENTIAL COIL CONFIGURATION 100KHZ-2MHZ. 2.0" WORKING LENGTH				
AURX-1.0-1.060	ADJUSTABLE X (SCREW) ROTARY PROBE 4 PIN FISCHER CONNECTOR WITH RANGE OF 1.000"-1.060", REFLECTION / DIFFERRENTIAL COIL CONFIGURATION 100KHZ-2MHZ. 2.0" WORKING LENGTH				
AURX-1.186-1.217	ADJUSTABLE X (SCREW) ROTARY PROBE 4 PIN FISCHER CONNECTOR WITH RANGE OF 1.186"-1.217", REFLECTION / DIFFERRENTIAL COIL CONFIGURATION 100KHZ-2MHZ. 2.0" WORKING LENGTH				
AURX-1.436-1.467	ADJUSTABLE X (SCREW) ROTARY PROBE 4 PIN FISCHER CONNECTOR WITH RANGE OF 1.436"-1.467", REFLECTION / DIFFERRENTIAL COIL CONFIGURATION 100KHZ-2MHZ. 2.0" WORKING LENGTHWORKING LENGTH				
AURY-3.9-4.5M/45MWL	ADJUSTABLE "V" ROTATING SCANNER PROBE 3.9mm-4.5mm SPREAD, 45 mm WORKING LENGTH. 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMANN MR3.				
AURY-4.8-5.5M/45MWL	ADJUSTABLE "V" ROTATING SCANNER PROBE 4.8mm-5.5mm SPREAD, 45mm WORKING LENGTH.100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMANN MR3.			•	
AURFX187SE-1.5T/4L	ADJUSTABLE FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 4.0" LENGTH. 1.5" TIP LENGTH SPLIT END .187250 DIAMETER	VMUR101SF 0.187-0.250, 1.5			
AURFX250SE-1.5T/4L	ADJUSTABLE FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 4.0" LENGTH. 1.5" TIP LENGTH SPLIT END .250312 DIAMETER	TEK-3005U.250SE/4WL	VMUR101SF 0.250-0.312, 1.5		
AURFX187SE-2.0T/4L	ADJUSTABLE FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 4.0" LENGTH. 2.0" TIP LENGTH SPLIT END .187250 DIAMETER	VMUR101SF 0.187-0.250, 2.0			
AUREX-2505F-2.0T/41	ADJUSTABLE FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 4.0" LENGTH. 2.0" TIP LENGTH SPLIT END .250312 DIAMFTER	VMUR101SF 0.250-0.312, 2.0			

# AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURX437500/4WL	ADJUSTABLE ROTARY X-PROBE .437"500" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 4.0" INCH WORKING LENGTH	BXEM28/32/4"WL			
AURX500625/4WL	ADJUSTABLE ROTARY X-PROBE .500"625" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 4.0" INCH WORKING LENGTH	BXEM-32/40			
AURX625750/4WL	ADJUSTABLE ROTARY X-PROBE .625"750" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 4.0" INCH WORKING LENGTH	BXEM-40/48/4"WL			
AURX750875/4WL	ADJUSTABLE ROTARY X-PROBE .750"875" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 4.0" INCH WORKING LENGTH	BXU-48/56-4.0WL	BXU-48-56-4.0WL		
AURX10-14MM	ADJUSTABLE ROTARY HOLE PROBE 100KHZ-2MHZ,				
ARRX250312	ADJUSTABLE ROTARY HOLE PROBE, 2.0"WL, FOR NORTEC RECHII 100KHZ-2MHZ 4 PIN STEP LEMO				
ARRX312375	ADJUSTABLE ROTARY HOLE PROBE, 2.0"WL, FOR NORTEC RECHII 100KHZ-2MHZ 4 PIN STEP LEMO				
ARRX750875/3WL	ADJUSTABLE ROTARY HOLE PROBE, 3.0"WL, FOR NORTEC RECHII 100KHZ-2MHZ				
ARRX-1.125-1.250/3WL	ADJUSTABLE ROTARY HOLE PROBE, 3.0"WL, FOR NORTEC RECHII 100KHZ-2MHZ 4 PIN STEP LEMO				
ARRX-1.125-1.500/3WL	ADJUSTABLE ROTARY HOLE PROBE, 3.0"WL, FOR NORTEC RECHII 100KHZ-2MHZ 4 PIN STEP LEMO				
AURX1.360-1.420/3WL	ADJUSTABLE ROTARY HOLE PROBES 100K-2MHZ, 3"WL				
AURX1.800-1.860/3WL	ADJUSTABLE ROTARY HOLE PROBES 100K-2MHZ, 3"WL				
AURX1.920-1.980/3WL	ADJUSTABLE ROTARY HOLE PROBES 100K-2MHZ, 3"WL				a
AURX2.000-2.060/3WL	ADJUSTABLE ROTARY HOLE PROBES 100K-2MHZ, 3"WL				
AURX2.215-2.275/3WL	ADJUSTABLE ROTARY HOLE PROBES 100K-2MHZ, 3"WL				
AURX2.328-2.388/4WL	ADJUSTABLE ROTARY HOLE PROBES 100K-2MHZ, 3"WL				
AURX2.375-2.500	ADJUSTABLE ROTARY HOLE PROBES 100KHZ-2MHZ FOR MINIMITE FISCHER SCANNER, SPITFIRE 2000	BXU 144/152, URX1.000- 1.125			
AURX2.150-2.250	ADJUSTABLE ROTARY HOLE PROBES 100KHZ-2MHZ FOR MINIMITE FISCHER, SPITFIRE 2000	BXU 136/144, URX1.000- 1.125			
AURX2.00-2.125	ADJUSTABLE ROTARY HOLE PROBES 100KHZ-2MHZ FOR MINIMITE FISCHER,SPITFIRE 2000 SCANNER	BXU 128/136, URX1.000- 1.125			
AURX.250312/12"WL	ADJUSTABLE ROTARY HOLE PROBES 100KHZ-2MHZ, 12"WL 4 PIN FISCHER	URX.250312			
AURX.875-1.000	ADJUSTABLE ROTARY HOLE PROBES 1-2MHZ	URX.875-1.000			
AURX1.000-1.125	ADJUSTABLE ROTARY HOLE PROBES 1-2MHZ	URX1.000-1.125			
AURX1.125-1.250	ADJUSTABLE ROTARY HOLE PROBES 1-2MHZ	URX1.125-1.250			
AURX1.250-1.375	ADJUSTABLE ROTARY HOLE PROBES 1-2MHZ	URX1.250-1.375			
AURX1.375-1.500	ADJUSTABLE ROTARY HOLE PROBES 1-2MHZ	URX1.375-1.500			
AURX.187250/12"WL	ADJUSTABLE ROTARY HOLE PROBES 1-2MHZ, 12"WL	URX.187250			
AURX375437/5WL	ADJUSTABLE ROTARY HOLE X-PROBE ".375437" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 5.0" WORKING LENGTH				
AURX437500	ADJUSTABLE ROTARY X-PROBE ".437500" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR	BXU-28/32	EMRX.437500		
AURX625687	ADJUSTABLE ROTARY X-PROBE .625"687" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR	BXU-40/44			
AURX687750	ADJUSTABLE ROTARY X-PROBE .687"750" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR				
AURY-6-7MM/2WL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 2WL (50MMWL)4 PIN FISCHER				
AURY-6-7M	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER	RSMV-S/SL6-7	RSMV-S/SL6-7		
AF-6001-A	ADJUSTABLE SLIDING PROBE, REFLECTION, 1KHZ-100KHZ, WITH 2 SINGLE MICRODOT	ASLD-1K-A			
AURY375437/3WL	ADJUSTABLE UNIVERSAL ROTARY PROBE 3.0" WORKING LENGTH .375"437' 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR				
AURYFB-250281/1.5WL	ADJUSTABLE UNIVERSAL ROTARY PROBE FLAT BOTTOM .250"281" 1.5 WL 100KHZ-2MHZ"	URYF250281/1.5WL			
AURYF250281/1.6WL	ADJUSTABLE UNIVERSAL ROTARY PROBE .250"281" 1.6 WL SHEILDED 100KHZ-2MHZ"	URYF.250281/1.6WL			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURY437500/3WL	ADJUSTABLE UNIVERSAL ROTARY PROBE 3.0" WORKING LENGTH .437"500", 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR				
AURY500625/3WL	ADJUSTABLE UNIVERSAL ROTARY PROBE 3.0" WORKING LENGTH 500"625" 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR				
AURY625687/3WL	ADJUSTABLE UNIVERSAL ROTARY PROBE 3.0" WORKING LENGTH 625"687" 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR				
AURY687750/3WL	ADJUSTABLE UNIVERSAL ROTARY PROBE 3.0" WORKING LENGTH 687"750" 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR				
AMHY500531/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 1/2" OD				
AMHY250281/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 1/4" OD				
AMHY687718/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 11/16" OD				
AMHY343375/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 11/32" OD				
AMHY406437/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 13/32" OD				
AMHY468500/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 15/32" OD				
AMHY531-562/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 17/32" OD				
AMHY591625/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 19/32" OD				
AMHY656687/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 21/32" OD				
AMHY718750/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 23/32" OD				
AMHY187218/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 3/16"" OD				
AMHY750781/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 3/4" OD				
AMHY312343/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 5/16"OD				
AMHY625656/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 5/8" OD				
AMHY437468/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 7/16" OD				
AMHY218250/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-11MHz, 7/32" OD				
AMHY562-591/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 9/16" OD				
AMHY281312/3WL	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 300KHZ-1MHz, 9/32" OD				
AMHY375437	ADJUUSTABLE "Y" MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, ,MICRODOT CONNECTOR, 50KHz-500KHz, 3/8" - 437" OD.				
AHA1890	BEAD PROBE ART72				
ABL-990-6	BLADE PROBE 90 DEG. 090" THICK 6.0" LONG MICRODOT CONNECTOR, 50-500KHZ. Includes Test Report and Certificate of Conformance.				
ATBL.030-10	BLADE PROBE, .030 THICK, 10" L, STRAIGHT, 50-500KHZ, TRIAX FISCHER. Includes Test Report and Certificate of Conformance.	TBLFC.030-6			
ATBL.030-6	BLADE PROBE, .030 THICK, 6" LONG, STRAIGHT, 50-500KHZ, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TBLFC.030-6			
ATBL030-9	BLADE PROBE, .030" THICK, 9.0" LONG, STRAIGHT SHAFT, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TBL.030-9			
ATBL045-10	BLADE PROBE, .045 THICK, 10"L, STRAIGHT, 50-500KHX, TRIAX FISCHER				
ATBL045-15	BLADE PROBE, .045 THICK, 15°L, STRAIGHT, 50-500KHX, TRIAX FISCHER				
ATBL9045-6	BLADE PROBE, .045 THICK, 6.0" LONG, 90°, 50-500KHz, TRIAX FISCHER CONNECTOR.	MP90.045-60BL			
ATBL460-6	BLADE PROBE, .045 THICK, 60°, 6″L, 50-500KHX, TRIAX FISCHER				
ATBL045-7	BLADE PROBE, .045 THICK, 7"L, STRAIGHT, 50-500KHX, TRIAX FISCHER				
ATBL060-8	BLADE PROBE, .060 THICK, 8" LONG, STRAIGHT, 50-500KHZ, TRIAX FISCHER	NEC-1016-3			
ATBL080-6	BLADE PROBE, -080" THICK, 6.0" LONG, STRAIGHT, 50-500KHz, TRIAX FISCHER CONNECTOR.	NEC-1058			
NDT722-P1	BOEING 777 POSITIONER PART 6 55-17-02, PAGE 7 FIGURE 2				

# AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
NDT722-P2	BOEING 777 POSITIONER PART 6 55-17-02, PAGE 8 FIGURE 3				
NDT722-P3	BOEING 777 POSITIONER PART 6 55-17-02, PAGE 9 FIGURE 4				
ARP-1000	BOEING SPECIAL RING PROBE ASSEMBLY				
ARR.156SS/1.5WL	BOLT HOLE PROBE 100K-2MHZ 1.5WL, STAINLESS STEEL				
ARR.625SS/1.5WL	BOLT HOLE PROBE 100K-2MHZ 1.5WL, STAINLESS STEEL				
ARR.234SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL	-			
ARR.375SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL				
ARR.421SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL				
ARR.484SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL				
ARR.546SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL				
ARR.859SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL				
ARR.500562SE/1.1WL	BOLT HOLE PROBE 100KHZ-1MHZ. SPLIT END FOR RA SCANNER, 1.1WL				
ARR.125	BOLT HOLE PROBE 100KHZ-2MHZ FOR RA 2000, MINIMITE(LEMO) SCANNER				
ARR.250SE/FB	BOLT HOLE PROBE 100KHZ-2MHZ, SPLIT END, FLAT BOTTOM HOLE(.250281)				
ARR.281SE/FB	BOLT HOLE PROBE 100KHZ-2MHZ, SPLIT END, FLAT BOTTOM HOLE(.281312)				
ARR.312SE/FB	BOLT HOLE PROBE 100KHZ-2MHZ, SPLIT END, FLAT BOTTOM HOLE(.312375)				
ARR.375SE/FB	BOLT HOLE PROBE 100KHZ-2MHZ, SPLIT END, FLAT BOTTOM HOLE(.375437)				
ARR.437SE/FB	BOLT HOLE PROBE 100KHZ-2MHZ, SPLIT END, FLAT BOTTOM HOLE(.437-500)				
AMH.187/2MHZ	BOLT HOLE PROBE 1-3 MHZ MICRODOT	504P12			
ARR.125/4WL	BOLT HOLE PROBE 1-3 MHZ, 4"WL				
ARR.250/2WL	BOLT HOLE PROBE 200KHZ-1MHZ, 2"WL	RA-1/4			
AMH.500/500K	BOLT HOLE PROBE 200KHZ-1MHZ, MICRODOT, OAL 2"				
ARR.156B/SE	BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END				
ARR.218B/SE	BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END				
ARR.375B/SE	BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END				
ARR.500B/SE	BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END				
ARR.750B/SE	BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END				
ARR.750B/SE/1.1WL	BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END, 1.1WL FOR RA 2000 SCANNER				
ARR1.0B/SE/1.1WL	BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END, 1.1WL,RA 2000 SCANNER				
ARR.500562/1.1WL	BOLT HOLE PROBE 200KHZ-1MHZ. SPLIT END FOR RA SCANNER				
ARR.218SE/FB	BOLT HOLE PROBE 4 PIN STEP LEMO 100KHZ-2MHZ, SPLIT END, FLAT BOTTOM HOLE(.218250)				
AMH.312/4L	BOLT HOLE PROBE 50-500Khz 4 INCH LONG WITH MICRODOT CONNECTOR UNSHIELDED .312" HEAD	VM101BS-0.312			
AMH.375/4L	BOLT HOLE PROBE 50-500Khz 4 INCH LONG WITH MICRODOT CONNECTOR UNSHIELDED .375" HEAD	VM101BS-0.375			
AMH1.062/4L	BOLT HOLE PROBE 50-500Khz 4 INCH LONG WITH MICRODOT CONNECTOR UNSHIELDED 1.062" HEAD	VM101BS-1.062			
AMH1.087/4L	BOLT HOLE PROBE 50-500Khz 4 INCH LONG WITH MICRODOT CONNECTOR UNSHIELDED 1.087" HEAD	VM101BS-1.087			
AMH4.5-5.5MM/200KHZ	BOLT HOLE PROBE 50-500KHZ MICRODOT				

PART NUMBER AMH.468 AMH.531	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AMH.531	BOLT HOLE PROBE 50-500KHZ MICRODOT CONNECTOR 15/32" x 3.0" OVERALL LENGTH				
	BOLT HOLE PROBE 50-500KHZ MICRODOT CONNECTOR 17/32" x 3.0" OVERALL LENGTH				
AMH.593	BOLT HOLE PROBE 50-500KHZ MICRODOT CONNECTOR 19/32" x 3.0" OVERALL LENGTH				
AMH.656	BOLT HOLE PROBE 50-500KHZ MICRODOT CONNECTOR 21/32" x 3.0" OVERALL LENGTH				
AMH.718	BOLT HOLE PROBE 50-500KHZ MICRODOT CONNECTOR 23/32" x 3.0" OVERALL LENGTH		•		
AL35-45	BOMBARDIER SURFACE REFERENCE STANDARD - 7075-T7ALUMINUM. FULL WIDTH EDM NOTCHES .008", .020", .040" (.005"W +/002, MAX.006) BLOCK SIZE: 3.75"L x 1.50"W x 0.25"H				
APN-4FX/2MHZ	FLEXIBLE SURFACE PROBE 1-3MHZ 4.0" LONG MICRODOT CONNECTOR				
APN-45-6FX/2MHZ	FLEXIBLE SURFACE PROBE 1-3MHZ 6.0" LONG 45 DEG .500" DROP MICRODOT CONNECTOR .125" TIP				
APN-91-6FX/2MHZ	FLEXIBLE SURFACE PROBE 1-3MHz 90 DEGREES .100" DROP 6.0 INCHES LONG WITH MICRODOT CONNECTOR .125" TIP	PENFLX91-6-2M			a
ACR53-172942	CALIBRATED CONDUCTIVITY REFERENCE STAND SET. 17%,29%, 42% IACS NOMINAL VALUES				
AUR-14MSS/50MWL	CASONI STAINLESS STEEL ROTATING SCANNER PROBE 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ, 14mm(.551") DIAMETER HEAD 50mm WORKING LENGTH	CASONI			
AUR-22MSS/50MWL	CASONI STAINLESS STEEL ROTATING SCANNER PROBE 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ, 22mm(.886") DIAMETER HEAD 50mm WORKING LENGTH	CASONI			
AWP-AZ91E	CAST WHEEL PROBE FOR CUSTOMER SUPPLIED MAGNESIUM NOSE WHEEL. 50-500KHZ TRIAX FISCHER CONNECTOR DIFFERENTIAL/BRIDGE				a
CDR-2.7X4.0/1M	COIL - DIFFERENTIAL REFLECTION 150MM				
ACP375/60K	CONDUCTIVITY PROBE .375 O.D., 5 PIN LEMO CONNECTOR, 60KHz	CPH.375-60K			
AM21-BNC	CONNECTOR, MIZ TO BNC, 50-500KHZ				
ACRM-501G	CONTACT TRANDSUCER, SIDEMOUNT MICRODOT 1.0 MHZ .500 DIA. GAMMA SERIES				
ACRM-505G	CONTACT TRANDSUCER, SIDEMOUNT MICRODOT 5.0 MHZ .500 DIA. GAMMA SERIES				
ACSM100500	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 1/2" OD				
ACSM100687	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 11/16" OD				
ACSM100343	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 11/32" OD				
ACSM100406	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 13/32" OD				
ACSM100468	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 15/32" OD				
ACSM100531	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 17/32" OD				
ACSM100591	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 19/32" OD				
ACSM100656	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 2132" OD				
ACSM100718	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 23/32" OD				
ACSM100750	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 3/4" OD		•		
ACSM100375	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 3/8" OD				
ACSM100312	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 5/16" OD				
ACSM100-625	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 5/8" OD				
ACSM100437	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 7/16" OD		•		
ACSM100562	COUNTER SINK PROBE 100 DEG 50-500KHz WITH MICRODOT CONNECTOR 9/16" OD				
ACSU100-11.0M	COUNTER SINK PROBE 100K-2MHZ	CSEM100-11.0M			
ACSU100-13.0M	COUNTER SINK PROBE 100K-2MHZ	CSEM100-13.0M			
ACSU100-15.0M	COUNTER SINK PROBE 100K-2MHZ	CSEM100-15.0M			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ACSU100-4.0M	COUNTER SINK PROBE 100K-2MHZ	CSEM100-4.0M			
ACSU100-4.35M-SS	COUNTER SINK PROBE 100K-2MHZ	CSEM100-4.0M			
ACSU100-6.0M	COUNTER SINK PROBE 100K-2MHZ	CSEM100-6.0M			
ACSU100-6.4M-SS	COUNTER SINK PROBE 100K-2MHZ	CSEM100-4.0M			
ACSU100-7.0M	COUNTER SINK PROBE 100K-2MHZ	CSEM100-7.0M			
ACSU100120	COUNTER SINK PROBE 100KHZ-2MHZ				
ACSU100125	COUNTER SINK PROBE 100KHZ-2MHZ				
ACSU100156	COUNTER SINK PROBE 100KHZ-2MHZ				
ACSU100187	COUNTER SINK PROBE 100KHZ-2MHZ				
ACSU100250	COUNTER SINK PROBE 100KHZ-2MHZ				
ACSU1001875S	COUNTER SINK PROBE 100KHZ-2MHZ, STAINLESS STEEL				
ACSU100-9.0M	COUNTERSINK PROBE 100K -2MHZ	CSEM100-9.0M			
AF-5151	CUSTOM BLADE PROBE, ABSOLUTE .030 THICK, UNSHIELDED, 6" LONG, STRAIGHT, S0-500KHZ, TRIAX FISCHER CONNECTOR.				
AF-5150	CUSTOM BOLT PROBE FOR A286 STEEL, HEAD-TO-SHANK "FILLET" INSPECTION. FREQUENCY 500KHz-1MHz.				
AF-5165	CUSTOM DUAL COIL EDDY CURRENT PROBE FOR GROOVE INSPECTION, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. REFERENCE: SLS-CRES-60D-GRV.				
AFNDT-1031/10MM	CUSTOM EDDY CURRENT CALIBRATION BLOCK 4130 or 4340 STEEL. SOmm x 50mm x 15mm with 10mm diameter hole. Midwall EDM notch (1.5mm long +/- 0.15)x (0.76mm deep +/- 0.07) x (0.18mm MAX width )				
AFNDT-1031/6MM	CUSTOM EDDY CURRENT CALIBRATION BLOCK 4130 or 4340 STEEL. S0mm x 50mm x 15mm with 6mm diameter hole. Midwall EDM notch( 1.5mm long +/- 0.15 )x (0.76mm deep +/- 0.07 ) x (0.18mm MAX width )				
AFNDT-1030/8MM	CUSTOM EDDY CURRENT CALIBRATION BLOCK 4130 or 4340 STEEL. S0mm x 50mm x 15mm with 8mm diameter hole. Midwall EDM notch( 9.5mm long +/- 0.95 )x (0.13mm deep +/- 0.01 ) x (0.18mm MAX width )				
AF-5113	Custom Eddy Current Probe for clamp inspection grooves. Frequency 500KHz-1MHz. Triax Fischer connector, Reflection				
AF-5100L/2MHZ	CUSTOM EDDY CURRENT SURFACE PROBE LEFT HAND 1-3 MHz WITH MICRODOT CONNECTOR.	314P001	TEK-2032L		
AF-5100R/2MHZ	CUSTOM EDDY CURRENT SURFACE PROBE RIGHT HAND 1-3 MHz WITH MICRODOT CONNECTOR.	314P002	TEK-2032R		
AF-5132	CUSTOM FLEXIBLE SURFACE PROBE 5.0° LONG, 1.6" DROP, 1.3" LONG TOTHE RIGHT SIDE OF THE 1.6" DROP AND .200" FINAL DROP FROM THE 1.3" LEAD LENGTH. 1-3MHz, TRIAX FISCHER CONNECTOR.	TEK-2096			
AF-5028	CUSTOM HIGH FREQUENCY THREADED PROBE 500KH2-1MHz TRIAX FISCHER CONNECTOR. FOR 2.0-12 THREAD 15-5PH STEEL BOLT.				
D0815E1042-2001	CUSTOM LARGE DIAMETER PROBE COLLAR, .430"Ø THRU HOLE, OD, .2.0"Ø OD. MATERIAL: BLACK DELRIN(ACETAL).				
AF-4200	CUSTOM LOW FREQUENCY REFLECTION RING PROBE FOR 777X, 1-3KHz, .670°Ø1.D WITH .120° WALL THICKNESS.				
AF-SPO-6450/5719	CUSTOM NORTEC SPO-6450 STYLE MANUAL BOLT HOLE PROBE 500KHz-2MHz with SPO-5719 STYLE HOLDING FIXTURE W/ 1/16" PER rEVOLUTION THREAD.	SPO-6450			
ACL-125	CUSTOM PROBE COLLAR, .125"Ø THRU HOLE, .500"Ø TIP OD, .750"Ø BODY OD. MATERIAL: BLACK DELRIN(ACETAL). 1823427	1823427	D0815E1015-2099		
ARP-1.57-1.0/100H	CUSTOM RING PROBE REFLECTION TRIAX FISHER CONNECTOR,1.57"OD and 1.0" IDx1.0"H, 100HZ-1KHZ				
AF-4123	CUSTOM RING PROBE REFLECTION, 1.25" OD x .800" ID(20.3mm), 100HZ-1KHZ TRIAX FISCHER CONNECTOR				
AUR750SE/2.5WL	Custom Size Universal Rotary Hole Probe 0.700°Ø inch to 0.750°Ø inch diameter, Self Expanding 2.5° inch (63.5 mm) working length. Operating frequency 100 kHz - 2 MHz, Fischer 4 pin connector, reflection differential coil configuration. Expandable from	SPO-6700			
7637987-19	CUSTOM SPO-2664 SLIDING PROBE FIXTURE USED WITH DC-10 REFERENCE STANDARD 7637987-15				
AF-5138	CUSTOM THREADED BOLT PROBE FOR A286 STEEL BLOT 5/16-24 THREAD. FREQUENCY 500KHz-1MHz.				
ASC-0513	CUSTOM TRANSDUCER USED FOR THE DC10 BANIO INSPECTION				
AP-352P1B/2MHZ	DELRIN UNSHIELDED KNIFE PROBE 90° 1-3MHz, 5.0 INCES LONG MICRODOT CONNECTOR.	352P1B			
AF-5212/7L	Detachable Pencil Probe 100-500KHz Shielded with 7 pin Lemo connector. Tip diameter .187" with adjustable collar.	9222180			
AF-5112/7L	Detachable Pencil Probe 100-500KHz Unshielded with 7 pin Lemo connector. Tip diameter .187" with adjustable collar.	9222412			

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPRU-6	DETACHABLE REFLECTION ABSOLUTE UNSHIELDED STRAIGHT 6.0" LONG (.187" DIA TUBING) TRIAX FISCHER CONNECTOR 100KHZ-1MHZ	PR/100KHZ-1MHZ/AU			
AF-4105/7L	Detachable Surface Spot Probe, bridge diameter of .310 in. (7.9 mm) and a operating Frequency range of 1 kHz - 50 kHz (equivalent to SPO-1284, SPO- 1598), 7-pin LEMO Powerlink Connector	9222161			
ASP.44	DIFFERENTIAL PROBE 500HZ-40KHZ	9213547			
ALP93-5B/2-12KHZ	DIFFERENTIAL PROBE	•			
ASP3-5K	DIFFERENTIAL PROBE 1-5KHZ	SDP.3-5K			
ASP4-5K	DIFFERENTIAL PROBE 1-5KHZ	SDP.4-5K			
ASP5-5K	DIFFERENTIAL PROBE 1-5KHZ	SDP.5-5K			
ARB3075/500HZ	DIFFERENTIAL PROBE SOOHZ-SKHZ				
ASDP25/100K	DIFFERENTIAL PROBE, SPRING LOADED	SPD.125-100K			
ASDP375/5K	DIFFERENTIAL PROBE, SPRING LOADED5 -20 KHZ TRIAX FISCHER CONNECTOR	SPD.375-5K-2			
ARP-1.4062	DIFFERENTIAL RING PROBE 1.40"OD .620" ID TRIAX FISCHER CONNECTOR100HZ-1KHZ	SPO-1154	SPO-1154L	.9230326	
ARDP.56/1.15	DIFFERENTIAL RING PROBE 100HZ-1KHZ .560ID 1.15 OD 1.5"H	SPO-1744, RB1.1-100H-2			
AF92-5/20KHZ	DIFFERENTIAL SURFACE PROBE 20-25KHZ.2500D	RS902-50/20K/2D			
AF-9000/WSP.219	EDDY CURRENT PROBE 450KHZ-2.5MHZ, .219 TIPØ, 2.5OL, .50THD	WSP.190	632-267-008	•	
ATPN453-6FX	FLEXIBLE SURFACE PROBE 45 DEG .300" DROP 6.0" LONG TRIAXFISCHER CONNECTOR 50-500KHZ	MTF453-60FX		•	
APN-92-10FX	FLEXIBLE SURFACE PROBE 50-500KHZ				
APN-92-5FX	FLEXIBLE SURFACE PROBE 50-500KHZ	PEN902-50FX			
ATPN-45-5FX/1-6M	FLEXIBLE SURFACE PROBE 45° DEGREES, 5.0° LONG, TRIAX FISCHER CONNECTOR, 1-6MHz.	BCMTF-455-60FX-1-6M			
ATPN-45-6FX/1-6M	FLEXIBLE SURFACE PROBE 45° DEGREES, 6.0" LONG, TRIAX FISCHER CONNECTOR, 1-6MHz.	BCMTF-455-60FX-1-6M	MTF-455-60FX-1-6M	•	
AES100/6.4M	ELOTEST PROBE, 57-14-02 PT 6	RS50/6.4			
AES50/6.4M	ELOTEST PROBE, 57-14-02 PT 6	RS50/6.4			
AES-6.2SS/35MMWL	ELOTEST PROBE, STAINLESS STEEL, 100KHZ-2MHZ	RSK35-6.2	RSK35-6.2		
AES-7.8SS/50MMWL	ELOTEST PROBE, STAINLESS STEEL, 100KHZ-2MHZ	RSK50-7.8	RSK50-7.8		
AECS100-10.8MSS/50MWL	ELOTEST PROBE, STAINLESS STEEL, SOKHZ-2.5MHZ	RSK-50-6.2-10.8-100	RSK-50-6.2-10.8-100		
AECS100-13.6MSS/35MWL	ELOTEST PROBE, STAINLESS STEEL, SOKHZ-2.5MHZ	RSK-35-7.8-13.6-100	RSK-35-7.8-13.6-100		
AECS100-6.2MSS/35MWL	ELOTEST PROBE, STAINLESS STEEL, SOKHZ-2.5MHZ, 100° COUNTER SINK,	RSK-35-6-2	RSK-35-6-2		
AECS100-7.8MSS/50MWL	ELOTEST PROBE, STAINLESS STEEL, SOKHZ-2.5MHZ, 100° COUNTER SINK,	RSK-507-8	RSK-507-8		
AF-6001	ENGINE BLADE PROBE, REFLECTION, 6'L ATTACHED TO 16PIN LEMO CONNECTOR, 1-4MHZ, TI				
AF-6016/TF	FIXED SLIDING PROBE REFLECTION TRIAX FISCHER CONNECTOR 500Hz-100KHz	SLD500H-2M			
AF-5098/.875	FLAP HINGE FITTING PROBE .875" OD DIFF TRIAX FISCHER CONN 50-500KHZ	TEK-3029875	NEC-1002	•	
AF-5098/1.125	FLAP HINGHE FITTING PROBE 1.125" ODDIFF TRIAX FISCHER CONN 50-500KHZ	TEK-3029-1.125		•	
ARRFB687SE/1.5WL	FLAT BOTTOM ROTARY PROBE SPLIT END 4 PIN STEP LEMO 1.5" WORKING LENDTH 100KHZ-2MHZ				
ARRFB625SE/1.5WL	FLAT BOTTOM ROTARY PROBE SPLIT END 4 PIN STEP LEMO 1.5" WORKING LENGTH 100 KHZ-2MHZ				
ARRFB-1.083SE/1.5WL	FLAT BOTTOM ROTARY PROBE SPLIT END 4 PIN STEP LEMO 1.5" WORKING LENGTH 100KHZ-2MHZ				
AURFB625	FLAT BOTTOM ROTATING PROBE .625 DIAMETER 100KHZ-2MHZ 2.0" WL 4 PIN FISHER CONNECTOR, SPLIT ENDS				
AURFB687	FLAT BOTTOM ROTATING PROBE .687 DIAMETER 100KHZ-2MHZ 2.0" WL 4 PIN FISCHER CONNECTOR				

## AeroFab NDT LLC

AnameIndex (a)Index (a)	PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
Automatical and an and and			EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AnimanAnimanon and anomaly and animan constraints of any			•	•		
NUMBERInformation production of the sector of t					:	
MAIL STATURAINTERDED KONTONE MORE STATURE THAN SERVICE STATURE THAN			•	*	•	
MNR3351/LVMINTERDEMONING MODE LODGE SING MODE SOUCH SANDERSIn				•		
with stand in the intervention of the interventin of the intervention of the intervention			•	*		
MRAB3DYNAMEWARDA (NO E 1000-2004)NAME AND			•	•		
MarshardAnderstands prode isobe AndAnderstandsAnderstand	,		•			
AMPAGADAANTONANTAMENDALISANSALAMENTALISANSALAME			•	•		
NUMAn Information from information of the inf			•			
Aurra-sóReformation for the source and a function for the source and a						
NumberNumbe			•			
Autor<						
AnimatesAnimate			•			
Alter STOM KOTING PORE LOOK2-JANA SAME STELLAlter STOM KOTING PORE LOOK2-JANA SAME STELL AND KODERAlter STOM KOTING PORE LOOK2-JANA SAME STELL AND KODERAlter STOM KOTING PORE LOOK2-JANA SAME STELL AND KODERAlter STOM KOTING PORE LOOK2-JANA SAME STELL AND KODER SAME SAME STELL AND KODER SAME SAME SAME SAME SAME SAME SAME SAME						
All PerformanceAll reactions probes toole-2-Mice Statutes Stretch And Length PrischerSector<						
AlterArt and Total protect look 2-2ML2 STALLES STELL 2-WLA PM FISCHERPrepase STL5/64.14ReferenceReferenc	AURFB-11.0M	FLAT BOTTOM ROTATING PROBE 100KHZ-2MHZ 4 PIN FISCHER				
All PB-12/2 J75WL/AMAll POTOM ROATING PROBE_125*DUAL-SUME LEADER MAPPING LEADER ONNECTORUPE 12/2 J75WL/AMIme Ime Image Pote Pote Pote Pote Pote Pote Pote Pot	AURFB-4.7MMSS	FLAT BOTTOM ROTATING PROBE 100KHZ-22MHZ STAINLESS STEEL				
HARE STORFLAR BOTTOM ROTATING PROBE STOR '0 20' WA APIN FISCHER LOOKIG-ZAMIZI.I.I.I.I.I.I.ALREPE-SOSFLAR BOTTOM ROTATING PROBE STOR '0 20' WA APIN FISCHER LOOKIG-ZAMIZVORKING LENGTH WITH A PIN FISHER CONNECTORI. </td <td>AURFB234SS/1.4"WL</td> <td>FLAT BOTTOM ROTATING PROBE 100KHZ-2MHZ STAINLESS STEEL1.4"WL.4 PIN FISCHER</td> <td>RTPRB,SST,15/64,1.4'</td> <td></td> <td></td> <td></td>	AURFB234SS/1.4"WL	FLAT BOTTOM ROTATING PROBE 100KHZ-2MHZ STAINLESS STEEL1.4"WL.4 PIN FISCHER	RTPRB,SST,15/64,1.4'			
ALR DOTION ROTATING PROBESPLIT END., 650°Ø DIAMETER 100KH2-2MH2, 20° WORKING LENGT WITH 4 PIN FSHER CONNECTOR.InclInclInclInclALR DOTION ROTATING PROBESPLIT END., 650°Ø DIAMETER 100KH2-2MH2, 20° WORKING LENGT WITH 4 PIN FSHER CONNECTOR.InclInclInclInclInclALR PROBE 100KH2-2MH2, 4°WL, STAMLESS STELL 2mm TP LENGTH. (224°) PIN FSHER CONNECTORInclInc	AURFB125/2.75WL/2M	FLAT BOTTOM ROTATING PROBE .125" DIA 1-3MHZ, 2.75" WORKING LENGTH 4 PIN FISCHER CONNECTOR	URFB.125/2.75WL/2M			
AURFX 15/6453/AVV.FLEX PROBE 100KH2 2MH2, 4'WL, STANLESS STEEL 12mm TIP LENGTH . (. 257) 4 PN FISHER CONNECTORImage: Constant Const	AURFB550	FLAT BOTTOM ROTATING PROBE .550" OD2.0" WL 4 PIN FISCHER 100KHZ-2MHZ				
AURYA 106PLK PROBE 100KHZ 2MHZ, 4"WL, STANLESS STEEL 12mm TIP LENGTH (250") 4 PIN FISHER CONNECTORAURX 10/6455/4WLFLK PROBE 100KHZ 2MHZ, 4"WL, STANLESS STEEL 12mm TIP LENGTH (250") 4 PIN FISHER CONNECTOR <td>AURFB650SE/2WL</td> <td>FLAT BOTTOM ROTATING PROBE SPLIT END, .650" DIAMETER 100KHz-2MHz, 2.0" WORKING LENGTH WITH 4 PIN FISHER CONNECTOR.</td> <td></td> <td></td> <td></td> <td></td>	AURFB650SE/2WL	FLAT BOTTOM ROTATING PROBE SPLIT END, .650" DIAMETER 100KHz-2MHz, 2.0" WORKING LENGTH WITH 4 PIN FISHER CONNECTOR.				
AURX: 17/6435/W1       REX PROBE 100KH2:2MH2,4'WL, STAINLESS STEEL 12mm TIP LENGTH(256'') 4 PIN FISHER CONNECTOR       Content       Conten       Content       Content	AURFX-15/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH (.234") 4 PIN FISHER CONNECTOR				
AURPX-13/64S3/AVLFLEX PROBE 100KH2-2MH2, 4'WL, STAINLESS STEEL 12mm TIP LENGTH (236') A PIN FISHER CONNECTORSolSolSolSolAURPX-21/64S5/AVLFLEX PROBE 100KH2-2MH2, 4'WL, STAINLESS STEEL 12mm TIP LENGTH (328') A PIN FISHER CONNECTORSolSolSolSolSolAURPX-22/64SS/AVLFLEX PROBE 100KH2-2MH2, 4'WL, STAINLESS STEEL 12mm TIP LENGTH (339') A PIN FISHER CONNECTORSolSolSolSolSolAURPX-22/64SS/AVLFLEX PROBE 100KH2-2MH2, 4'WL, STAINLESS STEEL 12mm TIP LENGTH (359') A PIN FISHER CONNECTORSolSolSolSolSolAURPX-23/64SS/AVLFLEX PROBE 100KH2-2MH2, 4'WL, STAINLESS STEEL 12mm TIP LENGTH (359') A PIN FISHER CONNECTORSolSolSolSolSolAURPX-23/64SS/AVLFLEX PROBE 100KH2-2MH2, 4'WL, STAINLESS STEEL 12mm TIP LENGTH (359') A PIN FISHER CONNECTORSolSolSolSolSolAURPX-23/64SS/AVLFLEX PROBE 100KH2-2MH2, 4'WL, STAINLESS STEEL 12mm TIP LENGTH (357') A PIN FISHER CONNECTORSolSolSolSolSolAURPX-13/64SS/AVLFLEX PROBE 100KH2-2MH2, FOR MIN MITELEX PROBE 100KH2-2MH2, FOR MIN MITESolSolSolSolSolSolAURPX-13/64SS/AVLFLEX PROBE 100KH2-2MH2, FOR MIN MITE 4 PIN FISHER CONNECTOR // WORKING LONGSolSolSolSolSolSolSolAURPX-157-VNLFLEX PROBE 100KH2-2MH2, FOR MINI MITE 4 PIN FISHER CONNECTOR // WORKING LONGSolSolSolSolSolSolSolSolSolSolSolSol <td< td=""><td>AURFX-16/64SS/4WL</td><td>FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH (. 250") 4 PIN FISHER CONNECTOR</td><td></td><td></td><td></td><td></td></td<>	AURFX-16/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH (. 250") 4 PIN FISHER CONNECTOR				
AURP-21/64S5/AWL       FLEX PROBE 100KH2-2MH2, 4"WL, STAINLESS STEEL 12mm TIP LENGTH(.328") 4 PIN FISHER CONNECTOR       Sole       Sole       Sole       Sole         AURP-22/64S5/AWL       FLEX PROBE 100KH2-2MH2, 4"WL, STAINLESS STEEL 12mm TIP LENGTH(.339") 4 PIN FISHER CONNECTOR       Sole       Sole      Sole       Sole       Sole       Sole       Sole       Sole       Sole       Sole       Sole       Sole       Sole       Sole	AURFX-17/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH (. 265") 4 PIN FISHER CONNECTOR				
AURFX-22/64S5/AWLFLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH (.343" 4 PIN FISHER CONNECTORAURFX-23/64S5/AWLFLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH (.359" 4 PIN FISHER CONNECTOR	AURFX-19/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH( .296") 4 PIN FISHER CONNECTOR				
AURFX-23/64SS/AWL       FLX PROBE 100KH2-2MH2, 4"WL, STAINLESS STEEL 12mm TIP LENGTH(.359") 4 PIN FISHER CONNECTOR       C       C       C       C         AURFX-23/64SS/AWL       FLEX PROBE 100KH2-2MH2, 4"WL, STAINLESS STEEL 12mm TIP LENGTH(.375") 4 PIN FISHER CONNECTOR       C	AURFX-21/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH( .328") 4 PIN FISHER CONNECTOR				
AURFX-24/64SS/AWL REX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH(.375" A PIN FISHER CONNECTOR	AURFX-22/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH(.343") 4 PIN FISHER CONNECTOR		-		-
AURFX-13/64SS/AWL REX PROBE 100KHZ-2MHZ, 40°WL, STAINLESS STEEL 12mm TIP LENGTH (.203°) WITH A 4 PIN FISHER CONNECTOR	AURFX-23/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH( .359") 4 PIN FISHER CONNECTOR				
AURFX.218-7VL         FLEX PROBE 100KHZ-2MHZ, FOR MINI MITE 4 PIN FISCHER         March	AURFX-24/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH (375") 4 PIN FISHER CONNECTOR				
AURFX 375-7VIL     FLEX PROBE 100KHZ-2MHZ, FOR MINI MITE 4 PIN FISCHER     MORE     MORE     MORE     More     More       AURFX 356-7VIL     FLEX BLE ROTARY PROBE 100KHZ-2MHZ, FOR MINI MITE 4 PIN FISCHER CONNECTOR 7.0° WORKING LONG     Image: More     Image: More <td< td=""><td>AURFX-13/64SS/4WL</td><td>FLEX PROBE 100KHZ-2MHZ, 4.0"WL, STAINLESS STEEL 12mm TIP LENGTH(.203") WITH A 4 PIN FISHER CONNECTOR</td><td></td><td></td><td></td><td></td></td<>	AURFX-13/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4.0"WL, STAINLESS STEEL 12mm TIP LENGTH(.203") WITH A 4 PIN FISHER CONNECTOR				
AURPS.156-7VL         FEXBLE ROTARY PROBE 100KHZ-2MHZ, FOR MINI MITE 4 PIN FISCHER CONNECTOR 7.0" WORKING LONG         Annotation	AURFX.218-7WL	FLEX PROBE 100KHZ-2MHZ, FOR MINI MITE				
APN-92-FX         FLEXIBLE SURFACE PROBE 50-SO0KHZ         MPO2	AURFX.375-7WL	FLEX PROBE 100KHZ-2MHZ, FOR MINI MITE 4 PIN FISCHER				
APN-92-8FX EXIBLE SURFACE PROBE 50-500KHZ 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	AURFX.156-7WL	FLEXIBLE ROTARY PROBE 100KHZ-2MHZ, FOR MINI MITE 4 PIN FISCHER CONNECTOR 7.0" WORKING LONG				
	APN-92-7FX	FLEXIBLE SURFACE PROBE 50-500KHZ	MP902-70FX			
ARRFX156/8WL FLEXIBLE PROBE FOR RA2000 SCANNER 100KHZ-2MHZ	APN-92-8FX	FLEXIBLE SURFACE PROBE 50-500KHZ	MP-902-80FX			
	ARRFX156/8WL	FLEXIBLE PROBE FOR RA2000 SCANNER 100KHZ-2MHZ				

# AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARRFX250/8WL	DESCRIPTION FLEXIBLE PROBE FOR RA2000 SCANNER 100KHZ-2MHZ	RFLX.250-RWL	EQUIVALENT	EQUIVALENT	EQOIVALENT
			-	•	
ARRFX312/8WL	FLEXIBLE PROBE FOR RA2000 SCANNER 100KHZ-2MHZ	RFLX.250-RWL		•	
ARRFX625/6WL	FLEXIBLE PROBE FOR RECHII SCANNER 100KHZ-2MHZ, 4 PIN STEP LEMO	•		•	
ARRFX750/6WL	FLEXIBLE PROBE FOR RECHII SCANNER 100KHZ-2MHZ, 4 PIN STEP LEMO				
ARRFX875/6WL	FLEXIBLE PROBE FOR RECHII SCANNER 100KHZ-2MHZ, 4 PIN STEP LEMO			•	
AURFX750/6WL	FLEXIBLE PROBE FOR UNIVERSAL 100KHZ-2MHZ, 4 PIN FISCHER				
AURFX875/6WL	FLEXIBLE PROBE UNIVERSAL 100KHZ-2MHZ, 4 PIN FISCHER			•	
AURFX625/6WL	FLEXIBLE PROBE UNIVERSAL100KHZ-2MHZ, 4 PIN FISCHER WITH COLLAR				
AURFBFX-4.1MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 4.1MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ ( TAPER END OF THE PROBE)				
AURFBFX-4.7MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 4.7MMØ HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ ( TAPER END OF THE PROBE)				
ARRFBFX-4.7MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 4.7MMØ HEAD STAINLESS STEEL 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE)				
AURFBFX-4.7SS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 4.7MMØ HEAD STAINLESS STEEL 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE)				
AURFBFX-4.8MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 4.8MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ ( TAPER END OF THE PROBE)				,
AURFBFX-5.0MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 5.0MMØ HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE)				
AURFBFX-5.1MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 5.1MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ ( TAPER END OF THE PROBE)				
AURFBFX-5.4MSS/5L	FIGUE POTARY FLAT BOTTOM PROBE 5.0" LONG 5.4MMØ HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE)				-
AURFBFX-5.5MSS/5L	FROBE) FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 5.5MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ ( TAPER END OF THE PROBE)				
AURFBFX-6.25MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 6.25MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE)				
AURFBFX-6.2MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 6.2MMØ HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE)			•	
AURFBFX-6.6MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 6.6MMØ HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE)			•	•
AURFBFX-7.0MSS/5L	FLXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 7.0MMØ HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ ( TAPER END OF THE PROBE)				
AURFBFX-7.1MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 7.1MMØ HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPERED END OF THE PROBE)				
AURFBFX-7.2MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 7.2MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KH2-2MHZ ( TAPER END OF THE PROBE)				
AURFBFX-7.5MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 7.5MMØ HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPERED END OF THE PROBE)				•
AURFBFX-7.8MSS/5L	FROBEJ FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 7.8MMØ HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ ( TAPER END OF THE PROBE)				
AURFBFX-7.9MSS/5L	FROBE) FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 7.9MMØ HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPERED END OF THE PROBE)				
AURFX312/5WL	FLEXIBLE ROTARY PROBE .312 DIAMETER, 5.0" WORKING LENGTH, 4 PINFISCHER CONNECTOR 100KHZ-2MHZ				
AURFX-11.9MSS/100MWL	FLEXIBLE ROTARY PROBE 100K-2MHZ, STAINLESS STEEL HEAD 11.9mmØ 4 PIN FISCHER CONNECTOR 100mm WORKING LENGTH			•	
AURFX-12.7MSS/100MWL	FLEXIBLE ROTARY PROBE 100K-2MHZ, STAINLESS STEEL HEAD 12.7mmØ 4 PIN FISCHER CONNECTOR 100mm WORKING LENGTH			•	
AURFX-7.8MSS/90MWL	FLEXIBLE ROTARY PROBE 100K-2MHZ, STAINLESS STEEL HEAD 7.8MM 4 PIN FISCHER CONNECTOR 90MM WORKING LENGTH				•
AURFX-3MSE/8L	FLEXIBLE ROTARY PROBE 3MM TO 4MM 8.0" LONG WITH COLLAR 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
AURFX-4MSE/8L	FLEXIBLE ROTARY PROBE 4MM TO 6MM 8.0" LONG WITH COLLAR 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
AURFX187/6L	FLEXIBLE ROTARY PROBE 6.0" OVERALL LENGTH WITH COLLAR .187 DIA PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
AURFX240/6L	FLEXIBLE ROTARY PROBE 6.0" OVERALL LENGTH WITH COLLAR .240 DIA PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
ARRFX250/6L	FLEXIBLE ROTARY PROBE 6.0" OVERALL LENGTH WITH COLLAR .250 DIA PLASTIC HEAD 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ				
AURFX307/6L	FLEXIBLE ROTARY PROBE 6.0" OVERALL LENGTH WITH COLLAR .307 DIA PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				-

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFX366/6L	FLEXIBLE ROTARY PROBE 6.0" OVERALL LENGTH WITH COLLAR .366 DIA PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
AURFX437/6L	FLEXIBLE ROTARY PROBE 6.0" OVERALL LENGTH WITH COLLAR .437 DIA PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	•		•	
ARRFX932/6L	FLEXIBLE ROTARY PROBE 6.0" OVERALL LENGTH WITH COLLAR .932 DIA PLASTIC HEAD 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ				
AURFX-5.1MSS/6WL	FLEXIBLE ROTARY PROBE 6.0" WORKING LENGTH WITH COLLAR .5.5MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	•			
AURFX-6.25MSS/6WL	FLEXIBLE ROTARY PROBE 6.0" WORKING LENGTH WITH COLLAR .6.25MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	•			
AURFX-7.2MSS/6WL	FLEXIBLE ROTARY PROBE 6.0" WORKING LENGTH WITH COLLAR .7.2MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	•			
AURFX-7.9MSS/6WL	FLEXIBLE ROTARY PROBE 6.0" WORKING LENGTH WITH COLLAR .7.9MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
AURFX-4.1MSS/6WL	FLEXIBLE ROTARY PROBE 6.0" WORKING LENGTH WITH COLLAR 4.1MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	•			
AURFX-5.5MSS/6WL	FLEXIBLE ROTARY PROBE 6.0" WORKING LENGTH WITH COLLAR 5.5MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	•			
AURFX-6.7MSS/6WL	FLEXIBLE ROTARY PROBE 6.0" WORKING LENGTH WITH COLLAR 6.7MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
AURFX-4.8MSS/6WL	FLEXIBLE ROTARY PROBE 6.0" WORKINLENGTH WITH COLLAR .4.8MM HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
ARRFX250/8L	FLEXIBLE ROTARY PROBE 8.0" OVERALL LENGTH WITH COLLAR .250"Ø DIA PLASTIC HEAD 4 PIN STEP LEMO CONNECTOR FOR RA-2000 SCANNER 100KHZ 2MHZ.				
ARRFX312/8L	FLEXIBLE ROTARY PROBE 8.0" OVERALL LENGTH WITH COLLAR .312"Ø DIA PLASTIC HEAD 4 PIN STEP LEMO CONNECTOR FOR RA-2000 SCANNER 100KHZ 2MHZ				
AURFX875/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH COLLAR. 875 DIA PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	EMFLX.875/8WL			
AURFX250SS/9L	FLEXIBLE ROTARY PROBE 9.0" LONG .250" DIA HEAD STAINLESS STEEL WITH COLLAR 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
AURFX500SS/9L	FLEXIBLE ROTARY PROBE 9.0" LONG .500" DIA HEAD STAINLESS STEEL WITH COLLAR 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ.				
AURFX187SS/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR .187 DIA HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	EMFLX.187/9L			
AURFX240SS/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR .240" DIA HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
AURFX307SS/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR .307" DIA HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	•			
AURFX366SS/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR .366" DIA HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	•		•	
AURFX437SS/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR .437" DIA HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	EMRFLX.437/9L			
AURFX437SE/9L	FLEXIBLE ROTARY PROBE 9.0" OVERALL LENGTH WITH COLLAR437"500"Ø EXPANDABLE PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KH2-2MHZ	•			
AURFX187SE/9L	FLEXIBLE ROTARY PROBE 9.0" OVERALL LENGTH WITH COLLAR .187"250"Ø EXPANDABLE PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHz-2MHz	•			
AURFX250SE/9L	FLEXIBLE ROTARY PROBE 9.0" OVERALL LENGTH WITH COLLAR .250"312"Ø EXPANDABLE PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHz-2MHz				
AURFX312SE/9L	FLEXIBLE ROTARY PROBE 9.0" OVERALL LENGTH WITH COLLAR .312"375"Ø EXPANDABLE PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHz-2MHz	•			
AURFX375SE/9L	FLEXIBLE ROTARY PROBE 9.0" OVERALL LENGTH WITH COLLAR .375"437"Ø EXPANDABLE PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHz-2MHz	•		•	
AUR-11MFB/SS/104MWL	FLEXIBLE ROTARY PROBE STAINLESS STEEL 104MM WL FLAT BOTTOM COIL AT 30 DEG 100 KHZ-2MHZ 4 PIN FISCHER	TEK3005UFB- 11M/SS/104WL		•	
AUR-11.8MFB/SS/104MWL	FLEXIBLE ROTARY PROBE STAINLESS STEEL 104MM WL FLAT BOTTOM COIL AT 30 DEG 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR	TEK3005UFB- 11.8M/SS/104MWL		•	
AURFX.250/8WL	FLEXIBLE ROTATING PROBE 100K-2MHZ8 INCH WORKING LENGTH 4 PIN FISCHER CONNECTOR	•			
AURFX.187SS/5WL	FLEXIBLE ROTATING PROBE STAINLESS STEEL, 100K-2MHZ5 INCH WL				
AURFBFX-18M/100MWL	FLEXIBLE ROTATRY FLAT BOTTOM PROBE 18MM DIAMETER 100MM WORKING LENGTH 100KH2-2MHz 4 PIN FISCHER CONNECTOR			•	
APN-92-9.5FX	FLEXIBLE SURFACE PROBE 50-500KHZ	•		•	
AP925-6FX	FLEXIBLE SURFACE PROBE	PAB90C60.25FX/50- 500KHZ			
APN-95-12FX	FLEXIBLE SURFACE PROBE 50-500KHZ	•			
APN-3FX	FLEXIBLE SURFACE PROBE 50-500KHZ 3.0" LONG MICRODOT CONNECTOR	MP30FX			
APN-6FX	FLEXIBLE SURFACE PROBE 50-500KHZ 6.0" LENGTH MICRODOT CONNECTOR				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
APN-45-6FX	FLEXIBLE SURFACE PROBE 50-500KHZ 6.0" LONG 45 DEG .500" DROP CURVE MICRODOT CONNECTOR .125" TIP				
ASPN-4FX/7L/1-3MHZ	FLEXIBLE SURFACE PROBE 1-3MHZ 4", 7PIN LEMO		9403364		
APN-45-8FX	FLEXIBLE SURFACE PROBE 50-500KHZ 8.0" LONG 45 DEG .500" DROP CURVE MICRODOT CONNECTOR .125" TIP	MP-455-80FX			
APN-95-7FX	FLEXIBLE SURFACE PROBE 50-500KHZ 90 DEG .500" DROP 7.0" LONG MICRODOT CONNECTOR .125" TIP				
APN91-3FX	FLEXIBLE SURFACE PROBE 50-500KHZ 90 DEGREES . 100" DROP 3.0 INCHES LONG WITH MICRODOT CONNECTOR	PEN91-3FLX			
ATPN-92-5FX	FLEXIBLE SURFACE PROBE 90 DEG .200"DROP 5.0" LONG TRIAX FISCHERCONNECTOR 200KHZ-1MHZ	MTF902-50FX			
APN-91-7FX	FLEXIBLE SURFACE PROBE 50-500KHZ 90 DEGREES .100" DROP 7.0 INCHES LONG WITH MICRODOT CONNECTOR .125" TIP				
ATPN-96-7FX/2MHZ	FLEXIBLE SURFACE PROBE 90 DEG .600" DROP 7.0" LONG 1-3MHZ TRIAX FISCHER CONNECTOR	TPENFLX96-7/2M			
ATPN95-7FX	FLEXIBLE SURFACE PROBE 90 DEGREES .500" DROP, .130" DIA. TRIAX FISCHER CONNECTOR, 50-500KHZ, 7.0" LONG				
ATPN-910-8FX	FLEXIBLE SURFACE PROBE 90 DEGREES 1.0" DROP. TF CONNECTOR 50-500KHZ				
ATPN-925-9FX	FLEXIBLE SURFACE PROBE 90" DEGREES, .500" DROP 9.0" LONG 50-500KHz WITH TRIAX FISCHER				
ATPN-975-6FX	FLEXIBLE SURFACE PROBE 90DEG .750" DROP 6.0" INCH LONG 50-500KHZHZ , TRIAX FISCHER CONNECTOR				
ATPN-903-85FX	FLEXIBLE SURFACE PROBE STRAIGHT .030 DROP 8.5" LONG TRIAX FISCHER CONNECTOR. 50-500KHz	MTF9003-85FX			
APN-92-4FX	FLEXIBLE SURFACE PROBE 50-500KHz 90° DEGREES .200" DROP 4.0 " LONG MICRODOT CONNECTOR	PAB09402FX			
APN-452-6FX	FLEXIBLE SURFACE PROBE 50-500KHZ, 45°, .25 DROP	MP455-60FX			
APN-455-6FX	FLEXIBLE SURFACE PROBE 50-500KHZ, 45°, .5 DROP	MP455-60FX			
APN-95C-5BFX	FLEXIBLE SURFACE PROBE 50-500KHZ, BENT	MP905-50BCFX			
APN-95-7FX/2MHZ	FLEXIBLE SURFACE PROBE 90 DEG .500" DROP 7.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
APN-910-5FX/2MHZ	FLEXIBLE SURFACE PROBE 90 DEG 1.00" DROP 5.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
APN-910-5FX	FLEXIBLE SURFACE PROBE 90 DEG 1.00" DROP 5.0" LONG MICRODOT CONNNECTOR 50-500KHz .125" TIP				
APN-910-7FX/2MHZ	FLEXIBLE SURFACE PROBE 90 DEG 1.00" DROP 7.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
APN-95-10FX	FLEXIBLE SURFACE PROBE 90° .500° DROP, 50-500KHZ MICRODOT CONNECTOR				
APN-93-6FX	FLEXIBLE SURFACE PROBE, 50-S00KHZ				
APN-91-3	RIGID SHAFT SURFACE PROBE 90 DEGREE .100" DROP 3 INCHES LONG .125" TUBING Ø. MICRODOT CONNECTOR 50-500KHZ				
APN-10	RIGID STRAIGHT SURFACE PROBE 50-500KHz, .125"Ø TUBING WITH MICRODOT CONNECTOR.	MP-100			
APN-925-4.5	RIGID SURFACE PROBE ABSOLUTE SHIELDED 90° DEGREES .250°, DROP 4.5" LONG MICRODOT CONNECTOR 50-500KHZ	309P24F			
APN-45-3/2MHZ	RIGID SURFACE PROBE 1-3MHZ 3.0" LONG 45 DEG .500" DROP MICRODOT CONNECTOR .125" TIP	PEN45-3 500K-2M			
APN-4/2MHZ	RIGID SURFACE PROBE 1-3MHZ 4.0" LONG MICRODOT CONNECTOR	MP-40-1-3M			
APN-6/2MHZ	RIGID SURFACE PROBE 1-3MHZ 6.0" LENGTH				
APN-92-4/1-3MHZ	RIGID SURFACE PROBE 1-3MHz 90° DEGREES .200° DROP 4.0 " LONG MICRODOT CONNECTOR	MP902-40/1-3M			
APNU-45-3/2M	RIGID SURFACE PROBE 45° DEGREES UNSHIELDED, MICRODOT CONNECTOR, 1-3MHz, 3.0" LONG				
AXSPN35-5FX	FLEXIBLE SURFACE PROBE 50-500KHZ, TIP OD .062 , 30" .5 DROP ,5.0" LONG, MICRODOT				
AXSPN45-5FX	FLEXIBLE SURFACE PROBE 50-500KHZ, TIP OD .062 , 45° .5 DROP ,5.0" LONG, MICRODOT				
AXSPN925-5FX	FLEXIBLE SURFACE PROBE 50-500KHZ, TIP OD .062 , 90° .25 DROP ,5.0° LONG, MICRODOT				
AXSPN955-5FX	FLEXIBLE SURFACE PROBE 50-500KHZ, TIP OD .062 , 90° .50 DROP ,5.0° LONG, MICRODOT				
AXSTPN45-5FX	FLEXIBLE SURFACE PROBE 50-500KHZ, TRIAX, 062 TIP 0D 45 DE .5 DROP ,5.0" LONG				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AXSTPN925-5FX	FLEXIBLE SURFACE PROBE 50-500KHZ, TRIAX.062 TIP .5.0" LONG				
AXSTPN955-5FX	FLEXIBLE SURFACE PROBE 50-500KHZ, TRIAX.062 TIP .5.0" LONG				
APN-8	RIGID SURFACE PROBE 50-S00KHZ 8.0" LENGTH MICRODOT CONNECTOR				
APN-975-3	RIGID SURFACE PROBE 50-500KHZ 90 DEG .750" DROP 3.0" LONG MIDRODOT CONNECTOR .125" TIP				
APN-91-7	RIGID SURFACE PROBE 50-500KHZ 90 DEGREES .100" DROP 7.0 INCHES LONG WITH MICRODOT CONNECTOR .125" TIP				
ASTPN95-5B/FX	FLEXIBLE SURFACE PROBE 50-500KHZ, TRIAX .092 TIP OD, .5 DROP, 6.0" LONG, BENT				
APN-92-4	RIGID SURFACE PROBE 50-500KHZ 90° DEGREES .200" DROP 4.0 " LONG MICRODOT CONNECTOR	MP902-40			
APN-95-7B	RIGID SURFACE PROBE 50-500KHZ 90° DEGREES, .500° DROP 7.0° LONG BENT, MICRODOT CONNECTOR .125° TIP	MP905-70B			
ATPN-4FX	FLEXIBLE SURFACE PROBE STRAIGHT .125" UNSHIELDED 50-500KHz, 4.0" LONG WITH TRIAX FISCHER CONNECTOR.	TPENFLX-4			
APN-95-7	RIGID SURFACE PROBE 50-500KHZ 90° DEGREES, .500° DROP 7.0° LONG MICRODOT CONNECTOR .125" TIP	MP905-70			
APN-925-3/2MHZ	RIGID SURFACE PROBE 90 DEG .250" DROP 3.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
APN-925-5/2MHZ	RIGID SURFACE PROBE 90 DEG .250" DROP 5.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
APN-95-3/2MHZ	RIGID SURFACE PROBE 90 DEG .500" DROP 3.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
PN-95-7FX/2MHZ	FLEXIBLE SURFACE PROBE 90 DEG .500" DROP 7.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
ATPN-8FX	FLEXIBLE SURFACE PROBE STRAIGHT, TRIAX FISCHER CONN 8.0" LONG 50-500KHZ	TPENFLX-8 50-500KHZ			
APN-95-7/2MHZ	RIGID SURFACE PROBE 90 DEG .500" DROP 7.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
APN-910-3/2MHZ	RIGID SURFACE PROBE 90 DEG 1.00" DROP 3.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
APN-910-5/2MHZ	RIGID SURFACE PROBE 90 DEG 1.00" DROP 5.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
ATPN-91-6FX/1MHZ	FLEXIBLE SURFACE PROBE, 90 DEG .100" DROP TRIAX FISCHER 200K-1MHZ				
ATPN-903-5FX/200K-1M	FLEXIBLE SURFACE PROBE, .030" DROP 5.0" LONG TRIAX FISCHER CONNECTOR 200KHz-1MHz	TPENFLX903-5/200K-1M			
APN-910-5	RIGID SURFACE PROBE 90 DEG 1.00" DROP 5.0" LONG MICRODOT CONNNECTOR 50-500KHz .125" TIP				
APN-95-7/1M	RIGID SURFACE PROBE 90° .500° DROP 1-3MHz, 7.0° LONG WITH MICRODOT CONNECTOR.	MP-905-70/1MHZ			
ATPN-903-6FX/1-6M	FLEXIBLE SURFACE PROBE, .030" DROP, BENT 90", 6.0" LONG TRIAX FISCHER CONNECTOR 1-6MHz	BCMTF9003-60FX-1-6M	MTF9003-60FX-1-6M	D0815E1015-2113	
ATPN-903-6FX	FLEXIBLE SURFACE PROBE, .030" DROP, BENT 90", 6.0" LONG TRIAX FISCHER CONNECTOR 50-500KHz	BCMTF9003-60FX			
ATPN-45-6FX/2MHZ	FLEXIBLE SURFACE PROBE, 45 DEG .500 DROP TRIAX 1-3MHZ				
ATP-95-5FX	FLEXIBLE SURFACE PROBE 90DEGREE .500" DROP 5.0" LONG .187" DIA TUBING 50-500KHZ TRIAX FISCHER CONNECTOR				
ATPN-92-4FX/2MHZ	FLEXIBLE SURFACE PROBE, 90° .200" DROP TRIAX FISCHER CONNECTOR 1-3MHZ, 4.0" LONG				
ATPN-92-6FX/1-6M	FLEXIBLE SURFACE PROBE, 90° .200" DROP TRIAX FISCHER CONNECTOR 1-6MHz, 6.0" LONG	BCMTF902-60FX-1-6M			
ATPN-92-4FX	FLEXIBLE SURFACE PROBE, 90° .200" DROP TRIAX FISCHER CONNECTOR 50-500KHZ, 4.0" LONG	TPENFLX92-4			
ATPN-92-6FX	FLEXIBLE SURFACE PROBE, 90° .200" DROP, 6.0" LONG, TRIAX FISCHER CONNECTOR 50-500KHz.	BCMTF902-60FX	TPENFLX92-6 50-500KHZ	MTF902-60FX	BCMTF902-60FX
ATPN-92-6.5FX	FLEXIBLE SURFACE PROBE, 90°.200° DROP, 6.5" LONG, TRIAX FISCHER CONNECTOR 50-500KHz.	TPENFLX92-6.5 50-500KHZ	TPENFLX92-6.5 50-500KHZ		
ATPN-92-6FX/2MHZ	FLEXIBLE SURFACE PROBE, 90° .200" DROP, TRIAX FISCHER CONNECTOR 1-3MHZ, 6.0" LONG	TPENFLX92-6 50-500KHZ			
ATPN-92-6FX/1MHZ	FLEXIBLE SURFACE PROBE, 90° .200" DROP, TRIAX FISCHER CONNECTOR 200KHz-1MHZ, 6.0" LONG	TPENFLX920-6/200K-1M			
ATPN-95-9FX/1MHZ	FLEXIBLE SURFACE PROBE, 90° .500" DROP TRIAX FISCHER CONNECTOR 500-2MHHZ, 9.0" LONG	LPENFLX95-9/1M			
ATPN-91-6FX/200K-1M	FLEXIBLE SURFACE PROBE, 90° DEGREES .100" DROP 6.0" LONG TRIAX FISCHER CONNECTOR 200KHZ-1MHz	TPENFLX91-6	MTF901-60FX-200K-1M	MTF901-60FX-200K-1M	
ATPN-91-6FX	FLEXIBLE SURFACE PROBE, 90° DEGREES . 100° DROP 6.0° LONG TRIAX FISCHER CONNECTOR 50KHZ-500KHz	TPENFLX91-6			

# AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
APN-97-6	RIGID SURFACE PROBE 90" .700" DROP 50-500KHz WITH MICRODOT CONNECTOR, 6.0" LONG.	MP907-60			
ATPN-95-6FX	FLEXIBLE SURFACE PROBE, 90° DEGREES, .500° DROP 6.0° LONG WITH TRIAX FISCHER CONNECTOR. 50-500KHz	MTF905-60FX	TPENFLX95-6	MTF905-60FX	
APN-92-5B/L500K	STAINLESS STEEL SURFACE PROBE 50-500KHZ 90° BENT, .125°Ø TIP, .200° DROP 5.0° LONG WITH MICRODOT CONNECTOR LOCATOR 500K	MP902-50B/L500K			
APN-7FX	STRAIGHT FLEXIBLE SURFACE PROBE, .1/8"DIA TUBING 50-500KHZ, 7.0" LONG. MICRODOT CONNECTOR	MP-70FX		•	
ATPNU-925-6FX	FLEXIBLE SURFACE PROBE, 90°, .25DROP, 50-500KHZ, 6°L, TRIAX CONNECTOR, UNSHIELDED			•	
ATPN95-6FX/2MHZ	FLEXIBLE SURFACE PROBE, 90°, .SD, 6°L, 1-3MHZ, TF CONNECTOR				
ATPN-6FX/2MHZ	FLEXIBLE SURFACE PROBE, TRIAX FISCHER 1-3MHZ 6.0" LONG	TPENFLX-6 50-500KHZ			
ATPN-903-8FX	FLEXIBLE SURFACE PROBE, TRIAX FISCHER CONNECTOR .030 DROP 8.0" LONG 50-500KHZ	TPENFLX903-8 50-500KHZ			
APN-902-4/1-3M	STRAIGHT SURFACE PROBE 1-3MHZ 4.0" LONG WITH MICRODOT CONNECTOR	MP902-4/1-3M		•	
ATPN-910-7FX	FLEXIBLE SURFACE PROBE, TRIAX 50-500KHZ	MTF-9010-70FX			
ATPN-91-5FX	FLEXIBLE SURFACE PROBE, TRIAX 50-500KHZ				
ATPNU-45-5FX	FLEXIBLE SURFACE PROBE, TRIAX FISCHER 50-500 KHZ, UNSHIELDED 5.0" LONG				
ATPN-925-12FX	FLEXIBLE SURFACE PROBE, TRIAX FISCHER CONNECTOR 50-500KHZ, 12.0" LONG 1/4" DROP				
ATP-95-063-6FX	FLEXIBLE SURFACE PROBE, 90° DEGREES, .125°Ø SHAFT, BENT 30° 1.0° FROM THE TIP, .187°Ø HEAD TAPERED TO .063°Ø, .250° DROP, 50-500KHz. TMTF-187-063-60FX	TMTF-187-063-60FX	D0815E1015-2079		
ATPNU-93-6FX	FLEXIBLE SURFACE PROBE, TRIAX FISCHER CONNECTOR 50-500 KHZ, UNSHIELDED, 6"LONG	UMTF9025-60FX			
ATPN-4FX/2MHZ	FLEXIBLE SURFACE PROBE, TRIAX FISCHER CONNECTOR, 1-3MHz	MTF-40FX-1-3M			
ATPNU-9FX/1-6M	FLEXIBLE SURFACE PROBE, UNSHIELDED, .125"Ø, TRIAX FISCHER CONNECTOR, 9.0" LONG, 1-6MHz. UMTF-90FX-1-6M	UMTF-90FX-1-6M	D0815E1015-2059		
ATPN-5/500K-1M	RIGID STRAIGHT SHAFT SURFACE PROBE, TRIAX FISCHER CONNECTOR 5.0° LONG. FREQUENCY 50-500KHz-1MHz				
ATPN910-4	RIGID SURFACE PROBE 50-500KHz .125"Ø TIP SHIELDED TRIAX FISHCER CONNECTOER 90" DEGREES 1.0" DROP				
ATPN-93-5/200KHZ-2MHZ	RIGID SURFACE PROBE 50-500KHZ, BENT 90", .300"(0.8CM) DROP, 5.0"(13CM) LONG TRIAX FISCHER CONNECTOR.			•	
ATPN92-6B	RIGID SURFACE PROBE 90° DEGREES .200° DROP ,6.0° LONG, TRIAX FISCHER CONNECTOR 50-500KHz	MTF902-60	MTF902-60B		
ATPN-92-5/2MHZ	RIGID SURFACE PROBE 90° DEGREES, .200" DROP, 125"Ø O.D. TIP 5.0" LONG, TRIAX FISCHER CONNECTOR 1-3 MHZ.				
ATPN-92-5	RIGID SURFACE PROBE 90° DEGREES, .200" DROP, 125"Ø O.D. TIP 5.0" LONG, TRIAX FISCHER CONNECTOR 50-500KHz.	BCMTF-902-50	MTF-902-50		
ATPN-92-6/7L/2MHZ	RIGID SURFACE PROBE 90° DEGREES, .200" DROP, 125"Ø O.D. TIP 6.0" LONG, 7 PIN LEMO CONNECTOR 1-6MHZ.	9403409			
ATPN-92-6/7L	RIGID SURFACE PROBE 90" DEGREES, .200" DROP, 125"Ø O.D. TIP 6.0" LONG, 7 PIN LEMO CONNECTOR 50-500KHz.	9403360			
ATPN-92-6/200KHZ-1MHZ	RIGID SURFACE PROBE 90" DEGREES, .200" DROP, 125"Ø O.D. TIP 6.0" LONG, TRIAX FISCHER CONNECTOR 200KHz-1MHZ.	9403408			
ATPN-92-6	RIGID SURFACE PROBE 90" DEGREES, .200" DROP, 125"Ø O.D. TIP 6.0" LONG, TRIAX FISCHER CONNECTOR 50-500KHz.	MTF902-60	BCMTF902-60		
ATPN-903-3	RIGID SURFACE PROBE ABSOLUTE SHIELED. 125" Ø TUBING 90° DEGREES , .030" DROP 3.0" LONG WITH TRIAX FISCHER CONNECTOR 20-200KHz	300P13F			
ATPN-92-4B/.050	RIGID SURFACE PROBE WITH .050" DIA. TUBING, 90 DEGREES .200" DROP BENT SHAFT 4,0" LONG TRIAX FISCHER CONNECTOR 50-500KHz	TXPEN92-4B			
ATPN-45-8	RIGID SURFACE PROBE, 45" .125" DIAMETER .500" DROP TRIAX FISCHER CONNECTOR 50-500KHZ.8.0" LONG	TPEN-45-8			
ATPNU-45-5/2M	RIGID SURFACE PROBE, 45" DEGREES CRANKED, .500" DROP, 5.0" LONG TRIAX FISCHER CONNECTOR 1-3MHz.	DPT45U			
ATPN-95-5/800KHZ	RIGID SURFACE PROBE, 1/8" STAINLESS STEEL TUBE, 90 DEGREE, .500" DROP, 5" LONG, 1-5MHZ, CENTER FREQUENCY 800KHZ, TRIAX FISCHER CONNECTOR. For TI reference standard.				
ATPN-95-5/300K-1MHZ	RIGID SURFACE PROBE, 1/8" STAINLESS STEEL TUBE, 90 DEGREE, .500" DROP, 5" LONG, 300KHz-1MHZ, TRIAX FISCHER CONNECTOR. For SS reference standard.				
AURXFX500/6L	FLEXIBLE UNIVERSAL ADJUSTABLE ROTARY X-PROBE .500"625" 100KHZ-2MHZ ,4 PIN FISCHER, 6.0" LONG				
AURFX11575T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH115"Ø, .75" TIP LENGTH.	OPXV4-74B119151-251	74B119151-251		
AUR281SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KH2-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 218"Ø.75" TIP LENGTH SPLIT END				

# AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFX218SE75T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 218"Ø.75" TIP LENGTH SPLIT END	OPXV4-74B119151-257	74B119151-257		
AUR250SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 250"Ø.75" TIP LENGTH SPLIT END				
AUR218SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH281"Ø, 1.5" TIP LENGTH SPLIT END.				
AUR312SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 312"Ø, 1.5" TIP LENGTH SPLIT END.				
AUR375SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 375"Ø, 1.5" TIP LENGTH SPLIT END.				
AUR437SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 437"Ø, 1.5" TIP LENGTH SPLIT END.				
AUR500SE-2.0T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH500"Ø, 2.0" TIP LENGTH SPLIT END.				
AURFX08375T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 75" TIP LENGTH	OPXV4-74B119151-247	74B119151-247		
AURFX09975T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 75" TIP LENGTH	OPXV4-74B119151-249	74B119151-249		
AURFX12575T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 75" TIP LENGTH				
AURFX156SE75T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 75" TIP LENGTH SPLIT END	OPXV4-74B119151-253	74B119151-253		
AURFX187SE75T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 75" TIP LENGTH SPLIT END	OPXV4-74B119151-255	74B119151-255		
AURFX156/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 750" TIP LENGTH SPLIT END, 156"Ø				
AURFX437/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END				
AURFX500SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END				
AURFX187/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, .187" Ø				
AURFX250SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, .250" Ø	OPXV4-74B119151-259	74B119151-259		
AURFX281/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, .281 🎾				
AURFX281SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, .281"Ø	OPXV4-74B119151-261	74B119151-261		
AURFX312/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, .312" Ø				
AURFX312SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, .312"Ø	OPXV4-74B119151-263	74B119151-263		
AURFX375/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, .375" Ø				,
AURFX375SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, .375" Ø	OPXV4-74B119151-265	74B119151-265		
AURFX437SE-1.5T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, .437" Ø	OPXV4-74B119151-267	74B119151-267		
AURFX500/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, .500"Ø				
AURFX500SE-2.0T/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 2.0" TIP LENGTH SPLIT END, .500"Ø	OPXV4-74B119151-269	74B119151-269		
AF-5126/L00	Foerster Shielded NFe Straight Surface Probe 200KHz-6MHz, 500" (12.7mm) long, .125"Ø Tubing. 63mm overall length. LEMO 00 CONNECTOR Use 500K Shield	2-835-69-2000			
AF-5126	Foerster Shielded NFe Straight Surface Probe 200KHz-6MHz, 500" (12.7mm) long, .125"Ø Tubing, 63mm overall length. MICRODOT CONNECTOR Use 500K Shield	2-835-69-2000			
AF-5120/7L	GE Weldscan probe; straight; 11 mm DIA 100-600KHZ 7 Pin Straight Lemo Connector	NA			
AF-5119/7L	GE Weldscan probe; straight; 11 mm DIA(100kHz) 7 Pin Straight Lemo Connector	NA			
AF-5069	GE Weldscan probe; straight; 16 mm (100kHz) 4 Pin Straight Lemo Connector	800P04MB1P			
AF-5121/7L	GE Weldscan probe; straight; 8.0 mm DIA 100-600KHZ 7 Pin Straight Lemo Connector	9403356		,	
AF-5070	GE Weldscan probe; straight; 9,5 mm (100-600kHz) 4 Pin Straight Lemo Connector	800P01MB3P			
AF-5056/4F	HIGH FREQUENCY PROBE 100KHZ-3MHZ, ABS				
AF-5066/4F	HIGH FREQUENCY PROBE 100KHZ-5MHZ, 4PIN FISCHER, ABS				
AF-5044	HIGH FREQUENCY ABS REFLECTION, 2 COILS, .850H, .7000D, .260ID 5-30KHZ				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-5077/4F	HIGH FREQUENCY ABS, SHIELED 100KHZ-3MHZ	KAS31H1575	KAS31H1575		
AF-5072-48/56	HIGH FREQUENCY ABSOLUTE /REFLECTION PROBE, 750"875', 1-3MHZ 4 PIN FISCHER	TEK-3013-48/56	NEC3129-48/56		
AF-5062.250	HIGH FREQUENCY ABSOLUTE PROBE 200KHZ, .250°Ø, B°L, TRIAX CONNECTOR, (WITH THIN CENTRE SHAFT FOR USE ON LARGE Ø WHEELS)		50PA24/200K		
AF-5062.375	HIGH FREQUENCY ABSOLUTE PROBE 200KHZ, .375"Ø, 8"L, TRIAX CONNECTOR, WITH THIN CENTRE SHAFT FOR USE ON LARGE Ø WHEELS)		50PA16/200K		
AF-5062.375/L500K	HIGH FREQUENCY ABSOLUTE PROBE 500KHZ, .375°Ø, 8°L, TRIAX CONNECTOR, WITH THIN CENTRE SHAFT FOR USE ON LARGE Ø WHEELS)		50PA16/500K		
AF-5045-U	HIGH FREQUENCY ABSOLUTE REFLECTION PROBE .330ID,10-100KHZ (SOLIDPROBEASSY1)				
AF-5025-U	HIGH FREQUENCY ABSOLUTE REFLECTION PROBE 1.00H .330ID.8000D 10-100KHZ				
AF-4177/TF	HIGH FREQUENCY ABSOLUTE SPOT PROBE, 500KHz-4MHz, .500" OD, 1.80" HEIGHT TRIAX FISCHER CONNECTOR FLAT SURFACE.	720P1F10	632-768-100		
AF-5072-56/64	HIGH FREQUENCY ABSOLUTE/ REFLECTION PROBE,, 1-3MHZ .875" -1.0" 4 PIN FISCHER	TEK-3013-56/64	NEC3129-56/64		
ABM.187FX-6	HIGH FREQUENCY BOLT HOLE PROBE 200-500KHZ				
AF-5040	HIGH FREQUENCY DIFFERENTAIL PROBE 100KHZ-500KHZ	TEK-4085			
AF-5034/.918964	HIGH FREQUENCY DIFFERENTIAL ADJUSTABLE PROBE , 25KHZ, 4.325WL, TF	NEC-3039			
AF-5055/2M	HIGH FREQUENCY DIFFERENTIAL BLADE PROBE, 1-3MHZ, TF , 6"L, FLEX SHAFT, .060 FLAT (THICK), SHIELDED	TEK-2059-1	NEC-1016-1	,	
AF-5041	HIGH FREQUENCY DIFFERENTIAL EDGE PROBE 45° ANGLE 50-500KHZ				Í
AF-5047	HIGH FREQUENCY DIFFERENTIAL EDGE PROBE 90° ANGLE 50-500KHZ				
AF-5046	HIGH FREQUENCY DIFFERENTIAL PROBE .8000D, .330ID, 1.0H, 4 COILS, DELRIN HOUSING 10-100KHZ				
AF-5024-P	HIGH FREQUENCY DIFFERENTIAL PROBE 10KHZ-100KHZ PLASTIC HOUSING, 1.00H .8600D.390ID				
AF-5020	HIGH FREQUENCY DIFFERENTIAL PROBE, 10KHZ-100KHZ, AL HOUSING, 1.00H .8000D .330ID	TEK-1450			
AF-5021	HIGH FREQUENCY DIFFERENTIAL PROBE, 10KHZ-100KHZ, PLASTIC HOUSEING, .670H7930D .330ID	TEK-1452			
AF-5020-P	HIGH FREQUENCY DIFFERENTIAL PROBE, 10KHZ-100KHZ, PLASTIC HOUSING, 1.00H .8000D . 330ID	TEK-1450			
AF-5043	HIGH FREQUENCY DIFFERENTIAL PROBE, 4 COILS, .750H, .7000D, .260ID, 1-5KHZ				
AF-5079	HIGH FREQUENCY DIFFERENTIAL PROBE, SOOKHZ-2MHZ SHIELDED, TF CONNECTOR				
AF-5052	HIGH FREQUENCY DIFFERENTIAL PROBE, SPRING LOADED, EDDY CURRENT SOOKHZ-1MHZ Lockheed F-22 Flaperon				
AF-5007/6.1MM	HIGH FREQUENCY FLEXIBLE ROTARY PROBE 100KHZ-2MHZ , 6.1mm Ø(.240").x 90mm(3.54") WORKING LENGTH, 4-PIN FISHER CONNECTOR 53-31-50- PB6	KD-1H-524.			
AF-5007/6.1M	HIGH FREQUENCY FLEXIBLE ROTARY PROBE 100KHZ-2MHZ , 6.1mm O.D.x 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR	KD1H52404-2	KD1H52404-3		
AF-5007/6.25MM	HIGH FREQUENCY FLEXIBLE ROTARY PROBE 100KHZ-2MHZ , 6.25mmø(.247") O.D.x 90mm(3.54") WORKING LENGTH, 4-PIN FISHER CONNECTORPT.6 53-15-79	KD-1H-524.10.2			
AF-5018	HIGH FREQUENCY I.D. SCAN EDDY CURRENT PROBE, SPRING LOADED				
AF-5051	HIGH FREQUENCY PENCIL PROBE 50-500KHZ, 90° ANGLE, .500 DROP 5.0" LONG, TRIAX FISCHER CONNECTOR				
AF-5050	HIGH FREQUENCY PENCIL PROBE 900KHZ-2MHZ, 90° ANGLE, .500 DROP 5.0" LONG, TRIAX FISCHER CONNECTOR				
AF-5053	HIGH FREQUENCY PENCIL PROBE, 1-3 MHZ, TAPER .062 TIP, 3.0" LONG, TF CONNECTOR				
AF-5067/4F	HIGH FREQUENCY PROBE 100KHZ-SMHZ, 4PIN FISCHER, ABS				
AF-5071	HIGH FREQUENCY PROBE 1-3 MHZ, TRIAX CONNECTOR				
AF-5010	HIGH FREQUENCY PROBE 1-3MHZ, .092 OD TIP, .50DROP, 60° ANGLE DOWN, TRIAX FISCHER CONNECTOR	TEK-2061	813P09		
AF-5049	HIGH FREQUENCY PROBE 500KHZ-1MHZ ABSSOLUTE SHIELDED W/ TRIAX FISCHER CONNECTOR (.080TIP)				
AF-5001	HIGH FREQUENCY PROBE ABS/SHIELDED LOO CONNECTOR 52-31-25-991-004-A , 1-3MHZ				
AF-5060	HIGH FREQUENCY PROBE ABS/SHIELDED LOO CONNECTOR 52-31-25-991-004-A , 1-3MHZ				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-5042/4F	HIGH FREQUENCY PROBE ABSOLUTE, SHIELDED 4.5" LONG, 4 PIN FISCHER 100KHZ-3MHZ				
AF-5073	HIGH FREQUENCY PROBE, 100-500KHZ, .045 THICK, 7"LONG (HANDLE 2.5") 45" ANGLE, .5" DROP				
AF-5058	HIGH FREQUENCY PROBE, 100KHZ-500KHZ, DIFFERENTIAL, UNSHIELDED, CROSS WOUND				
AF-5083	HIGH FREQUENCY PROBE, 50-500KHZ, SHIELDED,	IRR89F71/16			
AF-5000	HIGH FREQUENCY PROBE, TRIAX FISHER CONNECTOR DIFFERENTIAL 100KHz-500KHz	TEK-1508			
AF-5057	HIGH FREQUENCY REFLECTION PENCIL PROBE, 500KHZ-3MHZ, DIFFERENTIAL				
AF-5072-64/72	HIGH FREQUENCY REFLECTION PROBE, ABS, 1-3MHZ	TEK-3013-64-72	NEC3129-64/72		
AF-5002.460/.675/TI	HIGH FREQUENCY RING PROBE 1.1 HEIGHT TI 500K - 1MHZ DIFF, SHIELD, ABS COIL				
AF-5002.755/.530/TI	HIGH FREQUENCY RING PROBE 1.1 HEIGHT TI 500K - 1MHZ DIFF, SHIELD, ABS COIL				
AF-5084	HIGH FREQUENCY ROTARY PROBE, .437ID 25-500KHZ WITH GUIDE 1.375 OD				
AF-5003.725/.455/TI	HIGH FREQUENCY SPOT PROBE .700 CLEARANCE, ABSOLUTE, SHIELD, S00KHZ-1MHZ .725 OD ,.455 ID TRIAX FISCHER +.000002 (NDT3269)				
AF-5003.800/.530/TI	HIGH FREQUENCY SPOT PROBE .700 DEEP CLEARANCE, ABSOLUTE ,SHIELD, SO0KHZ-1MHZ (NDT3269) ID +.000002 .800 OD,.530 ID TRIAX FISCHER CONNECTOR.				
AF-5032/2MHZ	HIGH FREQUENCY SURFACE PROBE 1-3MHz 15° CRANK WITH 90° TIP, .250° DROP. MICRODOT CONNECTOR	314P26			
AF-5022	HIGH FREQUENCY SURFACE PROBE 1-3MHZ, ABS COIL, .500 DROP,.098 TUBING, 6.0" LONG, MICRODOT BENT AT 30 DEG 1.0" FROM THE HANDLE	2-835-07-6901			
AF-5017	HIGH FREQUENCY SURFACE SCAN EDDY CURRENT PROBE, SPRING LOADED				
AF-5054	HIGH FREQUENCY THREAD PROBE, 1-3 MHZ				
AF-5128	Hocking 12 pin hardwired 6.0" feet long 90" degrees reflection, .250"Ø tubing, .500" drop, 1-5KHz. Inclludes Test Report and Certificate of Conformance. Used with Hocking Phasec Series instruments	964491			
AF-5063L	HOCKING HIGH FREQUENCY PROBE (LEFT) 50-500KHZ, .125"Ø TUBING,BENT 40°, RADIUS 20MM(.787"), 20° TIP, MICRODOT CONNECTOR. 8.5" LONG.	815P206A	815P206A		
AF-5063R	HOCKING HIGH FREQUENCY PROBE (RIGHT) 50-S00KHZ, .125"Ø TUBING,BENT 40°, RADIUS 20MM(.787"), 20° TIP, MICRODOT CONNECTOR. 8.5" LONG.	815P206B	815P206B		
AFRR.156SE	HOLE PROBE 100KHZ - 2 MHZ, 1.1" WL	SPO.156187			
AF-5162	ID ENCIRCLING PROBE, DIFFERENTIAL 1-6MHZ, 1/4" OD, 8" WORKING LENGTH, TRIAX FISCHER CONNECTOR.				a
AF-5161	ID ENCIRCLING PROBE, DIFFERENTIAL 1-6MHZ, 1/8" OD, 8" WORKING LENGTH, TRIAX FISCHER CONNECTOR.				
AF-5163	ID ENCIRCLING PROBE, DIFFERENTIAL 1-6MHZ, 3/8" OD, 8" WORKING LENGTH, TRIAX FISCHER CONNECTOR.				
AF-4161	LF DIFFERENTIAL PROBE WITH 6.0" PIG TAIL TRIAX FISCHER 1-10KHZ ( GO THRU .250' AL)				a
AF-4156/.375H	LF REFLECTION PROBE .375 HEIGHTPRESSURE BULKHEAD TEA MD80) 6.0" PIG TAIL TRIAX FISCHER CONNECTOR 5-10KHZ INSPECT@ 7KHZ	C/N 935-0120 P/N APB/MSP			
AF-4156/.625H	LF REFLECTION PROBE .625 HEIGHT (PRESSURE BULKHEAD TEA MD80)6.0" PIG TAIL TRIAX FISCHER 5-10KHZ INSPECT@7KHZ	APB/MSP			
AF-4159	LF REFLECTION RING PROBE .400" ID .750" OD TRIAXFISCHER CONNECTOR200HZ-10KHZ	RR057-5-TF			
ARP-1.0-100H-1	LF REFLECTION RING PROBE .500" ID 1.0" OD TRIAX FISCHER SOHZ-3KHZ	RDP1.0-100H-1			
AF-4157	LF REFLECTION RING PROBE .500" ID.940' OD TRIAX FISCHER CONNECTOR200HZ-10KHZ	RR0510-5-TF			
AF-4165	LF REFLECTION RING PROBE .820"ID 1.310" OD .975" HEIGHT TRIAX FISCHERCONNECTOR 100HZ-1KHZ				
AF-4062/8M-23M	LF REFLECTION RING PROBE 80MM IDX23.0MM OD 30HZ-5KHZ TRIAX FISCHER CONNECTOR	ARK 31-2			
AF-4160	LF RELECTION RING PROBE .330" ID .700" OD TRIAX FISCHER CONNECTOR200HZ-10KHZ	RR057-6-TF			
AF-4155	LF RING PROBE .880" ID 1.30"OD REFL .900" HEIGHT TRIAXFISCHER CONNECTOR 50HZ-250 HZ				
ARP674/2K	LF RING PROBE REFLECTION .670" OD .400" ID 500HZ-5KHZ TRIAX FISCHER CONNECTOR (AF-4081)	RDP.674/2K	(AF-4081)		
ARP4/.75	LF RING PROBE REFLECTION .400" ID .750" OD .950' HEIGHT 100HZ-10KHZ TRIAX FISCHER CONNECTOR				
ATP95-5/5KHZ	LF SURFACE PROBE 90 DEG .500" DROP 5.0" LONG TRIAX FISCHER CONNECTOR.8-10KHZ BRIDGE (DIFF) .187" OD TUBE				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-5093	LFEC PROBE 90 DEG DROP 1.125 DIFF 6.0" LONG 1- 40KHZ TRIAX FISCHER CONNECTOR .187 TUBING	SPC-189			
AF-4153/TI	LOW FREQ PROBE REFLECTION ID.565" OD.910" 1/8 RADIUS 1.1' OAL TRIAX FISCHER CONNECTOR. 1-15 KHZ TEST @1-1.5KHZ (NDT 3225)			•	
ASDP44	LOW FREQUENCY REFLECTION SPOT PROBE .440"Ø DIA 2.0" LONG TRIAX FISCHER CONNECTOR 300HZ-100KHZ				
ASDP93	LOW FREQUENCY REFLECTION SPOT PROBE .930" DIA 2.0" LONG TRIAX FISCHER CONNECTOR 80HZ-60KHZ				
AF-4174/TF	LOW FREQUENCY REFLECTION SPOT PROBE .930" Ø 2.0" TALL TRIAX FISCHER CONNECTOR 1KHz-100KHz	632-483-007			
AF-4007	LOW FREQUENCY SPOT PROBE 90deg 5.0° LONG, .50° DROP REFLECTION TRIAX FISCHER CONNECTOR				
AF-4096/12L	LOW FREQUENCY ABS/DIFFERENTIAL STAINLESS STEEL SPOT PROBE, 1.5KHz-10KHZ,12.7mm(.500")Ø HARD WIRED TO 12 PIN LEMO, 6.0' FT. LONG.	720P1F5	632-761-003	•	
AF-4093/12L	LOW FREQUENCY ABS/DIFFERENTIAL STAINLESS STEEL SPOT PROBE, 1.5KHz-10KHZ,19mm(.750"Ø) HARD WIRED TO 12 PIN LEMO, 6.0' FT. LONG.	720P2F5L		•	
AF-4019	LOW FREQUENCY ABS/REFLECTION BOLT HOLE PROBE, 700HZ-1KHZ, 1.5"OD, 2.5"OAL WITH COLLAR TRIAX FISCHER CONN	NEC-1017			
AF-4073/TF	LOW FREQUENCY ABSOLUTE SPOT PROBE, 50KHz-400KHz, .500° OD; 1.80° HEIGHT TRIAX FISCHER CONNECTOR FLAT SURFACE.	720P1F30	632-765-100		
AF-4173/TF	LOW FREQUENCY ABSOLUTE SPOT PROBE, 5KHz-40KHz, -500" OD, 1.80" HEIGHT TRIAX FISCHER CONNECTOR FLAT SURFACE.	720P1F40	632-763-100	•	
AF-4001	LOW FREQUENCY BRIDGE RING PROBE .380" ID 1.00" OD 100HZ-1KHZ TRIAX FISCHER CONNECTOR	SPO-1746		•	
АТР95-4/5К	LOW FREQUENCY DIFFERENTAIL SURFACE PROBE . 187'Ø OD 4.0" LONG 2-20KHZ, TRIAX FISCHER CONNECTOR	P905-40-5K/TF			
AF-4191	LOW FREQUENCY DIFFERENTIAL PROBE, 1-40khz. Maximum height of .50" inches and diameter of of .375 max 6 inches overall length				
AF-4018	LOW FREQUENCY DIFFERENTIAL PROBE 20-30KHZWITH BENT SHAFT, 4.0° LONG, .400° DROP, SHIELDED, Outside Diameter 0.94°Ø WITH TRIAX FISCHER / LEMO CONNECTOR. USED WITH BOEING REFERENCE STANDARD NDT787				
ATP95-6/30K	LOW FREQUENCY DIFFERENTIAL PROBE SPOT 5.0 " long 5-30KHZ 90" DEGREES (RIGHT ANGLE) .500" DROP, .190" Ø OD. TRIAX FISHER CONNECTOR	SPC-4TF-105-3			
AF-4106/BAL	LOW FREQUENCY DIFFERENTIAL PROBE, 100HZ-1KHZ, MICRODOT, ID .620, OD1.10 HEIGHT .320	SPO-1240		•	a
AF-4106/S	LOW FREQUENCY DIFFERENTIAL PROBE, 100HZ-1KHZ, MICRODOT, ID .620, OD1.10 HEIGHT .320	SPO-1240		•	
AF-4106/TF	LOW FREQUENCY DIFFERENTIAL PROBE, 100HZ-1KHZ, TRIAX FISCHER CONNECTOR. ID .620, OD1.10 HEIGHT .320	SPO-1240			
AF-4152	LOW FREQUENCY DIFFERENTIAL PROBE, 100K-1.5MHZ			•	
AF-4042	LOW FREQUENCY DIFFERENTIAL PROBE, BRIDGE, SOOHZ-SKHZ	RB.8-500H-1			
ASDP4/1K	LOW FREQUENCY DIFFERENTIAL SPOT PROBE .400" O.D. 1-5KHz TRIAX FISCHER CONNECTOR	SPO 1391	SB.4-1K-1	•	
ASDP35/400HZ-2KHZ	LOW FREQUENCY DIFFERENTIAL SPOT PROBE TOP MOUNT, .350°Ø O.D. 400Hz-2KHz TRIAX FISCHER CONNECTOR				
AF-4149/.375	LOW FREQUENCY DIFFERENTIAL SPOT PROBE. TRIAX FISHER CONNECTOR 50-500KHz			•	a
АР-3/50К	LOW FREQUENCY PROBE STRAIGHT, DIFFERENTIAL, .187Ø OD TUBING 3.0" LONG 30-50KHz WITH TRIAX FISCHER CONNECTOR	MT-30/50K	MT-30/50K	P/50-100K/A/0.0/3	
AF-4025	LOW FREQUENCY REFLECTION PROBE 20-SOKHZ OD.310, .285PC,	SPO-1598			
AF-4162	LOW FREQUENCY REFLECTION PROBE WITH 6.0" PIG TAIL TRIAX FISCHER CONNECTOR, 1-10KHZ ( GO THRU .250' AL)			•	
ARP79312	LOW FREQUENCY REFLECTION RING PROBE .312" ID .790" OD 100H2-5KHZ TRIAX FISCHER CONNECTOR			•	a
AF-4094	LOW FREQUENCY REFLECTION RING PROBE 150HZ-1KHZ. TRIAX FISCHER CONNECTOR. 1.0" O.D. x .595" I.D. x 1.50"H	NEC-4028-3	NEC-4028-3	TEK-3006-3	
AF-4051	LOW FREQUENCY REFLECTION SPOT PROBE TF CONNECTOR 500H-30KHZ	TEK-1528	NEC-4031	•	
AF-4121	LOW FREQUENCY REFLECTION SPOT PROBE, 2-200KHZ6200D, STRAIGHT	SPO-2134		•	
AF-4024	LOW FREQUENCY REFLECTION SURFACE SPOT PROBE 100HZ-SKHZ (APS/20/S).75" O.D. TRIAX FISCHER CONNECTOR.	9213555	APS/20/S	•	
AF-4028	LOW FREQUENCY REFLECTION PROBE 5.0 " LONG BENT 15" DEGREES 5-30KHZ 90" DEGREES (RIGHT ANGLE).300" DROP WITH A .190" OUTSIDE DIAMETER. TRIAX FISHER CONNECTOR.	NEC-1084	TEK-1522		
AF-4069	LOW FREQUENCY REFLECTION PROBE OD .425 700HZ-80KHZ		SPO-5238	•	
AF-4043/TI	LOW FREQUENCY REFLECTION PROBE .3000D, .400H, 5.5L COPPER SHAFT, OAL 8", 2-10KHZ, TI			•	
AF-4002	LOW FREQUENCY REFLECTION PROBE .4500D .300ID HEIGHT .550 1-10KHZ				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-4066/4F	LOW FREQUENCY REFLECTION PROBE 100HZ-10KHZ 4 PIN FISCHER CONNECTOR				
AF-4000/TI	LOW FREQUENCY REFLECTION PROBE 1-15K, ID.550 OD .900 HEIGHT 1.1 TI, RADIUS 1/8 TEST @1-1.5KHZ (NDT3225)				
AF-4080	LOW FREQUENCY REFLECTION PROBE 1-30KHZ	SDP.4-4K-1	RS404-1		
AF-4003/UNSH	LOW FREQUENCY REFLECTION PROBE 1-50KHZ, UNSHIELDED 303SS TRIAX FISCHER CONNECTOR				
AF-4049/2K	LOW FREQUENCY REFLECTION PROBE 1-5KHZ	RDP.6-2K-5	RR206-5		
AF-4076	LOW FREQUENCY REFLECTION PROBE 1-5KHZ ID.42, OD.75 .05H				
AF-4009	LOW FREQUENCY REFLECTION PROBE 20-50KHZ, ABS, 4" LONG, BENT SHAFT, .5" DROP, .100 OD TIP				
AF-4140	LOW FREQUENCY REFLECTION PROBE 2-30KHZ, TRIAX CONNECTOR				•
AF-4053	LOW FREQUENCY REFLECTION PROBE 2-40KHZ, TRIAX FISCHER	TEK-2039	NEC-2079		
AF-4059	LOW FREQUENCY REFLECTION PROBE, .3500D, .750-1.0H, 200HZ-15KHZ				
AF-4023	LOW FREQUENCY REFLECTION PROBE, 100HZ-350HZ, MAX .900H, ID.750", OD1.30" TRIAX FISCHER CONNECTOR	TEK-4062	LR058-1-TF	LR058-1	
AF-4078	LOW FREQUENCY REFLECTION PROBE, 100KHZ-20KHZ, .620OD, TF				
AF-4134	LOW FREQUENCY REFLECTION PROBE, 10KHZ-100KHZ ABS	TEK-4080			
AF-4089	LOW FREQUENCY REFLECTION PROBE, 1-5KHZ, .187OD, RIGHT ANGLE	LFSR187	LFSR187		
AF-4077	LOW FREQUENCY REFLECTION PROBE, 1-5KHZ, .250ID, .815 OD TRIAX FISCHER CONNECTOR.				
AF-4197	LOW FREQUENCY REFLECTION PROBE, 3KHz-15KHz, .250"I.D., .550"Ø O.D.(Tolerance of -0, +.007") WITH TRIAX FISCHER CONNECTOR.				
AF-4062/4F	LOW FREQUENCY REFLECTION PROBE, ID.433", OD 1.0", HEIGHT .630", 30HZ-5KHZ. 4-PIN FISCHER CONNECTOR	ARK 31-2			
AF-4062	LOW FREQUENCY REFLECTION PROBE, ID.433", OD 1.0", HEIGHT .630", 30HZ-5KHZ. TRIAX FISCHER CONNECTOR		NEC-4028-5	,ARK31-2,	
AF-4054	LOW FREQUENCY REFLECTION PROBE, REFLECTION, 1-5KHZ, .186OD, 2"L, TRIAX	PT.04	SPO-2883		
AF-4082	LOW FREQUENCY REFLECTION PROBE, SPOT, 100HZ-2KHZ75"OD,1.75H,TRIAX FISCHER CONNECTOR		SPO-5496		
AF-4010	LOW FREQUENCY REFLECTION PROBE, SPOT, SHIELDED, TRIAX CONNECTOR, 1-100KHZ	SB.2-1K-1	RS-102-1-TF		
AF-4056	LOW FREQUENCY REFLECTION PROBE, TRIAX SOOH-10KHZ, ID .375, OD.600, 1 <sup>1</sup> H	RDP.7-25-5-4F			
AF-4169	LOW FREQUENCY REFLECTION RING PROBE .275"ID TRIAX FISCHER CONNECTOR 800HZ-3KHZ				
ARP85/.35-500HZ	LOW FREQUENCY REFLECTION RING PROBE .35" ID .85" OD TRIAX FISCHER CONNECTOR 500HZ-SKHZ				
AF-4171	LOW FREQUENCY REFLECTION RING PROBE .450 I.D.(11.4mm), .900"(22.8mm) O.D. TRIAX FISCHER CONNECTOR 900HZ-5KHZ	RR017-1/TF			
AF-4135	LOW FREQUENCY REFLECTION RING PROBE .605ID X1.160 OD TRIAX FISCHER CONNECTOR 50HZ-3KHZ	RR112-5-TF	RR112-5-TF	RDP1.2-100H-5	
AF-4107	LOW FREQUENCY REFLECTION RING PROBE .651" ID .940" OD REFLECTION 100Hz-500Hz TRIAX FISCHER CONNECTOR.	TEK-4050			
AF-4117	LOW FREQUENCY REFLECTION RING PROBE 100HZ-10KHZ .187ID TRIAX FISCHER CONNECTOR	SPC-365R187			
AF-4095	LOW FREQUENCY REFLECTION RING PROBE 100HZ-10KHZ, ID.500"OD1.25"TRIAX FISCHER CONNECTOR		SPO-2030		
ARP75-1K	LOW FREQUENCY REFLECTION RING PROBE 1-10KHZ TRIAX FISCHER CONNECTOR .830" OD and .670" ID	RDP.75-1K			
ARP9-100H-2	LOW FREQUENCY REFLECTION RING PROBE 50H2-5KHz, TRIAX FISCHER CONNECTOR 1.060" OD and .500" ID	RDP.9-100H-2			
AF-4092	LOW FREQUENCY REFLECTION RING PROBE FOR THE NDT3255 500HZ-3KHZ				
AF-4060	LOW FREQUENCY REFLECTION RING PROBE, .555ID, .8400D, 1.3"H, 400HZ-5KHZ				
AF-4133	LOW FREQUENCY REFLECTION RING PROBE, .55ID, 1.00D, .700H 200HZ-1KHZ FOR NDT2032-A TRIAX FISCHER	SPC-427			
AF-4114	LOW FREQUENCY REFLECTION RING PROBE, .650 ID X 1.3180D TRIAX FISCHER CONNECTOR 100HZ-10KHZ	TEK-4045-5	NEC-4137-5	SPO-5608	
AF-4138	LOW FREQUENCY REFLECTION RING PROBE, 1-20KHZ TRIAX CONN MAX .890 HEIGHT	TEK-4065			

# AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-4083	LOW FREQUENCY REFLECTION RING PROBE, 300-500HZ ID.850 OD1.4, 1.70H	RDP-1.485-200H	RDP-1.485-200H	ТЕК-4000В	
ARP-1.07/1.57-500HZ	LOW FREQUENCY REFLECTION RING PROBE. 1.07" ID 1.57" OD TRIAX FISCHER CONNECTOR 500HZ-1KHZ	RDP1.57-1.07/500H			
AF-4072	LOW FREQUENCY REFLECTION SPOT PROBE, 300HZ-100KHZ, DELRIN .625"OD, 1.77H TRIAX FISCHER CONNECTOR	9222160 / 9213554	700P16A		
ASDP.98-100HT	LOW FREQUENCY REFLECTION SPOT PROBE 1KHZ-30KHZ TRIAX FISCHER CONNECTOR	SDP.98-100HT	SDP.98-100HT		
ASDP38-500H/T	LOW FREQUENCY REFLECTION SPOT PROBE 500Hz-15KHz, TOP MOUNT TRIAX FISCHER CONNECTOR.	D0815E1015-2117	D0815E1015-2117	SDP.3-500H/T	
AF-4148	LOW FREQUENCY REFLECTION SPOT PROBE .300" DROP ,90" DEGREES, BENT ,.250" Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. 1-20KHz (AL ).	NEC-1084	TPNR.187-95-6B	RS902-50B	
AF-4011/7L	LOW FREQUENCY REFLECTION SPOT PROBE 1KHZ-100KHZ .440°OD, USE WITH NDT396 7 PIN LEMO CONNECTOR	SPO-5328L.44, 9230403			
AF-4047	LOW FREQUENCY REFLECTION SPOT PROBE 1KHZ-40KHZ TRIAX FISCHER CONNECTOR, .500" DIAMETER	RS-1005-5/TF	SDP.5-10K2	RS-1005-2/TF	
AF-4128	LOW FREQUENCY REFLECTION SPOT PROBE 300HZ-3KHz,385" OD, TOP MOUNT 1.8" HEIGHT TRIAX FISCHER CONNECTOR				a
ASDP6-500H-2	LOW FREQUENCY REFLECTION SPOT PROBE 500H-5KHZ .600" OD 1.8" HEIGHT TOP MOUNTED TRIAX FISCHER CONNECTOR	SPO 5255, SDP.6-500H			
AF-4044	LOW FREQUENCY REFLECTION SPOT PROBE 500Hz-15KHZ, TRIAX FISCHER CONNECTOR .460" OD	SDP.45-1K		•	
AF-4180	LOW FREQUENCY REFLECTION SPOT PROBE TOP MOUNT, .350"Ø O.D. 400Hz-2KHz TRIAX FISCHER CONNECTOR			•	
ASDP25/2-100KHZ	LOW FREQUENCY REFLECTION SPOT PROBE, 250" Ø OD, .750" HIGH, 2KH2-100KHz, SIDE MOUNT TRIAX FISCHER CONNECTOR. SR2K-100K-02RA-TF	SR2K-100K-02RA-TF	D0815E1015-2089		
ASDP50/300HZ-40KHZ	LOW FREQUENCY REFLECTION SPOT PROBE, 500" Ø OD, 1.35" HIGH, 300Hz-40KHz, SIDE MOUNT TRIAX FISCHER CONNECTOR. SR300H-40K-05RA-TF	SR300H-40K-05RA-TF	D0815E1015-2091	•	
AF-4090	LOW FREQUENCY REFLECTION SPOT PROBE, 2-200KHZ2500D, STRAIGHT, TRIAX FISCHER CONNECTOR.	LFSR250	LFSR250	•	
AF-4122	LOW FREQUENCY REFLECTION SPOT PROBE, 2-200KHZ4400D, STRAIGHT	SPO-2025			
AF-4088	LOW FREQUENCY REFLECTION SPOT PROBE, 2-20KHZ TRIAX FISCHER CONNECTOR .	RS203-1/TF	RS203-1/TF	SDP.3-2K	
AF-4105	LOW FREQUENCY REFLECTION SPOT PROBE, 300HZ-10KHZ, .620" O.D, TOP MOUNT TRIAX FISCHER CONNECTOR	9222161	SPO-2134	9222161	
AF-4150	LOW FREQUENCY REFLECTION SPOT PROBE, 500HZ-2KHZ	SDP.4-1K			
AF-4064	LOW FREQUENCY REFLECTION SPOT PROBE, STEEL BODY 1KHZ-100KHZ, .280"OD, 1.80" HEIGHT TRIAX FISCHER CONNECTOR	-			
ATPR-95-3/1-10KHZ	LOW FREQUENCY REFLECTION SURFACE PROBE 90°.500" DROP, .187" OD TUBING 3.0" LONG REFLECTION, TRIAX FISCHER CONNECTOR				
AF-4013	LOW FREQUENCY REFLECTION SURFACE/SPOT PROBE 300HZ-40KHZ .500" OD, TRIAX FISCHER CONNECTOR (SPO-2136)	SPO-2136,9213553	SPO-2136	TEK-4001-5	
AF-4091	LOW FREQUENCY REFLECTION, 500HZ-5KHZ, ID.498, OD.900 TRIAX FISCHER COONECTOR				
AF-4037	LOW FREQUENCY RING PROBE .250"IDX.650" OD REFLECTION TRIAX FISCHER CONNECTOR 500HZ-10KHZ				a
AF-4113	LOW FREQUENCY RING PROBE 100Hz-1KHz REFLECTION800"IDx1.3"OD MAX HEIGHT .900" TRIAX FISCHER CONNECTOR				
AF-4079	LOW FREQUENCY RING PROBE 800HZ, .33ID, .54OD				
ARP8-500H-1	LOW FREQUENCY RING PROBE REFLECTION .305 ID X 820 OD TRIAX FISCHER CONNECTOR 500Hz-SKHz.	RDP.8-500H-1	RDP.8-500H-1		
AF-4164	LOW FREQUENCY RING PROBE REFLECTION .750" ID x 1.400" O.D. x .750" H, TRIAX FISCHER CONNECTOR 100HZ-3KHZ	-			
AF-4163/100HZ	LOW FREQUENCY RING PROBE REFLECTION .750" ID x 1.450" OD TRIAX FISCHER CONNECTOR (LEMO) 100HZ-3KHZ	-			
AF-4101	LOW FREQUENCY RING PROBE, .7000D, .350ID, 1KHZ-10KHZ, TRIAX	-			
AF-4102	LOW FREQUENCY RING PROBE, .7000D, .350ID, 50HZ-5KHZ, TRIAX			•	
AF-4120	LOW FREQUENCY RING PROBE, 10KHz-100KHz, REFLECTION, .400°ID, .800°OD TRIAX FISCHER CONNECTOR USED WITH REFERENCE STANDARD: NDT1102-100 TI			•	
AF-4145/.187	LOW FREQUENCY RING PROBE, BRIDGE .187 ID/.531 OD 30HZ-SKHZ, TRIAX			•	
AF-4145/.248	LOW FREQUENCY RING PROBE, BRIDGE .248 ID/.875 OD 30HZ-SKHZ, TRIAX			•	
AF-4145/.315	LOW FREQUENCY RING PROBE, BRIDGE .315 ID/.906 OD 30HZ-SKHZ, TRIAX			•	
AF-4145/.433	LOW FREQUENCY RING PROBE, BRIDGE .433 ID/1.093 OD 30HZ-5KHZ, TRIAX				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-4145/.512	LOW FREQUENCY RING PROBE, BRIDGE .512 ID/1.125 OD 30HZ-5KHZ, TRIAX				
AF-4145/.630	LOW FREQUENCY RING PROBE, BRIDGE .630 ID/1.50 OD 30HZ-5KHZ, TRIAX				
ARP85-5K	LOW FREQUENCY RING PROBE, REFLECTION,1-SKHZ TRIAX FISCHER CONNECTOR	RDP.85-5K			
AF-4108	LOW FREQUENCY RING PROBE500Hz-5KHz REFLECTION TF CONNECTOR				
AF-5033	LOW FREQUENCY SPOT PROBE REFLECTION 300HZ-10KHZ. TRIAX FISCHER CONNECTOR .600" diameter.	NEC-4087-7	NEC-4087-7	TEK-4001-7	
AF-4055	LOW FREQUENCY SPOT PROBE, DIFFERENTIAL 2-20KHZ, .3200D, 2"L, TRIAX	SB.3-4K-2	SPO-1284		
ASDP310/5K	LOW FREQUENCY SPOT PROBE, DIFFERENTIAL SKHZ-100KHZ, 1.75L, WITH TOP MOUNT TRIAX FISCHER CONNECTOR.				
AF-4119	LOW FREQUENCY SPOT PROBE, DIFFERENTIAL, .325OD, 1-20KHZ, TRIAX CONNECTOR	LS203-2			
AF-4118	LOW FREQUENCY SPOT PROBE, DIFFERENTIAL, .375OD, 5-30KHZ, TRIAX CONNECTOR	LS1003-1			
AF-4137	LOW FREQUENCY SPOT PROBE, DIFFERENTIAL, S00HZ-SKHZ, OD .280, TRIAX CONNECTOR	LS102-1			
AF-4070	LOW FREQUENCY SPOT PROBE, REFLECTION 1-20KHz374" OD x 1.75" H				
AF-4012-1	LOW FREQUENCY SPOT REFLECTION PROBE .310"OD,1KHZ-20KHZ TOP MOUNT TRIAX FISCHER CONNECTOR	RS903-1			`.
ASDP-053-1	LOW FREQUENCY SPOT REFLECTION PROBE 200Hz-10KHz, .360" OD CASE	RS053-1			
ATP-5/2KHZ	LOW FREQUENCY STRAIGHT PENCIL PROBE (.187" DIA TUBING) BRIDGE 5.0" LONG TRIAX FISCHER CONNECTOR WITH AN OPERATING FREQUENCY OF 2KHZBRIDGE				
ATPQ-5/3-5K	LOW FREQUENCY SURFACE PROBE .250" DIA 5.0" LONG 3-5KHZ DIFFERENTIAL TRIAX FISCHER CONNECTOR				
ATP-5/100KHZ-500KHZ	LOW FREQUENCY SURFACE PROBE 100KHZ-500KHZ, STRAIGHT .156" OD TUBING 5.0" LONG DIFFERENTIAL, TRIAX FISCHER CONNECTOR				
ATP-95-5/12K	LOW FREQUENCY SURFACE PROBE 12KHz, 90° DEGREES, .500° DROP .187°Ø TUBING 5° LONG DIFFERENTIAL, TRIAX FISHER CONNECTOR				
ATP-3 /1-50K	LOW FREQUENCY SURFACE PROBE 1-50KHZ, .187"Ø TUBING 3.0" LONG DIFFERENTIAL, TRIAX FISHER CONNECTOR				
ATP-3.5 /1-50KHz	LOW FREQUENCY SURFACE PROBE 1-50KHZ, .187"Ø TUBING 3.5" LONG DIFFERENTIAL, TRIAX FISHER CONNECTOR				
ATP-45-3.5/1-50KHZ	LOW FREQUENCY SURFACE PROBE 1-50KHZ, 45° DEGREE .500° DROP .187°Ø TUBING 3.5° LONG DIFFERENTIAL, TRIAX FISHER CONNECTOR				
ATPR-95-6/5K	LOW FREQUENCY SURFACE PROBE 1-50KHZ, 90".500" DROP, .187" OD TUBING 6.0" LONG REFLECTION, TRIAX FISCHER CONNECTOR				
ATP-95-3.5/1-50KHZ	LOW FREQUENCY SURFACE PROBE 1-50KHZ, 90" DEGREE .500" DROP .187"Ø TUBING 3.5" LONG DIFFERENTIAL, TRIAX FISHER CONNECTOR				
ATP-95-6/1-50KHZ	LOW FREQUENCY SURFACE PROBE 1-50KHZ, 90" DEGREE .500" DROP .187"Ø TUBING 6.0"LONG DIFFERENTIAL, TRIAX FISHER CONNECTOR	RS-60/1-20KHZ			
ATP-95-7/2K	LOW FREQUENCY SURFACE PROBE 2-10KHZ, 90" .500" DROP .187" DIAMETER TUBING 7.0"LONG DIFFERENTIAL, TRIAX FISHER CONNECTOR	TPN95-7/2K			a
ATPR-95-5/5k	LOW FREQUENCY SURFACE PROBE 2-20KHz 90 DEG .5' DROP 187" OD TUBING 5.0" LONG REFLECTION, TRIAX FISCHER CONNECTOR	TPNR95-5/5K			
ATP-95-4/5K	LOW FREQUENCY SURFACE PROBE 5-20KHZ, 90°. S' DROP .187° DIAMETER TUBING 4.0°LONG DIFFERENTIAL, TRIAX FISHER CONNECTOR	TPN95-41/5K			
ATP-95-6/5K	LOW FREQUENCY SURFACE PROBE 5-20KHZ, 90°.5' DROP .187" DIAMETER TUBING 6.0"LONG DIFFERENTIAL, TRIAX FISHER CONNECTOR	TPN95-6/5K			
AF-5107	LOW FREQUENCY SURFACE PROBE 90 DEG .250" DROP 3.0" LONG DIFFERENTIAL TRIAX FISCHER 1-40KHZ	SPO-3714	NEC-4111,TEK2026		
ATP-94-4/1K	LOW FREQUENCY SURFACE PROBE 90° DEGREES .400° DROP 4.0° LONG BRIDGE/DIFFERENTIAL1KHZ, TRIAX FISCHER CONNECTOR .187" DIA TUBING				
APQ925-6B/1-20K	LOW FREQUENCY SURFACE PROBE 90° DIFFERENTIAL, .250° DROP .25° DIAMETER, BENT, 1-20KHz 6.0° LONG	VMD120-04-625			
APQ95-5B/1-30K	LOW FREQUENCY SURFACE PROBE 90° DIFFERENTIAL, .500° DROP .25° DIAMETER, BENT, 1-30KHz 5.0° LONG	LPQ905-50B/TF/1-30K			
ATPQ-95-6B/1-30K	LOW FREQUENCY SURFACE PROBE DIFFERENTIAL, .250"Ø, 90".500" DROP 6.0" LONG, BENT, 1-30KHZ DIFFERENTIAL TRIAX FISCHER CONNECTOR. LPQ905-608-TF-1-30K	LPQ905-60B-TF-1-30K	D0815E1015-2081		
ATPR-95-6B1/4-100K	LOW FREQUENCY SURFACE PROBE REFLECTION 4-100KHZ, 15° CRANK 1" FROM THE TIP, 90° .500" DROP, .187" OD TUBING 6.0° LONG , TRIAX FISCHER CONNECTOR				
ATPN-45-3	RIGID SURFACE PROBE, 45° .125" DIAMETER, TRIAX FISCHER CONNECTOR, 50-500KHZ, 3.0" LONG	MTF455-30			
AMHY156187	MANUAL BOLT HOLE PROBE 1.5WL 50-500KHZ MICRODOT CONNECTOR				
AMH.098	MANUAL .098 DIAMETER BOLT HOLE PROBE WITH COLLAR 50-500KHZ MICRODOT CONNECTOR 1.3" WORKING LENGTH	VM101BS-5/32			

# AeroFab NDT LLC

mandMainMa		DECODIDION	EQUIVALENT			
manualMain standard sequence of inclusion sequence of inclusio	PART NUMBER			EQUIVALENT	EQUIVALENT	EQUIVALENT
MAILMAILMailMa						
HalingMaximumMain ManufactMain Manufact<			10103-5/52			
NumberNumbe			NEC-3110-1 120/1 240/EX	*		
NumberNumbe				•		
Anis Laba AriaAnis Laba Aria Teles Construction Laba Aria Construction Laba AriaSinceSinceSinceSinceAme Aria TamAnis Laba Aria Teles Laba Aria Teles Laba Aria Construction Laba AriaMark				*		
AnalysicMuklestructurestrestrestrestrestrestrestrestrestrest			brind-off		•	
Number			•		•	
Run and a maximum set of the			NEC 2014	NEC 2014	500 5704	
Any-Abs/Abs/Abs/Abs/Abs/Abs/Abs/Abs/Abs/Abs/						
stratesMAUL NOT HOLE MORE SIDE INFO UNMERTED YOULD, ALS COLT, FAUSolSolSolSolREMAIL DET AGLE MORE SIDE UNMERTED YOULD, ALS COLT, FAUSolSolSolSolSolREMAIL DET AGLE MORE SIDE UNMERTED YOULD, ALS COLT, FAUSolSolSolSolSolREMAIL DET AGLE MORE SIDE UNMERTED YOULD, ALS COLT, FAUSolSolSolSolSolSolREMAIL DET AGLE MORE SIDE UNMERTED YOULD, ALS COLT, FAUSolSolSolSolSolSolREMAIL DET AGLE MORE SIDE UNMERTED YOULD, ALS COLT, FAUSolSolSolSolSolSolREMAIL DET AGLE MORE SIDE UNMERTED YOULD, ALS COLT, FAUSolSolSolSolSolSolREMAIL DET AGLE MORE SIDE UNMERTED YOULD, ALS COLT, FAUSol					SPO-5850	
NumberNumbe			NEC-30780867.910	NEC-30780867.910		
NAME BOT THE PRODUCTION OF UNDER MERCIPACIPACIES AND CONTRACT TANKNote of the probability of the proba			•	•	•	
NUMALNUMAL BOTHOLE PROFE BOORDE LIMEE LIMERING DWY COLLAR, ABS COL, TF, 7W,NUMAL			•		•	
NH1235-3272WNR1UL BOLT HOLE PRODE SOURCY LINK HILDED W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Source Source Source Link W/ COLLAR, ABS COL, TY, 2W.Image: Source Sourc			•	•		
Anityal Bolt Hole Probe Booker Link Unshielded Wichlag, Ass Coll, Tr, 2NLInI			•			
AntipationAntipati	ATMH.281312/2WL	MANUAL BOLT HOLE PROBE 300KHZ 1MHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL				
And the set of the probest sooker with clustering between sooker with cluster	ATMH.312375/2WL	MANUAL BOLT HOLE PROBE 300KHZ 1MHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL				
ATTHALS26327.WLMANUAL BOLT HOLE PROBE 300K/2 LIMICUNSHELDED W/ COLLAR, ASS COIL, TF, ZWLImage: Coll Coll Coll Coll Coll Coll Coll Col	ATMH.375437/2WL	MANUAL BOLT HOLE PROBE 300KHZ 1MHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL	•		•	
Anima SectionAnima Boit Hole PROBE 300RH2 INHE UNSHIELDED W/COLLAR, ABS COIL, T., 2WLIn	ATMH.437500/2WL	MANUAL BOLT HOLE PROBE 300KHZ 1MHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL	•		•	
ATMAK 687-750/2WL       MANUAL BOLT HOLE PROBE 500KHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL       Second of the second	ATMH.562625/2WL	MANUAL BOLT HOLE PROBE 300KHZ 1MHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL	•			
ATMAL28ANNAL2 BOLT HOLE PROBE 50-SOOKHZ UNSHIELDED W/ COLLARCOLARCOL	ATMH.625687/2WL	MANUAL BOLT HOLE PROBE 300KHZ 1MHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL				
ATMH 375       MANUAL BOLT HOLE PROBE 50-500KH2 UNSHIELDED W/ COLLAR       COLLAR       Collar       Collar       Collar       Collar         ATMH 375       MANUAL BOLT HOLE PROBE 50-500KH2 UNSHIELDED W/ COLLAR	ATMH.687750/2WL	MANUAL BOLT HOLE PROBE 300KHZ IMHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL				
ATMH 437AMANUAL BOLT HOLE PROBE 50-SOOKHZ UNSHIELDED W/ COLLAR, ABS COIL, TRIAX FISCHER CONNECTOR 2.0" WORKING LONGCalon 3Calon 3Calon 3Calon 3ATMH 5005 FZ WLMANUAL BOLT HOLE PROBE 50-SOOKHZ UNSHIELDED W/ COLLAR, TRIAXSoot ADS	ATMH.281	MANUAL BOLT HOLE PROBE 50-S00KHZ UNSHIELDED W/ COLLAR	6200-3/16-BH-BNC			
ATM       ANUAL BOLT HOLE PROBE 50-500KHZ UNSHIELDED W/ COLLAR, ABS COIL, TRIAX FISCHER CONNECTOR 2.0" WORKING LONG       A       A       A         ATMH;50052/WL       MANUAL BOLT HOLE PROBE 50-500KHZ UNSHIELDED W/ COLLAR, TRIAX       S	ATMH.375	MANUAL BOLT HOLE PROBE 50-S00KHZ UNSHIELDED W/ COLLAR	6200-3/8-BH-BNC			
ATMH-SMMANALA BOLT HOLE PROBE 50-500KHZ UNSHIELDED W/ COLLAR, TRIAXATMAAAAAAATMH-SMMANUAL BOLT HOLE PROBE 50-500KHZ, UNSHIELDED W/ COLLAR, TRIAXAAA<	ATMH.437	MANUAL BOLT HOLE PROBE 50-500KHZ UNSHIELDED W/ COLLAR	6200-3/8-BH-BNC			
ATMH-9MM       ANNUAL BOLT HOLE PROBE 50-500KHZ UNSHIELDED W/ COLLAR, TRIAX       Coll	ATMH.500SE/2WL	MANUAL BOLT HOLE PROBE 50-500KHZ UNSHIELDED W/ COLLAR, ABS COIL, TRIAX FISCHER CONNECTOR 2.0" WORKING LONG	•	-		
ATM H-921 MANUAL BOLT HOLE PROBE 50-500KH2, 2.5" LONG UNSHIELDED, W/ COLLAR TRIAX FISCHER CONNECTOR MANUAL BOLT HOLE PROBE 50-500KH2, 2.5" LONG UNSHIELDED, W/ COLLAR TRIAX FISCHER CONNECTOR MANUAL BOLT HOLE PROBE 50-500KH2, W/ COLLAR, MICRODOT CONNECTOR200KH2 MANUAL BOLT HOLE PROBE 50-500KH2, W/ COLLAR, MICRODOT CONNECTOR200KH2 MANUAL BOLT HOLE PROBE 6.0" LONG WITH COLLAR MICRODOT CONNECTOR200KH2 MANUAL BOLT HOLE PROBE 6.0" LONG WITH COLLAR MICRODOT CONNECTOR200KH2 MANUAL BOLT HOLE PROBE 6.0" LONG WITH COLLAR MICRODOT CONNECTOR200KH2 MANUAL BOLT HOLE PROBE 6.0" LONG WITH COLLAR MICRODOT CONNECTOR200KH2 MANUAL BOLT HOLE PROBE 6.0" LONG WITH COLLAR MICRODOT CONNECTOR500KH2 MANUAL BOLT HOLE PROBE 6.0" LONG WITH COLLAR MICRODOT CONNECTOR500KH2 MANUAL BOLT HOLE PROBE 6.0" LONG WITH COLLAR STRIAX FISCHER CONNECTOR 10-30KH2 MANUAL BOLT HOLE PROBE ABS/REFLS00" DO 6.0" LONG WITH COLLAR STRIAX FISCHER CONNECTOR 10-30KH2 MANUAL BOLT HOLE PROBE ABS/REFLS00" DO 6.0" LONG WITH COLLAR STRIAX FISCHER CONNECTOR 10-30KH2 MANUAL BOLT HOLE PROBE ABS/REFLS00" DO 6.0" LONG WITH COLLAR STRIAX FISCHER CONNECTOR 10-30KH2 MITH COLLAR MICRODOT CONNECTORS00KH2 WITH COLLAR MICRODOT CONNECTOR	АТМН/5ММ	MANUAL BOLT HOLE PROBE 50-500KHZ UNSHIELDED W/ COLLAR, TRIAX	•			
AMH-11 10M       MANUAL BOLT HOLE PROBE 50-500KHZ, W/ COLLAR, MICRODOT       AMICRODOT       S	АТМН/9ММ	MANUAL BOLT HOLE PROBE 50-500KHZ UNSHIELDED W/ COLLAR, TRIAX				
AMH-158 MA       MANUAL BOLT HOLE PROBE 50-500KHZ, W/ COLLAR, MICRODOT       AMM-250-6L/200K       School       <	ATMH.921	MANUAL BOLT HOLE PROBE 50-500KHz, 2.5" LONG UNSHIELDED, W/ COLLAR TRIAX FISCHER CONNECTOR	6200-59/64-BH-BNC			
AMH-250-6L/200K       MANUAL BOLT HOLE PROBE 6.0° LONG WITH COLLAR MICRODOT CONNECTOR200KHz       Image: Control of the	AMH-11.10M	MANUAL BOLT HOLE PROBE 50-500KHZ, W/ COLLAR, MICRODOT	•			
AMH-250-6L/S00K ANUAL BOLT HOLE PROBE 6.0° LONG WITH COLLAR MICRODOT CONNECTORS00KHz MICRODOT CONNECTORS00KHz MICRODOT CONNECTORS00KHz MICRODOT CONNECTORS00KHz WITH COLLAR STRIAX FISCHER CONNECTOR 10-30KHz MICRODOT CONNECTORS00KHz WITH COLLAR MICRODOT CONNECTORS00KHz	AMH-15.80M	MANUAL BOLT HOLE PROBE 50-500KHZ, W/ COLLAR, MICRODOT	•			
ATMH-S00/6/25KHZ       MANUAL BOLT HOLE PROBE ABS/REFLS00° DD 6.0° LONG WITH COLLARS TRIAX FISCHER CONNECTOR 10-30KHZ       VM101BR-1/2X6 10-30KHZ       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG WITH COLLARS TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       VM101BR-1/2X6 10-30KHZ       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° DD 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR       Manual Bolt Hole PROBE ABS/REFLS00° LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH CO	AMH250-6L/200K	MANUAL BOLT HOLE PROBE 6.0" LONG WITH COLLAR MICRODOT CONNECTOR 200KHz	•			
ATMH-SMM ANUAL BOLT HOLE PROBE ABSOLUTE SMM DIA 3.5" LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR	AMH250-6L/500K	MANUAL BOLT HOLE PROBE 6.0" LONG WITH COLLAR MICRODOT CONNECTOR 500KHz				
	ATMH500/6/25KHZ	MANUAL BOLT HOLE PROBE ABS/REFL500" OD 6.0" LONG WITH COLLARS TRIAX FISCHER CONNECTOR 10-30KHZ	VM101BR-1/2X6 10-30KHZ			
ATMH-11MM MANUAL BOLT HOLE PROBE ABSOLUTE500KKHZ-1MHZ 11MM DIA TRIAX FISCHER CONNECTOR 3.5" LONG WITH COLLAR	АТМН-5ММ	MANUAL BOLT HOLE PROBE ABSOLUTE 5MM DIA 3.5" LONG TRIAX FISCHER CONNECTOR 50-500KHZ WITH COLLAR				
	ATMH-11MM	MANUAL BOLT HOLE PROBE ABSOLUTE500KKHZ-1MHZ 11MM DIA TRIAX FISCHER CONNECTOR 3.5" LONG WITH COLLAR				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATMHD.218	MANUAL BOLT HOLE PROBE DIFFERENTIAL COIL TRIAX FISCHER CONNECTOR 1.0" WORKING LENGTH 500KHZ-2MHZ	9216170			
AMHF156/500K	MANUAL BOLT HOLE PROBE SWIVEL COLLAR 500KHZ-1 MHZ FERRITE SHIELDED W/ COLLAR ,MICRODOT CONN.	MHF.125/500K			•
AMHF187/500K	MANUAL BOLT HOLE PROBE SWIVEL COLLAR 500KHZ-1 MHZ FERRITE SHIELDED W/ COLLAR ,MICRODOT CONN.	MHF.125/500K			<u>.</u>
AMH343	MANUAL BOLT HOLE PROBE SWIVEL COLLAR MICRODOT CONNECTOR 50-500KHZ 3.0" LONG				
AMH095/1.3WL	MANUAL BOLT HOLE PROBE UNSHIELDED, WITH COLLAR, MICRODOT CONNECTOR 50-500KHZ 1.3" WORKING LENGTH				
ATMH770/6WL/25K	MANUAL BOLT HOLE PROBE WITH COLLAR .770° OD 6.0°WL TRIAX FISCHER25KHZ DIFF	NEC-3014-1	NEC-3014-1	.SPO-5849	
ATMH250	MANUAL BOLT HOLE PROBE, 50 -SOOKHZ UNSHIELDED				
ATMH375437/SE	MANUAL BOLT HOLE PROBE, SPLIT END, 500KHZ -1MHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL				
ATMH500625/SE	MANUAL BOLT HOLE PROBE, SPLIT END, 500KHZ -1MHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL				
ATMH750875/SE	MANUAL BOLT HOLE PROBE, SPLIT END, 500KHZ -1MHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL				
ATMH-875-1.00/SE	MANUAL BOLT HOLE PROBE, SPLIT END, 500KHZ -1MHZ UNSHIELDED W/ COLLAR, ABS COIL, TF, 2WL				
AMHF125	MANUAL BOLT HOLE PROBE, SWIVEL COLLAR 500KHZ-1MHZ FERRITE SHIELDED W/ COLLAR ,MICRODOT CONN.	MHF.125/500K			
MCSP-003	MANUAL COUNTER SINK PROBE 100° DEGREES 500KHz-2MHz WITH TRIAX FISCHER CONNECTOR .156"Ø				
MCSP-001	MANUAL COUNTER SINK PROBE 100° DEGREES 500KHz-2MHz WITH TRIAX FISCHER CONNECTOR .187"Ø				
MCSP-005	MANUAL COUNTER SINK PROBE 100° DEGREES 500KHz-2MHz WITH TRIAX FISCHER CONNECTOR .230°Ø				
MCSP-002	MANUAL COUNTER SINK PROBE 100° DEGREES 500KHz-2MHz WITH TRIAX FISCHER CONNECTOR .250°Ø				
MCSP-006	MANUAL COUNTER SINK PROBE 100" DEGREES 500KHz-2MHz WITH TRIAX FISCHER CONNECTOR .312"Ø				
ATMHR.500-6/25KHZ	MANUAL HOLE BOLT PROBE 6.0" LONG TRIAX FISCHER CONNECTOR ABS/REFLWITH COLLARS 10-30KHZ TRIAX FISCHER CONNECTOR	VM101BR-1/2X6 10-30KHZ			
ATMHX312375	MANUAL X BOLT HOLE PROBE312375 TRIAX FISCHER CONNECTOR				•
ATMHX-1.567/5WL/2MHZ	MANUAL X BOLT HOLE PROBE 1.567" 0D5.0" WL TRIA X FISCHER CONNECTOR WITH COLLAR 1-3MHZ( ABS COIL)FISCHER CONNECTOR				
AURFB6-7MM	MINI ADJUSTABLE ROTARY PROBE WITH COIL SET AT 30 DEG. FLAT BOTTOM 45mm WORKING LENGTH	MARP30-RUK-2-6-7-45			
AF-5039/2MHZ	MODIFIED-RIGHT ANGLE HOCKING SURFACE PROBE ABSOBLUTE 1-3MHZ .092" TIP .500" DROP SHIELDED 1.75" TIP LENGTH, MICRODOT CONNECTOR	813P009			
PPG-125/5	PENCIL PROBE GUIDE, .750"Øx.500" H FOR .125"Ø PROBE TIPS. MATERIAL: DELRIN OR EQUIVALENT.				
AF-5130	PENCIL SURFACE PROBE TAPERED TIP 15° DEGREES, 4.0" LONG, TRIAX FISCHER CONNECTOR, 50-500KHz.	DPTTAPU-001			
APNU-5/2M	STRAIGHT SURFACE PROBE 5.0" LONG MICRODOT CONNECTOR, UNSHIELDED, 500KHz-2MHz	ZHHD-DPTU-E00.125-15			
APN-7	STRAIGHT SURFACE PROBE 50-500KHz WITH MICRODOT CONNECTOR.114mm LONG	MP-70			
APN-45-4/2M	SURFACE PROBE 1-3MHZ	MP455-40-1-3M			
AF-5127-EXT	PROBE EXTENSION HANDLE, FEMALE RECEPTACLE 4 PIN FISCHER TO TRIAX FISCHER, 8" LONG	NEC-3129EXT	TEK-3013EXT		
ARRF187	PROBE FOR RA2000 SCANNER 100KHZ-2MHZ	BPRAF-12 3/16			
AF-7000/.244	QCT PROBE 100KHZ-2MHZ	SPO-5000			
ARRFX187/6L	RA SCANNER FLEX-SHAFT ROTARY PROBE 100KHz-1MHz. 4 PIN STEP LEMO CONNECTOR 6.0" INCH LONG	RFLX.187-6			•
ARR-1.437	RA SCANNER PROBE 2 INCH WORKING LENGTH. 100KHz-2MHz				•
ARR-1.60	RA SCANNER PROBE 2 INCH WORKING LENGTH. 100KHz-2MHz				•
ARR600	RA SCANNER PROBE 2 INCH WORKING LENGTH. 4 PIN STEP LEMO100KHz-2MHz				•
ARR.125/SE	RECHII BOLT HOLE PROBE 100KHZ-2MHZ, SPLIT END .125"156", 1.1" WORKING LENGTH FOR RA 2000 MINIMITE(LEMO), SCANNER. 4 PIN STEP LEMO CONNECTOR	RR.125SE	SPO-3564		
ARR250/1.5WL	RECHII BOLT HOLE PROBE 100KHZ-2MHZ, SPLIT END FOR RA SCANNER, 1.5" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 250"281"				

# AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARR.090/SE	RECHII BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END .090125 1.1WL FOR RA 2000 4 PIN STEP LEMO	RR.090SE	SPO-3564		
AUR187SE	RECHII BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END FOR RA SCANNER, 1.1" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 187".218"	•		•	
ARR-1.56SE/1.5WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END FOR RA SCANNER, 1.5" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 156"187"				
ARR156SE/2WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END FOR RA SCANNER, 2.0" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 156"187"				
ARR187SE/2WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END FOR RA SCANNER, 2.0" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 187"218"				
ARR218SE/2WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END FOR RA SCANNER, 2.0" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 218"-250"				
ARR-2.18SE/1.5WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END FOR RA SCANNER, 2.0" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 218"250"	SPO-3564		•	
ARR281SE/2.0WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END FOR RA SCANNER, 2.0" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 281"312"	SPO-3564			
ARR250SE/4.5WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END MINIMITE STEP LEMO SCANNER., 4.5" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR.				
ARR375437/2WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ. SPLIT END FOR RA SCANNER 2.0" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR .375"437"				
ARR437SE/2.0WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ. SPLIT END FOR RA SCANNER 2.0"WORKING LENGTH 4 PIN STEP LEMO CONNECTOR .437"500"				
ARR562SE/2.0WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ. SPLIT END FOR RA SCANNER 2.0"WORKING LENGTH 4 PIN STEP LEMO CONNECTOR .562"- 625"				
ARR6255E/2.0WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ. SPLIT END FOR RA SCANNER 2.0"WORKING LENGTH 4 PIN STEP LEMO CONNECTOR .625"687"				
ARR687SE/2.0WL	RECHII BOLT HOLE PROBE 200KHZ-1MHZ. SPLIT END FOR RA SCANNER 2.0"WORKING LENGTH 4 PIN STEP LEMO CONNECTOR .687"750"				
ARR250SE/2WL	RECHII BOLT HOLE PROBE 200KHZ-3MHZ, SPLIT END FOR RA SCANNER, 2.0" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 250"312"				
ARRCS100500	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 1/2" OD 3.0" OVERALL				
ARRCS100.250	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 1/4" OD 3.0" OVERALL			•	a
ARRCS100125	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 1/8"Ø OD 3.0" OVERALL				
ARRCS100687	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 11/16" OD 3.0" OVERALL				
ARRCS100343	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 11/32" OD 3.0" OVERALL				
ARRCS100406	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 13/32" OD 3.0" OVERALL				
ARRCS100468	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 15/32" OD 3.0" OVERALL				
ARRCS100531	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 17/32" OD 3.0" OVERALL				
ARRCS100592	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 19/32" OD 3.0" OVERALL				
ARRCS100656	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 21/32" OD 3.0" OVERALL				
ARRCS100718	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 23/32" OD 3.0" OVERALL				
ARRCS100.187	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 3/16" OD 3.0" OVERALL				
ARRCS100187	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 3/16" OD 3.0" OVERALL				
ARRCS100750	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 3/4" OD 3.0" OVERALL				
ARRCS100.375	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 3/8" OD 3.0" OVERALL				
ARRCS100375	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 3/8" OD 3.0" OVERALL				
ARRCS100.312	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 5/16" OD 3.0" OVERALL				
ARRCS100312	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 5/16" OD 3.0" OVERALL				
ARRCS100.156	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 5/32" OD 3.0" OVERALL LENGTH			•	
ARRCS100156	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 5/32"Ø OD 3.0" OVERALL			•	
ARRCS100625	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 5/8" OD 3.0" OVERALL		•		

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARRCS100437	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 7/16" OD 3.0" OVERALL				
ARRCS100562	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 9/16" OD 3.0" OVERALL				
ARRCS100281	RECHII RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 9/32" OD 3.0" OVERALL				
ARR1.0SE	RECHII RA SCANNER PROBE100KHz-2MHz 4 PIN STEP LEMO 1.0°Ø OD 2.0° OVERALL LENGTH SPLIT END	RR 1.0 SE			
ARR.875SE	RECHII RA SCANNER PROBE100KHz-2MHz 4 PIN STEP LEMO 7/8"" OD 2.0" OVERALL LENGTH SPLIT END				
ARR.500SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 1/2" OD 3.0" OVERALL LENGTH SPLIT END .500531	SPO-3564			
ARR.406SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 13/32" OD 3.0" OVERALL LENGTH SPLIT END .406437	SPO-3564			
ARR.437SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 15/32" OD 3.0" OVERALL LENGTH SPLIT END .437468	SPO-3564	SPO-3564		
ARR.531SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 17/32" OD 3.0" OVERALL LENGTH SPLIT END 531562	SPO-3564			
ARR.593SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 19/32" OD 3.0" OVERALL LENGTH SPLIT END .593625	SPO-3564			
ARR.656SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 21/32" OD 3.0" OVERALL LENGTH SPLIT END .656687	SPO-3564			
ARR.718SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 23/32" OD 3.0" OVERALL LENGTH SPLIT END .718750	SPO-3564			
ARR.750SE/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 3/4" OD 1.5" WORKING LENGTH SPLIT END .750781	RR.750SE/1.5WL			
ARR.750SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 3/4" OD 3.0" OVERALL LENGTH SPLIT END .750781	SPO-3564			
ARR.375SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 3/8' OD 3.0" OVERALL LENGTH SPLIT END .375406	SPO-3564			
ARR-4.1M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 4.1mm OD 1.5" WORKING LENGTH				
ARR-4.4M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 4.4mm OD 1.5" WORKING LENGTH				
ARR-4.8M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 4.8mm OD 1.5" WORKING LENGTH				
AUR-4.8M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 4.8mm OD 1.5" WORKING LENGTH				
ARR-4.0M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 4mm OD 1.5" WORKING LENGTH				
ARR-5.6M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 4mm OD 1.5" WORKING LENGTH				
AUR-4.4M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 4mm OD 1.5" WORKING LENGTH				
ARR-5.2M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 5.2mm OD 1.5" WORKING LENGTH				
ARR.281SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 5/16" OD 3.0" OVERALL LENGTH SPLIT END 281312	SPO-3564, 9217156			
ARR.312SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 5/16" OD 3.0" OVERALL LENGTH SPLIT END 312343	SPO-3564			
ARR.625SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 5/8" OD 3.0" OVERALL LENGTH SPLIT END .625656	SPO-3564, 9218786			
ARR-6.0M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 6.0mm OD 1.5" WORKING LENGTH				
ARR-6.1M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 6.1mm OD 1.5" WORKING LENGTH				
ARR-6.2M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 6.2mm OD 1.5" WORKING LENGTH				
ARR-6.3M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 6.3mm OD 1.5" WORKING LENGTH				
ARR-6.4M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 6.4mm OD 1.5" WORKING LENGTH				
ARR-7.9M/1.5WL	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 7.9mm OD 1.5" WORKING LENGTH				
ARR.468SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 7/16" OD 3.0" OVERALL LENGTH SPLIT END .468-500	SPO-3564			
ARR.562SE	RECHII SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO 9/16" OD 3.0" OVERALL LENGTH SPLIT END 562-593	SPO-3564, 9218785			
ARR.218SE	RECHII SCANNER PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 3/16" OD 1.1" WORKING LENGTH SPLIT END218"250"	SPO-3564, 9217154			
ARR.187SE	RECHII SCANNER PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 3/16" OD 1.1" WORKING LENGTH SPLIT END .187218	SPO-3564, 9217153	SPO-3564,RR.187SE		

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARR187SE/6WL	RECHII SCANNER PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 3/16" OD 6.0" WORKING LENGTH SPLIT END .187218				
ARR.156SE/1.1WL	RECHII SCANNER PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 5/32" OD 1.1" WORKING LENGTH SPLIT END .156187	•			-
ARR156SE/6WL	RECHII SCANNER PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 5/32" OD 6.0" WORKING LENGTH SPLIT END .156187	•		•	
ARR.156SE	RECHII SCANNER PROBE FOR RA2000 SCANNER 200KHz-3MHz 4 PIN STEP LEMO 5/32" OD 3.0" OVERALL LENGTH SPLIT END .156187	SPO-3564, 9230078	SPO-3564,RR.156SE		
ARR.750/1.5WL	RECHII SCANNER PROBE, .750 1.5"WL, 100KHZ-2MHZ	9216296			
ARR.437SE/2WL	RECHII SCANNER PROBE, SPREAD END, .437500, 2"WL, 100KHZ-2MHZ	RR.437SE/2WL			
ARR.750SE/2WL	RECHII SCANNER PROBE, SPREAD END, .750830, 2"WL, 100KHZ-2MHZ	RR.750SE/2WL			
ARR.343SE	RECHII SCANNER PROBE100KHz-2MHz 4 PIN STEP LEMO 11/32" OD 3.0" OVERALL LENGTH SPLIT END .343375	SPO-3564			
ASRS-123A	REFERENCE STANDARD ALUMINUM .008, .010, .040				
AF-4143	REFL RING PROBE .500" ID X 1.00" DIA OD X .875 HEIGHT TRIAX CONNECTOR100HZ-10KHZ	TEK-3006-2 MOD TO .875" H	TEK-3006-2 MOD TO .875" H	NA	
ARP-1.0-100H-5/4L	REFL RING PROBE 50H-3KHZ WITH 4 PIN LEMO CONNECTOR	RDP1.0-100H-5/4L	RR0110-5-4L		
ARP7-2K-5/4F	REFLECTION RING PROBE SOUHz-2 KHz TRIAX FISCHER CONNECTOR				
ARP-1.0/.4/2K	REFLECTION RING PROBE, 1-5KHZ .400" ID 1.0" OD TRIAX FISCHER CONNECTOR	RDP1.04/2K			
ASDP31/700HZ	REFLECTION SPOT PROBE TOP MOUNT 700HZ 80KHZ TRIAX FISCHER CONNECTOR	•			
ATMHR.800/700HZ-3.5L	REFLECTION PROBE 500HZ-2KHZ				
ARP-1.4085-200H	REFLECTION RING PROBE .85" I.D. 1.40" O.D. TRIAX CONNECTOR 100Hz-500Hz. REFERENCE STANDARD NDT3176-X 737 PT 6 57-10-59	RDP1.4085-200H			
ARP834-2K	REFLECTION RING PROBE, .340°Ø ID .800°Ø OD TRIAX FISCHER CONNECTOR 900Hz -5KHz.	RDP.834/2K			
ARP8-1K	REFLECTION RING PROBE, .400"Ø ID .800"Ø OD TRIAX FISCHER CONNECTOR 1KHz -20KHz.	RDP.8-1K			
AF-4127/100H	REFLECTION RING PROBE, 1.0" O.D., .545" I.D.,	RDP1.0-100H-6			
ASDP440	REFLECTION SPOT PROBE .440° OD TOP MOUNT TRIAX FISCHER 400HZ-60KHZ	9213552			
ASDP6-500HZ	REFLECTION SPOT PROBE 500HZ -5KHZ .600" OD 1.80" HEIGHT TOP MOUNTED TRIAX FISCHER CONNECTOR	SDP.6-500H			
AF-5099	REFLECTION SURFACE PROBE STRAIGHT SHEILDED 3.0" LONG .125" OD SHAFT TRIAX FISCHER CONNECTOR 25KHZ-100KHZ	•			
AF-4142/TF	RIGHT ANGLE BRIDGE SPOT PROBE .300"Ø 1KHz-100KHz, TRIAX FISCHER CONNECTOR	SB.3-1-100K			
AXPN-93-5/TL	RIGHT ANGLE SURFACE PROBE90 DEG 0.3" DROP .072" DIA TUBING 7 PIN LEMO CONNECTOR 50-500KHZ 5.0" LONG	MM7L903-50	9403445	U8629698	
APN-903-10/2M	SURFACE PROBE 1-3MHZ	MP9003-100/2M			
ATPN-45-6/2MHZ	RIGID SURFACE PROBE, 45°, .500° DROP 6.0° LONG TRIAX FISCHER CONNECTOR, 1-3MHZ.	TPEN-45-6/2M			
APN-903-5/2M	SURFACE PROBE 1-3MHZ	PEN903-50500-2M			
APN-97.5-5/2M	SURFACE PROBE 1-3MHZ	PEN97.5-5 500K-2M			
ATPN-92-6B	RIGID SURFACE PROBE, 90° DEGREES .200" DROP BENT, 50-500KHZ, TRIAX FISCHER CONNECTOR, 6.0" LONG. RMTF902-25-60B	RMTF902-25-60B	TPEN92-6B	D0815E1015-2077	VM229-1/4 x 6
AF-5129	RIGID SURFACE PROBE .118" Ø DIAMETER TUBING, 20" DEGREES, 1.0" DROP 500KHz-1MHz WITH TRIAX FISCHER CONNECTOR.	KAS-34H-132.44.1			
APN-2/2MHZ	SURFACE PROBE 1-3MHZ 2.0" LONG MICRODOT CONNECTOR				
APN-3/2M	SURFACE PROBE 1-3MHZ 3.0" LONG MICRODOT CONNECTOR	102P3			
APN-925-6/2MHZ	SURFACE PROBE 1-3MHZ 90 DEG .250" DROP 6.0" LONG MICRODOT CONNECTOR	•			
APN-92-4B/2M	SURFACE PROBE 1-3MHZ, BENT 90 DEG .200" DROP 4.0" LONG MICRODOT	MP902-40B			
APN-4/200K-1M	SURFACE PROBE 200KHZ-1MHZ	MP-40-1-3M			
APN-92-6/1MHZ	SURFACE PROBE 200KHZ-1MHZ	MP-902-60			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
APNU-937-3	SURFACE PROBE 3/8" DROP 3"OAL MICRODOT, UNSHIELDED, 50-500KHZ				
APN-453-5	SURFACE PROBE 45 DEG .300" DROP 5.0" LONG MICRODOT CONNECTOR 50-500KHZ	MP453-50			
ATPN-925-6/200K	RIGID SURFACE PROBE, TRIAX FISCHER CONNECTOR, 500KHz-1MHz, 6.0" LONG 1/4" DROP				
APN-45-4.5	SURFACE PROBE 45 DEG .500" DROP 4.5" LONG MICRODOT CONNECTOR 50-500KHZ				
APN-45-5/6MHz	SURFACE PROBE 45 DEG .500" DROP6 MHZ 5.0" LONG MICRODOT CONNECTOR				
APN475-4.5	SURFACE PROBE 45 DEG .75" DROP 4.5" LONG MICRODOT CONNECTOR 50-500KHZ				
APN-475-4.5/L500K	SURFACE PROBE 45 DEG .750" DROP 4.5" LONG LOCATOR 500KHZ ( 47UH) MICRODOT CONNECTOR	205P4F			
APN-457-6/500K	SURFACE PROBE 45", .750 " DROP 6.0" LONG MICRODOT CONNECTOR, 50-500KHz	MP457-60			
APN-45-4/500K	SURFACE PROBE SOOKHZ	MP455-40-200K-1M			
APN-925-4B/L-500K	SURFACE PROBE SOOKHZ BENT				
APN-92-5B/500K	SURFACE PROBE SOOKHZ, BENT	MP902-50B/500K			
ATPNU-91-5B/2M	RIGID UNSHIELED SURFACE PROBE, 90° 100° DROP 5.0° LONG BENT, TRIAX FISCHER CONNECTOR 1-3 MHz	TPENU91-5B/2M			
APN-93-5B/500K	SURFACE PROBE SOOKHZ, BENT	MP903-50B/L500K			
APN-457-4C	SURFACE PROBE 500KHZ, CURVED 45 DEG .500° DROP MICRODOT CONN				
APN-937-2/500K-1M	SURFACE PROBE 500KHZ-2MHZ				
APN-95-12	SURFACE PROBE 50-500 KHZ				
PN-925-7/2MHZ	RIGID SURFACE PROBE 90 DEG .250° DROP 7.0° LONG MICRODOT CONNNECTOR 1-3MHz .125° TIP				
APN-45-8	SURFACE PROBE 50-SOOKHZ	MP-455-80			
APN-9	SURFACE PROBE 50-500KHZ	MP-90			
APN-9010-4	SURFACE PROBE 50-500KHZ	MP902-40			
APN-902-5	SURFACE PROBE 50-500KHZ	MP902-5			
APN-902-6	SURFACE PROBE 50-500KHZ	PEN903-5, MP9003-6	MP902		
APN-903-12FX	SURFACE PROBE 50-500KHZ				
APN-903-15	SURFACE PROBE 50-500KHZ	MP9003-150			
APN-910-6	SURFACE PROBE 50-500KHZ	MP9010-100			
APN-91-6	SURFACE PROBE 50-500KHZ				
ATPN-10FX/2M	STRAIGHT FLEXIBLE SURFACE PROBE, 10.0" LONG, TRIAX FISCHER CONNECTOR, 1-3MHz.	TPENFLX-10/2M			
ATPN-10FX/1-6M	STRAIGHT FLEXIBLE SURFACE PROBE, 10.0" LONG, TRIAX FISCHER CONNECTOR, 1-6MHz.	BCMTF-100FX-1-6M			
ATPN-10FX	STRAIGHT FLEXIBLE SURFACE PROBE, 10.0" LONG, TRIAX FISCHER CONNECTOR, 50-500KHz.	BCMTF-100FX	TPENFLX-10		
ATPN-6FX/1-6M	STRAIGHT FLEXIBLE SURFACE PROBE, 6.0° LONG, TRIAX FISCHER CONNECTOR, 1-6MHz.	BCMTF-60FX-1-6M			
ATPN-6FX	STRAIGHT FLEXIBLE SURFACE PROBE, 6.0" LONG, TRIAX FISCHER CONNECTOR, 50-500KHz.	BCMTF-60FX	TPENFLX-6 50-500KHZ	DPTFLX-001	
ATPN-6B1.0"	SUFACE PROBE STRAIGHT 6.0" LONG 30 DEG BENT 1.0" FROM TIP ROUNDED 1/4"TRIAX FISCHER CONN 50-500KHZ				
ATPN-95-5FX/2M	SURFACE PROBE , TF, 1-3MHZ				
ATPN-9125-5B	SURFACE PROBE , TRIAX 50-SOOKHZ				
ASPN-95-5B/2M	RIGID SURFACE PROBE ABS SHIELDED 1-3MHz, 90° DEGREES, BENT 30° DEGREES, .500° DROP .098°(2.5mm)Ø DIAMETER TIP 5.0° LONG MICRODOT CONNECTOR	3551AS			
AXPN-95-4	RIGID SURFACE PROBE ABS, .072" TIP, 90°, .500" DROP 4.0" LONG 50-500KHZ, MICRODOT CONNECTOR.	MMP905-40			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATP-45-6	RIGID SURFACE PROBE ABSOLUTE SHIELDED 45" DEGREES .187"Ø TUBING 6.0" LONG WITH TRIAX FISCHER CONNECTOR 20-200KHz	200P6	611-054-077		
ATP-925-3	RIGID SURFACE PROBE ABSOLUTE SHIELDED 90° DEGREES .250° DROP, 0.187°Ø TUBING 3.0° LONG WITH TRIAX FISCHER CONNECTOR 20-200KHz.	300P23	611-074-007		
APN-92-5	SURFACE PROBE 50-500KHZ	MP902-50			
ATPN-3/2MHZ	SURFACE PROBE 1-3MHZ TRIAX FISCHER 3.0" LONG	MTF-30/1-6MHZ			
ASPN-95-5B/L500K	RIGID SURFACE PROBE SHIELDED 90" DEGREES, BENT 30" DEGREES .500" DROP .098" DIAMETER TIP 5.0" LONG MICRODOT CONNECTOR (LOCATOR 500KHZ ,47 UH)				
AP-4/400K-3MHZ	RIGID SURFACE PROBE STRAIGHT, 400KHz-3MHz BRIDGE, 4.0" LONG 5/32"Ø TIP WITH TRIAX FISCHER CONNECTOR.	379-004-360			
ATPNU-4/2M	SURFACE PROBE 1-3MHZ TRIAX UNSHIELDED	TPNU-4/2M	UMTF-40		
ATPNU-5/2MHZ	SURFACE PROBE 1-3MHZ TRIAX UNSHIELDED				
ATPN-95-8/3MHZ	SURFACE PROBE 350KHz-3MHz ABS SHIELDED 90 DEGREES .125" DIAMETER TUBING, 8.0" LONG. TRIAX FISCHER CONNECTOR	310P18			
APN-925-10	SURFACE PROBE 50-500KHZ	PEN925-10			
ATPN-925-7FX/.187	SURFACE PROBE 50-100KHZ , TRIAX, 90", .187Ø COPPER SHAFT X .25" DROP, 7" LONG				
ATPN90-2	SURFACE PROBE 50-500KHz .125" TIP SHIELDED TRIAX FISCHER CONNECTOR 90 DEGREES 1.0" DROP				
ATPN910-5	SURFACE PROBE 90 DEG 1.0" DROP 5.0" LONG 50-500KHZ TRIAX FISCHER CONNECTOR				a
ATPN-925-6/2M	SURFACE PROBE 90 DEG .25" DROP 6.0 INCH LONG 1-3 MHZ TF CONNECTOR				
ATPN-975-4/2M	SURFACE PROBE 90 DEGREE .750" DROP 4" LONG. 1-3 MHz TRIAX FISCHER CONNECTOR.	TPEN-975-4/2M			
APN-92-6	SURFACE PROBE 50-500KHZ	MP-902-60			
ATPN-95-8C	SURFACE PROBE CURVED TRIAX 50-500khz 8.0inch long	VM202AF-8			
ATPN-4/.062	SURFACE PROBE STAIGHT 50-500KHZ, .062" DIA TIP, 4.0" LONG TRIAX FISCHER CONNECTOR				
ASTPN-4.5/2-10M	RIGID SURFACE PROBE,ABS. 2-10MHz, .092"Ø TIP O.D., STRAIGHT 4.5 " LONG WITH A TRIAX FISCHER (4-5 UH)				
ASTPN-4.5	RIGID SURFACE PROBE,ABS. 50-500KHz, . 092"Ø TIP O.D., STRAIGHT 4.5 " LONG WITH A TRIAX FISCHER	MYTF-45	D0815E1015-2061		
ATPN-925-4.5/500KHZ	SURFACE PROBE, ABSOLUTE SHIELED 90 DEG .250" DROP 4.5" LONG TRIAX FISCHER SOOKHZ-1MHZ				
ARP385/.720	RING PROBE FOR APB-3302 .385" ID .720"OD REFLECTION TRIAXFISCHER CONNECTOR 500HZ -5KHZ				
ARP-1.0-500H-3	RING PROBE REFLECTION .425" ID 1.0" OD 500 HZ-10KHZ TRIAX FISCHER CONNECTOR.	RDP1.0-500H-3			
ARP-1.50/2.0-100HZ	RING PROBE REFLECTION 2.0" OD 1.50" ID 100 HZ-1KHZ TRIAX FISCHER CONNECTOR	RDP2.0-1.50/100H			
ARP96/1.45-500HZ	RING PROBE REFLECTION 1.45" OD .960" ID 500HZ -3KHZ TRIAX FISCHER CONNECTOR	RDP1.95-960/500H			
ARP552/1.0	RING PROBE, REFLECTION, 100HZ-5KHZ, .552ID TRIAX FISCHER CONNECTOR	702P14A			
ARP197/.750	RING PROBE, REFLECTION, 100HZ-5KHZ, .197ID TRIAX FISCHER CONNECTOR	702P05A			
ARP394/.850	RING PROBE, REFLECTION, 100HZ-5KHZ, .394ID	702P10A			
ARP512/1.0	RING PROBE, REFLECTION, 100HZ-5KHZ, .512ID TRIAX CONNECTOR	702P13A			
ARP32/.75-100KHZ	RING PROBE, REFLECTION, 10KHZ -200KHZTRIAX FISCHER CONNECTOR				
ARP330750	RING PROBE, REFLECTION, 1-10KHZ TRIAX FISCHER CONNECTOR, .330" INSIDE DIAMETER, .750" OUTSIDE DIAMETER. B777-200/300 PART 6 57-20-03 PAGE 1				
ARP65-5K	RING PROBE, REFLECTION, 1-5KHZ TRIAX CONN	RDP.65-5K			
ARP75-5K	RING PROBE, REFLECTION, 1-5KHZ TRIAX FISHER CONNECTOR	RDP.75-5K			
ARP45/.700-500HZ	RING PROBE, REFLECTION, 1KHZ .45ID, .7000D 1.0"H				
ARP65/1.1-200HZ	RING PROBE, REFLECTION, 1KHZ .65ID, 1.10D 1.0"H				
ARP4/1.0	RING PROBE, REFLECTION, 200 HZ-10 KHZ 400" ID 1.0" OD 1.2" HEIGHT TRIAX FISCHER CONNECTOR	RR0110-5	RDP1.0-100H-5		

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARP4/200KHZ	RING PROBE, REFLECTION, 200-300HZ				
ARP4/.95-200HZ	RING PROBE, REFLECTION, 200HZ TRIAXFISCHER CONNECTOR	DP-425/950-R			
ARP45/.700-300HZ-3KHZ	RING PROBE, REFLECTION, 300HZ - 300HZ-3KHZ, ID. 450, OD .700 1.1H				
ARP4/1.1-300H	RING PROBE, REFLECTION, 300HZ .400" ID 1.1" OD TRIAX FISCHER CONNECTOR	SPO-2030			
ARP440-1.0	RING PROBE, REFLECTION, 300HZ-1KHZ .440" ID 1.0" OD TRIAX 1.77" HEIGHT, FISCHER CONNECTOR				
ARP7-2K-5-4F	RING PROBE, REFLECTION, 500HZ-2KHZ 4 PIN FISCHER CONNECTOR	RDP.7-2K-4F			
ARP440810	RING PROBE, REFLECTION, 500HZ-5KHZ.440°ID .810° OD TRIAX FISCHER CONNECTOR				
ARP54/1.0-100HZ	RING PROBE, REFLECTION, 50HZ-3KHZTRIAX FISHER CONNECTOR	RDP1.0-100H-6			
ARP310/.750	RING PROBE, REFLECTION, 70HZ-80KHZ TRIAX FISHER CONNECTOR				
ARP32/.75-1KHZ	RING PROBE, REFLECTION, 100HZ -5KHZTRIAX FISCHER CONNECTOR				
AUR-12.5MSS/50MWL	ROHMAN STAINLESS STEEL ROTATING SCANNER PROBE 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ, 12.5mm DIAMETER HEAD 50mm WORKING LENGTH	RS12-5-50			
AUR-6.4MSS/35MWL	ROHMANN MINI STAINLESS STEEL ROTARY PROBE 100KHz-2MHz. 6.4MM DIA. HEAD 35MM WORKING LENGTH, 4 PIN FISHER CONNECTOR	RSM-6.4-35			
AUR-11.3MSS/50MWL	ROHMANN STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR, 11.35mm DIAMETER HEAD 50 mm WORKING LENGTH	RSMV11-3-50			
AUR-9.7MSS/50M	ROHMANN STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR, 9.7mm DIAMETER HEAD 50 mm WORKING LENGTH	RSMVS9-7-50			
AUR-8.0M/SE	ROTAING SCANNER PROBE SPLIT END8.0M-9.0M 4 PIN FISCHER CONNECTOR 51MM WORKING LENGTH 100KHZ-2MHZ				
ARRX770/4.5WL	ROTARY ADJ PROBE .770° OD 4.5° WL 4 PIN STEP LEMO DIFF/REFL	NEC-3032	NEC-3032		
ARR.187SE/FB	ROTARY PROBE 4 PIN STEP LEMO 100KHZ-2MHZ, SPLIT END, FLAT BOTTOM HOLE (.187218)				
ARRY125156	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 1.3" WORKING LENGTH .125"156" SPREAD				
ARRY156187	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 1.3" WORKING LENGTH .156"187" SPREAD				
ARRY187218	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 1.3" WORKING LENGTH .187"218" SPREAD				
ARRY187250	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 1.3" WORKING LENGTH .187"250" SPREAD				
ARRY218250	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 1.3" WORKING LENGTH .218"250" SPREAD				
ARRY250281	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 2.0" WORKING LENGTH .250"281" SPREAD				
ARRY281312	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 2.0" WORKING LENGTH -281"312" SPREAD				
ARRY312375	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 2.0" WORKING LENGTH .312"375" SPREAD				
ARRY375437	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 2.0" WORKING LENGTH .375"437" SPREAD				
ARRY437500	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KH2-2MHz, 2.0" WORKING LENGTH .437"500" SPREAD				
ARRY500562	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 2.0" WORKING LENGTH .500"562" SPREAD				
ARRY500625	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 2.0" WORKING LENGTH .500"625" SPREAD				
ARRY562625	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 2.0" WORKING LENGTH .562"625" SPREAD				
ARRY625687	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 2.0" WORKING LENGTH .625"687" SPREAD				
ARRY625750	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 2.0" WORKING LENGTH .625"750" SPREAD				
ARRY687750	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 2.0" WORKING LENGTH .687"750" SPREAD				
ARRY750875	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KH2-2MHz, 2.0" WORKING LENGTH .750"875" SPREAD				
ARRY875-1.00	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KH2-2MHz, 2.0" WORKING LENGTH .875"-1.0" SPREAD				
ARRY875-1.0/4.5WL	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 4.5" WORKING LENGTH .875"-1.0"	RRY.875-1.0/4.5WL			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARRY-1.0-1.125/4.5WL	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 4.5'" WORKING LENGTH 1.0"-1.125"	RRY1.0-1.125/4.5WL			
ARRY687750/6WL	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 6.0" WORKING LENGTH .687"750" SPREAD				
ARRX936-1.0	ROTARY ADJ PROBE .936'-1.0" 2.0"WL 4 PIN STEP LEMO 100 KHZ-2MHZ	TEK-3038			
ARRX850/4.5WL	ROTARY ADJ PROBE .850" OD 4.5 WL 4 PIN STEP LEMO DIFF/REFL 50-200KHZ	NEC-3014-UX	NEC-3014-UX		
ARRX-1.10/4.5WL	ROTARY ADJ PROBE 1.10° OD 4.5° WL 4 PIN STEP LEMO DIFF/REFL 50-200KHZ	NEC-3033	NEC-3033		
ARR937-1.00/1.5WL	ROTARY BOLT HOLE PROBE SPLIT END .937"-1.00", 1.5" WORKING LENGTH 200KHZ-1MHZ. FOR RA SCANNER, 4 PIN STEP LEMO				
AURCS100187/70MMWL	ROTARY COUNTER SINK PROBE 100 DEGREES 100-2MHz WITH 4 PIN FISCHER CONNECTOR 3/16*** OD TIP 70 mm WORKING LENGTH		CSM VM103C	CSM-100-12	
AURCS100-4.8-8MM/50M	ROTARY COUNTER SINK PROBE 100 DEGREES 100-2MHz WITH 4 PIN FISCHER CONNECTOR 4.8mm-8.0mm COUNTERSINK DIAMETER 50mm WORKING LENGTH				
AURCS100-7.5-9.5MM/50M	ROTARY COUNTER SINK PROBE 100 DEGREES 100-2MHz WITH 4 PIN FISCHER CONNECTOR 7.5mm-9.5mm COUNTERSINK DIAMETER 50mm WORKING LENGTH				
AURCS100250/70MMWL	ROTARY COUNTER SINK PROBE 100 DEGREES 100khz -2MHz WITH 4 PIN FISCHER CONNECTOR 1/4" OD TIP 70mm WORKING LENGTH	CSM VM103C	CSM-100-16		
AURCS100218/70MMWL	ROTARY COUNTER SINK PROBE 100 DEGREES 100khz-2MHz WITH 4 PIN FISCHER CONNECTOR 7/32" OD TIP 70mm WORKING LENGTH	CSM VM103C			
AURCS100156/70MMWL	ROTARY COUNTER SINK PROBE 100 DEGREES, 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR 5/32* OD TIP 70mm WORKING LENGTH		CSM VM103C		
ARRCS100156SS	ROTARY COUNTERSINK STAINLESS STEEL 100 DEGREES, 4.0mm(.156") DIAMETER 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ (RA SCANNER) 50.8mm/2.0") WORKING LENGTH	CSRA100-10/SS			
AURFB-11.1M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE 1.5"WL 4 PIN FISCHER 100KHZ-2MHZ				
AURFB-10.7M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 10.7mm, 2.0"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFB-11.4M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 11.4mm 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFB-11.8M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 11.8mm 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFB-12.2M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 12.2mm 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFB-13.1M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 13.1mm 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
ARUFB-13.5MSS/2WL	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 13.5mm 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFB-13.5MSS/2.0WL	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 13.5mm 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFB-13.8M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 13.8mm 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFB-3.5M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 3.5mm 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ- 2MHZ				
AURFB-5.8M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 5.8mm 1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFB-9.4M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 9.4mm, 2.0"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFB-9.8M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE, 9.8mm, 2.0"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFB-12.6M/SS	ROTARY FLAT BOTTOM STAINLESS STEEL PROBE,12.6mm 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ				
AURFX.187/4WL/.5	ROTARY FLEX SHAFT PROBE 4WL.5" TIP LONG 100K-2MHZ ,4 PIN FISCHER CONNECTOR				
AURFX.156-6	ROTARY FLEX SHAFT PROBE 6.0" LONG 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ 1.850" PROBE LENGTH (TIP TO SPRING), SPRING LENGTH 4.150", CONNECTION LENGTH (SPRING TO END) IS 1.4" LONG	UFLX.156-6			
AURFX.250-6	ROTARY FLEX SHAFT PROBE 6.0" LONG 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ 1.850" PROBE LENGTH (TIP TO SPRING), SPRING LENGTH 4.150", CONNECTION LENGTH (SPRING TO END) IS 1.4" LONG	UFLX.250-6			
AURFX.187-6	ROTARY FLEX SHAFT PROBE 6.0" LONG4 PIN FISCHER CONNECTOR 100KHZ-2MHz, PROBE LENGTH = 1.850"(TIP TO SPRING), SPRING LENGTH = 4.150", CONNECTION LENGTH (SPRING TO END) IS 1.4" LONG.	UFLX.187-6WL			
AURFX.250-8	ROTARY FLEX SHAFT PROBE 8.0" LONG 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ 1.850" PROBE LENGTH (TIP TO SPRING), SPRING LENGTH 6.150", CONNECTION LENGTH (SPRING TO END) IS 1.4" LONG AND 1.0" SLEEVE FOR 8" PROBE	UFLX.250-8			
AURFX.187-8	ROTARY FLEX SHAFT PROBE 8.0" LONG 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ 1.850" PROBE LENGTH (TIP TO SPRING), SPRING LENGTH 6.150", CONNECTION LENGTH (SPRING TO END) IS 1.4" LONG AND 1.0" SLEEVE FOR 8" PROBE	UFLX.187-8WL			
AF-5029/.875	ROTARY HIGH FREQUENCY REFLECTION PROBE .875" 25-500KHz 4 PIN FISCHER CONNECTOR	TEK-3021			
ARR-3.2M/SE	ROTARY HOLE PROBE, Ø 3.2MM-3.9MM, 1.1WL FOR RA 2000				
ARR-3.9M/SE	ROTARY HOLE PROBE, Ø 3.9MM-4.7MM, 1.1WL FOR RA 2000				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARR-4.7M/SE	ROTARY HOLE PROBE, Ø 4.7MM-5.5MM, 1.1WL FOR RA 2000	9217153			
ARRY187218/3WL	ROTARY PROBE .187"218" DIAMETER, 100KHZ-2MHZ FOR RA SCANNER 3.0" WORKING LENGTH				
AURX770/4.5WL	ROTARY PROBE .770" OD 4.5" WL 4 PIN FISCHER DIFF/REFL	NEC-3032	NEC-3032		
AURX850/4.5WL	ROTARY PROBE .850" OD 4.5 WL 4 PIN FISCHER DIFF/REFL 50-200KHZ	NEC-3014-UX	NEC-3014-UX		
AURX-1.10/4.5WL	ROTARY PROBE 1.10" OD 4.5" WL 4 PIN FISCHER DIFF/REFL 50-200KHZ	NEC-3033	NEC-3033		
ARRY250312	ROTARY PROBE 100KHZ-2MHZ FOR RA 2000 SCANNER 4 PIN STEP LEMO CONNECTOR 2.0" WORKING LENGTH .250"312 SPREAD				
ARRY156187/3WL	ROTARY PROBE 100KHZ-2MHZ FOR RA SCANNER 3.0" WORKING LENGTH				
ARRY218250/3WL	ROTARY PROBE 100KHZ-2MHZ FOR RA SCANNER 3.0" WORKING LENGTH				
ARRY250312/3WL	ROTARY PROBE 100KHZ-2MHZ FOR RA SCANNER 3.0" WORKING LENGTH				
ARRY312375/3WL	ROTARY PROBE 100KHZ-2MHZ FOR RA SCANNER 3.0" WORKING LENGTH				
ARRY375437/3WL	ROTARY PROBE 100KHZ-2MHZ FOR RA SCANNER 3.0" WORKING LENGTH				
ARRY437500/3WL	ROTARY PROBE 100KHZ-2MHZ FOR RA SCANNER 3.0" WORKING LENGTH				
ARRY500625/3WL	ROTARY PROBE 100KHZ-2MHZ FOR RA SCANNER 3.0" WORKING LENGTH				
ARRY625750/3WL	ROTARY PROBE 100KHZ-2MHZ FOR RA SCANNER 3.0" WORKING LENGTH				
AURY500562/6WL	ROTARY PROBE 100KHZ-2MHZ, 6.0"WL4PIN FISCHER CONNECTOR				
AURY562625/6WL	ROTARY PROBE 100KHZ-2MHZ, 6.0"WL4PIN FISCHER CONNECTOR				
AURY625687/6WL	ROTARY PROBE 100KHZ-2MHZ, 6.0"WL4PIN FISCHER CONNECTOR				
AURY687750/6WL	ROTARY PROBE 100KHZ-2MHZ, 6.0"WL4PIN FISCHER CONNECTOR				
AURY750875/6WL	ROTARY PROBE 100KHZ-2MHZ, 6.0"WL4PIN FISCHER CONNECTOR				
AURY875937/6WL	ROTARY PROBE 100KHZ-2MHZ, 6.0"WL4PIN FISCHER CONNECTOR				
AURY937-1.0/6WL	ROTARY PROBE 100KHZ-2MHZ, 6.0"WL4PIN FISCHER CONNECTOR				
AF-5081	ROTARY PROBE 25KHZ-500KHZ REFLECTION				
AF-5081-G	ROTARY PROBE 25KHZ-500KHZ REFLECTION, GUIDE				
ARR-1.392	ROTARY PROBE 4 PIN STEP LEMO (STAVELY MINI MITE) 2.0" WORKING LENGTH 100KHZ-2MHZ				
ARR-1.662	ROTARY PROBE 4 PIN STEP LEMO (STAVELY MINI MITE) 2.0" WORKING LENGTH 100KHZ-2MHZ				
ARR-1.445/3.0WL	ROTARY PROBE 4 PIN STEP LEMO (STAVELY MINI MITE) 3.0" WORKING LENGTH 100KHZ-2MHZ				
ARR-1.392/4.5WL	ROTARY PROBE 4 PIN STEP LEMO (STAVELY MINI MITE) 4.5" WORKING LENGTH 100KHZ-2MHZ				
ARR-1.662/4.5WL	ROTARY PROBE 4 PIN STEP LEMO (STAVELY MINI MITE) 4.5" WORKING LENGTH 100KHZ-2MHZ				a
AURFX171/8WL	ROTARY PROBE FLEXIBLE 8.0" WL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	BEMFX-11/8WL			
ARR.125SE/1.3WL	ROTARY PROBE FOR NORTEC/RECHII RA SCANNER 100KHZ -2MHZ, 1.3"WL				
ARR.125SE/2.0WL	ROTARY PROBE FOR NORTEC/RECHII RA SCANNER 100KHZ -2MHZ, 2.0"WL				
ARR.531	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO 17/32" OD3.0" OVERALL LENGTH				
ARR093SE/1.5WL	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO, EXPANDABLE FROM .093"125" 1.5" WORKING LENGTH				
AURF218	ROTARY PROBE SHIELDED 4 PIN FISCHER CONNECTOR 100 K-2MHZ	BPUF-14			
AURF187	ROTARY PROBE SHIELDED 4 PIN FISCHER CONNECTOR 100K-2MHZ	BPUF-12			
AUR-3.9MSS/140MWL	ROTARY PROBE STAINLESS STEEL 3.9MM DIA 140MM WORKING LENGTH 4 PIN FISCHER CONNECTOR( MINI ROHMANN)	RSM3-9-50 140MM			

# AeroFab NDT LLC

AnimalInterfact or any state of the sector of t	PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
sh. JipinIndex (an Hold Jipin Park and Part Distance Data Jipin Park and Park	ARR.437SS/3WL					
Any-AppendixMain for the Mark of the Mark of	APS5R.312/2.0WL	ROTARY PROBE, STAINLESS, 200KHZ-1MHZ REFLECTION	RD-312			
an. Joint And and and and any	ARR375/3WL	ROTARY RECHII PROBE .375" 3.0" WL4 PIN STEP LEMO 100KHZ-2MHZ				
Any and any and any	ARR375/4WL	ROTARY RECHII PROBE .375" 4.0" WL 4 PIN STEP LEMO 100KHZ-2MHZ				
NA. 5727ANUM SCANAL FREEL 1 WASHING LING AN UNDERGREGADE CONNECTION AND AND AND AND AND AND AND AND AND AN	ARR500/3WL	ROTARY RECHII PROBE .500" 3.0" WL 4 PIN STEP LEMO 100KHZ-2MHZ				
HARMARERELAY ANALYS THE LANDREG LINER LEADED AND A PHY IGON COMMUNE AND A DAY THE AGON LINES INII<	ARR500/4WL	ROTARY RECHII PROBE .500" 4.0" WL 4 PIN STEP LEMO 100KHZ-2MHZ				
And And And And And And And And And And And And And	AUR375/2WL	ROTARY SCANNER PROBE 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
NumberNumbe	AUR.218SS/1.5WL	ROTARY STAINLESS STEEL 1.5 WORKING LENGTH 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR				
MI-17.2 M.M.PixTMS SAMER PROFE CONCEPTS LOW YOUNDS LIBERTPixTMSPixTM	AUR095	ROTATING SCANNER BOLT HOLE PROBE 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .095", 1.3" WORKING LENGTH				
NumberNumbe	AUR156/2.0WL	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH	619P010F051			
NAMEReferenceR	AUR171/2.0WL	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH				
NAMEPRIVE SAME PROFE SAME DATIONS CAME, STARLESS STEL 4 PM FSCHER CONNECTION BOOM NORMER LINGTHPinePinePineNUM 22 7555 COMMSTATUS CAMER PROFE SAME DATION CONNECTION ISON CAME, STALLESS STEL 4 PM FSCHER CONNECTION ISON CAME, A PM FSCHER CONNECTION ISON	AUR218/2.0WL	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH				
NUM_22 7MS550WC NUM_22 7MS1NG SAMRAF PROFE STARLESS THE LAPPA FSGRE CONNECTION LODGE 2MGL 21/2 mm DMATTER HGD SDM WORKING LINGTHNUM22 7MS1Num22 7M	AUR234/2.0WL	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH				
Numerica contractionName: Contraction <th< td=""><td>AUR-3.9M/35MWL</td><td>ROTATING SCANNER PROBE 3.9MM DIA 100KHZ-2MHZ , STAINLESS STEEL4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH</td><td></td><td></td><td></td><td></td></th<>	AUR-3.9M/35MWL	ROTATING SCANNER PROBE 3.9MM DIA 100KHZ-2MHZ , STAINLESS STEEL4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH				
NUMBERCONNETTORCONNETTORCONNETTORCONNETTORCONNETTORConnettorNUM-A2137CONNETTORCONNETTORCONNETTORSCANNER PROBE 107/MC217/9 (PEDD and GAMME) 25 / WORKING LENDEH. 1008/P2/MC2 HILLED, STAILES STEL, A PIN FORSIPPO 77065SIPPO 7706	AUR-12.7MSS/50MWL	ROTATING SCANNER PROBE STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ, 12.7mm DIAMETER HEAD 50M WORKING LENGTH	RSMV12-7-50			
NUMBERCONNECTOR <th< td=""><td>AUR406SS/2.5WL</td><td></td><td>615P026F065</td><td></td><td></td><td></td></th<>	AUR406SS/2.5WL		615P026F065			
NURSIDD-194         ORTING SCANNER PROBE 100 DIGRESS CUNTERSIN 10069-2MIC.4 PN PSOHED (190 194, counterini: 100 dgress, 0.3748 0.381)         Image: Counter State of Cou	AUR421SS/2.5WL		615P027F065			
NUMBER BarneryImageImageImageImageImageImageAUNES 100-1201ROTING SCANNER PROBE LOD ORGERES COUNTERSINE LODIE/22MEZ A PIN FISCHER (0.2159 2.23.) quontersine 100 degrees, 0.329 0.33 datametImage <td< td=""><td>AURCS100207</td><td>ROTATING SCANNER PROBE 100 DEG100KHZ-2MHZ 4 PIN FISCHER CONNECTOR (0.203-0.207, countersink: 100 degrees, 0.3748-0.3819 diameter)</td><td></td><td></td><td></td><td></td></td<>	AURCS100207	ROTATING SCANNER PROBE 100 DEG100KHZ-2MHZ 4 PIN FISCHER CONNECTOR (0.203-0.207, countersink: 100 degrees, 0.3748-0.3819 diameter)				
NURSID-21RITATING SCANNER PROBE 100 DEGREES COUNTERSINK 100/R-2-MPL SCHER 0.225-0.231, countersink: 100 degrees, 0.292-0.338 diamedRICHRICHRICHALIRSID-26RITATING SCANNER PROBE 100 DEGREES COUNTERSINK 100/R-2-MPL SCHER 0.250-0.2530, countersink: 100 degrees, 0.292-0.338RICHRICHRICHRICHALIRSID-26RITATING SCANNER PROBE 100 COUNTER SINK 100/R-2-MPL SCHER 0.2014 RCMRICH <t< td=""><td>AURCS100194</td><td></td><td></td><td></td><td></td><td>•</td></t<>	AURCS100194					•
AURS200-263       ROTATING SCANRER PROBE 100 DEGREES COUNTERSINK 100KH2-2MH2.4 PIN FISCHER CONNECTOR (0.2605-0.2630, countersink: 100 degrees, 0.00       Section       Sec	AURCS100223	ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ.4 PIN FISCHER (0.219-0.223, countersink: 100 degrees, 0.3748-0.3819)				
NUMESION 2004 alimeteryImage of the problemImage of the problem </td <td>AURCS100231</td> <td>ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ4 PIN FISCHER (0.225-0.231, countersink: 100 degrees, 0.329-0.338 diameter)</td> <td></td> <td></td> <td></td> <td></td>	AURCS100231	ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ4 PIN FISCHER (0.225-0.231, countersink: 100 degrees, 0.329-0.338 diameter)				
AURCS100-11.1M       ACTATING SCANNER PROBE 100° COUNTER SINK 100KH2-2MHZ       AURCS100-11.2M       AURCS100-12M       AURCS10M       A	AURCS100263					•
AURCS100-11.SM       ROTATING SCANNER PROBE 100' COUNTER SINK 100KH2-2MHZ       .	AURCS100-10.3M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-11.9M       ROTATING SCANNER PROBE 100*COUNTER SINK 100KH2-2MHZ       AURCS100-13.5M       Contained Scanner PROBE 100*COUNTER SINK 100KH2-2MHZ       Scanner PROBE 100*COUN	AURCS100-11.1M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				•
AURCS 100-13.5MROTATING SCANNER PROBE 100° COUNTER SINK 100KH2-2MHZSolutionSolutio	AURCS100-11.5M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
Aurcs100-14.0M       Control Scanner ProBe 100° COUNTER SINK 100KHZ-2MHZ       Control Scanner ProBe 100° COUNTER SINK 10	AURCS100-11.9M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-14.3M       ROTATING SCANNER PROBE 100° COUNTER SINK 100KH2-2MHZ       S	AURCS100-13.5M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-14.6M       FORTATING SCANNER PROBE 100° COUNTER SINK 100KH2-2MHZ       Solone       So	AURCS100-14.0M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-15.1M       ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ       SIG       SIG       SIG       SIG       SIG         AURCS100-15.9M       ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ       SIG       SIG       SIG       SIG       SIG         AURCS100-16.3M       ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ       SIG	AURCS100-14.3M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS 100 - LS PM       FOAT TING SCANNER PROBE 100' COUNTER SINK 100KHZ-2MHZ       Solon - LA PM       Solon - LA PM <td< td=""><td>AURCS100-14.6M</td><td>ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ</td><td></td><td></td><td></td><td></td></td<>	AURCS100-14.6M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-16.3M         ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ         AURCS100-16.3M         Scannee	AURCS100-15.1M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-16.7M       ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ       Image: Comparison of the co	AURCS100-15.9M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-3.6M RTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ	AURCS100-16.3M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
	AURCS100-16.7M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-5.2M ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ	AURCS100-3.6M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
	AURCS100-5.2M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURCS100-5.7M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-6.7M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-7.9M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-8.3M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				•
AURCS100-8.7M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				•
AURCS100-9.5M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-9.9M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ				
AURCS100-3.9M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR. 3.9mm				
AURCS100-4.0M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR. 4.0mmØ				•
AURCS100-4.7M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR. 4.7 mm				
AURCS100-4.8M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR. 4.8mm				
AURCS100-5.5M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR. 5.5mm				
AURCS100-5.6M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR. 5.6mmØ	-			
AURCS100-6.3M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR. 6.3mm				
AURCS100-7.7M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR. 7.7 mmØ.	-			
AURCS100-9.3M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR. 9.3mm				•
AURCS100-4.1M/SS	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR STAINLESS STEEL PROBE				
AURCS100-4.8M/SS	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR STAINLESS STEEL PROBE				
AURCS100-5.5M/SS	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR STAINLESS STEEL PROBE				•
AURCS100-6.3M/SS	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR STAINLESS STEEL PROBE				
AURCS100-12.5M/50M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 12.5 mm DIAMETER HEAD 50 MM WORKING LENGHTH	RSK50/5/12/12.5/100			•
AURCS100-6.4M/50M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 6.4mm DIAMETER HEAD 50 MM WORKING LENGHTH	RSK50/5/12/6.4/100			
AURCS100-7.0M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 7.0MM DIAMETER HEAD 4 PIN FISCHER CONNECTOR				•
AUR313375/SE/4.5WL	ROTATING SCANNER PROBE 100K-2MHZ 4 PIN FISCHER				
AUR-6.7M	ROTATING SCANNER PROBE 100KHZ-2MHZ				
AURCS100-4M/SS	ROTATING SCANNER PROBE 100KHZ-2MHZ	CSU 100-4M			
AURCS100-5M/SS	ROTATING SCANNER PROBE 100KHZ-2MHZ	CSU 100-5M			
AUR171	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER				
AUR185	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER	BPD-12, VMED101185			
AUR687	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WL				
AUR156/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 1.5 INCH WORKING LENGTH	BPU-10			
AUR234/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 1.5 INCH WORKING LENGTH				
AUR156/6WL	ROTATING SCANNER PROBE 100KHZ-2MHZ 6.0" WL 4 PIN FISCHER CONNECTOR				
AURC100/6.3MM	ROTATING SCANNER PROBE 100KHZ-2MHZ CS 100 DEG 4 PIN FISCHER				
AURC100/5.5MM	ROTATING SCANNER PROBE 100KHZ-2MHZ CS 100DEG 4 PIN FISCHER				
AURC100/3.9MM	ROTATING SCANNER PROBE 100KHZ-2MHZ CS 100DEG 4 PIN FISCHER				

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR093SS/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ STAINLESS STEEL4 PIN FISCHER				EQUIVALENT
AUR250/6FX	ROTATING SCANNER PROBE 100KHZ-2MHZ , FLEXIBLE 4 PIN FISCHER CONNECTOR				
AUR062SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ , STAINLESS STEEL4 PIN FISCHER CONNECTOR . USED WITH 40A100 SCANNER	EMR.062SS			
AUR093SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ , STAINLESS STEEL4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER	EMR.093SS			
AUR175	ROTATING SCANNER PROBE 100KHZ-2MHZ 1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR				
AUR218SE	ROTATING SCANNER PROBE 100KHZ-2MHZ 2.0WL, SPLIT END 4 PIN FISCHER CONNECTOR				
AUR150	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER				
AUR473	ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER 2.0"WORKING LENGTH				
AUR187/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ 4PIN FISCHER CONNECTOR1.5 INCH WORKING LENGTH	BPD-12, VMED101187			
AURC100/7.9MM	ROTATING SCANNER PROBE 100KHZ-2MHZ CS 100 DEG 4 PIN FISCHER				
AUR225	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED	BPD-12, VMED101225			
AUR234	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED				
AUR245	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED	BPD-12, VMED101245			
AUR250/12WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED				
AUR270	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED	BPD-12, VMED101270			
AUR281	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED	URF.281			
AUR295	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED	BPD-12, VMED101295			
AUR310	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED	BPD-12, VMED101310			
AUR375437SE/2.0WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED				
AUR500	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED	URF.500			
AUR500/4WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED				
AUR656	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED	URF.656			
AUR718	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED				
AUR781	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED				
AUR787	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED				
AUR875	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED	URF.750			
AUR937	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED	URF.750			
AURCSF100156	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED				
AURCSF100187	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED				
AURCSF100250	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED				
AUR171/35MM	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 35mm WORKING LENGTH 4 PIN FISCHER				
AUR187/12WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER				
AUR3123755E	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER				
AUR375	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER	URF.375			
AUR437	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER	URF.437	BPU-28		
AUR-1.00	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER	URF1.00			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR218SE/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER CONNECTOR	BPD-12, VMED101187	9219980		
AUR593	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER CONNECTOR				•
AUR562	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER CONNECTOR WITH 2.0" WORKING LENGTH				
AUR562/2.0WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER CONNECTOR WITH 2.0" WORKING LENGTH	619P036			
AUR218	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4PIN FISCHER CONNECTOR				
AUR295/F	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 2"WL SOLID HEAD	BPD-12, VMED101295			
AUR310/F	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 2"WL SOLID HEAD	BPD-12, VMED101310			
AUR225/F	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 2"WL SOLID HEAD 4 PIN FISCHER	BPD-12, VMED101225			
AUR622/4.3L	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4.30WL, .ROHMAN MINI UNIT 4 PIN FISCHER CONNECTOR	RSMVS16-20			
AUR312/4.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4.5"WL 4 PIN FISCHER	SPO-53935-16			
AUR250SE/FB	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, FLAT BOTTOM HOLE	URF.250			
AUR218/6FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, FLEXIBLE 4 PIN FISCHER				
AUR281/6FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, FLEXIBLE 4 PIN FISCHER				
AUR187/6FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, FLEXIBLE SHAFT				
AUR312/6FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, FLEXIBLE SHAFT				
AUR375/6FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, FLEXIBLE SHAFT 4 PIN FISCHER				
AUR312SE	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END				
AUR750SE	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END				
AUR875/SE	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END	9231090			
AUR150SE	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END 4 PIN FISCHER				
AUR187SE/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH, EXPANDABLE FROM .250"281"	BPD-12, VMED101187	9216679		•
AUR375SE/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH, EXPANDABLE FROM .375"437"	619PO24F051			
AUR187SE/2.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END, .187218, 2.5WL				
ARR437SE/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END, 1.1" WORKING LENGTH, 4 PIN STEP LEMO, BOLT HOLE SIZE RANGE .437-500				
ARR500SE/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END, 1.1" WORKING LENGTH, 4 PIN STEP LEMO, BOLT HOLE SIZE RANGE.500"562"				
ARR562SE/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END, 1.1" WORKING LENGTH, 4 PIN STEP LEMO, BOLT HOLE SIZE RANGE.562"625"				
ARR625SE/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END, 1.1" WORKING LENGTH, 4 PIN STEP LEMO, BOLT HOLE SIZE RANGE.625"687"				
ARR687SE/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END, 1.1" WORKING LENGTH, 4 PIN STEP LEMO, BOLT HOLE SIZE RANGE-687"750"				
AUR500SE/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END, 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR	619P032F051			
AUR125SS/2.0WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR .125" DIAMETER, 2.0" WORKING LENGTH				
AUR250SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR, 250"Ø	OPXV4-74B119151-219	EMR.250SS	74B119151-219	
AUR1875SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR, .1875"Ø1.5" WORKING LENGTH	EMR.187SS	615P012F035		
AUR125SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER125"Ø	EMR.125SS	BPEM-8/SS/1.5WL(1/8)		
AUR156SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER156"Ø	EMR.156SS	615P010F035		
AUR187SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER187"Ø	EMR.187SS	615P012F035		
AUR218SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER218"Ø	EMR.218SS	615P014F035		

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR281SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER281"Ø	615P018F035	LOONALLIN		EQUIVALENT
AUR312SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER. 312"Ø	EMR.312SS			
AUR343SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER343"Ø	EMR.343SS			
AUR406SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER. 406"Ø	EMR.406SS			
AUR437SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER. 437"Ø				
AUR078SS/65MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 2.5WL	615P005F065	HR.078SS/2.5WL		
AUR-3.5MSS/50MMWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	RSM 3-5-50			
AUR-3.9MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER 3.9MM DIA,50MM WORKING LENGTH.	RSM3-9-50			
AUR156SS/20MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR	615P010F020			
AUR-10.7MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 10.7mm HEAD SIZE.				
AUR-11.9MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 11.9mm HEAD SIZE.				
AUR-12.3MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 12.3mm HEAD SIZE.				
AUR-13.1MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 13.1mm HEAD SIZE.				
AUR-13.5MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 13.5mm HEAD SIZE.				
AUR-14.0MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 14.0mm HEAD SIZE.				
AUR-15.5MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 15.5mm HEAD SIZE.	SEU-15.5-35			
AUR-3.8MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 3.8mm HEAD SIZE.	615P038M035			
AUR-4.4MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 4.4mm HEAD SIZE.				
AUR-4.8MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 4.8mm HEAD SIZE.	RSM 4-8-35			
AUR-9.9MSS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 35 mm WORKING LENGTH 9.9mm HEAD SIZE.				
AUR-10.3MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 50 mm WORKING LENGTH 10.3mm HEAD SIZE.				
AUR-11.9MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 50 mm WORKING LENGTH 11.9mm HEAD SIZE.				
AUR-13.49MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 50 mm WORKING LENGTH 13.49mm HEAD SIZE.				
AUR-3.57MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 50 mm WORKING LENGTH 3.57mm HEAD SIZE.				
AUR-3.97MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 50 mm WORKING LENGTH 3.97mm HEAD SIZE.				
AUR-4.37MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 50 mm WORKING LENGTH 4.37mm HEAD SIZE.				
AUR-4.76MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 50 mm WORKING LENGTH 4.76mm HEAD SIZE.				
AUR-5.16MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 50 mm WORKING LENGTH 5.16mm HEAD SIZE.				
AUR-5.5MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 50 mm WORKING LENGTH 5.5mm HEAD SIZE.				
AUR-3.5MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR SOmm WORKING LENGTH 3.50mmØ HEAD SIZE.	RSM3-5-50			
AUR-5.6MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 5.6mm HEAD SIZE.	RSM5-6-50			
AUR-5.7MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR SOmm WORKING LENGTH 5.7mm HEAD SIZE.				
AUR-6.1MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR. 6.1mm DIA, ,50MM WORKING LENGTH	RSM6-1-50			
AUR-7.94MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR. HEAD SIZE=7.94mm, PROBE WORKING LENGTH =50mm	621P020			
AUR-6.1MSS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR. 6.1mm	RSMF-ATR-6.1			
AUR-6.3MSS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR. 6.3mm	RSMF-ATR-6.3			

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR-6.5MSS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR. 6.5mm.	RSMF-ATR-6.5			
AUR140SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR	615P009F051			
AUR374SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR.				
AUR-1.125SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR.	615P072F035			
AUR090SS/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR125SS/51MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P008F051			
AUR154SS/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR172SS/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR187SS/0.75WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR187SS/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	BPU-12SS			
AUR187SS/20MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P012F020			
AUR196SS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR197SS/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR199SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	HR.1995			
AUR209SS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR215SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR218SS/20MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P014F020			
AUR243SS/0.75WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR244/SS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR246SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR250SS/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR250SS/20MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P016F020			
AUR265/SS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR281SS/20MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P018F020			
AUR296/SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P019F035			
AUR296SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	6150P19F051			
AUR296SS/51MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	6150P19F051			
AUR312SS/0.75WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR328SS/36MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P021F036			
AUR343SS/0.75WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR343SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P022F051			
AUR359SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P023F051			
AUR360SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P023F051			
AUR373SS/0.75WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR375/SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P024F035			
AUR375SS/0.75WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR375SS/20MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P024F020			
AUR375SS/4.0WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	BPEM-24-SS-4.0WL			
AUR390SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P025F051			
AUR421SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P027F051			
AUR434SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR437SS/0.75WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR437SS/20MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P028F020			
AUR437SS/3WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR468SS/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P030F051			
AUR500SS/20MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P032F020			
AUR656SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P042F035			
AUR671SS/65MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P043F065			
AUR687SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P044F035			
AUR703SS/65MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P045F065			
AUR718SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P046F035			
AUR734SS/65MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P047F065			
AUR753SS/65MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P049F065			
AUR875SS-1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR-1.01SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P065F035			
AUR-1.03SS/51MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P066F051			
AUR-1.04SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P067F035			
AUR-1.06SS/51MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P068F051			
AUR-1.07SS/52MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P069F052			
AUR-1.09SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P070F035			
AUR-1.0SS/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				
AUR-1.10SS/51MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	615P071F051			
AUR-11.9MSS/FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	FMRP-RUK-5-5.7			
AUR-12.3MSS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	RSM 12.3			
AUR-14.3MSS/FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	FMRP-RUK-5-5.7			
AUR-2.7MSS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	RSM 2.7			
AUR-3.5MSS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	RSM 3.5			
AUR-4.65MSS/FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	FMRP-RUK-5-5.7			
AUR-4.76MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.187"(4.76mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-5.7MSS/FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	FMRP-RUK-5-5.7			
AUR-6.1MSS/40M/FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	KD-1H-393.04.1			
AUR-6.2MM/SS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER				

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR-6.2MSS/17	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	KD1H1472			
AUR-6.2SS/35	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	RSM-35-6.2			•
AUR-6.4MSS/FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	FMRP-RUK-5-6.4			
AUR-6.5MSS/40M/FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	KD-1H-1393.06.1			
AUR-7.1MSS/FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	FMRP-RUK-5-5.7			
AUR-7.8MSS/FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	FMRP-RUK-5-5.7			
AUR-7.94MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ, 3125"(7.94mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-7.9MSS/FX	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	FMRP-RUK-5-5.7			
AUR-9.9MM/SS	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER	W20B5KAL			
AUR-11.1M/SE	ROTATING SCANNER PROBE 100KHZ-2MHZ, 11.1-12.1, SPLIT END, 4 PIN FISHER, 2.0WL	619P028			
AUR218/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN FISCHER, 1.5 WORKING LENGTH				
AUR250/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN FISCHER, 1.5 WORKING LENGTH				
AUR281/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN FISCHER, 1.5 WORKING LENGTH				a
AUR312/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN FISCHER, 1.5 WORKING LENGTH				
AUR375/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN FISCHER, 1.5 WORKING LENGTH				
AUR437/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN FISCHER, 1.5 WORKING LENGTH				
AUR500/1.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN FISCHER, 1.5 WORKING LENGTH				
AUR-10.3M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-11.1M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-11.5M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-11.9M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				a
AUR-3.6M/SE	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-4.0M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-4.1M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-4.4M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-5.6M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-7.9	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-7.9M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-8.3M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-8.7M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-9.5M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-9.9M	ROTATING SCANNER PROBE 100KHZ-2MHZ, 4.0-5.0, SPLIT END, 4 PIN FISHER, 2.0WL				
AUR-9.5M/SE	ROTATING SCANNER PROBE 100KHZ-2MHZ, 9.5M-10.5M, SPLIT END, 4 PIN FISCHER CONNECTOR , 51MM WORKING LENGTH				
AUR500SE/1.1WL	ROTATING SCANNER PROBE 100KHZ-2MHZ, SPLIT END (.500"562"), 1.1" WORKING LENGTH 4 PIN FISCHER CONNECTOR.				
AUR453SS/2.5WL	ROTATING SCANNER PROBE 11.5MM(.453")Ø HEAD and 65MM(2.5") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P029F065			
AUR484SS/2.5WL	ROTATING SCANNER PROBE 12.30MM(.484")Ø HEAD and 65MM(2.5") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P031F065			

# AeroFab NDT LLC September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR51555/1.5WL	ROTATING SCANNER PROBE 13.08MM(.515")Ø HEAD and 35MM(1.378") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P033F035			
AUR515SS/35MWL	CONNECTOR ROTATING SCANNER PROBE 13.08MM(.515")Ø HEAD and 35MM(1.378") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P033F035			
AUR515SS/2.5WL	ROTATING SCANNER PROBE 13.08MM(.515")Ø HEAD and 65MM(2.5") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P033F065			
AUR531SS/35MWL	ROTATING SCANNER PROBE 13.487MM(.531")Ø HEAD and 35MM(1.378") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P034F035			
AUR547SS/35MWL	ROTATING SCANNER PROBE 13.89MM(.547")Ø HEAD and 35MM(1.378") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P035F035			
AUR281312/SE/4.5WL	ROTATING SCANNER PROBE 1-3MHZ 4 PIN FISCHER				
UR281312/SE/7WL	ROTATING SCANNER PROBE 1-3MHZ 4 PIN FISCHER				
UR21855/65MWL	ROTATING SCANNER PROBE 14MM HEAD and 65MM WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P014F065			
UR265SS/65MWL	ROTATING SCANNER PROBE 17MM HEAD and 65MM WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P017F065			
UR281/SS/35MWL	ROTATING SCANNER PROBE 18MM HEAD and 35MM WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P018F035			
AUR281SS/65MWL	ROTATING SCANNER PROBE 18MM HEAD and 65MM WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P018F065			
UR32855/65MWL	ROTATING SCANNER PROBE 21MM HEAD and 65MM WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P021F065			
AUR343SS/65MWL	ROTATING SCANNER PROBE 22MM HEAD and 65MM WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P022F065			
AUR343SS/2.5WL	ROTATING SCANNER PROBE 22MM(.343")Ø HEAD and 65MM(2.5") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR	615P022F065			
URY-5-6M/30M	ROTATING SCANNER PROBE 30MM WL 100KHZ-2MHZ 4 PI FISCHER	RSMV/S 5-6X30MM			
UR750	ROTATING SCANNER PROBE SHEILDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH	URF.750			
UR312	ROTATING SCANNER PROBE SHIELDED 4 PIN FISCHER CONNECTOR 100K-2MHZ 1.5" WORKING LENGTH, SPLIT END EXPANDABLE. 5/16"Ø				
UR093SE	ROTATING SCANNER PROBE, SELF-EXPANDING .093"Ø, 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 1.1" WORKING LENGTH, = .093"Ø.				
RR.187SS	ROTATING SCANNER PROBE, SS, FOR RA 2000. 1.1WL, 4 PIN STEP LEMO, 100KHZ-2MHZ	BPRA-12-SS			
UR250SE	Self-adjusting, Universal with "Bell" backshell Rotary Hole Probe 0.250 in. (6.35 mm) diameter, Self Expanding 2 in. (50.8 mm) working length. Operating frequency 200 kHz - 3 MHz, Fischer 4 Pin connector, reflection differential coil configuration.	SUB16-18			
UR281SE	Self-adjusting, Universal with "Bell" backshell Rotary Hole Probe 0.281 in. (7.14 mm) diameter, Self Expanding 2 in. (50.8 mm) working length. Operating frequency 200 kHz - 3 MHz, Fischer 4 Pin connector, reflection differential coil configuration.	SUB-18-20			
F-6020 SPACER SET	SET OF SPACERS AND SCREWS FOR USE WITH AF-6020 PROBE. TWO EACH OF 0.010, 0.025, 0.050, 0.100 WIDTH SPACERS AND 6 SCREWS.				
F-SC.125	Shoulder collar 0.125" diameter with set screw. For probe stabilization.				
F-6009	SLIDING PROBE , 100KZ-20KHZ	TEK-1544	SPO-5251		
F-6011	SLIDING PROBE , REFLECTON 1-SOKHZ, TF CONNECTOR, A318-A321 PT 6 57-43-04	PLA3-11			
F-6000	SLIDING PROBE 1.0" LONG X .500" WIDE X 1.0" HIGH 1-100KHZ REFLECTION TRIAX FISCHER CONNECTOR	SPO-2664	NEC-4097,TEK-4040		
AF-6010	SLIDING PROBE 1-5KHZ, REFLECTION TRIAX FISCHER CONNECTOR USED WITH NDT3088 AND NDT3118	TEK-1527			
F-6014	SLIDING PROBE 500Hz-80KHz REFLECTION WITH TRIAX FISCHER CONNECTOR. 737 PART 6 53-10-52	NEC-1099	TEK-1510		
F-6007	SLIDING PROBE 500Hz-80KHz, reflection TF connector	NEC-1099	NEC-1099		
F-6002/4F	SLIDING PROBE, REFLECTION, 400HZ-SOKHZ, 4 PIN FISCHER CONNECTOR	851P001			
F-6002/4L	SLIDING PROBE, REFLECTION, 400HZ-S0KHZ, 4 PIN LEMO CONNECTOR	851P001			
F-5110	SPECIAL EDGE SURFACE PROBE , TRIAX FISHER CONNECTOR 2MHZ (NFE) DIFFERENTIAL (CRI200)	SPO-5463			
F-6013/4F	SPECIAL SLIDING PROBE REFLECTION WITH 4 PIN FISCHER CONNECTOR 1KHZ-20KHZ (PRA12) ROHMANN	PRA12		PRA12	
AF-5122/U	SPECIAL UNIVERSAL ROTARY PROBE 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	NEC-3152/U3			
AUR218250SE	SPLIT END ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER CONNECTOR. EXPANDABLE FROM .218" to .250"	SUB-14-16			
AF-4142/2M	SPOT BRIDGE PROBE .300Ø 20-50KHZ, 2PIN MICRODOT	SB.3-20K/2M			

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-4141/2M	SPOT BRIDGE PROBE .300Ø 500HZ-2KHZ, 2PIN MICRODOT	SB.3-500H/2M			
AF-4141/TF	SPOT BRIDGE PROBE .300Ø 500HZ-2KHZ, TRIAX FISCHER	SB.3-500H/2M			•
ARS.440/1-150H	SPOT PROBE 200-300HZ	RS016-5			
ASP.75/200HZ	SPOT PROBE 200HZ	DP-750-SP			
ASDP25/3-100KHZ	SPOT PROBE DIFFERENTIAL / BRIDGE 3KHz-100KHz TOP MOUNTED TRIAX FISCHER CONNECTOR.	SPO-5164	SDP.25-3K		
ASPD.375/12-40K	SPOT PROBE REFLECTION .375" OD TRIAX FISCHER CONNECTOR 12-40KHZ				
ASDP562	SPOT PROBE REFLECTION .562" OD 700HZ-80KHZ TRIAX FISCHER CONNECTOR	SDP.562			
ASDP7-50H-4L	SPOT PROBE REFLECTION .700" DIA 50HZ-5KHZ 4 PIN LEMO CONNECTOR	SDP.7-50H-4L			
AF-4151	SPOT PROBE SS HOUSING 20MM OD 62MM HEIGHT BRIDGE WITH TRIAX FISCHER CONNECTOR 100KHZ-1.5MHZ	KD29-H1124			
ASDP375/1-10KHZ	SPOT PROBE, REFLECTION 1-10KHZ TRIAX FISCHER CONNECTOR	ASPD.375/K			
AF.375	SPRING LOADED COLLAR PROBE				
AURFB250SS/1.4WL	STAINLESS STEEL FLAT BOTTOM ROTATING PROBE, 1/4" DIAMETER100KHZ-2MHZ 1.4"WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR.	RTPRB,SST1/4,1.4"			
AURFB187SS/1.4WL	STAINLESS STEEL FLAT BOTTOM ROTATING PROBE, 3/16" DIAMETER100KHZ-2MHZ 1.4 "WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR.	RTPRB,SST,3/16,1.4"			
AURFB375SS/1.4WL	STAINLESS STEEL FLAT BOTTOM ROTATING PROBE, 3/8" DIAMETER100KHZ-2MHZ 1.4"WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR.	RTPRB,SST,3/8,1.4"			
AURFB312SS/1.4WL	STAINLESS STEEL FLAT BOTTOM ROTATING PROBE, 5/16" DIAMETER100KHZ-2MHZ 1.4"WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR.	RTPRB,SST,5/16,1.4"			
AURFB218SS/1.4"WL	STAINLESS STEEL FLAT BOTTOM ROTATING PROBE, 7/32" DIAMETER100KHZ-2MHZ 1.4"WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR.	RTPRB,SST,7/32,1.4"			
AURFB281SS/1.4WL	STAINLESS STEEL FLAT BOTTOM ROTATING PROBE, 9/32" DIAMETER100KHZ-2MHZ 1.4 "WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR.	RTPRB,SST,9/32,1.4"			
AURFB250SS/2.0WL	STAINLESS STEEL FLAT BOTTOM ROTATING PROBE. 100KHZ-2MHZ 2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR.				
AURFB312SS/2.0WL	STAINLESS STEEL FLAT BOTTOM ROTATING PROBE. 100KHZ-2MHZ 2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR.	•			
AURFBFX-17.5MSS/100M	STAINLESS STEEL FLEXIBLE ROTARY FLAT BOTTOM PROBE 100mm WORKING LENGTH, 17.5mmØ HEAD .750° LONG TIP, 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPERED END OF THE PROBE WITH 30° COIL ANGLE)		•		
AURFBFX-7.9MSS/100M	STAINLESS STEEL FLEXIBLE ROTARY FLAT BOTTOM PROBE 100mm WORKING LENGTH, 7.9mmØ HEAD.750" LONG TIP, 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPERED END OF THE PROBE WITH 30° COIL ANGLE)	•			
AURFBFX-6.7MSS/5L	STAINLESS STEEL FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0° LONG 6.7MMØ HEAD, 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ (TAPERED END OF THE PROBE)				
AUR-6.2MSS/50MWL	STAINLESS STEEL ROTARY PROBE 100KHz-2MHz. 6.2MM DIA. HEAD 50MM WORKING LENGTH, 4 PIN FISHER CONNECTOR	RSM6-2-50			
ARR312SS/2.0WL	STAINLESS STEEL ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO, .312°Ø OD, 2.0° WORKING LENGTH.	•			
ARR375SS/2.0WL	STAINLESS STEEL ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO, .375°Ø OD, 2.0° WORKING LENGTH.	•			
AURCS100250SS	STAINLESS STEEL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK (1/4")100KHZ-2MHZ. 4 PIN FISCHER CONNECTOR	UC1.250SS			
AURCS10018755	STAINLESS STEEL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK (3/16")100KHZ-2MHZ. 4 PIN FISCHER CONNECTOR	UC1.18755			
AURCS100312SS	STAINLESS STEEL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK (5/16")100KHZ-2MHZ. 4 PIN FISCHER CONNECTOR	•			
AURCS100156SS	STAINLESS STEEL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK (5/32")100KHZ-2MHZ. 4 PIN FISCHER CONNECTOR	UC1.156SS			
AURCS100218SS	STAINLESS STEEL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK (7/32")100KHZ-2MHZ. 4 PIN FISCHER CONNECTOR	UC1.21855			
AURCS100281SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK (9/32")100KHZ-2MHZ 1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR	•			
AURCS100281SS	STAINLESS STEEL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK (9/32")100KHZ-2MHZ. 4 PIN FISCHER CONNECTOR	•			-
AURCS100-4.0MSS	STAINLESS STEEL ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4.0MM DIAMETER HEAD 4 PIN FISCHER CONNECTOR				
AUR094SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR. 094" Ø (2.38mm), 35mm WORKING LENGTH.	•			
AUR157SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR157" Ø (3.98mm), 35mm WORKING LENGTH.	•			
AUR186SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR186" Ø (4.72mm), 35mm WORKING LENGTH.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR188SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR188" Ø (4.775mm), 35mm WORKING LENGTH.				
AUR-1.88SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR188" Ø (4.77mm), 35mm WORKING LENGTH.				•
ARR083SS	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. 1.1" WORKING LENGTH	BPU-0.083-SS			
AUR083SS/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.1" WORKING LENGTH	OPXV4-74B119151-201			•
AUR099SS/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.1" WORKING LENGTH	OPXV4-74B119151-203	74B119151-203		
AUR11555/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.1" WORKING LENGTH	OPXV4-74B119151-205	74B119151-205		•
AUR14555/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.1" WORKING LENGTH	OPXV4-74B119151-207	74B119151-207		
AUR160SS/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.1" WORKING	OPXV4-74B119151-209	74B119151-209		•
AUR175SS/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.1" WORKING LENGTH	OPXV4-74B119151-211	74B119151-211		
AUR190SS/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.1" WORKING LENGTH	OPXV4-74B119151-213	74B119151-213		-
AUR205SS/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.1" WORKING	OPXV4-74B119151-215	74B119151-215		
AUR280SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.5" WORKING LENGTH. 280'Ø HEAD	OPXV4-74B119151-223	74B119151-223		•
AUR375SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.5" WORKING IFINGTH. 375*/0	OPXV4-74B119151-233	74B119151-233		
AUR235SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.5" WORKING LENGTH	OPXV4-74B119151-217	74B119151-217		-
AUR265SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.5" WORKING LENGTH	OPXV4-74B119151-221	74B119151-221		
AUR300SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.5" WORKING	OPXV4-74B119151-225	74B119151-225		•
AUR315SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.5" WORKING	OPXV4-74B119151-227	74B119151-227		
AUR330SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2/MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.5" WORKING	OPXV4-74B119151-229	74B119151-229		
AUR360SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.5" WORKING LENGTH	OPXV4-74B119151-231	74B119151-231		
AUR390SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.5" WORKING LENGTH	OPXV4-74B119151-235	74B119151-235		
AUR420SS/1.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 1.5" WORKING LEINGTH	OPXV4-74B119151-237	74B119151-237		
AUR583SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 2.0" WORKING LENGTH.				
AUR685SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 2.0" WORKING LENGTH.				
AUR312SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 2.0" WORKING LENGTH	•			
AUR61055/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 2.0" WORKING LENGTH	OPXV4-74B119151-243	74B119151-243		
AUR670SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 2.0" WORKING LENGTH	OPXV4-74B119151-245	74B119151-245		
AUR485SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 2.0" WORKING LENGTH	OPXV4-74B119151-239	74B119151-239		
AUR550SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ REFLECTION/DIFFERENTIAL UNSHIELDED, 4 PIN FISCHER CONNECTOR. 2.0" WORKING LENGTH	OPXV4-74B119151-241	74B119151-241		
AUR-3.2MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER CONNECTOR 35mm WORKING LENGTH 3.2mm HEAD SIZE				
AUR-3.1MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 3.1mm HEAD SIZE	•			
AUR-3.2MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 3.2mmØ(1/8") HEAD SIZE.	RSM3-2-50			
AUR-3.2MSS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED 4 PIN FISCHER CONNECTOR 51mm WORKING LENGTH 3.2mmØ(1/8") HEAD SIZE.	•			-
AUR-11.0MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 11.0mm Ø HEAD. 50mm WORKING LENGTH	RSM11-0-50			
AUR-12.6MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 12.6mm Ø HEAD. 50mm WORKING LENGTH	RSM12-6-50			
AUR-4.0MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 4.0mm HEAD SIZE.	•			
AUR-4.5MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 4.5mm HEAD SIZE.	•			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR-4.8MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 4.8mm HEAD SIZE.				EQUIVALENT
AUR-5.0MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 5.0mm HEAD SIZE.	RSM5-0-50			
AUR-5.2MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 5.2mm HEAD SIZE.				
AUR-6.0MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 6.0mm HEAD SIZE.				•
AUR-6.4MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 6.4mm HEAD SIZE.	RS50/6.4			
AUR-6.5MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 6.5mm HEAD SIZE.	RSM6-5-50			
AUR-6.7MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 6.7mm HEAD SIZE.	RSM6-7-50	FMRP-5-6.7		
AUR-7.0MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 7.0mm HEAD SIZE.	RSM7-0-50			•
AUR-7.1MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 7.1mm HEAD SIZE	RSMV7-1-50			
AUR-7.5MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 7.5mm HEAD SIZE.				
AUR-7.9MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 7.9mm HEAD SIZE.	RSMVS7-9-50			
AUR-8.1MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 8.1mm HEAD SIZE.	RSM8-1-50			
AUR-8.3MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 8.3mm HEAD SIZE.				
AUR-6.7MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 65mm WORKING LENGTH 6.7mm HEAD SIZE.				
AUR-7.8MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 7.8mm Ø HEAD. 50mm WORKING LENGTH	RSM7-8-50			
AUR-7.9MSS/76MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 76mm(3.0") WORKING LENGTH 7.9mmØ(5/16") HFAD SIZF				
AUR-7.9MSS/80MWL	TEAD SIZE. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 80mm WORKING LENGTH 7.9mm HEAD SIZE.	RSM7-9-80			
AUR-3.6MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR, 3.6mm DIAMETER, 50mm WORKING LENGTH 3.6mm HFAD SIZE	RSM3-6-50			
AUR18455/1.1WL	Stonnin Herke Size STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. 1.1" WORKING LENGTH				
AUR828SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:828" (53/64") 2.95"(75mm) WORKING I FNGTH	615P053F075			
AUR843SS/75MWL	VORNING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:843" (27/32") 2.95"(75mm) WORKING LENGTH	615P054F075			
AUR859SS/75MWL	STAINES STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:859" (55/64") 2.95"(75mm) WORKING LENGTH	615P055F075			
AUR875SS/75MWL	VORKING LENGTH STAILESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:875" (7/8") 2.95" (75mm) WORKING I FINGTH	615P056F075			
AUR890SS/75MWL	VORNING LENGTH STAINESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:890" (57/64") 2.95"(75mm) WORKING LENGTH	615P057F075			
AUR906SS/75MWL	VICKNING LENGTH STAINESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:906" (29/32") 2.95"(75mm) WORKING I FINGTH	615P058F075			
AUR921SS/75MWL	WORKING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:921" (59/64") 2.95"(75mm) WORKING LENGTH	615P059F075			
AUR9375SS/75MWL	VORKING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:9375" (15/16") 2.95" (75mm) WORKING LENGTH	615P060F075			
AUR953SS/75MWL	VORNING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:953" (61/64") 2.95"(75mm) WORKING LENGTH	615P061F075			
AUR968SS/75MWL	STAINESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:968" (31/32") 2.95"(75mm) WORKING LENGTH	615P062F075			
AUR984SS/75MWL	WORKING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER:984" (63/64") 2.95"(75mm) WORKING LENGTH	615P063F075			<u> </u>
AUR125SS/3.0WL	WORKING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .125" (1/8"), 2.95"(75mm) WORKING LENGTH	615P008F075	,	,	
AUR125SS/75MWL	WORKING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .125" (1/8"), 2.95"(75mm) WORKING LENGTH	615P008F075	,	,	
AUR125SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .125"(3.175mm) 35mm	615P008F035			,
AUR140SS/3.0WL	WORKING LENGTH STAILESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .140" (9/64"), 2.95"(75mm)	615P009F075			
AUR140SS/75MWL	WORKING LENGTH STAILESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .140" (9/64"), 2.95"(75mm) UNDERWISE LISTER ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .140" (9/64"), 2.95"(75mm)	615P009F075			
AUR140SS/35MWL	WORKING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .140"(3.56mm) 35mm WORKING	615P009F035			
	LENGTH	010,0001000			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR140SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .140"(3.56mm) 51mm WORKING	615P009F051			
AUR156SS/50MWL	LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .156 <sup>6</sup> (3.96mm) 50mm WORKING LENGTH				
AUR156SS/51MWL	EENG IN STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .156"(3.96mm) 51mm WORKING LENGTH	615P010F051			
AUR187SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .187"(4.75mm) 51mm WORKING LENGTH	615P012F051			
AUR187SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .187"(4.75mm) 75mm WORKING LENGTH	615P012F075			
AUR203SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .203" (13/64") 2.95"(75mm) WORKING LENGTH	615P013F075			
AUR203SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .203" (13/64") 2.95" (75mm) WORKING LENGTH	615P013F075			
AUR218SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .218" (7/32") 2.95"(75mm) WORKING LENGTH	615P014F075			
AUR218SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .218" (7/32") 2.95"(75mm) WORKING LENGTH	615P014F075			
AUR218SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .218"(5.54mm), 35mm WORKING LENGTH	615P014F035			
AUR218SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .218"(5.54mm), 51mm WORKING LENGTH	615P014F051			
AUR250SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .250"(6.35mm), 35mm WORKING LENGTH	615P016F035			
AUR265SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .265" (17/64") 2.95"(75mm) WORKING LENGTH	615P017F075			
AUR265SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .265" (17/64") 2.95"(75mm) WORKING LENGTH	615P017F075			
AUR281SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .281" (9/32"), 2.95"(75mm) WORKING LENGTH	615P018F075			
AUR281SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .281" (9/32"), 2.95"(75mm) WORKING LENGTH	615P018F075			
AUR296SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .296" (19/64") 2.95" (75mm) WORKING LENGTH	615P019F075			
AUR296SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .296" (19/64") 2.95" (75mm) WORKING LENGTH	615P019F075			
AUR296SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .296"(7.54mm), 35mm WORKING LENGTH	615P019F035			
AUR328SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .328" (21/64") 2.95"(75mm) WORKING LENGTH	615P021F075			
AUR328SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .328" (21/64") 2.95"(75mm) WORKING LENGTH	615P021F075			
AUR328SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .328"(8.33mm), 35mm WORKING LENGTH	615P021F035			
AUR343SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .343" (11/32") 2.95"(75mm) WORKING LENGTH	615P022F075			
AUR343SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .343" (11/32") 2.95"(75mm) WORKING LENGTH	615P022F075			
AUR343SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .343"(8.71mm) 51mm WORKING LENGTH	615P022F051			
AUR343SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .343"(8.73mm), 35mm WORKING LENGTH	615P022F035			
AUR359SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .359" (23/64") 2.95"(75mm) WORKING LENGTH	615P023F075			
AUR359SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .359" (23/64") 2.95"(75mm) WORKING LENGTH	615P023F075			
AUR375SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .375" (3/8") 2.95"(75mm) WORKING LENGTH	615P024F075			
AUR375SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .375" (3/8") 2.95"(75mm) WORKING LENGTH	615P024F075			
AUR390SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .390" (25/64") 2.95"(75mm) WORKING LENGTH	615P025F075			
AUR390SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .390" (25/64") 2.95"(75mm) WORKING LENGTH	615P025F075			
AUR406SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .406" (13/32") 2.95"(75mm) WORKING LENGTH	615P026F075			
AUR406SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .406" (13/32") 2.95"(75mm) WORKING LENGTH	615P026F075			
AUR406SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .406"(10.31mm) 51mm WORKING LENGTH.	615P026F051			
AUR421SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .421" (27/64") 2.0"(51mm) WORKING LENGTH	615P027F051			

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR421SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .421" (27/64") 2.95"(75mm)	615P027F075	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR42155/75MWL	WORKING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .421" (27/64") 2.95"(75mm)	615P027F075	·		
AUR453SS/75MWL	WORKING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .453" (29/64") 2.95"(75mm) WORKING LENGTH	615P029F075			
AUR453SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .453" (29/64") 2.95"(75mm) WORKING !ENGTH	615P029F075			
AUR468SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .468" (15/32") 2.95" (75mm) WORKING LENGTH	615P030F075			
AUR468SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .468" (15/32") 2.95" (75mm) WORKING LENGTH	615P030F075			•
AUR484SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .484" (31/64") 2.0"(51mm) WORKING LENGTH	615P031F051			
AUR484SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .484" (31/64") 2.95" (75mm) WORKING LENGTH	615P031F075			
AUR484SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .484" (31/64") 2.95" (75mm) WORKING LENGTH	615P031F075			
AUR500SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .500" (1/2") 2.95"(75mm) WORKING LENGTH	615P032F075			
AUR500SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .500" (1/2") 2.95"(75mm) WORKING LENGTH	615P032F075	•		
AUR515SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .515" (33/64") 2.95"(75mm) WORKING LENGTH	615P033F075			
AUR515SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .515" (33/64") 2.95"(75mm) WORKING LENGTH	615P033F075			
AUR531SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .531" (17/32") 2.95" (75mm) WORKING LENGTH	615P034F075	•		
AUR531SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .531" (17/32") 2.95"(75mm) WORKING LENGTH	615P034F075			
AUR547SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .547" (35/64") 2.95" (75mm) WORKING LENGTH	615P035F075			
AUR547SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .547" (35/64") 2.95" (75mm) WORKING LENGTH	615P035F075			
AUR562SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .562" (9/16") 2.95"(75mm) WORKING LENGTH				
AUR562SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .562" (9/16") 2.95"(75mm) WORKING LENGTH	615P036F075			
AUR578SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .578" (37/64") 2.95"(75mm) WORKING LENGTH	615P037F075			
AUR593SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .593" (19/32") 2.95"(75mm) WORKING LENGTH	615P038F075			
AUR609SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .609" (39/64") 2.95"(75mm) WORKING LENGTH	615P039F075			
AUR640SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .641" (41/64") 2.95"(75mm) WORKING LENGTH	615P041F075			
AUR656SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .656" (21/32") 2.0"(51mm) WORKING LENGTH	615P042F051			
AUR656SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .656" (21/32") 2.95"(75mm) WORKING LENGTH	615P042F075			
AUR671SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .671" (43/64") 2.0"(51mm) WORKING LENGTH	615P043F051			
AUR671SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .671" (43/64") 2.95"(75mm) WORKING LENGTH	615P043F075			
DUP AUR687SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .687" (11/16") 2.95"(75mm) WORKING LENGTH	615P044F075	•		
AUR6875SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .6875" (11/16") 2.95"(75mm) WORKING LENGTH	615P044F075			
AUR703SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .703" (45/64") 2.95"(75mm) WORKING LENGTH	615P045F075			
AUR718SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .718" (23/32") 2.95"(75mm) WORKING LENGTH	615P046F075			
AUR734SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .734" (47/64") 2.95"(75mm) WORKING LENGTH	615P047F075	•		
AUR750SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .750" (3/4") 2.95"(75mm) WORKING LENGTH	615P048F075			
AUR765SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .765" (49/64") 2.95"(75mm) WORKING LENGTH	615P049F075			
AUR781SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .781" (25/32") 2.95"(75mm) WORKING LENGTH	615P050F075			
AUR796SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .796" (51/64") 2.95" (75mm) WORKING LENGTH	615P051F075			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR8125SS/75MWL	DESCRIPTION STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .797" (13/16") 2.95" (75mm)	615P052F075	EQUIVALENT	EQUIVALENT	EQUIVALENT
	WORKING LENGTH STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: 1.0° (64/64°) 2.95°(75mm)				
AUR-1.0SS/75MWL	WORKING LENGTH	615P064F075	•	•	
AUR-1.98MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ, 4 PIN FISCHER CONNECTOR, 35MM(1.50") WORKING LENGTH, 1-98MM(0.078")Ø HEAD	615P005F035			
AUR-2.38MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR, 35MM(1.50") WORKING LENGTH, 2.38MM(0.0937")Ø HEAD	615P006F035			
AUR-2.78M/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR, 35MM(1.50") WORKING LENGTH, 2.78MM(0.109")Ø HEAD	615P007F035			
AUR453SS/2WL	STAINLESS STEEL ROTATING SCANNER PROBE 11.5MM(.453")Ø HEAD and 51MM(2.0") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR	615P029F051			
AUR-6.7MSS/45MWL	STAINLESS STEEL ROTATING SCANNER PROBE 6.7mmØ(.264") HEAD,100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 45mm WORKING LENGTH 6.7mm HEAD SIZE.				
ARRCS100218SS	STAINLESS STEEL ROTATING SCANNER PROBE RA-2000. 100 DEGREES COUNTERSINK 100KHZ-2MHZ. 4 PIN STEP LEMO CONNECTOR				
ARRCS100250SS	STAINLESS STEEL ROTATING SCANNER PROBE RA-2000. 100 DEGREES COUNTERSINK 100KHZ-2MHZ. 4 PIN STEP LEMO CONNECTOR				
ARRCS10031255	STAINLESS STEEL ROTATING SCANNER PROBE RA-2000. 100 DEGREES COUNTERSINK 100KHZ-2MHZ. 4 PIN STEP LEMO CONNECTOR				
APN-92-7B	SURFACE PROBE 50-500KHZ	MP902-70B			
ACSU100-4.0MSS	STAINLESS STEEL UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHz-2MHz 4-PIN FISCHER CONNECTOR. 4.0M(.157")Ø	CSEM100-4.0M			
AURCS100-3.6MSS/50MWL	STAINLESS STEEL100° COUNTER SINK ROTATING SCANNER PROBE, 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR., 3.6mm/@ SOmm WORKING LENGTH.				
AURCS100-12.5MSS/50MWL	STAINLESS STEEL100° COUNTER SINK ROTATING SCANNER PROBE, 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR.,12.5mmØ 50mm WORKING LENGTH.				
AURCS100-4.7MSS/50MWL	STAINLESS STEEL100° COUNTER SINK ROTATING SCANNER PROBE, 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR, 4.7mm/d SOmm WORKING LENGTH.				
AURCS100-9.5MSS/50MWL	STAINESS STEEL100° COUNTER SINK ROTATING SCANNER PROBE, 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR FOR ROHMAN MINI ROTOR.9.Smm/d 50mm WORKING LENGTH.				
AES-6.3MSE	STANDARD ELOTEST ROTARY PROBE SPLIT END 6.3MM 100KHZ-2MHZ 2.0" WORKING LENGTH	ESR6.3MSE			
AESY125156	STANDARD ELOTEST ROTARY PROBE 100KHZ-2MHZ 1.3" WORKING LENGTH	ESRY.125156			
AESY156187	STANDARD ELOTEST ROTARY PROBE100KHZ-2MHZ 1.3" WORKING LENGTH	ESRY.156187			
AF-5118/L500K	STRAIGHT ABSOLUTE SURFACE PROBE MICRODOT CONNECTOR, UNSHIELDED, 500KHZ-1MHZ Fe/NFe.	121P1A	610-015-000		
APN-92-9B	SURFACE PROBE 50-500KHZ	M902-90B			
APN-9-6	SURFACE PROBE 50-500KHZ	MP-90			
APN-96-5	SURFACE PROBE 50-500KHZ	MP906-50			
ATPN-903-12	SURFACE PROBE, .030" DROP 12.0" LONG TRIAX FISCHER CONNECTOR 50-500KHZ	MTF9003-120			
ATPN-903-4	SURFACE PROBE, .030" DROP 4.0" LONG TRIAX FISCHER CONNECTOR 50-500KHZ	MTF9003-40			
ATPN-903-5	SURFACE PROBE, .030" DROP 5.0" LONG TRIAX FISCHER CONNECTOR 50-500KHZ	MTF9003-50			
ATPN-903-3B	SURFACE PROBE, .030" DROP,BENT 3.0" LONG TRIAX FISCHER CONNECTOR 50-500KHZ				
ATPN-903-6B	SURFACE PROBE, .030" DROP,BENT 6.0" LONG TRIAX FISCHER CONNECTOR 50-500KHZ	MTF9003-60-1-3M			
АТР-4/1-20К	STRAIGHT RIGID SURFACE PROBE LOW FREQUENCY DIFF/BRIDGE SHIELDED .187"Ø TUBING 4.0" LONG WITH TRIAX FISCHER CONNECTOR 1-20KHz				
AP-4.5	STRAIGHT SHIELDED SURFACE PROBE 50-500KHz WITH MICRODOT CONNECTOR.114mm LONG .187" DIA. TUBING				
ATP-3	STRAIGHT STAINLESS STEEL SHAFT .1870" DIA TUBING SURFACE PROBE SHIELDED ,TRIAX FISCHER CONNECTOR 20-200KH2 ABSOLUTE SHIELDED, 3.0" LONG	100P3	611-034-001		
ATP-6	STRAIGHT STAINLESS STEEL SHAFT .187Ø" DIA TUBING SURFACE PROBE SHIELDED ,TRIAX FISCHER CONNECTOR 50-500KH2 ABSOLUTE SHIELDED, 6.0"	101P6	611-035-003		
APN-97.5-5	SURFACE PROBE 50-SOOKHZ	PEN97.5-5 50-500K			
APN-97-10	SURFACE PROBE 50-SOOKHZ	MP907-100			
APN-92-3B	SURFACE PROBE 50-500KHZ, BENT	MP902-30B			
AFIN-32-38					

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AXXTPN-6/1-6M	STRAIGHT SURFACE PROBE, .062" TIP, 1-6MHz, 6.0" LONG. TRIAX FISCHER CONNECTOR. MZTF-60	MZTF-60-1-6M	D0815E1015-2071		
AXXTPN-4	STRAIGHT SURFACE PROBE, .062" TIP, 50-500KHZ, 4.0" LONG. TRIAX FISCHER CONNECTOR	MXTF-40	MXTF-40		
AXXTPN-6	STRAIGHT SURFACE PROBE, .062" TIP, 50-500KHZ, 6.0" LONG. TRIAX FISCHER CONNECTOR. MZTF-60	MZTF-60	D0815E1015-2067		
AP-122P1A/2MHZ	STRAIGHT UNSHIELDED DELRIN SURFACE PROBE 1-3MHz 5.0° LONG WITH MICRODOT CONNECTOR	122P1A			•
AF-5109	SUFACE PROBE .100" DIA TUBING SHIELDED SPECIAL ANGLE FOR CRI200 8.5" LONG TRIAX FISCHER CONNECTOR 500KHZ-1MHZ	NEC-2092			
ATPN-903-5B	SURFACE PROBE, .030"DROP ,BENT 5.0" LONG TRIAX FISCHER CONNECTOR	MTF9003-50B			
ATPR-6/1-10K	SURFACE LF ROBE 1-10KHZ, 6.0" LONG .250" TIP; REFLECTION, TF CONNECTOR				
ATPR-6/1-20K	SURFACE LF ROBE 1-20KHZ, 6.0" LONG .250" TIP; REFLECTION, TF CONNECTOR	RS-60/1-20KHZ			•
ATP-6/1-20KHZ	SURFACE LF ROBE 1-20KHZ, 6.0" LONG DIFFERENTIAL, TF CONNECTOR	RS-60/1-20KHZ DIFF	RS-60/1-20KHZ		
ATPR-6/1-50K	SURFACE LF ROBE 1-50KHZ, 6.0" LONG .250" TIP; REFLECTION, TF CONNECTOR				
ATPR-6/20-50K	SURFACE LF ROBE 20-50KHZ, 6.0" LONG .250" TIP; REFLECTION, TF CONNECTOR	RS-60/20KHZ.			
ATP-4.5/1-50khz	SURFACE LOW FREQUENCY PROBE 1-50khz .1870D, DIFF TRIAX CONN 4.5" LONG				
APN-95-3B	SURFACE PROBE 50-500KHZ, BENT 90 DEGREES .500° DROP 3.0° LONG MICRODOT CONNECTOR	MP905-30B			
APN-925-4/500K/LOO	SURFACE PROBE 90 DEG .250" DROP 4.0"LONG LEMO OO CONNECTOR 500KHZ-1MHZ	KAPS214-1E			
ATP-95-4/1K	SURFACE LF PROBE 1-5KHZ, 90 DEG .5' DROP .187" OD TUBING 5.0" LONG DIFFERENTIAL, TRIAX FISCHER CONNECTOR	TPN95-4/1K			
ATP-95-5/1K	SURFACE LF PROBE 1-5KHZ, 90 DEG .5' DROP .250" OD TUBING 5.0" LONG DIFFERENTIAL, TRIAX FISCHER CONNECTOR				
ATP-6/20-50KHZ	SURFACE LF PROBE 20-50KHZ, 6.0" LONG DIFFERENTIAL, TF CONNECTOR	RS-60/20-50KHZ DIFF	RS-60/20-50KHZ		
ATP-95-6/20-50KHZ	SURFACE LF PROBE 20-50KHZ, 90 DEG .5" DROP 6.0" LONG DIFFERENTIAL, TF CONNECTOR	RS-905-60/TF/20-50KHZ			
ATP-95-4/2K	SURFACE LF PROBE 2-10KHZ, 90 DEG .5' DROP .187" OD TUBING 4.0" LONG DIFFERENTIAL, TRIAX FISCHER	TPN95-4/2K			
ATP-95-5/2K	SURFACE LF PROBE 2-10KHZ, 90 DEG .5' DROP .250" OD TUBING 5.0" LONG DIFFERENTIAL, TRIAX FISCHER				
АТР-95-5/5К	SURFACE LF PROBE 5-20KHZ, 90 DEG .5' DROP .250" OD TUBING 5.0" LONG DIFFERENTIAL, TRIAX FISCHER				
AXTPN35-5/2M	SURFACE PROBE072" DIA TUBING 35", .500" DROP1-3MHZ TRIAX FISCHER CONNECTOR	MMTF305-50/2M			
AXTPN45-5U	SURFACE PROBE - 45', .50DROP, .062 TIP 50-500K, 5"L, UNSHIELDED, TF				
APN95-4.5B	SURFACE PROBE 90 DEG .5" DROP 4.5" LONG 15DEG CRANK MICRODOT CONNECTOR 50-500KHZ				
ATPN-35-4	SURFACE PROBE, 35 DEGREES, TRIAX FISCHER CONNECTOR 50-500KHZ 4.0" LONG				
ASPN-95-5	SURFACE PROBE, .093" TUBING, .500"DROP 90"ANGLE MICRODOT CONNECTOR 50-500KHZ	DPT90-003			
ATPN-35-6	SURFACE PROBE, 35 DEGREES, TRIAX FISCHER CONNECTOR 50-500KHZ 6.0° LONG				
ATPN-45-4/500K	SURFACE PROBE, 45 DEG .500" DROP 4.0" LONG TRIAX FISCHER CONNECTOR500KHZ-1MHZ				
APN-975-4.5/3M	SURFACE PROBE 90 DEG .750" DROP .125" TIP, PROBE LENGTH 4.5 " LONG MOCRODOT CONNECTOR 1-3MHZ	310P44			
ASPN-45-4.5B/2MHZ	SURFACE PROBE .092" TIP, 4.5" LONG, 45" BENT .500" DROP 1-3MHZ, MICRODOT CONNECTOR	206P4F			•
ASTPN-925-8	SURFACE PROBE .093" TUBING SHEILDED 90 DEG .250" DROP 8.0" LONG 50-500KHZ TRIAX FISCHER CONNECTOR				
AF-5108	SURFACE PROBE .100" DIA TUBING FOR CRI2DO SHIELDED SPECIAL ANGLE TRIAX FISCHER CONNECTOR 11.0" LONG 500KHZ-1MHZ	NEC-2091	,		
AP97-10	SURFACE PROBE .187 SHAFT, 50-500KHZ				
AP45-4.5L/500K	SURFACE PROBE .187 TIP, 4.5"L,45° BENT, .5"DROP 500KHZ LOCATOR, MICRODOT				
AP-3/2MHZ	SURFACE PROBE .1870D, UNSHIELDED, PLASTIC TIP, 1-3 MHZ	UP30			
ATPU-3/2MHZ	SURFACE PROBE .1870D, UNSHIELDED, PLASTIC TIP, 1-3 MHZ WITH TRIAX FISCHER CONNECTOR.	UP30			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
312P34U	SURFACE PROBE 0.187" DIAMETER, .500" DROP, 200KHZ, MICRODOT CONNECTOR	312P34U	610-094-171		
APN-91-5/2M	SURFACE PROBE 90 degree .100" DROP 5.0" LONG 1-3MHZ MICRODOT CONNECTOR	PEN91-5 500K-2M			
APNU-91-7/500K	SURFACE PROBE 90° .100° DROP 7.0° LONG MICRODOT CONNECTOR, UNSHIELDED, 500KHz-1MHz	APNU-91-7/500K			
APN-925-5B/L-500K	SURFACE PROBE 90DEG .250" DROP 5.0" LONG 15 DEG CRANK AT 1.0" SHAFT .125" DIA TIP MICRODOT CONNECTOR (LOCATOR 500KHZ ,47 UH)	•			
APN95-4.5	SURFACE PROBE 90DEG .5" DROP 4.5" LONG 50-500KHZ MICRODOT CONNECTOR	•			
APN-93-4FX	SURFACE PROBE FLEXIBLE 90 DEG .300" DROP 4.0" LONG MICRODOT CONNECTOR	•			
APN-91-4.5/L-500K	SURFACE PROBE LOCATOR 500KHZ	•			
APN-5/L500K	SURFACE PROBE LOCATOR 500KHZ,47 UH WITH MICRODOT 5.0°LONG	MP-50L500KHZ			
APN-93-6B	SURFACE PROBE SHIELDED 1/8" DIA TUBE 90 DEG.300" DROP 15 DEG BENT6.0" LONG MICRODOT CONNECTOR 50-500KHZ	MP903-60B			
APN-5/50-300KHZ	SURFACE PROBE STRAIGHT 5.0° LONGMICRODOT CONNECTOR 50-300KHZ	MP-50/50-300KHZ			
AXPN-45-5/2M	SURFACE PROBE 1-3MHZ 45 DEG .500' DROP 5.0 "LONG MICRODOT CONNECTOR	XPEN45 500K-2M			
APN-902-4	SURFACE PROBE STRAIGHT. 50-500KHZ	MP902-40			
ASPN-93-5/2MHZ	SURFACE PROBE 1-3MHZ MICRODOT, .093, .35 DROP 90°ANGLE				
ASPN-95-5/6MHZ	SURFACE PROBE 1-3MHZ MICRODOT, .093, .5 DROP 90"ANGLE	•			
ATPN-95-4/500K	SURFACE PROBE, 90 DEG .500" DROP 4.0" LONG TRIAX FISCHER CONNECTOR500KHZ-1MHZ	•			
ATPN-91-5B	SURFACE PROBE, 90° .100" DROP 5.0" LONG 15" BENT. TRIAX FISCHER CONNECTOR 50-500KHZ	MTF901-50B			
ATPN-91-5	SURFACE PROBE, 90" .100" DROP 5.0" LONG. TRIAX FISCHER CONNECTOR 50-500KHZ	MTF901-50			
ASTPN-4/2MHZ	SURFACE PROBE 1-3MHZ, .092 TIP STRAIGHT 4.0" LONG TRIAX FISCHER CONNECTOR				
ASTPN45-4/2MHZ	SURFACE PROBE 1-3MHZ, . 092 TIP 0D ,45 DEG .5 DROP ,5.0' LONG TRIAX FISCHER CONN				
ASPN-94-4.5/2M	SURFACE PROBE 1-3MHZ, .092 OD TIP, .400DROP, 4.5LONG	MPEN94-4.5/2M			
APN-5/50-500KHZ	SURFACE PROBE, 50-S00KHZ, MICRODOT				
APNU-5	SURFACE PROBE, UNSHIELDED, 5.0" LONG WITH MICRODOT CONNECTOR 50-500KHZ	UMP-50			
ATPNU-91-5	SURFACE PROBE, 90" .100" DROP 5.0" LONG. TRIAX FISCHER CONNECTOR 50-500KHZ UNSHIELDED.	UMTF901-50			
ASTPN45-6/2M	SURFACE PROBE 45 DEG .5 DROP .092 OD TUBING 6.0 INCH LONG 1-3MHZ TRIAX FISCHER CONN	•			
ASTPN-45-6	SURFACE PROBE 45 DEG .5 DROP .092 OD TUBING 6.0 INCH LONG 50-500KHZTRIAX FISCHER CONN				
ASPN-475-10/2MHZ	SURFACE PROBE 45 DEG .75" CRANK 10.0" LONG .093" DIA TUBING SHIELDED MICRODOT CONNECTOR 1-3MHZ	206P10FU			
AXPN-45-5	SURFACE PROBE 45 DEG 5.0 " LONG .072" dia TUBE MICRODOT CONNECTOR 50-500khz	XPEN45 50-500K			
AP475-4.5/L500K	SURFACE PROBE 45 DEGREES .750" CRANK 4.5" LONG HOCKING LOCATOR 500K MICRODOT CONNECTOR .187" OD TUBING	205P4	610-055-076		
ATPN-91-6	SURFACE PROBE, 90° DEGREES .100° DROP 6.0° LONG TRIAX FISCHER CONNECTOR 50KHZ-500KHz	MTF901-60			
ATPN-45-4/2MHZ	SURFACE PROBE, TRIAX 1-3MHZ	TPEN-45-4			
ATP-45-5/30KHZ	SURFACE PROBE 45DEGREE .500" DROP 5.0" LONG BRIDGE/DIFFERENTIAL30-50KHZ TRIAX FISCHER CONNECTOR.187" DIA TUBING	•			
ATPR-45-5/30KHZ	SURFACE PROBE 45DEGREE .500" DROP 5.0" LONG REFLECTION30-50KHZ TRIAX FISCHER .187" Ø TUBING				
AP121P1A/L-500K	SURFACE PROBE 500K UNSHIELDED 4" LONG	121P1A			
AP-95-4.5/L500K	SURFACE PROBE 500KHZ , .187OD TIP, 90°, .50 DROP, 4.5LONG, SHIELDED, MICRODOT	309P34			
ASPN-925-4.5/L500K	SURFACE PROBE 500KHZ, .092" OD TIP, .250 " DROP, HOCKING LOCATOR, MICRODOT CONNECTOR (47UH)	MPEN903-4.5			
ATPN-3/1-50KHZ	SURFACE PROBE, TRIAX 1-50KHZ, 3"L	•			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
APN-925-10FX	FLEXIBLE SURFACE PROBE 90 DEG .250" DROP 10.0" INCH LONG MICRODOT CONNECTOR 50-500KHZ				
APN-95-6C	Eddy Current Surface Probe 90° degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long, 50-500 kHz with Microdot Connector.				•
APN-95-7.5FX	FLEXIBLE COPPER SURFACE PROBE 7.5" LONG STRAIGHT SHAFT WITH MICRODOT CONNECTOR. 50-500KHz	MP-95FX			
APN-91-4FX	FLEXIBLE SHAFT SURFACE PROBE 90 DEGREE .100" DROP 4 INCHES LONG .125" TUBING DIA. MICRODOT CONNECTOR 50-500KHZ	MP901-40FX			
APN-45-10FX	FLEXIBLE SURFACE PROBE 50-SOOKHZ				
APN-903-10FX	FLEXIBLE SURFACE PROBE 50-500KHZ .030" DROP 10.0" LONG MICRODOT CONNECTOR	VM202RAFX			
APN-903-6FX	FLEXIBLE SURFACE PROBE 50-SO0KHZ .030" DROP 6 .0" LONG MICRODOT CONNECTOR	MP9003-6/FX	VM202RAFX		
APN-98-10FX	FLEXIBLE SURFACE PROBE 50-500KHZ, 800" DROP 90 DEG 10.0 INCH LONG, MICRODOT CONNECTOR				
APN-925-7FX	FLEXIBLE SURFACE PROBE 90 DEG .250° DROP 7.0° LONG MICRODOT CONN 50-500KHZ .125° TIP				
APN-925-7FX/2MHZ	FLEXIBLE SURFACE PROBE 90 DEG .250° DROP 7.0° LONG MICRODOT CONNECTOR 1-3MHz .125" TIP				
APN-925-8FX	FLEXIBLE SURFACE PROBE 90 DEG .250° DROP 8.0° LONG MICRODOT CONN 50-500KHZ .125° TIP				
APN-903-5FX	FLEXIBLE SURFACE PROBE 90° Degrees, .030° Drop, 50-500KHz with Microdot Connector.	PEN903-5/FX	MP9003-50FX		
APN-92-4FX/2MHZ	FLEXIBLE SURFACE PROBE, 90° .200" DROP MICRODOT CONNECTOR 1-3MHZ, 4.0" LONG				
APN-92-6FX	FLEXIBLE SURFACE PROBE, 90° .200" DROP MICRODOT CONNECTOR 50-500KHZ, 6.0" LONG	MP902-60FX			
APN-92-6FX/2MHZ	FLEXIBLE SURFACE PROBE, 90° .200" DROP, MICRODOT CONNECTOR 1-3MHZ, 6.0" LONG				
APN-95-5/500K	RIGID SURFACE PROBE 500KHz-1MHz; 90 DEG .500" DROP 5.0" LONG MICRODOT CONNECTOR .125" TIP				
APN-45-6	RIGID SURFACE PROBE 50-500KHZ 6.0" LONG 45 DEG .500" DROP CURVE MICRODOT CONNECTOR .125" TIP	MP455-60	MP455-60	PEN45-6	
ATPN-3/1-6MHZ	SURFACE PROBE, TRIAX 1-6MHZ, 3"L				
APN-925-7	RIGID SURFACE PROBE 90 DEG .250" DROP 7.0" LONG MICRODOT CONN 50-500KHZ .125" TIP				
AXSTPN35-5	SURFACE PROBE 50-S00KHZ, TIP OD .062 , 30 DE .5 DROP ,5.0" LONG				
AXSTPN45-5	SURFACE PROBE 50-500KHZ, TRIAX, 062 TIP 0D 45 DE .5 DROP ,5.0" LONG				
AXSTPN925-5	SURFACE PROBE 50-S00KHZ, TRIAX.062 tip .5.0" long				
ASTPN35-4	SURFACE PROBE 50-S00KHZ, . 092 TIP OD 35" .5 DROP 5.0" LONG				
ASPN-45-4.5	SURFACE PROBE 50-500KHZ, 45DEG .092"OD TIP,500"DROP, 4.5 "LONG MICRODOT CONN.				
APN-925-7/2MHZ	RIGID SURFACE PROBE 90 DEG .250" DROP 7.0" LONG MICRODOT CONNNECTOR 1-3MHz .125" TIP				
APN-925-8	RIGID SURFACE PROBE 90 DEG .250" DROP 8.0" LONG MICRODOT CONN 50-500KHZ .125" TIP	PEN925-8			
APN-910-3	RIGID SURFACE PROBE 90 DEG 1.00" DROP 3.0" LONG MICRODOT CONNNECTOR 50-500KHz .125" TIP				
APN-95-6/2MHZ	RIGID SURFACE PROBE, 90" DEGREES, .500" DROP 6.0" LONG MICRODOT CONNECTOR 1-3MHZ	MP905-60/1-3MHZ	MP905-60/1-3MHZ	MP905-60/1-3MHZ	
APN-8FX	STRAIGHT COPPER SHAFT FLEXIBLE SURFACE PROBE, ABS, 50-500KHZ .125"Ø (3.3mm) TIP, 8.0"(203.2mm) LONG WITH MICRODOT CONNECTOR				
ASTPN-95-6B1	SURFACE PROBE 50-500KHZ, TRIAX FISCHER CONNECTOR.092 "TUBING .5 DROP 6.0" LONG BENT 15 DEG AT 1.0" FROM TIP				
ASTPN-4	SURFACE PROBE 50-500KHZ,, 092 TIP OD STRAIGHT 4.0 " LONG				
ASTPN45-4	SURFACE PROBE 50-SOOKHZ,, 092 TIP OD 45 DE .5 DROP 5.0" LONG				
AP-65-6B	Surface Probe 60 Degree 0.5 drop 6.0" Long Bent with Microdot connector 50-500K HZ (.187 dia tubing)	P605-60B			
ATP-65-6B	Surface Probe 60 Degree 0.5 drop 6.0" Long Bent with Triax Fischer connector 50-500K HZ (.187 dia tubing)	P605-60B			
ATPN-8/500KHZ-1MHZ	SURFACE PROBE, TRIAX 500KHZ-1MHA				
AF-5091	SURFACE PROBE 90 DEG SHIELDED.500" DROP .125" TUBING 4.5" LONG 15 DEG BACK CRANK IN THE SHAFT MICRODOT 1-3MHZ	314P14			

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPN-910-6/1MHZ	SURFACE PROBE, TRIAX 500KHZ-1MHZ				
ATPN-43-4	SURFACE PROBE, TRIAX 50-500KHZ	MTF453-40			
ASPN-925-4.5	SURFACE PROBE 90 DEG .250 DROP .093 TUBING OD 50-500KHZ, 4.5" LONG. MICRODOT CONNECTOR				
APN-10FX	STRAIGHT FLEXIBLE SURFACE PROBE 10" LONG, MICRODOT CONNECTOR 50-500KHZ				
ATPN-45-4.5	SURFACE PROBE, TRIAX 50-500KHZ	6100-1/8-S-BNC			
APN-903-3	STRAIGHT SURFACE PROBE .030 DROP, .125" Ø TIP, 3.0" LONG WITH MICRODOT CONNECTOR 50-500KHz	PEN903-3	MP9003-30		
APN-925-4.5/L500K	SURFACE PROBE ABSOLUTE SHIELDED 90" DEGREES, .250" DROP 4.5" LONG HOCKING LOCATOR 500KHZ ( 47 UH) MICRODOT CONNECTOR	309P24			
APN-45-2/2M	SURFACE PROBE 1-3MHZ 2.0 INCH LONG MICRODOT CONN 45 DEG	MP-455-2	206P2		
ASPN-92-6C	SURFACE PROBE 90 DEG CURVE .200 DROP .093 TUBING OD 50-500KHZ, 6.0" LONG. MICRODOT CONNECTOR	309P24XF			
AXPN-95-6	SURFACE PROBE 90 DEG, .500 Drop 6.0 " LONG .072" dia TUBE MICRODOT CONNECTOR 50-500khz				
APN-903-6/1MHZ	SURFACE PROBE 1MHZ	MP9003-6			
ASTPN-925/2-10MHZ	SURFACE PROBE 90 DEGREE .250" DROP .093" DIA TUBE 2-10MHZ 3.0" LONG TRIAXFISCHER CONNECTOR	303P23			
ATP-95-5/30KHZ	SURFACE PROBE 90 DEGREE .500" DROP 5.0" LONG BRIDGE/DIFFERENTIAL30-50KHZ TRIAX FISCHER .187" DIA TUBING				
ATPN-902-7F	SURFACE PROBE, TRIAX 50-500KHZ	MTF9002-70FX			
APN-95-6/1MHZ	SURFACE PROBE 200KHZ-1MHZ	MP905-60-1M, VM112			
APN-45-6-QMDFX	SURFACE PROBE 45 DEG 50-500KHZ, QUICK DISCONNECT MICRODOT, FLEX SHAFT TUBING.				
APN-45-2	SURFACE PROBE 45DEG .500" DROP 2.0"LONG, MICRODOT CONN 50-500KHZ	PEN45-2			
AF-5136	SURFACE PROBE 90° 2" FROM THE HANDLE 1" AFTER THE 90°, .250 DROP .125" DIAMETER TIP, 100KHZ - 3 MHZ, 4.50" LONG TRIAX FISCHER CONNECTOR	TEK-2015			
ATPR-95-5/30KHZ	SURFACE PROBE 90° DEGREE .500° DROP 5.0° LONG REFLECTION30-50KHZ TRIAX FISCHER .187° Ø TUBING				
APN-903-8	SURFACE PROBE 50-500KHZ	MP9003-80			
APN-903-9	SURFACE PROBE 50-500KHZ	MP9003-90			
AP-93-5B/2-12K	SURFACE PROBE 90° DEGREES, .187"Ø TUBING .300" DROP 5.0" LONG BENT SHAFT TRIAX FISCHER CONNECTOR 2-12KHZ DIFFERENTIAL	LP903-50B/2-12K			
AF-5065	SURFACE PROBE 90*, .03" ROP, .0960D TUBING, 6.5L, Triax FICHER CONN SHIELDED50-500KHZ				
AP92-4/6M	SURFACE PROBE 90", .200 DROP, 4.0" LONG (2.0"WL) 6MHZ				a
AP-95-6/L500KHZ	SURFACE PROBE 90".500" DROP 6.0" LONG LOCATOR 500KHZ(47UH) MICRODOT CONNECTOR TIP 4.4MM( .187")	309P36			
APN-907-100	SURFACE PROBE 50-SOOKHZ	MP907-100			
APN-95-5/200K	SURFACE PROBE 50-SOOKHZ	VM112			
APN-925-12	SURFACE PROBE 50-500KHz 90 DEG .250" DROP 12.0" LONG WITH MICRODOT CONNECTOR				
AXTPN35-5	SURFACE PROBE ABSOLUTE BRIDGE500" DROP 35", .072" Ø TUBING, 50-S00KHZ TRIAX FISCHER CONNECTOR.	MMTF305-50			
AXPN95-4	SURFACE PROBE ABSOLUTE, 50-500KHZ, 90°.072 OD TUBE .500° DROP 4.0° LONG MICRODOT CONNECTOR	MMP905-4			
AP925-4.5	SURFACE PROBE ABSOLUTE, 90° 50-500KHZ CENTER FREQUENCY 200KHz187" TIP DIAMETER, 6.4mm(.25")TIP LENGTH, OVERALL PROBE LENGTH 114mm(4.5") Fe/NFe. MICRODOT CONNECTOR	308P24			
ATPN-92-6C	SURFACE PROBE, TRIAX 50-500KHZ, 90°, 30° BEND 1" FROM THE TIP, .125Ø X.2" DROPX 6" LONG	TPEN92-6C			
АТР95-5В/30К	SURFACE PROBE DIFFERENTIAL, 10-50KHX, 5.0°L, 90°, .5 DROP				
APN-95-5B	SURFACE PROBE 50-S00KHZ, BENT 90°, .500° DROP 5.0 ° LONG MICRODOT CONNECTOR	MP905-50B			
APN-91-7.5	SURFACE PROBE 90 DEG .DROP 0.10" 7.5 LONG MICRODOT CONNECTOR				
APN-96-5/2MHZ	SURFACE PROBE 90 DEGREES, .600" DROP 5 INCHES LONG 1-3MHz MICRODOT CONNECTOR	29P335			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPR-95-5B	SURFACE PROBE REFLECTION .187" TIP 90 DEG .500" DROP 5.0" LONG BENT 15DEG AT HANDLE 1-50KHZ, , TRIAX FISCHER CONNECTOR	SPC-514/REFL	LPR905-50B-TF-1-50		
AP95-5B/30-50KHZ	Surface Probe- Right angle bent, 5.0" inches overall length with 0.5" inch drop and 0.25" inch diameter tip. Operating frequency 1KHz -30KKHz, Triax Fischer/Lemo triax connector, bridge differential coil configuration	LS905-50B			
APN-91-65/2MHZ	SURFACE PROBE 90° .100° DROP, 6.5" LONG, 1-3MHZ MICRODOT CONNECTOR.	813P014F			
ASPN-9375-4.5/2MHZ	SURFACE PROBE SHIELDED 90 DEG .092" TIP DIA .375" TIP LENGTH 4.5 " LONG MICRODOT CONNECTOR 1-3MHz				
ATPN-92-3	SURFACE PROBE, TRIAX FISCHER CONNECTOR 90° DEGREES .200° DROP, 3.0" LONG 50-500KHz	MTF-902-30	BCMTF-902-30		
APN-903-4	SURFACE PROBE 90° DEGREES, .030" DROP, .125"Ø TIP 4.0" LONG MICRODOT CONNECTOR, 50-500KHz	PEN903-4			
APN-925-6QMDFX	SURFACE PROBE 90DEG .25 DROP 50-500KHZ QUICK DISCONNECT MICRODOT , FLEX SHAFT TUBING 6.0 INNCH				
AP92-2/6M	SURFACE PROBE TIP 8F .156 2" LENGTH				
ASTPNU-95-5C	SURFACE PROBE UNSHIELDED 90 DEG .500" CURVED .090" TIP 5.0" LONG 50-S00KHZ TRIAX FISCHER CONNECTOR	PAUBM906505C			
AXT5PN-35-5	SURFACE PROBE WITH .050" DIAMETER TUBING, 35 DEGREES .500" DROP SHAFT 5.0" LONG TRIAX FISCHER CONNECTOR 50-500KHz	TX5PEN35-5			
ATPN-6/2MHZ	SURFACE PROBE, TRIAX, 1-3MHZ				
ATPN-925-4/2MHZ	SURFACE PROBE,90 DEG .250" DROP 4.0' LONG TRIAX FISCHER 1-3MHZ	TPEN925-4/2M			
ATP-6/50khz	SURFACE PROBE, .187" OD TUBING 6.0' LONG 50KHZ DIFFERENTIAL TRIAX FISCHER CONNECTOR				•
ASPN-45-45	SURFACE PROBE, 0.092Ø, 50-500KHZ	205PFXF			
ASPN-8	SURFACE PROBE, 0.092Ø, 50-500KHZ	309P18XF			•
ASPN-45-12/2MHZ	SURFACE PROBE, 2MHz, MICRDOT, HANDLE 2.5", 1/8 SHAFT 8.5", 45° .093 SHAFT 1.0", .500 DROP	206P14F			•
AXXTPN-35-4	SURFACE PROBE, 35" DEGREES ANGLED, .062"Ø TIP, .500" DROP 50-500KHZ, TRIAX FISCHER CONNECTOR 4.0 INCHES LONG.	TSPEN35-4			
AXXTPN-45-4	SURFACE PROBE, 45" DEGREES ANGLED, .062"Ø TIP, .500" DROP 50-500KHZ, TRIAX FISCHER CONNECTOR 4.0 INCHES LONG.	TXPEN454			
AXPN-925-3	SURFACE PROBE, 50-500KHZ, 90 DEG .25 DROP 3.0" LONG MICRODOT CONNECTOR(.072" )TUBING				
AXPN94-4	SURFACE PROBE, 50-500KHZ, 90 DEG .4 DROP 4.0" LONG .073 TUBE MICRODOT CONNECTOR	MMP904-40			
AXPN95-6	SURFACE PROBE, 50-500KHZ, 90 DEG .500° DROP .073 TUBE 5.0° LONG MICRODOT CONNECTOR	MMP905			
AXPN95-3/FX	SURFACE PROBE, 50-500KHZ, 90 degree .5 drop .072 od MICRODOT	MMP905			
APN-95-6B	SURFACE PROBE, 50-500KHZ, 90°500° DROP 6.0° LONG MICRODOT CONNECTOR, BENT	MP905-60B			
APN-95-6-QMDFX	SURFACEPROBE 90 DEG .5 DROP 50-500KHZ, QUICK DISCONNECT MICRODOT, FLEX SHAFT TUBING.				
MTF901-50	SURFACE PROBE, 90" .100" DROP 5.0" LONG. TRIAX FISCHER CONNECTOR 50-500KHZ	ATPN-91-5			
UMTF901-50	SURFACE PROBE, 90" .100" DROP 5.0" LONG. TRIAX FISCHER CONNECTOR 50-500KHZ UNSHIELDED.	ATPNU-91-5			
AXXTPN-92-12/1-6MHZ	SURFACE PROBE, 90" DEGREES ANGLED062"Ø TIP .200" DROP, 12" LONG. 1-6MHZ, TRIAX FISCHER CONNECTOR	MMTF902-120-1-6M			•
AXXTPN-95-12/200KHZ-1MHZ	SURFACE PROBE, 90" DEGREES ANGLED, .062"Ø TIP .500" DROP, 12" LONG. 200KHZ-1MHZ, TRIAX FISCHER CONNECTOR	MMTF905-120-200k-1M			
AXXTPN-92-4	SURFACE PROBE, 90" DEGREES ANGLED, .062"Ø TIP .200" DROP, 50-500KHZ, TRIAX FISCHER CONNECTOR	MXTF902-40B	MXTF902-40B		
AXXTPN-92-12	SURFACE PROBE, 90" DEGREES ANGLED, .062"Ø TIP .200" DROP, 12" LONG. 50-500KHZ, TRIAX FISCHER CONNECTOR	MMTF902-120			•
AXXTPN-95-6/1-6M	SURFACE PROBE, 90" DEGREES ANGLED062"Ø TIP .500" DROP, 1-6MHz, TRIAX FISCHER CONNECTOR, 6" LONG. MZTF905-60-1-6M	MZTF905-60-1-6M	D0815E1015-2073		
AXXTPN-95-6	SURFACE PROBE, 90° DEGREES ANGLED, .062°Ø TIP .500° DROP, 50-500KHZ, TRIAX FISCHER CONNECTOR, 6° LONG	MZTF905-60	D0815E1015-2069		
AXXTPN-95-12/1-6MHZ	SURFACE PROBE, 90° DEGREES ANGLED, .062°Ø TIP .500° DROP, 12″ LONG. 1-6MHZ, TRIAX FISCHER CONNECTOR	MMTF905-120-1-6MHZ			
AF-4105/TF	Surface Probe, Standard Bridge Detachable Surface Probe with a diameter of .31 in. (7.9 mm) and a operating range of 1 kHz - 50 kHz (equivalent to SPO- 1284, SPO-1596), Triax Fischer/ LEMO Connector	9213012	SPO-1284, SPO-1596	SPO-1596	
APN-925-6-QMDFX	SURFECE PROBE SO-SOOKHZ, QUICK DISCONNECT MICRODOT				
AF-5000G	TEK-1508 HIGH FREQUENCY PROBE GUIDE 767 PT 6 57-50-08	TEK-1508H-S			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-5000H	TEK-1508 HIGH FREQUENCY PROBE HOLDER 767 PT 6 57-50-08	ТЕК-1508Н			
AF-5095	THREADED PROBE 3/8-16 1.0"DEEP WL2.5" LONG WITH TRIAX FISCHER 50-500KHZ DIFF			•	
AHS29-1T-0	Titanium(GAL-4V) Multi-hole reference standard with certificate. Contains 29 holes; 1/8", 5/32", 3/16", 7/32", 1/4", 9/32", 5/16", 11/32", 3/8", 13/32", 7/16", 15/32", 1/2", 17/32", 9/16", 19/32", 5/8", 11/32", 23/32", 3/4", 25/32", 13/16", 27/	MHS-29-1T-0			
ATMB250312	TRIAX FISCHER MANUAL BOLTHOLE PROBE. 100KHz-1MHz				
ATMB312375	TRIAX FISCHER MANUAL BOLTHOLE PROBE. 100KH2-1MHz				
ATMB375437	TRIAX FISCHER MANUAL BOLTHOLE PROBE. 100KHz-1MHz				
ATMB125156	TRIAX FISCHER MANUAL BOLTHOLE PROBE. 100KHz-1MHz				
ATMB156187	TRIAX FISCHER MANUAL BOLTHOLE PROBE. 100KHz-1MHz				
ATMB187250	TRIAX FISCHER MANUAL BOLTHOLE PROBE. 100KHz-1MHz				
ARTPX-008	Type: Rotating Probe Head - Straight Section; Model: ARTPX = Adjustable Rotating Probe for Mini Scanners, Reflection D colls (Driver Pick-up), X Type; Item Diameter: 0.375in (10mm); Tube ID: 0.375-0.437in (9.53-11.1mm); Coli: 1000=100-2000 kHz; Poly	AURX375437			
ARTPX-029	Type: Rotating Probe Head - Straight Section; Model: ARTPX = Adjustable Rotating Probe for Mini Scanners, Reflection D coils (Driver Pick-up), X Type; Item Diameter: 0.750in (19mm); Tube ID: 0.750-0.875in (19.05-22.23mm); Coil: 1000= 100-2000 kHz; Pol	ARRX750875			
ARTPX-030	Type: Rotating Probe Head - Straight Section; Model: ARTPX = Adjustable Rotating Probe for Mini Scanners, Reflection D coils (Driver Pick-up), X Type; Item Diameter: 0.875in (22mm); Tube ID: 0.875-1.000in (22.23-25.4mm); Coil: 1000=100-2000 kHz; Poly	ARRX875-1.00			
AURX-1.0-1.125/2WL	UNIVERSAL ADJUSTABLE X (SCREW) ROTARY PROBE 4 PIN FISCHER CONNECTOR WITH RANGE OF 1.0"-1.125", REFLECTION / DIFFERRENTIAL COIL CONFIGURATION 100KHZ-2MHZ. 2.0" WORKING LENGTH.	HRX1.0-1.125			
AURX-1.125-1.250/2WL	UNIVERSAL ADJUSTABLE X (SCREW) ROTARY PROBE 4 PIN FISCHER CONNECTOR WITH RANGE OF 1.125"-1.250", REFLECTION / DIFFERRENTIAL COIL CONFIGURATION 100KHZ-20HIZ. 2.0" WORKING LENGTH.				
AURX-1.375-1.500/2WL	UNIVERSAL ADJUSTABLE X (SCREW) ROTARY PROBE 4 PIN FISCHER CONNECTOR WITH RANGE OF 1.375"-1.500", REFLECTION / DIFFERRENTIAL COIL CONFIGURATION 100KHZ-2MHZ. 2.0" WORKING LENGTH.				
AURY156187/2WL	UNIVERSAL ADJUSTABLE "Y" ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .156187	URY.156187/2WL			
AURY187218/2WL	UNIVERSAL ADJUSTABLE "Y" ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .187218	URY.187218/2WL			
AURY187218/6WL	UNIVERSAL ADJUSTABLE "Y" ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH .187218	URY.187218/6WL			
AUR187SE/1.5WL	UNIVERSAL BOLT HOLE PROBE 200KHZ-1MHZ, SPLIT END FOR RA SCANNER, 1.5" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 187"218"				
AUR250SE/4.5WL	UNIVERSAL BOLT HOLE PROBE SPLIT END. 200KHZ-1MHZ, MINIMITE FISCHER SCANNER., 4.5" WORKING LENGTH (4 PIN FISCHER CONNECTOR).				
AURYFB187218/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .187"218"	URYFB187218-2			
AURYFB218250/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .218250	URYFB.218250-2			
AURYFB250312/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .250312	URYFB.250312-2			
AURYFB312375/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH 312-375	URYFB.312375-2			
AURYFB375437/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .375437	URYFB.375437-2			
AURYFB437500/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH 437"500"	URYFB.437500-2			
AURYFBF187218/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0 "WORKING LENGTH .187"-218"	URYFB187218-2			
AURYFBF250312/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0 WORKING LENGTH .250.312	URYFB.250312-2			
AURYFBF312375/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0 WORKING LENGTH .312375	URYFB.312375-2			
AURYFBF375437/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0 WORKING LENGTH .375437	URYFB.375437-2			
AURYFBF437500/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0 WORKING LENGTH .437500	URYFB.437500-2			
AURYFBF218250/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE SHIELDED100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .218250	URYFB.218250-2			
AURFB475SE	UNIVERSAL FLAT BOTTOM ROTATING PROBE, SPLIT -END, 100KHZ-2MHZ 2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR.				
AURYF156187/2WL	UNIVERSAL ROTARY ADJUSTABLE "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .156187	URY.156187/2WL			
AURYF187218/2WL	UNIVERSAL ROTARY ADJUSTABLE "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .187218	URY.187218/2WL			
AURYF187250/2WL	UNIVERSAL ROTARY ADJUSTABLE "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .187250	URY.187250/2WL			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURYF250312/2WL	UNIVERSAL ROTARY ADJUSTABLE "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .250312	URY.250312/2WL			
AURYF312375/2WL	UNIVERSAL ROTARY ADJUSTABLE "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .312375	URY.312375/2WL			
AURYF375437/2WL	UNIVERSAL ROTARY ADJUSTABLE "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .375437	URY.375437/2WL		•	•
AURYF-375437/2WL	UNIVERSAL ROTARY ADJUSTABLE "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .375437	URY.375437/2WL		•	
AURYF437500/2WL	UNIVERSAL ROTARY ADJUSTABLE "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .437500	URY.437500/2WL		•	
AURYF500625/2WL	UNIVERSAL ROTARY ADJUSTABLE "Y" PROBE SHIELDED 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .500625	URY.500625/2WL		•	
AURFB628SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45DEG .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ-2MHZ	•			
AURFB590/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45DEG .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LONG 100KHZ-2MHZ			•	
AUR843SE/2.0WL	Universal Rotary Hole Probe 0.843 inch (21.41 mm) to 0.875 inch (22.22 mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration (.843-875)			•	
AUR125SE/1.3WL	Universal Rotary Hole Probe 0.125 inch (3.18mm) to 0.156 inch (3.96mm) diameter, Self Expanding 1.3 inch (33 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration (.125"156")	SPO-5965, 9230531	RTP-013	•	
AUR125SE/1.75WL	Universal Rotary Hole Probe 0.125 inch (3.18mm) to 0.156 inch (3.96mm) diameter, Self Expanding 1.75 inch (44 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration (.125"156")	SPO-5965, 9230531	RTP-013	•	
AUR343SE/4.0WL	Universal Rotary Hole Probe 0.343 inch (8.71 mm) to 0.3 inch (9.52 mm) diameter, Self Expanding 4 inch (101.6 mm) working length, Operating frequency 100khz-2MHZ MHz Fischer 4 pin connector, reflection differential coil configuration (.343375)				
AUR468SE/2.0WL	Universal Rotary Hole Probe 0.468" inch (11.87mm) to 0.500" inch (12.7mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration (.468"500")	SPO-5965	RTP-033	SPO-5965	
AUR562SE/2.0WL	Universal Rotary Hole Probe 0.562 inch (14.27mm) to 0.625 inch (15.87mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration (.562"-625")	SPO-5965, 9230156	RTP-009		
AUR593SE/2.0WL	Universal Rotary Hole Probe 0.593 inch (15.06mm) to 0.625 inch (15.87mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration (.562"625")	RTP-035		•	
AUR625SE/2.0WL	Universal Rotary Hole Probe 0.625 inch (15.87mm) to 0.687 inch (17.45mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration (.625"-687").	SPO-5965, 9230157	RTP-010	•	
AUR650SE/2.0WL	Universal Rotary Hole Probe 0.650 inch (16.51mm) diameter, Self Expanding 2 inch (50 mm) working length, frequency 100 kHz - 2MHz Fischer 4 pin connector, reflection differential coil configuration (.625"650")				
AUR656SE/2.0WL	Universal Rotary Hole Probe 0.656 inch (16.66mm) to 0.687 inch (17.45mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration (.625°-687″)	•	RTP-036	•	
AUR687SE/2.0WL	Universal Rotary Hole Probe 0.687 inch (17.45mm) to 0.750 inch (19.3mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration (.687"750").	SPO-5965, 9230158	RTP-011	•	
AUR718SE/2.0WL	Universal Rotary Hole Probe 0.718 inch (18.23mm) to 0.750 inch (19.3mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration (.687"750").	RTP-037			
AUR750SE/2.0WL	Universal Rotary Hole Probe 0.750 inch (19.0 mm) to 0.812 inch (20.6 mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 100 kHz - 2MHz Fischer 4 pin connector, reflection differential coil configuration (.750812)	SPO-5965, 9230159	RTP-012	SUB-48-52	
AUR750SE/4.0WL	Universal Rotary Hole Probe 0.750 inch (19.0 mm) to 0.812 inch (20.6 mm) diameter, Self Expanding 4 inch (100 mm) working length, Operating frequency 100 kHz - 2MHz Fischer 4 pin connector, reflection differential coil configuration (.750-812)	•		•	
AUR875SE/2.0WL	Universal Rotary Hole Probe 0.875 inch (22.22 mm) to 0.937 inch (23.80 mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coli configuration (.875-937)	SPO-9565, 9231090	9231090	SUB-48-52	
AUR937SE/2.0WL	Universal Rotary Hole Probe 0.937 inch (23.80 mm) to 1.0 inch (25.40 mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration (.937-1.0)				
AUR-1.00SE/2.0WL	Universal Rotary Hole Probe 1.000" inch (25.4 mm) to 1.125" inch (28.58 mm) diameter, Self Expanding 2.0 inch (51 mm) working length, Operating frequency 100 kHz - 2MHz Fischer 4 pin connector, reflection differential coli configuration (1.000"-1.125")	•			-
AUR-1.00SE/4.0WL	Universal Rotary Hole Probe 1.000" inch (25.4 mm) to 1.125" inch (28.58 mm) diameter, Self Expanding 4 inch (100 mm) working length, Operating frequency 100 kHz - 2MHz Fischer 4 pin connector, reflection differential coil configuration (1.000"-1.125")				
AUR250SE/3OAL	Universal Rotary Hole Probe Self expanding from 0.250 inch (6.35 mm) to 0.281 inch (7.14 mm) diameter, 3.0" inch (76.2mm) Overall length with a 2.0 inch working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differentia	•			
AUR250SE/4.0WL	Universal Rotary Hole Probe Self expanding from 0.250 inch (6.35 mm) to 0.281 inch (7.14 mm) diameter, 4.00 inch (101.6 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Include				
AUR250SE/5OAL	Universial Rotary Hole Probe Self expanding from 0.250 inch (6.35 mm) to 0.281 inch (7.14 mm) diameter, 5.0 inch (127mm) overall length with a 4.0" working length, 5.0" Overall Length. Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflect				
AUR281SE/5OAL	Universal Rotary Hole Probe Self expanding from 0.281 inch (7.14 mm) to 0.312 inch (7.92 mm) diameter, 5.0 inch (127mm) overall length with a 4.0" working length, 5.0" Overall length. Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflect				
AUR312SE/5OAL	Universal Rotary Hole Probe Self expanding frequency 100 ktr 2 mm to 0.343 inch (8.71 mm) diameter, 5.0 inch (127mm) overall length with a 4.0" Working length, 5.0" Overall Length. Operating frequency 100 ktr 2 MHz Fischer 4 pin connector, reflect				
AUR343SE/2.0WL	Universal Rotary Hole Probe Self Expanding From 0.343 inch (7.9 mm) to 0.375 inch (9.52 mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 100khz-2MHZ MHz Fischer 4 pin connector, reflection differential coll configuration	SPO-3565	RTP-031		
AUR343SE/5OAL	Universal Rotary Hole Probe Self expanding from 0.343 inch (8.71 mm) to 0.375 inch (9.525 mm) diameter, 5.0 inch (127mm) overall length with a 4.0" working length, 5.0" Overall Length. Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflec				
AUR375SE/5OAL	Universal Rotary Hole Probe Self expanding from 0.375 inch (9.525 mm) to 0.406 inch (10.31 mm) diameter, 5.0 inch (127mm) overall length with a 4.0" working length, 5.0" Overall Length. Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, refle				
AUR875SE	Universal Rotary Hole Probe Self Expanding from 0.875 inch (22.22 mm) to 0.937 inch (23.80 mm) diameter, 2 inch (50 mm) working length, Operating frequency 100 kHz - 2 MHz With a Fischer 4 pin connector, reflection differential coli configuration (.87				
·			1	1	

## AeroFab NDT LLC

PART NUMBER	DECONDICAL	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR187SS/2WL	DESCRIPTION UNIVERSAL ROTARY PROBE .187" DIA. HEAD, STAINLESS STEEL, 100KHZ-2MHZ, 2.0" WORKING LENGTH, 4PIN FISCHER CONNECTOR	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR18755/65MWL	UNIVERSAL ROTARY PROBE .187" DIA. HEAD, STAINLESS STELLE, 100KHZ-2MHZ, 2:0 WORKING LENGTH, 4PIN FISCHER CONNECTOR	615P012F065	•	•	
AUR387 SE/27.0"	UNIVERSAL ROTARY PROBE .387"417" 27.0" LONG 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ			*	
AUR900SE/43WL	UNIVERSAL ROTARY PROBE .900"-1.0", 43.0" LONG 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ		·	*	
AUR437/27.0"	UNIVERSAL ROTARY PROBE 100K-2MHZ 27.0" LONG 4 PIN FISCHER CONNECTOR		·		
AUR.125/1.1WL	UNIVERSAL ROTARY PROBE 100KHZ -22MHZ, 1.1"WL, 4PIN FISCHER	BPFM-8	•	•	
AUR.1255E/1.1WL	UNIVERSAL ROTARY PROBE 100kHZ -20MHZ, 1.1 WL, 4PIN FISCHER	BPEM-8	BPEM-8		
AURY-1.125-1.250	UNIVERSAL ROTARY PROBE 100ARE -20MR2, 1.1 WL, 4FIN FISCHER	URY1.125-1.375	DFEIVI-0		-
			•	•	
AURY-1.250-1.375	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ	URY1.125-1.375			
AURY-1.50-1.625	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ	URY1.150-1.625			
AURY625750	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .625750	URY.625687			
AURY875937	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .875-937				
AURY937-1.0	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .937-1.0				
AURY156187/2M	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 1.3" WORKING LENGTH	BYU-12/16/2M			
AURY187250/2M	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 1.3" WORKING LENGTH				
AURY-1.00-1.063	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 2.0" WL MINIMITE 4 PIN FISCHER				-
AURY938-1.0	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER 2.0" WL				
AURY875938	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER 2.0"WL				
AURY875984/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER 3.0" WL	URY.875984			
AURY890984/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER 3.0"WL	URY.890984			
AURY890-1.0/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER 3.0"WL	URY.890-1.0			
AURY156187/3.50AL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 3.5" OVERALL LENGTH .156"187"				
AURY187250/3.50AL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 3.5" OVERALL LENGTH .187"250"				
AURY250312/3.50AL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 3.5" OVERALL LENGTH .250"312"				
AURY312375/3.50AL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 3.5" OVERALL LENGTH .312"375"				
AURY375437/3.50AL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 3.5" OVERALL LENGTH 375"437"				
AURY500625/3.50AL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 3.5" OVERALL LENGTH500"625"				
AURY500562/4WL	UNIVERSAL ROTARY PROBE 100khz-2mhz 4 PIN FISCHER CONNECTOR 4.0" WORKING LENGTH				
AURY953-1.04/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4PIN FISCHER 3.0"WL	URY.953-1.04			
AURY796890/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4PIN FISCHER 3.0"WL	URY.796890			
AURY215250/1.5WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ REFLECTION / DIFFERENTIAL,4 PIN FISCHER, 1.5WL				
AURY247312/1.5WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ REFLECTION / DIFFERENTIAL,4 PIN FISCHER, 1.5WL				
AUR-1.125/3WL	UNIVERSAL ROTARY PROBE 100KHz-2MHz, 1.125"Ø, 3.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR. 100KHz-2MHz	BPU-72/3WL			
AURY563626/2WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 2"WL	URY.187250 , BYU-12/16			
AURY626689/2WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 2"WL	URY.187250 , BYU-12/16			
AURY752815/2WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 2"WL	URY.187250 , BYU-12/16			-
					•

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURY815878/2WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 2"WL	URY.187250 , BYU-12/16			
AURY878941/2WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 2"WL	URY.187250 , BYU-12/16			
AURY689752/2WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 2"WL 4 PIN FISCHER	URY.187250 , BYU-12/16			
AURX-3.07-3.19/3.5WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 3"WL				
AURY625687/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4"WL	URY.500-625			
AURY687750/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4"WL	URY.500-625	•		
AURY-1.0-1.125/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4"WL	URY1.0-1.125			
AURY875-1.0/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4"WL 4 PIN FISCHER	URY.500-625			
AURY750875/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4"WL 4PIN FISCHER	URY.500-625			a
AURY312375/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4.0 <sup>°</sup> WL 4 PIN FISCHER	URY.312375	•		
AURY-22M-25M/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4WL 4PIN FISCHER CONNECTOR	RSMVS20-25			
AURY-20M-22M/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4WL,4 PIN FISCHER CONNECTOR	RSMVS20-25			
AUR875/3WL	UNIVERSAL ROTARY PROBE 100KHz-2MHz, 875"Ø, 3.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR. 100KHz-2MHz	BPU-56/3WL			a
AURY187218/1.5WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ,4 PIN FISCHER CONNECTOR 1.5WL		•		
AURY375437/1.5WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ,4 PIN FISCHER CONNECTOR 1.5WL				
AURY437500/1.5WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ,4 PIN FISCHER CONNECTOR 1.5WL				
AURY437500/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ. 4.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR				
AURY250312/2WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ- 2.0 WORKING LENGTH, 4 PIN FISCHER CONNECTOR	URY.250312			
AURY500563/2WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ- 2.0 WORKING LENGTH, 4 PIN FISCHER CONNECTOR	URY.187250 , BYU-12/16			
AURY625750/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ. 3.0 WORKING LENGTH, 4 PIN FISCHER CONNECTOR	URY625750			
AURY750875/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ. 3.0 WORKING LENGTH, 4 PIN FISCHER CONNECTOR	URY.750875			
AURY875-1.0/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ. 3.0 WORKING LENGTH, 4 PIN FISCHER CONNECTOR	URY.875-1.0			
AURY-1.250-1.375/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ. 3.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR				
AURY-1.375-1.500/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ. 3.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR				
AURY-1.500-1.625/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ. 3.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR				
AURY-1.625-1.750/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ. 3.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR				
AURY156187/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ. 4.0 WL, 4PIN FISCHER				
AURY375437/4WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ. 4.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR	URY.375437			
AURY626689/2M	UNIVERSAL ROTARY PROBE 1-3MHZ	URY.187250, BYU-12/16			
AURY250312/2M	UNIVERSAL ROTARY PROBE 1-3MHZ 2.0" WL 4 PIN FISCHER				
AURY312375/2M	UNIVERSAL ROTARY PROBE 1-3MHZ 2.0"WL 4 PIN FISCHER	URY.312375 , BYU-12/16			
AURY375437/2MHZ	UNIVERSAL ROTARY PROBE 1-3MHZ 2.0"WORKING LENGTH 4PIN FISCHER CONNECTOR				
AURY437500/2M	UNIVERSAL ROTARY PROBE 1-3MHZ 4 PIN FISCHER	URY.187250 , BYU-12/16			
AURY563626/2M	UNIVERSAL ROTARY PROBE 1-3MHZ 4 PIN FISCHER	URY.187250, BYU-12/16			
AURY689752/2M	UNIVERSAL ROTARY PROBE 1-3MHZ 4 PIN FISCHER	URY.187250 , BYU-12/16			
		1			

## AeroFab NDT LLC

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURY752815/2M	UNIVERSAL ROTARY PROBE 1-3MHZ 4 PIN FISCHER	URY.187250 , BYU-12/16			
AURY815878/2M	UNIVERSAL ROTARY PROBE 1-3MHZ 4 PIN FISCHER	URY.187250 , BYU-12/16			
AURY500625/2M	UNIVERSAL ROTARY PROBE 1-3MHZ 4PIN FISCHER	URY.187250 , BYU-12/16			
ARRY625750/2M	UNIVERSAL ROTARY PROBE 1-3MHZ 4PIN STEP LEMO CONNECTOR, 2.0"WL				
AURY878941/2M	UNIVERSAL ROTARY PROBE 1-3MHZ4 PIN FISCHER 20" WL	URY.187250, BYU-12/16			
AURY500625/2WL	UNIVERSAL ROTARY PROBE 2.0" WORKING LENGTH 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR	URY.500625			
AUR-4.8M/100MWL	UNIVERSAL ROTARY PROBE 4.8MM DIA 100MM WORKING LENGTH ( PLASTIC BODY) 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ				
AURY-15M-20M	UNIVERSAL ROTARY PROBE ADJUSTABLE 15MM-20MM 2.0" WORKING LENGTH 10KHZ-2MHZ 4 PIN FISCHER CONNECTOR		•		
AURY-20M-25M	UNIVERSAL ROTARY PROBE ADJUSTABLE 20MM-25MM 2.0" WOKING LENGTH 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR				
AUR 4.7M/SS	UNIVERSAL ROTARY PROBE FOR MINI ELOTEST, HOCKING 2.0WL 100KHZ-2MHZ	UR 4.7M/SS			
AUR 6.2M/SS	UNIVERSAL ROTARY PROBE FOR MINI ELOTEST, HOCKING 2.0WL 100KHZ-2MHZ	UR 6.2M/SS			
AUR 7.8M/SS	UNIVERSAL ROTARY PROBE FOR MINI ELOTEST, HOCKING 2.0WL 100KHZ-2MHZ	UR 7.8M/SS			
AURYF218250	UNIVERSAL ROTARY PROBE SHIELDED 100KHZ-2MHZ, 4PIN FISCHER CONNECTOR 1.3" WORKING LENGTH				
AURYF187218	UNIVERSAL ROTARY PROBE SHIELDED 100KHZ-2MHZ, 4PIN FISCHER CONNECTOR 1.3" WORKING LENGTH.				
AURYF312375/7WL	UNIVERSAL ROTARY PROBE SHIELDED, EXPANDABLE FROM .312"375"Ø, 100KHz-2MHz, 4 PIN FISCHER CONNECTOR, 1.7" WORKING LENGTH.	URYF312375/7WL			
AURYF375437/7WL	UNIVERSAL ROTARY PROBE SHIELDED, EXPANDABLE FROM .375"437"Ø, 100KHz-2MHz, 4 PIN FISCHER CONNECTOR, 1.7" WORKING LENGTH.	URYF375437/7WL			
AURYF437500/7WL	UNIVERSAL ROTARY PROBE SHIELDED, EXPANDABLE FROM .437"500"Ø, 100KHz-2MHz, 4 PIN FISCHER CONNECTOR, 1.7" WORKING LENGTH.	URYF437500/7WL			
AUR1406SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER.039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR1718SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER.039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR2031SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ		•		
AUR2343SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR2656SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR2812SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR2968SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ		•		
AUR3281SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER.039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR3437SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR3593SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR4062SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5 " WORKING LENGTH COIL DIAMETER.039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR3906SS/1.5WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 1.5" WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR375SS/2.0WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 2.0 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR2812SS/2.0WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 2.0 " WORKING LENGTH COIL DIAMETER.039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR2968SS/2.0WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 2.0 " WORKING LENGTH COIL DIAMETER.039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				-
AUR3125SS/2.0WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 2.0 " WORKING LENGTH COIL DIAMETER.039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR3281SS/2.0WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 2.0 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ		•		
AUR3437SS/2.0WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 2.0 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ		•		
AUR3593SS/2.0WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 2.0 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ		•		

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR3906SS/2.0WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 2.0 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ			•	
AUR4062SS/2.0WL	UNIVERSAL ROTARY PROBE STAINLESS STEEL 2.0 " WORKING LENGTH COIL DIAMETER .039" 4 PIN FISCHER CONNECTOR 100KHZ -2MHZ				
AUR.312SS/2WL	UNIVERSAL ROTARY PROBE, STAINLESS STEEL, 100KHZ-2MHZ, 2"WL, 4PIN FISCHER CONNECTOR,	NA			
AUR.375SS/2WL	UNIVERSAL ROTARY PROBE, STAINLESS STEEL, 100KHZ-2MHZ, 2"WL, 4PIN FISCHER CONNECTOR,		•		
AUR.437SS/2WL	UNIVERSAL ROTARY PROBE, STAINLESS STEEL, 100KHZ-2MHZ, 2"WL, 4PIN FISCHER CONNECTOR,		•		
AUR.500SS/2WL	UNIVERSAL ROTARY PROBE, STAINLESS STEEL, 100KHZ-2MHZ, 2"WL, 4PIN FISCHER CONNECTOR,				
AUR.562SS/2WL	UNIVERSAL ROTARY PROBE, STAINLESS STEEL, 100KHZ-2MHZ, 2"WL, 4PIN FISCHER CONNECTOR,		•		
AUR.625SS/2WL	UNIVERSAL ROTARY PROBE, STAINLESS STEEL, 100KHZ-2MHZ, 2"WL, 4PIN FISCHER CONNECTOR,				
AUR.250SS/2WL	UNIVERSAL ROTARY PROBE, STAINLESS STEEL, 100KHZ-2MHZ, 2.0" WORKING LENGTH, 4PIN FISCHER CONNECTOR	NA			
AUR153SS/50M	UNIVERSAL ROTARY STAINLESS STEEL PROBE .153" OD 50 MM WL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ	615P098M050	•		
AURX-1.567/5WL/2MHZ	UNIVERSAL ROTARY X-PROBE 1.567" OD 5.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR 1-3MHZ USED WITH (P8-STD-P039)		•		
AURCS100205	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHz-2MHz 4-PIN FISCHER CONNECTOR205"Ø		•		
ACSU100218	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHz-2MHz 4-PIN FISCHER CONNECTOR218"Ø	CSU100-14			
AURCS100375	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHz-2MHz 4-PIN FISCHER CONNECTOR375°Ø	UC1.375	CSU100-24		
AURCS100390	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHz-2MHz 4-PIN FISCHER CONNECTOR390"Ø				
ACSU100-5.0M	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHz-2MHz 4-PIN FISCHER CONNECTOR. 5.0M(.197")Ø	CSU100-5.0M	CSEM100-5.0M		
AURCS100202	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100264	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100281	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100327	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100343	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100389	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100437	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100452	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100467	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100500	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100514	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100530	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100562	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100576	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100592	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR				
AURCS100250/4WL	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR, 4.0" WORKING LENGTH	CSU100-12-4.0WL			
AURCS100142	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KH2-2MHZ . 4 PIN FISCHER CONNECTOR . 142" $\phi$		•		
AURCS100173	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR . 173"Ø				
AURCS100406	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR. 406"Ø		•		
AURCS100407	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR. 407"Ø				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURCS100469	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHZ-2MHZ . 4 PIN FISCHER CONNECTOR469"Ø				
AURCS100312	UNIVERSAL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK 100KHz-2MHz. 4-PIN FISCHER CONNECTOR	UC1.312			•
AURCB187SS/1.5WL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER COUNTERBORE PROBE FOR SURFACE INSPECTION, (3/16" - 7/32")100KHz-2MHz, 4 PIN FISCHER CONNECTOR,1.5" WORKING LENGTH. 9222392	SPO-6636	9222392		<u>.</u>
AURCB156SS/1.5WL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER COUNTERBORE PROBE FOR SURFACE INSPECTION, (5/32" - 3/16")100KHz-2MHz, 4 PIN FISCHER CONNECTOR,1.5" WORKING LENGTH. 9222391	SPO-6635	9222391		
AURCS100250SS/1.5WL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100° DEGREES COUNTERSINK (1/4")100KHz-2MHz, 4 PIN FISCHER CONNECTOR,1.5" WORKING LENGTH.	9222389	SPO-5787		
AURCS100187SS/1.5WL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100° DEGREES COUNTERSINK (3/16″)100KHz-2MHz, 4 PIN FISCHER CONNECTOR, 1.5″ WORKING LENGTH.	9222387	SPO-5787		
AURCS100312SS/1.5WL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100° DEGREES COUNTERSINK (5/16″)100KHz-2MHz, 4 PIN FISCHER CONNECTOR, 1.5″ WORKING LENGTH.	9222390	SPO-5787		
AURCS100156SS/1.5WL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100° DEGREES COUNTERSINK (5/32″)100KHz-2MHz, 4 PIN FISCHER CONNECTOR, 1.5″ WORKING LENGTH.	9222386	SPO-5787		
AURCS100218SS/1.5WL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100° DEGREES COUNTERSINK (7/32″)100KHz-2MHz, 4 PIN FISCHER CONNECTOR, 1.5″ WORKING LENGTH.	9222388	SPO-5787		•
AUR750SS/2.0WL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ- 2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR, .750"Ø	615P048F051	.615P048F051	UR.750SS	
AUR562SS/2.0WL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ- 2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. USED WITH 40A100 SCANNER. 562"Ø	UR.562SS			
AUR.625SE/2WL	UNIVERSIAL ROTARY PROBE, 100KHZ-2MHZ, 4 PIN FISCHER, 2"WL	RR.625SE/2WL			
AF-4204G	V-SHAPED PROBE GUIDE FOR A 0.175" RADIUS CONVEX SURFACE INSPECTION. USED WITH AF-4204 SPOT PROBES				
AF-5085/600KHZ	WELD PROBE 5MM DIA XSOMM L WITH TRIAX CONNECTOR 200-600KHZ				
AWP-3-1674	WHEEL PROBE FOR GOODRICH MAIN WHEEL 3-1674. DIIFFERENTIAL/ BRIDGE, 50-500KHz, WITH TRIAX FISCHER CONNECTOR.	3-1674			
AWP-SD3-60	WHEEL PROBE FOR SHORTS SD3-60 MAIN WHEEL 2MHz TRIAX FISCHER CONNECTOR DIIFF/ BRIDGE				
APN-910-4FX	FLEXIBLE SURFACE PROBE 50-500KHZ	MP9010-40			
APN-91-10FX	FLEXIBLE SURFACE PROBE 50-500KHZ	PENFLX91-10			
APNU-45-5	RIGID SURFACE PROBE 45" .500" DROP 50-500KHZ, UNSHIELDED WITH MICRODOT CONNECTOR, 5.0" LONG				
APNU-45-6	RIGID SURFACE PROBE 45" .500" DROP 50-500KHZ, UNSHIELDED WITH MICRODOT CONNECTOR, 6.0" LONG	VM204A-6	VM204A-6		
APNU-45-6/2M	RIGID SURFACE PROBE, 45" DEGREES CRANKED, .500" DROP, 5.0" LONG, WITH MICRODOT CONNECTOR, 1-3MHz.	DPT45U			
APN-98-95FX	SURFACE FLEXIBLE PROBE 90 DEG .800"DROP 9.5" LONG MICRODOT CONNECTOR 50-500KHZ	MP908-95FX			
APN-995-95FX	SURFACE FLEXIBLE PROBE 90 DEG .950" DROP 9.5" LONG MICRODOT CONNECTOR 50-500KHZ	MP9095-95FX			
APN-910-10	SURFACE PROBE 50-500KHZ	MP9010-40			
APN-910-4	SURFACE PROBE 50-SOOKHZ	MP9010-40			
APNU-3/2M	SURFACE PROBE, UNSHIELDED, 1-3MHZ	PENU-3/2M	UMP-30		
APNU-6/2M	SURFACE PROBE, UNSHIELDED, 1-3MHZ	PENU-3/2M	UMP-30		
APNU-3	SURFACE PROBE, UNSHIELDED, 50-500KHZ, .187"Ø TUBING, MICRODOT CONNECTOR 3.0" LONG	SPC-545	UMP-30		
APN-2/4F/500K-1MHZ	SURFACE PROBE 1.25" LONG TIP STRAIGHT 2.0" LONG 4 PIN FISCHER CONNECTOR 500K-1MHZ	•			
APN-2/4F	SURFACE PROBE 1.25" LONG TIP STRAIGHT 2.0" LONG 4 PIN FISCHER CONNECTOR 50-500KHZ	•			
APN-903-3/4L	RIGID SURFACE PROBE ABSOLUTE SHIELED .125"Ø TUBING 90" DEGREES , .030" DROP 3.0" LONG WITH 4 PIN LEMO CONNECTOR 20-200KHz	300P13F	611-084-001		
APNU-45-5/2M	SURFACE PROBE 45", .500" DROP UNSHIELDED, TRIAX FISCHER CONNECTOR, 1-3MHZ. 5.0" LONG.	VM204A-6	VM204A-6		
APN-95-3.5/7L	RIGID SURFACE PROBE 50-500KHZ 90 DEG .500" DROP 3.5" LONG 7 PIN LEMO CONNECTOR .125" TIP				
APN-4/7L/6M	Bridge Absolute shielded metal shaft 7 Pin LEMO "PowerLink" detachable pencil probe. Operates on a 1 MHz - 6MHz frequency range and has a center frequency of 2 Mhz. Straight shaft with a 0.125 in. diameter tip. 4 in. overall length	9403404			
APN-4/7L/500K	Bridge Absolute shielded metal shaft 7 Pin LEMO "PowerLink" detachable pencil probe. Operates on a 200 kHz - 1 MHz frequency range and has a center frequency of 500 kHz. Straight shaft with a 0.125 in. diameter tip. 4 in. overall length	9403403	U8629527		
APN-4/7L	POWER LINK METAL SHAFT SURFACE PENCIL PROBE .125" DIA TUBING 4 .0" LONG 7 PIN LEMO CONNECTOR (POWER LINK) 50-500KHZ	ML/50-500KHZ/A/0.0/4	9403359	U8629526	

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
APN-4/7L/500KHZ	POWER LINK METAL SHAFT SURFACE PROBE .125" DIA TUBING 4 .0" LONG 7 PIN LEMO CONNECTOR 200KHZ-1MHZ		9403403	U8629527	
APN-95-6/7L	Bridge Absolute Shielded Metal Detachable Pencil Probe. 7 Pin Fischer/LEMO "PowerLink", Operates on a 50 kHz - 500 kHz and has a center frequency of 200 kHz, Right Angle Shaft, 0.50 in. (12.7 mm) drop with a 0.125 in. diameter tip. 6 in. overall length.	9403410	9403410		•
APN-95-6C/7L	Eddy Current Surface Probe 90° degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long, 50-500 kHz with 7 Pin Lemo Connector.	9222164	U8616093		
APN-93-6/7L/500KHZ	POWER LINK METAL SHAFT RIGHT ANGLE SURFACE PROBE .125" DIA TUBING .6.0" LONG 7 PIN LEMO CONNECTOR 200KHZ-1MHZ	M7L90-60-200K-1MHZ	9403447		
APN-903-6/7L	SURFACE PROBE .030 DROP 6.0" LONG 7 PIN LEMO OB SIZE 50-500KHZ	9403405			
APN-925-6B/7L	SURFACE PROBE 50-S00KHZ, BENT, 7PIN LEMO	•			
APN-903-4/7L	SURFACE PROBE 90" DEGREES, .030" DROP 4.0" LONG 7 PIN LEMO CONNECTOR (.125" TIP) 500KHZ-1MHZ	•			
APN-6/7L	SURFACE PROBE 50-SOOKHZ 7 PIN LEMO		•		
APN-8FX/7L/1-6MHZ	FLEXIBLE SURFACE PROBE 1-6MHZ 8", 7PIN LEMO	9403503			
ATPN-4/.050	STRAIGHT SURFACE PROBE .050 " DIA TUBING TRIAX FISCHER CONNECTOR 4.0" LONG 50-500KHZ	TXPEN-4			
ATPN-92-4B/1-6MHZ	ABSOLUTE BRIDGE. RIGID SURFACE PROBE WITH .1250 <sup>o</sup> (3.2mm) DIAMETER TUBING, 90° DEGREES .200° DROP BENT SHAFT .984°[25.0mm) FROM THE TIP, 1.378° LONG FROM THE HANDLE BEFORE THE .984°[25.0mm) BEND, 4.0° TOTAL LENGTH WITH TRIAX FISCHER CONNECTOR. 1-6MHz	MTF902-40B			
ATPN-92-4B	ABSOLUTE BRIDGE. RIGID SURFACE PROBE WITH .1250 <sup>6</sup> (3.2mm) DIAMETER TUBING, 90° DEGREES .200° DROP BENT SHAFT .984°[25.0mm) FROM THE TIP, 1.378° LONG FROM THE HANDLE BEFORE THE .984°[25.0mm) BEND, 4.0° TOTAL LENGTH WITH TRIAX FISCHER CONNECTOR. 50-500K	PAB90C402			
ATPN-65-6C	Eddy Current Surface Probe 60 degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long, 50-500 kHz with Triax Fischer Connector				
ATPN-95-6C	Eddy Current Surface Probe 90° degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long, 50-500 kHz with Triax Fischer Connector	9222164	VM202A-6		
ATPN-125-6C	Eddy Current Surface Probe120 degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long 50-500 kHz with Triax Fischer Connector				
ATPN92-10FX/2M	FLEXIBLE SURFACE PROBE 1-3MHZ, 90 DEG TRIAX CONN .200 DROP,10 INCH LONG	•			
ATPN45-7FX/500K	FLEXIBLE SURFACE PROBE 45 DEGREES .500" DROP, .130" DIA. TRIAX FISCHER CONNECTOR, 500KHZ-1MHZ, 7.0" LONG				
ATPN45-7FX	FLEXIBLE SURFACE PROBE 45 DEGREES .500" DROP, .130" DIA. TRIAX FISCHER CONNECTOR, 50-500KHZ, 7.0" LONG	•			
ATPNU-12FX	FLEXIBLE SURFACE PROBE, 50-500KHZ, TRIAX, UNSHIELDED				
ATPNU-3FX	FLEXIBLE SURFACE PROBE, TRIAX 50-500 KHZ, UNSHIELDED				
ATPNU-5FX	FLEXIBLE SURFACE PROBE, TRIAX 50-500 KHZ, UNSHIELDED				
ATPNU-95-5FX	FLEXIBLE SURFACE PROBE, TRIAX 50-500 KHZ, UNSHIELDED	•			
ATPNU-92-5FX	FLEXIBLE SURFACE PROBE, TRIAX 50-500 KHZ, UNSHIELDED, 5"L	UMTF902-50			
ATPNU-9FX/2MHZ	FLEXIBLE SURFACE PROBE, TRIAX, 1-3MHZ UNSHIELDED, 9"L	UMTF902-50			
ATPN-92-10FX/2MHZ	SURFACE PROBE SHEILDED 90 DEG .200" DROP COOPER FLEX SHAFT TRIAX CONN 10"LONG 1-3MHZ				
ATPN-92-12.5FX/2MHZ	SURFACE PROBE 90 DEG .200"DROP 10"WL COOPER PLEX SHAFT TRIAX CONN 1-3 MHZ TOTAL HEIGHT .325"				
ATPN-45-7FX/500K	SURFACE PROBE, 45" DEGREE .500" DROP 7.0" LONG TRIAX FISCHER CONNECTOR500KHZ-1MHZ				
ATPN-910-6/2MHZ	SURFACE PROBE, TRIAX 1-3MHZ				
ATPN-975-6FX/500K	FLEXIBLE SURFACE PROBE 90DEG .750" DROP 6.0" INCH LONG 200KHZ-1MHZ, TRIAX FISCHER CONNECTOR				
ATPN-8FX/2M	FLEXIBLE SURFACE PROBE STRAIGHT, TRIAX FISCHER CONN 8.0" LONG 1-3 MHZ	•			
ATPN-4.5/1-20KHZ	LOW FREQUENCY SURFACE PROBE, TRIAX 1-20KHZ, 4.5"L, .187OD	•	•		
ATPN-95-5/3-6MHZ	RIGID SURFACE PROBE ,90 DEG .500" DROP 5.0" LONG TRIAX FISCHER CONNECTOR, 3-6 MHZ	•			
ATPN-92-5/3-6MHZ	RIGID SURFACE PROBE 90" DEGREES, .200" DROP, 125"Ø O.D. TIP 5.0" LONG, TRIAX FISCHER CONNECTOR 3-6 MHZ.	•			
ATPN-903-5.5B/1.0	RIGID SURFACE PROBE,1/8"Ø DIAMETER TUBING, .030" DROP, BENT 20" AT 1.0" FROM THE TIP. 5.5" LONG TRIAX FISCHER CONNECTOR 50-500KHz	KAS34H132-44-1	KAS 34H132-44-1	KAS-34H132-44-1	
ATPN-95-5/7L/6MHZ	SURFACE PROBE, 90 DEGREES .500" DROP 5.0" LONG 7 PIN LEMO CONNECTOR 6 MHZ. :125" TIP				
/					

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPN-925-9B	SURFACE PROBE 90 DEG .250" DROP, BENT 30° 1.0" FROM THE TIP, 9.0" LONG, 50-500KHZ TRIAX FISCHER CONNECTOR	VM219-1/4x9			
ATPN-4510-4.25/.050	SURFACE PROBE 45* 1.0" DROP, .050" TIP DIAMETER, 50-500KHZ, 4.25" LONG. TRIAX FISCHER CONNECTOR	•		•	•
ATPN-45-6/.062	SURFACE PROBE 45DEG .500" DROP .062" DIA TIP TRIAX CONN 6.0" LONG 50-500KHZ	NA	NA	VM141-734WS/M	NA
APN-95-6/.250	SURFACE PROBE 1-S0KHZ, REFLECTION, MICRODOT CONNECTOR, .2500D, .500DROP, 6.0"AL				
APN-15	TRANSDUCER 15MHZ STRAIGHT PEN, W/ REPLACEABLE DELAY TIP				
ARP250/1.1-500HZ-5K	Handheld Detachable Probe w/o Cable; Model: RNG = Detachable Ring Probe with Reflection (Driver Pick-up Colis); Item Diameter: 0.250in (6.4mm); Tube ID: ; Coli! #= Special; Poly Type: None; Length: No cable; Connector: 1 Pin Female Triaxial Connecto	RNG-002			
ASPN-4FX/L00/200K-1M	Surface probe, 4 inches long(10.1cm), measurement tubing diameter 0.072" Ø inch (1.8mm). Frequency 200kHz -1MHz, cable connection 00 Lemo (MM7L-40FX-200K-1M).	9403363	MM7L-40FX-200K-1M		
APN-8FX/N16	PENCIL LEXIBLE SURFACE PROBE 50-S00KHZ, WITH 16 PIN LEMO CONNECTER, 6' CABLE				
AURX-10-12MM/80MWL	ADJUSTABLE ROTARY X-PROBE, EXPANDABLE FROM 10.0mm - 12.0mm 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 80mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•			
AFK-AURY14	V-Type Rotating scanner probe with 4 Pin Fischer Connector. Probe KIT Contains 1 each of the following in a Shipping / storage container, 14 Probes Total: AUKY-125-156(1.75WL, AUKY-156-187/1.75WL, AUKY-187-218/1.75WL, AUKY-218-250/2.0WL, AUKY-250-281, AUKY-281-312, AUKY-312- 325 AUKY-326 427 AUKY 427 COA LUKY COA				
AURX-1.00-1.250	ADJUSTABLE ROTARY X-PROBE 1.00"-1.250" 100KHZ-2MHZ 2.0" WORKING LENGTH 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AFK-ARRY11	Lustom kotary Y Probe for KA Scanner. Kit includes 11 probes in a waterproof storage case. One each of the following items: (ARKY-156-187), (ARKY- 187-218), (ARRY-218-250), (ARRY-250-312), (ARRY-312-375), (ARRY-375-437), (ARRY-437-500), (ARRY-500-562), (ARRY-562-625), (ARRY-625-				
AURX-15-17MM/80MWL	CP31 (ABIV: CP3 - TEC) Includes Text Beand and Certificate of Conferences ADJUSTABLE ROTARY X-PROBE, EXPANDABLE FROM 15.0mm - 17.0mm 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 80mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AWP-5	CUSTOM WHEEL PROBE 4. DIIFFERENTIAL/ BRIDGE, 50-500KHz, WITH TRIAX FISCHER CONNECTOR.	•			
AURX-5-7MM/80MWL	ADJUSTABLE ROTARY X-PROBE, EXPANDABLE FROM 5.0mm - 7.0mm 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 80mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•			
AURX-7-9MM/80MWL	ADJUSTABLE ROTARY X-PROBE, EXPANDABLE FROM 7.0mm - 9.0mm 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 80mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•			
AURX-9-11MM/80MWL	ADJUSTABLE ROTARY X-PROBE, EXPANDABLE FROM 9.0mm - 11.0mm 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 80mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AURX-11-13MM/80MWL	ADJUSTABLE ROTARY X-PROBE, EXPANDABLE FROM 11.0mm - 13.0mm 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 80mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AF-5228	RIGID SURFACE PROBE BENT 50-500KHz, 90" DEGREES, SHIELDED, 125" DROP CRANKED AT 35" 1.250" FROM THE PROBE TIP. SUPPLIED WITH A TRIAX FISCHER CONNECTOR 5.0" LONG. Includes Test Report and Certificate of Conformance.	•			
AFX-569AS	69° IN ALUMINUM 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, 187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	XA-695S			
ATPN-95-6C/7L	Eddy Current Surface Probe 90° degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long, 50-500 kHz with 7 Pin Lemo Connector. Includes Test Report and Certificate of conformance.	922164			
AURX-1.000-1.200/500K	ADJUSTABLE ROTARY X-PROBE. EXPANDABLE FROM 1.000"-1.200" 100KHz-1MHz 2.0" WORKING LENGTH, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AURX-1.875-2.125/500K	ADJUSTABLE ROTARY X-PROBE. EXPANDABLE FROM 1.875"-2.125" 100KHz-1MHz 2.0" WORKING LENGTH, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURX-2.625-2.875/500K	ADJUSTABLE ROTARY X-PROBE. EXPANDABLE FROM 2.625"-2:875" 100KHz-1MHz 2.0" WORKING LENGTH, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AURX-3.625-3.875/500K	ADJUSTABLE ROTARY X-PROBE. EXPANDABLE FROM 3.625"-3.875" 100KHz-1MHz 2.0" WORKING LENGTH, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AURX-3.375-3.625/500K	ADJUSTABLE ROTARY X-PROBE. EXPANDABLE FROM 3.375"-3.625" 100KHz-1MHz 2.0" WORKING LENGTH, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•	•	•	
AURX-8-10MM/80MWL	ADJUSTABLE ROTARY X-PROBE, EXPANDABLE FROM 8.0mm - 12.0mm 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 80mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
APN-5FX/200K-1MHZ	Flexible Surface Pencil Probe, absolute shielded, frequency: 200KHz-1MHz with the center frequency 500KHz. Measurement head diameter tubing 0.125"Ø inch (3.18mm). Total length: 5 inches (12.7cm). LO0 cable connection.	MP-50FX-200K-1M	MP-50FX-200K-1M	•	
APN-925-8FX /N16	BENDABLE SURFACE PROBE 90 DEG .250" DROP 8.0"LONG WITH 16 PIN LEMO CABLE ATTACHED 50-500KHZ				
AFK-ATMH14	Manual bolt hole probe Kit. Contanins 14 probe sizes: 0.125"750" inch diameters, frequency range 50kHz - 500kHz, bridge absolute coil configuration supplied with a triax fischer connector. Includes waterproof box Test Reports and Certificate of Conformance.				
ARRX500625	ADJUSTABLE ROTARY X-PROBE. EXPANDABLE FROM: .500"625" 100KHz-2MHz SUPPLIED WITH A 4 PIN STEP LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURX-6-8MM/80MWL	ADJUSTABLE ROTARY X-PROBE, EXPANDABLE FROM 6.0mm - 8.0mm 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 80mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BUX-6M-8M			
AF-5019/4F	CUSTOM ROHMANN HIGH FREQUENCY PROBE,100KHz-500KHz SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. REFERENCE: AIRBUS A318/A319/A320/A321 CARGO DOOR. Includes Test Report and Certificate of Conformance	KDB7H1658-03-1			
AF-5019/TF	CUSTOM ROHMANN HIGH FREQUENCY PROBE,100KHz-500KHz SUPPLIED WITH A TRIAX FISCHER/LEMO PUSH/PULL CONNECTOR. REFERENCE: AIRBUS A318/A319/A320/A321 CARGO DOOR. Includes Test Report and Certificate of Conformance	KDB7H1658-03-1			
ATPN-925-6FX/500K-1M	FLEXIBLE SURFACE PROBE, 125" Ø, .250" DROP, 500KHz-1MHz, 6.0" LONG SUPPLIED WITH A TRIAX FISCHER CONNECTOR. IncludesTest Report and Certificate of Conformance.				
ATPN-925-6FX/2MHZ	FLEXIBLE SURFACE PROBE, 125" Ø, .250" DROP, 1-3MHz, 6.0" LONG SUPPLIED WITH A TRIAX FISCHER CONNECTOR. IncludesTest Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATMH.625	Manual hole probe, 0.625 inch (15.875mm) diameter and 2.0 inch (5.08cm) working length, frequency 50kHz - 500kHz, triax fischer connector, bridge	6200-5/8-BH-BNC			
ATMH.687	absolute coll configuration. Includes Test Report and Certificate of Conformance. Manual hole probe, 0.687 inch (17.45mm) diameter and 2.0 inch (5.08cm) working length, frequency 50kHz -500kHz, triax fischer connector, bridge absolute coll configuration. Includes Test Report and Certificate of Conformance.	6200-5/8-BH-BNC			
ATMH.750	Manual hole probe, 0.750 inch (19.05mm) diameter and 2.0 inch (5.08cm) working length, frequency 50kHz -500kHz, triax fischer connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	6200-3/4-BH-BNC			
AXTPN-92-5FX/1-6MHZ	FLEXIBLE SURFACE PROBE, 1- 6MHz, 072" Ø DIA TUBING 90" DEGREES, 200"(5.08mm) DROP 5.0"(12.7mm) LONG WITH TRIAX FISCHER CONNECTOR 1- 6MHz. Includes Test Report and Certificate of Conformance.	•			
APN-35-5/1MHz-3M	RIGID SURFACE PROBE1MHz-3M 5.0" LONG 30" DEGREES .500" DROP CURVE MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.	•			
APNU-5/100kHz-500kHz	ABSOLUTE SURFACE PROBE, UNSHIELDED, 5.0" LONG WITH MICRODOT CONNECTOR 100-500KHZ	•			
APNU-95-6B1	RIGID SURFACE PROBE, UNSHIELDED 90", 500" DROP, BENT 15" 1.0" INCHES FROM THE TIP. 50-500KHZ, 6.0" LONG SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	VM215-1/2X6			
AUR-4.90MSS/35MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR, 4.90mmØ HEAD SIZE, 35mm(1.49") WORKING LENGTH. Includes Test Report and Certificate of Conformance	SEU-4.9-35			
AUR-5.8MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,(5.8mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SEU-5.8-35			
ATPN-975-6.5	SURFACE PROBE 90° DEGREES, .750° DROP, 6.5° LONG. 50-500 KHz, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. IncludesTest Report and Certificate of Conformance				
ARR187SS	ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO STAINLESS STEEL.187" OD, 1.1" WORKING LENGTH Includes Test Report and Certificate of Conformance				
AF-6011-1	SLIDING PROBE, REFLECTON 1-50KHz, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. REFERENCE: Bae 53-10-03. Includes Test Report and Certificate of Conformance				
APNU-95-5FX	FLEXIBLE SURFACE PROBE, 90°, .500° DROP, 50-500KHZ, UNSHIELDED SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	•			
AF-4074	LOW FREQUENCY REFLECTION SPOT PROBE, .320" OD, 2-10KHZ, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	SDP.3-2K-1	RS-203-1		
ARR.125SS	RECHII STAINLESS STEEL ROTATING SCANNER PROBE, 125" Ø USED WITH RA 2000 SCANNER. 1.1" WOIRKING LENGTH, SUPPLIED WITH A 4 PIN STEP LEMO, 100KHz-2MHz Includes Test Report and Certificate of Conformance.	BPRA-8-SS			
ARR.156SS	RECHII STAINLESS STEEL ROTATING SCANNER PROBE, .156 <sup>®</sup> USED WITH RA 2000 SCANNER. 1.1 <sup>®</sup> WOIRKING LENGTH, SUPPLIED WITH A 4 PIN STEP LEMO, 100KHz-2MHz Includes Test Report and Certificate of Conformance.	BPRA-10-SS			
ARR.218SS	RECHII STAINLESS STEEL ROTATING SCANNER PROBE, .218"Ø USED WITH RA 2000 SCANNER. 1.1" WOIRKING LENGTH, SUPPLIED WITH A 4 PIN STEP LEMO, 100KHz-2MHz Includes Test Report and Certificate of Conformance. of Conformance	BPRA-14-SS			
AF-5226	CUSTOM MICRO INDEXING EDDY CURRENT SURFACE PROBE ASSEMBLY WITH 3 PROBE TIPS: 100KHz-300KHz, 500KHz, 1-3MHz. INCLUDES Includes Test Report and Certificate of Conformance. Reference: MD-11 Section 2-2 figure 2.7 PG.5.	10053-5, P1, G1,G2			
AF-5227	CUSTOM BOBBIN PROBE, 100-500KHz, DIFFERENTIAL, .425" Ø 1.6" LONG WITH A 4 PIN FISCHER CONNECTOR. Used to inspect brass tubing I.D Includes Test Report and Certificate of Conformance.	•			
AFS-1401-45	TRANSDUCER, 45° in STEEL 6MHz, 3mm(.118") x.4mm(157") ELEMENT WITH TOP MOUNT MICRODOT CONNECTOR. CASE SIZE: 15mm(.591"L ) x (7mm).276"W x 12mm(.472"H). Includes Test Report and Certificate of Conformance.	AM6S-3X4-45			
ARR.250SS	RECHII STAINLESS STEEL ROTATING SCANNER PROBE, .250°Ø USED WITH RA 2000 SCANNER. 1.1° WOIRKING LENGTH, SUPPLIED WITH A 4 PIN STEP LEMO, 100KHz-2MHz Includes Test Report and Certificate of Conformance.	BPRA-16-SS	9230484		
AF-5225/500K	RIGID SURFACE PROBE .062"Ø TUBING ABS SHIELDED 90", 60" Joggle.020" DROP, 6.0" LONG, , 500KHz, SUPPLIED WITH A TRIAX FISCHER CONNECTOR Includes Test Report and Certificate of Conformance. Reference: MD-11 Section 2-2 figure 2.4 PG.4	1RR88M43/4.02J			
APN-2	RIGID SURFACE PROBE STRAIGHT 50-500KHZ MICRODOT CONNECTOR 2.0" LONG. Includes Test Report and Certificate of Conformance.	PEN-2	MP-20		
AF-5224/2MHZ	SURFACE PROBE.070°Ø TUBING ABS SHIELDED 90°, .300° DROP, 6.0° LONG, , 1-3MHz, SUPPLIED WITH A TRIAX FISCHER CONNECTOR Includes Test Report and Certificate of Conformance. Reference: MD-11 Section 2-2 figure 2.4 PG.3	P/1MHz-2mhZ/A/90.03/6			
APN-3	RIGID SURFACE PROBE 50-500KHZ 3.0" LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP-30	PEN-3	VM200F-3	
APN-35-3	RIGID SURFACE PROBE 50-500KHZ 3.0" LONG 30" DEGREES .500" DROP CURVE MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.	•			
APN-35-3/2MHZ	RIGID SURFACE PROBE 1-3MHZ 3.0" LONG 35 DEG .500" DROP MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.				
APN-35-5/2M	RIGID SURFACE PROBE 1-3MHZ 5.0" LONG 35 DEG .500" DROP MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.	PEN35-5 500K-2M			
APN-35-6	Conformance.	PEN35-6			
APN-35-6FX	FLEXIBLE SURFACE PROBE 50-500KHZ 6.0" LONG 30 DEGREE .500" DROP MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.				
APN-4	RIGID SURFACE PROBE STRAIGHT 50-500KHZ MICRODOT CONNECTOR 4.0" LONG. Includes Test Report and Certificate of Conformance.	MP-40			
APN-4.5	RIGID SURFACE PROBE STRAIGHT SHIELDED 4.5" LONG 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
APN-4.5/500KHZ	RIGID STRAIGHT SURFACE PROBE 500KHz, HOCKING LOCATOR 4.5" LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	105P4F	610-045-002		
APN-4.5/L500KHZ	RIGID SURFACE PROBE, ABS, SHD, 4, 5"LONG, 50-500KHZ WITH MICRODOT CONNECTOR187" Ø. Includes Test Report and Certificate of Conformance	105P4			
APN-455-4B	RIGID SURFACE PROBE 45° DEGREES .500° DROP 50-500KHZ, BENT 15°, 5.0° LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP455-40B			
APN-45-5FX	FLEXIBLE SURFACE PROBE 50-500KHZ 45" DEGREES .500" DROP, 5.0" LONG WITH MIDRODOT CONNECTOR,125" TIP. Includes Test Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
APN-5	STRAIGHT RIGID SURFACE PROBE 5.0" LONG .125" WITH MICRODOT CONNECTOR 50-500KHz Includes Test Report and Certificate of Conformance.	MP-50	PEN-5		
APN-5/1-3MHZ	STRAIGHT RIGID SURFACE PROBE, 125"Ø, 5.0" LONG, 1-3 MHz, WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	MP-50/1-3MHZ			
APN-6	RIGID SURFACE PROBE STRAIGHT 50-500KHZ MICRODOT CONNECTOR 4.0" LONG. Includes Test Report and Certificate of Conformance.	PEN-6	SS-AFB2X6		
APN-910-7	RIGID SURFACE PROBE ABSOLUTE SHIELDED, 50-500KHz, 90° DEGREES, 125" Ø TIP 1.00" DROP 7.0" LONG WITH MICRODOT CONNNECTOR. Includes Test Report and Certificate of Conformance.	302P57			
APN-910-7/2M	RIGID SUFACE PROBE ABSOLUTE SHIELDED,1-3MHz, 90° DEGREES, .125°Ø TIP 1.00° DROP 7.0° LONG WITH MICRODOT CONNNECTOR. Includes Test Report and Certificate of Conformance.	302P57			
APN-9125-4	RIGID SURFACE PROBE, 90° DEGREES, .125" DROP, .125" # TIP, 4.0" LONG MICRODOT CONNECTOR 50-500KHz IncludesTest Report and Certificate of				
APN-9125-5	Conformance. RIGID SURFACE PROBE, 90° DEGREES, .125° DROP, .125° Ø TIP, 5.0° LONG MICRODOT CONNECTOR 50-500KHz IncludesTest Report and Certificate of Conformance.				
APN-91-3FX	ELEXIBLE SHAFT SURFACE PROBE 90" DEGREES, .125"Ø, .100" DROP, 50-500KHz, 3.0" INCHES LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP901-80FX-3			
APN-91-5	RIGED SURFACE PROBE, 90° DEGREES .100° DROP, 125°Ø TIP, 5.0 INCHES LONG WITH MICRODOT CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.	PEN91-5 50-500K			
APN-925-5	RIGID SURFACE PROBE, 90° DEGREES, .250° DROP, .125°Ø TIP 5.0° LONG MICRODOT CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.	MP902-50	PEN925-5 50-500K		
APN-925-5/2M	RIGID SURFACE PROBE 1-3MHz, .125" JIP, 90° DEGREES, .250" DROP 5.0" LONG MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PEN925-5 500K-2M			
APN-925-5FX	FLEXIBLE SURFACE PROBE 90° DEGREES .250° DROP, 5.0° LONG WITH MICRODOT CONNECTOR 50-500KHZ,125°Ø TIP. Includes Test Report and Certificate of Conformance.				
APN-925-5FX/2MHZ	FLEXIBLE SURFACE PROBE 90° DEGREES .250° DROP, 5.0° LONG WITH MICRODOT CONNECTOR 1-3MHZ,125°Ø TIP. Includes Test Report and Certificate of Conformance.				
APN-95-4	RIGID SURFACE PROBE 90° DEGREES, 500° DROP 4.0° LONG, SHEILDED 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance				
APN-96-6	RIGID SURFACE PROBE. 50-500KHZ 90* .600" DROP 6.0" LONG. MICRODOT CONNECTOR Includes test report and Certificate of Conformance.				
APN-45-4C	SURFACE PROBE, CURVED, 50-500KHZ				
ATPN-92-8FX/2MHZ	FLEXIBLE SURFACE PROBE, 90° DEGREES .200" DROP TRIAX FISCHER CONNECTOR 1-3MHZ 8.0" LONG. Includes test report and Certificate of Conformance.				
ATPNU-903-6FX	UNSHIELDED FLEXIBLE SURFACE PROBE 90° DEGREES, .030° DROP, .125°Ø O.D. TIP, 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHz IncludesTest Report and Certificate of Conformance.	UMTF9003-60FX	D0815E1015-2031		
ATPN-903-6/200K-1M	RIGID SURFACE PROBE 90° DEGREES, 030° DROP, 125°Ø O.D. TIP 6.0° LONG, TRIAX FISCHER CONNECTOR 200KHz-1MHZ. Includes Test Report and Certificate of Conformance	MTF9003-60-200K-1M			
ATPN-92-6/1-6M	RIGID SURFACE PROBE, 90° . 200" DROP TRIAX FISCHER CONNECTOR 1-6MHz, 6.0" LONG Includes Test Report and Certificate of Conformance	MTF902-60-1-6M			
ATPN-95-6/200K-1M	RIGID SURFACE PROBE ABS 90° DEGREES, .500° DROP, .125°Ø O.D. TIP, 6.0° LONG TRIAX FISCHER CONNECTOR 200KHz-1MHz. Includes Test Report and Certificate of Conformance.	MTF905-60-200K-1M			
ATPN-12FX	FLEXIBLE COPPER SURFACE PROBE, TRIAX FISCHER CONNECTOR 50-500KHz 12.0" LONG. Includes Test Report and Certificate of Conformance.	PAB001200FX	PAB001200FX	D0815E1015-2101	
ATPN-2	RIGID STRAIGHT SURFACE PROBE, 2.0" LONG, 1/8" TRIAX FISCHER CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.	MTF-20	VM2500F-2	TPEN-2, BCMTF-20	MTF-20
ATPN-2/1-6M	RIGID STRAIGHT SURFACE PROBE, 2.0" LONG, 1/8" TRIAX FISCHER CONNECTOR, 1-6MHz. Includes Test Report and Certificate of Conformance.	BCMTF20-1-6M	MTF20-1-6M		
ATPN-2/2M	RIGID SURFACE PROBE 1-3MHZ TRIAX FISCHER , CONNECTOR 2.0" LONG. Includes Test Report and Certificate of Conformance.	TPEN-2/2M			
ATPN-205-5/1-6M	RIGID SURFACE PROBE, ABS., 20°, .500° DROP, 5.0° LONG, 1/8°Ø TUBING, TRIAX FISCHER CONNECTOR, 1-6MHz. Includes Test Report and Certificate of Conformance. BCMTF-50-1-6M	BCMTF205-50-1-6M	D0815E1015-2037		
ATPN-25-5/1-6M	RIGID SURFACE PROBE 20° DEGREES, .500° DROP, 5.0° LONG, 1/8°Ø TUBING TRIAX FISCHER CONNECTOR, 1-6MHz. Includes Test Report and Certificate of Conformance. D0815E1015E-2037	BCMTF205-50-1-6M			
APN45-6	RIGID SURFACE PROBE, 50-500KHZ, 45°, .125" Ø, .500" DROP, 6.0" LONG SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance				
ATPN-3	RIGID STRAIGHT SURFACE PROBE, 3.0" LONG, 1/8"Ø TRIAX FISCHER CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.	PAB0030	VM2500F-3, BCMTF-30	MTF-30/50-300KHz	PAB0030
ATPN-35-3	RIGID SURFACE PROBE, 35° DEGREES, TRIAX FISCHER CONNECTOR 50-500KHZ 3.0" LONG. Includes Test Report and Certificate of Conformance.	MTF305-30			
AF-4219	LOW FREQUENCY REFLECTION RING PROBE. 420" Ø ID, 1.0" Ø OD SUPPLIED WITH A TRIAX FISCHER CONNECTOR 200Hz-10KHz. Includes Test Report and Certificate of Conformance.	RR0510-3-4L			
AF-4220	LOW FREQUENCY REFLECTION RING PROBE .312"Ø ID, .790"Ø OD SUPPLIED WITH A TRIAX FISCHER CONNECTOR 100Hz-5KHz. Includes Test Report and Certificate of Conformance.	RR028-1-4L			
ATPN-35-5	RIGID SURFACE PROBE, 35* DEGREES, .500 DROP, TRIAX FISCHER CONNECTOR 50-500 KHZ, 5.0* LONG. Includes Test Report and Certificate of Conformance.	MTF305-50			
ATPN-35-5/2MHZ	RIGID SURFACE PROBE, 35° DEGREES, .500 DROP, TRIAX FISCHER CONNECTOR 1-3 MHZ 5.0° LONG. Includes Test Report and Certificate of Conformance.				
ATPN-3FX	FLEXIBLE STRAIGHT SURFACE PROBE, 3.0" LONG, 1/8"Ø TRIAX FISCHER CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.				
ATPN-4	RIGID STRAIGHT SURFACE PROBE ABSOLUTE SHIELDED, 4.0" LONG, TRIAX FISCHER CONNECTOR 50-500KHZ. Includes Test Report and Certificate of	9216191	MTE-40	DPT-006	

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPN-4.5	RIGID STRAIGHT SURFACE PROBE 500KHz, 4.5" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATPN-4.5/200K	RIGID STRAIGHT SURFACE PROBE,ABS,SHIELDED,TRIAX FISCHER CONNECTOR 4.5" LONG 20-200KHZ.4.5"LONG, 20-200KHZ, Fe/NFe, L=114mm(4.5""), Tip 4.35mm(.187"Ø) WITH TRIAX FISCHER CONNECTOR187"Ø TUBING. Includes Test Report and Certificate of Conformance.	104P4	610-034-002		
ATPN-4.5/2MHZ	RIGID STRAIGHT SURFACE PROBE 1-3MHz, SHIELDED, 28mm TIP LENGTH, TRIAX FISCHER CONNECTOR, 4.5" LONG. Includes Test Report and Certificates.	PS002PS028-114N			
ATPN-4/2MHZ	RIGID STRAIGHT SURFACE PROBE 1-3MHz, SHIELDED, 28mm TIP LENGTH, TRIAX FISCHER CONNECTOR, 4.0" LONG. Includes Test Report and Certificates.	MTF-40/1-3MHZ	DPT-007		
ATPN-453-4.5/2MHZ	RIGID SURFACE PROBE, 45° DEGREES, .300° DROP, TRIAX FISCHER CONNECTOR, 1-3MHz., 4.5° LONG. Includes Test Report and Certificate of Conformance.	MTF453-45 / 1-3MHZ			
ATPN-45-4	RIGID SURFACE PROBE 45" DEGREES, :125" Ø TUBING, 4.0" LONG TRIAX FISCHER CONNECTOR. FREQUENCY: 50-500KHz IncludesTest Report and Certificate of Conformance.	TPEN45-4			
ATPN-45-4FX/2MHZ	FLEXIBLE SURFACE PROBE, 45° DEGREES, .125° Ø TUBING, 4.0° LONG TRIAX FISCHER CONNECTOR. FREQUENCY: 1-3MHz IncludesTest Report and Certificate of Conformance.	TPEN-45-4			
ATPN-45-5	RIGID SURFACE PROBE 45" DEGREES, .500" DROP, 5.0" LONG TRIAX FISCHER CONNECTOR. FREQUENCY: 50-500KHz IncludesTest Report and Certificate of Conformance.	TPEN-45-5	DPT45-002	BCMTF455-50	
ATPN-45-5/2M	RIGID SURFACE PROBE 45° DEGREES, 500° DROP, 5.0° LONG TRIAX FISCHER CONNECTOR. FREQUENCY: 1-3MHz IncludesTest Report and Certificate of Conformance.	TPEN-45-5/2M			
ATPN-45-5/7L	RIGID SURFACE PROBE 45" DEGREES, .500" DROP, 5.0" LONG, 7 PIN OB SIZE LEMO CONNECTOR. FREQUENCY: 50-500KHz IncludesTest Report and Certificate of Conformance.				
ATPN-45-5FX	FLEXIBLE SURFACE PROBE 45* DEGREES, 5.0" LONG, TRIAX FISCHER CONNECTOR, 50-500KHz IncludesTest Report and Certificate of Conformance	MTF-455-50FX			
APN-12	RIGID STRAIGHT SURFACE PROBE 50-S00KHz, 125"Ø TUBING WITH MICRODOT CONNECTOR, 12.0" LONG. Includes Test Report and Certificate of Conformance.	PEN -12			
APN-12FX	FLEXIBLE COPPER SURFACE PROBE, MICRODOT CONNECTOR 50-500KHz 12.0" LONG. Includes Test Report and Certificate of Conformance.	PENFLX-12			
APN-2FX	STRAIGHT FLEXIBLE SURFACE PROBE 2.0" LONG WITH MICRODOT CONNECTOR. 50-500KHZ. Includes Test Report and Certificate of Conformance.				
ATPN-45-5FX/2M	FLEXIBLE SURFACE PROBE 45° DEGREES, 5.0" LONG, TRIAX FISCHER CONNECTOR, 1-3MHz IncludesTest Report and Certificate of Conformance				
APN-35-4	RIGID SURFACE PROBE 50-500KHZ 4.0" LONG 30" DEGREES .500" DROP CURVE MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.	PEN35-4			
APN-35-5	RIGID SURFACE PROBE 50-500KHZ 5.0" LONG 30" DEGREES .500" DROP CURVE MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.	PEN35-5 50-500K			
APN-35-6/2MHZ	RIGID SURFACE PROBE 1-3MHZ 6.0" LONG 30 DEGREE .500" DROP MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.				
AURY171218	UNIVERSAL ROTARY "/" PROBE 1-3MHZ 1.3" WORKING LENGTH. EXPANDABLE FROM .171"218". SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AUR250/2.0WL	ROTARY SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	9219987			
AUR-5.2MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 35mm WORKING LENGTH 5.2mm HEAD SIZE. Includes Test Report and Certificate of Conformance	MSR5-2-35	RSM5-2-35		
AUR156SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .156" (5/32") 3.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance Certificate of Conformance.	615P010F075			
AUR-7.8MSS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 7.8mmØ(.307") HEAD, 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 51mm WORKING LENGTH 7.8mm HEAD SIZE. Includes Test Report and Certificate of Conformance	615P078M051			
AURY-13-15MM//50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 13.0-15.0mmØ. Includes Test Report and Certificate of Conformance.				
AURY-15-17MM/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 15.0-17.0mmØ. Includes Test Report and Certificate of Conformance.				
AURY-17-19MM/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 17.0-19.0mmØ. Includes Test Report and Certificate of Conformance.				
AURY-4.0-5.0MM/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 4.0-5.0mm	BYU-4M/5M			
AURY-7.0-9.0MM/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 7.0-9.0mmØ. Includes Test Report and Certificate of Conformance.				
AF-5213/7L	Detachable Pencil Probe 500KHz-3MHz Unshielded Reflection, with 7 pin Lemo connector. Tip diameter .187" with adjustable collar. Includes Test Report and Certificate of Conformance.	9222430			
AF-5213/7L	Detachable Pencil Probe 500KHz-3MHz Unshielded Reflection, with 7 pin Lemo connector. Tip diameter .187" with adjustable collar. Includes Test Report and Certificate of Conformance.	9222430			
ATPN-45-6	RIGID SURFACE PROBE, 45° DEGREES, .500° DROP, 6.0° LONG WITH A TRIAX FISCHER CONNECTOR 50-500KHz IncludesTest Report and Certificate of Conformance.	TPEN45-6	PAB45605	BCMTF455-60	MTF455-60
AF-5214/7L	Detachable Pencil Probe 500KHz-1MHz Absolute Shielded, with 7 pin Lemo connector. Tip diameter .187" with adjustable collar. IncludesTest Report and Certificate of conformance.	9222162			
AF-4175/4L	LOW FREQUENCY REFLECTION SPOT PROBE, 1KHz-100KHz, DELRIN(ACETAL) BODY .440°Ø O.D., 1.77" TALL, SUPPLIED WITH A 4 WAY LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	700P11A			
AWP-5012373M	50-500KHz WHEEL PROBE FOR CHALLENGER CL604/605 MAIN WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AWP-5010598N	50-500KHz WHEEL PROBE FOR CHALLENGER CL604/605 NOSE WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AWP-2606671M	S0-500KHz WHEEL PROBE FOR BOEING 737 - 300/400/500/600 BENDIX MAIN WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AWP-2602875N	50-500KHz WHEEL PROBE FOR BOEING 737 - 300/400/500/600 BENDIX NOSE WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance				
AWP-AHA1290N	SO-SOMOTHAIRCE. SO-SOMOKH2 WHEEL PROBE FOR BOEING 737 - 300 DUNLOP NOSE WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AWP-3-1438-1N	50-500KHz WHEEL PROBE FOR BOEING 737 - 300/500 GOODRICH NOSE WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AWP-3-1439M	50-500KHz WHEEL PROBE FOR BOEING 737 - 300/400/500/600 GOODRICH MAIN WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AURFX125SE/6WL	TEEDIBLE UNIVERSAL RUTARY PROBE LOURN-Z-ZMIZ, JA PUN FISCHER CONNECTOR 6.0" WORKING LENGTH. UNIVERSAL FLEXIBLE RUTARY PROBE LOURNZ- 2MHZ /A-PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 6.0" WORKING LENGTH. 750" TIP LENGTH SPLIT END, EXPANDABLE FROM .125"156"Ø. Comparision with Olimping Data Nurver 2002055 Loudica Tata Bangart and Cartificator & Conformation.				
AWP-2609801M	50-500KHz WHEEL PROBE FOR BOEING 737 - 300/400/500/600 BENDIX MAIN WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AUR875SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 7/8" HEAD SIZE and 2.0" WORKING LENGTH. 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AUR-1.0SS/2.0WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER Includes Test Report and Certificate of Conformance			•	
AWP-90001935N	S0-500KHz WHEEL PROBE FOR GULFSTREAM 450 MEGGIT/ABSC NOSE WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AWP-1159SCL472-5M	S0-500KHz WHEEL PROBE FOR GULFSTREAM 450 MEGGIT/ABSC MAIN WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AWP-50001935M	50-500KHz WHEEL PROBE FOR GULFSTREAM 450 MEGGIT/ABSC MAIN WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AUR812SE/2.0WL	Universal Rotary Hole Probe 0.812 inch (20.6 mm) to 0.875 inch (22.2 mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coil configuration (.812-875) Includes Test Report and Certificate of Conformance	SUB-52-56			
AUR875SE/2.0WL	Universal Rotary Hole Probe 0.875 inch (22.22 mm) to 0.937 inch (23.80 mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration (.875-937) Includes Test Report and Certificate of Conference of the context of the	SUB-56-60		•	
AUR937SE/2.0WL	Universal Rotary Hole Probe 0.937 inch (23.80 mm) to 1.0 inch (25.40 mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration (.937-1.0) includes Test Report and Certificate of Conformance	SUB-60-64			
AUR-1.0SE/2.0WL	Universal kotary Hole Probe 1.0 Inch (2>40 mm) to 1.0625 inch (2>35 mm) diameter, set expanding 2 inch (2) mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coli configuration (1.0-1.062) includes Test Report and Certificate of formersal kotary Hole Probe 1.0625 inch (2>55 mm) to 1.125 inch (2>57 mm) diameter, set expanding 2 inch (50 mm) working length, Operating	SUB-64-68			
AUR-1.0625SE/2.0WL	frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration (1.0625-1.125) Includes Test Report and Certificate of	SUB-68-72			
AUR-1.187SE/2.0WL	Universal Rofary Hole Probe 1.187 Inch [30.15 mm] to 1.250 Inch [31.75 mm] diameter, Self Expanding 2 Inch [50 mm] working length, Operating frequency 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coll configuration (1.187-1.250) Includes Test Report and Certificate of Conference 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coll configuration (1.187-1.250) Includes Test Report and Certificate of Conference 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coll configuration (1.187-1.250) Includes Test Report and Certificate of Conference 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coll configuration (1.187-1.250) Includes Test Report and Certificate of Conference 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coll configuration (1.187-1.250) Includes Test Report and Certificate of Conference 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coll configuration (1.187-1.250) Includes Test Report and Certificate of Conference 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coll configuration (1.187-1.250) Includes Test Report and Certificate of Conference 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coll configuration (1.187-1.250) Includes Test Report and Certificate of Conference 200 kHz - 3MHz Fischer 4 pin connector, reflection of the sector of the sector 4 pin connector	SUB-76-80	RTP-021	•	
AUR-1.312SE/2.0WL	Universal Rotary Hole Probe 1.312 Inch [33.32 mm] to 1.375 Inch [34.92 mm] diameter, Self Expanding 2 Inch [50 mm] working length, Operating frequency 200 KHz - 3MHz Fischer 4 pin connector, reflection differential coll configuration (1.312-1.375) Includes Test Report and Certificate of Conference	SUB-84-88		•	
AUR-1.375SE/2.0WL	UNIVEY31 R0Tary Hote Prope 1.375 Inch 134.92 mm) to 1.4375 Inch (36.51 mm) diameter, Self Expanding 2 Inch (su mm) working length, Uperating frequency 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coil configuration (1.375-1.4375) Includes Test Report and Certificate of Conference	SUB-88-92		•	
AUR-1.4375SE/2.0WL	Universal Rofary Hole Proze 14375 Inch (56.51 mm) to 1.500 inch (38.1 mm) diameter, Self Expanding 2 inch (50 mm) working length, Uperating frequency 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coll configuration (1.4375-1.500) includes Test Report and Certificate of Conference	SUB-92-96			
AUR-1.500SE/2.0WL	UniVersal Rofary Hole Probe 1:500 inch (38.1 mm) to 1:562 inch (39.67 mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 200 kHz - 3MHZ Fischer 4 pin connector, reflection differential coll configuration (1:500-1:562) includes Test Report and Certificate of Configuration (1:500-1:562) includes the second	SUB-96-100			
AUR-1.562SE/2.0WL	Universal Rólary Hole Proze 1:562 incn (39:67 mm) to 1:623 incn (41.27 mm) diameter, Seit Expanding 2 incn (50 mm) working length, Uperating frequency 200 kHz - 3MHz Fischer 4 pin connector, reflection differential coil configuration (1:562-1:625) includes Test Report and Certificate of Conferences -	SUB-100-104			
AUR-1.6875SE/2.0WL	Universal Rotary Hole Probe 1-6875 Inch (42:86 mm) to 1.750 Inch (44:45 mm) diameter, Self Expanding 2 Inch (50 mm) working length, uperating frequency 200 KHz - 3MHz Fischer 4 pin connector, reflection differential coli configuration (1.6875-1.750) includes Test Report and Certificate of Conference	SUB-108-112			
AF-4212	LOW FREQUENCY DIFFERENTIAL SURFACE PROBE 4.0 " LONG, 2-20KHz, 90" DEGREES (RIGHT ANGLE), BENT AT 1.0" FROM THE HANDLE, .187"(3/16")" DROP,156"(5/32")Ø TUBING WITH A TRIAX FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-4039-3TF	NEC-4071-3TF		
AURFB156SE/1.5WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE, 4 PIN FISCHER CONNECTOR 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM .156"187"Ø Includes Test Report and Certificate of Conformance.				
AURFB187SE/1.5WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM 187"250"Ø Includes Test Report and Certificate of Conformance.				
AURFB250SE/1.5WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR 1.5" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM 250"312"Ø Includes Test Report and Certificate of Conformance.			•	
ABL030-6/500K-2MHZ	BLADE PROBE, STRAIGHT, .030" THICK, 6.0" LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
ABL045-6	BLADE PROBE, .045 THICK, 6.0" LONG, STRAIGHT SHAFT, 50-500KHz, MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP.045-60BL	MP045-60BL	BLD-003 ZHHD-BLD- E00.045-250-0	
ABL060-6/500K-2MHZ	BLADE PROBE, STRAIGHT, .060" THICK, 6.0" LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL100-6/500K-2MHZ	BLADE PROBE, STRAIGHT, .100" THICK, 6.0" LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL-1045-6/500K-2MHZ	45" BLADE PROBE, .100" THICK, 6.0" LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL-1060-6/500K-2MHZ	60" BLADE PROBE, .100" THICK, 6.0" LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL-1090-6/500K-2MHZ	90" BLADE PROBE, .100" THICK, 6.0" LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL-345-6/500K-2MHZ	45" BLADE PROBE, .030" THICK, 6.0" LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL-360-6/500K-2MHZ	60° BLADE PROBE, .030" THICK, 6.0" LONG, S00KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ABL-390-6/500K-2MHZ	90" BLADE PROBE, .030" THICK, 6.0" LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL-445-6	BLADE PROBE, .045 THICK, 6.0" LONG, 45°, 50-500KHz, MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL-645-6/500K-2MHZ	45" BLADE PROBE, .060" THICK, 6.0" LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL-660-6/500K-2MHZ	60* BLADE PROBE, .060" THICK, 6.0" LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL-690-6/500K-2MHZ	90° BLADE PROBE, .060° THICK, 6.0° LONG, 500KHZ-2MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ABL-945-6	BLADE PROBE, .045 THICK, 6.0" LONG, 90°, 50-500KHz, MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ACPM-E175-IB	Inner Wheel Probe, Embraer 175 Inner Wheel Bead Seat 90000582: 1 , 50-500KHZ Triax Fischer Connector. Includes Test Report and Certificate of Conformance				
ACPM-E175-OB	Outer Wheel Probe, Embraer 175 Outer Wheel Bead Seat 90000582: 1, 50-500KHZ, Triax Fischer Connector. Includes Test Report and Certificate of Conformance	-			
ACSM100125	MANUALCOUNTER SINK PROBE 100° DEGREES 50-500KHz WITH MICRODOT CONNECTOR 1/8"Ø OD . Includes Test Report and Certificate of Conformance.	CSM-100-8			
ACSM100156	MANUAL COUNTER SINK PROBE 100° DEGREES 50-500KHz WITH MICRODOT CONNECTOR 5/32°Ø OD. Includes Test Report and Certificate of Conformance.	CSM-100-10			
ACSM100187	Comornance. MANUAL COUNTER SINK PROBE 100° DEGREES 50-500KHz WITH MICRODOT CONNECTOR 3/16"Ø OD. Includes Test Report and Certificate of Conformance.	CSM-100-12			-
ACSM100218	MANUAL COUNTER SINK PROBE 100° DEGREES 50-500KHz WITH MICRODOT CONNECTOR 7/32"Ø OD. Includes Test Report and Certificate of	CSM-100-14			-
ACSM100-250	Conformance. MANUALCOUNTER SINK PROBE 100° DEGREES 50-500KHz WITH MICRODOT CONNECTOR 1/4"Ø OD . Includes Test Report and Certificate of	CSM-100-16			
ACSM100281	Conformance. MANUALCOUNTER SINK PROBE 100° DEGREES 50-500KHz WITH MICRODOT CONNECTOR 9/32" OD . Includes Test Report and Certificate of	CSM-100-18		•	
ACSMF100156/1M	Conformance. MANUAL COUNTER SINK PROBE 100° DEGREES 200KHz - 1MHz WITH A CENTER FREQUENCY OF 500KHz, SHIELDED, WITH MICRODOT CONNECTOR	CSMF-100-10/200K-1M	MCF1.156/500K		
	.156"Ø DIAMETER. Includes Test Report and Certificate of Conformance. MANUAL COUNTER SINK PROBE 100° DEGREES 200KHz - 1MHz WITH A CENTER FREQUENCY OF 500KHz, SHIELDED, WITH MICRODOT CONNECTOR			•	
ACSMF100187/1M	.187"Ø DIAMETER. Includes Test Report and Certificate of Conformance. MANUAL COUNTER SINK PROBE 100° DEGREES 200KHz - 1MHz WITH A CENTER FREQUENCY OF 500KHz, SHIELDED, WITH MICRODOT CONNECTOR	CSMF-100-12/200K-1M	MCF1.187/500K		
ACSMF100218/1M	.218'% DIAMETER. Includes Test Report and Certificate of Conformance. MANUAL COUNTER SINK PROBE 100° DEGREES 200KHz - 1MHz WITH A CENTER FREQUENCY OF 500KHz, SHIELDED, WITH MICRODOT CONNECTOR	CSMF-100-14/200K-1M	MCF1.218/500K		
ACSMF100250/1M	.250"Ø DIAMETER. Includes Test Report and Certificate of Conformance.	CSMF-100-16/200K-1M	MC1F.250/500K		
ACSMF100250/500K	MANUAL COUNTER SINK PROBE 100° DEGREES 200KHz - 1MHz, SHIELDED, WITH MICRODOT CONNECTOR. 250" DIAMETER. Includes Test Report and Certificate of Conformance.	MCF1.250/500K			
AF-1525/10K	LOW FREQUENCY SPRING LOADED PROBE, REFLECTION .500°Ø DIA. 5-50KHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AF-5011/1.120-1.240/FX	FLEXIBLE ROTARY ADJUSTABLE X-PROBE. 1.120"-1.240", 7.25" LONG, 4 PIN FISCHER CONNECTOR, REFLECTION, 25KHz-500KHz Includes Test Report and Certificate of Conformance.	NEC-3109-1.120/1.240/FX	NEC-3109-1.120/1.240/FX		
AF-5011/1.565-1.685/FX	FLEXIBLE ROTARY ADJUSTABLE X-PROBE. 1.565"-1.685", 7.25" LONG, 4 PIN FISCHER CONNECTOR, REFLECTION, 25KHz-S00KHz Includes Test Report and Certificate of Conformance.	NEC-3109-1.565/1.685/FX			
AES187SS/1.5WL	STAINLESS STEEL STANDARD ELOTEST ROTARY PROBE, 3/16"Ø,100KHZ-2MHZ 1.5" (38.1mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPE12SS			
AF-2039/4F	HIGH FREQUENCY ABSOLUTE REFLECTION SHEILDED PROBE, 1-40 KHz, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	2-832-01-2520	2-832-01-2520	NEC-2079	TEK-2039
AF-2039/TF	FORRESTER HIGH FREQUENCY EDDY CURRENT PROBE, 2-40 KHz, SHEILDED, ABSOLUTE REFLECTION, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	2-832-01-2520	2-832-01-2520	NEC-2079	TEK-2039
AF-2040/TF	HIGH FREQUENCY PROBE, 500KHz-1MHz, DIFFERENTIAL, 30mm(1.18") DROP, 3mm(.118")Ø TIP, 0°-20° MAXIMUM PIVOT ANGLE, TRIAX FISCHER CONNECTOR 22.5" LONG, (508mm)20° WORKING LENGTH. Includes Test Report and Certificate of Conformance.				TER 2000
AF-3007-1.0	MANUAL BOLT HOLE PROBE DIFFERENTIAL WITH COLLAR 25 KHZ 6.0" LONG, 1.0" (25.4mm) DIAMETER. TRIAX FISCHER FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-3007	TEK-3019		
AF-3007-1.0/RA	ROTARY BOLT HOLE PROBE RA 2000 SCANNER, 25 KHZ ABSOLUTE REFLECTION. 6.0" LONG, 1.0" (25.4mm) DIAMETER. 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	NEC-3007			
AF-3014816	MANUAL BOLT HOLE PROBE WITH COLLAR 25 KHZ 5.25" LONG816" OD TRIAX FISCHER FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	NEC-3014	NEC-3014		
AF-3014816/RA	Conformance. ROTARY BOLT HOLE PROBE RA2000 SCANNER 25 KHZ ABSOLUTE REFLECTION 5.25" LONG816" (20.7mm) DIAMETER. 4 PIN STEP LEMO CONNECTOR FOR RA SCANNER. Includes Test Report and Certificate of Conformance.	NEC-3014			
AF-3014-UX.810	FOR RAS SLANNEK. INCLUES 1 EST REPORT and CERTIFICATE OT CONTORMANCE. ADJUSTABLE ROTARY UNIVERSAL ABSOLUTE/REFLECTION PROBE 25 KHZ 5.25" LONG, 0.810" (20.5mm) DIAMETER. 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-3014-UX	NEC-3014-2	TEK-3025-81	
AF-3015880	Includes Test Report and Certificate of Conformance. MANUAL BOLT HOLE PROBE DIFFERENTIAL2SKHZ, 0.880° (22.3mm) DIAMETER. TRIAX FISCHER CONNECTOR Includes Test Report and Certificate of Conformance	NEC-3015	NEC-3015		
AF-3015880/RA	ROTARY BOLT HOLE PROBE RA 2000 SCANNER 25 KHZ ABSOLUTE REFLECTION, 5.25" LONG, 0.880" (22.3mm) DIAMETER. 4 PIN FISCHER CONNECTOR.	NEC-3015			
AF-3016960	Includes Test Report and Certificate of Conformance. MANUAL BOLT HOLE PROBE DIFFERENTIAL WITH COLLAR 25 KHZ 5.25" LONG, 0.960" (24.3mm) DIAMETER. TRIAX FISCHER CONNECTOR. Includes Test	NEC-3016	NEC-3016	TEK-3025.960	
	Report and Certificate of Conformance. ROTARY BOLT HOLE PROBE RA2000 SCANNER, 25 KHZ ABSOLUTE REFLECTION 5.25" LONG, 0.960" (24.3mm) DIAMETER. 4 PIN FISCHER CONNECTOR.		NEC-3010	1EK-3025.900	
AF-3016960/RA	Includes Test Report and Certificate of Conformance. ADJUSTABLE ROTARY UNIVERSAL ABSOLUTE/REFLECTION PROBE 25 KHZ 5.25" LONG, 0.960" (24.3mm) DIAMETER. 4 PIN FISCHER CONNECTOR.	NEC-3016			
AF-3016-UX.960	Includes Test Report and Certificate of Conformance.	NEC-3016-UX	NEC-3016-UX		

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-4003	LOW FREQUENCY REFLECTION SURFACE PROBE 90°.250" FLAT TIP .400" DROP, BENT, 1-25KHz , SHIELDED, 416 STAINLESS STEEL, TRIAX FISCHER	NEC-1084			
AF-4003/4F	CONNECTOR. Includes Test Report and Certificate of Conformance. LOW FREQUENCY REFLECTION PROBE 90°.400° DROP BENT, 1-25KHz , SHIELDED, 416SS 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate	NEC-1084			
AF-4003-1	of Conformance. LOW FREQUENCY REFLECTION, SURFACE PROBE 90°, .156°Ø.400° DROP BENT, 1-50KHz, SHIELDED, 416 STAINLESS STEEL, TRIAX FISCHER CONNECTOR. Includes Text Report and Certificate of Conformance.	TEK-1521-3			
AF-4003-1FT	Includes rest Report and Certificate or Comonimance. LOW FREQUENCY REFLECTION, SUFFACE PROBE 90°, 156°Ø FLAT TIP .400° DROP BENT, 1-50KHz , SHIELDED, 416 STAINLESS STEEL, 5.0° LONG WITH A TRIAK FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-1521-1			
AF-4003FT	LOW FREQUENCY REFLECTION, SURFACE PROBE 90°, 250°Ø FLAT TIP. 400° DROP BENT, 1-50KHz, SHIELDED, 416 STAINLESS STEEL, 5.0° LONG WITH A TRIAX FISCHER CONNECTOR, Includes Test Report and Certificate of Conformance.	TEK-1521			•
AF-4003ST	LOW FREQUENCY REFERENCE MADE THE PROFENSION OF COMMUNICATION OF COMMUNICATIO COMMUNICATION OF COMMUNICATION OF COMMUNICATIONO				•
AF-4004	LOW FREQUENCY REFLECTION RING PROBE, .870° OD x.310° OID 1-100KHz WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-4059-08A-TF			
AF-4006	LOW FREQUENCY REFLECTION RING PROBE .840" Ø ID 1.205Ø " OD WITH A TRIAX FISCHER CONNECTOR, 900Hz-5KHz. Includes Test Report and Certificate of Conformance	TEK-4000A		•	
AF-4008/4F	LOW FREQUENCY PROBE ABSOLUTE REFLECTION, SHIELDED, 2-20KHz, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. Reference: 51-10-16-066	PKA27H1359	PKA-27 H-1359	PKA-27H1359	РКА-27 Н-1359
AF-4011	LOW FREQUENCY RELECTION SPOT PROBE 500HZ-100KHZ.400°OD, USE WITH NDT396 TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	SPO-5328	SPO-5328 TEK-4001-4	SPT-001	FKA-27 H-1555
AF-4012	OF COMONTANCE. LOW FREQUENCY DETACHABLE REFLECTION SPOT PROBE, SHIELDED, .310 <sup>o</sup> Ø OD, 700HZ-80KHZ WITH TOP MOUNTED TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-5327, 9217896	TEK-4001-3	NEC-4087-3	9217896
AF-4012/7L	LOW FREQUENCY REFLECTION SPOT PROBE, 310° Ø OD, 700Hz-80KHz WITH TOP MOUNTED 7-PIN LEMO CONNECTOR. Includes Test Report and Certificate of Conformance	SPO-5327L		•	5217650
AF-4014	SPRING LOADED REFLECTION LOW FREQUENCY PROBE .340" DIA 5-SOKHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-1005	NEC-1005	TEK-1525	
AF-4015-2.5L/20K	LOW FREQUENCY SPRING LOADED SPOT PROBE, 20KHz, DIFFERENTIAL 2.5" LONG. TRIAX FISCHER CONNECTOR . Includes test report.	SNG.375/2.5L-20K		•	
AF-4015-2.5L/2K	LOW FREQUENCY SPRING LOADED SPOT PROBE, 2KHz, DIFFERENTIAL 2.5" LONG. TRIAX FISCHER CONNECTOR. Includes test report.	SNG375-2.5L-2K		•	
AF-4015-3L/20K	LOW FREQUENCY SPRING LOADED SPOT PROBE, 20KHz, DIFFERENTIAL 3.0" LONG. TRIAX FISCHER CONNECTOR . Includes test report.	SNG375-3L-20K-TF		•	•
AF-4015-3L/25K	LOW FREQUENCY SPRING LOADED SPOT PROBE, DIFFERENTIAL, 25KHz, 3.0" LONG. TRIAX FISCHER CONNECTOR . Includes test report.	SNG375-3L/25K/TF		•	
AF-4020	LOW FREQUENCY REFLECTION PROBE 800Hz-20KHz WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-1087	TEK-1536	•	
AF-4021	LOW FREQUENCY DIFFERENTIAL / BRIDGE DETACHABLE SURFACE PROBE 500Hz-40KHz, .440" Ø. Includes Test Report and Certificate of Conformance.	SPO-1391	SPO-1402	9213547, 9213554	SB.4-1K-1
AF-4022	LOW FREQUENCY DIFFERENTIAL RING PROBE, 0.300" Ø I.D., 0.700" Ø O.D., 500Hz - 5KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-996	LR0110-1	RB.8-500H-1	
AF-4030	LOW FREQUENCY SPOT PROBE REFLECTION .500" OD TOP MOUNT TRIAX FISCHER 10-40 KHz. Includes Test Report and Certificate of Conformance.	NEC-1095	NEC-1095		
AF-4031/TF	LOW FREQUENCY SLIDING PROBE, REFLECTION, 400HZ-SOKHZ, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. Reference: 737 PART 6 53-30-24 page 2.	SPC-335-4	NEC-4170	TEK-4042	SPC-335-4
AF-4032	LOW FREQUENCY DIFFERENTIAL SURFACE SPOT PROBE 5.0 " LONG, 5-30KHz, 90" DEGREES (RIGHT ANGLE).250" DROP, .190"Ø OD WITH TRIAX FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-6464	SPO-6464	TEK-1534	NEC-1053,
AF-4035	LOW FREQUENCY REFLECTION RING PROBE .540" ID 1.0" OD 100HZ-10KHZ, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-2432	ARP/13.5/29P	RDP1.2-100H-1	RDP1.2-100H-1
AF-4036	LOW FREQUENCY REFLECTION RING PROBE, 200Hz-10KHz SUPPLIED WITH TRIAX FISCHER CONNECTOR930"Ø O.D. x. 305"Ø I.D. Includes Test Report and Certificate of Conformance.	RR058-1	RDP.8/500H-1	RR058-1	
AF-4039	LOW FREQUENCY ADJUSTABLE SLIDING PROBE, REFLECTION, 2 SINGLE MICRODOT CONNECTORS, 100HZ-50KHZ(RM7). Includes Test Report and Certificate of Conformance. 9230982	SPO-1958	9230982	ASLD-100H-50K	LTW0423-1
AF-4040	LOW FREQUENCY REFLECTION RING PROBE 200Hz- 2KHz, .500"Ø ID x 1.00"Ø DIA OD x 1.160" H, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-4028-1, SPO783	SPO783	•	
AF-4041	LOW FREQUENCY DIFFERENTIAL PROBE, 1-40KHZ. Maximum height of.50" inches and diameter of.300" to .320" inches. Flat at the end. Used with ANDT3016-B reference standard. Includes Test Report and Certificate of Conformance.	NEC-4088-1	SPT-005	TEK-2007	SPT-005
AF-4041/4F	LOW FREQUENCY DIFFERENTIAL PROBE, 1-40KHZ. Maximum height of. 50" inches and diameter of. 300" to. 320" inches, 4 Pin Fischer Connector. Flat at the end. Used with ANDT3016-B reference standard. Includes Test Report and Certificate of Conformance.	NEC-4088-1		•	
AF-4041/7L	LOW FREQUENCY DIFFERENTIAL PROBE, 1-40KHZ. Maximum height of .50° inches and diameter of .300° to .320° inches. Supplied with a 7 pin Lemo connector. Includes Test Report and Certificate of Conformance.	NEC-4088-1		•	
AF-4041-1	LOW FREQUENCY DIFFERENTIAL PROBE , 1-40KHZ. Maximum height of .400" inches and diameter of .300" to .320" inches. Flat at the end. Includes Test Report and Certificate of Conformance.			•	
AF-4045	LOW FREQUENCY REFLECTION SPOT PROBE 400Hz-60KHz, -44"0Ø OD, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-4001-4		•	
AF-4046	LOW FREQUENCY REFLECTION SPOT PROBE, 700Hz-80KHz, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-4001-3	RS5005-5TF	•	
AF-4048	LOW FREQUENCY REFLECTION SPOT PROBE, TOP MOUNT TRIAX FISCHER CONNECTOR. FREQUENCY .620"OD,100HZ-20KHZ. Includes Test Report and Certificate of Conformance.	SPO-5330	SPO-5330	TEK-4001-6	
AF-4050	LOW FREQUENCY REFLECTION RING PROBE, 500Hz-20KHz, .640Ø O.D. x .360Ø I.D., 1.050" HIGH x 1.650" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RDP.7-2K-5	RR207-5		
AF-4052	ROHMANN LOW FREQUENCY REFLECTION SPOT PROBE, 500Hz-250KHz, (23.0mm(.900" LONG x 20.0mm(.780") High) SUPPLIED WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. Reference: Airbus A318/A319/A320/A321 57-51-63-991-002-A	KAS-42-5E	ТЕК-4046	KAS-42-5E	OPXV4-D0815E1015-2117

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-4052/4F	ROHMANN LOW FREQUENCY REFLECTION SPOT PROBE, 500Hz-250KHz, (23.0mm(.900" LONG x 20.0mm(.780") High) SUPPLIED WITH 4 PIN FISCHER	KAS 42-5E			
AF-4057	CONNECTOR. Includes Test Report and Certificate of Conformance. Reference: Airbus A318/A319/A320/A321 57-51-63-991-002-A LOW FREQUENCY REFLECTION PROBE, SHIELDED 1-20KHz .400"Ø, 1.75"H, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	SDP.375-8K			
AF-4058	Conformance. FORRESTER LOW FREQUENCY PROBE, REFLECTION, SHEILDED, 2-40KHZ TRIAX FISCHER CONNECTOR, 187"Ø TUBING. Includes Test Report and Certificate of Conformance.	2-832-02-2455, TEK-2038	NEC-2078	ТЕК-2038	2-832-02-2455
AF-4061	LOW FREQUENCY REFLECTION SPOT PROBE, .500"Ø OD, 300Hz to 40KHz, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-4001-5			
AF-4063	LOW FREQUENCY REFLECTION PROBE, .570"Ø ID, .970"Ø OD WITH .200" RADIUS, 2-20KHZ. Includes Test Report and Certificate of Conformance.	TEK-4064			
AF-4065	LOW FREQUENCY REFLECTION RING PROBE, TRIAX FISCHER CONNECTOR, 50-500HZ, .600" INSIDE DIAMETER, 1.550" OUTSIDE DIAMETER. B777-200/300 57-20-01 PART 6 PAGE 2. Includes Test Report and Certificate of Conformance	TEK-4053			
AF-4067	LOW FREQYENCY REFLECTION RING PROBE,500HZ-20KHZ, .365"Ø I.D., .700"Ø O.D. WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RR207-5			
AF-4068	LOW FREQUENCY REFLECTION PROBE, 355"Ø ID, 650"Ø OD, 500H2-5KH2 WITH TRIAX FISHER CONNECTOR. REFERENCE: 737 PART 6 55-10-64. Includes Test Report and Certificate of Conformance.	•			
AF-4073/4F	LOW FREQUENCY REFLECTION SPOT PROBE .930" Ø 2.0" HIGH, 4 Pin Fischer FISCHER CONNECTOR 80Hz-60KHz. Includes Test Report and Certificate of Conformance.	700P24A	700P24A		
AF-4075	LOW FREQUENCY REFLECTION PROBE 90°, .500° DROP, 2-200KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-1083	TEK-1542		
AF-4081	UNIBODY LOW FREQUENCY REFLECTION RING PROBE 500Hz-5KHz, 400"Ø ID, .670"Ø OD WITH TRIAX FISCHER CONNECTOR. REFERENCE: 737 PART 6 55- 10-64. Includes Test Report and Certificate of Conformance.	RDP.674/2K	RDP.674/2K	D0815E1015-2111	
AF-4084	LOW FREQUENCY REFLECTION RING PROBE, 800HZ-10KHZ, .320"Ø ID, 600"Ø OD x .700"H, WITH TRIAX FISCHER CONNECTOR. REFERENCE: 767 PART 6 53-10-22, NDT6075 REFERENCE STANDARD. Includes Test Report and Certificate of Conformance.	•			
AF-4085	LOW FREQUENCY REFLECTION PROBE .31" Ø OD .900" TALL, 800Hz-20KHz, RIGHT ANGLE STEM WITH TRIAX FISHER. Includes Test Report and Certificate of Conformance.		SDP.3-2K		
AF-4086	LOW FREQUENCY REFLECTION SPOT PROBE, 1-40KHZ .660" OD CASE TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RS1005-2/TF	SPD.5-10K-2		
AF-4087	LOW FREQUENCY REFLECTION PROBE 90". 250" DROP, BENT. 187" 416SS TUBING. 1-50KHZ, SHIELDED, FLAT PROBE TIP, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-1089			
AF-4097	LOW FREQUENCY REFLECTION PROBE, 300HZ-3KHZ .605"ID, 1.1160D TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RR0112-5-TF	RDP1.0-500H-3	RR0112-5-TF	
AF-4098	LOW FREQUENCY REFLECTION RING PROBE ID .788"Ø, OD 1.40"Ø, 300Hz-3KHz SUPPLIED WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RR0114-3-TF	RDP1.4780-100H	RR0114-3-TF	
AF-4099	LOW FREQUENCY RING PROBE, REFLECTION, 100HZ-5KHz .425' I.D., .900" O.D. TRIAX FISCHER CONNECTOR. Includes Test Report and COC.	RR019-1-TF	RDP.85-500H	RR019-1-TF	
AF-4103	LOW FREQUENCY REFLECTION PROBE SHIELDED, 200HZ-100KHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	KAS 61-7			
AF-4103/7L	LOW FREQUENCY REFLECTION PROBE SHIELDED, 200HZ-100KHZ 7 PIN LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	KAS 61-7		KAS 61-7	
AF-4103/TF	LOW FREQUENCY REFLECTION RING PROBE ABSOLUTE SHIELDED, 200Hz-100KHz WITH A TRIAX FISCHER CONNECTOR. DIMENSIONS: 37mm X 13mm X 23mm. Includes Test Report and Certificate of Conformance.	KAS 61-7, ASP05750	ASP05750	KAS61-7	
AF-4104	LOW FREQUENCY REFLECTION RING PROBE. 680" Ø I.D. 1.50" Ø O.D. WITH A TRIAX FISCHER CONNECTOR CONNECTOR 100Hz-2KHz., 737 PT 6 57-30-04. Includes test report and Certificate of Conformance.	RRO 115-3			
AF-4109/TI	LOW FREQUENCY REFLECTION RING PROBE, ID .470, OD.900, 3-10KHZ. For reference standard NDT 3259. Includes Test Report and Certificate of Conformance.				
AF-4110	LOW FREQUENCY SPOT PROBE, DIFFERENTIAL, .250" OD, 5KHZ-100KHZ, TRIAX FISCHER CONNECTOR. (SL/5KHz-100KHz/.25), SPO-2132. Includes Test Report and Certificate of Conformance.	SL/5KHz-100KHz/.25	SPO-2132	9213546	
AF-4110/7L	LOW FREQUENCY SPOT PROBE, DIFFERENTIAL, .250" OD, 5KHZ-100KHZ, 7 PIN LEMO CONNECTOR. (SL/5KHz-100KHz/.25), SPO-2132. Includes Test Report and Certificate of Conformance.	SL/5KHz-100KHz/.25			
AF-4112	LOW FREQUENCY REFLECTION SPOT PROBE .25"Ø(6.4MM) DIAMETER 2KHz-200KHz,(Olympus NDT) USED WITH NDT781 777 57-40-02 PAGE 1 FIGURE 2. IncludesTest Report and Certificate of Conformance.	SDP.2-50-3K	SPC-354/.25		
AF-4116	LOW FREQUENCY REFLECTION RING PROBE 1.060" Ø O.D., .580" Ø I.D., 50HZ-5KHZ. Includes Test Report and Certificate of Conformance.	TEK-4055			
AF-4124/300H	REFLECTION RING PROBE TRIAX FISHER CONNECTOR, 1.25"0D.75" ID(19.6mm) 300HZ-1KHZ. 737 PART 6 57-10-53, pg.2, USED WITH REFERENCE STANDARD NDT3168 AND NDT3176-X. Includes test report and Certificate of Conformance.	RDP1.2575/300H			
AF-4125/100H	CUSTOM REFLECTION RING PROBE 1.2" OD., 605" ID, 50Hz-3KHz TRIAX FISHER CONNECTOR. 737 PART 6 57-10-58, pg.2. and 737 PART 6 57-10-54, pg.2 USED WITH NDT3153-X AND 3167-X SERIES REFERENCE STANDARDS. Includes Test Report and Certificate of Conform	RDP1.2-100H-7	SPO-6626		
AF-4126/500H	LOW FREQUENCY REFLECTION RING PROBE .750°OD .400°ID 500Hz-2 KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RDP.75-500H-5			
AF-4131/500H	LOW FREQUENCY REFLECTION RING PROBE, 100Hz-1KHz, 1.35"Ø O.D.x.850"Ø I.D. WITH A TRIAX FISCHER CONNECTOR USED ON NDT3178G 737 PART 6 57-10-62, pg.2. Includes Test Report and Certificate of Conformance.	RDP1.35850/500H			
AF-4132	LOW FREQUENCY REFLECTION RING PROBE 900Hz -5KHz WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-4067			
AF-4136	LOW FREQUENCY SPOT PROBE, DIFFERENTIAL, 50-500HZ, OD. 275, TRIAX CONNECTOR. Includes Test Report and Certificate of Conformance.	LS013-5			
AF-4139	LOW FREQUENCY REFLECTION RING PROBE .350" Ø ID x .750" Ø OD, TRIAX FISCHER CONNECTOR SOH2-4KH2. Includes Test Report and Certificate of Conformance.	RR017-5/TF	RR017-5/TF	RDP.7-100H-5	
AF-4144	LOW FREQUENCY DIFFERENTIAL PROBE, 1-40KHZ. Maximum height of .50° inches and diameter of .300° to .320° inches. 10 inches long Flat at the end. Used with ANDT3016-B reference standard. Includes Test Report and Certificate of Conformance.	SPO-1071	SPO 1071	TEK-4017	
	LOW FREQUENCY REFLECTION PROBE 90° DEGREES, .400" DROP, 5.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of				

HardSignal	PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
And the set of th					EQUIVALENT	EQUIVALENT
			510 5525	5110105	,	,
			•	•	•	
MarkadowMarkado					•	
Physical static stat				•	•	
MarkadeMarkadeMarkadeMarkadeMarkadeMarkadeMarkadeMarkade44-50CompanyMarkade	AF-4166/500H		SDP.35-500H-1			
ValueControl <th< td=""><td>AF-4167</td><td>IncludesTest Report and Certificate of Conformance.</td><td>SPC-354/.25</td><td></td><td></td><td></td></th<>	AF-4167	IncludesTest Report and Certificate of Conformance.	SPC-354/.25			
Variable         Control of the second o	AF-4170		TEK-4025		•	
Wards of a set	AF-4172/TF		720P1F50	632-761-000	720P1F5J	
Weak of the section	AF-4175/TF		700P11A	632-483-011		
ValueContinuousCo	AF-4176/TF		700P24A	632-483-024	•	
Value         Configure of continuance.         Concision of continuance.         Concision of continuance.         Concision of continuance.           V4.131.40         Tables 255 (Continuance.         Tables 255 (Continuance.         Continuance.	AF-4178		SDP.375-20K			
ValueMapper and conflictuat of conflictuates of c	AF-4179		NEC-4083	NEC-4083-1	TEK-4031	
Valuation         Model and certificate of colormatics         Model         initial         initial         initial           V4-132         More and certificate of colormatics         More and certificate of colormatics <td< td=""><td>AF-4181/4L</td><td></td><td>700P07A</td><td></td><td></td><td></td></td<>	AF-4181/4L		700P07A			
MarkanModel <th< td=""><td>AF-4181/TF</td><td></td><td>700P07A</td><td></td><td>•</td><td></td></th<>	AF-4181/TF		700P07A		•	
ValueCalify and Calify and Calify High 23, 777 pm 65 537-03Cike 25 70Cike 25 70	AF-4182		SPO-4081D MODIFIED		•	
Number         Conversion         Science	AF-4183		TEK-4056			
Number	AF-4184	LOW FREQUENCY SPOT PROBE, DIFFERENTIAL/BRIDGE, .375" ODØ, CASE OD: 0.425"Ø, FREQUENCY 100Hz-2KHz, TRIAX FISCHER CONNECTOR. Includes	LS023-2		•	
MarkaneTest Report and certificate of Conformance.Incl <th< td=""><td>AF-4185</td><td>REFLECTION SPOT PROBE ACETAL BODY WITH PROTECTIVE WEAR RESISTANT FACE, 200Hz-200KHz, .511"Ø (13.0mm)OD, 1.5" LONG STRAIGHT (TOP</td><td></td><td></td><td></td><td></td></th<>	AF-4185	REFLECTION SPOT PROBE ACETAL BODY WITH PROTECTIVE WEAR RESISTANT FACE, 200Hz-200KHz, .511"Ø (13.0mm)OD, 1.5" LONG STRAIGHT (TOP				
NameCONNECTOR. Include/state laport and Certificate of Conformance.Image: Configuration of	AF-4186					
Number 10Conformance.	AF-4187				•	
NumberLongingLongingRel 2 (10H-3Rel 2 (10	AF-4188/7L		310P24	•	•	
NameConformance.POI-128	AF-4189		LR0112-B3	RB1.2-100H-3	•	
Name     Notation     Notation     Notation     Notation     Notation       AP-133     Gov FEGUENCY REFLECTION SPD ROBE. TPD MARTER 0F. 500°/G12 zmm, BODY DAMETER 0F (14.80mm/ß), 1.600°(4.01mm) HIGH, 1-30ktt, 90° DEGREES (RIGHT ANGLE) TRIAX FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.     NeC-0033     Image: Control Science	AF-4190		SPO-1238	9203394	•	
Name       Spot Beges (Richt ANGLI) TRIAX FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.       Net-A033       Net-A034         AF-4194       Cold Grance       Cold FREQUENCY REFLECTION PROBE, 360°Ø (D). 500°Ø (D). 500°/ 20. WITH TRIAX FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.       Science	AF-4192/4F		RS013-5/4F	SDP.3-1K/4L		
AF-4194       LOW FREQUENCY REFLECTION PROBE, 360°g DD, 500H2-5KH2 WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.       Image: Conformance includes incl	AF-4193		NEC-4033		•	
AF-4195       LOW FREQUENCY REFLECTION PROBE, 70042-250HZ .605° ID, 1.300°Ø O.D. WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.       Image: Conformance of Conformance of Conformance of Conformance of Conformance of Conformance.       Image: Conformance of Conformance of Conformance of Conformance of Conformance of Conformance.       Image: Conformance of Conformance of Conformance of Conformance of Conformance of Conformance.       Image: Conformance of Conformance of Conformance of Conformance of Conformance of Conformance of Conformance.       Image: Conformance of Conformance of Conformance of Conformance of Conformance.       Image: Conformance of Conformance of Conformance of Conformance of Conformance.       Image: Conformance of Conformance. <td>AF-4194</td> <td>LOW FREQUENCY REFLECTION PROBE, .360" DID, .600" OD, 500Hz-5KHz WITH TRIAX FISHER CONNECTOR. Includes Test Report and Certificate of</td> <td></td> <td></td> <td></td> <td></td>	AF-4194	LOW FREQUENCY REFLECTION PROBE, .360" DID, .600" OD, 500Hz-5KHz WITH TRIAX FISHER CONNECTOR. Includes Test Report and Certificate of				
AF-4196/DIFF       Differential/BRIDGE RING PROBE.750°Ø OD.400°Ø OD.980° HIGH, TRIAX FISCHER CONNECTOR, 100Hz-1KHz Includes test report and Certificate       Image: Control of Conformance.       Image: Conformance.         AF-4198       LOW FREQUENCY REFLECTION SURFACE PROBE 90°.400° DOD, 980° HIGH, TRIAX FISCHER CONNECTOR, 100Hz-1KHz Includes test report and Certificate       Image: Conformance.       Image: Conformance	AF-4195	LOW FREQUENCY REFLECTION PROBE, 70HZ-250HZ .605"ID, 1.300" Ø O.D. WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of				
AF-4198       LOW FREQUENCY REFLECTION SURFACE PROBE 90".400" DROP BENT, 187" DIAMETER, 5.0" LONG 1-50KHz, SHIELDED, 416 STAINLESS STEEL, TRIAX       Image: Constraint of the cons	AF-4196/DIFF	DIFFERENTIAL/BRIDGE RING PROBE .750"Ø OD .400"Ø OD, .980" HIGH, TRIAX FISCHER CONNECTOR, 100Hz-1KHz. Includes test report and Certificate				
AF-4199       LOW FRQUENCY RING PROBE. DIFFERENTIAL/BRIDGE650°Ø OD. 1.060°Ø OD, TRIAX FISCHER CONNECTOR, 80-800H2 includes test report and certificate of conformance.       LR0111-2/TF       LR0111-2/TF       LR0111-2/TF         AF-4201       LOW FREQUENCY REFLECTION PROBE, 450H2-2kH2 for Aluminium, ID 0.415°, OD 0.760° (MAX). 1.35° HEIGHT. TRIAX FISCHER CONNECTOR. Includes	AF-4198	LOW FREQUENCY REFLECTION SURFACE PROBE 90°. 400" DROP BENT, .187" DIAMETER, 5.0" LONG 1-50KHz, SHIELDED, 416 STAINLESS STEEL, TRIAX				
AF-4201       LOW FREQUENCY REFLECTION PROBE, 450HZ-2kHZ for Aluminium, ID 0.415", OD 0.760" (MAX). 1.35" HEIGHT. TRIAX FISCHER CONNECTOR. Includes       Image: Conformance.         AF-4202       LOW FREQUENCY REFLECTION RING PROBE, 50HZ-5KHZ, ID 0.325", OD 0.790" (MAX). 1.05" HEIGHT. TRIAX FISCHER CONNECTOR. USED WITH NDT6097       Image: Conformance.         AF-4203       LOW FREQUENCY REFLECTION RING PROBE, 50HZ-5KHZ, ID 0.300", OD 0.800" (MAX). 1.05" HEIGHT. TRIAX FISCHER CONNECTOR. USED WITH NDT6097       Image: Conformance.         AF-4203       LOW FREQUENCY REFLECTION RING PROBE, 90HZ-5KHZ, ID 0.300", OD 0.800" (MAX). 1.170" HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.       Image: Conformance.         AF-4204-1       LOW FREQUENCY REFLECTION RIGE SPOT PROBE, SHIELDED, REFLECTION, 2-100KHZ, 500" DROP, 200" OD ROUNDED TIP, TRIAX FISCHER CONNECTOR.       Image: Conformance.         AF-4204-2       LOW FREQUENCY REFLECTION RIGE SPOT PROBE, SHIELDED, REFLECTION, 2-100KHZ, 500" DROP, 200" OD FLAT TIP, TRIAX FISCHER CONNECTOR. Includes       Image: Conformance.         AF-4204-2       LOW FREQUENCY REFLECTION RIGE SPOT PROBE, SHIELDED, REFLECTION, 2-100KHZ, 500" DROP, 200" OD FLAT TIP, TRIAX FISCHER CONNECTOR. Includes       Image: Conformance.       Image: Conformance.         AF-4204-2       LOW FREQUENCY REFLECTION RIGE SPOT PROBE, SHIELDED, REFLECTION, 2-100KHZ, 500" DROP, 200" OD FLAT TIP, TRIAX FISCHER CONNECTOR. Includes       Image: Conformance.       Image: Conformance.       Image: Conformance.       Image: Conformance.       Image: Conformance.       Imag	AF-4199	LOW FREQUENCY RING PROBE. DIFFERENTIAL/BRIDGE650"Ø OD .1.060"Ø OD, TRIAX FISCHER CONNECTOR, 80-800Hz Includes test report and	LR0111-2/TF			
AF-4202       LOW FREQUENCY REFLECTION RING PROBE, 500HZ-5KHZ, ID 0.325", OD 0.790" (MAX). 1.05" HEIGHT. TRIAX FISCHER CONNECTOR. USED WITH NDT6097       Image: Constraint of the image: Constraint	AF-4201	LOW FREQUENCY REFLECTION PROBE, 450HZ-2kHZ for Aluminium, ID 0.415", OD 0.760" (MAX). 1.35" HEIGHT. TRIAX FISCHER CONNECTOR. Includes				
AF-4203       LOW FREQUENCY REFLECTION RING PROBE, 900H2-5KHZ, ID 0.300°, OD 0.800° (MAX), 1.170° HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.       Image: Conformance of Conformance.       Image: Conformance of Conformanc	AF-4202	LOW FREQUENCY REFLECTION RING PROBE, 500HZ-5KHZ, ID 0.325", OD 0.790" (MAX). 1.05" HEIGHT. TRIAX FISCHER CONNECTOR. USED WITH NDT6097			•	
AF-4204-1       LOW FREQUENCY RIGHT ANGLE SPOT PROBE, SHIELDED, REFLECTION, 2-100KHZ, .500° DROP, .200° DD ROUNDED TIP, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.       Image: Conformance includes in the conformance includes	AF-4203	LOW FREQUENCY REFLECTION RING PROBE, 900HZ-5KHZ, ID 0.300", OD 0.800" (MAX). 1.170" HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test Report				
AF-4204-2 LOW FREQUENCY RIGHT ANGLE SPOT PROBE, SHIELDED, REFLECTION, 2-100KHZ, .500° DR OP, .200° DD FLAT TIP, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415°, OD 0.760° (MAX). 1.10° MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test LOW FREQUENCY RING RING RING RING RING RING RING RING	AF-4204-1	LOW FREQUENCY RIGHT ANGLE SPOT PROBE, SHIELDED, REFLECTION, 2-100KHZ, 500" DROP, 200" OD ROUNDED TIP, TRIAX FISCHER CONNECTOR.			•	
A DAGE LOW REQUENCY REFLECTION RING PROBE, 450HZ-2KHZ, ID 0.415", OD 0.760" (MAX). 1.10" MAX HEIGHT. TRIAX FISCHER CONNECTOR. Includes Test	AF-4204-2	LOW FREQUENCY RIGHT ANGLE SPOT PROBE, SHIELDED, REFLECTION, 2-100KHZ, 500" DROP, .200" OD FLAT TIP, TRIAX FISCHER CONNECTOR. Includes				
	AF-4206					

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-4207	LOW FREQUENCY ABSOLUTE SPOT PROBE, 1.5KHz-10KHz, .750" OD, 1.80" HEIGHT TRIAX FISCHER CONNECTOR FLAT SURFACE. Includes Test Report	720P2FJ	632-761-001		
AF-4209	and Certificate of Conformance. LOW FREQUENCY REFLECTION RING PROBE 1.40" Ø OD, .800" Ø ID, 100HZ-500HZ, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	TEK-4021-1	RR0114-5/TF		
AF-5004L	Conformance. HIGH FREQUENCY PENCIL PROBE, ABSOLUTE SHIELDED. LEFT HAND SIDE; NFE, 2MHZ, MICRODOT CONNECTOR. REFERENCE: AIRBUS A300-600 53-15-30. Includes Test Report and Certificate of Conformance.	206P004	206P004		
AF-5004R	HIGUDES TEST REPORT and Centrate Or Comonitance. HIGH FREQUENCY PENCIL PROBE, ABSOLUTE SHIELDED. RIGHT HAND SIDE; NFE, 2MHZ, MICRODOT CONNECTOR. REFERENCE: AIRBUS A300-600 53-15- 30. Includes Test Report and Centificate of Conformance.	206P003	206P003		
AF-5005	HIGH FREQUENCY SPRING LOADED EDDY CURRENT SURFACE SPOT PROBE, REFLECTION 50-500KHz. Includes Test Report and Certificate of Conformance.	•			
AF-5007/10.0MSS	HIGH FREQUENCY FLEXIBLE STAINLESS STEEL ROTARY PROBE, 100KHZ-2MHZ, 10.0mmØ, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance Reference: Airbus A318 A319/A320/A321 53-31-50-PB6.	KD1H52404,TEK-3005UFB			
AF-5007/10.4MSS	HIGH FREQUENCY FLEXIBLE STAINLESS STEEL ROTARY PROBE, 100KHZ-2MHZ, 10.4mmØ, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance Reference: Airbus A318 A319/A320/A321 53-31-50-PB6.	KD1H52404,TEK-3005UFB			
AF-5007/10.8MSS	HIGH FREQUENCY FLEXIBLE STAINLESS STEEL ROTARY PROBE, 100KHZ-2MHZ, 10.8mmØ, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR . Includes Test Report and Certificate of Conformance Reference: Airbus A318/A319/A320/A321 53-31-50-PB6.	KD1H52404,TEK-3005UFB			
AF-5007/11.0MSS	HIGH FREQUENCY FLEXIBLE STAINLESS STEEL ROTARY PROBE, 100KHZ-2MHZ, 11.0mmØ, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance Reference: Airbus A318/A319/A320/A321 53-31-50-PB6.	KD1H52404,TEK-3005UFB			
AF-5007/4.7MM	HIGH FREQUENCY FLEXIBLE ROTARY PROBE 100KHZ-2MHZ, 4.75mm(.187") O.D.x 90mm(3.54") WORKING LENGTH, 4-PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance53-31-50-PB6	KD-1 H-524.04.2			
AF-5007/6.1MSS	HIGH FREQUENCY FLEXIBLE STAINLESS STEEL ROTARY PROBE, 100KHZ-2MHZ, 6.1mmØ, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR . Includes Test Report and Certificate of Conformance Reference: Airbus A318.A319/A320/A321 53-31-50-PB6.	TEK-3005EM-6.1MM/SS			
AF-5007/7.8MM	HIGH FREQUENCY FLEXIBLE ROTARY PROBE, 100KHZ-2MHZ, 7.8mmØ, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR . Includes Test Report and Certificate of Conformance Reference: Airbus A318.A319/A320/A321 53-31-50-PB6	KD1H52404-1, KD1H52404 2			
AF-5007/7.8MSS	HIGH FREQUENCY FLEXIBLE STAINLESS STEEL ROTARY PROBE, 100KHZ-2MHZ, 7.8mmØ, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance Reference: Airbus A318.A319/A320/A321 53-31-50-PB6.	TEK-3005EM-7.8MM/SS			
AF-5007/9.0MSS	HIGH FREQUENCY FLEXIBLE STAINLESS STEEL ROTARY PROBE, 100KHZ-2MHZ, 9.0mm/Ø, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance Reference: Airbus A318.A319/A320/A321 53-31-50-PB6.	KD1H52404, TEK-3005UFB			
AF-5007/9.3MSS	HIGH FREQUENCY FLEXIBLE STAINLESS STEEL ROTARY PROBE, 100KHZ-2MHZ, 9.3mmǿ, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance Reference: Airbus A318.A319/A320/A321 53-31-50-PB6.	TEK-3005EM-9.3MM/SS			
AF-5007/9.4MSS	HIGH FREQUENCY FLEXIBLE STAINLESS STEEL ROTARY PROBE, 100KHZ-2MHZ, 9.4mmØ, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance Reference: Airbus A318.A319/A320/A321 53-31-50-PB6.	KD1H52404,TEK-3005UFB	KD1H52404-2	KD1H52404-1	
AF-5007/9.8MSS	HIGH FREQUENCY FLEXIBLE STAINLESS STEEL ROTARY PROBE, 100KHZ-2MHZ, 9.8mmØ, 90mm WORKING LENGTH, 4-PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance Reference: Airbus A318.A319/A320/A321 53-31-50-PB6.	KD1H52404,TEK-3005UFB			
AURYFB812875/2WL	UNIVERSAL FLAT BOTTOM ROTARY "Y" PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH .812"875" Includes Test Report and Certificate of Conformance.	URYFB812875			
AF-5008-1.120-1.240	MANUAL ADJUSTABLE X-PROBE. 1.120"-1.240", 9.0" LONG WITH SLEEVE, TRIAX FISCHER CONNECTOR, DIFFERENTIAL 25KHz-500KHz Includes Test Report and Certificate of Conformance.	NEC-3112-1.120/1.240			
AF-5008-1.235-1.355	MANUAL ADJUSTABLE X-PROBE. 1.565"-1.685", 9.0" LONG WITH SLEEVE, TRIAX FISCHER CONNECTOR, DIFFERENTIAL 25KHz-500KHz Includes Test Report and Certificate of Conformance.	NEC-3112-1.235/1.355			
AF-5008-1.565-1.685	MANUAL ADJUSTABLE X-PROBE, ABSOLUTE REFLECTION, 1.565"-1.685", 9.0" LONG WITH SLEEVE, TRIAX FISCHER CONNECTOR, DIFFERENTIAL 25KHz- 500KHz Includes Test Report and Certificate of Conformance.	NEC-3112-1.565/1.685			
AF-5009	HIGH FREQUENCY EDDY CURRENT PROBE, DIFFERENTIAL, .200" DROP 10° CRANK. FREQUENCY: 25KHZ-100KHZ WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-1006	TEK-2000		
AF-5014	ROHMANN HIGH FREQUENCY PROBE, STRAIGHT SHAFT SHIELDED. ABSOLUTE REFLECTION, 100KHz-6MHz WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. (ASP05400)	KAS 2-4	TEKR-24AS	ASP05400	
AF-5015	ROHMAN HIGH FREQUENCY ABSOLUTE / REFLECTION PROBE, 100Hz-10KHz, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PKA 19-5	TEK-4027		
AF-5015/7L	ROHMAN HIGH FREQUENCY ABSOLUTE / REFLECTION PROBE, 100Hz-10KHz, 7 PIN LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	PKA 19-5			
AF-5015-1.120/1.240	ROTARY ADJUSTABLE X-PROBE. 1.120"-1.240", 6.1" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, REFLECTION, 25KHz-500KHz Includes Test Report and Certificate of Conformance.	NEC-3111-1.120/1.240			
AF-5015-1.235/1.355	ROTARY ADJUSTABLE X-PROBE. 1.235"-1.355", 6.1" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, REFLECTION, 25KHz-500KHz Includes Test Report and Certificate of Conformance.	NEC-3111-1.235/1.355			
AF-5015-1.565/1.685	ROTARY ADJUSTABLE X-PROBE. 1.565"-1.685", 6.1" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, REFLECTION, UNSHIELDED 25KHz-500KHz Includes Test Report and Certificate of Conformance.	NEC-3111-1.565/1.685			
AF-5016	ROHMANN HIGH FREQUENCY PROBE, STRAIGHT SHAFT SHIELDED. REFLECTION / BRIDGE, 500KHz-8MHz WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	KDS 2-2			
AF-5023-1.375-1.5/5WL	HIGH FREQUENCY REFLECTION ROTARY PROBE, 5.0"WORKING LENGTH, EXPANDABLE FROM 1.375"-1.500", 25-500KHz USED WITH NDT618. Includes Test Report and Certificate of Conformance.	NEC-3036	TEK-3023		
AF-5026-1.0/1.125/5WL	HIGH FREQUENCY ROTARY PROBE, REFLECTION, EXPANDABLE FROM 1.0"-1.125", 25-500KHz SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. USED WITH NDT617. Includes Test Report and Certificate of Conformance.	NEC-3035	TEK-3021		
AF-5027875-1.0/5WL	HIGH FREQUENCY ROTARY PROBE, REFLECTION, 25-500KHz, EXPANDABLE FROM .875" -1.0". SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. USED WITH NDT618A Includes Test Report and Certificate of Conformance.	NEC-3113875	NEC-3113	TEK-3022.870	
AF-5032TF/2MHZ	HIGH FREQUENCY SURFACE PROBE 1-3MHz 15" CRANK WITH 90" TIP, 250" DROP. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	314P26			
AF-5227	CUSTOM BOBBIN PROBE, 100-500KHz, DIFFERENTIAL, .425" # 1.6" LONG WITH A 4 PIN FISCHER CONNECTOR. Used to inspect brass tubing I.D Includes Test Report and Certificate of Conformance.	•			
AF-5034	HOCKING RIGID SURFACE PROBE, 50-500KHz, .125" Ø 90" TIP 15" CRANK, .100" DROP WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	313P14			
AF-5034/.964-1.034	HIGH FREQUENCY BRIDGE DIFFERENTIAL ADJUSTABLE PROBE , 25KHZ, 4.325WL, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	NEC-3039	NFC-3039		

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-5034/.964-1.034/RA	HIGH FREQUENCY ROTARY PROBE RA 2000 SCANNER ABSOLUTE REFLECTION, 25KHZ, 4.325WL, 4 PIN FISCHER CONNECTOR. Includes Test Report and	NEC-3039	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-50347.964-1.034/RA	Certificate of Conformance. ROHMANN HIGH FREQUENCY ADJUSTABLE PROBE, 0° to 90°, 50KH2-3MHz, ABSOLUTE / REFLECTION, SHIELDED TRIAX FISCHER / LEMO CONNECTOR.	KAS 70-4	TEKR704AS	•	
AF-5036G1	Includes Test Report and Certificate of Conformance. PROBE GUIDE Material: Delrin. Diameter 0.430 ±0.025 (10.92mm ±0.064). Used in Boeing procedure 57-53-03 Part 6. Includes Certificate of	NDT2033			
AF-5036G2	Conformance. PROBE GUIDE Material: Delrin. Diameter 0.515 ±0.025 (13.08mm ±0.064). Used in Boeing procedure 57-53-03 Part 6. Includes Certificate of Conformance.	NDT2033			
AF-5048	HIGH FREQUENCY PROBE UNSHIELDED 25-500KHZ DIFFERENTIAL, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	NEC-1062	NEC-1062 TEK-1540		
AF-5048G	NDT ENGINEERING CORP. NEC-1062 PROBE GUIDE. Includes Certificate of Conformance.	NEC-1062G			•
ARRX625750	ADJUSTABLE ROTARY X-PROBE. EXPANDABLE FROM: .625"750" 100KHz-2MHz SUPPLIED WITH A 4 PIN STEP LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	BXRA-40-48	U8600934		
AF-5055	HIGH FREQUENCY DIFFERENTIAL BLADE PROBE, 50-500KH2(200KH2 CENTER FREQUENCY), TRIAX FISCHER CONNECTOR, 6.0" LONG, FLEXIBLE SHAFT, .060" FLAT (THICK), SHIELDED. Includes Test Report and Certificate of Conformance.	TEK-2059-1	NEC-1016-1	,	,
AF-5059	HIGH FREQUENCY BLADE PROBE, STRAIGHT, 6.5" LONG 50-500KHz WITH TRIAX FISCHER CONNECTOR.Includes Test Report and Certificate of Conformance.	•			
AF-5064	PENCIL PROBE 90° DEGREES, 1.5" DROP, UNSHIELDED, 50-500KHz. Includes Test Report and certificate of Conformance.	NEC-2110/TF	NEC-2110/TF	TEK-2030/TF	
AF-5068/2MHZ	HIGH FREQUENCY SURFACE PROBE 1/8"\$ .100" DROP, 25" DEGREES BENT, 1-3MHz, ABS SHIELDED WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	306P15	306P15		
AF-5078	HIGH FREQUENCY SURFACE PROBE, 072" OD, 4.0" LONG, BENT 35" AT 1.0", .200 DROP, SO0KHZ-1MHZ. TRIAX FISCHER CONNECTOR Includes Test Report and Certificate of Conformance.	PABM90C402/072	PABM90C402/072		
AF-5086	HIGH FREQUENCY EC PROBE 500KHz-2MHz ABSOLUTE SHIELDED 90° DEGREES WITH .200° DROP 1.0° CRANK TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PAB90C602			
AF-5087	CUSTOM EC-NDT SLIDING PROBE, DIFFERENTIAL SUPPLIED WITH A SIDE MOUNTED TRIAX FISCHER CONNECTOR. 50-500KHz. Includes Test Report and Certificate of Conformance.	SPC-345	TEK-1546	SPC-345	
AF-5088	CUSTOM ABSOLUTE EDDY CURRENT SLIDING PROBE, .375" RADIUS WITH .120" WIDE FIN FOR GROOVE INSPECTION, SUPPLIED WITH A TOP MOUNTED TRIAX FISCHER CONNECTOR 25-100KHz. Includes Test Report and Certificate of Conformance.	SPC-520B	TEK-4052	SPC-520B	
AF-5089	SUFACE PROBE SHIELDED, .075"Ø(1.9mm) TIP RIGHT ANGLE SHIELDED .118"(3mm) DROP, BENT 30° APPROXIMATELY 0.787"(20mm) AT HANDLE 5.0" LONG TRIAX FISCHER 50-500KHZ. Includes Test Report ancd Certificate of Conformance.	PABM90C2401/.072	PABM90C2401/.072		
AF-5091/.093	RIGID SURFACE PROBE,1-3MHZ, 90° DEGREES SHIELDED.500" DROP.093"Ø TUBING 4.5" LONG 15° DEGREES CRANK IN THE SHAFT, MICRODOT CONNECTOR. Includes Test Report and Certificate of conformance.	314P14F	314P14F		
AF-5096/2M	SURFACE PROBE ABSSOLUTE SHEILDED, 1-3MHZ, 90° DEGREES, 200° DROP, .098°Ø TUBING, 4.0° LONG 30° DEGREES BENT AT 1.0" FROM THE HANDLE WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	2-835-74-6901	2-835-74-6901		
AF-5096/2M/LOO	RIGID SURFACE PROBE ABS SHEILDED 90° DEGREES.200" DROP, .098"Ø, 30°DEGREES CRANK AT 1.0" FROM THE HANDLE , 4.0" LONG WITH LEMO 00 CONNECTOR 1-3MHZ. Includes Test Report and Certificate of Conformance.	2-835-74-6901	2-835-74-6901		
AF-5097/2M	RIGID SURFACE PROBE ABSOLUTE SHEILDED 1-3 MHZ, CURVED 45° DEGREES, .490° DROP, 2.0° LONG .098°Ø TUBING WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	2-835-07-6902	2-835-07-6902		
AF-5097/2M/LOO	RIGID SURFACE PROBE ABS SHEILDED,45° DEGREES CURVED1-3 MHz, .098°Ø .490° DROP 2.0° LONG WITH LEMO 00 CONNECTOR. Includes Test Report and Certificate of Conformance.	2-835-07-6902	2-835-07-6902		
AF-5101	LOW FREQUENCY REFLECTION SHIELDED SPOT PROBE TRIAX FISCHER CONNECTOR 800Hz-30KHz. NTM 53-31-81, PT 6. Includes Test Report and Certificate of Conformance.	NEC4031	TEK-1528	SPT-2011	
AF-5104	SPECIAL SPRING LOADED SURFACE PROBE, ABSOLUTE COIL 1-3MHz WITH MICRODOT CONNECTOR. PER AIRBUS SPECIFICATION A318/A319/A320/A321 57-20-40-991-002-A. Includes Test Report and Certificate of Conformance.	LT-82-1E	TEK-2035,	LT82-1E, LT 82-1E	
AF-5105	SURFACE PROBE.093"Ø DIA. TUBING .040" DROP, .062"Ø DIA TUBING BENT AT 1.5" 30" DEGREES, TRIAX FISCHER CONNECTOR 6.0" LONG 50-500KHz. Includes Test Report and Certificate of Conformance.	NEC-2111/TF			
AF-5106	SUBSURFACE PROBE REFLECTION .160"Ø DIA, .500" DROP, BENT AT 1.0" SHAFT 6.0" LONG, TRIAX FISCHER CONNECTOR 4-100KHz includes Test Report and Certificate of Conformance.	SPC-304R/FE			
AF-5111/4F	ROHMANN SURFACE PROBE ABSOLUTE SHEILDED 30° DEGREES, 4.0mm Ø DIA (.156") WITH 4 PIN FISCHER CONNECTOR, 100KHZ-5MHZ. Includes Test Report and Certificate of Conformance. (ASP05351)	KAS 66-3	KAS-66-3	KAS66-3	
AF-5111/TF	ROHMANN SURFACE PROBE ABSOLUTE SHEILDED 30° DEGREES, 4.0mm Ø DIA (.156") WITH TRIAX FISCHER CONNECTOR, 100KHZ-5MHZ. Includes Test Report and Certificate of Conformance. (ASP05351)	KAS 66-3	KAS-66-3	KAS66-3	
AF-5111R/4F	ROHMANN SURFACE PROBE REFLECTION 30° DEGREES, 4.0mm Ø DIA (.156") WITH 4 PIN FISCHER CONNECTOR, 100KHZ-5MHZ. Includes Test Report and Certificate of Conformance. (ASP05351)	KAS 66-3			
AF-5114	SURFACE EDGE PROBE TRIAX FISCHER CONNECTOR DIFFERENTIAL 50-500KHZ. 6.0" LONG PIGTAIL CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AF-5115	CUSTOM ROHMANN SURFACE PROBE ABSOLUTE STRAIGHT 75mm(2.95") LONG TRIAX FISCHER CONNECTOR 2.0mm TIP Ø DIA (.079") 10KHZ-800KHZ. Includes Test Report and Certificate of Conformance.	KA 2-1	ASP00100		
AF-5115/4F	CUSTOM ROHMANN SURFACE PROBE ABSOLUTE STRAIGHT 75mm(2.95") LONG 4 PIN FISCHER CONNECTOR 2.0mm TIP Ø DIA (.079") 10KHZ-800KHZ. Includes Test Report and Certificate of Conformance.	KA 2-1	ASP00100		
AF-5116/1MHZ	CUSTOM S-SHAPED FLEXIBLE SURFACE PROBE FOR LOWER SURFACE FLAP TRACK INSPECTION. 500KHz-2MHz, 7.0° LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	EMB145			
AF-5117	HIGH FREQUENCY SPOT PROBE, UNSHIELDED DIFFERENTIAL / BRIDGE, .250"Ø COIL, .312"Ø TIP , 100KHz-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPTU-001			
AF-5123/4F	CUSTOM PIVOTING EDDY CURRENT PROBE DIFFERENTIAL 50-100KHz. 4-PIN FISCHER CONNECTOR. AIRBUS A300-600 PT 6 53-19-27 PAGE 619. Includes Test Report and Certificate of Conformance.	MDK4-5	TEK-1514		
AF-5124/1MHZ	CUSTOM L-SHAPED FLEXIBLE SURFACE PROBE FOR LOWER SURFACE FLAP TRACK INSPECTION. 500KHz-2MHz, 7.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	EMB145		•	
AF-5125/1MHZ	CUSTOM J-SHAPED FLEXIBLE SURFACE PROBE FOR LOWER SURFACE FLAP TRACK INSPECTION. SOOKH2-2MH2, 7.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	EMB145			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EOUIVALENT	EQUIVALENT
AF-5133/16L	LOW FREQUENCY REFLECTION SURFACE PROBE, .187"Ø TUBING, 1.0" LONG HARDWIRD TO 16 PIN LEMO CONNECTOR 6.0' LONG, 1-5KHz. Includes Test	D0815F1015-2107	SPO-2883I	EQOIVALENT	EQUIVALENT
AF-5133/10L AF-5134L/2MHZ	Report and Certificate of Conformance. SURFACE PROBE 90° DEGREES, .030° DROP125" Ø TUBING, LEFT HAND, 15.50° LONG, 1.378° RADIUS WITH MICRODOT CONNECTOR 1-3MHz. Includes	813P027A	5PU-2883L	•	
AF-5134R/2MHZ	Test Report and Certificate of Conformance. SURFACE PROBE 90° DEGREES, 0.30° DROP. 125° Ø TUBING, RIGHT HAND, 15.50° LONG, 1.378° RADIUS WITH MICRODOT CONNECTOR 1-3MHz.	813P027B			
AF-5135L/2MHZ	Includes Test Report and Certificate of Conformance. SURFACE PROBE 90° DEGREES, .030° DROP. 125° Ø TUBING, LEFT HAND, 10.0° LONG, 1.535° RADIUS WITH MICRODOT CONNECTOR 1-3MHz. Includes Test Report and Certificate of Conformance.	813P028A		•	
AF-5135R/2MHZ	Test Report and Certificate of Conformance. SURFACE PROBE 90° DEGREES, 030° DROP. 125″ Ø TUBING, RIGHT HAND, 10.0° LONG, 1.535° RADIUS WITH MICRODOT CONNECTOR 1-3MHz. Includes Test Report and Certificate of Conformance.	813P028B			
AF-5137	Pencil Probe with Acrylic Adjustable Collar 100KHz-500KHz, ABS/Bridge Shielded Supplied with Triax Fischer Connector. Includes Test Report and Certificate of Conformance.	9213408	U8623158		•
AF-5139	CUSTOM ROTATING SCANNER PROBE 118-135 DEGREE DRILLED COUNTERSINK (.256"Ø)100KHZ-2MHZ. 4 PIN FISCHER CONNECTOR. Includes Test Report and Certification of conformance.				
AF-5140	Custom Eddy Current Encirling Probe, 890"Ø ID, 500KHz-1MHz Differential, Triax Fischer Connector. Inspecting ASTM A513 Type 5 Steel Includes Test Report and Certificate of Conformance.			•	
AF-5141/TF	USTOM EDDY CURRENT PENCIL PROBE(DELRIN - BLACK ACETAL), STRAIGHT SHAFT WITH THE COIL CENTERED AT THE TIP .250"Ø, 50-500KHz UNSHIELDED WITH TRIAX FISCHER CONNECTOR, 3.0: LONG. Includes Test Report and Certificate of Conformance.	•			
AF-5142	Rigid Surface Probe Abs Unhielded, 200KHz Center Frequency, 50-500KHz operating range, .187"Ø Handle with .093"Ø Straight Shaft Metal 2.5" With Delrin Tip, 4.5" Total Length with Microdot Connector. Includes Test Report and Certificate of Conformance	379-002-502			
AF-5143	ABSOLUTE UNSHIELDED BROAD BAND PROBE, 100KHz. FREQUENCY RANGE: 35KHz-250KHz. SUPPLIED WITH BNC SOCKET CONNECTOR. Includes Test Report and Certificate of Conformance.	PUB100K			
AF-5144	Rigid Surface Probe Absolute Shielded, 200KHz Center Frequency, .187*Ø Tip, 90*, .250° DROP, 15° Degree Crank, 4.5° long with Microdot Connector. Includes Test Report and Certificate of Conformance. Reference: 610-094-111	312P24	610-094-111	•	
AF-5145	Custom Rotary Probe for Radiused Hole Inspection100KHz-2MHz., .250"Ø 4 Pin Fischer Connector with 2.0: working Length. Includes Test Report and Certificate of Conformance.			•	
AF-5145/4F	ABSOLUTE SMALL SURFACE CRACK PROBE. 10KHZ-100KHZ. 76.5 x 12 mm (HxW). 4-PIN FISCHER CONNECTOR. PLASTIC PENCIL HOUSING. Includes test report.	KA 82-5			
AF-5146/2MHZ	RIGID SURFACE PROBE ABS SHEILDED 90° DEGREES.200° DROP, .098°Ø TIP .156°Ø TUBING REDUCED TO .079 AT THE TIP, 4.0° LONG WITH MICRODOT CONNECTOR 1-3MHZ. Includes Test Report and Certificate of Conformance.	2-835-03-6902			
AF-5146/L00	RIGID SURFACE PROBE ABS SHEILDED 90° DEGREES.200° DROP, .098°Ø TIP .156°Ø TUBING REDUCED TO .079 AT THE TIP, 4.0° LONG WITH LEMO 00 CONNECTOR 1-3MHZ. Includes Test Report and Certificate of Conformance.	2-835-03-6902			
AF-5147/4F	ABSOLUTE SURFACE PROBE, TIP OD 1.6 mm. 45 DEG. ANGLE. 5" LONG. 100KHZ-3MHZ. 4-PIN FISCHER CONNECTOR. Includes test report.	KA-2H-1744.03.1			
AF-5149/4F	CUSTOM ROHMANN SURFACE PROBE ABSOLUTE STRAIGHT 75mm(2.95") LONG 4 PIN FISCHER CONNECTOR 9.5MM Ø DIA (.374") 500KHZ-3MHZ PLASTIC HOUSING. Includes Test Report and Certificate of Conformance.	KA 2-4	ASP00210		
AF-5150/2M/7L	ABSOLUTE REFLECTION PENCIL PROBE. SHIELDED. POWERLINK CONNECTOR/7-Pin LEMO. 4" LONG. BODY DELRIN. 1MHZ-3MHZ. Includes Test Report and Certificate of Conformance.	9222430			
AF-5153/7L	DIFFERENTIAL REFLECTION PENCIL PROBE. UNSHIELDED. POWERLINK CONNECTOR/7-Pin LEMO CONNECTOR. 4" LONG. BODY DELRIN. 500KHZ-3MHZ. Includes Test Report and Certificate of Conformance.	•		•	
AF-5154	LOW FREQUENCY SURFACE PROBE. DIFFERENTIAL375 DROP312 TIP DIAMETER. 6.0" LONG. 1-20KHZ. TRIAX FISCHER CONNECTOR. Includes test reportCONDUCTIVITY REFLECTION PROBE. RIGHT ANGLE. 200HZ-100KHZ. CENTER FREQUENCY 60KHZ. TRIAX FISCHER CONNECTOR	VMD120-05-6375 SH		•	
AF-5155	LOW FREQUENCY SURFACE PROBE. REFLECTION500 DROP312 TIP DIAMETER. 6.0" LONG. 1-20KHZ. TRIAX FISCHER CONNECTOR. Includes test report. CONDUCTIVITY REFLECTION PROBE. RIGHT ANGLE. 200HZ-100KHZ. CENTER FREQUENCY 60KHZ. TRIAX FISCHER CONNECTOR. I	VMR120-05-6.5		•	
AF-5156	RIGHT ANGLE CONDUCTIVITY PROBE. CENTER FREQUENCY 60 KHZ. 200HZ-100KHZ FREQUENCY. TRIAX FISCHER CONNECTOR420 DIAMETER. Includes Test Report and Certificate of Conformance.	KAS-7 H190.03.1			
AF-5157-2.5	CUSTOM WHEEL BEAD SEAT PROBE WITH A .125" RADIUS, UNSHIELDED 50-500KHz WITH A MICRODOT CONNECTOR, 2.50" INCHES LONG. Includes Test Report and Certificate of Conformance.	TEK-2020-2.5, NEC-2012			
AF-5157-3	CUSTOM WHEEL BEAD SEAT PROBE WITH A .125" RADIUS, UNSHIELDED 50-500KHz WITH A MICRODOT CONNECTOR, 3.0" INCHES LONG. Includes Test Report and Certificate of Conformance.	TEK-2020-3, NEC-2012-3			
AF-5158/L500K	SURFACE PROBE ABSOLUTE SHEILDED, LOCATOR 500K. 90° DEGREES, 500° DROP, 175°Ø TUBING, (47uH) 6.0° LONG 15° DEGREES BENT AT 1.0° FROM THE TIP WITH A MICRODOT CONNECTOR. 125 SHAFT OD. Includes Test Report and Certificate of Conformance.	313P36		•	
AF-5159	CUSTOM STRAIGHT SHAFT SURFACE PROBE WITH DELRIN TIP 50-500KHz WITH MICRODOT CONNECTOR, 6.0" LONG. Includes Test Report and Certificate of Conformance.	•		•	
AF-5160	SURFACE PROBE UNSHIELDED, DIFFERENTIAL 2.0" LONG, WITH GUIDE PIN, 25-200KHZ, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-1079	TEK-2017	•	
AF-5164/TF	MANUAL BOLT HOLE PROBE WITH DELRIN (PLASTIC)50-500KHZ DIFFERENTIAL UNSHIELDED, WITH A TRIAX FISCHER CONNECTOR.250" DIA., 3.0" INCH WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•			
AF-5166	OD ENCIRCLING PROBE, DIFFERENTIAL 1-6MHZ, 1/8" TUBING OD. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	•			
AF-5167	OD ENCIRCLING PROBE, DIFFERENTIAL 1-6MHZ, 1/4" TUBING OD, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AF-5168	OD ENCIRCLING PROBE, DIFFERENTIAL 1-6MHZ, .375" TUBING OD, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AF-5169/3KHZ	CONDUCTIVITY REFLECTION PROBE. RIGHT ANGLE. 200HZ-100KHZ. CENTER FREQUENCY 60KHZ. TRIAX FISCHER CONNECTOR. Includes Test Report and	PU001V1			
AF-561A	RIGID SURFACE PROBE 50-500KHz, BENT LEFT 60° AT 1.0" FROM THE TIP, .030" DROP, .125"Ø TUBING, 6.0" LONG. Includes Test Report and Certificate of Conformance.	SPC-561A		•	
AF-561C	RIGID SURFACE PROBE 50-500KHz, BENT UP 60" AT 1.0" FROM THE TIP, .030" DROP, .125"Ø TUBING, 6.0" LONG. Includes Test Report and Certificate of Conformance.	SPC-561C			
AF-6002/TF	GE SLIDING PROBE, ABSOLUTE REFLECTION, 400H2-50KHz, .790" WIDE by 2.0" LONG. SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of conformance.	851P001,632-481-500	851P001 TEK-4012	.spc-555c/refl	

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AF-6003/TF	SLIDING PROBE , REFLECTION, 1-100KHZ, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-2210	SPO-2210 TEK-4035		
AF-6004	SLIDING PROBE, REFLECTION, 1KHz-100KHz, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformation.	NEC-4039,TEK-1504	SLD-001, PKA-52-H-1835	PKA-52 H-1835;379-010- 300	9211636, SPO-367 DF
AF-6004/4L	SLIDING PROBE, REFLECTION, 1KHz-100KHz, WITH 4 PIN LEMO CONNECTOR. Includes Test Report and Certificate of Conformation.	TEK-1504/4L			
AF-6004/7L	SLIDING PROBE, REFLECTION, 1KHz-100KHz, WITH 7 PIN LEMO CONNECTOR. Includes Test Report and Certificate of Conformation.	NEC-4039/7L			
AF-6005/150HZ	ADJUSTABLE SLIDING PROBE, REFLECTION, 50HZ-8KHZ, WITH 2 SINGLE MICRODOT CONNECTORS. Includes Test Report and Certificate of Conformance.	SPO-1957			
AF-6006	SLIDING PROBE, REFLECTION, 1-40KHZ TRIAX FISHER CONNECTOR. REFERENCE STANDARD USED (NDT1099) 757 PT. 6, 53-30-14. Includes Certification Report and COC.	TEK-4070-1.0	SPC-555A	NEC 1108;	
AF-6008	SLIDING PROBE 5-30KHz, REFLECTION, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPC-555C		SPC-555C/REFL	
AF-6012	FIXED SLIDING PROBE,1KHz-100KHz REFLECTION, 1.5" Long x.800" Wide X 1.0" High, TRIAX FISCHER CONNECTOR (NEC1059,SPO-3806). PART 6 53-10- 03. Includes Test Report and Certificate of Conformance.	SPO-3806	NEC-1059	9230492	,
AF-6012/L00	FIXED SLIDING PROBE REFLECTION LEMO 00 CONNECTOR 1,5" L X .800" W X1.0" H 1-100KHZ (NEC1059,SPO-3806), 9222242. Includes Test Report and Certificate of Conformance.	SPO-3806L	9222242		
AF-6015/TF	FIXED SLIDING PROBE, REFLECTION, 1KHZ-100KHZ, WITH A TRIAX FISCHER CONNECTOR.SIZE: 1.30"L x.850"W x1.20"H. Includes Test Report and Certificate of Conformance	SLD-1K-T 1-100khz			
AF-6017	SLIDING PROBE, REFLECTION, 100Hz-40KHz, WITH 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformation.	PKA4H34-03-01			
AF-6018	ADJUSTABLE SLIDING PROBE, REFLECTION, 100HZ-500KHZ, WITH 2 SINGLE MICRODOT. Includes Test Report and Cerfificate of Conformance.	851P002	851P002	ASLD-500H	
AF-6019	ADJUSTABLE SLIDING PROBE, REFLECTION, 100HZ-S00HZ, WITH 2 SINGLE MICRODOT CONNECTORS. SIZE: 3.50"L x 1.312"W x 1.250"H. Includes Test Report and Certificate of Conformance.	NEC-4081			
AF-6020	ADJUSTABLE SLIDING PROBE, REFLECTION, 1KHZ-20KHZ, WITH 2 SINGLE MICRODOT CONNECTORS. 5" DIA. 100" spacers and .050" spacers. Includes Test Report and Certificate of Conformance.	SLDADJ-001			
AF-6021	ABOSLUTE SLIDING PROBE WITH SEPARATE DRIVER/RECEIVER COILS, REFLECTION. ALUMINUM HOUSING. 200HZ-100KHz. 4-Pin FISCHER CONNECTOR. Includes Test Report and Certificate of Conformation.	PKA-162-18E			
ASDP-7MM/100K	LOW FREQUENCY REFLECTION SPOT PROBE, 7MM(.275") 1KHz-100KHz TOP MOUNTED TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AFNDT-3133	CUSTOM 100° COUNTERSINK BOLT HOLE STANDARD MAUNUFACTURED TO BOEING PART NUMBER 194A, 737 PART 6 53-30-00. MATERIAL: 2024-T3 CLAD ALUMINUM. HOLE SIZES: 2 HOLES 8.6mmØ. Includes Test Report and Certificate of Conformance.				
ASDP-13MM/100K	LOW FREQUENCY REFLECTION SPOT PROBE,13MM(.512") 200Hz-100KHz TOP MOUNTED TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AURY-3.0-5.0MM/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 3.0-5.0mmØ. Includes Test Report and Certificate of Conformance.	•			
AURY-5.0-7.0MM/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 5.0-7.0mmØ. Includes Test Report and Certificate of Conformance.				
ASDP-11MM/100K	LOW FREQUENCY REFLECTION SPOT PROBE,11MM(433") 300Hz-100KHz TOP MOUNTED TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AFK-5300SE-7	LUSIOM EDUT CURRENT FLEXIBLE SPRING SHAFT RUTARY PROBE KIT. 125 'Ø TO 500' Ø. INCLUDES THE FULLOWING 7 PROBE PART NUMBERS. AF-5300- 1255E/17-6L, AF-5300-1555E/17-6L, AF-5300-1875E/17-6L, AF-5300-2505E/17-6L, AF-5300-3125E/17-6L, AF-5300-3755E/17-6L, AF-5300- 137E/17-11, elvides Vietnered Kir Bound Ford Conference of Cardination Provides Conference of Cardination P	•		•	
AF-6022/4F	CUSTOM SLIDING PROBE, REFLECTION WITH A 4 PIN FISCHER CONNECTOR 50Hz-50KHz .905" WIDE x 1.18" HIGH x 1.77" LONG, INCLUDES PLEXIGLASS GUIDE.	MBB543A	2-832-01-3400		
AF-6023	FIXED SLIDING PROBE, 1KHz-100KHz REFLECTION, 1.7" Long x 1.0" Wide X 1.2" High, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. 9216183	SPO-3993	9216183		
AF-8001/4F	PRATT & WHITTNEY ENGINE BLADE PROBE, DIFFERENTIAL 1-4 MHz, SUPPLIED WITH 4 PIN FISCHER CONNECTOR. DIFFERENTIAL 1-4 MHz. Includes Test Report and Certificate of Conformance.	PWA75909A			
AFLX-10	STRAIGHT FLEXIBLE SHAFT PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 10.0° LENGTH. Includes Certificate of Conformance.	AMF-MR-10FX			
AFLX-12	STRAIGHT FLEXIBLE SHAFT PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 12.0° LENGTH. Includes Certificate of Conformance.				
AFLX-18	STRAIGHT FLEXIBLE SHAFT PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 18.0" LENGTH. Includes Certificate of Conformance.	•			
AFLX-3	STRAIGHT FLEXIBLE SHAFT PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 3.0" LENGTH. Includes Certificate of Conformance.	•			
AXXTPN-92-3/200K-1M	SURFACE PROBE, 90° DEGREES ANGLED, .062°Ø TIP .20° DROP, 200KHz-1MHz, TRIAX FISCHER CONNECTOR, 3° LONG. Includes Test Report and Certificate of Conformance	MZTF902-30-200K-1M			
AURY-11-13MM/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 11.0mm-13.0mm. Includes Test Report and Certificate of Conformance.	URY 11-13M			
AFLX-6	STRAIGHT FLEXIBLE SHAFT PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 6.0" LENGTH. Includes Certificate of Conformance.	MFLX-6			
AFLX-8	STRAIGHT FLEXIBLE SHAFT PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 8.0" LENGTH. Includes Certificate of Conformance.	AMF-MR-8FX			
AF-5034/TF	HOCKING RIGID SURFACE PROBE, 50-500KHz, 125"Ø 90" TIP 15" CRANK, .100" DROP, 4.5"(114MM) LONG SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AFLX-9	STRAIGHT FLEXIBLE SHAFT PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 9.0" LENGTH. Includes Certificate of Conformance.	MFLX-9			
AFLXR-10	90" DEGREE FLEXIBLE SHAFT RIGHT ANGLE PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 10.0" LENGTH. Includes Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURY-9.0-11MM/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 9.0-10.0mmØ.	EQUIVALENT	EQONALINI	EQONALLINT	EQOIVALENT
AMHF-1.0	Includes Test Report and Certificate of Conformance. MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ MICRODOT CONNECTOR 1.0" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report	BPMF-64			
AFLXR-12	and Certificate of Conformance. 90° DEGREE FLEXIBLE SHAFT RIGHT ANGLE PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 12.0° LENGTH. Includes Certificate of	Drivil -04			
AFLXR-15	Conformance. 90° DEGREE FLEXIBLE SHAFT RIGHT ANGLE PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 15.0° LENGTH. Includes Certificate of	•			
AFLXR-6	Conformance. 90° DEGREE FLEXIBLE SHAFT RIGHT ANGLE PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 6.0" LENGTH. Includes Certificate of	MFLXR-6	AFLX90-6	AMF-MR-6FX/S	
	Conformance. 90° DEGREE FLEXIBLE SHAFT RIGHT ANGLE PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 8.0° LENGTH. Includes Certificate of			ANT-NIK-OFA/3	
AFLXR-8	Conformance.	SPC-604FX-8	MFLXR-8	•	
AURY-7.0-9.0MM/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 7.0-9.0mmø. Includes Test Report and Certificate of Conformance.			•	
ACSM100-8.5M	100° DEGREE COUNTER SINK PROBE 50-500KHz, SUPPLIED WITH A MICRODOT CONNECTOR, 8.5mmØ OD. Includes Test Report and Certificate of Conformance				
AF-MBB403-7-1	CUSTOM STAINLESS STEEL EDDY CURRENT ROTARY PROBE INCLUDING COLLAR, FREQUENCY 100KHz-20HHz WITH 4 PIN FISCHER CONNECTOR. REFERENCE: AIRBUS A300-600 FIGURE 603 PART 6 53-19-27 PAGE 604 PROCEDURE A. Includes Test Report and Certificate of Conformance.	MBB403-7-1			
C-130 FIXTURE	Custom C-130 Blade Inside Bushing Probe Fixture per Drawing No. 201757983. Material: ABS Plastic machined not 3D Printed.	201757983			
AF-PTR002PNFE/2M	External / Internal Threads Probe, Thread, 90° degrees., 2 MHz, Pointed, FE, Unshielded with microdot connector. Includes Test Report and Certificate of Conformance.	PTR002PNFE			
AF-PTR500PFE/L500K	External / Internal Threads Probe, Thread, 90° degrees., 500 kHz, 47UH Locator Pointed, FE, Unshielded with microdot connector. Includes Test Report and Certificate of Conformance.	PTR500PFE			
ASPN-95-5B/7L	RIGID PENCIL PROBE ABS SHIELDED 50-500KHz, 90° DEGREES, BENT 30° DEGREES, .500° DROP .093 TUBING. 5.0° LONG. 7 Pin LEMO CONNECTOR. Includes Test Report and Certificate of Conformance	PA7B90C505			
AURFB-8.0MSE/1.5WL	UNIVERSAL FLAT BOTTOM ROTARY PROBE (DELRIN) WITHA 30° COIL ANGLE, 8.0mmø(0.315°), 40mm(1.5°) WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KH2-2MHZ. Includes Test Report and Certificate of Conformance.	•			
AURFB-9.0MSE/1.5WL	UNIVERSAL FLAT BOTTOM ROTARY PROBE (DELRIN) WITH A 30° COIL ANGLE, 9.0mm¢(0.354"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.			•	
AURFX687SE/.5T/4WL	ADJUSTABLE FLEX SHAFT ROTARY PROBE, SPLIT END, :687"750", 0.500" LONG TIP, 4.0" WORKING LENGTH (NO SLEEVE). 4 PIN FISCHER CONNECTOR 100KHz-2MHz. Includes Test Report and Certificate of Conformance.	•			
ACSM100-8.4M	100° DEGREE COUNTER SINK PROBE 50-500KHz, SUPPLIED WITH A MICRODOT CONNECTOR, 8.4mmØ OD. Includes Test Report and Certificate of Conformance				
AXPN-92-4.5FX/7L	PENCIL SURFACE PROBE. 90° 4.5 " LONG .072" MINI Tip. 50-500KHz. 7 Pin LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	PABM9045200	MMTF902-45FX		
AMH.125	Manual hole probe, 0.125 inch (3.1mm) diameter and 1.1 inch (27.9mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration Includes Test Report and Certificate of Conformance.	BPM-8	U8600033, MBA 1-8	VM101BS-1/8	BPM-8
AMH.125/1.1WL	MANUAL .125" Ø DIAMETER BOLT HOLE PROBE WITH COLLAR 50-500KHZ MICRODOT CONNECTOR 1.1" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•			
AMH125L00SE/76MWL	STAINLESS STEEL MANUAL BOLT HOLE PROBE WITH DELRIN(PLASTIC) SPLIT END TIP. 200KHZ SHIELDED, 00 LEMO CONNECTOR 76mm WORKING LENGTH 3.2mm@(1/8") HEAD SIZE. Includes Test Report and Certificate of Conformance.	PB200R032			
AMH.156	Manual hole probe, unshielded, 0.156 inch (3.9mm) diameter and 1.1 inch (27.9mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	BPM-10 9216153	BPM-10, 9216153	VM101BS-5/32	U8600001
AMH.156/1.1WL	MANUAL .156"Ø DIAMETER BOLT HOLE PROBE WITH COLLAR 50-500KHZ MICRODOT CONNECTOR 1.1" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AMH.156SE	Manual Bolt Hole Probe, Split End(SE) 0.156 inch (4.7mm) diameter expandable from .156"187", 1.1 inch (27.9mm) working length, frequency 50kHz - 500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of C	MHX156187			
AMH.187	Manual hole probe, 0.187 inch (4.7mm) diameter and 1.1 inch (27.9mm) working length, frequency S0kHz -S00kHz, microdot connector, bridge absolute coil configuration. Includes Text Beoort and Certificate of Conformance.	BPM-12	U8600003, MH.187	9216154	BPM-12
AMH.187/1.1WL	Concoming a storm includes rest report and certificate or comormance. MANUAL .187"Ø DIAMETER BOLT HOLE PROBE WITH COLLAR 50-500KHZ MICRODOT CONNECTOR 1.1" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				DFINI-12
AMH.187/BNC-6	MANUAL BOLT HOLE PROBE 50-500KHZ HARD WIRED TO 6.0' FT. LONG CABLE TO BNC CONNECTOR, 187"Ø. Includes Test Report and Certificate of Conformance.	6200-3/16-BH-BNC			
AMH.187SE	Contomance: Manual Bolt Hole Probe, Split End(SE) 0.187 inch (4.7mm) diameter expandable from .187"-250", 2.0 inch (27.9mm) working length, frequency 50kHz - 500kHz, microdot connector, bridge absolute coli configuration. Includes Test Report and Certificate of C	•			
AMH.218	Source, microad connector, bridge absolute con coninguration. Includes risk report and certificate of C Manual hole probe, 0.218 inch (5.5mm) diameter and 1.1 inch (27.9mm) working length, frequency SokHz -SoOkHz, microdot connector, bridge absolute coil configuration. Includes Tex Report and Certificate of Conformance.	BPM-14	U8600352		
AMH.234	Concomguration. Includes rest report and certificate of conformance. Manual hole probe, 0.234 inch (5.94mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coli configuration. Includes Test Report and Certificate of Conformance.				-
AMH.250	assolute coil configuration. Includes Test Report and Certificate of Conformance. Manual hole probe, 0.250 inch (6.35mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	BPM-16	U8600007	9216156	
AMH.250SE	assolute coil configuration. Includes Test Report and Certificate of Conformance. Manual hole probe, 0.250 inch (6.35mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	•			
AMH.281	Manual hole probe, 0.281 inch (7.1mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute	BPM-18	U8600010		
AMH.312	coil configuration. Includes Test Report Certificate of Conformance. Manual hole probe, 0.312 inch (7.9mm) diameter and 2.0 inch (5.08cm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute	BPM-20	U8600011		
AMH.343	coil configuration. Includes Test Report and Certificate of Conformance. Manual hole probe, 0.343 inch (8.71mm) diameter and 2.0 inch (5.08cm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute	BPM-22			
AMH.375	coil configuration. Includes Test Report and Certificate of Conformance. Manual hole probe, 0.375 inch (9.5mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute	BPM-24			
AU1.3/3	coil configuration. Includes Test Report and Certificate of Conformance.	DT W1*24	000001/	•	

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AMH.406	Manual hole probe, 0.406 inch (10.31mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge	BPM-26	U8600598		
AMH.437	absolute coil configuration. Includes Test Report and Certificate of Conformance. Manual hole probe, 0.437 inch (11.1mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	BPM-28	U8600018		
AMH.500	Ausual hole probe, 0.500 inch (12.7mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coli configuration. Includes Test Report and Certificate of Conformance.	BPM-32	U8600022		
AMH.562	Manual hole probe, 0.562 inch (14.27mm) diameter and 2.0 inch (5.08cm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	BPM-36			
AMH.625	Manual hole probe, 0.625 inch (15.875mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	BPM-40			
AMH.625/1.1WL	MANUAL. 625" Ø DIAMETER BOLT HOLE PROBE WITH COLLAR 50-500KHZ MICRODOT CONNECTOR 1.1" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•			
AMH.687	Manual hole probe, 0.687 inch (17.45mm) diameter and 2.0 inch (5.08cm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	BPM-44			
AMH.750	Manual hole probe, 0.750 inch (19.05mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	BPM-48			
AMH.875	MANUAL BOLT HOLE PROBE, 50-500KHZ MICRODOT CONNECTOR .750" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	BPM-56			
AMH.937	MANUAL BOLT HOLE PROBE, 50-500KHZ MICRODOT CONNECTOR.937"Ø x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	BPM-60			
AMH-12.5ML00SE/76MWL	MANUAL BOLT HOLE PROBE WITH DELRIN(PLASTIC) SPLIT END TIP. 200KHZ SHIELDED, 00 LEMO CONNECTOR 76mm WORKING LENGTH 12.5mmØ(1/2"), EXPANDABLE TO 14.0mmØ. Includes Test Report and Certificate of Conformance.	PB200R125-140			
AMH-19.0ML00SE/76MWL	MANUAL BOLT HOLE PROBE WITH DELRIN(PLASTIC) SPLIT END TIP. 200KHZ SHIELDED, 00 LEMO CONNECTOR 76mm WORKING LENGTH 19mmø(3/4"), EXPANDABLE TO 20.5mmø. Includes Test Report and Certificate of Conformance.	PB200R190-205			
AMH-22ML00SE/76MWL	MANUAL BOLT HOLE PROBE WITH DELRIN(PLASTIC) SPLIT END TIP. 200KHZ SHIELDED, 00 LEMO CONNECTOR 76mm WORKING LENGTH 22.0mm@(7/8"), EXPANDABLE TO 23.5mm@. Includes Test Report and Certificate of Conformance.	PB200R220-235			
AMH-23.5ML00/76MWL	SMANUAL BOLT HOLE PROBE WITH DELRIN(PLASTIC) SPLIT END TIP. 200KHZ SHIELDED, 00 LEMO CONNECTOR 76mm WORKING LENGTH 23.5mm@(0.925"), EXPANDABLE TO 25.0mm@. Includes Test Report and Certificate of Conformance.	PB200R235-250			
AMH-4.5ML00SE/76MWL	MANUAL BOLT HOLE PROBE WITH DELRIN(PLASTIC) SPLIT END TIP. 200KHZ SHIELDED, 00 LEMO CONNECTOR 76mm WORKING LENGTH 4.5mmØ, EXPANDABLE TO 5.5mmØ. Includes Test Report and Certificate of Conformance.	PB00R045-055			
AMH-6.0ML00SE/76MWL	MANUAL BOLT HOLE PROBE WITH DELRIN(PLASTIC) SPLIT END TIP. 200KHZ SHIELDED, 00 LEMO CONNECTOR 76mm WORKING LENGTH 6.0mmø, EXPANDABLE TO 7.0mmø. Includes Test Report and Certificate of Conformance.	PB200R060-070			
AMH-6.4M/2MHZ	Manual bolt hole probe, 0.250° inch (6.40mm) diameter and 2.0 inch (50.8mm) working length, frequency 1MHz -3MHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	504P16			
AMH-7.5ML00SE/76MWL	MANUAL BOLT HOLE SCANNER PROBE WITH DELRIN(PLASTIC) SPLIT END TIP. 200KHZ SHIELDED, 00 LEMO CONNECTOR 76mm WORKING LENGTH 7.5mm@(5/16"), EXPANDABLE TO 9.0mm@. Includes Test Report and Certificate of Conformance.	PB200R075-090			
AMH-9.5ML00/76MWL	STAINLESS STEEL MANUAL SCANNER PROBE WITH DELRIN(PLASTIC) SPLIT END TIP. 100KH2-2MH2 SHIELDED, 00 LEMO CONNECTOR 76mm WORKING LENGTH 9.5mmØ(3/8"), CXPANDABLE TO 11.0mmØ. Includes Test Report and Certificate of Conformance.	PB200R095-110			
AMHF187	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ MICRODOT CONNECTOR (3/16) .187" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	VM101BS-3-16			
AMHF250	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ MICRODOT CONNECTOR (1/4) . 250" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	VM101BS-1-4			
AMHF375	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ MICRODOT CONNECTOR .375" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	BPMF-24			
AMHF437	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ MICRODOT CONNECTOR .437" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	BPMF-28	•		
AMHF562	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ MICRODOT CONNECTOR (9/16) .562" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	VM101BS-1/2			
AMHF625	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ MICRODOT CONNECTOR (5/8). 625" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	VM101BS-5-8			
AMHF750	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ MICRODOT CONNECTOR.750" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	BPMF-48	•		
AMHF875	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ MICRODOT CONNECTOR .875" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	BPMF-56	VM101BS-7-8		
AMHF937	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ MICRODOT CONNECTOR(15/16) .9375" x 3.0" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	VM101BS-15-16			
AMHX187250	ADJUSTABLE X MANUAL BOLT-HOLE PROBE 3" OVERALL LENGTH, WITH MICRODOT CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.	BXM-12/16	MHX.187250		
AMHX250312	ADJUSTABLE "X" MANUAL BOLT-HOLE PROBE WITH COLLAR .250".312". 3.0" OVERALL LENGTH, ,MICRODOT CONNECTOR, 50-500KHZ. Includes Test Report and Certificate of Conformance	MHX250312			
AMHX312375	ADJUSTABLE "X" MANUAL BOLT-HOLE PROBE WITH COLLAR .312".375". 3.0" OVERALL LENGTH, ,MICRODOT CONNECTOR, 50-500KHZ. Includes Test Report and Certificate of Conformance	MHX.312375			
AMHX437500	ADJUSTABLE "X" MANUAL BOLT-HOLE PROBE WITH COLLAR .437".500". 3.0" OVERALL LENGTH, ,MICRODOT CONNECTOR, 50-500KHZ. Includes Test Report and Certificate of Conformance	MHX-437-500			
AMHX500625	ADJUSTABLE "X" MANUAL BOLT-HOLE PROBE WITH COLLAR .500".625". 3.0" OVERALL LENGTH, ,MICRODOT CONNECTOR, 50-500KHZ. Includes Test Report and Certificate of Conformance	MHX.500625			
AMHX625750	ADJUSTABLE "X" MANUAL BOLT-HOLE PROBE WITH COLLAR .625".750". 3.0" OVERALL LENGTH, ,MICRODOT CONNECTOR, 50-500KHZ. Includes Test Report and Certificate of Conformance	MHX625750			
AXXPN-4	STRAIGHT SURFACE PROBE, .062" TIP, 50-500KHZ, 4.0" LONG. MICRODOT CONNECTOR Includes Test Report and Certificate of Conformance.				
AXXPN-45-4	SURFACE PROBE, 45° DEGREES ANGLED, .062°Ø TIP, .500° DROP 50-500KHZ, MICRODOT CONNECTOR 4.0 INCHES LONG. Includes Test Report and Certificate of Conformance				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPN-455-5/2MHZ	RIGID SURFACE PROBE 45° DEGREES, .500" DROP, .125" Ø TUBING, 5.0" LONG TRIAX FISCHER CONNECTOR. FREQUENCY: 1-3MHz IncludesTest Report				
ATPN-455-5	and Certificate of Conformance. RIGID SURFACE PROBE 45° DEGREES, .500° DROP, .125° Ø TUBING, 5.0° LONG TRIAX FISCHER CONNECTOR. FREQUENCY: S0-500KHz IncludesTest Report and Certificate of Conformance.				
AURCS10037555	REDUT AID CETINATE OF COMONTANCE. STAINLESS STEEL ROTATING SCANNER PROBE 100° DEGREES COUNTERSINK 100KHz-2MHz , 4-PIN FISCHER CONNECTOR, 3/8"Ø. Includes Test Report and Certificate of Conformance	•			
AURCS100437SS	STAINLESS STELL ROTATING SCANNER PROBE 100° DEGREES COUNTERSINK 100KHz-2MHz , 4-PIN FISCHER CONNECTOR, 7/16°Ø. Includes Test Report and Certificate of Conformance				
AURCS100500SS	STAINLESS STEEL ROTATING SCANNER PROBE 100° DEGREES COUNTERSINK 100KHz-2MHz , 4-PIN FISCHER CONNECTOR, 1/2"Ø. Includes Test Report and Certificate of Conformance	•			
AF-6004S	SLIDING PROBE, REFLECTION, 100Hz-40kHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AUR-56.0MSE/4WL	Universal Rotary Bolt Hole Probe, self expanding from 56mm(2.20") to 60mm(2.36") diameter, 4.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.	•			
AUR-60.0MSE/4WL	Universal Rotary Bolt Hole Probe, self expanding from 56mm(2.36") to 64mm(2.52") diameter, 4.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AURCS100125SS	STAINLESS STEEL ROTATING SCANNER PROBE 100 DEGREES COUNTERSINK (1/8")Ø100KHZ-2MHZ. 4 PIN FISCHER CONNECTOR Includes Test Report and Certificate of Conformance				
AMHX-1.0-1.125	ADJUSTABLE "X" MANUAL BOLT-HOLE PROBE WITH COLLAR 1.0"-1.125": 3.0" OVERALL LENGTH, ,MICRODOT CONNECTOR, 50-S00KHZ. Includes Test Report and Certificate of Conformance	BXM 64/72			
AMHX-1.125-1.250	ADJUSTABLE "X" MANUAL BOLT-HOLE PROBE WITH COLLAR 1.125"1.250". 3.0" OVERALL LENGTH, ,MICRODOT CONNECTOR, 50-500KHZ. Includes Test Report and Certificate of Conformance	BXM 72/80			
AMHX-1.250-1.375	ADJUSTABLE "X" MANUAL BOLT-HOLE PROBE WITH COLLAR 1.250"-1.375". 3.0" OVERALL LENGTH, ,MICRODOT CONNECTOR, 50-500KHZ. Includes Test Report and Certificate of Conformance	BXM 80/88			
AMHX-10M-12M	ADJUSTABLE "X" MANUAL BOLT-HOLE PROBE WITH COLLAR .393"472(10mm-12mm). 3.0" OVERALL LENGTH, ,MICRODOT CONNECTOR, 50-500KHZ. Includes Test Report and Certificate of Conformance	BXM-10M-12M			
AP-352P1A/2MHZ	UNSHIELDED KNIFE PROBE 65" 1-3MHz, 5.0 INCES LONG MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	352P1A			
AP-4.5/200K	RIGID STRAIGHT SURFACE PROBE,ABS,SHIELDED, MICRODOT CONNECTOR 4.5" LONG 20-200KHZ.4.5"LONG, 20-200KHZ, Fe/NFe, L=114mm(4.5""), Tip 4.35mm(187"Ø) WITH MICRODOT CONNECTOR.187"Ø TUBING. Includes Test Report and Certificate of Conformance.	104P4			
AP-475-4.5/200K	RIGID SURFACE PROBE .187'Ø TIP, 4.5" LONG, 45° CRANK, .750" DROP 50-500KHz LOCATOR, MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance. GE P/N: 610-054-076	204P4	610-054-076		
AP-93-5B/2-12K/4F	SURFACE PROBE 90° DEGREES, 187"Ø TUBING .300° DROP 5.0° LONG BENT SHAFT, 4 PIN FISCHER CONNECTOR.2-12KHZ DIFFERENTIAL. Includes Test Report and Certificate of Conformance.	LP903-50B	LP903-50B/2-12K		
AP-94-6/4L/1-30KHZ	RIGID SURFACE PROBE, DIFFERENTIAL 90° 1-30KHZ , .187" Ø OD TIP, .400" DROP, 6.0" LONG, 4 PIN LEMO CONNECTOR. Includes Certification Report and Certificate of Conformance.	•			
AP-94-6/7L/1-30KHZ	RIGID SURFACE PROBE, DIFFERENTIAL 90° 1-30KHZ , .187" Ø OD TIP400" DROP, 6.0" LONG, 7 PIN LEMO CONNECTOR. Includes Certification Report and Certificate of Conformance.	LP904-60/1-30K/7L			
AP-95-4	SURFACE PROBE 100-500KHZ , .187" OD TIP, 90°, .500" DROP, 4.0" LONG, SHIELDED, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	VM102AF			
APN-35-6FX/2MHZ	FLEXIBLE SURFACE PROBE 1-3MHZ 6.0" LONG 30 DEGREE .500" DROP MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.				
APN-4.5/2M	RIGID SURFACE PROBE STRAIGHT ABS SHIELDED 4.5" LONG 1-3MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	106P4	106P4		
APN-45-3	RIGID SURFACE PROBE 50-500KHz 3.0" LONG 45" DEGREES, .500" DROP CURVED MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.	MP-455-3			
APN-45-4	RIGID SURFACE PROBE 45° DEGREES, .500° DROP 4.0° LONG, SHEILDED 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PEN45-4			
APN-45-4.5/.500KHZ	RIGID SURFACE PROBE 45" DEGREES .500" DROP 4.5" LONG .125" Ø DIA TUBING MICRODOT CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.	•			
APN-45-4.5/2MHZ	RIGID SURFACE PROBE 1-3MHZ, 45" DEGREES, .500" DROP 4.5" LONG WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	617-057-076	MP455-45/2M		
APN-45-5	RIGID SURFACE PROBE 45° DEGREES .500° DROP, .125"Ø, 5.0" LONG WITH MICRODOT CONNECTOR, 50-500KHZ, Includes Test Report and Certificate of Conformance.	MP455-50	PEN45-5 50-500K	DPT45-001	PA45505
APN-45-5.5	RIGID SURFACE PROBE 50-500KHz, 45" DEGREES, .500" DROP 5.5" LONG WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP455-45			
APN-45-5/2MHz	RIGID SURFACE PROBE 45° DEGREES .500° DROP, .125"Ø, 5.0" LONG WITH MICRODOT CONNECTOR, 1-3MHz. Includes Test Report and Certificate of Conformance.	PEN45-5 500K-2M			
APN-45-5/L 500K	RIGID SURFACE PROBE SHIELDED, 125"Ø TIP DIAMETER500" DROP, CRANKED 45" DEGREES, 5.0" LONG WITH MICRODOT CONNECTOR. (LOCATOR 500KHZ,47UH). Includes Test Report and Certificate of Conformance.				
APN-45-5B	RIGID SURFACE PROBE 45" DEGREES BENT .500" DROP, .125"Ø, 5.0" LONG WITH MICRODOT CONNECTOR, 50-500KHZ, Includes Test Report and Certificate of Conformance.	PEN45-5B			
APN-45-6/2MHZ	RIGID SURFACE PROBE 1-3MHZ 6.0" LONG 45".500" DROP MICRODOT CONNECTOR .125" TIP. Includes Test Report and Certificate of Conformance.	206P6			
APN-45-6C	SURFACE PENCIL PROBE 50-500KHZ SHIELDED. CURVED 45" DEGREES TIP, .500" DROP, MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP455-60C	MP455-60C		
APN-475-4.5/2MHZ	RIGID SURFACE PROBE .118 TIP, 4.5" LONG, 45" CRANK, .750" DROP 1-3MHZ LOCATOR, MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	206P4	206P4	PS002PC195-114N	
APN-5/2M	STRAIGHT RIGID SURFACE PROBE, 125" Ø, 5.0" LONG, 1-3 MHz, WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	2-835-01-2000	PEN900-5 500K-2M		
APN-5FX	STRAIGHT FLEXIBLE SURFACE PROBE 5.0" LONG WITH MICRODOT CONNECTOR 50-500KHZ. Includes Test Report and Certificate of Conformance.	MP-50FX			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
APN-7FX/500K	FLEXIBLE SURFACE PROBE 90° DEGREES , .500" DROP, MICRODOT CONNECTOR 500KHZ-1MHZ 7.0" LONG 4.5" SHAFT LENGTH .125"OD TIP. Includes	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
	Test Report and Certificate of Conformance. STRAIGHT COPPER SHAFT FLEXIBLE SURFACE PROBE, ABS, 350KHz-3MHz .125*Ø (3.3mm) TIP, 8.0"(203.2mm) LONG WITH MICRODOT CONNECTOR.		•	•	
APN-8FX/350KHZ-3MHZ	Includes Test Report and Certificate of Conformance. STRAIGHT RIGID SURFACE PROBE .030" DROP, .125"Ø, 50-500KHz, 5.0" LONG WITH MICRODOT CONNECTOR 50-500KHz. Includes Test Report and	106P8C	615-037-004	•	
APN-903-5	Certificate of Conformance. RIGID SURFACE PROBE125'Ø TIP 90°, .030"(1mm) DROP ABS. SHIELDED, 6.0" (150mm)LONG WITH MICRODOT CONNECTOR. FREQUENCY: 50-500KHz.	PEN903-5			
APN-903-6	Includes Test Report and Certificate of Conformance.	MP9003-6	•	•	
APN-903-7	RIGID SURFACE PROBE, 125"Ø TIP 90°, 0.30"(1mm) DROP, 7.0" (178mm) OVERALL LENGTH WITH MICRODOT CONNECTOR. FREQUENCY: 50-500KHz. Includes Test Report and Certificate of Conformance.	MP9003-70	•		
APN-903-7/2M	RIGID SURFACE PROBE125"Ø TIP 90", .030"(1mm) DROP, 7.0" (178mm) LONG WITH MICRODOT CONNECTOR. FREQUENCY: 1-3MHz. Includes Test Report and Certificate of Conformance.	•			
APN-903-7FX	FLEXIBLE SURFACE PROBE 50-500KHZ .030" DROP 7.0" LONG MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PENFLX903-7			
APN-910-8/2MHZ	RIGID SURFACE PROBE125" [# TIP 1.0" INCH DROP 8.0" LONG WITH MICRODOT CONNNECTOR. 1-3MHZ Includes Test Report and Certificate of Conformance		•		
APN-91-10	RIGID SURFACE PROBE, 90" DEGREES .100" DROP, 125" (# TIP, 10.0 INCHES LONG WITH MICRODOT CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.	PEN 91-10	•		_
APN-91-4	HOCKING RIGID SURFACE PROBE, 90° Degrees, Absolute Shielded, 50-500KHz, .125°Ø TIP, .100° Drop, 4.0° Long with Microdot Connector. Includes Test Report and Certificate of Conformance.	PEN91-4			
APN-91-4.5	HOCKING RIGID SURFACE PROBE, 90° Degrees, Absolute Shielded, 50-500KHz, .125°Ø TIP, .100° Drop, 4.5° Long with Microdot Connector. Includes Test Report and Certificate of Conformance.	309P14			
APN-91-4.5/2MHZ	RIGID SURFACE PROBE, 90° Degrees, Absolute Shielded, 1-3MHz, .100° Drop, 4.5° Long with Microdot Connector. Includes Test Report and Certificate of Conformance.	310P14	310P14	PS002PR027-114N	
APN-91-4.5B/2MHZ	RIGID SURFACE PROBE BENT 1-3MH2 90 DEGREES .100" DROP. 4.5 INCHES LONG WITH MICRODOT CONNECTOR .125" TIP. 15 DEG CRANK 1" FROM THE TIP. FREQUENCY RANGE1-3MHZ. Includes Test Report and Certificate of Conformance.	MP901-50B			_
APN-91-5.5/2MHZ	RIGID SURFACE PROBE ABSOLUTE, 1MHz-3MHz, 90° .072" OD TUBING .100" DROP, 5.5" LONG, MICRODOT CONNECTOR. lincludes Test Report and Certificate of Conformance.	813P014			
APN-91-5FX	FLEXIBLE SURFACE PROBE 50-500KHZ 90° DEGREES .100° DROP 5.0 INCHES LONG WITH MICRODOT CONNECTOR .125° TIP. Includes Test Report and Certificate of Conformance.	MP901-50FX	MP901-50FX		
APN-91-6B	RIGID SURFACE PROBE BENT 15" DEGREES 1.0" FROM THE TIP, 125"Ø, 50-500KHz , 90" DEGREES .100" DROP, 6.0" INCHES LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP901-60B			
APN-91-6FX	FLEXIBLE SHAFT SURFACE PROBE 90" DEGREES, 125"Ø, 100" DROP, 50-500KHz, 6.0" INCHES LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP901-80FX-6			
APN-91-7.5FX	FLEXIBLE SHAFT SURFACE PROBE 90" DEGREES, .125"Ø, .100" DROP, 50-500KHz, 7.5" INCHES LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP901-80FX-7.5			
APN-91-9FX	FLEXIBLE SHAFT SURFACE PROBE 90° DEGREES, .125" Ø, .100° DROP, 50-500KHz, 9.0° INCHES LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP901-80FX-9		•	
APN-92-4B	RIGID SURFACE PENCIL PROBE. Right Angle Shaft, 0.200" in. (5.08 mm) drop. 50KHz-500KHz, 4.0" LONG. Includes Test Report and Certificate of Conformance.	MP902-40			
APN-925-3	STAINLESS STEEL SURFACE PROBE 50-500KHZ 90*, .125" TIP, .250" DROP 3.0" LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PEN925-3			
APN-925-3.5/2MHZ	Rigid Surface Probe Absolute Shielded, , 90°, 1MHz-3MHz, .250° Drop, 3.5° long With Microdot Connector. Includes Test Report and Certificate of Conformance.				
APN-925-3/350K-3MHZ	SURFACE PROBE Shielded Surface, 90 Degrees Tip, 2 MHz NFe, L=114mm(4.5"), Tip Dia 3.3, Plastic TL=6.4mm, Abs. Includes Test Report and Certificate of Conformance.	306P23.			
APN-925-4	RIGID SURFACE PROBE 90° DEGREES .250° DROP 4.0° LONG WITH A MICRODOT CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.	PEN925-4	•		
APN-925-4.5B/2M	Rigid Surface Probe Absolute Shielded, 4.5" long, 90°, 350KHz-3MHz, .250" Drop, 15" Degree Crank. 6" Long With Microdot Connector. Includes Test Report and Certificate of Conformance	314P24			
APN-925-4.5B/L500K	SURFACE PROBE 90° DEGREES, .250" DROP 15" DEGREE CRANK ( BENT) LOCATOR 500KHZ 4.5" LONG. Includes Test Report and Certificate of Conformance.	313P24			
APN-925-4FX/2MHZ	FLEXIBLE SURFACE PROBE 90° DEGREES .250" DROP,1-3MHz, .125"Ø TIP 4.0" LONG WITH MICRODOT CONNECTOR . Includes Test Report and Certificate of Conformance.				
APN-925-6	STAINLESS STEEL SURFACE PROBE 50-500KHZ 90°, .125" TIP, .250" DROP 6.0" LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PEN925-6	PEN925-6	MP902-6	
APN-925-6B	RIGID SURFACE PROBE ABSOLUTE SHIELDED 50-500Hz, 90°, .250° DROP BENT 30° 2.0° FROM THE TIP,6.0 ° LONG WITH MICRODOT CONNECTOR. Includes Test Report ancd Certificate of Conformance.	VM229F-1/4x6			
APN-925-6FX/2MHZ	FLEXIBLE SURFACE PROBE 90° DEGREES .250" DROP,1-3MHz, .125" Ø TIP 6.0" LONG WITH MICRODOT CONNECTOR . Includes Test Report and Certificate of Conformance.				
APN-92-5B	STAINLESS STELL SURFACE PROBE 50-500KHZ 90° BENT, .125°Ø TIP, .200° DROP 5.0° LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP902-50B			
APN-92-6B	RIGID SURFACE PENCIL PROBE. Right Angle Shaft, 0.200" in. (5.08 mm) drop. 50KHz-500KHz. Includes Test Report and Certificate of Conformance.	MP902-60			
APN-93-5/2M	Surface Probe Absolute Shielded, 5.0" long, 90° degrees, 350KHz-3MHz, .300" drop with microdot connector. Includes Test Report and Certificate of Conformance	310P24			
APN-95-10	RIGID SURFACE PROBE, 90° DEGREES .500° DROP, 125°Ø TIP, 10.0 INCHES LONG WITH MICRODOT CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.	PEN 95-10	MP905-100		
APN-95-3	STAINLESS STEEL SURFACE PROBE 50-500KHZ 90°, .125" TIP, .500" DROP 3.0" LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PEN95-3	MP-905-30		
APN-95-4.5/2MHZ	SURFACE PROBE ABS SHIELDED 90° DEGREES .500° DROP 4.5° LONG 1-3MHz WITH MICRODOT CONNECTOR. (610-077-014). Includes Test Report and Certificate of Conformance.	310P34	610-077-014		

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
APN-95-45FX	FLEXIBLE SURFACE PROBE, 50-500KHz, BENT 90° DEGREES .500" DROP, 4.5" LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate	MP905-45FX			
APN-95-4FX	of Conformance. FEXIBLE SURFACE PROBE. 90".500" DROP. MICRODOT CONNECTOR 50-500KHZ. 4.0" LONG. Includes Test Report and Certificate of Conformance.	WI 505-451X	•	•	
APN-95-4FX/2MHZ	FLEXIBLE SURFACE PROBE 90° DEGREES .500° DROP,1-3MHz, .125°Ø TIP 4.0° LONG WITH MICRODOT CONNECTOR . Includes Test Report and Certificate				
APN-95-5	of Conformance. RIGID SURFACE PROBE, 90° DEGREES, .500" DROP, .125"Ø TIP, 5.0" LONG MICRODOT CONNECTOR 50-500KHz IncludesTest Report and Certificate of	MP905-50	РЕN95-5 50-500К	DPT90-001	
APN-95-5/2MHZ	Conformance. RIGID SURFACE PROBE, 90" DEGREES, .500" DROP, .125"Ø, 5.0" LONG WITH MICRODOT CONNECTOR 1-3MHz. IncludesTest Report and Certificate of	PEN95-5/2M	121055 550 500		
AF-5175	Conformance. ABSOLUTE SURFACE PROBE, SHIELDED, 3.0" INCHES LONG WITH MICRODOT CONNECTOR. 125" TIP. FREQUENCY RANGE 20-200KHZ. Includes Test	379-010-550			
AF-5175 AWPM-3-1571	Report and Certificate of Conformance. WHEEL PROBE FOR GOODRICH MAIN WHEEL 3-1571 FOR CESSNA 560XL. DIIFFERENTIAL/ BRIDGE, 50-500KHz, WITH TRIAX FISCHER CONNECTOR.	379-010-550		•	
AWPM-3-15/1 AF-5176	Includes Test Report and Certificate of Conformance. LOW FREQUENCY SURFACE PROBE 1-SKHz, REFLECTION, .500 DROP,312"Ø(8mm) TUBING, 8.27" (210mm)LONG, MICRODOT BENT 65mm FROM THE	•	•	•	
AF-5176	HANDLE Includes Test Report and Certificate of Conformance	•	•		
APN-95-5FX	FLEXIBLE SURFACE PROBE 50-500kHZ 90° DEGREES .500° DROP 5.0° LONG WITH MICRODOT CONNECTOR, 125" Ø TIP. Includes Test Report and Certificate of Conformance.				
APN-95-5FX/2MHZ	FLEXIBLE SURFACE PROBE 1-3MHZ 90° DEGREES .500° DROP 5.0° LONG WITH MICRODOT CONNECTOR,125° Ø TIP. Includes Test Report and Certificate of Conformance.				
ATPN-45-6/.083	RIGID SURFACE PROBE, 45", .083Ø TUBING, .500" DROP 6.0" LONG TRIAX FISCHER CONNECTOR, 200KHz-2MHz. Includes Test Report and Certificate of Conformance.	PAB4560-1.0/.083	VM2085/45-6		
AURFB-4.4MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 4.4MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURY-4.0-4.8M/45MWL	ADJUSTABLE "Y" ROTATING SCANNER PROBE 4.0mm-4.8mm SPREAD, 45mm WORKING LENGTH.100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMANN MR3. Includes Test Report and Certificate of Conformance				
AUR765SS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-20HZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .765" (49/64") 2.56"(65mm) WORKING LENGTH Includes Test Report and Certificate of Conformance	615P049F065			
AF-6026-2&7	SLIDING PROBE WITH 2:00 NOTCH TANGENT COIL ARRANGEMENT TO DETECT 45° TANGENTIAL CRACKS, REFLECTION, 1KHz-100KHz, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformation.				
AF-6027-3&9	SLIDING PROBE WITH 3:00 NOTCH TANGENT COIL ARRANGEMENT TO DETECT 45° TANGENTIAL CRACKS, REFLECTION, 1KHz-100KHz, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformation.	•			
AF-6025-10&4	SLIDING PROBE WITH 10:00 NOTCH TANGENT COLL ARRANGEMENT TO DETECT 45" TANGENTIAL CRACKS, REFLECTION, 1KHz-100KHz, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformation.				
APN-95-6	STAINLESS STEEL SURFACE PROBE 50-500KHZ 90°, .125" TIP, .500" DROP 6.0" LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PEN-95-6	PEN95-6, DPT90-005	VM202AF-6	MP905-60
ATPN-45-6/1-6M	RIGID SURFACE PROBE 45" DEGREES, 6.0" LONG, 1/8" Ø TUBING TRIAX FISCHER CONNECTOR, 1-6MHz. Includes Test Report and Certificate of Conformance.	BCMTF-455-60-1-6M	MTF-455-60-1-6M		
APN-95-6B/2MHZ	RIGID SURFACE PROBE ABSOLUTE SHIELDED 1-3MHZ, 90° BENT 30° 6.0 " LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	310P36	310P36	2-835-01-2100	
APN-95-6C/1M	Eddy Current Surface Probe 90° degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long, 500kHz-2MHZ with Microdot Connector. Includes Test Report and Certificate of Conformance.				
ARR125SS/1.5WL	STAINLESS STEEL ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz WITH A 4 PIN STEP LEMO CONNECTOR, 1/8"(.125")Ø, 1.5" WORKING LENGTH Includes Test Report and Certificate of Conformance				
ARR156SS/1.5WL	STAINLESS STEEL ROTARY PROBE FOR RA2000 SCANNER 100KH2-2MH2 WITH A 4 PIN STEP LEMO CONNECTOR, 5/32"(.156")Ø, 1.5" WORKING LENGTH Includes Test Report and Certificate of Conformance				*
ARR187SS/1.5WL	STAINLESS STEEL ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz WITH A 4 PIN STEP LEMO CONNECTOR, 3/16"(.187")Ø, 1.5" WORKING LENGTH Includes Test Report and Critificate of Conformance				•
ARR250SS/1.5WL	STAINLESS STEEL ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz WITH A 4 PIN STEP LEMO CONNECTOR, 1/4"(.250")Ø, 1.5" WORKING LENGTH Includes Test Report and Certificate of Conformance				
ARR281SS/1.5WL	TAILUISES TEST REPORT AND CEMINARE OF COMMINANCE STAINLESS STEL ROTARY PROBE FOR RA2000 SCANNER 100KH2-2MH2 WITH A 4 PIN STEP LEMO CONNECTOR, 9/32"(.281")Ø, 1.5" WORKING LENGTH Includies TEST REPORT AND CEMINERATE OF CONFORMANCE				-
AUR562SS/35MWL	STAINESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .562"(14.27mm) 35mm WORKING IFWGTH Includer: Set Renort and Certificate of Conformance	615P036F035			
AUR750SS/35MWL	TAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .750"(19.05mm)Ø, 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P048F035			
APN-95-6FX	FLEXIBLE SURFACE PROBE, 90°.500 DROP, 6" LONG 50-500KHZ, MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
APN-95-6FX/2MHZ	FLEXIBLE SURFACE PROBE 90° DEGREES .500" DROP,1-3MHz, .125" Ø TIP 6.0" LONG WITH MICRODOT CONNECTOR . Includes Test Report and Certificate of Conformance				
APN-975-4.5B/2MHZ	SURFACE PROBE 90° DEGREES.750° DROP 15° DEGREES CRANK AT 1/2° TIP, 4.5 ° LONG WITH MOCRODOT CONNECTOR. FREQUENCY 1-3MHZ. Includes Test Report and Certificate of Conformance.	314P44			
APNU-95-5/2M	SURFACE PROBE 90", .500" DROP UNSHIELDED, MICRODOT CONNECTOR, 1-3MHZ. 5.0" LONG. Includes Test Report and Certificate of Conformance.	DPT90U-001			-
APN-45-4FX	FLEXIBLE SURFACE PROBE 45" DEGREES, .500" DROP 4.0" LONG, SHEILDED 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance				
APNU-4	RIGID SURFACE PROBE STRAIGHT UNSHIELDED 50-500KHZ MICRODOT CONNECTOR 4.0" LONG. Includes Test Report and Certificate of Conformance.				
APN-925-2	RIGID SURFACE PROBE; 90° DEGREES, .250° DROP, .125°Ø TIP 2.0° LONG MICRODOT CONNECTOR, 50-500KHz. Includes Test Report and Certificate of	PFN925-2			
	Conformance. RIGID SURFACE PROBE 90°, SHIELDED, 200° DROP, 5.0 ° LONG 6MHz WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of	311P24		·	
APN-92-5/6MHZ	Conformance.	511P24			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
APN-925/93-4.5/6MHZ	DESCRIPTION SURFACE PROBE 45" DEGREES, .250" DROP .093"Ø TUBING, 4.5" LONG SHIELDED 6MHz WITH A MICRODOT CONNECTOR. Includes Test Report and	315P24	EQUIVALENT	EQUIVALENT	EQUIVALENT
APN-925/93-4.5/6MHZ	Certificate of Conformance. RIGID STRAIGHT SURFACE PROBE, 500KHZ-2MHz, .125°Ø, 5.0° LONG WITH A MICRODOT CONNECTOR includes Test Report and Certificate of	315P24		•	
APN-5/1MHZ	Conformance				
APN-95-5/1MHZ	RIGID SURFACE PROBE, 90° DEGREES, .500° DROP, .125°Ø, 5.0° LONG WITH MICRODOT CONNECTOR 500KHz-2MHz. IncludesTest Report and Certificate of Conformance.				
APN-5/500K	RIGID STRAIGHT SURFACE PROBE, 200KHz-1MHz WITH A CENTER FREQUENCY OF 500KHz, 31 um Coil. 125"Ø, 5.0" LONG WITH A MICRODOT CONNECTOR Includes Test Report and Certificate of Conformance				
APN-903-8FX	FLEXIBLE SURFACE PROBE 50-500KHZ .030" DROP 8.0" LONG MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PENFLX903-8			
APN-92-10FX/1-3M	FLEXIBLE SURFACE PROBE, 90° .200" DROP SUPPLIED WITH A MICRODOT CONNECTOR 50-500KHZ, 10.0" LONG. Includes Test Report and Certificate of Conformance.	MP902-100FX/1-3M			
APN-92-6/1M	RIGID SURFACE PENCIL PROBE. Right Angle Shaft, 0.20 in. (5.08 mm) drop. 200KHz-1MHz. Includes Test Report and Certificate of Conformance	MP902-60-200K-1M	MP902-60-200K-1M		
APN-94-6B	RIGID SURFACE PROBE ABSOLUTE SHIELDED, 90° DEGREES, 400° DROP, 6.0° LONG, BENT, WITH A MICRODOT CONNECTOR, 30KHz-300KHz. Includes Test Report and Certificate of Conformance.	PKA33H121-02-1			
APN-95-5B/2M	SURFACE PROBE 2MHz, BENT 90°, .500° DROP, .125°Ø TIP 5.0 ° LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PEN-95-5B/2M	PEN-95-5B/2M		
APN-95-8/2MHZ	RIGID SURFACE PROBE 90" DEGREES, .125"Ø TUBING, .500" DROP, 8.0" LONG WITH MICRODOT CONNECTOR. 1-3MHz Includes Test Report and Certificate of Conformance.	310P38			
APN-925-12FX	FLEXIBLE SURFACE PROBE 90° DEGREES, .250" DROP 12.0" INCH LONG WITH MICRODOT CONNECTOR 50-500KHZ. Includes Test Report and Certificate of Conformance.				
APN-45-14FX	FLEXIBLE SURFACE PROBE 45° DEGREES, 14.0" LONG, MICRODOT CONNECTOR, 50-500KHz IncludesTest Report and Certificate of Conformance				
APNU-5/200KHZ	ABSOLUTE UNSHIELDED STRAIGHT PENCIL PROBE .093"Ø TUBING. 5" LONG MICRODOT CONNECTOR 50-500KHz. Includes Test Report	379-010-550			
APN-9FX/500K	STRAIGHT FLEXIBLE SURFACE PROBE 9" LONG, MICRODOT CONNECTOR 500KHz. Includes Test Report and Certificate of Conformance.				
APN-95-10FX/7L	FLEXIBLE SURFACE PROBE, 90° DEGREES, .500" DROP, .125" TIP, 10.0" LONG 7 PIN LEMO CONNECTOR 50-500KHz IncludesTest Report and Certificate of Conformance.				
APN-95-10FX/7L/1-6MHZ	FLEXIBLE SURFACE PROBE, 90° DEGREES, .500" DROP, .125" TIP, 10.0" LONG 7 PIN LEMO CONNECTOR 1-6 MHZ IncludesTest Report and Certificate of Conformance.				
ATPN-45-6FX	FLEXIBLE SURFACE PROBE 45° DEGREES, 6.0" LONG, TRIAX FISCHER CONNECTOR, 50-500KHz IncludesTest Report and Certificate of Conformance	BCMTF455-60FX	MTF455-60FX		
APN-4/7L/100-500KHZ	RIGID STRAIGHT SURFACE PROBE BRIDGE / ABSOLUTE SHIELDED, 100-500KHz, 1/8"Ø, 4.0" LONG SUPPLIED WITH A 7 PIN LEMO POWERLINK CONNECTOR. Includes Test Report and Certificate of Conformance.	9222202			
APN-4/7L/50-100KHZ	90° DEGREE SURFACE PROBE BRIDGE / ABSOLUTE SHIELDED, SOKH2-100KHz, .500° DROP, .125°OD TIP. SUPPLIED WITH A 7 PIN LEMO POWERLINK CONNECTOR, 4.0° LONG. Includes Test Report and Certificate of Conformance.	9222165			
APN-9/7L/500KHZ-1MHZ	RIGID STRAIGHT SURFACE PROBE BRIDGE / ABSOLUTE SHIELDED, 500KHz-1MHz, 125"OD TIP. SUPPLIED WITH A 7 PIN LEMO POWERLINK CONNECTOR, 6.0" LONG. Includes Test Report and Certificate of Conformance.	9222208			
AUR-7.8MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 7.8mmØ(.307") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-7.8-35			
APN-92-4FX/7L	FLEXIBLE COPPER SHAFT PENCIL SURFACE PROBE. 50-500KHz 90° DEGREES .200" DROP 4.0 " LONG. 7 Pin LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	PAB90402FX	MTF902-45FX		
APN-95-6/7L/500K-1M	90° DEGREE SURFACE PROBE BRIDGE / ABSOLUTE SHIELDED, 500KHz-11MHz, 500° DROP, .125°OD TIP. SUPPLIED WITH A 7 PIN LEMO POWERLINK CONNECTOR, 6.0° LONG. Includes Test Report and Certificate of Conformance. NSN: 6635-01-521-1508	9222208			
ATPN-45-8FX	FLEXIBLE SURFACE PROBE 45° DEGREES, 8.0" LONG, TRIAX FISCHER CONNECTOR, 50-500KHz IncludesTest Report and Certificate of Conformance	TPENFLX45-8 50-500KHZ			
ATPN-5	STRAIGHT SURFACE PROBE - 50-500KHZ, .125"Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	MTF-50	DPT-002		
ATPN-5/1-6M	RIGID STRAIGHT SURFACE PROBE, 5.0" LONG, 1/8"Ø TRIAX FISCHER CONNECTOR, 1-6MHz. Includes Test Report and Certificate of Conformance.	BCMTF-50-1-6M	MTF-50-1-6M		
APN95-6C/L00	SURFACE PROBE 90° DEGREES, ABSOLUTE BRIDGE COIL CONFIGURATION, .500 " DROP CURVE 6.0" LONG WITH A 7 PIN LEMO CONNECTOR. FREQUENCY: 100KHz-500KHz. Includes Test Report and Certificate of Conformance. 9222164, U8616093	.ML/100KHZ- 500KHZ/A/90.5/6			
APN-95-8/7L	RIGID SURFACE PROBE ABS 90" DEGREES, S00" DROP, .125"Ø O.D. TIP, 8.0" LONG. 50-S00KHz 7 PIN LEMO CONNECTOR . Includes Test Report and Certificate of Conformance.				
APN-93-6/7L	SURFACE PROBE SHIELDED 1/8" DIA TUBE 90 DEGREE, .300" DROP, 6.0" LONG 7 PIN LEMO CONNECTOR 50-500KHZ Includes Test Report and Certificate of Conformance				
APN-455-4FX/7L	ABSOLUTE BRIDGE FLEXIBLE PROBE. 4.0" LONG. 45 DEG. TIP. 0.5 IN. (12.7MM) DROP. 50KHZ-500KHZ. 0.125IN. (3.17MM) SHAFT. 7-Pin-LEMO POWERLINK CONNECTOR. Includes Test Report and Certificate of Conformance.	9230535			
APN-45-6/7L	ABSOLUTE BRIDGE SURFACE PROBE, ANGLE SHAFT, 45" DEGREES TIP. 0.5" (NCH. (12.7MM) DROP, 100KHz-500KHz, 0.125"Ø (3.17MM) SHAFT WITH A 7 PIN LEMO POWERLINK CONNECTOR, 6.0" LONG. Includes Test Report and Certificate of Conformance.	9222355			
APN-95-10/7L	ABSOLUTE BRIDGE RIGHT ANGLE. 10.0" LONG. 100KHZ-500KHZ. 0.125IN. (3.17MM) SHAFT SIZE. 7-Pin-LEMO POWERLINK CONNECTOR. Includes Test Report and Certificate of Conformance	9231730			
APR-4/1-50KHZ	LOW FRQUENCY REFLECTION SURFACE PROBE.250°Ø DIA TUBING 1-50KHz, 4.0° LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate Report.	SPO-2816	TEK-2058		
ARP255/.650	DIFFERENTIAL/BRIDGE LOW FREQUENCY RING PROBE, 500HZ-10KHZ, .255"Ø ID, .650"Ø OD WITH TRIAX CONNECTOR. Includes Test Report and Certificate of Conformance.	LR106-1-TF	U8620455		
ARP30/.80	LOW FREQUENCY REFLECTION RING PROBE .30" I.D80" O.D. TRIAX FISCHER CONNECTOR 100Hz-10KHz Includes Test Report and Certificate of Conformance.	SPO-2031			
ARP30/.80/7L	LOW FREQUENCY REFLECTION RING PROBE :30" I.D. :80" O.D. 7-Pin LEMO CONNECTOR 100Hz-10KHz Includes Test Report and Certificate of Conformance.	9222237			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
	DESCRIPTION BRIDGE RING PROBE .300"(0.76 cm) ID .850" (2.16cm) OD 300Hz-5KHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	RDP.3-5K	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARP30/.85 ARP300/.750	Conformance. DIFFERENTIAL/BRIDGE LOW FREQUENCY RING PROBE, 500HZ-10KHZ, .300"Ø ID, .750"Ø OD WITH TRIAX CONNECTOR. Includes Test Report and	КDP.3-5К LT107-1-TF	U8636077	•	
ARP315/.866/4L	Certificate of Conformance. LOW FREQUENCY RING PROBE, REFLECTION, 250HZ-40KHZ, 0.315"Ø(8mm) ID, 0.866"Ø(22mm) OD, 1.250"H. 4 WAY LEMO CONNECTOR. Includes Test	702P08A	08030077	•	
ARP315/.866/TF	Report and Certificate of Conformance. LOW FREQUENCY RING PROBE, REFLECTION, 250HZ-40KHZ, 0.315"Ø(8mm) ID, 0.866"Ø(22mm) OD, 1.25"H. TRIAX FISCHER CONNECTOR. Includes Test	702P08A	RNG-006	•	•
	Report and Certificate of Conformance. LOW FREQUENCY REFLECTION RING PROBE REFLECTION .350"Ø ID .600"Ø OD TRIAX FISCHER CONNECTOR 1-5KHZ. Includes Test Report and Certificate	702P08A	RNG-006	•	•
ARP3560/1-5K	of Conformance.	TEK-4066			
ARP35/.850-300HZ	LOW FREQUENCY REFLECTION RING PROBE, 35' ID MAX OD .84' 300HZ-2KHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				•
ARP37/.84-2KHZ	LOW FREQUENCY REFLECTION RING PROBE, 37' ID MAX OD .84' 500HZ-5KHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RDP.8437/2K	RDP.8437/2K		
ARP40/.80	LOW FREQUENCY REFLECTION RING PROBE .40" I.D80" O.D. TRIAX FISCHER CONNECTOR 100Hz-10KHz Includes Test Report and Certificate of Conformance.	SPO-2131			
ARP42/.80	LOW FREQUENCY REFLECTION RING PROBE .42" I.D80" O.D. TRIAX FISCHER CONNECTOR 200Hz-1KHz Includes Test Report and Certificate of Conformance.	SPO-2352			
ARP45800-500HZ	RING PROBE, REFLECTION, 500HZ-10KHZ.450°Ø ID .800°Ø OD WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-RDP .8-1K			
ARP46-1.0	LOW FREQUENCY REFLECTION RING PROBE .46" I.D. 1.0" O.D. TRIAX FISCHER CONNECTOR 100HZ-10KHZ Includes Test Report and Certificate of Conformance.	9232174			
ARP5/.8/100HZ-2K	BRIDGE ABSOLUTE SHIELDED RING PROBE .500" ID .800" OD LEMO TRIAX CONNECTOR 100Hz-2KHz. Includes test report and Certificate of Conformance.	RSPO-4-S			
ARP5/1.0-200HZ	REFLECTION RING PROBE .500" ID 1.0" OD TRIAX FISCHER CONNECTOR 200Hz-3KHz. 737 PT 6 57-10-60. Includes test report and Certificate of Conformance.	RDP1.05-200H			
ARP5/1.1-300HZ	LF RING PROBE, REFLECTION, 300HZ-3KHZ .500" ID 1.10" OD TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	RR0110-1/TF			
ARP5390	CUSTOM RING PROBE REFLECTION TRIAX FISHER CONNECTOR,900°Ø OD x .530°Ø ID .900° TALL, SOHz-SKHz. Includes Test Report and Certificate of Conformance. 737 PART 6 57-10-62, pg.2	TEK-4057	SPC-258R		
ARP54/.88	LOW FREQUENCY REFLECTION RING PROBE .54" I.D., .88" O.D. TRIAX FISCHER CONNECTOR 100Hz-10KHz. 9216710. Includes Test Report and Certificate of Conformance.	SPO-2434	9216705		
ARP54-1.0	LOW FREQUENCY REFLECTION RING PROBE.54" I.D. 1.0" O.D. TRIAX FISCHER CONNECTOR 100HZ-10KHZ. Includes Test Report and Certificate of Conformance.	9222488			
ARP55/1.0/200HZ	LOW FREQUENCY REFLECTION RING PROBE, 200Hz-5KHz .550" I.D. 1.0" O.D. 1.200"H TRIAX FISCHER CONNECTOR. Includes test report and Certificate of Conformance.	RR011-5/TF	LFRR-0.55/1.0		
ARP6-200H-1	LOW FREQUENCY REFLECTION RING PROBE .255" Di X .600" DI 100Hz-5KHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RR026-1	RDP.6-200-1-TF		
ARP65-500H	LOW FREQUENCY REFLECTION RING PROBE .350" DIX.650" DIXHz-10KHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RDP.65-500H			
ARP7-2K-1	LOW FREQUENCY REFLECTION RING PROBE .355" DI X .600" D 500Hz-20KHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RR207-1	RDP.7-2K-1		
ARP7540/100H	REFLECTION RING PROBE.750°Ø OD.400°Ø ID, 980° HIGH, TRIAX FISCHER CONNECTOR, 100Hz-10KHz Includes test report and Certificate of Conformance. RR0407-100H-10K-TF	RR0407-100H-10K-TF	D0815E1015-2083		
ARP75-1.25/300Hz	REFLECTION RING PROBE, 1.25"OD. 75" ID(19.6mm) TRIAX. FISHER CONNECTOR 300HZ-1KHZ. REFERENCE STANDARD NDT3176-X 737 PT 6 57-10-59, 737 PART 6 57-10-53 NDT3168. Includes Test Report and Certificate of Conformance.	RDP1.2575/300H			
ARP75-500H-5	LOW FREQUENCY REFLECTION RING PROBE, 550Hz-2KHz, .750"Ø OD .405"Ø ID, TRIAX FISCHER CONNECTOR, 100Hz-10KHz. Includes test report and Certificate of Conformance.	RDP75-500H-5			
ARP8030/100HZ-10KHZ	RING PROBE, REFLECTION, 100HZ-10KHZ .300"Ø ID .800"Ø OD WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-2031	RNG-005		
ARP8040-500HZ	LOW FREQUENCY REFLECTION RING PROBE, 500HZ-10KHZ.400" Ø ID .800" Ø OD WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RDP.8/.4-500H			
ARP80/.40/200H	LOW FREQUENCY RING PROBE REFLECTION .400" ID .800"OD TRIAX FISCHER CONNECTOR 100HZ-10KHZ . REFERENCE: 737 PART 6 57-10-60, pg.2. USED WITH (NDT3156, 57, 59, 61, 62, 63, 64). Includes test report and Certificate of Conformance.	RDP.84-200H	SPO-2131	SPO-2131	RDP.84-200H
ARP84435/400HZ-5KHZ	LOW FREQUENCY RING PROBE, REFLECTION, 400HZ-SKHZ, 0.435" ID, 0.840"Ø OD, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RNG-007			
ARP85/1.40-200Hz	LOW FREQUENCY REFLECTION RING PROBE.85" I.D. 1.40" O.D. TRIAX CONNECTOR 100Hz-500Hz. REFERENCE STANDARD NDT3176-X 737 PT 6 57-10-59. Includes ter report and Certificate of Conformance.	RDP1.4085-200H			
ARP85-100H-1	LOW FREQUENCY RING PROBE, REFLECTION 100Hz-5KHz850" O.D.x.375"I.D. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RDP.85-100H-1			
ARP87/1.40	LOW FREQUENCY REFLECTION RING PROBE .85" I.D. 1.40" O.D. TRIAX FISCHER CONNECTOR 100Hz-10KHz. 9216710. Includes Test Report and Certificate of Conformance.	SPO-2435	9216710		
ARP9025/500HZ	LOW FREQUENCY REFLECTION RING PROBE 500Hz- 5KHz, .250"Ø ID x .900"Ø DIA OD, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Confermance.				
ARP9-100H-5	LOW FREQUENCY RING PROBE, REFLECTION, 80 Hz-4KHz WITH TRIAX FISCHER CONNECTOR. 737 PART 6 57-10-59, pg.2. 737 PART 6 57-10-58, pg.2. 737 PART 6 57-10-54, pg.2. Includes Test Report and Certificate of Conformance.	RR019-5/TF	RR019-5/TF	RDP.9-100H-5	
ARP-0510-6/TF	LOW FREQUENCY REFLECTION RING PROBE .525" Ø ID 1.025" Ø OD, TRIAX FISCHER CONNECTOR 200Hz-10KHz. Includes Test Report and Certificate of Conformance.	RR0510-6/TF			
ARP-1.04/2K	REFLECTION RING PROBE, 2KHz, .400" ID 1.0" OD TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RDP1.04/2K			
ARP-1.040/100H	REFLECTION RING PROBE 1.00"Ø OD .400"Ø OD, 1.20" HIGH, TRIAX FISCHER CONNECTOR, 100Hz-10KHz. Includes test report and Certificate of Conformance. RR0410-100H-10K-TF	RR0410-100H-10K-TF	D0815E1015-2085		·
	CONTOLINIAICE, NRV41V-100H-10R-IF				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
	DESCRIPTION LOW FREQUENCY REFLECTION RING PROBE 100Hz- 2KHz, .42"Ø ID x 1.0"Ø DIA OD, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	RDP.9-1K		EQUIVALENT	EQUIVALENT
ARP-1.042/100H	Conformance.		TEK-1005	•	•
ARR.090SS/1.1WL	BOLT HOLE PROBE 100K-2MHZ, 1.1WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.090SS	•	•	
ARR.125SS/1.5WL	BOLT HOLE PROBE 100K-2MHZ, 1.5WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.125SS			
ARR.156SS/1.5WL	BOLT HOLE PROBE 100K-2MHZ, 1.5WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.156SS			•
ARR.187SS/1.5WL	BOLT HOLE PROBE 100K-2MHZ, 1.5WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.18755			
ARR.250SS/1.5WL	BOLT HOLE PROBE 100K-2MHZ, 1.5WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.250SS			
ARR.31255	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.312SS			
ARR.437SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.437SS	-		
ARR.500SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.500SS			
ARR.562SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.562SS			
ARR.625SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.62555			
ARR.750SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.750SS			
ARR.875SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR.875SS			
ARR1.0SS	BOLT HOLE PROBE 100K-2MHZ, 2.0WL STAINLESS STEEL RECHII, 4 PIN STEP LEMO. Includes Test Report and Certificate of Conformance	RR1.0SS			
ARP-1.050/500H	LOW FREQUENCY BRIDGE / DIFFERENTIAL RING PROBE .500"Ø ID 1.00"Ø OD, TRIAX FISCHER CONNECTOR 500H2-5KH2. Includes Test Report and Certificate of Conformance.	LR0110-1			
ARP-1.055/100H	REFLECTION RING PROBE 1.00"Ø OD .550"Ø OD, 1.20" HIGH, TRIAX FISCHER CONNECTOR, 100Hz-10KHz Includes test report and Certificate of Conformance. RR0510-100H-10K-TF	RR0510-100H-10K-TF	D0815E1015-2087		
ARP-1.060-100H	LOW FREQUENCY REFLECTION RING PROBE 60° ID 1.0° OD 100HZ-3KHZ TRIAX FISCHER CONNECTOR 737 PT 6 57-10-55 and 777-200/300 57-20-03 PART 6 PAGE 1. Includes Test Report and Certificate of Conformance.	RDP1.0-100H-6, LFRR600- 1.0	LFRR600-1.0	LFRR600-1.0	
ARP-1.0/.312/500HZ	LOW FREQUENCY REFLECTION RING PROBE 500Hz- 5KHz, .312"Ø ID x 1.0"Ø DIA OD, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ARP-1.0/.33-1k	LOW FREQUENCY REFLECTION RING PROBE .330" ID 1.0" OD 100HZ-1KHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ARP-1.0/.50/200H	LOW FREQUENCY REFLECTION RING PROBE .500°Ø ID x 1.0°Ø OD 200Hz-3KHz WITH A TRIAX FISCHER CONNECTOR. 737 PART 6 57-10-60, pg.2 USED WITH NDT3157. Includes Test Report and Certificate of Conformance.	RDP1.0/.5-200H	RNG-008		
ARP-1.0/100H-6	CUSTOM LOW FREQUENCY RING PROBE 100Hz-SKHz REFLECTION WITH TRIAX FISHER CONNECTOR737 PART 6 57-10-55, pg.2 USED WITH NDT3152-X SERIES. Includes test report and Certificate of Conformance	RDP1.0-100H-6			
AUR125SS/65MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR .125" DIAMETER, 2.5" WORKING LENGTH Includes Test Report and Certificate of Conformance				
AUR250SS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .250"(7.14mm), 2.5"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR312SS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .312"(7.92mm), 2.5"(65mm)	-			-
ARP-1.0-100H-5	REFL RING PROBE 500 HZ-3KHZ, 1.0"Ø OD, .500"Ø ID WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RDP1.0-100H-5/TF	RR0110-5-4L		÷
ARP8040-50HZ	LOW FREQUENCY REFLECTION RING PROBE .4" ID .8" OD 50Hz-3kHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	-			
ARP-1.1625/100HZ	LOW FREQUENCY RING PROBE, BRIDGE / DIFFERENTIAL, .625" Ø ID 1.1" Ø OD, 100Hz-1KHz WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance				*
ARP-1.1625/100HZ	LOW FREQUENCY RING PROBE, BRIDGE / DIFFERENTIAL, .625"Ø ID 1.1"Ø OD, 100Hz-1KHz WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				-
ARP-1.1067-100H	LOW FREQUENCY REFLECTION RING PROBE, 100Hz-1KHz, .670°Ø ID 1.100°Ø OD SUPPLIED WITH A TRIAX FISCHER CONNECTOR 100Hz-1KHz. IncluderSter Report and Certificate of Conformance.	RDP1.167/100H	RNG-001		
ARP-1.1-100H	Includes rest Report and Certificate of Comornance. LOW FREQUENCY REFLECTION RING PROBE .750°Ø ID 1.100°Ø OD WITH A TRIAX FISCHER CONNECTOR 50Hz-3KHz. Includes Test Report and Certificate of Conformance.	RDP1.1-100H			·
ARP-1.26/100H	OF CONTORMANCE: LOW FREQUENCY REFLECTION RING PROBE 1.20"Ø OD .600"Ø ID TRIAX FISCHER CONNECTOR 50HZ-3KHZ. Includes Test Report and Certificate of Conformance	RDP1.26/50H-3KHZ	RDP1.26/50H-3KHZ,	ARP/16/40P	RR0112-5/TF
ARP-1.2/100H-7	Comornance. LOW FREQUENCY REFLECTION RING PROBE 1.2" OD, 605" ID, 50Hz-3KHz TRIAX FISHER CONNECTOR. 737 PART 6 57-10-58, pg.2. and 737 PART 6 57- 10-54, pg.2 USED WITH NDT3153-X AND 3167-X SERIES REFERENCE STANDARDS. Includes Test Report and Certificate of	RDP1.2-100H-7	RR0112-5/TF	RDP1.2-100H-7	RDP1.2-100H-7
ARP-1.2575-300H	10-59, pg. 2 OSED WITH NOTS135*X AND SID*X SERIES REFERENCE STRUDARDS. INCLUDE TEX REPORT and Certificate Of REFLECTION RING PROBE TRIAX FISHER CONNECTOR, 1.25"(D.75" ID(19.6mm) 300HZ-1KHZ. 737 PART 6 57-10-53, pg.2, USED WITH REFERENCE STANDARD ND13168 AND NDT3176-X. Includes text report and Certificate of Conformance	RDP1.2575/300H			1.01 1.2-1001*/
ARP-1.2577/300H	LOW FREQUENCY RING PROBE REFLECTION TRIAX FISHER CONNECTOR, 1.25" OD[31.8mm] .77" ID[19.6mm] 300HZ-1KHZ. 737 PART 6 57-10-62, pg.2. Includes Test Report and Certificate of Conformance.	RDP1.2577/300H			-
ARP-1.25/.5	Includes Test Report and Certificate of Conformance. LOW FREQUENCY RING PROBE, BRIDGE / DIFFERENTIAL, .500°Ø ID 1.25°Ø OD, 100Hz-1KHz WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-783		SPO-783	
ARP-1.25/.74/50HZ	Lerrificate of Conformance. LOW FREQUENCY REFLECTION RING PROBE, 50HZ- 1KHZ. 74"ID 1.25" OD TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	RDP1.2574/50HZ			<u>.</u>
	Lonrormance.		l		

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARP-1.25/.86/50HZ-3kHZ	LOW FREQUENCY REFLECTION RING PROBE 1.25" Ø OD, .860" Ø ID, 50HZ-3kHZ, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	RR0115-4/TF	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARP-1.378-500H	Conformance. LOW FREQUENCY REFLECTION RING PROBE .780°Ø ID, 1.300°Ø OD WITH A TRIAX FISCHER CONNECTOR, 500Hz-20KHz. Includes Test Report and	RDP1.378-500H	RDP1.378-500H-TI		
ARP-1.3585-500H	Certificate of Conformance. LOW FREQUENCY RING PROBE, REFLECTION 100Hz-1KHz, 1.35" O.D.x.850"LD. TRIAX FISCHER CONNECTOR USED ON NDT3178G 737 PART 6 57-10-62, pg.2. Includes Test Report and Certificate of Conformance.	RDP1.3585-500H			
ARP-1.4060/80HZ	LOW FREQUENCY REFLECTION RING PROBE.50°Ø1.D. 1.40°Ø.O.D. TRIAX CONNECTOR 80Hz-3KHz., 757 PT 6 57-20-03. Includes test report and Certificate of Conformance.		•		
ARP-1.40/.85-200Hz	LOW FREQUENCY REFLECTION RING PROBE. 85" I.D. 1.40" O.D. TRIAX FISCHER CONNECTOR 100Hz-500Hz. REFERENCE STANDARD NDT3176-X 737 PT 6 57-10-59. Includes test report and Certificate of Conformance.	RDP1.4085-200H			
ARP-1.60/.90-100Hz	LOW FREQUENCY REFLECTION RING PROBE .90" I.D. 1.60" O.D. TRIAX CONNECTOR 100Hz-1KHz Includes test report and Certificate of Conformance.				
ARP-31.8M/19.6M-100H	CUSTOM RING PROBE REFLECTION TRIAX FISHER CONNECTOR, 1.25"OD(31.8mm).77" ID(19.6mm) 100HZ-1.5KHZ. Includes Test Report and Certificate of Conformance.		•		
ARP-34.3M/21.6M-100H	CUSTOM RING PROBE REFLECTION TRIAX FISHER CONNECTOR, 1.35" OD (34.3mm) .77" ID (22.4mm) 100HZ-1.5KHZ. Includes Test Report and Certificate of Conformance.				
ARR099SS	STAINLESS STEEL ROTATING SCANNER PROBE, 0.099Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. 1.1" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	RR.090SSI	BPU-0.099-SSI		
ARR125	OLYMPUS NDT / NDT ENGINEERING CORP. ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO, 1/8"(.125") OD, 1.1" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPRA8-1-8	BPRA8-1/8		
ARR125SE/1.1WL	RECHII BOLT HOLE PROBE 200KHz-3MHz, SPLIT END FOR RA SCANNER, 1.1" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 125"156". Includes Test Report and Certificate of Conformance.	9230784			
ARR125SE/2.0WL	RECHII BOLT HOLE PROBE 200KHz-3MHz, SPLIT END FOR RA SCANNER, 2.0" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 125"156". Includes Test Report and Certificate of Conformance.		-		
ARR125SS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 125"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. SOMM(1.97") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.125SS			
ARR140SS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 125"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. SOMM(1.97") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.140SS			
ARR156SE/1.1WL	RECHII BOLT HOLE PROBE 200KHz-3MHz, SPLIT END FOR RA SCANNER, 1.1" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR 156"187". Includes Test Report and Certificate of Conformance.	SPO-3564,9230078	SPO-3564		
ARR156SE/1.5WL	RECHII BOLT HOLE PROBE 100KHz-2MHz, SPLIT END .156"187"Ø 1.5" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER. Includes Test Report and Certificate of Conformance. SPO-3564		-		
ARR156SS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE, .156"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. SOMM(1.97") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.156SS			
ARR156SS/80MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 1.56"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. 80MM(3.15") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.156SS			
ARR171SS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 1.71 "Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. SOMM(1.97") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.171SS			
ARR187SE/1.1WL	RECHII BOLT HOLE PROBE 500KHz-3MHz, SPLIT END 187"218"Ø, 1.1" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER.Includes Test Report and Certificate of Conformance. SPO-3564	9217153	SPO-3564		
ARR187SE/1.5WL	RECHII BOLT HOLE PROBE 200KHz-3MHz, SPLIT END 187"218"Ø, 1.5" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER.Includes Test Report and Certificate of Conformance. SPO-3564	SPO-3564,9217153			
ARR1875S/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN STEP LEMO CONNECTORHEAD DIAMETER: .187"(4.75mm), 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
ARR187SS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE, .187"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. SOMM(1.97") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.187SS	-		
ARR187SS/80MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 137"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. 80MM(3.15") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.187SS			
ARR203SS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 203"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. SOMM(1.97") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.203SS			
ARR.203SS/80MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 203"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. SOMM(1.97") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.203SS			
ARR203SS/80MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 203"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. 80MM(3.15") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.203SS			
ARR218SE/1.1WL	RECHII BOLT HOLE PROBE 500KHz-3MHz, SPLIT END 218"250"Ø, 1.1" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER. Includes Test Report and Certificate of Confromance. SPO-3564	9217154			
ARR218SE/1.5WL	RECHII BOLT HOLE PROBE 200KHz-3MHz, SPLIT END 218"250"Ø, 1.5" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER.Includes Test Report and Certificate of Conformance. SPO-3564	SPO-3564, 9217154			
ARR218SS/2WL	STAINLESS STEEL ROTATING SCANNER PROBE, .218"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL SHIELDED, 4 PIN STEP LEMO CONNECTOR. S1MM(2.0") WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
ARR234SS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 234"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. SOMM(1.97") WORKING LENGTH Includes Test Report and Certificate of Conformance.	RR.234SS			
ARR.250SE	RECHII BOLT HOLE PROBE 200KHz-1MHz, SPLIT END, 250"-281" 1.1" WORKING LENGTH, 4 PIN STEP LEMO CONNECTOR. Includes test report and Certificate of Conformance.	SPO-3564, 9217155			
ARR250SE/1.1WL	RECHII BOLT HOLE PROBE 200KHz-3MHz, SPLIT END 250"283 "Ø, 1.1" WORKING LENGTH, 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER. Includes Test Report and Certificate of Conformance. SPO-3564				
APN-94-6FX/7L	FLEXIBLE SURFACE PROBE, ABS SHIELDED, 90° DEGREES, .400"(101mm) DROP, 6.0"(15.2CM) LONG, SUPPLIED WITH A 7 PIN LEMO CONNECTOR, 50KHz- 500KHz. Includes Test Report and Certificate of Conformance. U8629778, 9403474	M7L904-60FX	U8629778	9403474	
ARR250SE/1.5WL	RECHII BOLT HOLE PROBE 500KHz-3MHz, SPLIT END .218". 250"Ø, 1.5" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER.Includes Test Report and Certificate of Conformance. SPO-3564				
ARR250SE/2.0WL	RECHII BOLT HOLE PROBE 200KHz-1MHz, SPLIT END, 250"-281" 2.0" WORKING LENGTH, 4 PIN STEP LEMO CONNECTOR. Includes test report and Certificate of Conformance.	RTP-030			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EOUIVALENT
ARR250SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN STEP LEMO CONNECTOR. HEAD DIAMETER: .250"(7.14mm), 2.0"(51mm)	EQUIVILEI	EQUIVILEI	EQUIVILLEI	
ARR25055/50MWL	WORKING LENGTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE, 250°Ø 100kHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR.	RR.250SS	:	·	
ARR265SS/50MWL	50MM(1.97") WORKING LENGTH Includes Test Report and Certificate of Conformance. 5TAINLESS STEEL ROTATING SCANNER PROBE, 265"Ø 100KH-27MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR.	RR.265SS			
ARR281SE/1.5WL	SOMM(I.97") WORKING LENGTH Includes Test Report and Certificate of Conformance. RECHI BOLT HOLE PROBE 500KH-3MHz, SPLIT END 281", 312"Ø, 1.5" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER.	9217156		•	•
ARR281SS/50MWL	Includes Test Report and Certificate of Conformance. SPO-3564 STAINLESS STEEL ROTATING SCANNER PROBE, 281°Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. SOMMI4.39°V MORKING LENGTH. Includes Test Report and Certificate of Conformance.	RR28155		•	
ARR296SS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE, .265"Ø 100KHz-2MHz REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR.	RR.296SS			•
ARR305/52WL	50MM(1.97") WORKING LENGTH Includes Test Report and Certificate of Conformance. RECHI ROTARY PROBE FOR RA2000/ MINI MITE SCANNER USED WITH THE NORTEC 600. 100KHz-2MHz. 4 PIN STEP LEMO. 305"Ø OD, 52.0" WORKING				•
ARR312SE/1.5WL	LENGTH. Includes Test Report and Certificate of Conformance. RECHII BOLT HOLE PROBE 500KH-3-3MHz, SPLIT END. 312*.375°Ø 1.5" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER. Includes Test Report and Certificate of Conformance. SP0-3564	9217157		•	
ATBL-360-6	Includes Test Report and Certificate of Comormance: 5PO-3584 BLADE PROBE, 30°.060° THICK, 6.0° LONG, 50-500KH2 SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	BL360-6			
ATBL-490-6	EDDY CURRENT BLADE PROBE, .090" THICK, 45" ANGLE TIP, 6.0" LONG, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	BL490-6			
ATBL-645-6	Conformance. EDDY CURRENT BLADE PROBE, .045" THICK, 60" ANGLE TIP, 6.0" LONG, 50-500KHz, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	BL645-6		•	
ATBL-660-6	and certificate of conformance. EDDY CURRENT BLADE PROBE, LOGO" THICK, 60" ANGLE TIP, 6.0" LONG, 50-500KHz, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	BL660-6			
ARP3570/80Hz-4kHz	and Certificate of Conformance. LOW FREQUENCY REFLECTION RING PROBE .35" ID .7" OD 80Hz-4kHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ARP480/50Hz-3kHz	LOW FREQUENCY REFLECTION RING PROBE .4" ID .8" OD 50Hz-3kHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	•
	LOW FREQUENCY REFLECTION RING PROBE .6" ID 1.25" OD 50Hz-3kHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of				
ARP6-1.25/50Hz-3kHz ASDP31/700HZ-80khz	Conformance. IF REFLECTION SPOT PROBE .31" DIA 700HZ-80KHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				•
	LF REFLECTION SPOT PROBE .62" DIA 100HZ-20KHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ASDP62/100HZ-20khz ARP2560/100Hz-5khz	LOW FREQUENCY REFLECTION RING PROBE .25" ID .6" OD 100HZ-5KHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of				
AURFX312SS/9L	Conformance. FLEXIBLE ROTARY PROBE 9.0° LONG WITH COLLAR.312 DIA HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFX375SS/9L	Let flicate of conformance. FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR.375DIA HEAD STAINLESS STEEL 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ. Includes Test Report and Certificate of conformance.				
ARR312SE/2WL	Lee nicate of comormance. RECHII BOLT HOLE PROBE 200KHz-3MHz, SPLIT END. 312"375"Ø, 2.0" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER.Includes Test Report and Certificate of Conformance. SPO-3564	SPO-3564			
ARR312SS/50MWL	SCHWERNICIDUES TEST REDUCTION COMMANDER SPOSSON STAINLESS STEEL ROTATING SCANNER PROBE, 312°Ø 100KH-2-2MH2 REFLECTION / DIFFERENTIAL UNSHIELDED, 4 PIN STEP LEMO CONNECTOR. SOMM(1,97) WORKING LENGTH. I.Includes Test Report and Certificate of Conformance.	RR312SS			•
ARR375SE/1.5WL	RECHI BOLT HOLE PROBE 500KH-2: MHZ; SPLITE REPORTENDE CONTINUES: RECHI BOLT HOLE PROBE 500KH-2: MHZ; SPLITE BOL 375"-437"Ø, 1.5"WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER. Includes TEST Report and Certificate of Confromance. SPO:3564	9217158			
ARR3755E/2.0WL	RECHI SCANNER PROBE CINKHELE OF COMMINIMENTED SO OSCIONE RECHI SCANNER PROBE DIOKHZ-20HIZ 4 PIN STEP LEMO USED WITH RA SCANNER 3.0" OVERALL LENGTH SPLIT END .375"437", 2.0" WORKING LENGTH. ICIUEA TEST REPORT AND CERTIFICATE OF CONFORMANCE	SPO-3564	RTP-029	•	•
ARR375SE/2WL	RECHII BOLT HOLE PROBE 200KHz-3MHz, SPILT END.375", 437"Ø, 2.0" WORKING LENGTH 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER.Includes Test Report and Certificate of Conformance. SP0-3564	SPO-3564,9217158			
ARR437/8L	RECHI BOLT HOLE PROBE, 100KH-22MH2, EXPANDABLE FROM .437"500", SPLIT END USED WITH RA SCANNER, 8.0" OVERALL LENGTH WITH A 4 PIN STEP LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.			•	•
ARR437SE/1.5WL	RECHII BOLT HOLE PROBE 500KHZ-3MHZ, SPLIT END 437-500", 1.5"WORKING LENGTH, 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER. Includes Test Report and Certificate of Conformance. SP0-3564	9217159		•	
ARR437SE/2WL	RECHII SCANNER PROBE 200KHz-3MHz 4 PIN STEP LEMO USED WITH RA SCANNER 3.0" OVERALL LENGTH SPLIT END .437"500", 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance	SPO-3564,9217159			
ARR450SE/2.0WL	ROTARY PROBE FOR RADOO SCANNER 100KHz-2MHz 4 PIN STEP LEMO, .450°Ø OD, 2.0" WORKING LENGTH. Includes Teset Report and Certificate of Conformance.	SPC-982-FE			
ARR500SE/1.5WL	RECHII BOLT HOLE PROBE 500KHz-3MHz, SPLIT END, 1.5" WORKING LENGTH, 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER, 500"562". Includes Test Report and Certificate of Conformance. SP0-3564	9217160			
ARR500SE/2.0WL	RECHI SCANNER PROBE 100KHz-2MHz 4 PIN STEP LEMO USED WITH RA SCANNER 3.0" OVERALL LENGTH SPLIT END .500"562", 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
ARR500SE/2WL	RECHII SCANNER PROBE 200KHz-3MHz 4 PIN STEP LEMO USED WITH RA SCANNER 2.0" OVERALL LENGTH SPLIT END .500"625", 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SPO-3564			
ARR625SE/1.5WL	RECHII BOLT HOLE PROBE 200KHz-1MHz, SPLIT END, 1.5" WORKING LENGTH, 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER, 625"687". Includes Test Report and Certificate of Conformance. SP0-3564				
ATPN-35-6FX	FLEXIBLE SURFACE PROBE, 35" DEGREES .500" DROP 6.0" LONG TRIAX FISCHER CONNECTOR 50KHZ-500KHz. Includes Test Report and Certificate of Conformance.	MTF305-60FX			
ATPN-45-9FX	FLEXIBLE SURFACE PROBE 45" DEGREES, 9.0" LONG, TRIAX FISCHER CONNECTOR, 50-500KHz IncludesTest Report and Certificate of Conformance	TPENFLX45-9			
ATPN-91-12FX	FLEXIBLE SURFACE PROBE, 90° DEGREES .100" DROP 12.0" LONG TRIAX FISCHER CONNECTOR 50KHZ-500KHz. Includes Test Report and Certificate of	TPENFLX-9/500K	1		T

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPN-9FX/500K	FLEXIBLE SHAFT STRAIGHT COPPER SURFACE PROBE, .125"Ø TIP, TRIAX FISCHER CONNECTOR, 500KHz-1MHz, 9.0" LONG. Includes Test Report and Certificate of Conformance	TPENFLX-9/500K			
AUR-9.0MSS/50MWL	Let mixate of comominance UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .354"Ø(9.0mm), 50mm WORKING LENGTH. Compatible with Rohmann Elotest SMRA Rotor. Includes Test Report and Certificate of Conformance.	RSM9-0-50			
AUR-3.9MSS/75MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .154" Ø(3.90mm), 75mm WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.	RSM3-9-75			
AXPN-95-6FX	FLEXIBLE SURFACE PROBE 90° DEGREES, 500 DROP 6.0 " LONG .072" Ø SHAFT, 50-500khz SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	SPENFLX95-6			
AXPN-92-8FX	FLEXIBLE SUFACE PROBE.072*Ø OD TIP, 90* DEGREES, 200* DROP 8.0* LONG, 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MP902-80FX			
AUR-10.5MSS/50MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .413" Ø(10.5mm), 50mm WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.	RSM10-5-50			
AUR-10.0MSS/50MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .394 <sup>+</sup> Ø(10.0mm), 50mm WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.	RSM10-0-50			
AUR-8.7MSS/50MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .343"Ø(8.7mm), 50mm WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.	RSM8-7-50			
AUR-7.9MSS/75MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .311°Ø(7.9mm), 75mm WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.	RSM7-9-75			
ARR625SE/2WL	RECHII SCANNER PROBE 200KHz-3MHz 4 PIN STEP LEMO USED WITH RA SCANNER 2.0" OVERALL LENGTH SPLIT END .625"750", 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.ER THIS P/N	SPO-3564			
ARR687SE/1.5WL	RECHII BOLT HOLE PROBE 500KH2-3MHz, SPLITEND.687". 750", 1.5"WORKINGLENGTH, 4 PIN STEP LEMO CONNECTOR. USED WITH RA SCANNER. Includes Test Report and Certificate of Conformance. SPO-3564	9218787,U8614101	SPO-3564		
ARR750SE/2WL	RECHII SCANNER PROBE 200KHz-3MHz 4 PIN STEP LEMO USED WITH RA SCANNER 2.0" OVERALL LENGTH SPLIT END .750"875", 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SPO-5964			
ARR875SE/2WL	RECHII SCANNER PROBE 200KHz-3MHz 4 PIN STEP LEMO USED WITH RA SCANNER 2.0" OVERALL LENGTH SPLIT END .875"- 1.0", 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SPO-3564			
ARR-1.98MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN STEP LEMO CONNECTOR, 35MM(1.50") WORKING LENGTH, 1.98MM(0.078")Ø HEAD. Includes Test Report and Certificate of Conformance.				
ARR-2.38MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN STEP LEMO CONNECTOR, 35MM(1.50") WORKING LENGTH, 2.38MM(0.0937")Ø HEAD. Includes Test Report and Certificate of Conformance.				
ARR-2.78MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN STEP LEMO CONNECTOR, 35MM(1.50") WORKING LENGTH, 2.78MM(0.109")Ø HEAD. Includes Test Report and Certificate of Conformance.				
ARR-25.40SE/2WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END, 2.0" WORKING LENGTH, 4 PIN STEP LEMO, BOLT HOLE SIZE RANGE 25.40mm(1.000")Ø - 27.22mm(1.075")Ø. Includes Test Report and Certificate of Conformance.				
ARRCS100.218	RECHI RA SCANNER 100 DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 7/32"(.218") OD 3.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.				
ARRCS100218	RECHII RA SCANNER 100" DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 7/32"(.218") OD 3.0" OVERALL. Includes Test Report and Certificate of Conformance.	CSRA100-14	RC1.218		
ARRCS100.21855	RECHII RA SCANNER STAINLESS STEEL 100° DEGREE COUNTERSINK PROBE 100KHz-2MHz, 4 PIN STEP LEMO 7/32"(.218") OD 3.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.	CSRA100-14/SS			
ARRCS100250	RECHII RA SCANNER 100° DEGREE COUNTERSINK PROBE 100KHz-2MHz 4 PIN STEP LEMO 1/4"(.250")Ø OD 3.0° OVERALL. Includes Test Report and Certificate of Conformance.	CSRA100-16	CSRA100-16	RC1.250	
ARRFBFX-5.1MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 5.1MM HEAD STAINLESS STEEL 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE) Includes Test Report and Certificate of Conformance.				
AMH.062	Manual hole probe, 0.062 inch (1.5mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.				
AMH1.0	Manual hole probe, 1.0 inch (25.4mm) diameter and 2.0 inch (50.8mm) working length, frequency 50kHz - 500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.				
ARRFBFX-5.4MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 5.4MMØ HEAD STAINLESS STEEL 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE) Includes Test Report and Certificate of Conformance.				
ARRFBFX-6.2MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 6.2MMØ HEAD STAINLESS STEEL 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE) Includes Test Report and Certificate of Conformance.		•		
ARRFBFX-6.6MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 6.6MMØ HEAD STAINLESS STEEL 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE) Includes Test Report and Certificate of Conformance.		•		
ARRFBFX-7.0MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 7.0MMØ HEAD STAINLESS STEEL 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE) Includes Test Report and Certificate of Conformance.				
ARRFBFX-7.8MSS/5L	FLEXIBLE ROTARY FLAT BOTTOM PROBE 5.0" LONG 7.8MMØ HEAD STAINLESS STEEL 4 PIN STEP LEMO CONNECTOR 100KHZ-2MHZ (TAPER END OF THE PROBE) Includes Test Report and Certificate of Conformance.		•		
ARRFX.156SS/5.5WL	FLEXIBLE STAINLESS STEEL PROBE FOR RA2000 SCANNER 4-PIN STEP LEMO CONNECTOR. 100KHZ-2MHZ. 5.5" WORKING LENGTH. Includes Test Report & Certificate of Conformance.				
ARRFX.187SS/5.5WL	FLEXIBLE STAINLESS STEEL PROBE FOR RA2000 SCANNER 4-PIN STEP LEMO CONNECTOR. 100KHZ-2MHZ. 5.5" WORKING LENGTH. Includes Test Report & Certificate of Conformance.				
ARRX-2.20-2.325	ADJUSTABLE "X" ROTARY HOLE PROBE 100KHz-2MHz, 2.20" &-2.325" with a 4 PIN STEP LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-3160-2.2/2.325-U			
ARRX-2.31/2.435	ADJUSTABLE "X" ROTARY HOLE PROBE 100KHz-2MHz, 2.31" &-2.435" with a 4 PIN STEP LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-3160-2.31/2.435-U			
ARRX-2.56-2.685	ADJUSTABLE "X" ROTARY HOLE PROBE 100KHz-2MHz, 2.56" / -2.685" with a 4 PIN STEP LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-3160-2.56-2.685-U			
ARS-123/TI	EDDY CURRENT SURFACE REFERENCE STANDARD. MATERIAL: TI-6AL-6V-2SN. SIZE: 2.0" LONG x 1.0" WIDE. EDM NOTCH .040" DEEP +/002" x .005" WIDE +/001". Includes Test Report and Certificate of Conformance.				
ARS-1S	Surface reference standard, 4340 or 4130 steel, with EDM notch depth of 0.010" x .005" wide Reference standard overall dimensions 1.0" X 3.0" X 0.25" inches .007" W MAX. Includes Certification traceable to NIST.	SRS-1S			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ASDP25/2K-200KHz	LOW FREQUENCY REFLECTION SPOT PROBE 2KHz-200KHz TOP MOUNTED TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	SPO-5326	9218204		EQUIVILLI
ASDP25/7L	Conformance. DETACHABLE STANDARD REFLECTION SPOT PROBE. 0.25 IN. (6.3MM) DIAMETER. SkHZ-100KHZ. 7-Pin LEMO POWERLINK CONNECTOR. Includes Test Report and Certificate of Conformance.	9222196	U8626007	SPO1598,SPO1284	
ASDP25/7L/2-200K	REPORT and Certificate Oction mance. STANDARD REFLECTION SPOT PROBE: 0.25 IN. (6.3MM). 2kZ-200KHZ. 7-Pin LEMO POWERLINK CONNECTOR. Includes Test Report and Certificate of Conformance.	9222201	SPO-2404	APR/7/S	
ASDP25/L16-1-100K	STANDARD SIDE MOUNT REFLECTION SPOT PROBE WITH A 16 PIN LEMO 6.0 FT ATTACHED. 0.25 IN. (6.3MM). 1Khz100KHz. Includes Test Report and Certificate of Conformance.	SPO-2404			
ASDP25/TF/1-100K	STANDARD SIDE MOUNT REFLECTION SPOT PROBE. 0.25 IN. (6.3MM). 1K2-100KHz. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-2404	APR/7/S		
ASDP250/1-10KHZ	LOW FREQUENCY DIFFERENTIAL SPOT PROBE RIGHT ANGLE, .250" Ø O.D. 1-10KHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformation.	LS203-1T/F			
ASDP250/2KHZ-200KHZ	REFLECTION SPOT PROBE .250" OD TOP MOUNT TRIAX FISCHER CONNECTOR 2KHz-200KHz. Includes Test Report and Certificate of Conformance.	9213550	SPT-010		
ASDP250/300HZ-40KHZ	REFLECTION SPOT PROBE .250" OD TOP MOUNT TRIAX FISCHER CONNECTOR 300HZ-40KHZ. Includes test report and Certificate of Conformance.	SPT-008			
ASDP250/500HZ-60KHZ	REFLECTION SPOT PROBE .250" OD TOP MOUNT TRIAX FISCHER CONNECTOR 500KHZ-60KHZ. Includes test report and Certificate of Conformance.	SPT-009			
ASDP250/800HZ-20KHZ	LOW FREQUENCY REFLECTION SPOT PROBE .250" OD SIDE MOUNTED TRIAX FISCHER 800Hz-20KHz. Includes Test Report and Certificate of Conformance.	•			
ASDP250/TF/50-300KHz	HIGH FREQUENCY REFLECTION SPOT PROBE, 250" OD TOP MOUNTED TRIAX FISCHER CONNECTOR 50KHz-300KHz. Includes Test Report and Certificate of Conformance.	SPT-003			
ASDP31/7L	STANDARD REFLECTION SPOT PROBE. 0.31 IN. (7.9MM) DIAMETER. 700HZ-80KHZ. 7-Pin LEMO POWERLINK CONNECTOR. Includes Test Report and Certificate of Conformance.	9222200	SPO-2026	APR/8/S	
ASDP31/TF	STANDARD REFLECTION SPOT PROBE(STRAIGHT). 0.31"Ø (7.9MM) DIAMETER. 1KHz-50KHz. SUPPLIED WITH A TRIAX FISCHER / LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	9222162			
ASDP310	LOW FREQUENCY REFLECTION SPOT PROBE .310"Ø(7.87mm) O.D. SUPPLIED WITH A TOP MOUNTED TRIAX FISCHER CONNECTOR, 700Hz-80KHz. Includes Test Report and Certificate of Conformance. 1000 FREQUENCY REFLECTION INNG FROBE, 50Hz-3KHZ, 10 U.SUU (12.7mm)Ø, UU U.SUU (17.5mm)Ø, UVERALL HEIGHT = 1.56 (39.5mm) X UVERALL	9213551			
AF-4205	DIAMETER = .787"(20mm) Ø, WITH A TRIAX FISCHER CONNECTOR.Supplie with probe guide Figure 6 27-1-6023. Includes Test Report and Certificate of	SDP10H70T5			
ASDP312/1-20K	REFLECTION SPOT PROBE .312"Ø(7.85mm) TIP DIAMETER, .425"Ø(10.8mm) BODY DIAMETER. 1KHz-20KHz WITH TOP MOUNTED TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	VM120312			
ASDP312/500KHZ-1MHZ	HIGH FREQUENCY SPOT PROBE. REFLECTION .312" OD DIAMETER. 500KHz-1MHz, 200" Coil OD TRIAX FISCHER CONNECTOR. Includes Certificate of Conformance and Test Report.	SPT-014			
ASDP312/50-500KHZ	HIGH FREQUENCY SPOT PROBE. REFLECTION .312" OD DIAMETER. 50K-500KHz, .200"Ø coil OD. TRIAX FISCHER CONNECTOR. Includes Certificate of Conformance and Test Report.	SPT-013			
ASDP3-20K-1	LOW FREQUENCY REFLECTION SPOT PROBE, .300" Ø OD, 800Hz - 20KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	SDP.3-20K-1			
ASDP32-500H-1	LOW FREQUENCY SPOT PROBE, .320"ØOD x .950"High, 200Hz-15KHz, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SDP.32-500H-1			
AUR-4.7MSS/75MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MH2 SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .185"Ø(4.70mm), 75mm WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.	RSM4-7-75			
ASDP3-2K-1	LOW FREQUENCY DIFFERENTIAL SPOT PROBE RIGHT ANGLE, 320"Ø O.D. 1-10KHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformation.	LS203-1T/F	SB.3-2K-1		
ASDP.35-1K	LOW FREQUENCY REFLECTION SPOT PROBE, .350" Ø OD, 800Hz - 10KHz, SIDE MOUNT TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	SDP.35-1K			
ASDP38-500H	LOW FREQUENCY REFLECTION SPOT PROBE, .750"H x .380"Ø OD, 500Hz-5KHz WITH SIDE MOUNTED TRIAX FICHER CONNECTOR. Includes Test Report and Certificate of Conformance	SDP.3-500H			
ASDP4/2K	LOW FREQUENCY REFLECTION SPOT PROBE, 0.400° Ø OD, 800Hz-20KHz WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RS204-2TF			
ASDP4/50H-2Khz	LOW FREQUENCY REFLECTION SPOT PROBE TOP MOUNT, 0.400"Ø OD, 50Hz-2KHz WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ASDP44/7L	STANDARD REFLECTION SPOT PROBE. 0.44 IN. (11.2MM) DIAMETER. 400HZ-60KHZ. 7-Pin LEMO POWERLINK CONNECTOR. Includes Test Report and Certificate of Conformance.	9222199			
ASDP45/1KHZ	SURFACE SPOT PROBE, STANDARD BRIDGE .45" Ø DIAMETER TOP MOUNT TRIAX FISCHER CONNECTOR 1KHZ -5KHZ. Includes Test Report and Certificate of conformance.			•	
ASDP4-50H/4L	LOW FREQUENCY REFLECTION SPOT PROBE, 40'Ø DIAMETER SIDE MOUNT 4 PIN LEMO CONNECTOR 50Hz-2KHz. Includes Test Report and Certificate of Conformance.	SDP4-50H-4L		•	
ASDP470	LOW FREQUENCY REFLECTION SPOT PROBE, 470" Ø DIAMETER SIDE MOUNT TRIAX FISCHER CONNECTOR 500Hz-30KHz. Includes Test Report and Certificate of Conformance.	NEC-4031	TEK-1528		
ASDP5/100HZ-1KHZ	SPOT PROBE, REFLECTION, .500"Ø (13mm)OD, 1.5" TALL, TOP MOUNT(STRAIGHT) TRIAX FISCHER CONNECTOR. 100Hz-1KHz. Includes Test Report and Certificate of Conformance.	•		•	
ASDP5/10-40KHz	REFLECTION SPOT PROBE ACETAL BODY -500"Ø (13mm)OD, 1.8" LONG STRAIGHT (TOP MOUNT TRIAX FISCHER CONNECTOR) 10-40KHz. Includes Test Report and Certificate of Conformance.			•	
ASDP5/1-12KHz	REFLECTION SPOT PROBE ACETAL BODY .500"Ø (13mm)OD, 1.8" LONG STRAIGHT (TOP MOUNT TRIAX FISCHER CONNECTOR) 1-12KHz. Includes Test Report and Certificate of Conformance.	RS1005-5/TF			
ASDP5/1K	SPOT PROBE, DIFFERENTIAL, ACETAL BODY .500"Ø (13mm)OD, 1.5" LONG, .850" HIGH (SIDE MOUNT TRIAX FISCHER 500Hz-8KHz. Includes Test Report and Certificate of Conformance.	SDP.5-1K			
ASDP5/400HZ-30K	SURFACE SPOT PROBE, STANDARD BRIDGE .500°Ø DIAMETER TOP MOUNT TRIAX FISCHER CONNECTOR 400Hz-30KHz. Includes Test Report and Certificate of conformance. 9213548	SPO-565A	9213548		
ASDP5/4L	REFLECTION SPOT PROBE ACETAL BODY, 200Hz-200KHz, .511*Ø (13.0mm)OD, 1.5" LONG STRAIGHT (TOP MOUNT 4 PIN LEMO CONNECTOR). Includes Test Report and Certificate of Conformance.	700P13A, PUS13	TEK-4054-13A	700P13A	PUS13

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
	DESCRIPTION REFLECTION SPOT PROBE ACETAL BODY, SHIELDED, 500Hz-50KHz, .500"Ø (12.7mm)OD, 1.8" LONG STRAIGHT (TOP MOUNT TRIAX FISCHER		EQUIVALENT	EQUIVALENT	EQUIVALENT
ASDP5/500HZ-50K	CONNECTOR). Includes Test Report and Certificate of Conformance. STANDARD REFLECTION SPOT PROBE. 0.50 IN. (12.7MM) DIAMETER. 300HZ-40KHZ. 7-Pin LEMO POWERLINK CONNECTOR. Includes Test Report and	SPO-2136		•	
ASDP5/7L	Certificate of Conformance. REFLECTION SPOT PROBE ACETAL BODY, 200Hz-200KHz, .511"Ø (13.0mm)OD, 1.5" LONG STRAIGHT (TOP MOUNT TRIAX FISCHER CONNECTOR).	9222198	•	•	
ASDP5/TF	Includes Test Report and Certificate of Conformance. LOW FREQUENCY REFLECTION SPOT PROBE, 500°Ø DIAMETER TOP MOUNT TRIAX FISCHER CONNECTOR, 550Hz-5KHz, 440°Ø coil OD. Includes Test	PUS13	•	•	
ASDP500/550Hz-5KHz	Report and Certificate of Conformance. LOW FREQUENCY REFLECTION SPOT PROBE, 500°Ø DIAMETER TOP MOUNT TRIAX FISCHER CONNECTOR 5-50KHz, .440°Ø coil OD. Includes Test Report	SPT-011			
ASDP500/5-50Khz	and Certificate of Conformance.	SPT-012			
ASDP55/500HZ	SURFACE SPOT PROBE, STANDARD BRIDGE .55"Ø DIAMETER TOP MOUNT TRIAX FISCHER CONNECTOR 500Hz-5KHz. Includes Test Report and Certificate of conformance.		•		
ASDP620	SURFACE PROBE STANDARD BRIDGE.620" DIAMETER TOP MOUNT TRIAX FISCHER CONNECTOR 300Hz-10KHz. Includes Test Report and Certificate of conformance. Olympus P/N: 9213011	SPO-565	SPO-1125	9213011	
ASDP625	LOW FREQUENCY REFLECTION SPOT PROBE, COIL O.D500°Ø, OVERALL PROBE DIAMETER .625°Ø(OD) WITH TOP MOUNT TRIAX FISCHER CONNECTOR. FREQUENCY: 300HZ-10KHZ. Includes Test Report and Certificate of Conformance.		•		
ASDP625/10K	LOW FREQUENCY REFLECTION SPOT PROBE, COIL 0.D500"Ø, OVERALL PROBE DIAMETER .625"Ø(OD) WITH TOP MOUNT TRIAX FISCHER CONNECTOR. FREQUENCY: 5KHz-20KHz. Includes Test Report and Certificate of Conformance.				
ATMBF156187	TRIAX FISCHER MANUAL BOLT HOLE PROBE, SHEILDED, 100KHz-1MHz Includes Test Report and Certificate of Conformance	9216153.01			
ATMBF187250	TRIAX FISCHER MANUAL BOLT HOLE PROBE, SHEILDED 100KHz-1MHz Includes Test Report and Certificate of Conformance	9216154.01			
ATMBF250312	TRIAX FISCHER MANUAL BOLT HOLE PROBE, SHEILDED, 100KHz-1MHz Includes Test Report and Certificate of Conformance	9216156.01			
ATMBF312375	TRIAX FISCHER MANUAL BOLT HOLE PROBE, SHEILDED, 100KHz-1MHz Includes Test Report and Certificate of Conformance	9216158.01			
AF-5172/4F	HIGH FREQUENCY ABSOLUTE, SHIELED SURFACE PROBE, 100KHZ-6MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	KAS-3 H-65.08.1			
ASDP625/300HZ-10K	LOW FREQUENCY REFLECTION SPOT PROBE, COIL O.D500°Ø, OVERALL PROBE DIAMETER .625°Ø(OD) WITH TOP MOUNT TRIAX FISCHER CONNECTOR. FREQUENCY: 300HZ-10KHZ. Includes Test Report and Certificate of Conformance.				
ASDP980/100HZ	LOW FREQUENCY SPOT PROBE REFLECTION .980" DIAMETER(OD) TOP MOUNTED TRIAX FISCHER CONNECTOR. FREQUENCY: 100HZ-500HZ. Includes Test Report and Certificate of Conformance.	815P093	SDP.98-100H		
ASDP-1.0/300HZ	SURFACE SPOT PROBE, STANDARD BRIDGE 1.0"Ø DIAMETER TOP MOUNT TRIAX FISCHER CONNECTOR 300HZ. Includes Test Report and Certificate of conformance.				
ASDP-1.2/100HZ	LOW FREQUENCY SPOT PROBE REFLECTION 1.200 <sup>1</sup> Ø DIAMETER WITH SIDE MOUNTED TRIAX FISCHER CONNECTOR. FREQUENCY: 100HZ-700HZ. Includes Test Report and Certificate of Conformance.				
ASDP-10H70T5	LOW FREQUENCY REFLECTION SPOT PROBE SHIELDED, 50H2-3KH2 WITH TRIAX FICHER SIDE MOUNTED CONNECTOR. INCLUDES PROBE GUIDE FIGURE 6 27-1-6023 PART 6 57-20-07 PAGE 9. Test Report and Certificate of Conformance provided				
ASDP-6.746M/20-40K	LOW FREQUENCY SPOT PROBE REFLECTION 6.746 MM DIAMETER(OD) TOP MOUNT 7 PIN LEMO CONNECTOR. FREQUENCY: 20-40KHZ. Includes Test Report and Certificate of Conformance.	•	•		
APNR-45-6/7L	SURFACE PROBE, ABSOLUTE REFLECTION ANGLE SHAFT. 6.0" LONG. 45 DEG TIP. 0.5 IN. (12.7MM) DROP. 50KHZ-500KHZ. 0.125"Ø (3.17MM) SHAFT WITH A 7 PIN LEMO POWERLINK CONNECTOR. Includes Test Report and Certificate of Conformance.	9230999.00			
ASDP-9.128M	LOW FREQUENCY SPOT PROBE REFLECTION 9.128 MM DIAMETER(OD) TOP MOUNT 7 PIN LEMO CONNECTOR. FREQUENCY: 1-4KHZ. Includes Test Report and Certificate of Conformance.				
ASDPR25/2KHZ	LOW FREQUENCY REFLECTION SPOT PROBE, .250" Ø OD 1.5" LONG SIDE MOUNTED TRIAX FISCHER CONNECTOR 2KHz-100KHz. Includes Test Report and Certificate of Conformance.				
ASDPR5/100HZ-1KHZ	SPOT PROBE, REFLECTION, 500°Ø (13mm)OD, 1.5" LONG, .850" HIGH (SIDE MOUNT TRIAX FISCHER CONNECTOR. 100Hz-1KHz. Includes Test Report and Certificate of Conformance.				*
ASPN-4.5/20-200K	ABSOLUTE SHIELDED STRAIGHT PENCIL PROBE .092"Ø TUBING 4.5" LONG MICRODOT CONNECTOR 20-200KHz Includes Test Report and Certificate of Conformance.	104P4XF			
ASPN-4.5/2MHZ	STRAIGHT SURFACE PROBE, Absolute Shielded 1-3MHz, .092"Ø OD Tip, 4.5" Long with Microdot Connector. Includes Test Report and Certificate of Conformance.	106P4F	610-047-002		
ASPN-4.5/6MHZ	STRAIGHT SHIELDED SURFACE PROBE 6MHz WITH MICRODOT CONNECTOR 114mm LONG .092" DIA. TUBING. Includes Test Report and Certificate of Conformance.	107P4			
ASPN-45-4/2M	Comornance. RIGID SURFACE PROBE 45° 1-3MHz, .093°Ø° DIA TUBING, .500° DROP, 4.0° LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	SPEN45-4/2M			
ASPN-45-5	OI COMORTMARCE. RIGID SURFACE PROBE 45° 50-500KHz, .093°Ø° DIA TUBING, .500° DROP, 5.0° LONG SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ASPN-45-5/2MHZ	and centrate of conformance. RIGID SURFACE PROBE 45° 1-3MHz, .093°Ø° DIA TUBING, .500° DROP, 5.0° LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ASPN-475-4.5/2MHZ	RIGID SURFACE PROBE 45° DEGREES .750 CRANK, 4.5″ LONG .092″ Ø DIAMETER TUBING ABS SHIELDED 1-3MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	206P4F			
ASPN-5	RIGID SUFFACE PROBE, STRAIGHT SHAFT, 50-500KHz, 093"Ø, 5.0" LONG SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				-
AF-4034	LOW FREQUENCY REFLECTION RING PROBE, 500°Ø ID x 1.0°Ø OD x .1175"H. FREQUENCY RANGE: 100Hz-10KHz, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. Includes Test Report and Certificate of Conformance	NEC-4028-2	TEK-3006-2	SPO-6087	
AUR187SS/1.75WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.75" WORKING LENGTH. USED				
AUR250SS/1.75WL	WITH ROHMANNN MINI ROTOR. 187"Ø Includes Test Report and Certificate of Conformance ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.75" WORKING LENGTH. USED				
	WITH ROHMANNN MINI ROTOR250"Ø Includes Test Report and Certificate of Conformance RIGID SURFACE PROBE, STRAIGHT SHAFT, 1-3MHz, .093"Ø, , 5.0" LONG SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate				
ASPN-5/2MHZ	of Conformance.		•	•	

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR312SS/1.75WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.75" WORKING LENGTH. USED				EQUITIEET
AUR-4.7MSS/51MWL	WITH ROHMANNN MINI ROTOR312"Ø includes Test Report and Certificate of Conformance STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .185" (4.7MM) 2.0"(51mm)	615P047M051			
AUR-3.9MSS/51MWL	WORKING LENGTH Includes Test Report and Certificate of Conformance STAINLESS STEEL ROTATING SCANNER PROBE 100KH-2.3MH2 SHELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .155"(3.9mm) 2.0"(51mm) PROPUNCING TEXT AND A TEXT A	615P039M051			
AURFB312SE/1.5WL	WORKING LENGTH Includes Test Report and Certificate of Conformance UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE FROM DOT ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER FLAT BOTTOM PROBE SUPPLIED WITH				
AUR750MSS/35MWL	.312"-375"Ø Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .750"(19.05mm)Ø,	615P048F035			
APN-45-6/7L/1-6MHZ	35mm(1.378") WORKING LENGTH. Includes Test Report and Certificate of Conformance. SURFACE PROBE, ABSOLUTE BRIDGE ANGLE SHAFT. 6.0" LONG. 45 DEG TIP. 0.5 IN. (12.7MM) DROP. 1MHZ-6MHZ FREQUENCY. 0.125"Ø(3.17MM)	9403485			
AXPN-45-4	SHAFT WITH A 7 PIN LEMO POWERLINK CONNECTOR. Includes Test Report and Certificate of Conformance. SURFACE PROBE 45°, 4.0° LONG. 072°Ø TUBING 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
APNR-3/7L	ABSOLUTE REFLECTION STRAIGHT SURFACE PROBE. 3" LONG. 50KHZ-500KHZ. 0.125IN. (3.17MM) SHAFT SIZE. 7-Pin-LEMO POWERLINK CONNECTOR.	9231663			
AUR156SS/1.75WL	Includes Test Report and Certificate of Conformance. ROTATING SCANNER ROBE 100KH2-2MHZ SHELDED, STAINLESS STEEL SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.75" WORKING LENGTH. USED				
ASPN-91-4.5/2MHZ	WITH ROHMANNN MINI ROTOR156"Ø includes Test Report and Certificate of Conformance HOCKING RIGID SURFACE PROBE, 90° Degrees, .092"Ø(2.34mm) Tip, Absolute Shielded, 1-3MHz, .100" Drop, 4.5" Long with Microdot Connector.	310P14F			
ASPN-91-4.5L/500K	Includes Test Report and Certificate of Conformance. SURFACE PROBE .093" DIAMETER TIP, NFE, ABS, SHIELDED WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ASPN-925-4.5B/2MHZ	RIGID SURFACE PENCIL PROBE 1-3 MHz, .093" TIP DIAMETER. 15" DEGREE CRANK LENGTH .600" FROM TIP .250 DROP . MICRODOT CONNECTOR.	314P24F			
ASPN-9375-4.5/500K	Includes Test Report and Certificate of Conformance. RIGID SURFACE PROBE SHIELDED, 50-500KHz, 90° DEGREES, .092°Ø TIP, .375° TIP LENGTH 4.5° LONG WITH MICRODOT CONNECTOR. Includes Test	309P14F			
ASPN-9375-6/2MHZ	Report and Certificate of Conformance. RIGID SURFACE PROBE SHIELDED, 1-3MHz, 90° DEGREES, .092°Ø TIP, .375° TIP LENGTH 6.0 ° LONG WITH MICRODOT CONNECTOR. Includes Test Report	310P24F			
ASPN-95-5/2MHZ	and Certificate of Conformance. RIGID SURFACE PROBE 90° 1-3MHz, .062"Ø" DIA TUBING, .500" DROP, 5.0" LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate				
ARP-1.4596/500H	of Conformance. LOW FREQUENCY REFLECTION RING PROBE, 1.45"Ø O.D., .960"Ø I.D SUPPLIED WIRTH A TRIAX FISCHER CONNECTOR. FREQUENCY RANGE- 100Hz-1KHz.	RDP-1.45960/500H	RDP-1.4596/500H		
ASPN-95-6	Includes test report and Certificate of Conformance. RIGID SURFACE PROBE 50-500KHZ WITH MICRODOT CONNECTOR, 072"Ø TUBING, 500" DROP 90'ANGLE. Includes Test Report and Certificate of				
ASPN-95-8	Conformance. RIGID SURFACE PROBE 90° 50-500KHz, .093"Ø" DIA TUBING, .500" DROP, 8.0" LONG SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report				
ASPNU-4.5/200K	and Certificate of Conformance. RIGID SURFACE PROBE, STRAIGHT SHAFT, ABS UNSHIELDED, 50-500KHz, CENTER FREQUENCY OF 200KHz.093"Ø, , 4.5" LONG SUPPLIED WITH A	379-010-550			
ASPNU-5/200KHZ	MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance. ABSOLUTE SURFACE PROBE. UNSHIELDED. S" INCHES LONG WITH MICRODOT CONNECTOR .125" TIP. FREQUENCY RANGE 50-500KHZ. Includes Test	379-010-550			
ASTPN-3/350K-3MHZ	Report and Certificate of Conformance. STRAIGHT SURFACE PROBE SS ABS., .093" Ø TUBING 350KHz-3MHz, 3.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	102P3F			
ASTPN-4.5/350K-3M	Conformance. RIGID SURFACE PROBE, ABS. 350KHz-3MHz, . 092"Ø TIP O.D., STRAIGHT 4.5 " LONG WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and				
ASTPN-45-4.5/2M	Certificate of Conformance. RIGID SURFACE PROBE 1-3MHZ, . 092"Ø TIP ,45" DEGREES .500" DROP ,4.5" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	206P24F			
ASTPN-45-5	conformance. SUBRACE PROBE, 50-500KHz.093" TUBING SHEILDED 45" DEGREES, .500" DROP 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and				
ATPN-4/1-6MHZ	Certificate of Conformance. RIGID STRAIGHT SURFACE PROBE 1-6MHz, SHIELDED, 28mm TIP LENGTH, TRIAX FISCHER CONNECTOR, 4.0" LONG. Includes Test Report and Certificate of	MTF-40-1-6M			
ASTPN-45-5/2M	Conformance SURFACE PROBE, 1-3MHz.093" TUBING SHEILDED 45" DEGREES, .500" DROP 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and				
ASTPN-475-6/2-10MHZ	Certificate of Conformance. SUBRACE PROBE SS ABS., 45°, .750° DROP.093° Ø TUBING 2-10MHz 6.0° LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	203P6			
ASTPN-475-6/350K-3MHZ	Conformance. SUBRACE PROBE SS ABS., 45*, .750° DROP .093° Ø TUBING 350KHz-3MHz 6.0° LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate	202P6F			
ASTPN-475-6/50-500KHZ	of Conformance. SURFACE PROBE SS ABS., 45°, .750° DROP093° Ø TUBING SO-S00KHz 6.0° LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	201P6XF			
APN45-6/2M	Contormance. RIGID SURFACE PROBE, 1-3MHZ, CENTER FREQUENCY 2MHz, 45°, .125″ Ø, .500″ DROP, 6.0″ LONG SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	610-057-076			
ASTPN-5	Lest Report and Certificate of Conformance STRAIGHT SURFACE PROBE - 50-500KHZ, .093"Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ASTPN-5/2M	STRAIGHT SURFACE PROBE - 1-3MHz.093"Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ASTPN-6/2-10MHZ	STRAIGHT SURFACE PROBE SS, ABS., .093" Ø TUBING, 2-10MHZ, 6.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	103P6			
ASTPN-6/350K-3MHZ	Conformance. STRAIGHT SURFACE PROBE SS, ABS., .093" Ø TUBING 350KH2-3MHz 6.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	102P6F			
ASTPN-6/50-500KHZ	STRAIGHT SURFACE PROBE SS ABS., .093" Ø TUBING 50-500KHz, 6.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	101P6XF			
	SURFACE PROBE SS ABS., 90°, .250" DROP .093" Ø TUBING 2-10MHz, 3.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	303P23			-

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EOUIVALENT	EQUIVALENT
ASTPN-925-3/350K-3MHZ	SURFACE PROBE SS ABS., 90°, 250" DROP .093" Ø TUBING 350KHZ-3MHZ 3.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate	302P23F	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARRY312375/1.1WL	of Conformance. ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 200KHz-3MHz, 1.1" WORKING LENGTH .312"375" SPREAD Includes Test Report			·	
ASTPN-925-3/50-500KHZ	and Certificate of Conformance SURFACE PROBE SS ABS., 90°.250° DROP.093° Ø TUBING 50-500KHZ 3.0° LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	301P23XF			
ASTPN-95-4.5	Conformance. SURFACE PROBE 50-500KHZ, TRIAX FISCHER .092"TUBING .5 DROP 4.5" LONG. Includes Test Report and Certificate of Conformance.	•			
ASTPN-95-5	RIGID SURFACE PROBE093'Ø TIP 90" DEGREES .500" DROP, TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.				
ASTPN-95-5/2M	RIGID SURFACE PROBE093'Ø TIP 90" DEGREES .500" DROP, TRIAX FISCHER CONNECTOR 1-3MHz. Includes Test Report and Certificate of Conformance.				•
ASTPN-95-6	RIGID SURFACE PROBE 50-500KHZ WITH TRIAX FISCHER CONNECTOR, .093"Ø TUBING, .500" DROP 90"ANGLE. Includes Test Report and Certificate of Conformance	TSPEN95-6			
AURY312343	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH, EXPANDABLE FROM 312"-343". Includes Test Report and Certificate of Conformance.	•			
AURY750812	UNIVERSAL ROTARY "IP" PROBE DOKH2-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .750"812". Includes Test Report and Criticate of Conformance				•
AURY812875	report and certificate or Conformance. UNIVERSAL ROTARY "Y" PROBE 100KH2-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .812"875". Includes Test Report and certificate of Conformance.				
ATBL030-9/500K-2MHZ	BLADE PROBE, 030" THICK, 9.0" LONG, STRAIGHT SHAFT, 500 KHz - 2 MHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATBL045-12	EDDY CURRENT BLADE PROBE, .045 THICK, 12.0" LONG, STRAIGHT SHAFT, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•		•	
ATBL045-6	EDDY CURRENT BLADE PROBE, .045 THICK, 6.0" LONG, STRAIGHT SHAFT, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TBL045-6 or BL045-6	SPC-638BL	MP.045-6BL	
ATBL060-6	EDDY CURRENT BLADE PROBE, .060 THICK, 6.0" LONG, STRAIGHT SHAFT, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	MP.060-60BL	TBL.060-6	BLD-001	TBLFC.060-6
ATBL090-6	BLADE PROBE, .090" THICK, 6.0" LONG, STRAIGHT, 50-500KHZ, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TBL090-6		•	
ATBL445-6	EDDY CURRENT BLADE PROBE, .045" THICK, 45" ANGLE TIP, 6.0" LONG, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TBL445-6			
ATBL945-6	EDDY CURRENT BLADE PROBE, .045" THICK, 90° ANGLE TIP, 6.0" LONG, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TBL945-6			
ATBL-045U-6/2MHZ	EDDY CURRENT BLADE PROBE, UNSHIELDED, .045" THICK, 6.0" LONG, STRAIGHT SHAFT, 1-2MHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•		•	
ATBL09-1.2R-6	BLADE PROBE, .090" THICK, 6.0" WL, 8.5" LONG. 50-500KHz. 1.2 RADIUS. WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TBL09-1.2R-6			
ATBL4560-6	BLADE PROBE, .060" THICK, 6.0" LONG, 1.0" DROP, 45", 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	MP45.060-60BL			
ATBL-4560-7/1-3MHZ	EDDY CURRENT BLADE PROBE, 45° DEGREES,060" THICK, 7.0" LONG, 4.0" WORKING LENGTH, 1-3MHz SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	MP4510-60-70L-1-3M			
ATBL-9030-6	90° BLADE PROBE, .030" THICK, 6.0" LONG, 50-500KHz, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATBL-9060-6	BLADE PROBE, .060" THICK, 6.0" LONG, 90°, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TBL960-6			
ATBLU060-6	EDDY CURRENT BLADE PROBE UNSHIELDED, .060 THICK, 6.0" LONG, STRAIGHT SHAFT, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	BLDU-001			
ATCSM100125	MANUAL COUNTER SINK PROBE 100° DEGREES 50-500KHz WITH TRIAX FISCHER CONNECTOR .125" DIAMETER. Includes Test Report and Certificate of Conformance.	TMC1F.125			
ATCSM100156	MANUAL COUNTER SINK PROBE 100° DEGREES 50-500KHz WITH TRIAX FISCHER CONNECTOR.156°Ø DIAMETER. Includes Test Report and Certificate of Conformance.	TMC1F.156		•	
ATCSM100187	MANUAL COUNTER SINK PROBE 100° DEGREES 50-500KHz WITH TRIAX FISCHER CONNECTOR .187" DIAMETER. Includes Test Report and Certificate of Conformance.	TMC1F.187		•	
ATCSM100250	MANUAL COUNTER SINK PROBE 100° DEGREES 50KHz-500KHz, ABSOLUTE COIL WITH TRIAX FISCHER CONNECTOR.250°Ø. Includes Test Report and Certificate of Conformance.	MCSP-001	TMC1F.250	•	
ATCSM100312	MANUAL COUNTER SINK PROBE 100° DEGREES 50KHz-500KHz, ABSOLUTE COIL WITH TRIAX FISCHER CONNECTOR.312"Ø. Includes Test Report and Certificate of Conformance.	MCSP-002	TMC1F.312		
ATCSM100375	MANUAL COUNTER SINK PROBE 100° DEGREES 50-500KHz WITH TRIAX FISCHER CONNECTOR .375°Ø DIAMETER. Includes Test Report and Certificate of Conformance.	TMC1F.375			
ATMH098	MANUAL BOLT HOLE PROBE, SOLID 2.5mm(.098") DIAMETER WITH 1.1 INCH (27.9mm) WORKING LENGTH, FREQUENCY 50kHz -500kHz, TRIAX FISCHER CONNECTOR, ABSOLUTE COIL CONFIGURATION. Includes Test Report and Certificate of Conformance.				
ATMH.125	Manual hole probe, 0.125 inch (3.1mm) diameter and 1.1 inch (27.9mm) working length, frequency S0kHz -500kHz, triax fischer connector, bridge absolute coil configuration Includes Test Report and Certificate of Conformance.	6100-1/8-S-BNC			
ATMH137	MANUAL BOLT HOLE PROBE, SOLID 3.5mm(.137") DIAMETER WITH 1.1 INCH (27.9mm) WORKING LENGTH, FREQUENCY 50kHz -500kHz, TRIAX FISCHER CONNECTOR, ABSOLUTE COIL CONFIGURATION. Includes Test Report and Certificate of Conformance.				
ATMH.156	Manual hole probe, 0.156 inch (3.9mm) diameter and 1.1 inch (27.9mm) working length, frequency S0kHz -500kHz, triax fischer connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	6200-5/32-BH-BNC			
ATMH.187	Manual hole probe, 0.187 inch (4.7mm) diameter and 1.1 inch (27.9mm) working length, frequency S0kHz -500kHz, triax fischer connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	6200-3/16-BH-BNC			
ATMH187SE-5FX	FLEXIBLE MANUAL BOLT HOLE PROBE, SPLIT END, 50KHZ - 500KHZ. 5 IN. LONG. UNSHIELDED W/ COLLAR, ABS COIL 187250 TRIAX FISCHER CONNECTOR. Includes test report.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATMH.218	Manual hole probe, 0.218 inch (5.5mm) diameter and 1.1 inch (27.9mm) working length, frequency 50kHz -500kHz, triax fischer connector, bridge	6200-3/16-BH-BNC			
ATMH.250	absolute coil configuration. Includes Test Report and Certificate of Conformance. Manual hole probe, 0.250 inch (6.3mm) diameter and 1.1 inch (27.9mm) working length, frequency 50kHz -500kHz, triax fischer connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	6200-1/4-BH-BNC			
ATMH250SE/1.5WL	AUSDICE CON COMINGUAROUT. INCLUDES YES REPORT AND CENTRATE OF COMPONENCE. MANUAL BOLT HOLE PROBE, 250". 281" SPLIT END, 50KHz-500MHz UNSHIELDED W/ COLLAR, ABSOLUTE COIL, TRIAX FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	MBHP-001			
ATMH250SE-5FX	FLEXIBLE MANUAL BOLT HOLE PROBE, SPLIT END, 50KHZ-500KHZ. 5 IN. LONG. UNSHIELDED W/ COLLAR, ABS COIL250312 TRIAX FISCHER CONNECTOR. Includes test report.				
ATMH281SE/1.5WL	MANUAL BOLT HOLE PROBE, .281"312" SPLIT END, 50KHz -500KHz UNSHIELDED W/ COLLAR, ABSOLUTE COIL, TRIAX FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	MBHP-002			
ATMH.312	Manual hole probe, 0.312 inch (7.9mm) diameter and 2.0 inch (5.08cm) working length, frequency 50kHz -500kHz, triax fischer connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	6200-5/16-BH-BNC			
ATMH312SE/2.0WL	MANUAL BOLT HOLE PROBE, .312"375" SPLIT END, 50KHz -500KHz UNSHIELDED W/ COLLAR, ABSOLUTE COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	MBHP-003			
ATMH312SE-5FX	FLEXIBLE MANUAL BOLT HOLE PROBE, SPLIT END, 50KHZ - 500KHZ. 5 IN. LONG. UNSHIELDED W/ COLLAR, ABS COIL312375 TRIAX FISCHER CONNECTOR. Includes test report.	•			
ATMH.500	Manual hole probe, 0.500 inch (12.7mm) diameter and 2.0 inch (5.08cm) working length, frequency 50kHz -500kHz, triax fischer connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	SPO-7188	6200-1/2-BH-BNC		
ATMH.562	Manual hole probe, 0.562 inch (14.27mm) diameter and 2.0 inch (5.08cm) working length, frequency 50kHz -500kHz, triax fischer connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	6200-1/2-BH-BNC			
ATMHD.187	MANUAL BOLT HOLE PROBE DIFFERENTIAL COIL TRIAX FISCHER CONNECTOR 1.0" WORKING LENGTH 200KHZ-1MHZ Includes Test Report and Certificate of Conformance.	9216169,BPMD-12TF			
ATMHF.125/500K	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR .125" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF.125/500K			
ATMHF.156/500K	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR .156" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF.156/500K			
ATMHF.187/500K	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR .187" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF.187/500K			
ATMHF.250	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ TRIAX FISCHER CONNECTOR. 250" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	VM101BS-1/2			
ATMHF.250/500K	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR .250" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF.250/500K	•		
ATMHF.312	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ TRIAX FISCHER CONNECTOR .312" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	6100-5/16-S-BNC			
ATMHF.312/500K	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR. 312" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF.312/500K			
ATMHF.312-8WL	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ TRIAX FISCHER CONNECTOR .312" DIAMETER x 8.0" WORKING LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.				
ATMHF375	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ TRIAX FISCHER CONNECTOR .375" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	BPMF-24			
ATMHF.375/500K	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR .375" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF.375/500K			
ATMHF.437/500K	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR .437" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF.437/500K			
ATMHF.500	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ TRIAX FISCHER CONNECTOR .500" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	VM101BS-1/2			
ATMHF.500/500K	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR .500" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF.500/500K			
AF-4217	LOW FREQUENCY DIFFERENTIAL RING PROBE, 0.330° Ø.D., 0.830° Ø.D., 100Hz - 1KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. Includes Test Report and Certificate of Conformance	SPO-1589	9203307		
ATMHF.500-8WL	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ TRIAX FISCHER CONNECTOR .500" DIAMETER x 8.0" WORKING LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.				
ARR375SS/1.5WL	STAINLESS STEEL ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO, .375" Ø OD, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance	BPRA-24-SS	U8602133		
ARR437SS/1.5WL	STAINLESS STEEL ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO, .437" Ø OD, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance	BPRA-28-SS			
ARR500SS/1.5WL	STAINLESS STEEL ROTARY PROBE FOR RA2000 SCANNER 100KHz-2MHz 4 PIN STEP LEMO, .500°Ø OD, 1.5° WORKING LENGTH. Includes Test Report and Certificate of Conformance	BPRA-32-SS			
AUR-6.9MSS/35MWL	STAINLESS STEEL ROTARY PROBE 100KHz-2MHz. 6.9MM DIA. HEAD 35MM WORKING LENGTH, 4 PIN FISHER CONNECTOR includes Test Report and Certificate of Conformance.	RSM6-9-35			
AUR-7.3MSS/35MWL	STAINLESS STEEL ROTARY PROBE 100KHz-2MHz. 7.3MM DIA. HEAD 35MM WORKING LENGTH, 4 PIN FISHER CONNECTOR includes Test Report and Certificate of Conformance.	RSM7-3-35			
ATPN-5/2M	STRAIGHT SURFACE PROBE - 1-3MHz .125"Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATMHF.562	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ TRIAX FISCHER CONNECTOR .562" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	VM101BS-1/2			
ATMHF.562/500K	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR .562" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF.562/500K			
ATPN-45FX-9/500K	FLEXIBLE SURFACE PROBE, 50-500KHz.125"Ø TUBING, ABS SHEILDED 45° DEGREES, .500" DROP 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPENFLX45-9			
ATMHF.625/500K	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR. 625" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF.625/500K			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATMHE,750	MANUAL BOLT HOLE PROBE FERRITE SHIELDED 50-500KHZ TRIAX FISCHER CONNECTOR .750" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test	VM101BS-1/2		LEGONALINT	LOWALIN
ATMHF.750/500K	Report and Certificate of Conformance. MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR .750" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test	TMHF.750/500K			
ATMHF.875/500K	Report and Certificate of Conformance. MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR. 875" x 2.0" OVERALL LENGTH WITH COLLAR. Includes Test	TMHF.875/500K			
ATMHF1.0/500K	Report and Certificate of Conformance. MANUAL BOLT HOLE PROBE FERRITE SHIELDED 500K-1MHZ TRIAX FISCHER CONNECTOR 1.0" x 3.5" OVERALL LENGTH WITH COLLAR. Includes Test Report and Certificate of Conformance.	TMHF1.0/500K			
AF-5221	REDUCTION AND CENTRATE OF CONTINUMATE. CUSTOM HIGH FREQUENCY EDDY CURRENT PROBE FOR EDGE DEFECT DETECTION FOR THE KC10 ARB SUPPORT FITTING. Includes Test Report and CERTIFICATE of Conformance.				
ATMHS375	MANUAL BOLT HOLE PROBE 50-500KHZ SHIELDED W/ COLLAR, TRIAX FISCHER CONNECTOR. Includes Certificate of Conformance.				
ATMHYD.500-562	MANUAL BOLT-HOLE PROBE EXPANDABLE FROM .500"562"Ø, 2.0" WORKING LENGTH, SHIELDED, TRIAX FISCHER CONNECTOR, 500KH2-1MHz. Includest Test Report and Certificate of Conformance.	SPO-7188	SPO7188		
ATP-10/20-200KHZ	RIGID SURFACE PROBE, ABS/ BRIDGE., 90°. 125° Ø TIP, .030° DROP 10.0° LONG, FLAT TIP, TRIAX FISCHER CONNECTOR, 50-500KHZ. Includes Test Report and Certificate of Conformance.	308P110			
ATP-4.5/20-200KHz	LOW FREQUENCY SURFACE PROBE 20-200khz .187OD, DIFF TRIAX CONN 4.5" LONG. Includes Test Report and Certificate of Conformance.				
ATP-4.5/50-500KHz	LOW FREQUENCY SURFACE PROBE 50-500khz .187OD, DIFF TRIAX CONN 4.5" LONG. Includes Test Report and Certificate of Conformance.				
ATP-4/400K-3MHZ	STRAIGHT SHAFT RIGID SURFACE PROBE, .156"Ø TUBING DIFFERENTIAL SHIELDED, TRIAX FISCHER CONNECTOR 400KHz-3MHz 4.0" LONG. Includes Test Report and Certificate of Conformance. 379-004-360	5P495	379-004-360		
ATP-45-5/1-50KHZ	RIGID SURFACE PROBE 45° DEGREES .500° DROP 5.0° LONG TRIA X FISCHER CONNECTOR, DIFFERENTIAL 1-50KHZ .187" DIA TUBING. Includes Test Report and Certificate of Conformance.				
ATP-5/5KHZ	LOW FREQUENCY STRAIGHT SURFACE PROBE, DIFFERENTIAL, 2-10KHZ, .187"Ø DIAMETER TUBING 5.0" LONG WITH 3.0" WORKING LENGTH. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATP-910-6/1-20KHZ	LOW FREQUENCY SURFACE PROBE 1-20KHz, 90', 1.0" DROP .187"Ø TUBING 6.0" LONG, DIFFERENTIAL WITH TRIAX FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATP-910-8/1-20KHZ	LOW FREQUENCY SURFACE PROBE 1-20KHz, 90°, 1.0" DROP .187"Ø TUBING 8.0" LONG, DIFFERENTIAL WITH TRIAX FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATP-925-6/1-30KHZ	LOW FREQUENCY SURFACE PROBE DIFFERENTIAL, 187"Ø TUBING, 90", .250" DROP, 6.0" LONG 1-30KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	VMD120-04-625/TF/1-30			
ATP-93-5/1-30K	LOW FREQUENCY SURFACE PROBE 90° DEGREES .300° DROP, 5.0° LONG BRIDGE/DIFFERENTIAL, 1-30KHz, TRIAX FISCHER (LEMO) CONNECTOR .187°Ø TUBING. Includes Test Report and Certificate of Conformance.				
ATP-95-5/1-30K	LOW FREQUENCY SURFACE PROBE 90° DEGREES .500° DROP, 5.0° LONG BRIDGE/DIFFERENTIAL, 1-30KHz, TRIAX FISCHER CONNECTOR .187°Ø TUBING. Includes Test Report and Certificate of Conformance.				
ATP-95-5FX/7L	FLEXIBLE SURFACE PROBE 90 DEGREES, .500" DROP 5.0" LONG .190" DIAMETER TUBING 50-500KHZ 7 PIN LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATP-95-6/1-20KHZ	LOW FREQUENCY SURFACE PROBE 1-20KHz, 90", .500" DROP .187"Ø TUBING 6.0" LONG, DIFFERENTIAL WITH TRIAX FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURFB375SE/1.5WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR 1.5" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM 375"437"Ø Includes Test Report and Certificate of Conformance.				
ATPN-5/2MHZ	STRAIGHT SURFACE PROBE - 1-3MHz, .125"Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATPN-5/500K	STRAIGHT SURFACE PROBE - OPERATINGFREQUENCY 500KHZ, .125"Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-3512			
ATPN-5/6MHZ	RIGID STRAIGHT SURFACE PROBE, 5.0" LONG, 1/8"Ø TUBING TRIAX FISCHER CONNECTOR, 6MHz. Includes Test Report and Certificate of Conformance.				
AMHF218	Manual hole probe, ferrite shielded, 0.218 inch (5.5mm) diameter and 1.1 inch (27.9mm) working length, frequency 50kHz -500kHz, microdot connector, bridge absolute coil configuration. Includes Test Report and Certificate of Conformance.	BPMF-14			
AP-350P1A/200K	HOCKING DELRIN 65* ANGLED KNIFE PROBE FOR THREAD INSPECTION, UNSHIELDED, 50-500KHz, 5.0 INCES LONG SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATPN-5FX	FLEXIBLE SURFACE PROBE, TRIAX FISCHER CONNECTOR 5.0" LONG. FREQUENCY 50-500KHz. Includes Test Report and Certificate of Conformance.	MT-50FX/50K-300K			
APN-93-6	RIGID SURFACE PROBE, 50-500KHz ABS SHIELDED, 125" Ø(3.17 mm), 90" DEGREES, 300"(7.62 mm) DROP, 6.0"(152.4 mm) LONG SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	MP10B15-903-60			
ATPN-6	RIGID STRAIGHT SURFACE PROBE, ABS. 50-500KHz, .125"Ø O.D. TIP, 6.0" LONG SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPEN-6, BCMTF-60	6635-01-500-6799		
ATPN-6/1-6M	RIGID STRAIGHT SURFACE PROBE, 6.0" LONG, 1/8"Ø TRIAX FISCHER CONNECTOR, 1-6MHz. Includes Test Report and Certificate of Conformance.	BCMTF-60-1-6M	MTF-60-1-6M		
ATPN-7FX	STRAIGHT SHAFT FLEXIBLE SURFACE PROBE, TRIAX FISCHER CONNECTOR 7.0" LONG. FREQUENCY 50-500KHz. Includes Test Report and Certificate of Conformance.				
ATPN-902-7FX	FLEXIBLE SURFACE PROBE 90 DEG .020" DROP 7.0" LONG 50-500KHZ. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPENFLX902-7			
ATPN-903-10FX	FLEXIBLE SURFACE PROBE, TRIAX FISCHER CONNECTOR .030 DROP 10.0" LONG 50-500KHZ. Includes Test Report and Certificate of Conformance.	TPENFLX903-10	MTF9003-100FX		
ATPN-903-6	RIGID SURFACE PROBE 90", .030" DROP, .125"Ø, 6.0" LONG TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.				
ATPN-903-7FX	FLEXIBLE SURFACE PROBE, .030 DROP 7.0" LONG 50-500KHz WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPENFLX903-7	MTF9003-70FX/50K-300K		
ATPN-903-9.5FX	FLEXIBLE SURFACE PROBE, .030" DROP, BENT 90", 9.5" LONG TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.	MTF9003-95FX			-

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPN-903-9FX	FLEXIBLE SURFACE PROBE, .030" DROP, BENT 90°, 9.0" LONG TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of	MTF9003-90FX	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPN-910-10	Conformance. RIGID SURFACE PROBE, 90° DEGREES .100° DROP, 125°Ø TIP, 10.0 INCHES LONG WITH TRIAX FISCHER CONNECTOR, 50-500KHz. Includes Test Report	TPEN910-10			
ATPN-910-4	and Certificate of Conformance. RIGID SURFACE PROBE, 90° DEGREES .100° DROP, 125°Ø TIP, 4.0 INCHES LONG WITH TRIAX FISCHER CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.	TPEN910-10			
ATPN-910-5FX	Exercise or Conformation. FLEXIBLE SURFACE PROBE, 90° DEGREES,1.0° DROP TRIAX FISCHER CONNECTOR, 5.0° LONG 50-500KHz. Includes Test Report and Certificate of Conformance.	MTF9010-50FX			
ATPN-910-6	RIGID SURFACE PROBE, 50-500KHZ, 90° DEGREES, 1.0° DROP, 6.0° LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPEN9100-6			
ATPN-910-6B	RIGID SURFACE PROBE, 50-500KHZ, 90" DEGREES BENT, 1.0" DROP, 6.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATPN-910-6FX	FLEXIBLE SURFACE PROBE, 90° DEGREES,1.0" DROP TRIAX FISCHER CONNECTOR, 6.0" LONG 50-500KHz. Includes Test Report and Certificate of Conformance.	TPENFLX9100-6	MTF9010-60FX		
ATPN-9125-6B	RIGID SURFACE PROBE125" Ø TIP BENT 90" DEGREES , .125" DROP, TRIAX FISCHER CONNECTOR 50-500KHz, 6.0" LONG. Includes Test Report and Certificate of Conformance.	•			
ATPN-91-3/350K-3MHZ	SURFACE PROBE SS ABS., 90°.100" DROP.125" Ø TUBING 350KHz-3MHz 3.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	302P13			
ATPN-91-8	RIGID SURFACE PROBE125"Ø TIP 90" DEGREES , .100" DROP, TRIAX FISCHER CONNECTOR 50-500KHz, 8.0" LONG. Includes Test Report and Certificate of Conformance.	TPEN91-8			
ATPN-91-8FX	FLEXIBLE SURFACE PROBE, 50-500KHz 90° DEGREES, .100° DROP, 8.0° LONG WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPENFLX91-8/2M			
ATPN-91-8FX/2MHZ	FLEXIBLE SURFACE PROBE,1-3MHz WITH A CENTER FREQUENCY OF 2MHz 90° DEGREES, .100" DROP 8.0" LONG WITH TRIAX FISCHER CONNECTOR 1- 3MHZ. Includes Test Report and Certificate of Conformance.				
ATPN-92-12FX	FLEXIBLE SURFACE PROBE, 90°.200" DROP TRIAX FISCHER CONNECTOR 50KHz-500KHz, 12.0" LONG. Includes Test Report and Certificate of Conformance.	D0815E1015-2103			a
ARP40/.80-5	LOW FREQUENCY REFLECTION RING PROBE .40" I.D80" O.D. TRIAX FISCHER CONNECTOR 100Hz-10KHz Includes Test Report and Certificate of Conformance.	SPO-2131			
ARP-1.1-100H-1	LOW FREQUENCY REFLECTION RING PROBE .530" Ø ID 1.100" Ø OD WITH A TRIAX FISCHER CONNECTOR 50Hz-5KHz. Includes Test Report and Certificate of Conformance.	RDP-1.1-100H-1	RR0111-1		
ATPN-92-12FX/200KHZ-1MHZ	FLEXIBLE SURFACE PROBE, 90°.200" DROP TRIAX FISCHER CONNECTOR 200KHz-1MHz, 12.0" LONG. Includes Test Report and Certificate of Conformance.	•			
ATPN-925-12	RIGID SURFACE PROBE, TRIAX FISCHER CONNECTOR, 50-500KHZ, 12.0" LONG 1/4" DROP. Includes Test Report and Certificate of Conformance.	•			
ATPN-925-3	RIGID SURFACE PROBE, 90° DEGREES .250" DROP 3.0" LONG TRIAX FISCHER CONNECTOR 50-500KHZ. Includes Test Report and Certificate of Conformance.	•			
ATPN-925-4	RIGID SURFACE PROBE, 90° DEGREES .250" DROP 4.0" LONG TRIAX FISCHER CONNECTOR 50-500KHZ. Includes Test Report and Certificate of Conformance.	TPEN925-4			
ATPN-925-4.5	RIGID SURFACE PROBE ABSOLUTE SHIELEDED, 50- 500KHZ 90° DEGREES .250° DROP, 4.5" LONG WITH TRIAX FISCHER CONNECTOR 4.5" LONG. Includes Test Report and Certificate of Conformance.	309P14			
ATPN-925-4.5B/500KHZ	Rigid Surface Probe Absolute Shielded,4.5" long, 90°,300KHz- 1MHz, .250" DROP 15" Degree Crank with Triax Fischer Connector. Includes Test Report and Certificate of Conformance.	PS500PD064-114N			
AURY-5-6M/35MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 35mm WORKING LENGTH. EXPANDABLE FROM 5.0-7.0mmØ. Includes Test Report and Certificate of Conformance.	BYU-5/6M			
AURY-6-8M/51MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 51mm WORKING LENGTH. EXPANDABLE FROM 6.0-8.0mmØ. Includes Test Report and Certificate of Conformance.	BYU-6M/8M			-
AURY-8-10M/51MWL	ADJUSTABLE ROTATING "V" SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 51mm WORKING LENGTH. EXPANDABLE FROM 8.0-10.0mmØ. Includes Test Report and Certificate of Conformance.	BYU-8M/10M			
AURY-10-12M/51MWL	ADJUSTABLE ROTATING "V" SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 51mm WORKING LENGTH. EXPANDABLE FROM 10.0-12.0mmØ. Includes Test Report and Certificate of Conformance.	BYU-10M/12M			
AURY-12-15M/51MWL	ADJUSTABLE ROTATING "V" SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 51mm WORKING LENGTH. EXPANDABLE FROM 12.0-15.0mmø. Includes Test Report and Certificate of Conformance.	BYU-12M/15M			
AURY-15-18M/51MWL	ADJUSTABLE ROTATING "Y" SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 51mm WORKING LENGTH. EXPANDABLE FROM 12.0-15.0mmø. Includes Test Report and Certificate of Conformance.	BYU-15M/18M			-
AURY-18-21M/51MWL	ADJUSTABLE ROTATING "V" SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 51mm WORKING LENGTH. EXPANDABLE FROM 18.0-21.0mmØ. Includes Test Report and Certificate of Conformance.	BYU-18M/21M			
AUR-5MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.197°(S.0mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38°(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPFUF-5.0M/SS			
ATPN-925-4FX	FLEXIBLE SURFACE PROBE, 125" Ø TUBING, TRIAX FISCHER CONNECTOR 50-500KHz, 4.0" LONG 1/4" DROP. IncludesTest Report and Certificate of Conformance.				
ATPN-925-5	RIGID SURFACE PROBE 50-500KHz, 90° DEGREES, .250° DROP 5.0° LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPEN925-5			
AUR-4MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.157" (4.0mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38" (35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPUF4.0M/SS			
ATPN-925-5B	RIGID SURFACE PROBE BENT 50-500KHz, 90° DEGREES, .250" DROP 5.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPEN925-5B			
ATPN-925-5FX	FLEXIBLE SURFACE PROBE 50KHz-500KHz, 90" DEGREES, .250" DROP 5.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPENFLX925-5			
ATPN-925-5FX/200K-1M	FLEXIBLE SURFACE PROBE 200KHz-1MHz, 90° DEGREES, .250° DROP 5.0° LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPENFLX925-5/200K-1M			
ATPN-925-5FX/2MHZ	FLEXIBLE SURFACE PROBE 1-3MHz, 90° DEGREES, .250° DROP 5.0° LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPN-925-6	RIGID SURFACE PROBE, 50-500KHZ, 6.0" LONG .250" DROP, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPEN925-6			
ATPN-925-6/.083	SURFACE PROBE SHIELDED .083" DIA TUBING 90" DEGREES .250" TIP DROP 6.0" LONG, TRIAX FISCHER CONNECTOR 200KHz-2MHz. Includes Test Report and Certificate of Conformance.	VM2085RA-6			
ATPN-925-6/1MHZ	RIGID SURFACE PROBE SHIELDED. 118"Ø(3mm) DIA TUBING 90" DEGREES .250" TIP DROP 6.0" LONG, TRIAX FISCHER CONNECTOR 200KHz-2MHz. Includes Test Report and Certificate of Conformance.				
ATPN-925-6B30	SURFACE PROBE 90° DEGREES, .250° DROP (BENT 30° 1.0° FROM THE TIP),6.0° LONG, 50-500KHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. D0815E1015E-2077	RMTF902-25-60B	D0815E1015-2077		
ATPN-925-6FX	FLEXIBLE SURFACE PROBE, 125" Ø, .250" DROP, 50-500KHz, 6.0" LONG SUPPLIED WITH A TRIAX FISCHER CONNECTOR. IncludesTest Report and Certificate of Conformance.	TPENFLX925-6			
ATPN-925-8FX	FLEXIBLE COPPER SURFACE PROBE, TRIAX FISCHER/LEMO CONNECTOR 50-500KHZ, 8.0" LONG 1/4" DROP. Includes Test Report and Certificate of Conformance.	TPENFLX92-8			
ATPN-925-8FX/2M	FLEXIBLE SURFACE PROBE, TRIAX FISCHER/LEMO CONNECTOR 1-3MHz, 8.0" LONG 1/4" DROP. Includes Test Report and Certificate of Conformance.	TPENFLX925-8/2M			
ATPN92-5B	RIGID SURFACE PROBE 50-500KHz 90° DEGREES .200° DROP, 5.0° LONG ,BENT, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	MTF902-50B			
ATPN-92-5B	RIGID SURFACE PROBE, TRIAX FISCHER CONNECTOR 50-500KHZ, 90° DEGREES, 200 DROP BENT,5.0" LONG. Includes test report and Certificate of Conformance.	TPEN92-5B			
ATPN-92-6/1MHZ	RIGIDE SURFACE PROBE, 90°, .118Ø TUBING, .200° DROP, TRIAX FISCHER CONNECTOR 200KHz-1MHZ, 6.0° LONG. Includes Test Report and Certificate of Conformance.				
ATPN-92-6/200KHZ	RIGID SURFACE PROBE, 90°.200" DROP TRIAX FISCHER CONNECTOR 200KHz - 1MHz, 6.0" LONG. Includes Test Report and Certificate of Conformance.	MTF902-60-200K-1M			
ATPN-92-7FX/2MHZ	FLEXIBLE SURFACE PROBE 90 DEG .200" DROP 7.0" LONG 1-3MHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPENFLX92-7/2M			
ATPN-92-8FX	FLEXIBLE SURFACE PROBE, 90° DEGREES .200" DROP TRIAX FISCHER CONNECTOR 50-500KHZ 8.0" LONG. Includes test report and Certificate of Conformance.	TPENFLX 92-8 50-500KHZ			
ATPN-92-9	RIGID SURFACE PROBE 90° DEGREES, .200° DROP, 125°Ø O.D. TIP 9.0° LONG, TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.				
ATPN-92-9FX	FLEXIBLE SURFACE PROBE 90° DEGREES, .200" DROP 9.0" LONG 50-500KHz WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATPN-93-5B/2MHZ	RIGID SURFACE PROBE, 90°. 300" DROP, TRIAX FISCHER CONNECTOR, 1-3MHZ ,BENT 30°, 5.0" LONG. Includes Test Report and Certificate of Conformance.				
ATPN-93-6	RIGID SURFACE PROBE, SHIELDED 90° DEGREES, .125" # TUBING, .300" DROP 6.0" LONG 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATPN-93-6/2MHZ	PENCIL PROBE, SHIELDED 90 DEGREES WITH .300" DROP 6.0" LONG 1-3MHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	9216203	P/1MHZ-2MHZ/A/90.03/6		
ATPN-93-6FX	FLEXIBLE SURFACE PROBE 90DEG .300" DROP 6.0" INCH LONG 50-500KHZHZ , TRIAX FISCHER CONNECTOR				
ATPN-95/.058-4	Note: used ( STEEL FE REFERENCE BLOCK)				
ATPN-95-10	RIGID SURFACE PROBE 50-500KHZ, 90°.500° DROP, .125°Ø TUBING, 10.0° LONG WITH TRIAX FISCHER/LEMO QUICK DISCONNECT CONNECTOR Includes Test Report and Certificate of Conformance.				
ATPN-95-10FX	FLEXIBLE SURFACE PROBE 50-500KHZ, 90".500" DROP, TRIAX FISCHER CONNECTOR 10.0 " LONG. Includes Test Report and Certificate of Conformance.	MTF905-100FX			
ATPN-95-10FX/2MHZ	SURFACE PROBE , TRIAX, 1-3MHZ				
ATPN-95-12FX/200KHZ-1MHZ	FLEXIBLE SURFACE PROBE, 90° .500° DROP, TRIAX FISCHER CONNECTOR 200KHz-1MHz, 12.0° LONG. Includes Test Report and Certificate of Conformance.				
ATPN-95-3	SURFACE PROBE, TRIAX 50-500KHZ	MTF905-30	PAB305		
ATPN-95-3B	SURFACE PROBE, TRIAX FISCHER, 50-500KHZ, BENT	MTF905-30B			
ATPN-95-4	SURFACE PROBE 90" DEGREES SHEILED, .500" DROP, TRIAX FISCHER CONNECTOR 50-500KHZ 4.0" LONG .125"OD TIP. Includes Test Report and Certificate of Conformance.	VM202RAF-6	VM202RAF-6	PAB90405	TPEN95-4
ATPN-95-4/2MHZ	SURFACE PROBE, TRIAX 1-3MHZ				
ATPN-95-5	RIGID SURFACE PROBE 50-500KHz, .125" Ø TIP, 90° DEGREES, .500° DROP, 5.0° LONG TRIAX FISCHER CONNECTOR 50-500KHz IncludesTest Report and Certificate of Conformance.	MTF905-50	BCMTF905-50	DPT90-002	
ATPN-95-5/1-6M	RIGID SURFACE PROBE 90° DEGREES, .500° DROP, 5.0° LONG, 1/8°Ø TUBING TRIAX FISCHER CONNECTOR, 1-6MHz. Includes Test Report and Certificate of Conformance.	BCMTF-905-50-1-6M	MTF-905-50-1-6M		
ATPN-95-5/2M	RIGID SURFACE PROBE125'Ø TIP 90° DEGREES .500° DROP, TRIAX FISCHER CONNECTOR 1-3MHz. Includes Test Report and Certificate of Conformance.		DPT90-011		
ATPN-95-5/2MHZ	RIGID SURFACE PROBE125'Ø TIP 90° DEGREES .500° DROP, TRIAX FISCHER CONNECTOR 1-3MHz. Includes Test Report and Certificate of Conformance.				
ATPN-95-5/500K-1M	RIGID SURFACE PROBE 50-500KHz, 1:25"Ø TIP, 90° DEGREES, 500° DROP, 5.0" LONG TRIAX FISCHER CONNECTOR 500KHz-1MHz. IncludesTest Report and Certificate of Conformance.	DPT90-004			
AURX-1.725-1.825	ADJUSTABLE ROTARY X-PROBE 1.725"-1.825" 100KHz-2MHz 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AURX-1.460-1.560	ADJUSTABLE ROTARY X-PROBE 1.460"-1.560" 100KHz-2MHz 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AFW-45T/29R	45" IN TITANIUM LUCITE (PLEXIGLASS) WEDGE, 3/8-32 THREAD WITH A 29mm RADIUS USED WITH A .25"Ø DIAMETER TRANSDUCER WITH A 3/8-32 THREAD. Includes Certificate of Conformance. Reference part number AMS2630C.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFW-45T/22R	45° IN TITANIUM LUCITE (PLEXIGLASS) WEDGE, 3/8-32 THREAD WITH A 22mm RADIUS USED WITH A .25"Ø DIAMETER TRANSDUCER WITH A 3/8-32	EQUIVALENT	EQONALENT	EQUIVALENT	EQUIVALENT
ATPN-95-5/5-50KHz	THREAD. Includes Certificate of Conformance. Reference part number AMS2630C. RIGID SURFACE PROBE 5-50KHz, .125"Ø TIP, 90" DEGREES, .500" DROP, 5.0" LONG TRIAX FISCHER CONNECTOR. IncludesTest Report and Certificate of	DPT90-007	:		
ATPN-95-5B	Conformance. RIGID SURFACE PROBE, 90° .500° DROP, TRIAX FISCHER CONNECTOR. 50-500KHz. BENT 30°, 5.0° LONG includes test report and Certificate of conformance.	TPEN95-5B	DPT9030-001		
ATPN-95-5B/2MHZ	Conformance. RIGID SURFACE PROBE, 90°.500° DROP, TRIAX FISCHER CONNECTOR, 1-3MHZ,BENT 30°, 5.0° LONG. Includes Test Report and Certificate of Conformance.	TPEN-95-5/2M	DPT9030-002		
ATPN-95-5C/.083	CONFININCE. SUFACE PROBE 90° DEGREES, .500° DROP CURVED .083" TIP 5.0° LONG 50-S00KHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PABM906509C/.083			
ATPN-94-6B/300K	RIGID SURFACE PROBE ABSOLUTE SHIELDED, 90° DEGREES, .400° DROP, 6.0° LONG, BENT WITH A SINGLE PIN TRIAX FISCHER CONNECTOR, 30KHz- 300KHz, Includes Test Report and Certificate of Conformance.	PKA33H121-02-1			
AF-4008/4F	LOW FREQUENCY PROBE ABSOLUTE REFLECTION, SHIELDED, 2-20KHz, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. Reference: 51-10-16-pb6	PKA27H1359	PKA-27 H-1359	PKA-27H1359	PKA-27 H-1359
AF-6017	SLIDING PROBE, REFLECTION, 100Hz-40KHz, WITH 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformation.	PKA4H34-03-01			
ATPN-95-5FX	FLEXIBLE SURFACE PROBE 50-500KHz, .125"Ø TIP, 90" DEGREES, .500" DROP, 5.0" LONG TRIAX FISCHER CONNECTOR 50-500KHz IncludesTest Report and Certificate of Conformance.	MTF905-50FX	MTF905-50FX	TPEN95-5FX 50-500K	
ATPN-95-6	RIGID SURFACE PROBE ABS 90" DEGREES, S00" DROP, .125" Ø O.D. TIP, 6.0" LONG TRIAX FISCHER CONNECTOR 50-S00KHz. Includes Test Report and Certificate of Conformance.	MTF905-60	PAB90605, BCMTF905-60	9216222, MTF905-60	DPT90-010
ATPN-95-6/1-6M	RIGID SURFACE PROBE 90° DEGREES, .500° DROP, 6.0° LONG, 1/8°Ø TUBING TRIAX FISCHER CONNECTOR, 1-6MHz. Includes Test Report and Certificate of Conformance.	BCMTF-905-60-1-6M	MTF-905-60-1-6M		
ATPN-95-6B	RIGID SURFACE PROBE, TRIAX FISCHER CONNECTOR 50-500KHZ, 90° DEGREES, .500° DROP BENT, 6.0° LONG. Includes test report and Certificate of Conformance.	MTF905-60B	TPEN95-6B	MTF905-60B	
ATPN-95-6FX/2MHZ	FLEXIBLE SURFACE PROBE, 90° DEGREES, WITH A CENTER FREQUENCY OF 2MHz, .500° DROP 6.0° LONG TRIAX FISCHER CONNECTOR 1-3MHZ. Includes Test Report and Certification of Conformance.	•			
ATPN-95-7	RIGID SURFACE PROBE 90° DEGREES , .500° DROP, TRIAX FISCHER CONNECTOR 50-500KHZ 7.0° LONG 4.5° SHAFT LENGTH .125°OD TIP. Includes Test Report and Certificate of Conformance.	•			
ATPN-95-7FX	FLEXIBLE SURFACE PROBE 90° DEGREES , .500° DROP, TRIAX FISCHER CONNECTOR 50-500KHZ 7.0° LONG 4.5" SHAFT LENGTH .125" OD TIP. Includes Test Report and Certificate of Conformance.	•			
ATPN-95-8	RIGID SURFACE PROBE ABS 90° DEGREES, .500° DROP, .125"Ø O.D. TIP, 8.0° LONG TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.	•			
ATPN-95-9FX	FLEXIBLE SURFACE PROBE 90" DEGREES, .500" DROP, .125" TIP TRIAX FISCHER CONNECTOR, 50-500KHZ, 9.0" LONG. Includes Test Report and Certificate of Conformance.	TPENFLX95-9			
ATPN-96-6	RIGID SURFACE PROBE, TRIAX FISCHER CONNECTOR 50-500KHZ 90°.600° DROP 6.0° LONG. Includes test report and Certificate of Conformance.	TPEN96-6	VM202RAF-1/8-6	9216222	
ATPN-97-4	RIGID SURFACE PROBE 90° DEGREES, .700° DROP, .125°Ø TIP TRIAX FISCHER CONNECTOR, 50-500KHZ, 4.0° LONG. Includes Test Report and Certificate of Conformance.	TPEN97-4			
ATPN-975-4	SURFACE PROBE 90" DEGREES, .750" DROP, 4.0" LONG. 50-500 KHz, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. IncludesTest Report and Certificate of Conformance	TPEN975-4			
ATPN-975-4C	SURFACE PROBE 90" DEGREES, .750" DROP, CURVED 4.0" LONG. 50-500 KHz, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. IncludesTest Report and Certificate of Conformance	TPEN975-4C			
ATPN-975-7	SURFACE PROBE 90" DEGREES, .750" DROP, 7.0" LONG. 50-500 KHz, SUPPLIED WITH A TRIAX FISCHER CONNECTOR. IncludesTest Report and Certificate of Conformance	•			
ATPN-97-5FX	FLEXIBLE SURFACE PROBE 90° DEGREES, .700" DROP, .125" TIP TRIAX FISCHER CONNECTOR, 50-S00KHZ, 5.0" LONG. Includes Test Report and Certificate of Conformance.	TPENFLX97-5			
ATPN-9FX	FLEXIBLE STRAIGHT SURFACE PROBE, .125" [# TRIAX FISCHER CONNECTOR, 50-500KHZ, 9.0" LONG. Includes Test Report and Certificate of Conformance.	TPENFLX-9			
ATPNU-3	UNSHIELDED RIGID STRAIGHT SURFACE PROBE, 3.0" LONG, 1/8"Ø TRIAX FISCHER CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.	VM200-3			
ATPNU-4	RIGID STRAIGHT SURFACE PROBE 50-500KHz, UNSHIELDED, TRIAX FISCHER CONNECTOR, 4.0" LONG. Includes Test Report and Certificates.	UMTF-40	UMTF-40		
ATPNU-4/500KHZ	RIGID STRAIGHT SURFACE PROBE 50-300KHz-1MHz, UNSHIELDED, TRIAX FISCHER CONNECTOR, 4.0" LONG. Includes Test Report and Certificates.	PU500PSFE/NFE			
ATPNU-5	STRAIGHT RIGID SURFACE PROBE 50-500KHZ TRIAX FISCHER CONNECTOR UNSHIELDED. Includes Test Report and Certificates.	UMTF-50	D0815E1015-2027		
ATPNU-5/1-6M	UNSHIELDED RIGID STRAIGHT SURFACE PROBE, .125" Ø O.D. TIP, 5.0" LONG TRIAX FISCHER CONNECTOR 1-6MHz includesTest Report and Certificate of Conformance. UMTF-50-1-6M	UMTF-50-1-6M	D0815E1015-2055		
ATPNU-903-6FX	UNSHIELDED FLEXIBLE SURFACE PROBE 90° DEGREES, .030° DROP, .125°Ø O.D. TIP, 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHz includesTest Report and Certificate of Conformance.	UMTF9003-60FX	D0815E1015-2031		
ATPNU-95-5	UNSHIELDED RIGID SURFACE PROBE 90° DEGREES, .500° DROP, .125" Ø O.D. TIP, 5.0" LONG TRIAX FISCHER CONNECTOR 50-500KHz IncludesTest Report and Certificate of Conformance.	UMTF905-50	D0815E1015-2029		
ATPNU-95-5/1-3MHZ	UNSHIELDED RIGID SURFACE PROBE 90° DEGREES, .500° DROP, .125" Ø O.D. TIP, 5.0° LONG TRIAX FISCHER CONNECTOR 1-3MHz IncludesTest Report and Certificate of Conformance.				
ATPNU-95-5/1-6M	UNSHIELDED RIGID SURFACE PROBE 90° DEGREES, .500° DROP, .125"Ø O.D. TIP, 5.0° LONG TRIAX FISCHER CONNECTOR 1-6MHz IncludesTest Report and Certificate of Conformance. UMTF905-50-1-6M	UMTF905-50-1-6M	D0815E1015-2057		
ATPNU-95-5/2M	SURFACE PROBE 90", .500" DROP UNSHIELDED, TRIAX FISCHER CONNECTOR, 1-3MHZ. 5.0" LONG. Includes test report and certificate of conformance.				
ATPN-5/200K	STRAIGHT SURFACE PROBE - 50-500KHZ, WITH A CENTER FREQUENCY OF 200KHz, .125*Ø, 5.0° LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATPN-93-5B	PENCIL PROBE, SHIELDED, BENT 90° DEGREES WITH . 300" DROP. 50-500KHz TRIAX FISCHER CONNECTOR, 5.0" LONG. Includes Test Report and Certificate of Conformance.	TPEN930-5B			-

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ATPN-93-6B	PENCIL PROBE, SHIELDED, BENT 90° DEGREES WITH .300° DROP. 50-500KHz TRIAX FISCHER CONNECTOR, 6.0° LONG. Includes Test Report and	FPNS94-5B	EQUIVALENT	EQONALLINT	EQONALENT
	Certificate of Conformance. RIGID SURFACE PROBE, 90° DEGREES, WITH A CENTER FREQUENCY OF 2MHz, SHIELDED, 500° DROP 6.0° LONG TRIAX FISCHER CONNECTOR 1-3MHZ.		DDT00 044		
ATPN-95-6/2MHZ	Includes Test Report and Certification of Conformance. RIGID SURFACE PROBE, 90° 1-3MHz, BENT 45°, .500° DROP, 6.0° LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of	TPEN95-6/2M	DPT90-011	MFT905-60/2M	
ATPN-95-6B45/2M	Conformance. Eddy Current Surface Probe 90° degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long, 1-6MHz with Triax Fischer Connector. Includes Test			•	
ATPN-95-6C/2M	Report and Certificate of Conformance.	9403412	•	•	
ATPN-903-12FX	FLEXIBLE SURFACE PROBE, STRAIGHT, TRIAX FISCHER CONNECTOR .030 DROP(SIDE COIL) 12.0" LONG 50-500KHz. Includes Test Report and Certificate of Conformance.				
ATPN-12	STRAIGHT SHAFT RIGID SURFACE PROBE, TRIAX FISCHER CONNECTOR 50-500KHz 12.0" LONG. Includes Test Report and Certificate of Conformance.	TPEN-12		•	
ATPN-453-3	ABSOLUTE BRIDGE ANGLE SHAFT. 3.0" LONG. 45 DEG. TIP. 0.3IN. (7.62MM) DROP. 50KHZ-500KHZ. 0.125IN. (3.17MM) SHAFT SIZE. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	mtf453-30			
ATPN45-9FX/500K	FLEXIBLE SURFACE PROBE 45 DEGREES .500" DROP, .130" DIA. TRIAX FISCHER CONNECTOR, 50-500KHZ, 9.0" LONG. Includes Test Report and Certificate of Conformance			•	
ATPN-5/15KHZ	STRAIGHT LOW FREQUENCY SURFACE PROBE - 15KHz, .125"Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	DPT-005			
ATPN-8	STRAIGHT SURFACE PROBE - 50-500KHZ,125"Ø, 8.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	MTF-80			
ATPN-903-5FX	FLEXIBLE SURFACE PROBE, .030" DROP 5.0" LONG TRIAX FISCHER CONNECTOR 50KHz - 500KHz. Includes Test Report and Certificate of Conformance.	MTF9003-50FX			
ATPN-913-4.5	STAINLESS STEEL SURFACE PROBE 90° DEGREES, .130° DROP, DIFFERENTIAL FERRITE SHIELDED, 4.5" LONG, 50-500KHz. Includes Test Report and Certificate of Conformance. REFERENCE: US-3375	D0815E1015-2109	US-3375		
ATPN-91-7.5	RIGID SUFACE PROBE 90" DEGREES, 0.100" DROP, 5.0" SHAFT LENGTH 7.5" TOTAL LENGTH WITH TRIAX FISCHER CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.				
ATPN92-10FX	FLEXIBLE SURFACE PROBE 50-500KHZ, 90° DEGREES TRIAX FISCHER CONNECTOR, .200° DROP, 10.0° LONG. Includes Test Report and Certificate of Conformance				
ATPN-925-10FX	FLEXIBLE SURFACE PROBE, 125" Ø TUBING, TRIAX FISCHER CONNECTOR 50-500KHz, 10.0" LONG 1/4" DROP. IncludesTest Report and Certificate of Conformance.	TPENFLX925-10			
ATPN-925-4.5B/2M	Rigid Surface Probe Absolute Shielded, 4.5" long, 90°,1-3MHz, .250" DROP 15" Degree Crank with Triax Fischer Connector. Includes Test Report and Certificate of Conformance.	PS002PD064-114N			
ATPN-925-6B	RIGID SURFACE PROBE ABSOLUTE SHIELDED 50-500KHz, 90°, .250° DROP BENT 30° 2.0° FROM THE TIP,6.0 " LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	VM2529-1/4x6	MTF9025-60B, TPEN925- 6B	VM2529-1/4x6	
ATPN-92-9/1-6MHZ	RIGID SURFACE PROBE 90° DEGREES, 200° DROP, 125° Ø O.D. TIP 9.0° LONG, TRIAX FISCHER CONNECTOR 1-6MHzIncludes Test Report and Certificate of Conformance.	MTF902-90			
ATPN-93-4.5	RIGID SURFACE PROBE, SHIELDED 90° DEGREES, 125"Ø TUBING, 300" DROP 4.5" LONG 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	MTF903-45			
ATPN-93-6B/2M	PENCIL PROBE, SHIELDED, BENT 90° DEGREES WITH .300° DROP. 1-3MHz, OPERATING FREQUENCY 2MHz. SUPPLIED WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATPN-93-6B/500K-1M	PENCIL PROBE, SHIELDED, BENT 90° DEGREES WITH .300° DROP. 500KHz-11MHz, OPERATING FREQUENCY 2MHz. SUPPLIED WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATPN-95-6C/1M	Eddy Current Surface Probe 90° degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long, 1MHz with Triax Fischer Connector. Includes Test Report and Certificate of Conformance.	9230071			
ATPN-95-8FX	FLEXIBLE SURFACE PROBE 90 DEGREES .500" DROP. TRIAX FISCHER CONNECTOR, 50-500KHZ, 8.0" LONG. Includes Test Report and Certificate of Conformance.	PAB2502RAFX-1/2X-8			
ATPN-97-9FX/1MHZ	FLEXIBLE SURFACE PROBE 90° DEGREES, .700° DROP, .125°Ø TIP TRIAX FISCHER CONNECTOR, 200KHz-2MHz, 9.0° LONG. Includes Test Report and Certificate of Conformance. GET: 076-102-017	815P238	076-102-017		
ATPN-9FX/1MHZ	FLEXIBLE STRAIGHT COPPER SHAFT SURFACE PROBE, 125"Ø TIP, TRIAX FISCHER CONNECTOR, 200KHz-1MHz, 9.0" LONG. Includes Test Report and Certificate of Conformance. GEIT: 076-102-009	106P9C	076-102-009		
ATPND-6	RIGID STRAIGHT SURFACE PROBE, DIFF / BRIDGE. 50-500KHz, .125"Ø O.D. TIP, 6.0" LONG SUPPLIED WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
ATPND-95-4.5	RIGID SURFACE PROBE DIFF / BRIDGE 90° DEGREES, 500° DROP, .125°Ø O.D. TIP, 4.5° LONG TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.				
ATPND-95-6	RIGID SURFACE PROBE DIFF / BRIDGE 90° DEGREES, .500° DROP, .125°Ø O.D. TIP, 6.0° LONG TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.				
ATPNU-125-6CFX	Unshielded Surface Probe120 degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long 50-500 kHz TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
ATPNU-45-3FX	FLEXIBLE SURFACE PROBE, TRIAX 50-500 KHZ, UNSHIELDED. Includes Test Report and Certificates.				
ATPNU-95-5/2MHZ	UNSHIELDED RIGID SURFACE PROBE 90° DEGREES, .500° DROP, .125°Ø O.D. TIP, 5.0° LONG TRIAX FISCHER CONNECTOR 1-3MHz includesTest Report and Certificate of Conformance.				
AURFX250SE75T/6WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHz-2MHz, 1/4"(.250")Ø EXPANDABLE TO 5/16"(.312") Ø SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 6.0" WORKING LENGTH WITH A . 75" LONG TIP LENGTH SPLIT END. Includes Test Report and Certificate of Conformance.				
ATPNU-975-6/2M	UNSHIELDED RIGID SURFACE PROBE 90" DEGREES, 750" DROP, 125" O.D. TIP, 6.0" LONG, TRIAX FISCHER CONNECTOR. 1-3MHz IncludesTest Report and Certificate of Conformance.	TPENU975-6/2M			
ATPN-95-6C	Eddy Current Surface Probe 90° degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long, 50-500 kHz with Triax Fischer Connector. Includes Test Report and Certificate of conformance.	9222164	VM202A-6	9222164	
ATPN-45FX-4/500K	FLEXIBLE SURFACE PROBE, 45° DEGREES, .125° Ø TUBING, 4.0° LONG TRIAX FISCHER CONNECTOR. FREQUENCY: 500KHz-1MHz IncludesTest Report and Certificate of Conformance.	•			
ATPN-64-14FX	FLEXIBLE SURFACE PROBE, 60°.400" DROP SUPPLIED WITH A TRIAX FISCHER CONNECTOR 50-500KHz, 14.0" LONG. Includes Test Report and Certificate of Conformance.	MP604-140FX			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFX312SE75T/6WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHz-2MHz, 5/16"(.312")Ø EXPANDABLE TO 3/8"(.375")Ø SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 6.0"				
ATPN-903-4.5FX	WORKING LENGTH WITH A .75" LONG TIP LENGTH SPLIT END. Includes Test Report and Certificate of Conformance. FLEXIBLE COPPER SHAFT. TRIAX FISCHER PENCL PROBE. 90 DEG. 4.5" LENGTH. 0.30" DROP, 50-500KHZ. Includes Test Report and Certificate of Conformance.	PABM904503FX	MTF9003-45FX		
ATPN-925-5/2MHZ	RIGID SURFACE PROBE 1-3MHz, 90" DEGREES, 250" DROP 5.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPEN925-5/2M			
ATPN-92-5B/2MHZ	RIGID SURFACE PROBE, TRIAX FISCHER CONNECTOR 1-3 MHZ, 90" DEGREES, .200 DROP BENT, 5.0" LONG. Includes test report and Certificate of Conformance. BENT	MTF902-50B/2M			
ATPN-95-12FX	FLEXIBLE SURFACE PROBE 50-500KHz, .125" Ø TIP, 90° DEGREES, .500" DROP, 12.0" LONG TRIAX FISCHER CONNECTOR 50-500KHz IncludesTest Report and Certificate of Conformance.				
ARR-1.200SE/2.0WL	Universal Rotary Hole Probe 1.200 inch (30.48 mm) to 1.262 inch (32.05 mm) diameter, Self Expanding 2 inch (50 mm) working length, Operating frequency 100 kHz - 2MHz 4-pin step lemo connector, RA SCANNER reflection differential coil configuration (1.250-1.312) Includes Test Report and				
ATPN-95-5FX/7L	FLEXIBLE SURFACE PROBE 90 DEGREES .500" DROP 5.0" LONG 7 PIN LEMO CONNECTOR 50-S00KHZ. Includes Test Report and Certificate of Conformance.			•	
ATPN-95-6/30KHZ	RIGID SURFACE PROBE, 90" DEGREES, .500" DROP, FREQUENCY 30KHZ,,125" TIP DIAMETER, SHIELDED, 6.0" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certification of Conformance.	PS030PR064-114N			
ATPNR-92-8FX	ABSOLUTE /REFLECTION COPPER FLEXIBLE SURFACE PROBE SHIELDED 90° DEGREES, 200° DROP 8.0° LONG TRIAX FISCHER CONNECTOR 1-SOKHz. Includes Test Report and Certificate of Conformance.	,	,	,	
ATPN-95-6CFX	Eddy Current Flexible Surface Probe 90 degrees, 0.500 inch (12.70 mm) drop curve, 6.0 inch (152 mm)long, 50-500 kHz with Triax Fischer Connector. Includes Test Report and Certificate of Conformance	•			
ATPN-903-16FX	FLEXIBLE SURFACE PROBE, .030" DROP TRIAX FISCHER CONNECTOR, 50-500KHZ, 16" INCHES LONG. Includes Test Report and Certificate of Conformance.	9231258			
ATPN-45-4/.050/2M	SURFACE PROBE 45" .500" DROP, .050" TIP DIAMETER, 1-3MHZ, 4.0" LONG. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TX5PEN45-4/2M		•	
ATPN-92-6B/.065	RIGID PENCIL PROBE.065" TIP 90", .200" DROP 6.0" LONG 15" BENT WITH TRIAX CONNECTOR 50-500KHZ. Includes Test Report ancd Certificate of Conformance50-500KHZ	PABM90C3602/.065	PABM90C3602/.065		
ATPN-95-4/1K	SURFACE LF PROBE 1-5KHZ, 90 DEG .5' DROP .187" OD TUBING 4.0" LONG DIFFERENTIAL, TRIAX FISCHER CONNECTOR	TPN95-41/1K		•	
AUR390SE/2.0WL	UNIVERSAL ROTARY PROBE, SPLIT END, 390" Ø, 2.0 " WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR 100KHz -2MHz. Includes Test Report and Certificate of Conformance.			•	
ATPN-94-6B/300K	RIGID SURFACE PROBE ABSOLUTE SHIELDED, 90° DEGREES, 400° DROP, 6.0° LONG, BENT WITH A SINGLE PIN TRIAX FISCHER CONNECTOR, 30KHz- 300KHz. Includes Test Report and Certificate of Conformance.	PKA33H121-02-1		•	
APN-4.5/20-200K	RIGID STRAIGHT SURFACE PROBE,ABS,SHIELDED,TRIAX FISCHER CONNECTOR 4.5" LONG 20-200KHZ 4.5"LONG, 20-200KHZ, Fe/NFe, L=114mm(4.5""), Tip 3.30mm(.129"Ø) WITH TRIAX FISCHER CONNECTOR . 187"Ø TUBING. Includes Test Report and Certificate of Conformance.	104P4F			
AXTPN-9FX/500K	STRAIGHT FLEXIBLE SHAFT SURFACE PROBE .072" & TUBING TRIAX FISCHER CONNECTOR 9.0" LONG 500KHz. Includes Test Report and Certificate of Conformance.	TPENFLX-9/500K			
ATPN-902-12FX	FLEXIBLE SURFACE PROBE, STRAIGHT, TRIAX FISCHER CONNECTOR. 020 DROP(SIDE COIL) 12.0" LONG 50-500KHz. Includes Test Report and Certificate of Conformance.				
AF-5220156/.5T-3.5WL	FLEXIBLE SHAFT ROTARY PROBE, SPLIT END, 100KHz-2MHz. EXPANDABLE FROM. 156"187", 500" LONG TIP, 3.5" WORKING LENGTH (NO SLEEVE). SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AF-5300125SE/1T-6L	FLEXIBLE SHAFT WITH SPRING ROTARY PROBE, SPLIT END,100KHz-2MHz. EXPANDABLE FROM .125"Ø~.156"Ø, 1.0" LONG TIP, 6.0" LONG. SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AF-5300156SE/1T-6L	FLEXIBLE SHAFT WITH SPRING ROTARY PROBE, SPLIT END,100KHz-2MHz. EXPANDABLE FROM .156"Ø187"Ø, 1.0" LONG TIP, 6.0" LONG. SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AF-5300187SE/1T-6L	FLEXIBLE SHAFT WITH SPRING ROTARY PROBE, SPLIT END,100KHz-2MHz. EXPANDABLE FROM .187"Ø250"Ø, 1.0" LONG TIP, 6.0" LONG. SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AF-5300250SE/1T-6L	FLEXIBLE SHAFT WITH SPRING ROTARY PROBE, SPLIT END,100KHz-2MHz. EXPANDABLE FROM. 250°Ø312°Ø, 1.0° LONG TIP, 6.0° LONG. SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AF-5300312SE/1T-6L	FLEXIBLE SHAFT WITH SPRING ROTARY PROBE, SPLIT END,100KHz-2MHz. EXPANDABLE FROM. 312"Ø375"Ø, 1.0" LONG TIP, 6.0" LONG. SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AF-5300375SE/1T-6L	FLEXIBLE SHAFT WITH SPRING ROTARY PROBE, SPLIT END,100KHz-2MHz. EXPANDABLE FROM. 375"Ø437"Ø, 1.0" LONG TIP, 6.0" LONG. SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AF-5300437SE/1T-6L	FLEXIBLE SHAFT WITH SPRING ROTARY PROBE, SPLIT END,100KHz-2MHz. EXPANDABLE FROM .437"Ø500"Ø, 1.0" LONG TIP, 6.0" LONG. SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURYFBU125156	UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM .125"156"Ø Includes Test Report and Certificate of Conformance.	URYFBU.125156		•	
AURYFBU156187	UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM .156"187"Ø Includes Test Report and Certificate of Conformance.	URYFBU.156187			
AURYFBU187250	UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM .187"250"Ø Includes Test Report and Certificate of Conformance.	URYFBU.187250		•	
AURYFBU250312	UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM .250"312"Ø Includes Test Report and Certificate of Conformance.	URYFBU.250312			
AURYFBU312375	UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM. 312"375"Ø Includes Test Report and Certificate of Conformance.	URYFBU.312375		•	
AURYFBU375437	UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM. 375"- 437"Ø Includes Test Report and Certificate of Conformance.	URYFBU.375437			
AURYFBU437500	UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM .437"500"Ø Includes Test Report and Certificate of Conformance.	URYFBU.437500		•	
AURYFBU500562	UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM .500". 562"Ø Includes Test Report and Certificate of Conformance.	URYFBU.500562			
AURYFBU562625	UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM .562"-, 625"Ø Includes Test Report and Certificate of Conformance.	URYFBU.562625			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURYFBU625687	UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH 100KHz-2MHz.	URYFBU.625687			
AURYFBU687750	EXPANDABLE FROM. 632 <sup>-5</sup> .687 <sup>-6</sup> Includes Test Report and Certificate of Conformance. UNIVERSAL "Y" FLAT BOTTOM ROTARY PROBE, UNSHIELDED, SUPPLIED WITH 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM. 687 <sup>-15</sup> .00 <sup>-5</sup> Includes Test Report and Certificate of Conformance.	URYFBU.687750			
ATPNR-4/7L	RIGID STRAIGHT SURFACE PROBE, POWERLINK 7 PIN LEMO CONNECTOR 50-500KHz, 4.0" LONG. Includes Test Report and Certificate of Conformance.	9222209.00	U8626047		
ASDP312/2K	LOW FREQUENCY REFLECTION SPOT PROBE.312"Ø(7.85mm) TIP DIAMETER, 800Hz-20KHz WITH SIDE MOUNTED TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-196-3			
ATPNR-95-6/7L	RIGID SURFACE PROBE, POWERLINK AB5/REFLECTION 90° DEGREES, 500° DROP, .125°Ø O.D. TIP, 6.0° LONG 7 PIN LEMO CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.	9222215.00	U8616103		
ATPQ-925-2.5/1-100K	SURFACE PROBE 1-100KHZ , 250"Ø OD TIP, 90", 236" DROP, 2.5" LONG, DIFFERENTIAL/BRIDGE, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-4081D			
ATPR-45-5/1-30khz	LOW FREQUENCY REFLECTION PROBE .187" DIA TUBING(FLAT SHIELDED)45 DEG .500" DROP 5.0" LONG TRIAX FISCHER CONNECTOR 1-30KHz. Includes Test Report and Certificate of Conformance.	•			
ATPR-92-4/20K	LOW FREQUENCY SURFACE PROBE, REFLECTION, 1-SOKHz, 90° DEGREES, 200° DROP, 187" Ø TUBING, 4.0° LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPNR92-4/20K		•	
ATPR-92-5/20K	LOW FREQUENCY SURFACE PROBE, REFLECTION, 1-SOKHz, 90° DEGREES, 200° DROP, 187" Ø TUBING, 5.0° LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TPNR92-5/20K		•	
ATPR-95-6/1-40K	STAINLESS STEEL LOW FREQUENCY SURFACE PROBE 1-40khz 90° DEGREES .5' DROP .187" OD TUBING 6.0" LONG REFLECTION, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
ATPR-96-5/1-3KHZ	LOW FREQUENCY SURFACE PROBE, REFLECTION 1-3KHz, 90°, 600° DROP, 187'Ø OD TUBING SHAFT LENGTH 3.0° LONG, 5.0° OVERALL PROBE LENGTH WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
ATPR-97-6/1-3KHz	LOW FREQUENCY SURFACE PROBE, REFLECTION 1-3KHz, 90°, 700° DROP, 187'Ø OD TUBING SHAFT LENGTH 4.0° LONG, 6.0° OVERALL PROBE LENGTH WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
ATPRQ-95-5B/1k-50K	SURFACE LOW FREQUENCY PROBE 1-S0KHZ, 90" DEGREES, 500" DROP, .250"Ø O.D., 5.0" LONG BENT 15" DEGREES, REFLECTION, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SPC-4TF-105-1R	.NEC-1090	•	
AUR115SE/1.5WL	UNIVERSAL ROTATING SCANNER PROBE, SPLIT END, EXPANDABLE FROM .110"Ø125"Ø 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR, 1.5" INCH WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR125	UNIVERSAL ROTATING SCANNER PROBE, SPLIT END .125"Ø (1/8"Ø) 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPU-8,BPD-8	BPU-8,BPD-8	VMED101125	
AUR125/2.0WL	UNIVERSAL ROTATING SCANNER PROBE, 125"Ø 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance	•			
AUR155SS/2WL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .155"(3.94mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P010F051		•	
AUR155SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .155"(3.94mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P010F035			
AUR155SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .155"(3.94mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P010F051			
AUR156	UNIVERSAL ROTATING SCANNER PROBE, SPLIT END.156"Ø (5/32"Ø)100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPU-10	BPU-10	•	
AUR156F	ROTATING SCANNER PROBE SHIELDED 4 PIN FISCHER CONNECTOR 100K-2MHZ 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPUF-10		•	
AUR156SE/1.75WL	Universal Rotary Hole Probe Self Expanding from 0.156 inch (3.96 mm) to 0.187 inch (4.7 mm) diameter, 1.75 inch (44 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes T	SPO-5965, 9230061	SUB-10-12, U8610267	RTP-014	
AUR156SE/2.0WL	Universal Rotary Hole Probe Self expanding from 0.156 inch (3.96 mm) to 0.187 inch (4.7 mm) diameter, 2.0 inch (51 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Tes	PRF040-050051		•	
AUR156SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .156"(3.96mm), 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P010F051			
AUR156SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .156"(3.96mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P010F035		•	
AUR156SS/45MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .156"(3.96mm) 45mm(1.77") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•		•	
AUR171/1.5WL	UNIVERSAL ROTATING SCANNER PROBE 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR, 1.5" INCH WORKING LENGTH. Includes Test Report and Certificate of Conformance.			•	
AUR171SS/2WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .171"(4.34mm) 51mm WORKING LENGTH Includes Test Report and Certificate of Conformance.	615P011F051		•	
AUR171SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .171" (11/64") 2.95"(75mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P011F075			
AUR171SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .171°Ø(4.34mm), 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P011F035		•	
AUR171SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .171"(4.34mm) 51mm WORKING LENGTH Includes Test Report and Certificate of Conformance.	615P011F051		•	
AUR171SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .171" (11/64") 2.95"(75mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P011F075		•	
AUR172/2.0WL	UNIVERSAL ROTATING SCANNER PROBE, .172"(11/64) Ø 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR, 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	619P011F051		•	
AUR187	UNIVERSAL ROTATING SCANNER PROBE, SPLIT END .187" Ø (3/16" Ø) 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPU-12	BPU-12	•	
AUR187/2.0WL	UNIVERSAL ROTATING SCANNER PROBE, 187"(3/16)Ø 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	619P012F051	619P012F051		
AUR187SE/1.75WL	Universal Rotary Hole Probe Self expanding from 0.187 inch (4.75 mm) to 0.218 inch (5.54mm) diameter, 1.75 inch(44 mm) working length, Operating frequency 100 kHz - 2 MHz. Fischer 4 pin connector, reflection differential coil configuration, includes Te	SPO-5965, 9219979	SUB-12-14	RTP-001	

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR187SE/2.0WL	Universal Rotary Hole Probe Self expanding from 0.187 inch (4.75 mm) to 0.218 inch (5.54mm) diameter, 2.00 inch(51 mm) working length, Operating frequency 100 kHz - 2 MHz, Fischer 4 pin connector, reflection differential coil configuration. Includes Te	PRF047-057051			
AUR187SE/4.0WL	Incuder 200 km <sup>2</sup> - 2 mm <sup>2</sup> , reacher 4 priconnector, reflection differential coll configuration. Includes re Universal Rotary Hole Probe Self expanding from 0.187 inch (4.75 mm) to 0.218 inch (5.54mm) diameter, 4.00 inch(101.6 mm) working length, Operating frequency 100 kHz - 2 MHz, Fischer 4 pin connector, reflection differential coll configuration. Includes	•			
AUR187SE/6.0WL	Universal Rotary Hole Probe Self expanding from 0.187 inch (4.75 mm) to 0.218 inch (5.54mm) diameter, 6.00 inch(152.4 mm) working length, Operating frequency 100 kHz - 2 MHz, Fischer 4 pin connector, reflection differential coil configuration. Includes	•		•	
AUR-6.1MSS/51MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR. 6.1mm DIA, , 51MM WORKING LENGTH Includes Test Report and Certificate of Conformance	615P061M051			
AUR187SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .187"(4.75mm), 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P012F051			
AUR187SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .187"Ø(4.75mm), 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P012F035			
AURFX250/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, 250"Ø Includes Test Report and Certificate of Conformance	•			
AUR078SS/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 078"(1.98mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.1" WORKING LENGTH. Includes Test Report and Certificate of Conformance.			•	
AUR062SS/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.062"(1.57mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.1" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•			
AUR120SS/1.1WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .120"(3.05mm)Ø, 27.94mm(1.1") WORKING LENGTH. Includes Test Report and Certificate of Conformance.			•	
AURY218250/3WL	UNIVERSAL ADJUSTABLE ROTARY PROBE 3.0" WORKING LENGTH, EXPANDABLE FROM .218"250" 100KHz-2MHz, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AUR198SS/35MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHz- 2MHz, .198"Ø SHIELDED, 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance. ROMMANN LOW PRECURCY REPLECTION SPORT PROBE, ABSOLUTE FERRITE CORE (SHIELDED). 300Hz-100KHz. 0.4 110mm1 DIA. 0.85 121.5mm1 LENGTH.	•	•		
AF-4218/4F	NOTIFICATION OF TREAST AND A DEPENDENT AND A DEPENDENT ADDRESS ADDR	PKA 42-9E			
AF-4218/TF	0.79in (20mm) WIDTH. SUPPLIED WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. Reference P/N: SSI 55-11-	PKA 42-9E			
AUR203/1.5WL	UNIVERSAL ROTATING SCANNER PROBE, .203"Ø 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR203/2.0WL	UNIVERSAL ROTATING SCANNER PROBE, .203"Ø 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•	•		
AUR203SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .203"(5.15mm), 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P013F035			,
AUR203SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: 5.16MM (.203") 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P013F051			
AUR203SS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .203"(5.15mm), 65mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P013F065	•		
ARRY750875/3WL	ROTARY "Y" PROBE FOR RA SCANNER 4 PIN STEP LEMO CONNECTOR 100KHz-2MHz, 3.0" WORKING LENGTH .750"875" SPREAD Includes Test Report and Certificate of Conformance	•	•		
AUR218SE/2.0WL	Universal Rotary Hole Probe Self Expanding from 0.218 inch (5.5 mm) to 0.250 inch (6.3mm) diameter, 2.00 inch(50 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test	SPO-5965, 9219980	RTP-003		
AUR218SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .218"(5.54mm), 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P014F051		•	
AUR234SS/3.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .234" (15/64") 2.95"(75mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P015F075			
AUR234SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .234"(5.95mm), 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P015F035	•		
AUR234SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .234"(5.95mm), 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P015F051			
AUR234SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .234" (15/64") 2.95"(75mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P015F075	•		
AUR250	UNIVERSAL ROTATING SCANNER PROBE, SPLIT END .250" Ø (1/4" Ø) 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	URF.250			
AUR250281SE	Universal Rotary Hole Probe Self expanding from 0.250 inch (6.35 mm) to 0.281 inch (7.14 mm) diameter, 2.00 inch (51 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes T				
AUR250/2.0WL	ROTARY SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	619P016F051	619P016F051		
AUR250SE/2.0WL	Universal Rotary Hole Probe Self expanding from 0.250 inch (6.35 mm) to 0.281 inch (7.14 mm) diameter, 2.00 inch (51 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes T	SPO-5965, 9219981	RTP-004	SUB-16-18	PRF060-070051
AUR250SE/2.5WL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END EXPANDABLE FROM.250"281", 2.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•			
AUR250SE/3MHZ	Universal Rotary Hole Probe Self expanding from 0.250 inch (6.35 mm) to 0.281 inch (7.14 mm) diameter, 2.00 inch (51 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes T	9219981			
AURY156187/3WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 3.0" WORKING LENGTH EXPANDABLE FROM .156"187". Includes Test Report and Certificate of Conformance.				
AUR250SE/3WL	Universal Rotary Hole Probe Self expanding from 0.250 inch (6.35 mm) to 0.281 inch (7.14 mm) diameter, 3.00 inch (76 mm) working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes T				
AUR250SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .250"(7.14mm), 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P016F051			
AUR250SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .250"(6.35mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P016F051			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR250SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .250" (1/4"), 2.95" (75mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P016F075			
AUR265SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .265"(6.74mm), 35mm WORKING LENGTH includes Test Report and Certificate of Conformance.	615P017F035			
AUR265SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .265" (17/64") 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance	6150P17F051			
AUR281SE/2.0WL	Universal Rotary Hole Probe Self Expanding from 0.281 inch (7.14mm) to 0.312 inch (7.92mm) diameter, 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test	SPO-5965, 9219982	RTP-005		
AUR281SE/4.0WL	Universal Rotary Hole Probe Self Expanding from 0.281 inch (7.14mm) to 0.312 inch (7.92mm) diameter, 4 INCH working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report				
AUR281SE/6WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, EXPANDABLE FROM .281"312"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certificate of Conformance				
AUR281SS/2.0WL	ELOTEST MINI ROTOR STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, A PIN FISCHER CONNECTOR. HEAD DIAMETER: .281°(7.14mm)Ø, 2.0°(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPEMF-281SS	EMR.281SS	615P018F051	
AUR281SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .281"(7.14mm), 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P018F051			
AUR281SS/2WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .281"(7.14mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P018F051			
AUR281SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .281"(7.14mm), 35mm WORKING LENGTH Includes Test Report and Certificate of Conformance.	615P018F035			
AUR281SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .281"(7.14mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P018F051			
AUR297/2.0WL	UNIVERSAL ROTATING SCANNER PROBE, .297"(19/64)Ø 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	619P019F051			
AUR312/2.0WL	UNIVERSAL ROTATING SCANNER PROBE, 312"(5/16)Ø 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	619P020F051	619P020F051		
AUR312555/5.12WL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .312"(7.9375 mm) 5.12"(130 mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance				
AUR312SE/10.0WL	Universal Rotary Hole Probe Self expanding from 0.312 inch (7.9 mm) to 0.375 inch (9.5 mm) diameter, 10.0 inch (254 mm) working length, Operating frequency 100khz-2MHZ MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Te	RTP-038			
AUR312SE/12.0WL	Universal Rotary Hole Probe Self expanding from 0.312 inch (7.9 mm) to 0.375 inch (9.5 mm) diameter, 12.0 inch (304.8 mm) working length, Operating frequency 100khz-2MHZ MHz Fischer 4 pin connector, reflection differential coil configuration. Includes	RTP-039			
AUR312SE/2.0WL	Universal Rotary Hole Probe Self expanding from 0.312 inch (7.9 mm) to 0.375 inch (9.5 mm) diameter, 2.00 inch (50 mm) working length, Operating frequency 100kh-2MHz MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Tes	SPO-5965, 9219983	PRF078-080051	SUB-20-24, RTP-006	SPO-5965, 9219983
AUR312SE/4.0WL	Universal Rotary Hole Probe Self expanding from 0.312 inch (7.9 mm) to 0.375 inch (9.5 mm) diameter, 4.0 inch (101.6 mm) working length, Operating frequency 100kh2-2MHZ MHz Fischer 4 pin connector, reflection differential coil configuration. Includes T				
AUR312SS/20MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	615P020F020			
AUR312SS/35MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P020F035			
AUR312SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .312"(7.9375mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P020F051			
AUR312SS/95MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .312"(5/16"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P020F095			,
AUR328SS/2WL	STAINLESS STEEL ROTATING SCANNER PROBE 8.33MM(.328")Ø HEAD and 51MM(2.0") WORKING LENGTH. 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	615P021F051			
AUR328SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 8.33MM(.328")Ø HEAD and 51MM(2.0") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	615P021F051			
AUR328SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .328"(21/64"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P021F095			
AUR343SS/2.0WL	ELOTEST MINI ROTOR STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .343"(8.71mm)Ø, 2.0"(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPEME-22/SS	EMR.350SS		ĺ.
AUR343SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .343"(11/32"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P022F095			
AUR350SS/2.0WL	ELOTEST MINI ROTOR STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: 350°(8.89mm)Ø, 2.0°(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPEMF350/SS	EMR.350SS		
AUR359SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .359"(9.12mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P023F035			
AUR359SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .359"(23/64"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P023F095			
AUR360SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 9.14MM(.360")Ø HEAD and 51MM(2.0") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	615P023F051			
AUR370SS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, 370°Ø SHIELDED, 4 PIN FISCHER CONNECTOR, 2.0°(51mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR375SE/2.0WL	Universal Rotary Hole Probe Self Expanding from 0.375 inch (9.5mm) to 0.437 inch (11.0mm) diameter, 2 inch (50 mm) working length. Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Re	SPO-5965, 9219978	SPO-5965, 9219978	RTP-002	SUB-24-28
AUR375SE/4.0WL	Universal Rotary Hole Probe 0.375 inch (9.52 mm) to 0.406 inch (10.31 mm) immeter, Self Expanding 4 inch (101.6 mm) working length, Operating frequency 100kh-2MHZ MHz Fischer 4 pin connector, reflection differential coll configuration. Includes Test				
AUR375SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .375"(9.525mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P024F035			
AUR375SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .375"(9.525mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P024F051		1	1

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR375SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .375"(3/8"), 95mm WORKING	615P024F095			
AUR390SS/35MWL	LENGTH. Includes Test Report and Certificate of Conformance. STAINESS STEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .390°(9.92mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P025F035			,
AUR390SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 9:906MM(.390°)Ø HEAD and 51MM(2.0°) WORKING LENGTH. 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	615P025F051			
AUR390SS/95MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .390"(25/64"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P025F095			,
AUR406SE/2.0WL	Universal Rotary Hole Probe 0.406 inch (10.31 mm) to 0.437 inch (11.11 mm) diameter, Self Expanding 2.0 inch (50 mm) working length, Operating frequency 100khz-2MHZ MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test	SPO-5965	RTP-032		
AUR406SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .406"(10.31mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P026F035			
AUR406SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .406"(13/32"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P026F095			,
AUR421SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .421"(10.71mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P027F035			
AUR421SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .421"(27/64"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P027F095			,
AUR437SE/2.0WL	Universal Rotary Hole Probe Self Expanding from 0.437 inch (11.1mm) to 0.500 inch (12.7mm) diameter, 2 inch (50 mm) working length, Operating frequency 200 kHz - 3 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test R	SPO-5965, 9219984	SPO-5965, RTP-007	SUB 28-32	
AUR437SS/2.0WL	ROTATING SCANNER PROBE 11.09MM(437")Ø HEAD and 51MM(2.0") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	615P028F051			
AUR437SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .437"(11.11mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P028F035			
AUR437SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .437"(11.1mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P028F051			
AUR437SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .437"(7/16"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P028F095			,
AUR445SS/51MWL	ROTATING SCANNER PROBE 11.30MM(.445")Ø HEAD and 65MM(2.5") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PRR1130-051			
AF-5024	RIGID SURFACE PROBE ABSOLUTE SHIELDED 1-3MHZ, 90°, .50° DROP BENT 30° 1.0° FROM THE TIP, 0.125° DIAMETER SHAFT, 7.0 " LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	SS-AFB1X6			
AURFB312SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM 312"375"Ø. Includes Test Report and Certificate of Conformance.				
AURFB375SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM .375"437" // Includes Test Report and Certificate of Conformance.				
AURFB750SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .750"Ø. Includes Test Report and Certificate of Conformance.				
AURFB812SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .812"Ø. Includes Test Report and Certificate of Conformance.				
AURFB875SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .875"Ø. Includes Test Report and Certificate of Conformance.				
AURFB937SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .937"Ø. Includes Test Report and Certificate of Conformance.				
AURFB-1.0SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= 1.0"Ø. Includes Test Report and Certificate of Conformance.				
AURFB437SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM 437"500"Ø. Includes Test Report and Certificate of Conformance.				
AURFB500SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM 500"562"Ø. Includes Test Report and Certificate of Conformance.				
AURFB562SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM 562"625"Ø. Includes Test Report and Certificate of Conformance.				
AURFB625SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM 625"687"Ø. Includes Test Report and Certificate of Conformance.				
AURFB687SE/2WL	NIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .687"Ø. Includes Test Report and Certificate of Conformance.				
AUR453SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .453"(11.50mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P029F035			
AUR453SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 11.5MM(.453")Ø HEAD and 51MM(2.0") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	615P029F051			
AUR453SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .453"(29/64"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P029F095			,
AUR468SS/2.5WL	ROTATING SCANNER PROBE 11.89MM(.468")Ø HEAD (MACHINE TO 11.79mm(.464") and 65MM(2.5") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PRR1189-065	615P030F065		
AUR468SS/35MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .468"(11.90mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P030F035			
AUR468SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 11.79MM(.468")Ø HEAD and 51MM(2.0") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	615P030F051			
AUR468SS/95MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .468"(15/32"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P030F095			,
AUR484SS/35MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .484"(12.30mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P031F035			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR484SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .484"(31/64"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P031F095			
AUR500/2.0WL	ROTARY SCANNER PROBE 100KHZ-20HIZ 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				,
AUR500SE/2.0WL	Universal Rotary Hole Probe Self Expanding from 0.500 inch (12.6 mm) to 0.562 inch (14.2 mm) diameter, 2 inch (50 mm) working length, Operating frequency 100kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test	SPO-5965, 9219985	RTP-008		
AUR500SS/2.0WL	ROTATING SCANNER PROBE 12.7MM(.500")Ø HEAD and 51MM(2.0") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	615P032F051			
AUR500SS/2WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .500"(12.7mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P032F051			
AUR500SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .500"(12.70mm) 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P032F035			
AUR500SS/51MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .500"(12.7mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P032F051		•	
AUR515SS/65MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .515"Ø (33/64") 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P033F065			
AUR531SE/2.0WL	Universal Rotary Hole Probe Self Expanding from 0.531 inch (13.4 mm) to 0.562 inch (14.2 mm) diameter, 2 inch (50 mm) working length, Operating frequency 100kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test		RTP-034		
AUR531SS/95MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .531"(17/32"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P034F095			,
AUR562SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .562"(14.27mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P036F051			
AUR562SS/95MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .562"(9/16"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P036F095			,
AUR563SS/65MWL	ROTATING SCANNER PROBE 14.30MM(.563")Ø HEAD and 65MM(2.5") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PRR1430-065			
AUR571SE/1.0WL	Universal Rotary Hole Probe Self expanding 0.571 inch (14.50 mm), 1.00 inch(25.4 mm) working length, Operating frequency 100 kHz - 2 MHz, Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Confo	URB571 WL1.0			
AUR585SE	UNIVERSAL ROTATING SCANNER PROBE 100KHz-2MHz,. 4-PIN FISCHER CONNECTOR. 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR593SS/95MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .593"(19/32"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P038F095			,
AUR594SS/65MWL	ROTATING SCANNER PROBE 15.10MM(.594")Ø HEAD and 65MM(2.5") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PRR1510-065			
AUR625	UNIVERSAL ROTATING SCANNER PROBE, SPLIT END .625"Ø (5/8"Ø) 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	URF.625			
AURFX250SS5T/3.5WL	STAINLESS STEEL FLEX SHAFT ROTARY PROBE, 250" Ø, 0.500" LONG TIP, 3.5" WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR 100KHz- 2MHz. Includes Test Report and Certificate of Conformance.	TEK-3005U.250SS/3.5WL			
AURFX188SS5T/3.5WL	STAINLESS STEEL FLEX SHAFT ROTARY PROBE, 188" Ø, 0.500" LONG TIP, 3.5" WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR 100KHz- 2MHz. Includes Test Report and Certificate of Conformance.				
AUR625SS/2.0WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .625"(15.88mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P040F051	615P040F051	UR.625SS	
AUR625SS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz SHIELDED, 4 PIN FISCHER CONNECTOR. PROBE DIAMETER: .625"Ø (5/8")(15.90mm) WITH A 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P040F035			
AUR625SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .625"(15.88mm) 51mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P040F051			
AUR625SS/75MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz SHIELDED, 4 PIN FISCHER CONNECTOR. PROBE DIAMETER: .625"Ø (5/8") WITH A 2.95"(75mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance	615P040F075			
AUR626SS/65MWL	ROTATING SCANNER PROBE 15.90MM(.626")Ø HEAD and 65MM(2.5") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PRR1590-065			
AUR630SS/65MWL	ROTATING SCANNER PROBE 16.00MM(.630°)Ø HEAD and 65MM(2.5°) WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PRR1600-065			
AUR642SS/65MWL	ROTATING SCANNER PROBE 16.70MM(.642")Ø HEAD and 65MM(2.5") WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	PRR1630-065	615P041F065	PRR1189-065	
AUR656SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .656"(21/32"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P042F095			,
AUR687SS/2.0WL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ- 2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR, .687"Ø. Includes test report.				
AUR687SS/2WL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .687"(17.45mm)Ø, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P044F051			
AUR687SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .687"(17.45mm)Ø, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P044F051			
AUR689SS/65MWL	ROTATING SCANNER PROBE 17.50MM(.689°)Ø HEAD and 65MM(2.5°) WORKING LENGTH. 100KHZ-2MHZ SHIELDED, STAINLESS STEEL, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PRR1750-065			
AUR718SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .718"(23/32"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P046F095			,
AUR750SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .750"(19.05mm)Ø, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P048F051			
AUR812SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .812"(20.64mm)Ø, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P052F051			
AUR812SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .812"(13/16"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P052F095			,

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR875SS/2.5WL	STAINLESS STEEL ROTATING SCANNER PROBE 7/8" HEAD SIZE and 2.5" WORKING LENGTH. 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	615P056F065			
AUR875SS/51MWL	Inclues test keport and Lertificate or Conformance. STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .875"(22.22mm)Ø, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P056F051			
AUR875SS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 7/8" HEAD SIZE and 65MM WORKING LENGTH. 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	615P056F065			
AUR937SS/95MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .937"(15/16"), 95mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P060F095			,
AUR-1.0SE/2WL	Universal Rotary Hole Probe (1.0001"-1.0007") diameter, 2.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-1.0SS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: 1.00"(25.4mm)Ø, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P064F051			
AUR-1.125SE/2.0WL	Universal Rotary Hole Probe (1.125"-1.250") diameter, 2.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-1.125SE/2WL	Universal Rotary Hole Probe (1.125"-1.250") diameter, 2.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-1.250SE/2.0WL	Universal Rotary Hole Probe (1:250"-1.2508") diameter, 2.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-1.286/8WL	Universal Rotary Hole Probe1.286"Ø diameter, 8.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.	UR1.286/8WL			
AUR-1.30SE/4.0WL	UNIVERSAL ROTARY PROBE SPLIT END 100KHz-2MHz , 4PIN FISCHER CONNECTOR, EXPANDABLE FROM 1.30"-1.375"Ø WITH 4.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-1.347/8WL	Universal Rotary Hole Probe1.347"Ø diameter, 8.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.	UR1.347/8WL	NEC-3132-3		
AUR-1.5/2WL	Universal Rotary Hole Probe 1.500° Ø diameter, 2.0° working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-1.50SE/2WL	Universal Rotary Hole Probe (1.5000".1.5008") diameter, 2.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-1.625/2WL	Universal Rotary Hole Probe 1.625" Ø diameter, 2.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AF-4216	LOW FREQUENCY 90° RIGHT ANGLE SPOT PROBE. DIFFERENTIAL/BRIDGE. 0.500° OD, 0.560° CASE O.D, 1.380 LENGTH TRIAX FISCHER CONNECTOR. 10KHz-50KHz. Includes Test Report and Certificate of Conformance.	LS1504-1			
AF-4215	LOW FREQUENCY 90° RIGHT ANGLE SPOT PROBE. DIFFERENTIAL/BRIDGE. 1.0° OD, 1.1° CASE O.D, 1.850 LENGTH. TRIAX FISCHER. 100Hz-2KHz. Includes Test Report and Certificate of Conformance.	LS0210-1			
AUR-1.6255E/2.0WL	Universal Rotary Hole Probe (1.6250"-1.6258") diameter, 2.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-1.75SE/2WL	Universal Rotary Hole Probe (1.7500"-1.7509") diameter, 2.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-10.0M/SE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 10-12mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.				
AUR-10.0MSE/100MWL	Universal Rotary Hole Probe (10.0mm) diameter Split End, Expandable from 10-12mm, 100mm(3.94") working length, Operating frequency 100 kHz - 2 MHz Supplied with a 4 pin Fischer connector, reflection differential coil configuration. Includes Test Repo				
AUR-10.3MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 10.3mm (403") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-10.3-35			
AUR-10.4MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 10.4mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM10-4-50			
AUR-11.1MSE/51MWL	UNIVERSAL ROTATING SCANNER PROBE 100KHz-2MHz SHIELDED, SPLIT END, 4-PIN FISCHER CONNECTOR. EXPANDABLE FROM.11.1mm-12.1mm, 51mm (2.0") WORKING LENGTH. Includes Test Report and Certificate of Conformance	PRF111-121051			
AUR-11.1MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 11.1MM DIA 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SEU-11.1-35			
AUR-11.1MSS/50MWL	ROHMAN STAINLESS STEEL ROTATING SCANNER PROBE 11.4MM DIA 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR 50MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-11.4MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 11.4mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM11-4-50			
AUR-11.5MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 11.5mm	SEU-11.5-35			
AUR-11.8MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 11.8mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM11-8-50			
AUR-12.0M/SE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 12-15mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.				
AUR-12.0MSE/100MWL	Universal Rotary Hole Probe (12.0mm) diameter Split End, Expandable from 12-14mm, 100mm(3.94") working length, Operating frequency 100 kHz - 2 MHz Supplied with a 4 pin Fischer connector, reflection differential coil configuration. Includes Test Repo				
AUR-12.1MSS/50MWL	ROHMAN STAINLESS STEEL ROTATING SCANNER PROBE 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ, 12.5mmØ DIAMETER HEAD 50mm WORKING LENGTH. Includes Test Report and certificate of Conformance.				
AUR-12.7MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 12.7mmØ(.500") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-12.7-35			
AUR-12.7MSS/76MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR 76MM WORKING LENGTH, 12.7mmØ(1/2") HEAD. Includes Test Report and Certificate of Conformance.				
AUR-13.5M/SE	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, SPLIT END, SPREADABLE FROM 13.5mm-14.5mm, 4 PIN FISCHER CONNECTOR 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	619P034F051			
AUR-13.9MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 13.9mm@(.546") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-13.9-35			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR-14.0MSE/100MWL	Universal Rotary Hole Probe (14.0mm) diameter Split End, Expandable from 14-16mm, 100mm(3.94") working length, Operating frequency 100 kHz - 2				
AUR-14.0MSE/51MWL	MHz Supplied with a 4 pin Fischer connector, reflection differential coil configuration. Includes Test Repo UNIVERSAL ROTATING SCANNER PROBE 100KH-2MHz SHIELDED, SPLIT END, A-PIN FISCHER CONNECTOR. EXPANDABLE FROM.14.0mm-15.0mm, 51mm 12.0° WORKING LENGTH. Includes Test Report and Certificate of Conformance.	PRF140-150051			•
AUR-15.0M/SE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz-15-20mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.				
AUR-15.0MSE/65MWL	UNIVERSAL ROTATING SCANNER PROBE 100KHz-2MHz SHIELDED, SPLIT END, 4-PIN FISCHER CONNECTOR. EXPANDABLE FROM. 15.0mm-17.0mm, 65mm (2.5") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	PRF150-170065			
AUR-16.0M/50MWL	Universal Rotary Hole Probe (16.0mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.		•		
AUR-16.1MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 16.1MMØ DIA, 100KH2-2MHz , 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P161M035			
AUR-19.05MSS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. PROBE DIAMETER = .750"Ø (19.05mm), 2.0"(S1mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.	615P048F051			
AUR-19.0MSS/76MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR 76MM WORKING LENGTH, 19.05mmØ(3/4") HEAD. Includes Test Report and Certificate of Conformance.				
AUR-2.099SE/4WL	Universal Rotary Hole Probe (2.099"-2.198") diameter self expanding, 4.0" working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-2.0SE/5WL	Universal Rotary Hole Probe (2.000" Ø - 2.125" Ø) diameter Split End, 5.0" working length, Operating frequency 100 kHz - 2 MHz With 4 pin Fischer connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-2.20MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .086 <sup>®</sup> Ø(2.20mm), 2.0 <sup>°</sup> (51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-2.60MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: 102"Ø(2.60mm), 2.0"(S1mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-2.78MSS	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .1093"(2.78mm)Ø 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	PRR0278-035			
AUR-2.80SE/2WL	Universal Rotary Hole Probe (2.80"Ø - 2.90"Ø) diameter Split End, 2.0" working length, Operating frequency 100 kHz - 2 MHz With 4 pin Fischer connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-2.90SE/2WL	Universal Rotary Hole Probe (2.90"Ø - 3.0"Ø) diameter Split End, 2.0" working length, Operating frequency 100 kHz - 2 MHz With 4 pin Fischer connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-20.0M/50MWL	Universal Rotary Hole Probe (20.0mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-20.0M/SE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 20-25mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.		•		
AUR-22.0M/50MWL	Universal Rotary Hole Probe (22.0mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-22.3MSS/76MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR 76MM WORKING LENGTH, 22.3mmØ(7/8") HEAD. Includes Test Report and Certificate of Conformance.		•		
AUR-22.6MSS/51MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR.57/64"Ø (22.61mm) DIAMETER HEAD.Includes Test Report and Certificate of Conformance	615P057F051			
AUR-24.0M/50MWL	Universal Rotary Hole Probe (24.0mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.		•		
AUR-25.0M/SE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 25-30mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.				
AUR-25.4MSS/76MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR 76MM WORKING LENGTH, 25.4mm@(1.0") HEAD. Includes Test Report and Certificate of Conformance.				
AUR-3.0MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 3.0MM DIA 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SEU-3.0-35	U8602076		
AUR-3.0MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .118"Ø(3.0mm), 2.0"(S1mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-3.18MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .125"(3.18mm)Ø 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	PRR0318-035			
AUR-3.1MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 3.1MM DIA 100KH2-2MHZ , 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance OLYMPUS NDT ITEM P/N: U8609315	SEU-3.1-35, U8609315			
AUR-3.37SE/2.0WL/2M	Universal Rotary Hole Probe, Split End (3.37"-3.42") diameter, 2.0" working length, Operating frequency 1MHz - 3MHz, Center Frequency = 2MHz. Supplied with a Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and				
AUR-3.45MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .136"Ø(3.45mm), 2.0"(S1mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-3.57MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .1406"(3.57mm)Ø 35mm WORKING LENGTH. Includes Test Report and Certificate of Conformance.	PRR0357-035			
AUR-3.5MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 3.5MM DIA 100KH2-2MHZ , 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SEU-3.5-35	U8609316		
AUR-3.5MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .1378"Ø(3.5mm), 2.0"(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-3.6MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 3.6mmØ(.141") HEAD SIZE. Includes Test Report and Certificate of Conformance	SEU-3.6-35			
AUR-3.80MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .150°Ø(3.80mm), 2.0°(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-3.90MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .154"Ø(3.90mm), 2.0"(S1mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-3.9MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 3.9mmØ(.156") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-3.9-35	U8609317		

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR-36.8MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: 1.45"Ø(36.8mm), 65mm(2.56")	615P3698M065			
AUR-4.0M/SE/51MWL	WORKING LENGTH. Includes Test Report and Certificate of Conformance ROTATING SCANNER PROBE 100KHz-2MHz, 4.0-S.Oum, S.PLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, S1mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.	619P010			
AUR-4.0MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .157*Ø(4.00mm), 2.0*(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-4.20MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .165"Ø(4.20mm), 2.0"(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.			•	
AUR-4.2MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 4.2MM DIA 100KH2-2MHZ, 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SEU-4.2-35	U8602078	•	
AUR-4.3MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 4.3mmØ(.171") HEAD SIZE. Includes Test Report and Certificate of Conformance	SEU-4.3-35	RSM 4-3-35		
AUR-4.5M/50MWL	Universal Rotary Hole Probe (4.5mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coli configuration. Includes Test Report and Certificate of Conformance.			•	
AUR-4.60MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .181°Ø(4.60mm), 2.0°(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-4.70MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .185°Ø(4.70mm), 2.0°(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.			•	
AUR-4.75M/SE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 4.75-5.75mm (.187-226") Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.	619P012F51		•	
AUR-4.75MSS/40MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .187°Ø(4.75mm), 1.57°(40mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance				
AUR-4.76MSS/40MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR. HEAD SIZE=4.76mm, PROBE WORKING LENGTH =40mm. Includes Test Report and Certificate of Conformance	621P012			
AUR-4.7MSS/35M	ROHMAN STAINLESS STEEL ROTARY PROBE 100KHz-2MHz. 4.7MMØ DIA. HEAD 35MM WORKING LENGTH, 4 PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RS4-7-35			
AUR-4.7MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 4.7mmø(.187") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-4.7-35, RSM4-7-35			
AUR-4.7MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 4.7mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM4-7-50		•	
AUR-4.7MSS/80MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 80mm WORKING LENGTH 4.7mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM4-7-80		•	
AUR-4.90MSS/51MWL	UNIVERSAL STAILESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .192"Ø(4.90mm), 2.0"(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMRA Rotor. Includes Test Report and Certificate of Conformance.		,	•	
AUR-5.0M/50MWL	Universal Rotary Hole Probe (5.0mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.			•	
AUR-5.0MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .197*Ø(5.00mm), 2.0*(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.			•	
AUR-5.10MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .201°Ø(5.10mm), 2.0°(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.			•	
AUR-5.1MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 5.1mm@(.203") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-5.1-35			
AUR-5.1MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 5.1mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM5-1-50			
AUR-5.30MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .209°Ø(5.30mm), 2.0°(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 or Ether ARD002 Rotor. Includes Test Report and Certificate			•	
AUR-5.40MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .213°Ø(5.40mm), 2.0°(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.			•	
AUR-5.4MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 35mm WORKING LENGTH 5.4mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM5-4-35			
AUR-5.4MSS/50MWL	ROHMAN STAINESS STEEL ROTATING SCANNER PROBE 5.4MM DIA 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR 50MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-5.5M/50MWL	Universal Rotary Hole Probe (5.5mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-5.5MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 5.5MM DIA 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SEU-5.5-35			
AUR-5.6MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 5.6mm@(218") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-5.6-35			
AUR-5.6MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .220°Ø(5.60mm), 2.0°(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 or Ether ARD002 Rotor. Includes Test Report and Certificate				
AUR-5.9MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 5.9MM DIA 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SEU-5.9-35			
AUR-6.0M/50MWL	Universal Rotary Hole Probe (6.0mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-6.0M/SE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 6.0-7.0mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.	619P016			
AUR-6.10MSS/51MWL	UNIVERSAL STAILLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .240°Ø(6.10mm), 2.0°(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMRA Rotor. Includes Test Report and Certificate of Conformance.				
AF-4221/TF	ROHMANN LOW FREQUENCY ABSOULUTE / REFLECTION SPOT PROBE, 100Hz-10KHz, 43.5mm(1.70" LONG) x 16.0mm(.630")Ø SUPPLIED WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. Reference: BAE 53-20-01 Part 6	PLA32-16			
AF-4222/TF	ROHMANN ABSOULUTE / REFLECTION PENCIL PROBE, FREQUENCY RANGE 20Hz-6MHz, 100mm(.3.94")LONG, SUPPLIED WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance. Reference: BAe 53-10-20 Part 6 Page 9	KAS 99-1E			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR-6.20MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .244"Ø(6.20mm),				
AUR-6.25MSS/50MWL	2.0°(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance. ROHMANN STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 6.25mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM6-25-50			
AUR-6.25MSS/80MWL	ROHMANN STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 80mm WORKING LENGTH 6.25mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM6-25-80			
AUR-6.2MSS/35MWL	ROHMANN STAINLESS STEEL ROTARY PROBE 100KHz-2MHz. 6.2MMØ DIA. HEAD 35MM WORKING LENGTH, 4 PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.	SEU-6.2-35, RS6-2-35	•		
AUR-6.30MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .248"Ø(6.30mm), 2.0"(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-6.35MSS/50MWL	ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, STAINLESS STEEL4 PIN FISCHER CONNECTOR. HEAD SIZE=6.35mm, PROBE WORKING LENGTH =50mm. Includes Test Report and Certificate of Conformance	621P016			
AUR-6.3MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 6.3mm@(.250") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-6.3-35			
AUR-6.3MSS/50MWL	ROHMANN STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 6.3mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM6-3-50	•		
AUR-6.50MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .256"Ø(6.50mm), 2.0"(S1mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.				
AUR-6.5M/50MWL	Universal Rotary Hole Probe (6.5mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.		•		
AUR-6.60MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .260"Ø(6.60mm), 2.0"(51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.		•		
AUR-6.6MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 6.6mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM6-6-50			
AUR-6.70MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .264"Ø(6.70mm), 2.0" (51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.		•		
AUR-6.7MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 6.7mmø(.264") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-6.7-35			
AUR-6.90MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .272"Ø(6.90mm), 2.0" (51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.		•		
AUR-7.0M/50MWL	Universal Rotary Hole Probe (7.0mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.		•		
AUR-7.0M/SE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 7.0-8.5mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.		•		
AUR-7.0MSS/51MWL	UNIVERSAL STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR. HEAD DIAMETER: .276"Ø(7.00mm), 2.0" (51mm) WORKING LENGTH. Compatible with Rohmann Elotest SMR4 Rotor. Includes Test Report and Certificate of Conformance.		•		
AUR-7.1MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 7.1mm@(.281") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-7.1-35			
AUR-7.5-35	STAINLESS STEEL ROTATING SCANNER PROBE 7.5MM DIA 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-7.5M/50MWL	Universal Rotary Hole Probe (7.5mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-7.5MSE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 7.5-8.5mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.	619P020			
AUR-7.5MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 7.5MM DIA 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-7.9MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 7.9mmø/(.312") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-7.9-35			
AUR-8.0M/50MWL	Universal Rotary Hole Probe (8.0mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-8.2MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 8.2mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM8-2-50			
AUR-8.3MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 8.3mmø/(.328") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-8.3-35			
AUR-8.5M/SE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 8.5-10mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.				
AUR-8.6MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR S0mm WORKING LENGTH 8.6mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM8-2-50			
AUR-8.7MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 8.7mm@(.343") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-8.7-35			
AUR-8.9MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR SOmm WORKING LENGTH 8.9mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.				
AUR-9.0M/50MWL	Universal Rotary Hole Probe (9.0mm) diameter, 50 mm working length, Operating frequency 100 kHz - 2 MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR-9.0MSE/50MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 9.0-9.5mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 50mm(1.97") WORKING LENGTH. Includes Test Report and Certificate of conformance.				
AUR-9.1MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 9.1MM DIA 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.	SEU-9.1-35			
AUR-9.4MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR S0mm WORKING LENGTH 9.4mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM9-4-50			
AUR-9.5MSE/51MWL	ROTATING SCANNER PROBE 100KHz-2MHz, 9.5-10.5mm Ø, SPLIT END SUPPLIED WITH A 4 PIN FISHER CONNECTOR, 51mm(2.0") WORKING LENGTH. Includes Test Report and Certificate of conformance.	619P024			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR-9.5MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHz-2MHz, SHIELDED WITH A 4 PIN FISCHER CONNECTOR, 35mm WORKING LENGTH 9.5mmØ(.375") HEAD SIZE. Includes Test Report and Certificate of Conformance.	SEU-9.5-35			
AUR-9.5MSS/50MWL	HEAD SIZE. INCLUES TEST REPORT AND CENTRICATE OF CONTOMANCE. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 9.5mmØ HEAD SIZE. Includes TEST Report and Centrificate of Conformance.	RSM9-5-50			
AUR-9.5MSS/76MWL	STAINLESS STEEL ROTATING SCANNER PROBE, 100KHZ-2MHZ , 4 PIN FISCHER CONNECTOR 76MM WORKING LENGTH, 9.5mm@(3/8") HEAD. Includes Test Report and Certificate of Conformance.				
AUR-9.8MSS/50MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR S0mm WORKING LENGTH 9.8mmØ HEAD SIZE. Includes Test Report and Certificate of Conformance.	RSM9-8-50	MRS9-8-50		
AUR-9.8MSS/55MWL	ROHMANN STAINLESS STEEL ROTATING SCANNER PROBE 100KH2-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 9.8mm(386") Ø HEAD, 55mm(2.165") WORKING LENGTH. Includes Test Report anc Certificate of Conformance.	RSM9-8-55			
AURCS100125	100° DEGREE COUNTERSINK UNIVERSAL ROTATING SCANNER PROBE, .125Ø, 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURCS100156	100° DEGREE COUNTERSINK UNIVERSAL ROTATING SCANNER PROBE, .156Ø, 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	UC1.156	CSU100-10		
AURCS100187	100° DEGREE COUNTERSINK UNIVERSAL ROTATING SCANNER PROBE, .187Ø, 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	CSD100-12	CSD100-12	CRTP-001	
AURCS100218	100° DEGREE COUNTERSINK UNIVERSAL ROTATING SCANNER PROBE, .218°Ø, 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	CSU100-14			
AURCS100250	100° DEGREE COUNTERSINK UNIVERSAL ROTATING SCANNER PROBE, 250°Ø, 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	UC1.250	CSU100-16	CRTP-002	
AURCS100/4.0MSS	STAINLESS STEEL UNIVERSAL ROTATING SCANNER PROBE 100° COUNTER SINK, 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 4.0mmØ. Includes Test Report and Certificate of Conformance.	CSU100-4.0M-SS			
AURCS100/7.0MM	UNIVERSAL ROTATING SCANNER PROBE 100° COUNTER SINK, 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 7.0mmØ. Includes Test Report and Certificate of Conformance.				
AURCS100-12.6M/50M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 12.6 mm DIAMETER HEAD 50 MM WORKING LENGHTH. Includes Test Report and Certificate of Conformance.	RSK50/5/12/12.6/100			
AURCS100-3.0M	UNIVERSAL ROTATING SCANNER PROBE 100° DEGREE COUNTERSINK, 3.0mmØ 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURCS100-6.4MSS/50M	ROTATING SCANNER PROBE 100° COUNTER SINK 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 6.4 mm DIAMETER HEAD 50 MM WORKING LENGHTH. Includes Test Report and Certificate of Conformance.	RSMK50/5/12/6.4/100			
AURCSF100312	UNIVERSAL ROTATING SCANNER PROBE 100° DEGREES COUNTERSINK, 312"Ø(8.0mm), 100KHZ-2MHZ SHIELDED, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURCSF100375	UNIVERSAL ROTATING SCANNER PROBE 100° DEGREES COUNTERSINK, .375°Ø(9.5mm), 100KHZ-2MHZ SHIELDED, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AUR-D	EXTENSION HANDLE USED WITH FORRESTER INSTRUMENTS. Includes Certificate of Conformance.	RAU-D		•	
AURFB125SS/1.4WL	STAINLESS STEEL FLAT BOTTOM ROTATING PROBE, 1/8" ØDIAMETER100KHz-2MHz 1.4"WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURFB156SS/1.4WL	STAINLESS STEEL FLAT BOTTOM ROTATING PROBE, 5/32" DIAMETER100KHz-2MHz 1.4"WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RTPRB,SST,5/32,1.4"			
AURFB218	FLAT BOTTOM ROTARY PROBE, .218" Ø, 2.0" WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB312	FLAT BOTTOM ROTATING PROBE 100KHZ-2MHZ, 2.0" WL .312" Ø DIAMETER SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance				
AURFB312SE	FLAT BOTTOM ROTATING PROBE 100KHZ-2MHZ, 2.0" WL .312" Ø DIAMETER. EXPANDABLE FROM .312"325"Ø. SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance				
AURFB343	FLAT BOTTOM ROTATING PROBE 100KHZ-2MHZ, 2.0" WL .343" Ø DIAMETER SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance				
AURFB375	FLAT BOTTOM ROTATING PROBE 100KHZ-2MHZ, 2.0" WL .375" Ø DIAMETER SUPPLIED WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance				
AURFB528SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .528"Ø. Includes Test Report and Certificate of Conformance.	-			
AURFB560SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .560"Ø. Includes Test Report and Certificate of Conformance.				
AURFB575SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .575"Ø. Includes Test Report and Certificate of Conformance.				
AURFB590SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .590"Ø. Includes Test Report and Certificate of Conformance.				
AURFB593SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45DEG .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER=.593"Ø. Includes Test Report and Certificate of Conformance.				
AURFB600SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .600"Ø. Includes Test Report and Certificate of Conformance.				
AURFB609SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45DEG. 039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER=.609"Ø. Includes Test Report and Certificate of Conformance.				
AURFB625SS/2WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 5/8" (.625") Ø,2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB628/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LONG 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .628"Ø. Includes Test Report and Certificate of Conformance.			•	
AURFB660SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .660"Ø. Includes Test Report and Certificate of Conformance.				
AURFB6875SS/2WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 11/16"(.6875") Ø,2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFB690SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER=.690"Ø. Includes Test Report and Certificate of Conformance.				
AURFB700SE/2WL	ZMIRZ, PROBE PEAD DIAMETER* 500 W. Includes Test Report and Certificate of Conformance. UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES. 0.39"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- ZMIRZ. PROBE HEAD DIAMETER* - 700"Ø. Includes Test Report and Certificate of Conformance.				
AURFB728SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30-45 DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHZ- 2MHZ. PROBE HEAD DIAMETER= .728"Ø. Includes Test Report and Certificate of Conformance.				
AURFB750SS/2WL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 3/4"(.750") Ø,2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB8125SS/2WL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 13/16"(.8125") Ø,2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB828SS/2WL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 53/64"(.8281") Ø,2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB844SS/2WL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 27/32"(.8437") Ø,2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB859SS/2WL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 53/64" (.8593") Ø,2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB875SS/2WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 7/8"(.875") Ø,2.0" WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-10.0MSE/1.5WL	UNIVERSAL FLAT BOTTOM ROTARY PROBE (DELRIN) WITH A 30° COIL ANGLE, 10.0mmØ(0.394°), 40mm(1.5°) WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-10.0MSS/1.5WL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 10.0mm/0.394"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-10.2M/SS	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 10.2mm/0(0.402"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-10.3MSS/51MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 10.3mm/Ø(0.406"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.	UR10.3MFB/SS/15WL			
AURFB-10.6MM	FLAT BOTTOM ROTARY PROBE, 10.6mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-10.7MSS/51MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 10.7mm/0(0.421"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-10.8MSS/51MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 10.8mm/0(0.425"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-11.1MSS/51MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 11.1mm@(0.437"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.	UR11.1MFB/SS/15WL			
AURFB-11.2MSS/51MWL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 11.2mm/0.441 <sup>11</sup> ), 51mm(2.0 <sup>11</sup> ) WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-11.5MSS/51MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 11.5mm#(0.453"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.	UR11.5MFB/SS/15WL			
AURFB-11.6MSS/51MWL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 11.6mm/Ø(0.457"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-11.9MSS/51MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 11.9mm/0.0.469"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-12.0MSS/51MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 12.0mm/0(0.472"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-12.3MSS/51MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 12.3mm/0.484"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-12.4MSS/51MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 12.4mm/0(0.488"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-12.8MSS/51MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 12.8mm/Ø(0.504"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-13.2MSS/51MWL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 13.2mm/0(0.520"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-13.5MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 13.5MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-13.6MSS/51MWL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 13.6mm/0(0.535"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-13.9MSS/1.5WL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 13.9MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-14.0MSS/51MWL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 14.0mm/0.551"), 51mm(2.0") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-14.2MSS/1.5WL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 14.2MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-14.6MSS/1.5WL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 14.6MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-14.6MSS/50MWL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE, 14.6mm Ø, 50mm WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-15.0MSS/50MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE, 15.0mm Ø, 50mm WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-15.1MSS/1.5WL	STAINLESS STELE FLAT BOTTOM ROTARY PROBE 15.1MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.	•			
AURFB-15.4MSS/50MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE, 15.4mm Ø, 50mm WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFB-15.8MSS/50MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE, 15.8mm Ø, 50mm WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ.				
AURFB-16.2MSS/50MWL	Includes Test Report and Certificate of Conformance. STAINLESS STEL FLAT BOTTOM ROTARY PROBE, 16.2mm Ø, S0mm WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.	•			
AURFB-16.6MSS/50MWL	STAINLESS STEEL REPORT ON CERTIFICATE OF CONTONTANCE. STAINLESS STEEL FLAT BOTTOM ROTARY PROBE, 16.6mm Ø, 50mm WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-17.0MSS/50MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE, 17.0mm Ø, 50mm WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 100KH2-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-21.5MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES.039° DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96°) WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 21.5mmØ(.846°). Includes Test Report and Certificate of Conformance.	•		•	
AURFB-21.9MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES.039° DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96°) WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 21.9mmØ(.862°). Includes Test Report and Certificate of Conformance.	•		•	
AURFB-22.3MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES.039° DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96°) WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 22.3mmØ(.877°). Includes Test Report and Certificate of Conformance.	•		•	
AURFB-22.7MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 0.39" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KH2-2MHZ. PROBE HEAD DIAMETER = 22.7mmØ(.893"). Includes Test Report and Certificate of Conformance.	•			
AURFB-23.1MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 0.39" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KH2-2MHZ. PROBE HEAD DIAMETER = 23.1mmØ(.909"). Includes Test Report and Certificate of Conformance.	•			
AURFB-23.5MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 0.39" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 23.5mmØ(.925"). Includes Test Report and Certificate of Conformance.	•		•	
AURFB-23.9MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES.039° DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96°) WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 23.9mmØ(.940°). Includes Test Report and Certificate of Conformance.	•		•	
AURFB-24.3MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 0.39" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 24.3mmØ(.956"). Includes Test Report and Certificate of Conformance.			•	
AURFB-24.7MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES.039° DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96°) WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 24.7mmØ(.972°). Includes Test Report and Certificate of Conformance.	•			
AURFB-25.1MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 0.39" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 25.1mmØ(.988"). Includes Test Report and Certificate of Conformance.	•		•	
AURFB-25.5MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE [COIL ANGLE 30° DEGREES.039" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 25.5mmØ(1.003"). Includes Test Report and Certificate of Conformance.			•	
AURFB-25.9MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE [COIL ANGLE 30° DEGREES.039" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 25.9mmØ(1.019"). Includes Test Report and Certificate of Conformance.			•	
AURFB-26.3MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES.039° DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96°) WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 26.3mmØ(1.035°). Includes Test Report and Certificate of Conformance.	•			
AURFB-26.7MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES.039° DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96°) WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 26.7mmØ(1.051°). Includes Test Report and Certificate of Conformance.	•			
AURFB-27.1MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES.039° DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96°) WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 27.1mmØ(1.066°). Includes Test Report and Certificate of Conformance.	•		•	
AURFB-27.5MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 0.39" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KH2-2MHZ. PROBE HEAD DIAMETER = 27.5mmØ(1.082"). Includes Test Report and Certificate of Conformance.	•			
AURFB-27.9MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES.039° DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96°) WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 27.9mmØ(1.098°). Includes Test Report and Certificate of Conformance.	•		•	
AURFB-28.3MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 0.39" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KH2-2MHZ. PROBE HEAD DIAMETER = 28.3mmØ(1.114"). Includes Test Report and Certificate of Conformance.				
AURFB-28.7MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 0.39" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KH2-2MHZ. PROBE HEAD DIAMETER = 28.7mmØ(1.129"). Includes Test Report and Certificate of Conformance.	•			
AURFB-29.1MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 0.39" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KH2-2MHZ. PROBE HEAD DIAMETER = 29.1mmØ(1.145"). Includes Test Report and Certificate of Conformance.	•			
AURFB-29.5MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 039" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KH2-2MHZ. PROBE HEAD DIAMETER = 29.5mm/ (1.161"). Includes Test Report and Certificate of Conformance.	•			
AURFB-29.9MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 039" DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96") WORKING LENGTH 100KH2-2MHZ. PROBE HEAD DIAMETER = 29.9mmØ(1.177"). Includes Test Report and Certificate of Conformance.	•			
AURFB-3.0MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 3.0MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.	•		•	
AURFB-3.9MSS/1.5MWL	UNIVERSAL STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 3.9mm Ø,1.5"(38.1mm) WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.	•		•	
AURFB-30.3MSS/50MWL	UNIVERSAL ROTARY FLAT BOTTOM STAINLESS STEEL EDGE PROBE (COIL ANGLE 30° DEGREES. 0.39° DIA) 4 PIN FISCHER CONNECTOR 50mm(1.96°) WORKING LENGTH 100KH2-2MHZ. PROBE HEAD DIAMETER = 30.3mmØ(1.192"). Includes Test Report and Certificate of Conformance.	•			
AURFB30-14.3MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 14.3mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL		•	
AURFB30-14.7MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 14.7mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL		•	
AURFB30-15.1MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 15.1mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL		•	
AURFB30-15.5MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 15.5mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL			
AURFB30-15.9MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 15.9mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL		•	
AURFB30-16.3MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 16.3mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL			
AURFB30-16.7MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 16.7mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL		•	

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFB30-17.1MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 17.1mmØ, SOmm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL			
AURFB30-17.5MSS/50M	INUINE 30" DEGRES. Includes Test Report and Certificate of Comormance. UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 17.5mm/, SOmm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KH2-500KH2 INUINE 30" DEGRES. Includes Test Report and Certificate of Conformance.	RSM/SL			•
AURFB30-17.9MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 17.9mmØ, SOmm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz- INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL			
AURFB30-18.3MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 18.3mmØ, SOmm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-S00KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL	•		
AURFB30-18.7MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 18.7mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL			
AURFB30-19.1MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 19.1mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL			
AURFB30-19.5MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 19.5mm Ø, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL			
AURFB30-19.9MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 19.9mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL			
AURFB30-20.3MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 20.3mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL			
AURFB30-20.7MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 20.7mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL	•		
AURFB30-21.1MSS/50M	UNIVERSAL FLAT BOTTOM STAINLESS STEEL ROTARY PROBE, 21.1mmØ, 50mm WORKING LENGTH WITH 4 PIN FISCHER CONNECTOR, 300KHz-500KHz INLINE 30° DEGREES. Includes Test Report and Certificate of Conformance.	RSM/SL	•		
AURFB-4.0MSS/1.5WL	UNIVERSAL STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 4.0mm Ø,1.5"(38.1mm) WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.		•		
AURFB-4.7MM	FLAT BOTTOM ROTARY PROBE, 4.7mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-4.7MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 4.7MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance				
AURFB-4.8MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 4.8MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance				
AURFB-5.0MSE/1.5WL	UNIVERSAL FLAT BOTTOM ROTARY PROBE SPLIT END (DELRIN) WITH A 30° COIL ANGLE 5.0mmø/(0.196"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-5.0MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 5.0mm#(0.196"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.		•		
AURFB-5.1MM	FLAT BOTTOM ROTARY PROBE, 5.1mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-5.1MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 5.1MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance				
AURFB-5.4MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 5.4MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance		•		
AURFB-5.5M/40MWL	FIXED UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30°-45° DEGREES .039°DIA) SLIGHTLY RECESSED, 4 PIN FISCHER CONNECTOR 40mm WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER= 5.5mm Ø. Includes Test Report and Certificate of Conformance.				
AURFB-5.5M/51MWL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30° DEGREES.039"DIA) 4 PIN FISCHER CONNECTOR 51mm(2.0") WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 5.5mmØ(0.2165"). Includes Test Report and Certificate of Conformance.		•		
AURFB-5.5MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 5.5mmØ(0.2165"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-5.6MM	FLAT BOTTOM ROTARY PROBE, 5.6mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-5.7M/51MWL	UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30° DEGREES. 039"DIA) 4 PIN FISCHER CONNECTOR 51mm(2.0") WORKING LENGTH 100KHZ-2MHZ. PROBE HEAD DIAMETER = 5.7mmØ(0.224"). Includes Test Report and Certificate of Conformance.				
AURFB-5.8MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 5.8MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-6.0MSE/1.5WL	UNIVERSAL FLAT BOTTOM ROTARY PROBE (DELRIN) WITH A 30° COIL ANGLE, 6.0mm/Ø(0.236°), 40mm(1.5°) WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-6.0MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 6.0mm Ø(0.236"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-6.25MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 6.25MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance				
AURFB-6.2MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 6.2MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-6.3MM	FLAT BOTTOM ROTARY PROBE, 6.3mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-6.4MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 6.4MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance				
AURFB-6.5MSE/1.5WL	UNIVERSAL FLAT BOTTOM ROTARY PROBE (DELRIN) WITH A 30° COIL ANGLE 6.0mm/g(0.256°), 40mm(1.5°) WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-6.5MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 6.0mm#(0.256"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-6.6MM	FLAT BOTTOM ROTARY PROBE, 6.6mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-6.6MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 6.6MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFB-6.7MM	FLAT BOTTOM ROTARY PROBE, 6.7mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-7.0MM	EXPERIMENTED FOR THE ADDRESS OF THE				
AURFB-7.0MSE/1.5WL	UNIVERSAL FLAT BOTTOM ROTARY PROBE (DELRIN) WITH A 30° COIL ANGLE, 7.0mmø(0.276"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-7.0MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 7.0mm#(0.276"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-7.1MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 7.1MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance				-
AURFB-7.3MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 7.3MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-7.4MM	FLAT BOTTOM ROTARY PROBE, 7.4mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-7.6MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 7.3MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				-
AURFB-7.8MM	FLAT BOTTOM ROTARY PROBE, 7.8mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-7.8MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 7.8MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance				
AURFB-8.0MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 8.0mm#(0.315"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-8.2MM	FLAT BOTTOM ROTARY PROBE, 8.2mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-8.2MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 8.2MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
AURFB-8.6MM	FLAT BOTTOM ROTARY PROBE, 8.6mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-8.6MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 8.6MM Ø,1.5" WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				-
AURFB-8.9MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 8.9MM Ø,1.5"WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance				
AURFB-8.9MSS/50MWL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 8.9MM Ø, 50MM WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance				
AURFB-9.0M/SS	STAINLESS STEEL ROTARY FLAT BOTTOM PROBE, 9.0mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-9.0MSS/1.5WL	STAINLESS STEEL FLAT BOTTOM ROTARY PROBE 9.0mm Ø(0.354"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				-
AURFB-9.1M/SS	STAINLESS STEEL ROTARY FLAT BOTTOM PROBE, 9.1mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-9.4MM	FLAT BOTTOM ROTARY PROBE, 9.4mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFB-9.5MSS/50M	STAINLESS STEEL ROTARY FLAT BOTTOM PROBE, 9.5mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KH2-2MH2. Includes Test Report and Certificate of Conformance.	RSMA 50/9.5			
AURFB-9.8MM	FLAT BOTTOM ROTARY PROBE, 9.8mm Ø, 50mm WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFBFX375SS/100MWL	STAINLESS STEEL FLEXIBLE ROTARY FLAT BOTTOM PROBE 100mm WORKING LENGTH, 9.525mmØ(.375") HEAD .750" LONG TIP, 4 PIN FISCHER CONNECTOR 100KH2-2MHZ (TAPERED END OF THE PROBE WITH 30° COIL ANGLE) per Airbus NTM 51-10-18. Includes Test Report and Certific				
AURFBFX500SS/100MWL	STAINLESS STEEL FLEXIBLE ROTARY FLAT BOTTOM PROBE 100mm WORKING LENGTH, 12.7mmØ(.500") HEAD. 750" LONG TIP, 4 PIN FISCHER CONNECTOR 100KH2-2MHZ (TAPERED END OF THE PROBE WITH 30" COIL ANGLE) per Airbus NTM 51-10-18. Includes Test Report and Certifica				
AURFBSE-5.5M/40MWL	STANDARD UNIVERSAL EXPANDABLE FLAT BOTTOM ROTARY EDGE PROBE ( CENTERED COIL ), 4 PIN FISCHER CONNECTOR 40mm(1.57") WORKING LENGTH 100KHZ-2MHZ. EXPANDABLE PROBE HEAD DIAMETER=5.5mm(0.2165Ø - APPROXIMATELY 6.91mmØ 0.272"Ø. Includes Test Report and C				
AURFBSE-6.0M/51MWL	STANDARD UNIVERSAL EXPANDABLE FLAT BUTTOM RUTART EUGE PROBE (LENTERED CUIL), 4 PIN FISCHER CUNNECTOR SIMML2.0] WORKING LENGTH 100KHz-2MHz. EXPANDABLE PROBE HEAD DIAMETER= 8.0mm(0.236 <sup>+</sup> Ø) - 10.0mmØ(.315 <sup>+</sup> Ø). Includes Test Report and Certificate of Conformation				•
AURFBSE-8.0M/51MWL	STANDARD ONIVERSAL EXPANDABLE FLAT BOTTOM ROTARY EDGE PROBE ( CENTERED COIL ) , 4 PIN FISCHER CONNECTOR STIMM(2.0") WORKING LENGTH 100KH2-2MH2. EXPANDABLE PROBE HEAD DIAMETER= 8.0mm(0.315"Ø) - 10.0mmØ(.394"Ø). Includes Test Report and Certificate of Conferences				
AURFX156/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH COLLAR .156" DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.				
AURFX156/9WL	FLEXIBLE ROTARY PROBE 9.0" WORKING LENGTH WITH COLLAR .156" DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, Includes Test Report and Certificate of Conformance.				
AURFX156SE/4WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 4.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, EXPANDABLE FROM .156"187"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certificate of Conformance.				
AURFX156SE/6WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KH2-2MH2 ,4-PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 6.0" WORKING LENGTH750" TIP LENGTH SPLIT END, EXPANDABLE FROM .156"187". Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certif				
AURFX156SS/100MWL	FLEX SHAFT PROBE, STAINLESS STEEL, 100KHz-2MHz, 3-93"(100mm)WORKING LENGTH, 12mm(.472") TIP LENGTH, 5/32Ø (.156") SUPPLIED WITH A 4 PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURFX187/6WL-1	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END WITH NO STEP & NO SLEEVE(THROUGH HOLE STYLE), .187"Ø. Includes Test Report and Certificate of Conformance.	UFLX.187/6WL			
AURFX187/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH COLLAR .187"Ø DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.	EMFLX.187/8WL			
AURFX187/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR.187" DIA HEAD WITH A 4 PIN FISCHER CONNECTOR,100KHZ-2MHz. Includes Test Report and Certificate of Conformance.	EMFLX.187/9L			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFX187/9WL	FLEXIBLE ROTARY PROBE 9.0" WORKING LENGTH WITH COLLAR .187"Ø DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, Includes Test Report and Certificate of Conformance				
AURFX187SE/.5T/4WL	Report and Certificate of Conformance. ADJUSTABLE FLEX SHAFT ROTARY PROBE, SPLIT END, .187"218", 0.500" LONG TIP, 4.0" WORKING LENGTH ( NO SLEEVE). 4 PIN FISCHER CONNECTOR 100KHz-2MHz. Includes Test Report and Certificate of Conformance.	TEK-3005U.190SE/4WL			
AURFX187SE/4WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ /A PIN FISCHER CONNECTOR 4.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, EXPANDABLE FROM .18"				
AURFX187SE/4WL-2	ADJUSTABLE FLEX SHAFT ROTARY PROBE .187"218" 4.0" WORKING LENGTH 2.0" TIP 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ( WITH SLEEVE). Includes Test Report and Certificate of Conformance.	•			
AURFX187SE/6WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 6.0" WORKING LENGTH750" TIP LENGTH SPLIT END, EXPANDABLE FROM .187"218"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certif	AFRTP-001			
AURFX187SE/8WL	FLEXIBLE UNIVERSAL ROTARY PROBE, SPLIT END 0.187"-0.250" WITH SLEEVE 100KHz-2MHz ,4 PIN FISCHER CONNECTOR, 8.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•	•		
AURFX187SS/100MWL	FLEX SHAFT PROBE, STAINLESS STEEL, 100KHz-2MHz, 3.93"(100mm)WORKING LENGTH, 12mm(.472") TIP LENGTH, 3/16"Ø (.187") SUPPLIED WITH A 4 PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AURFX218/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 6.0" WORKING LENGTH700" TIP LENGTH SPLIT END, .218"Ø. Includes Test Report.	•	•		
AURFX218SE/4WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 4.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, EXPANDABLE FROM .218"250"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certificate of Conformance.		•		
AURFX218SE/6WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 6.0" WORKING LENGTH750" TIP LENGTH SPLIT END, EXPANDABLE FROM .218"250"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certif	•			
AURFX250/6WL-1	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR 6.0° WORKING LENGTH. 1.5° TIP LENGTH SPLIT END WITH NO STEP & NO SLEEVE(THROUGH HOLE STYLE), .250°Ø. Includes Test Report and Certificate of Conformance.	UFLX.250/6WL			
AURFX250/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH COLLAR 250"Ø DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.	EMFLX.250/8WL			
AF-5173/4MM	Custom Eddy Current Encirling Probe, 4mm tube (outer diameter), S0KHz-S00kHz, bridge differential, Supplied with a Triax Fischer Connector. Includes Test Report and Certificate of Conformance.		•		
AURFX250/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR .250" DIA HEAD WITH A 4 PIN FISCHER CONNECTOR,100KHZ-2MHz. Includes Test Report and Certificate of Conformance.	EMFLX.250/9L			
AURFX250/9WL	FLEXIBLE ROTARY PROBE 9.0" WORKING LENGTH WITH COLLAR .250" DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, Includes Test Report and Certificate of Conformance.		•		
AURFX250SE/.5T/4WL	ADJUSTABLE FLEX SHAFT ROTARY PROBE, SPLIT END, .250"312", 0.500" LONG TIP, 4.0" WORKING LENGTH (NO SLEEVE). 4 PIN FISCHER CONNECTOR 100KHz-2MHz. Includes Test Report and Certificate of Conformance.		•		
AURFX250SE/4WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 4.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, EXPANDABLE FROM .250"281"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certificate of Conformance.	•	•		
AURFX250SE/4WL-2	ADJUSTABLE FLEX SHAFT ROTARY PROBE .250312" 4.0" WORKING LENGTH 2.0" TIP 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ( NO SLEEVE). Includes Test Report and Certificate of Conformance.		•		
AURFX250SE/5.5WL	FLEXIBLE UNIVERSAL ROTARY PROBE 200KHZ-3MHZ, 4 PIN FISCHER CONNECTOR 5.5" WORKING LENGTH. EXPANDABLE FROM 0.250"-0.281" WITH SLEEVE. Includes Test Report and Certificate of Conformance.				
AURFX250SE/6WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 6.0" WORKING LENGTH750" TIP LENGTH SPLIT END, EXPANDABLE FROM .250"281"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certificate of Conformance.	AFRTP-002			
AURFX250SE/8WL	FLEXIBLE UNIVERSAL ROTARY PROBE, SPLIT END 0.250"-0.312" WITH SLEEVE 100KHz-2MHz ,4 PIN FISCHER CONNECTOR, 8.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.		•		
AURFX281SE/4WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 4.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, EXPANDABLE FROM .281"312"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certificate of Conformance.				
AURFX281SE/5.5WL	FLEXIBLE UNIVERSAL ROTARY PROBE 200KHZ-3MHZ ,4 PIN FISCHER CONNECTOR 5.5" WORKING LENGTH. EXPANDABLE FROM 0.281"-0.312" WITH SLEEVE. Includes Test Report and Certificate of Conformance.				
AURFX281SE/6WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100kHZ-2MHZ ,4-PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 6.0" WORKING LENGTH750" TIP LENGTH SPLIT END, EXPANDABLE FROM281". 312"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certif				
AURFX312/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH COLLAR 312"Ø DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.	EMFLX.312/8WL			
AURFX312/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR .312"Ø DIA HEAD WITH A 4 PIN FISCHER CONNECTOR,100KHZ-2MHz. Includes Test Report and Certificate of Conformance.	EMFLX.312/9L	VMUR101SF-5/16		
AURFX312/9WL	FLEXIBLE ROTARY PROBE 9.0" WORKING LENGTH WITH COLLAR .312" DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, Includes Test Report and Certificate of Conformance.				
AURFX312SE/.5T/4WL	ADJUSTABLE FLEX SHAFT ROTARY PROBE, SPLIT END, .312"375", 0.500" LONG TIP, 4.0" WORKING LENGTH (NO SLEEVE). 4 PIN FISCHER CONNECTOR 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFX312SE/1.5T/9L	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 9.0" TOTAL LENGTH. 1.5" TIP LENGTH SPLIT END. Includes Test Report and Certificate of Conformance.				
AURFX312SE/12WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100kHZ-2MHZ ,4-PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 12.0" WORKING LENGTH, .750" TIP LENGTH SPLIT END, EXPANDABLE FROM .312"375"Ø. Includes Test Report and Certificate of Conformance.				
AURFX312SE/4WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4 PIN FISCHER CONNECTOR 4.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, EXPANDABLE FROM .312"375"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certificate of Conformance.				
AURFX312SE/5.5WL	FLEXIBLE UNIVERSAL ROTARY PROBE 200KHZ-3MHZ ,4 PIN FISCHER CONNECTOR 5.5" WORKING LENGTH. EXPANDABLE FROM 0.312"-0.375" WITH SLEEVE. Includes Test Report and Certificate of Conformance.				
AURFX312SE/6WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100kHZ-2MHZ ,4-PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 6.0" WORKING LENGTH750" TIP LENGTH SPLIT END, EXPANDABLE FROM .312"375"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certif	AFRTP-003			
AURFX312SE/8WL	FLEXIBLE UNIVERSAL ROTARY PROBE, SPLIT END 0.312"-0375" WITH SLEEVE 100KHz-2MHz ,4 PIN FISCHER CONNECTOR, 8.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AURFX375/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH COLLAR 375"Ø DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.	EMFLX.375/8WL			
AURFX375SE/.5T/4WL	ADJUSTABLE FLEX SHAFT ROTARY PROBE, SPLIT END, .375"437", 0.500" LONG TIP, 4.0" WORKING LENGTH (NO SLEEVE). 4 PIN FISCHER CONNECTOR 100KHz-2MHz. Includes Test Report and Certificate of Conformance.	•			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFX375SE/4WL	ADJUSTABLE FLEX SHAFT ROTARY PROBE .375437" 4.0" WORKING LENGTH 1.5" TIP 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ( NO SLEEVE). Includes Test Report and Certificate of Conformance.				
AURFX375SE/6WL	Test Report and Certificate or Conformance. UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4-PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 6.0" WORKING LENGTH750" TIP LENGTH SPLIT END, EXPANDABLE FROM .375"437"/B. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certif				
AURFX437/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH COLLAR .437"Ø DIA: HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.	EMFLX.437/8WL			
AURFX437/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR .437" DIA HEAD WITH A 4 PIN FISCHER CONNECTOR, 100KHZ-2MHz. Includes Test Report and Certificate of Conformance.	EMFLX.437/9L			
AURFX437SE/.5T/4WL	ADJUSTABLE FLEX SHAFT ROTARY PROBE, SPLIT END, .437"S00", 0.500" LONG TIP, 4.0" WORKING LENGTH (NO SLEEVE). 4 PIN FISCHER CONNECTOR 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
ATPN-95-5/500K	RIGID SURFACE PROBE125 Ø TIP 90° DEGREES .500° DROP, TRIAX FISCHER CONNECTOR 350KHz - 3MHz. Includes Test Report and Certificate of Conformance.	DPT90-011			
ATPN-93-14/500K	RIGID SURFACE PROBE, 90". 300" DROP, TRIAX FISCHER CONNECTOR, 350KHz-3MHz, 14.0" LONG. Includes Test Report and Certificate of Conformance.				
ARR-1.50/10.5WL	ROTARY PROBE 4 PIN STEP LEMO (STAVELY MINI MITE) 1.50" DIAMETER, 10.5" WORKING LENGTH 100KHZ-2MHZ Includes Test Report and Certificate of Conformance				
ARR-1.0/10.5WL	ROTARY PROBE 4 PIN STEP LEMO (STAVELY MINI MITE) 1.00" DIAMETER, 10.5" WORKING LENGTH 100KHZ-2MHZ Includes Test Report and Certificate of Conformance				
ARR562/12.5WL	ROTARY PROBE 4 PIN STEP LEMO (STAVELY MINI MITE) 0.562" DIAMETER, 12.5" WORKING LENGTH 100KHZ-2MHZ Includes Test Report and Certificate of Conformance				
ARR562/6.5WL	ROTARY PROBE 4 PIN STEP LEMO (STAVELY MINI MITE) 0.562" DIAMETER, 6.5" WORKING LENGTH 100KHZ-2MHZ Includes Test Report and Certificate of Conformance				
ATMH-1.50/10.5WL/500K	MANUAL BOLT HOLE PROBE 1.50" DIAMETER, 350KHz-3MHz UNSHIELDED WITH COLLAR, ABSOLUTE COIL, TRIAX FISCHER CONNECTOR, 10.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance				
ATMH-1.0/10.5WL/500K	MANUAL BOLT HOLE PROBE 1.0" DIAMETER, 350KHz-3MHz UNSHIELDED WITH COLLAR, ABSOLUTE COIL, TRIAX FISCHER CONNECTOR, 10.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance				
ATMH562/12.5WL/500K	MANUAL BOLT HOLE PROBE 0.562" DIAMETER, 350KHz-3MHz UNSHIELDED WITH COLLAR, ABSOLUTE COIL, TRIAX FISCHER CONNECTOR, 12.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance				
ATMH562/6.5WL/500K	MANUAL BOLT HOLE PROBE 0.562" DIAMETER, 350KHz-3MHz UNSHIELDED WITH COLLAR, ABSOLUTE COIL, TRIAX FISCHER CONNECTOR, 6.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance				
AURFX437SE/6WL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHZ-2MHZ ,4-PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 6.0" WORKING LENGTH750" TIP LENGTH SPLIT END, EXPANDABLE FROM .437"500"Ø. Compatible with Olympus Minimite Part Number 9020266. Includes Test Report and Certif				
AURFX469SS/100MWL	FLEX SHAFT PROBE, STAINLESS STEEL, 100KHz-2MHz, 3.93"(100mm)WORKING LENGTH, 12mm(.472") TIP LENGTH, 15/32Ø (.469") SUPPLIED WITH A 4 PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURFX500/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH COLLAR. 500"Ø DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.	EMFLX.500/8WL			
AURFX500/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR .500" DIA HEAD WITH A 4 PIN FISCHER CONNECTOR,100KHZ-2MHz. Includes Test Report and Certificate of Conformance	EMFLX.500-9L			
AURFX500SE/.5T/4WL	ADJUSTABLE FLEX SHAFT ROTARY PROBE, SPLIT END, .500"562", 0.500" LONG TIP, 4.0" WORKING LENGTH (NO SLEEVE). 4 PIN FISCHER CONNECTOR 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFX500SE/6WL	FLEXIBLE UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, A PIN FISCHER CONNECTOR, INCLUDES SLEEVE. 6.0" WORKING LENGTH750" TIP LENGTH SPLIT END, .500"Ø. Includes Test Report and Certificate of Conformance.				
AURFX500SS/100MWL	FLEX SHAFT PROBE, STAINLESS STEEL, 100KHz-2MHz, 3.93"(100mm)WORKING LENGTH, 12mm(.472") TIP LENGTH, 1/2"Ø (.500") SUPPLIED WITH A 4 PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURFX562SE/.5T/4WL	ADJUSTABLE FLEX SHAFT ROTARY PROBE, SPLIT END,562"625", 0.500" LONG TIP, 4.0" WORKING LENGTH (NO SLEEVE). 4 PIN FISCHER CONNECTOR 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFX625/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH COLLAR 625"Ø DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.	EMFLX.625/8WL			
AURFX625SE/.5T/4WL	ADJUSTABLE FLEX SHAFT ROTARY PROBE, SPLIT END, .625"687", 0.500" LONG TIP, 4.0" WORKING LENGTH (NO SLEEVE). 4 PIN FISCHER CONNECTOR 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFX750/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH COLLAR .750" DIA. HEAD WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.	EMFLX.750/8WL			
AURFX750SE/.5T/4WL	ADJUSTABLE FLEX SHAFT ROTARY PROBE, SPLIT END, .750"875", 0.500" LONG TIP, 4.0" WORKING LENGTH (NO SLEEVE). 4 PIN FISCHER CONNECTOR 100KHz-2MHz. Includes Test Report and Certificate of Conformance.				
AURFX750SE/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH SLEEVE, EXPANDABLE FROM .750"875" Ø DIAMETER WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.				
AURFX875/9L	FLEXIBLE ROTARY PROBE 9.0" LONG WITH COLLAR.875"Ø DIA HEAD WITH A 4 PIN FISCHER CONNECTOR,100KHZ-2MHz. Includes Test Report and Certificate of Conformance.	VMUR101SF-7/8	VMUR101SF-7/8		
AURFX875SE/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH SLEEVE, EXPANDABLE FROM .875"-1.00"Ø DIAMETER WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.				
AURFX-1.0SE/8WL	FLEXIBLE ROTARY PROBE 8.0" WORKING LENGTH WITH SLEEVE, EXPANDABLE FROM 1.00"-1.125"Ø DIAMETER WITH A 4 PIN FISCHER CONNECTOR 100KHz-2MHz, 9.0" OVERALL LENGTH. Includes Test Report and Certificate of Conformance.				
AURFX-10/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH (.156") 4 PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance				
AURFX-10MSE/100MWL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHz-2MHz, A PIN FISCHER CONNECTOR 4.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, EXPANDABLE FROM 10-12mmØ. Includes Test Report and Certificate of Conformance.				
AURFX-11/64SS/4WL	FLEX PROBE 100KHZ-2MHZ, 4"WL, STAINLESS STEEL 12mm TIP LENGTH (.171") 4 PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURFX-12/64SS/4WL	FLEX SHAFT PROBE, STAINLESS STEEL, 100KHz-2MHz, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 4.75mmØ (.187") SUPPLIED WITH A 4 PIN FISHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURFX-12MSE/100MWL	UNIVERSAL FLEXIBLE ROTARY PROBE 100KHz-2MHz, 4 PIN FISCHER CONNECTOR 4.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, EXPANDABLE FROM 12-14mmØ. Includes Test Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EOUIVALENT	EOUIVALENT
AUREX-14/64SS/4WL	DESCRIPTION FLEX SHAFT PROBE 100KHZ-2MHZ, 4.0"WORKING LENGTH, STAINLESS STEEL, 12mm TIP LENGTH (.203") WITH A 4 PIN FISHER CONNECTOR. Includes	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFX-14/0433/4WL	Test Report and Certificate of Conformance. UNIVERSAL FLEXIBLE ROTARY PROBE 100KHz-2MHz ,4 PIN FISCHER CONNECTOR 4.0" WORKING LENGTH. 1.5" TIP LENGTH SPLIT END, EXPANDABLE	•		•	
AURFX-18/64SS/4WL	FROM 12-14mmØ. Includes Test Report and Certificate of Conformance. FLEX SHAFT PROBE, STAINLESS STEEL, 100KH2-2MH2, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 7.14mmØ (.281") SUPPLIED WITH A 4 PIN INCLUDED AND ADDRESS STEEL, 100KH2-2MH2, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 7.14mmØ (.281") SUPPLIED WITH A 4 PIN INCLUDED ADDRESS STEEL, 100KH2-2MH2, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 7.14mmØ (.281") SUPPLIED WITH A 4 PIN INCLUDED ADDRESS STEEL, 100KH2-2MH2, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 7.14mmØ (.281") SUPPLIED WITH A 4 PIN INCLUDED ADDRESS STEEL, 100KH2-2MH2, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 7.14mmØ (.281") SUPPLIED WITH A 4 PIN INCLUDED ADDRESS STEEL, 100KH2-2MH2, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 7.14mmØ (.281") SUPPLIED WITH A 4 PIN INCLUDED ADDRESS STEEL, 100KH2-2MH2, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 7.14mmØ (.281") SUPPLIED WITH A 4 PIN INCLUDED ADDRESS STEEL, 100KH2-2MH2, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 7.14mmØ (.281") SUPPLIED WITH A 4 PIN INCLUDED ADDRESS STEEL, 100KH2-2MH2, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 7.14mmØ (.281") SUPPLIED WITH A 4 PIN INCLUDED ADDRESS STEEL, 100KH2-2MH2, 4.0"WORKING LENGTH, 12mm(.472") TIP LENGTH, 7.14mmØ (.281") SUPPLIED WITH A 4 PIN INCLUDED ADDRESS STEEL, 4.0"WORKING LENGTH, 4.0"WORKING LENGTH			·	
AURFX-375SE/8WL	FISHER CONNECTOR. Includes Test Report and Certificate of Conformance. FLEXIBLE UNIVERSAL ROTARY PROBE, SPUT END 0.375"-0437" WITH SLEEVE 100KHz-2MHz ,4 PIN FISCHER CONNECTOR, 8.0" WORKING LENGTH.				
AURFX-6.1MSS/90MWL	Includes Test Report and Certificate of Conformance. FLEXIBLE ROTARY PROBE 100K-2MHZ, STAINLESS STEEL HEAD 6.1mmØ, 90MM WORKING LENGTH, 4 PIN FISCHER CONNECTOR. Includes Test Report and	RSMF-ATR-6.1			
AURFX-6.3MSS/90MWL	Certificate of Conformance. FLEXIBLE ROTARY PROBE 100K-2MHZ, STAINLESS STEEL HEAD 6.3mmØ, 90MM WORKING LENGTH, 4 PIN FISCHER CONNECTOR. Includes Test Report and	RSMF-ATR-6.3		-	
AURFX-6.5MSS/90MWL	Certificate of Conformance. FLEXIBLE ROTARY PROBE 100K-2MHZ, STAINLESS STEEL HEAD 6.5mmØ, 90MM WORKING LENGTH, 4 PIN FISCHER CONNECTOR. Includes Test Report and	RSMF-ATR-6.5		•	
AUR-RA	Certificate of Conformance. ADAPTOR FOR UNIVERSAL SCANNER (4 PIN FISCHER) TO RA RECHII PROBE (4 PIN STEP LEMO CONNECTOR). Includes Test Report and Certificate of	UR-SA	SA-EMR	U8767051	
AUK-KA	Conformance.	UR-SA	SA-EMR	08767051	
AUR-UR/3L	ROTARY ADAPTOR: MALE 4 PIN FISCHER TO FEMALE 4 PIN FISCHER. 3.0" INCH OVERALL LENGTH. Includes Certificate of Conformance.	•		•	
AUR-UR/5L	ROTARY ADAPTOR: MALE 4 PIN FISCHER TO FEMALE 4 PIN FISCHER. 5.0" INCH OVERALL LENGTH. Includes Certificate of Conformance.				
AUR-UR-4	ROTARY ADAPTOR: MALE 4 PIN FISCHER TO FEMALE 4 PIN FISCHER. 4 INCHES LONG. Includes Certificate of Conformance.			•	
AUR-UR-6	ROTARY ADAPTOR: MALE 4 PIN FISCHER TO FEMALE 4 PIN FISCHER. 6 INCHES LONG. Includes Certificate of Conformance.		,	,	,
AUR-URFX-8	FLEXIBLE ROTARY PROBE ADAPTOR MALE 4 PIN FISCHER TO RECEPTACLE (FEMALE) 8.0"(203mm) WORKING LENGTH. Includes Certificate of Conformance.			•	
AURX187250	ADJUSTABLE ROTARY X-PROBE, 187"- 250" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	BXEM-12/16,HRX.187250	EMRX.187250, BXU- 12/16	AFRTP-001, BXEM-12/16	HRX.187250
AURX250312	ADJUSTABLE ROTARY HOLE X-PROBE ".250312" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	HRX.250312	EMRX.250312	HRX.250312	BXU-16/20
AURX312375	ADJUSTABLE ROTARY X-PROBE .312"375" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	BXU-20/24	EMRX.312375	HRX.312375	
AURX375437	ADJUSTABLE ROTARY X-PROBE ".375437" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR, 2.0" INCH WORKING LENGTH. Includes Test Report and Certificate of Conformance.	EMRX.375437	EMRX.375437	BXU-24/28	
AURX500625	ADJUSTABLE ROTARY X-PROBE .500"625" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	BXU-32/40	EMRX.500625	•	
AURX625750	ADJUSTABLE ROTARY X-PROBE .625"750" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	BXU-40/48		•	
AURX725875	ADJUSTABLE ROTARY X-PROBE .725"875" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" INCH WORKING LENGTH. Includes Test Report and Certificate of Conformance	•		•	
AURX750875	ADJUSTABLE ROTARY X-PROBE .750"875" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	BXU-48/56	EMRX.750875	•	
AURX750-875/4WL	ADJUSTABLE ROTARY X-PROBE .750"875" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 4.0" INCH WORKING LENGTH.I Includes Test Report and Certificate of Conformance	EMRX.725-0.875		•	
AURX875-1.0	ADJUSTABLE ROTARY X-PROBE .875"-1.0" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	BXU-56/64	EMRX.875-1.0		
AURX936-1.0/2WL	ADJUSTABLE ROTARY "X" PROBE. EXPANDABLE FROM. 936"-1.0"Ø. 2.0" WORKING LENGTH WITH A 4 PIN FISCHER CONNECTOR, 100KHz-2MHz. Includes Test Report and Certificate of Conformance.	TEK-3038			
AURX-1.310-1.435/2.0WL	ADJUSTABLE ROTARY HOLE X-PROBE. EXPANDABLE FROM 1.310"-1.435"Ø 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURX-1.750-1.875/2.0WL	ADJUSTABLE ROTARY HOLE X-PROBE. EXPANDABLE FROM 1.750"-1.875"Ø 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	•
AURX10-12MM	ADJUSTABLE ROTARY X-PROBE, 2.75SHAFT, EXPANDABLE FROM 10.0mm - 12.0mm 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 70mm WORKING IFNGTH Includes Test Report and Certificate of Conformance.	RSMVS10-12			
AURX-2.20-2.325	ADJUSTABLE "X" ROTAY HOLE PROBE 100KHz-2MHz, 2.20"Ø-2.325"Ø with a 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-3160-2.2/2.325-U	NEC-3160		
AURX-2.31-2.435	Conformance. ADJUSTABLE "X" ROTARY HOLE PROBE 100KHz-2MHz, 2.31"Ø-2.435"Ø with a 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	NEC-3160-2.31/2.435-U	NEC-3160		
AURX-2.56-2.685	LONTOTMARCE. ADJUSTABLE "X" ROTARY HOLE PROBE 100KHz-2MHz, 2.56"Ø-2.685"Ø with a 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	NEC-3160-2.56/2.685-U	NEC-3160	•	-
AURX-3.17-3.29/2WL	ADJUSTABLE ROTARY HOLE X-PROBE. EXPANDABLE FROM 3.17"-3.29" 0100KHz-2MHz 4 PIN FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes	BXEM-3.17-3.29			
AURX-5.0-6.0M/30MWL	Test Report and Certificate of Conformance. ADJUSTATEL ROTARY 2-ROBE EXPANDABLE FROM 5.0mm - 6.0mm 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 30mm WORKING LENGTH.	•			
AURXF312375	Includes Test Report and Certificate of Conformance. ADJUSTABLE ROTARY X-PROBE FERRITE SHIELDED, 312"- 375" 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of	BXUF-20/24			
AURY125156	Conformance. UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 1.3" WORKING LENGTH, EXPANDABLE .125"156". Includes Test Report and	URY.125156	ARTP-002	BYU-8/10	
AURY125156/1.5WL	Certificate of Conformance. UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 1.5" WORKING LENGTH, EXPANDABLE .125"156". Includes Test Report and	011.123*.130	ANT -002	510-0/10	
	Certificate of Conformance. UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 1.75" WORKING LENGTH, EXPANDABLE .125"156". Includes Test Report and				
AURY125156/1.75WL	Certificate of Conformance.	ARTP-002		·	

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURY125156/3.0WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 3.0" WORKING LENGTH, EXPANDABLE .125"156". Includes Test Report and				
AURY125156/3.50AL	Certificate of Conformance. UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 3.5" OVERALL LENGTH .125"437" Includes Test Report and Certificate of Conformance.	•			
AURY156187	Communator: UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 1.3" WORKING LENGTH EXPANDABLE FROM .156"187". Includes Test Report and Certificate of Conformance.	URY.156187	ARTP-001		
AURY156187/1.5WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 1.5" WORKING LENGTH EXPANDABLE FROM .156". 187". Includes Test Report and Certificate of Conformance.			•	
AURY156187/1.75WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 1.75" WORKING LENGTH EXPANDABLE FROM .156".187". Includes Test Report and Certificate of Conformance.	ARTP-003			
AURY187218	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4PIN FISCHER CONNECTOR 1.3" WORKING LENGTH, EXPANDABLE .187"218". Includes Test Report and Certificate of Conformance.	URY.187218	ARTP-001	•	
AURY187218/1.75WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 1.75" WORKING LENGTH, EXPANDABLE .187"-218". Includes Test Report and Certificate of Conformance.	ARTP-031		•	
AURY187218/3.50AL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 3.5" OVERALL LENGTH .187"218". Includes Test Report and Certificate of Conformance.			•	
AURY187218/3WL	UNIVERSAL ADJUSTABLE ROTARY PROBE 3.0" WORKING LENGTH, EXPANDABLE FROM .187"218" 100KHz-2MHz, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AURY187250	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 1.3" WORKING LENGTH. EXPANDABLE FROM .187"250". Includes Test Report and Certificate of Conformance.	URY.187250 , BYU-12/16			
AURY187250/1.5WL	UNIVERSAL ROTARY PROBE 100KH2-2MHZ, 4PIN FISCHER CONNECTOR 1.5" WORKING LENGTH. EXPANDABLE FROM .187"250". Includes Test Report and Certificate of Conformance.	•			
AURY187250/2WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 2.0" WORKING LENGTH. EXPANDABLE FROM .187"250". Includes Test Report and Certificate of Conformance.	URY.187250			
AURY218250	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 1.3" WORKING LENGTH, EXPANDABLE .218"250". Includes Test Report and Certificate of Conformance.	URY.218250	RTP-004		
AURY218250/1.5WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 1.5" WORKING LENGTH, EXPANDABLE .218"250". Includes Test Report and Certificate of Conformance.			•	
AURY218250/2.0WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 2.0" WORKING LENGTH, EXPANDABLE .218"250". Includes Test Report and Certificate of Conformance.	ARTP-004		•	
AURY218250/3.50AL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ , 4PIN FISCHER CONNECTOR 3.5" OVERALL LENGTH .218"250" Includes Test Report and Certificate of Conformance.	•			
AURY250281	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .250"281". Includes Test Report and Certificate of Conformance.	URY.250281	ARTP-005	•	
AURY250312	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .250"312". Includes Test Report and Certificate of Conformance.	BYU 16-20	URY.250312	BYU 16-20	
AURY250312/1.5WL	UNIVERSAL ROTARY PROBE 100KH2-2MHZ , 4PIN FISCHER CONNECTOR 1.5" WORKING LENGTH. EXPANDABLE FROM .250"312". Includes Test Report and Certificate of Conformance.	•			
AURY281312	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH EXPANDABLE FROM .281"312". Includes test repot and certificate of conformance.	URY.281312	ARTP-006		
AURY281375	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .281"375". Includes test repot and certificate of conformance.	•			
AURY312375	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH, EXPANDABLE FROM .312"375". Includes Test Report and Certificate of Conformance.	URY.312375	ARTP-007	9279983	
AURY312375/1.5WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4PIN FISCHER CONNECTOR 1.5" WORKING LENGTH. EXPANDABLE FROM. 312"375". Includes Test Report and Certificate of Conformance.	-		•	
AURY312375/12.0WL	UNIVERSAL ROTARY PROBE 100KH2-2MH2 4 PIN FISCHER CONNECTOR, 12.0" WORKING LENGTH. EXPANDABLE FROM .312"375". Includes Test Report and Certificate of Conformance.	ARTP-039			
AURY312375/2WL	UNIVERSAL ROTARY PROBE 100KH2-2MHZ, 4PIN FISCHER CONNECTOR 2.0" WORKING LENGTH. EXPANDABLE FROM .312"375". Includes Test Report and Certificate of Conformance.	URY.312375		•	
AURY312375/3WL	ADJUSTABLE UNIVERSAL ROTARY PROBE 3.0" WORKING LENGTH .312"375' 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•		•	
AURY340400/12.0WL-C	UNIVERSAL ROTARY PROBE 100KH2-2MH2 4 PIN FISCHER CONNECTOR, 12.0" WORKING LENGTH WITH A GUIDE COLLAR ON THE SHAFT. EXPANDABLE FROM .340"400". Includes Test Report and Certificate of Conformance.	ARTP-040	ARTP-040	•	
AURY343375	UNIVERSAL ROTARY PROBE 100KH2-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH, EXPANDABLE FROM .343"375". Includes Test Report and Certificate of Conformance.	ARTP-032			
AURY375437	UNIVERSAL ROTARY PROBE 100KH2-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .375"437". Includes Test Report and Certificate of Conformance.	URY.375437	ARTP-008		
AURY375437/2WL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ, 4PIN FISCHER CONNECTOR 2.0" WORKING LENGTH. EXPANDABLE FROM .375"437". Includes Test Report and Certificate of Conformance.	URY.375437		•	
AURY406437	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .406"437". Includes Test Report and Certificate of Conformance.	ARTP-033			
AURY437500	UNIVERSAL ROTARY PROBE 100KH2-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .437"500". Includes Test Report and Certificate of Conformance.	URY.437500	ARTP-009		
AURY437500/2WL	UNIVERSAL ROTARY PROBE 100KH2-2MHZ, 4PIN FISCHER CONNECTOR 2.0" WORKING LENGTH. EXPANDABLE FROM .437"500". Includes Test Report and Certificate of Conformance.	URY.437500			
AURY437500/3.50AL	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 3.5" OVERALL LENGTH. EXPANDABLE FROM .437".500"Ø. Includes Test Report and Certificate of Conformance.			•	
AURY468500	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .468"500". Includes Test Report and Certificate of Conformance.	ARTP-034			
AURY500562	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .500562". Includes Test Report and Certificate of Conformance.	URY.500-562	ARTP-010		

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURY500625	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .500"625". Includes Test Report	URY.500-625			
AURY500625/4WL	and Certificate of Conformance. UNIVERSAL ADJUSTABLE ROTARY PROBE 4.0" WORKING LENGTH, EXPANDABLE FROM .500"625", 100KHz-2MHz, 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AURY531562	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .531562". Includes Test Report and Certificate of Conformance.	ARTP-035	•	•	
AURY562625	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .562625". Includes Test Report and Certificate of Conformance.	URY.562625	ARTP-011		
AURY593625	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .593625". Includes Test Report and Certificate of Conformance.	ARTP-036		•	
AURY625687	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM 625687. Includes Test Report and Certificate of Conformance.	URY.625687	ARTP-012	•	
AURY625750/2M	UNIVERSAL ROTARY "Y" PROBE EXPANDABLE FROM .625750" Ø, 1-3MHz WITH 4PIN FISCHER CONNECTOR,2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BYU-40/48	URY.625750,	•	
AURY656687	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM 656687. Includes Test Report and Certificate of Conformance.	ARTP-037			
AURY687750	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .687"750". Includes Test Report and Certificate of Conformance.	URY.687750	ARTP-013		
AURY718750	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .718"750". Includes Test Report and Certificate of Conformance.	ARTP-038	•	•	
AURY725850/2WL	ADJUSTABLE UNIVERSAL ROTARY PROBE 2.0" WORKING LENGTH. EXPANDABLE FROM .725"850", 100KHZ-2MHZ, 4 PIN FISCHER CONNECTOR. Includes Test Report Certificate of Conformance.	S06R4S725850			
AURY750875	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0"WORKING LENGTH EXPANDABLE FROM .750"875". Includes Test Report and Certificate of Conformance.	URY.750875	ARTP-014		
AURY875-1.0	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH .875" Ø-1.00" Ø. Includes Test Report and Certificate of Conformance.	URY.875-1.0		•	
AURY-1.00-1.125	UNIVERSAL ROTARY PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 1.000" Ø-1.125" Ø. Includes Test Report and Certificate of Conformance.	URY1.0-1.125			
AUR187F/1.1WL	UNIVERSAL ROTATING SCANNER PROBE, SHIELDED, SPLIT END .187"Ø (3/16"Ø) 100KHz-2MHz WITH 4 PIN FISCHER CONNECTOR, 1.1" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	BPDF-12			
AF-5173	Custom Eddy Current Encirling Probe, 10mm (.3937"Ø) ID, 200KHz-2MHz Differential Supplied with a Triax Fischer Connector. Includes Test Report and Certificate of Conformance.				
AURY-1.0-1.125/3WL	UNIVERSAL ROTARY "Y" PROBE. 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 3.0" WORKING LENGTH. EXPANDABLE FROM: 1.000"Ø-1.125"Ø. Includes Test Report and Certificate of Conformance.	URY-1.0-1.125		•	
AURY-1.125-1.250/3WL	UNIVERSAL ROTARY "Y" PROBE. 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR, 3.0" WORKING LENGTH. EXPANDABLE FROM: 1.125"Ø-1.250"Ø. Includes Test Report and Certificate of Conformance.				
AURY-10-12MM/70MWL	UNIVERSAL "Y" PROBE EXPANDABLE FROM 10mm-12mmØ, 70mm WORKING LENGTH 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RSMVS10-12-70	RSMVS10-12-70		
AURY-11-13M/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 11.0mm-13.0mm. Includes Test Report and Certificate of Conformance.	URY 11-13M		•	
AURY-12-15MM/50MWL	STAINLESS STEEL CONNECTOR END UNIVERSAL "Y" PROBE 12-15mm, 50MM WORKING LENGTH, 100KHz-2MHz, 4PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RSMVS12-15	RSMVS12-15-50	RSMVS12-15-50	
AURY-13-16M/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 13.0mm-16.0mm. Includes Test Report and Certificate of Conformance.	URY 13-16M		•	
AURY-15-20MM/110MWL	UNIVERSAL "Y" PROBE, EXPANDABLE FROM 15-20mm(.591"787")Ø, 110mm(4.33") WORKING LENGTH 100KHz-2MHz WITH 4PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RSMVS15-20-110	RSMVS15-20-110		
AURY-16-19M/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 16.0mm-19.0mm. Includes Test Report and Certificate of Conformance.	URY 16-19M		•	
AURY-19-22M/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 19.0mm-22.0mm. Includes Test Report and Certificate of Conformance.	URY 19-22M		•	
AURY-2.750-2.812/2WL	Universal Rotary Hole Probe (2.750° Ø - 2.812° Ø) diameter Split End "y" style with sleeve, 2.0" working length, Operating frequency 100 kHz - 2 MHz With 4 pin Fischer connector, reflection differential coil configuration. Includes Test Report and Certi				
AURY-2.812-2.862/2WL	Universal Rotary Hole Probe (2.812"Ø - 2.862"Ø) diameter Split End "y" style with sleeve, 2.0" working length, Operating frequency 100 kHz - 2 MHz With 4 pin Fischer connector, reflection differential coil configuration. Includes Test Report and Certi				
AURY-22-25M/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 22.0mm-25.0mm. Includes Test Report and Certificate of Conformance.	URY 22-25M			
AURY-25-30MM/110MWL	UNIVERSAL "Y" PROBE, EXPANDABLE FROM 25-30mm(.984"- 1.181")Ø, 110mm(4.33") WORKING LENGTH 100KHz-2MHz WITH 4PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RSMVS25-30-110			
AURY-3-4M/38WL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 38mm WORKING LENGTH. EXPANDABLE FROM 3.0-4.0mm. Includes Test Report and Certificate of Conformance.	URY 3-4M			
AURY-4.5-5.0/60MWL	ROHMANN ADJUSTABLE ROTATING SCANNER "Y" PROBE, EXPANDABLE FROM 4.5mm-5.0mmØ, 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RSS4-5-5-0-60			
AURY-4-5M/38MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 38mm WORKING LENGTH. EXPANDABLE FROM 4.0-5.0mm includes Test Report and Certificate of Conformance.	URY 4-5M		•	
AURY-5.5M/45MWL	ADJUSTABLE ROTATING SCANNER Y- PROBE 100KHz-2MHz, 4 PIN FISCHER CONNECTOR 45mm WORKING LENGTH. EXPANDABLE FROM 5.5-6.3mmØ. Includes Test Report and Certificate of Conformance.				
AURY-5-65M/38MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 38mm WORKING LENGTH. EXPANDABLE FROM 5.0-6.5mm. Includes Test Report and Certificate of Conformance.	URY 5-6.5M			
AURY-6.0-6.5/50MWL	ADJUSTABLE ROTATING SCANNER "Y" PROBE, EXPANDABLE FROM 6.0mm-6.5mmØ, 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RSS6-0-6-5-50			
AURY-6.0-7.0M/45MWI	ADJUSTABLE ROTATING SCANNER "Y" PROBE 100KHz-2MHz WITH A 4 PIN FISCHER CONNECTOR. EXPANDABLE FROM 6.0mmØ to 7.0mmØ, 45mm	RSMV6-7-45			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR-1.59MM/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.0625"(1.59mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING				
AUR-1.98MSS/35MWL	LENGTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.078"(1.98mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING			[ 	•
AUR-2.87MSS/35MWL	LENGTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNEE PROBE 100KHZ-2MHZ ,.113"(2.87mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING				
AUR-3.97MSS/35MWL	LENGTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.156"(3.97mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING				•
AUR-4.37MSS/35MWL	LENGTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.172"(4.37mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING				•
	LENGTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , .187"(4.76mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING	-		-	
AUR-4.76MSS/35MWL	LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-5.16MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 203"(5.16mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-5.56MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.219"(5.56mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-5.95MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 234"(5-95mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-6.35MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 250"[6.35mm]Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				•
AUR-6.75MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ, .266"(6.75mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-7.14MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ, .266"(6.75mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-7.54MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 297"(7.54mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38" (35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-7.94MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.3125"(7.94mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-8.33MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 328"(8.33mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-8.73MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 343"(8.73mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-9.13MSS/35MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 359"(9.13mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 1.38"(35mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-13.5MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.531"(13.5mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				·
AURY-6.0-7.0MM/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 6.0-7.0mmø. Includes Test Report and Certificate of Conformance.	RSMVS6-7-50			
AUR-13.9MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , .546"(13.9mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-14.3MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , .563"(14.3mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-14.7MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , S79"(14.7mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				·
AUR-15.1MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , S94"(15.1mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				*
AUR-15.5MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.610"(15.5mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING				•
AUR-15.9MSS/65MWL	LENGTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 625"(15.9mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING				
	LENGTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.642"(16.3mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING			-	
AUR-16.3MSS/65MWL	LENGTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 657"(16.7mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING	-		-	
AUR-16.7MSS/65MWL	LENGTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 689"(17.5mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING	•	•		
AUR-17.5MSS/65MWL	EINOTH. Includes Test Report and Certificate of Conformance. STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 704"(17.9mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING		•	•	
AUR-17.9MSS/65MWL	STAILLESS STELL ROTATING SCANKER PROBE 100KH2-2MH2, 720° (13.3mm)/g, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56° (55mm) WORKING STAILLESS STELL ROTATING SCANKER PROBE 100KH2-2MH2, 720° (18.3mm)/g, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56° (55mm) WORKING				
AUR-18.3MSS/65MWL	STAILLESS STEEL ROTATING SCANRER PROBE 100KH2-2MH2, 736'(18.7mm)Ø, SUPPLIED WITH A4 PHY FISCHER CONRECTOR, 2.56'(65mm) WORKING STAILLESS STEEL ROTATING SCANRER PROBE 100KH2-2MH2, 736'(18.7mm)Ø, SUPPLIED WITH A4 PHY FISCHER CONRECTOR, 2.56'(65mm) WORKING				
AUR-18.7MSS/65MWL	LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-19.1MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,.752"(19.1mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-19.5MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 768"(19.5mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-19.8MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 780"(19.8mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-20.2MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 795"(20.2mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-20.6MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 811"(20.6mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AUR-21.0MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 827"(21.0mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AX5PN45-5	LEWG IH. INCLUGES TEST REPORT AND CERTIFICATE OF CONFORMANCE. SURFACE PROBE 45". S00" DROP, 0.50" Ø TIP DIAMETER, 50-500KHz, 4.0" LONG WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	X5PEN45-5			
AUR168SS/1.5WL	STAINLESS STEEL UNIVERSAL ROTARY PROBE, SHEILDED, .168"Ø WITH A 1.5" WORKING LENGTH. SUPPLIED WITH A 4 PIN FISCHER 100KHZ -2MHZ Includes Tes Report and Certificate of Conformance.				
AUR192SS/1.5WL	STAINLESS STEEL UNIVERSAL ROTARY PROBE, SHEILDED, 192"Ø WITH A 1.5" WORKING LENGTH. SUPPLIED WITH A 4 PIN FISCHER 100KHZ -2MHZ Includes Test Report and Certificate of Conformance.			•	
APN-25FX/2MHZ	STRAIGHT RIGID SURFACE PROBE, 125" Ø, 25.0" LONG, 1-3 MHz, 2MHz CENTER FREQUENCY WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	2.835.69.0056		•	
AF-5177	STRAIGHT ABSOLUTE SURFACE PROBE MICRODOT CONNECTOR, UNSHIELDED, 50-500KHz WITH A CENTER FREQUENCY OF 200KHZFe/NFe. Includes Test Report and Certificate of Conformance	120P1A		•	
ATPNR-975-4/5K/4L	LOW FREQUENCY SURFACE PROBE, REFLECTION, 90° DEGREES, .750° DROP, .187° ØO.D. TIP, 4.0° LONG 4 PIN LEMO CONNECTOR 5-20KHZ. Includes Test Report and Certificate of Conformance.	TPNR975-4/5K-4L		•	
AUR187SE/3.0WL	Universal Rotary Hole Probe Self expanding from 0.187 inch (4.75 mm) to 0.218 inch (5.54mm) diameter, 3.00 inch(76.2 mm) working length, Operating frequency 100 kHz - 2 MHz, Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR312SE/3.0WL	Universal Rotary Hole Probe Self expanding from 0.312 inch (7.9 mm) to 0.375 inch (9.5 mm) diameter, 3.0 inch (76.2 mm) working length, Operating frequency 100khz-2MHZ MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.				
AUR343SE/3.0WL	Universal Rotary Hole Probe 0.343 inch (8.71 mm) to 0.3 inch (9.52 mm) diameter, Self Expanding 3 inch (76.2 mm) working length, Operating frequency 100khz-2MHZ MHz Fischer 4 pin connector, reflection differential coil configuration (.343375) Includes Test Report and Certificate of Conformance				
AUR375SE/3.0WL	Universal Rotary Hole Probe 0.375 inch (9.52 mm) to 0.406 inch (10.31 mm) diameter, Self Expanding 3 inch (76.2 mm) working length, Operating frequency 100khz-2MHZ MHz Fischer 4 pin connector, reflection differential coil configuration. Includes Test Report and Certificate of Conformance.		•	•	
AUR-21.4MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 843"(21.4mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-21.8MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 858"(21.8mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-22.2MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 874" (22.2mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56" (65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.			•	
AUR-22.6MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 890" (22.6mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56" (65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-23.0MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 906" (23.0mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56" (65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.			•	
AUR-23.4MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ ,921*[23.4mm]Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56*(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-23.8MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ , 937" (23.8mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56" (65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.		•		
AUR-24.2MSS/65MWL	STAINLESS STEEL ROTATING SCANNER PROBE 100KHZ-2MHZ, .953" (24.2mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56" (65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-24.6MSS/65MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ969"(24.6mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AUR-25.0MSS/65MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ 1.0"(25.4mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.		•	•	
AUR-25.4MSS/65MWL	STAINLESS STELL ROTATING SCANNER PROBE 100KHZ-2MHZ 1.0"(25.4mm)Ø, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 2.56"(65mm) WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AURY-6.3-7.1M/45MWL	ADJUSTABLE "Y" ROTATING SCANNER PROBE 6.3mm-7.1mm SPREAD, 45mm WORKING LENGTH.100KHZ-2MHZ 4 PIN FISCHER CONNECTOR FOR ROHMANN MR3. Includes Test Report and Certificate of Conformance.	-	•		
AURY-6.5-8M/38MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 38mm WORKING LENGTH. EXPANDABLE FROM 6.5-8.0mm. Includes Test Report and Certificate of Conformance.	URY-6.5-8M			
AURY-6-7MM/45MWL	EXPANDABLE "Y" ROTATING SCANNER PROBE, VARIABLE FROM 6.0mmø(.236") TO 7.0mm(.276")ø, 100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 45mm(1.77") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	RSVSC6-7-45		•	
AURY-7-8.5MM/55MWL	EXPANDABLE "Y" ROTATING SCANNER PROBE, VARIABLE FROM 7.0mmø(.276") TO 8.5mm(.335")ø ,100KHZ-2MHZ SHIELDED, 4 PIN FISCHER CONNECTOR 45mm(2.17") WORKING LENGTH. Includes Test Report and Certificate of Conformance.	RSVSC7-8-5-55		•	
AURY-8-9.5M/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 8.0-9.5mm. Includes Test Report and Certificate of Conformance.	URY 8-9.5M		•	
AURY-9.5-11M/50MWL	ADJUSTABLE ROTATING SCANNER PROBE 100KHZ-2MHZ 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH. EXPANDABLE FROM 9.5mm-11.0mm. Includes Test Report and Certificate of Conformance.	URY-9.5-11M		•	
AURYFB-10.0-12.5M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE 4 PIN FISCHER CONNECTOR S0mm WORKING LENGTH 100KHZ-2MHZ. PROBE EXPANDABLE FROM 10.0mmØ -12.5mm Ø. Includes Test Report and Certificate of Conformance.				
AURYFB-12.5-15.0M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHZ-2MHZ. PROBE EXPANDABLE FROM 12.5mmØ -15.0mm Ø. Includes Test Report and Certificate of Conformance.			•	
AURYFB-15.0-17.5M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE 4 PIN FISCHER CONNECTOR S0mm WORKING LENGTH 100KHZ-2MHZ. PROBE EXPANDABLE FROM 15.0mmØ -17.5mm Ø. Includes Test Report and Certificate of Conformance.				
AURYFB-17.5-20.0M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30° DEGREES. 039°DIA) 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KH2-2MHZ. PROBE EXPANDABLE FROM 17.5mmØ-20.0mm Ø. Includes Test Report and Certificate of Conformance.			•	
AURYFB30-10.0-12.5M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30° DEGREES. 039°DIA) 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KH2-2MHZ. PROBE EXPANDABLE FROM 10.0mmØ-12.5mm Ø. Includes Test Report and Certificate of Conformance.				
AURYFB30-11.1-13.3M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30° DEGREES. 039°DIA) 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KH2-2MHZ. PROBE EXPANDABLE FROM 11.1mmØ-13.3mm Ø. Includes Test Report and Certificate of Conformance.			•	
ATPN-95-28FX	FLEXIBLE SURFACE PROBE 90DEG .500" DROP 28.0" LONG TRIAX FISCHER CONN50-500KHZ				
AURFX-6MSE/8L	FLEXIBLE ROTARY PROBE 6MM TO 8MM 8.0" LONG WITH COLLAR 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ Includes Test Report and Certificate of Conformance				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AURFX-8MSE/8L	FLEXIBLE ROTARY PROBE 8MM TO 10MM 8.0" LONG WITH COLLAR 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ Includes Test Report and Certificate of Conformance				
AURFX-10MSE/8L	Comormance FLEXIBLE ROTARY PROBE 10MM TO 12MM 8.0" LONG WITH COLLAR 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ includes Test Report and Certificate of Conformance				
AURFB-3MSE/6FX	ELEXIBLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE SUPPLIED 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHz-2MHz. PROBE EXPANDABLE FROM 3mmØ-4mm Ø, 6.0" OVERALL WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AURFB-4MSE/6FX	FLEXIBLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE SUPPLIED 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHz-2MHz. PROBE EXPANDABLE FROM 4mm@-5mm @, 6.0" OVERALL WORKING LENGTH. Includes Test Report and Certificate of Conformance.			•	
AURFB-5MSE/6FX	FLEXIBLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE SUPPLIED 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHz-2MHz. PROBE EXPANDABLE FROM 5mm@-6mm @ .6.0" OVERALL WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
AURFB-6MSE/6FX	FLEXIBLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE SUPPLIED 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHz-2MHz.				•
AURFB-7MSE/6FX	PROBE EXPANDABLE FROM 6mmØ-7mm Ø, 6.0" OVERALL WORKING LENGTH. Includes Test Report and Certificate of Conformance. FLEXIBLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE SUPPLIED 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHz-2MHz.				
AURFB-8MSE/6FX	PROBE EXPANDABLE FROM 7mmØ-8mm Ø, 6.0" OVERALL WORKING LENGTH. Includes Test Report and Certificate of Conformance. FLEXIBLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE SUPPLIED 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHz-2MHz.			·	
	PROBE EXPANDABLE FROM 8mmØ-10mm Ø, 6.0" OVERALL WORKING LENGTH. Includes Test Report and Certificate of Conformance. FLEXIBLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE SUPPLIED 4 PIN FISCHER CONNECTOR S0mm WORKING LENGTH 100KHz-2MHz.	•			
AURFB-10MSE/6FX	PROBE EXPANDABLE FROM 10mm@,12mm @, 6.0" OVERALL WORKING LENGTH. Includes Test Report and Certificate of Conformance. FLEXIBLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE SUPPLIED 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHz-2MHz.	•		•	
AURFB-12MSE/6FX	PROBE EXPANDABLE FROM 10mmØ-12mm Ø, 6.0" OVERALL WORKING LENGTH. Includes Test Report and Certificate of Conformance.			•	
AURYFB30-12.5-15.0M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30° DEGREES. 039°DIA) 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHZ-2MHZ. PROBE EXPANDABLE FROM 12.5mmØ -15.0mmØ. Includes Test Report and Certificate of Conformance.				
AURYFB30-15.0-17.5M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30° DEGREES .039°DIA) 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHZ-2MHZ. PROBE EXPANDABLE FROM 15.0mmØ -17.5mmØ. Includes Test Report and Certificate of Conformance.			•	-
AURYFB30-16.0-17.5M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30° DEGREES .039"DIA) 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHZ-2MHZ. PROBE EXPANDABLE FROM 16.0mmØ -17.5mmØ. Includes Test Report and Certificate of Conformance.				
AURYFB30-9.5-11.1M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE (COIL ANGLE 30° DEGREES. 039°DIA) 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KH2-2MHZ. PROBE EXPANDABLE FROM 9.5mmØ -11.1mm Ø. Includes Test Report and Certificate of Conformance.			•	
AURYFB-7.5-10.0M/50MWL	ADJUSTABLE EXPANDABLE UNIVERSAL ROTARY FLAT BOTTOM EDGE PROBE 4 PIN FISCHER CONNECTOR 50mm WORKING LENGTH 100KHZ-2MHZ. PROBE EXPANDABLE FROM 7.5mm@-10.0mm@. includes Test Report and Certificate of Conformance.				
AWP-373NLG	50-S00KHz WHEEL PROBE FOR BOEING 737 NOSE WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				•
AWP-737MLG	50-500KHz WHEEL PROBE FOR BOEING 737 MAIN WHEEL. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AWP-8/Q200M	WHEEL PROBE FOR DeHaviland Dash-8 Q200 MAIN 50-500KHz TRIAX FISCHER / LEMO CONNECTOR DIFF/BRIDGE. Includes Test Report and Certificate of Conformance				
AWP-8/Q200N	WHEEL PROBE FOR DeHaviland Dash-8 Q200 NOSE 50-500KHz TRIAX FISCHER / LEMO CONNECTOR DIFF/BRIDGE. Includes Test Report and Certificate of Conformance.				
AWP-A321M	WHEEL PROBE FOR AIRBUS A321 MAIN WHEEL 50-500KHZ TRIAX FISCHER CONNECTOR DIIFF/ BRIDGE. Includes Test Report and Certificate of Conformance.				
AWP-A321N	WHEEL PROBE FOR AIRBUS A321 NOSE WHEEL 50-500KHZ TRIAX FISCHER CONNECTOR DIIFF/ BRIDGE. Includes Test Report and Certificate of Conformance.				
AWP-AHA2225-2N	WHEEL PROBE FOR AHA2225-2 NOSE WHEEL. DIFFERENTIAL/ BRIDGE, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AWP-AHA2226-2M	WHEEL PROBE FOR AHA2226-2 MAIN WHEEL. DIIFFERENTIAL/ BRIDGE, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AWP-Q400M	WHEEL PROBE FOR Q400 MAIN 50-500KHz TRIAX FISCHER / LEMO CONNECTOR DIIFF/ BRIDGE. Includes Test Report and Certificate of Conformance.				
AWP-Q400N	WHEEL PROBE FOR Q400 NOSE 50-500KHz TRIAX FISCHER / LEMO CONNECTOR DIFF/BRIDGE. Includes Test Report and Certificate of Conformance.				
AWS-SD3-60	SHORTS WHEEL REFERENCE STANDARD P/N: AHA1847 MAIN. 3 EDM NOTCHES.004"W +/002" x.020"D x.150"L. NOTCHES INSTALLED IN THE BEAD SEAT AREA OF THE WHEEL. CUSTOMER SUPPLIED PART	SD3-60			
AXPN-2	RIGID SURFACE PROBE STRAIGHT 2.0" LONG .072" TUBING 50-500KHZ WITH MICRODOT CONNECTOR	MMP20			
AXPN-3	SURFACE PROBE STRAIGHT .3.0" LONG .072" TUBING 50-500KHZ WITH MICRODOT CONNECTOR				
AXPN-3/2MHZ	ABSOLUTE SHIELDED SURFACE PROBE .072" DIA TUBING STRAIGHT SHAFT 3.0' LONG MICRODOT CONNECTOR 1-3MHZ	MMP-30-1-3M	U8616365		
AXPN35-3	SURFACE PROBE, 50-500KHZ, MICRODOT	SPEN35-3	MMP903-3		
AXPN-35-3	SURFACE PROBE 30°.500 DROP 3.0° OVERALL LENGTH .072°Ø TUBING 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP305-30			
AXPN35-4	SURFACE PROBE 50-500KHZ 35 DEG .500 DROP 4.0" LONG MICRODOT CONNECTOR				
AXPN-35-4	RIGID SURFACE PROBE, .062"Ø TUBING 30° DEGREES.500° DROP CURVE, 50-500KH2 4.0° LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP-305-40			
AXPN35-4.5	SURFACE PROBE, 50-500KHZ, MICRODOT	MMP305-45			
AXPN-35-4FX/7L	RIGID PENCIL PROBE ABS SHIELDED 50-500KHz, 90° DEGREES, BENT 30° DEGREES, .500° DROP .093 TUBING. 5.0° LONG. 7 Pin LEMO CONNECTOR. Includes Test Report and Certificate of Conformance.	PABM30405FX	MMTF305-40FX		
AXPN-35-5	SURFACE PROBE 30°. 500 DROP 5.0" OVERALL LENGTH .072"Ø TUBING 50-S00KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP305-50			

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AXPN-4	RIGID SURFACE PROBE STRAIGHT 4.0" LONG .072" TUBING 50-500KHZ WITH MICRODOT CONNECTOR	MMP-40			
AXPN4.5/2M	SURFACE PROBE, STRAIGHT 4.5" LONG .072" TUBE 1-3MHZ MICRODOT CONNECTOR	XPEN4.5 1-3MHZ	610-047-002		
AXPN-4/1M	SURFACE PROBE STRAIGHT 4.0" LONG .072" TUBING 2000KHz-1MHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP-40-200K-1M	MMP-40-200K-1M		
AXPN43-6	RIGID SURFACE PROBE, 50-500KHZ, 45°, 6.0° LONG, .300° DROP, .072Ø TIP, MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AXPN-45-3	SURFACE PROBE 45". 3.0" LONG .072"Ø TUBING 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AXPN45-6	RIGID SURFACE PROBE, 50-500KHZ, .072" Ø, 45", 6.0" LONG, .500" DROP SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				•
AXPN-45-6	RIGID SURFACE PROBE 45" DEGREES, .072" Ø TUBING WITH MICRODOT CONNECTOR, 50-500khz. 6.0 " LONG. Includes Test Report and Certificate of Conformance.				
AXPN-475-4.5/6MHZ	RIGID SURFACE PROBE SHIELDED, 45" DEGREES, .750"(19.5mm) DROP 4.5"(114mm) LONG, .072"Ø TUBING WITH MICRODOT CONNECTOR 6MHz.	PU006PC195-114FV1		•	а 
AXPN-5	RIGID SURFACE PROBE - STRAIGHT, ABS. SHIELDED, 5.0" (127mm) .072" OD TUBING. LONG WITH MICRODOT CONNECTOR. FREQUENCY: 50-500KHz. Includes Test Report and Certificate of Conformance.				
AXPN-5/2MHZ	RIGID SURFACE PROBE - STRAIGHT, ABS. SHIELDED, 5.0" (127mm) LONG WITH MICRODOT CONNECTOR. FREQUENCY: 1-3MHz. Includes Test Report and Certificate of Conformance.				
AXPN-6	RIGID SURFACE PROBE - STRAIGHT, ABS. SHIELDED, 6.0" (150mm)LONG WITH MICRODOT CONNECTOR. FREQUENCY: 50-500KHz. Includes Test Report and Certificate of Conformance.	MMP-60			
AXPN-6/2MHZ	RIGID SURFACE PROBE - STRAIGHT, ABS. SHIELDED, 6.0" (150mm)LONG WITH MICRODOT CONNECTOR. FREQUENCY: 1-3MHz. Includes Test Report and Certificate of Conformance				
AXPN-7FX	STRAIGHT FLEXIBLE SHAFT SURFACE PROBE .072"Ø TUBING WITH MICRODOT CONNECTOR 7.0" LONG 50-500KHZ. Includes Test Report and Certificate of Conformace.				
AXPN902-7FX	OF CANTONTARICE. FLEXIBLE SHAFT SURFACE PROBE .072 <sup>®</sup> Ø TIP 1.0 <sup>®</sup> LONG .020 DROP 7.0 <sup>®</sup> WORKING LENGTH, 50-500KHZ WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
AXPN-903-10/500KHZ	RIGID SURFACE PROBE 072" TIP 90", .030" DROP ABS. SHIELDED, 10.0" LONG WITH MICRODOT CONNECTOR. FREQUENCY: 350KHz-3MHz. Includes Test Report and Certificate of Conformance.				
AXPN-903-6	RIGID SURFACE PROBE - 0.72" TIP 90", 030" OROP ABS. SHIELDED, 6.0" LONG WITH MICRODOT CONNECTOR. FREQUENCY: 50KHz-500KHz. Includes Test Report and Certificate of Conformance.	•			
AXPN-903-6/2MHZ	RIGID SURFACE PROBE - 0.072" TIP 90", 0.30" (1mm) DROP ABS. SHIELDED, 6.0" (150mm)LONG WITH MICRODOT CONNECTOR. FREQUENCY: 1MHz-3MHz. Includes Test Report and Certificate of Conformance.				
AXPN-903-6FX	ELEVIDES VEX REPORT and Certificate of Comminiance. FLEXIBLE SURFACE PROBE072" ITIP 90", .030" DROP ABS. SHIELDED, 6.0" LONG WITH MICRODOT CONNECTOR. FREQUENCY: 50-500KHz. Includes Test Report and Certificate of Conformance.	MMP9003-60FX			
AXPN-903-6FX/2M	FLEXIBLE SURFACE PROBE072" TIP 90", .030"(1mm) DROP ABS. SHIELDED, 6.0" (150mm)LONG WITH MICRODOT CONNECTOR. FREQUENCY: 1MHz- 3MHz. Includes Test Report and Certificate of Conformance.	•			
AXPN-91-6/2M	SURFACE PROBE ABSOLUTE, 1MHz-3MHz, 90". 072 OD TUBE .100" DROP 6.0" LONG MICRODOT CONNECTOR. lincludes Test Report and Certificate of Conformance.				•
AXPN91-6FX	FLEXIBLE SURFACE PROBE 90" DEGREES .072"Ø TIP, .100" DROP, 6.0" LONG, 50-500KHZ WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	•		•	
AXPN92-14/2MHZ	SURFACE PROBE - 1-3MHZ, 90 DEG .200" DROP 14.0" LONG, .072"TUBING, MICRODOT CONNECTOR	310P002			
AXPN-92-3	RIGID SUFACE PROBE.072"Ø OD TIP, 90° DEGREES, .200" DROP 3.0" LONG, 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP902-30			
AXPN-92-4	RIGID SUFACE PROBE.07210 OD TIP, 90° DEGREES, 200° DROP 4.0° LONG, 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance. REFERENCE: AIRBUS A300-600 PART 6 57-54-04 PAGE 603 FIGURE 602	MMP902-40		•	
AXPN92-4.5	SURFACE PROBE, 50-S00KHZ	•	MMP904-40	•	
AXPN-92-4.5B	RIGID SUFACE PROBE.072"Ø OD TIP, 90° DEGREES, .200" DROP 4.5" LONG, 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP902-45			
MWB 70-4(E)	KRAUTKRAMER 70° ANGLE BEAM TRANSDUCER 8X9 4MHz				
AXPN-92-5	RIGID SUFACE PROBE.072"Ø OD TIP, 90° DEGREES, .200" DROP 5.0" LONG, 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP902-50	SPEN 92-5		
AXPN-925-6	RIGID SURFACE PROBE, 50-500KHz, 90° DEGREES, .25° DROP 6.0° LONG WITH A MICRODOT CONNECTOR( .072" Ø)TUBING. Includes Test Report and Certificate of Conformance.				
AXPN-92-5B	RIGID SUFACE PROBE.072"Ø OD TIP, 90° DEGREES, .200" DROP 5.0" LONG, BENT, 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
AXPN-92-6/2MHZ	POWER LINK METAL SHAFT RIGHT ANGLE SURFACE PROBE 0.72" DIA TUBING 0.2" DROP 6.0" LONG 7 PIN LEMO CONNECTOR 1-3MHZ	MM7L902-60-1-3M	9403446	MM7L902-60-1-3M	
AXPN-92-6B	SUFACE PROBE .072"Ø OD TIP, BENT 90" DEGREES .200" DROP 6.0" LONG 50-500KHZ MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP902-60B			
AXPN-92-8	RIGID SUFACE PROBE.072"Ø OD TIP, 90" DEGREES, .200" DROP 8.0" LONG, 50-500KHz WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP902-80			
AXPN-95-4.5	SURFACE PROBE ABS SHIELDED, 50-500KHz, 90° .072"Ø, .500" DROP 4.5" LONG WITH A MICRODOT CONNECTOR. lincludes Test Report and Certificate of Conformance.	PAM90455		•	
AXPN95-5	SURFACE PROBE, 50-500KHZ, 90 deg .073 OD TUBE .500" DROP 5.0" LONG MICRODOT CONNECTOR	MMP905			
	SURFACE PROBE ABS SHIELDED, 50-500KHz, 90°.072"Ø, .500" DROP 5.0" LONG WITH A MICRODOT CONNECTOR. lincludes Test Report and Certificate		1	1	1

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AXPN-95-5/2MHZ	SURFACE PROBE ABSOLUTE, 1MHz-3MHz, 90°.072"Ø, .500" DROP 5.0" LONG MICRODOT CONNECTOR. lincludes Test Report and Certificate of				Egonation
AXPN-95-5FX	Conformance. ELEXIBLE SURFACE PROBE072 TIP 90 DEGREES500° DROP 5.0° LENGTH. MICRODOT CONNECTOR 50-500KHz				
AXPN-95-6/2MHZ	SURFACE PROBE ABSOLUTE, 1MHz-3MHz, 90°.072 OD TUBE .500" DROP 6.0" LONG MICRODOT CONNECTOR. lincludes Test Report and Certificate of				
AXPN95-6B	Conformance. ELEXIBLE SURFACE PROBE, 50-S00KHZ, 90 DEG .500° DROP 6.0° LONG MICRODOT, BENT	MP905-			
AXPN95-80FX	SURFACE PROBE, 50-500KHZ, 90 deg, 073 OD TUBE :500° DROP 8.0° LONG MICRODOT CONNECTOR	MP905-80FX	•	•	
AXPN975-4.5/B/2MHZ	SURFACE PROBE - 1-3MHZ, 90 DEG, 750° DROP 4.5° LONG .072 TUBE MICRODOT CONNECTOR	314P44F	314P44F	610-107-231	
AXPN975-4.5/B/2MH2	SURFACE PROBE: 1-3WIR2, 90 DEG .500 DROP 4.5 LONG. U/2 TUBE MICRODOT CONNECTOR	314P44F	314P44F	610-107-231	
AXT5PN-5	SURFACE PROBE .050" DIAMETER TUBING, 5.0" LONG, TRIAX FISCHER CONNECTOR. 50-500KHZ. Includes Test Report and Certificate of Conformance.	-	•	•	
AXT5PN-91-5	SURFACE PROBE.050" DIAMETER TUBING 90" DEGREES, 100" DROP 5.0" LONG, TRIAX FISCHER CONNECTOR. 50-500KHZ. Includes Test Report and Certificate of Conformance.				
AXTPN-10FX/2M	STRAIGHT FLEXIBLE SHAFT SURFACE PROBE .072"Ø TUBING TRIAX FISCHER CONNECTOR 10.0" LONG 1-3MHZ. Includes Test Report and Certificate of Conformance.	SPENFLX-10/2M			
AXTPN35-10/1-6M	SURFACE PROBE - 10" DROP 35", .060 Ø 1-6MHZ	MMTF305-50			
AXTPN35-4	RIGID SURFACE PROBE 30°, .500' DROP 50-500KHZ WITH TRIAX FISCHER CONNECTOR, .072"Ø TUBING, 4.0" LONG. Includes Test Report and Certificate of Conformance.	TSPEN35-4			
AXTPN-4	STRAIGHT SURFACE PROBE DEGREES 4.0 " LONG .072" UBING, TRIAX FISCHER CONNECTOR, 50-500KHz. Includes Test Report and Certificate of Conformance.	TSPEN-4			
AXTPN-4/2MHZ	STRAIGHT SURFACE PROBE DEGREES 4.0 " LONG .072"Ø TUBING, TRIAX FISCHER CONNECTOR, 1-3MHz. Includes Test Report and Certificate of Conformance.	TX5PEN-4/2M			
AXTPN-4/50-100KHZ	STRAIGHT SURFACE PROBE .072" DIA TUBING 4.0" LONG TRIAX FISCHER CONNECTOR 50- 100KHZ( MAGNECTIC STEEL)				
AXTPN-453-6	ABSOLUTE BRIDGE ANGLE SHAFT. 6.0" LONG. 45 DEG TIP. 0.3 IN. (7.62MM) DROP, 50KHZ-500KHZ. 0.072IN. (1.83) SHAFT. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	MMTF453-60			
AXTPN45-4	SURFACE PROBE5" DROP 45", 4.0" long 50-500KHZ Triax Fischer connector				
AXTPN-45-4	RIGID SURFACE PROBE 45" DEGREES 4.0 " LONG .072" dia TUBING, TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.	TSPEN45-4			
AXTPN45-5	SURFACE PROBE - 45', .500" DROP, .072 TIP 50-500K, 5"LONG , SHIELDED, TRIAX FISCHER CONNECTOR				
AXTPN-45-5	RIGID SURFACE PROBE 45° DEGREES 5.0 " LONG .072" dia TUBING, TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.	TSPEN45-5			
AXTPN45-5/2M	SURFACE PROBE - 45', .50DROP, .072 TIP 1-3MHZ, 5"L, SHIELDED, TF				
AXTPN-45-5/2M	RIGID SURFACE PROBE 45" DEGREES 5.0 " LONG .072 "Ø dia TUBING, TRIAX FISCHER CONNECTOR 1-3MHz. Includes Test Report and Certificate of Conformance.				
AXTPN45-6	RIGID SURFACE PROBE - ABS SHIELDED 45" DEGREES, .500" DROP, .072" TIP, 50-500K, 6.0" LONG, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	MMTF455-60			
AXTPN-45-6	RIGID SURFACE PROBE 45" DEGREES, .072" Ø TUBING TRIAX FISCHER CONNECTOR 50-500khz. 6.0 " LONG				
AXTPN-5	STRAIGHT SURFACE PROBE - 50-500KHZ, .072"Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AXTPN-5/2M	STRAIGHT SURFACE PROBE - 1-3MHz. 072" Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AXTPN-6	RIGID STRAIGHT SURFACE PROBE, .072"Ø TIP, TRIAX FISCHER CONNECTOR, 50-500KHZ, 6.0" LONG.				
AXTPN-6/2MHZ	SURFACE PROBE 1-3MHZ, .072 TIP, .6.0" LONG TRIAX FISCHER				
AXTPN-7FX	STRAIGHT FLEXIBLE SHAFT SURFACE PROBE .072"Ø TUBING TRIAX FISCHER CONNECTOR 7.0" LONG 50-500KHZ. Includes Test Report and Certificate of Conformance.	TSPENFLX-7			
AXTPN-8	RIGID STRAIGHT SURFACE PROBE, SHIELDED, .072" Ø TIP, TRIAX FISCHER CONNECTOR, 50-500KHZ, 8.0" LONG, 5.5" SHAFT LENGTH. Includes Test Report and Certificate of Conformance.				
AXTPN902-7FX	FLEXIBLE SHAFT SURFACE PROBE .072"Ø TIP 1.0" LONG .020 DROP 7.0" WORKING LENGTH, 50-500KHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AXTPN903-7FX	SURFACE PROBE .072"TIP 1.0"LONG .030 DROP 7.0" WORKING LENGTH, FLEXIBLE SHAFT 50-500KHz WITH TRIAX FISCHER CONNECTOR.				
AXTPN903-7FX/500K	SURFACE PROBE.072"TIP 1.0"LONG .030 DROP 7.0" WORKING LENGTH, FLEXIBLE SHAFT 500KHz-1MHz WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AXTPN-91-10FX	FLEXIBLE SURFACE PROBE.072"Ø DIA TUBING 90" DEGREES .100"(2.54mm) DROP, 10.0" LONG WITH A TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.	SPENFLX91-10			
AXTPN-91-4/50-100KHZ	SURFACE PROBE 072" DIA TUBING 90" DEGREES, 100" DROP 4.0" LONG, TRIAX FISCHER CONNECTOR. 50-500KHZ. Includes Test Report and Certificate of Conformance.				
AXTPN91-6FX	FLEXIBLE SURFACE PROBE 90° DEGREES .072 "Ø TIP, .100" DROP, 6.0" LONG, 50-500KHZ TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance				
					l:

PART NUMBER		EQUIN (ALENIT	EQUIVALENT		FOUN /AL FAIT
AUGTONI OAL CEV	DESCRIPTION FLEXIBLE SURFACE PROBE ABSOLUTE, 50-500 kHz, 90° .072 OD TUBE .100° DROP 6.0° LONG TRIAX FISCHER CONNECTOR. Includes Test Report and	EQUIVALENT TSPENFLX91-6	EQUIVALENT	EQUIVALENT	EQUIVALENT
AXTPN-91-6FX ATP-5/5KHZ	Certificate of Conformance. LOW FREQUENCY STRAIGHT PENCIL PROBE (.187" DIA TUBING) BRIDGE/DIFFERENTIAL 5.0" LONG TRIAX FISCHER CONNECTOR WITH AN OPERATING	ISPENFLX91-6	•	•	
	FREQUENCY OF 5KHz-25KHz. Includes Test Report and Certificate of Conformance. SURFACE PROBE072 TIP 50-500K,90 DEG,.5 DROP ,4.0 INCH LONG	TSPEN95-4			
	SURFACE PROBE - 50-500K, 90 degree .200" drop, 4.0" long bent Triax Fisher Connector.	TSPEN92-4B		[	
	SURFACE PROBE072 TIP 90 DEG .200" DROP TRIAX FISCHER CONNECTOR 50-500KHz 5.0 INCH LONG	MMTF902-50			
	SURFACE PROBE072 TIP 90 DEGREE, .250" DROP TRIAX FISCHER CONNECTOR 50-500K				
	INTERE HODE - 072 IN 30 DEGREE, 250 DIGHT INDER SCHERCHINE CONTRECTOR S0-500K	РАМ90С402	•		
	RIGID SURFACE PROBE ABSOLUTE, 0/2 TIT, 50 CHAIRED 1:0 FROM TIT, 230 DROP 4:0 CORD SUBSOLUTE, TARA FISCHER CONNECTOR. FLEXIBLE SURFACE PROBE, 1- 6MHz, 072" Ø DIA TUBING 90° DEGREES, 200°(5.08mm) DROP 5.0°(12.7mm) LONG WITH TRIAX FISCHER CONNECTOR 1-	PAINISUC402	•	•	
	6MHz. Includes Test Report and Certificate of Conformance.			•	
AXTPN-92-6	RIGID SURFACE PROBE .072" Ø DIA TUBING 90° DEGREES, .200", TRIAX FISCHER CONNECTOR 50-500KHz, DROP 6.0" LONG.				
AXTPN-92-6FX	FLEXIBLE SURFACE PROBE .072" Ø DIA TUBING 90° DEGREES, .200" DROP 6.0" LONG TRIAX FISCHER CONNECTOR 50- 100KHz				
AXTPN92-7FX	FLEXIBLESURFACE PROBE 50-500KHZ, .072 TIP, 7.0"Long, .200" DROP TRIAX FISCHER CONNECTOR				
AXTPN-92-9	FLEXIBLE ABSOLUTE BRIDGE. 9.0" LONG. 50-KHZ-500KHZ. 90 DEG. TIP. 0.2IN (5.08MM) DROP. 0.072IN. (1.83MM) SHAFT SIZE. TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	MMTF902-90FX			
AXTPN-94-5FX	FLEXIBLE SURFACE PROBE .072" Ø DIA TUBING 90" DEGREES, .400" DROP 5.0" LONG TRIAX FISCHER CONNECTOR 50- 500KHz	PABM90B445FX/.072			
AXTPN-95-3	RIGID SURFACE PROBE072*Ø TIP 90° DEGREES .500° DROP, TRIAX FISCHER CONNECTOR 50-500KHz, 3.0° LONG. Includes Test Report and Certificate of Conformance.	•			
AXTPN-95-4	RIGID SURFACE PROBE072'Ø TIP 90° DEGREES .400° DROP, TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.	•			
AXTPN-95-4B	RIGID SURFACE PROBE, ABSOLUTE, 072"ØTIP, 90° CRANKED 1.0" FROM TIP, .500" DROP 4.0" LONG 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PAM90C405			
AXTPN-95-4B/2M	RIGID SURFACE PROBE ABS, 0.72" TIP, 90" CRANKED 1.0" FROM TIP, .500" DROP 4.0" LONG 1-3MHZ, TRIAX FISCHER CONNECTOR. Includes Test Report ancd Certificate of Conformance.				
AXTPN-95-5	RIGID SURFACE PROBE072'Ø TIP 90' DEGREES .500' DROP, TRIAX FISCHER CONNECTOR 50-500KHz. Includes Test Report and Certificate of Conformance.	DPT90-008			
AXTPN-95-5/2M	RIGID SURFACE PROBE072'Ø TIP 90° DEGREES .500° DROP, TRIAX FISCHER CONNECTOR 1-3MHz. Includes Test Report and Certificate of Conformance.	•			
AXTPN-95-5/500K-1M	RIGID SURFACE PROBE 500 Khz-1 Mhz, .072"Ø TIP, 90° DEGREES, .500" DROP, 5.0" LONG TRIAX FISCHER CONNECTOR 500KHz-1MHz. IncludesTest Report and Certificate of Conformance.	DPT90-009			
AXTPN-95-6	SURFACE PROBE072"Ø TIP 90" DEGREES, .200" DROP TRIAX FISCHER CONNECTOR 50-500KHz, 6.0" LONG.				
AXTPN-95-6B	RIGID SURFACE PROBE ABS, .072" TIP, 90° CRANKED 1.0" FROM TIP, .500" DROP 6.0" LONG 50-500KHZ, TRIAX FISCHER CONNECTOR. Includes Test Report ancd Certificate of Conformance.	PABM90C605			
AXTPN-95-6B/2M	RIGID SURFACE PROBE ABS, 072" TIP, 90° CRANKED 1.0" FROM TIP, .: 500" DROP 6.0" LONG 1-3MHZ, TRIAX FISCHER CONNECTOR. Includes Test Report ancd Certificate of Conformance.				
AXTPN96-4/.050	SURFACE PROBE - 50-500KHZ	•			
AXXPN-3	RIGID SURFACE PROBE, .062"Ø TUBING 50-500KHZ 3.0" LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP-30			
AXXPN-5	STRAIGHT RIGID SURFACE PROBE, .062"Ø TUBING 50-500KHz, 5.0" LONG WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AXXPN-925-6	RIGID SURFACE PROBE, 50-500KHz, 90° DEGREES, .25" DROP 6.0" LONG WITH A MICRODOT CONNECTOR( .062" Ø)TUBING. Includes Test Report and Certificate of Conformance.				
AXXTPN-5	STRAIGHT SURFACE PROBE - 50-500KHZ, 062" Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	•			
AXXTPN-7FX	STRAIGHT SURFACE PROBE - 50-500KHZ, 062"Ø, 7.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	TSPENFLX-7			
AXXTPN-91-6FX	FLEXIBLE SURFACE PROBE .062"Ø DIA TUBING 90° DEGREES .100°(2.54mm) DROP, 6.0" LONG WITH A TRIAX FISCHER CONNECTOR 50KHz-500KHz. Includes Test Report and Certificate of Conformance.	TSPENFLX91-6			
AXXTPN-92-6B	SURFACE PROBE, 90° DEGREES ANGLED, .062°Ø TIP .200° DROP, 50-500KHZ, TRIAX FISCHER CONNECTOR. 15° CRANK 3° FROM TIP. Includes Test Report and Certificate of Conformance.	•			
AZRP3580/200KHZ	HIGH FREQUENCY REFLECTION RING PROBE, 350" ID WITH A MAXIMUM OD OF .800", 200KHz CENTER FREQUENCY, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AZRP3580/600KHZ	HIGH FREQUENCY REFLECTION RING PROBE, 350° ID WITH A MAXIMUM OD OF .800°, 600 KHz CENTER FREQUENCY, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AZRP35/.80	LOW FREQUENCY REFLECTION RING PROBE, 350° ID WITH A MAXIMUM OD OF .800°, 300Hz CENTER FREQUENCY, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RNG-003			
AZRP35/.80/200KHZ	High FREQUENCY REFLECTION RING PROBE, 350° ID WITH A MAXIMUM OD OF .800°, 200KHz CENTER FREQUENCY, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RNG-010			
	HIGH FREQUENCY REFLECTION RING PROBE, .350" ID WITH A MAXIMUM OD OF .800", 600KHz CENTER FREQUENCY, TRIAX FISCHER CONNECTOR.	BNG-011			-

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EOUIVALENT
AZRP35/.80-1	LOW FREQUENCY REFLECTION RING PROBE, .350" ID WITH A MAXIMUM OD OF .800", 600Hz CENTER FREQUENCY, TRIAX FISCHER CONNECTOR. Includes	BNG-009	EQUIVALENT	EQOIVALENT	EQUIVALENT
AZRP40/.84	Test Report and Certificate of Conformance. LOW FREQUENCY REFLECTION, RING PROBE, CENTER FREQUENCY OF 300Hz., 400°Ø ID x. 840°Ø OD WITH TRIAX FISCHER CONNECTOR. Includes Test	RNG-004		·	
AURFB-3.1MSS/1.5	Report and Certificate of Conformance. UNIVERSAL STAINLESS STEEL FLATE BOTTOM ROTARY PROBE 3.1mm Ø(0.122"),1.5"(38.1mm) WORKING LENGTH, 4 PIN FISCHER CONNECTOR, 100KHz-				
AXXPN-45-5C	2MHz. Includes Test Report and Certificate of Conformance. RIGID SURFACE PROBE 45° CURVED, .062°Ø, 5.0° LONG. SUPPLIED WITH A MICRODOT CONNECTOR 50-500khz. Includes Test Report and Certificate of Conformance	MMP455-50C			
AZRP40/.84/200KHZ	HIGH FREQUENCY REFLECTION RING PROBE, .400" ID WITH A MAXIMUM OD OF .840", 200KHz CENTER FREQUENCY, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RNG-013			
AZRP40/.84/600KHZ	HIGH FREQUENCY REFLECTION RING PROBE, .400" ID WITH A MAXIMUM OD OF .840", 600KHz CENTER FREQUENCY, TRIAX FISCHER CONNECTOR.	RNG-014			
AZRP40/.84-1	LOW FREQUENCY REFLECTION RING PROBE, 400" ID WITH A MAXIMUM OD OF .840", 600Hz CENTER FREQUENCY, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	RNG-012			
AZRP8040-300HZ	LOW FREQUENCY REFLECTION RING PROBE, 100HZ-1KHZ.400"Ø ID .800"Ø OD WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
AZTBL060-6	EDDY CURRENT BLADE PROBE, UNSHIELDED .060 THICK, 6.0" LONG, STRAIGHT SHAFT, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.				
BLD-001	EDDY CURRENT BLADE PROBE, .060 THICK, 6.0" LONG, STRAIGHT SHAFT, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	ATBL060-6			
DPT-002	STRAIGHT SURFACE PROBE - 50-500KHZ, .125"Ø, 5.0" LONG WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	ATPN-5			
DPT45-002	RIGID SURFACE PROBE 45° DEGREES, .500° DROP, 5.0° LONG TRIAX FISCHER CONNECTOR. FREQUENCY: 50-500KHz Includes Test Report and Certificate of Conformance.	ATPN-45-5			
DPT90-002	RIGID SURFACE PROBE 50-500KHz, .125"Ø TIP, 90° DEGREES, .500° DROP, 5.0° LONG TRIAX FISCHER CONNECTOR 50-500KHz IncludesTest Report and Certificate of Conformance.	ATPN-95-5			
DPT9030-001	RIGID SURFACE PROBE, 90° .500" DROP, TRIAX FISCHER CONNECTOR. 50-500KHz. BENT 30', 5.0" LONG includes test report and Certificate of Conformance.	ATPN-95-5B	DPT9030-001		
DPT9030-002	RIGID SURFACE PROBE, 90°.500" DROP, TRIAX FISCHER CONNECTOR, 1-3MHZ, BENT 30°, 5.0" LONG. Includes Test Report and Certificate of Conformance.	ATPN-95-5B/2MHZ	DPT9030-002	TPEN-95-5/2M	
MBHP-004	MANUAL BOLT HOLE PROBE, .250°281" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				-
MBHP-005	MANUAL BOLT HOLE PROBE, 281"-312" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-006	MANUAL BOLT HOLE PROBE, 312"-375" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-007	MANUAL BOLT HOLE PROBE, .437"500" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.	•			
MBHP-008	MANUAL BOLT HOLE PROBE, .500". 562" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-009	MANUAL BOLT HOLE PROBE, .562".625" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-010	MANUAL BOLT HOLE PROBE, .625".687" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-011	MANUAL BOLT HOLE PROBE, .687"750" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-012	MANUAL BOLT HOLE PROBE, .750". 812" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-013	MANUAL BOLT HOLE PROBE, .125".156" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-014	MANUAL BOLT HOLE PROBE, .156".187" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 1.5" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-015	MANUAL BOLT HOLE PROBE, 812"-875" SPLIT END, S00KH2-2MH2 UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-016	MANUAL BOLT HOLE PROBE, .875".937" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-017	MANUAL BOLT HOLE PROBE, 337"-1.000" SPLIT END, 500KHz - 2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-018	MANUAL BOLT HOLE PROBE,1.000".1.062" SPLIT END, S00KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-019	MANUAL BOLT HOLE PROBE,1.062".1.125" SPLIT END, SOOKHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-020	MANUAL BOLT HOLE PROBE,1.125".1.137" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-021	MANUAL BOLT HOLE PROBE,1.187"-1.250" SPLIT END, 500KHz - 2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-022	MANUAL BOLT HOLE PROBE,1.250".1.312" SPLIT END, SOOKHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-023	MANUAL BOLT HOLE PROBE,1.312".1.375" SPLIT END, SOOKHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
MBHP-024	MANUAL BOLT HOLE PROBE, 1.375"-1.437" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
MBHP-025	MANUAL BOLT HOLE PROBE, 1.437"-1.500" SPLIT END, S00KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQOVALENT
MBHP-026	CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance. MANUAL BOLT HOLE PROBE,1.500"-1.562" SPLIT END, 500KHz -2MHz UNSHIELDED W/ COLLAR, DIFFERENTIAL/REFLECTION D COIL, TRIAX FISCHER			•	
MCSP-004	CONNECTOR, 2.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance. MANUAL COUNTER SINK PROBE 100" DEGREES SOOKHz-2MHz WITH TRIAX FISCHER CONNECTOR.125" DIAMETER. Includes Test Report and Certificate of Conformance.	•			
NDT734P1	or conformance. Boeing Transducer Positioner Part 4 57-54-02 Page 6 Figure 2. Includes Certificate of Conformance.				
NDT734P2L	Boeing Transducer Positioner Part 4 57-54-02 Page 7 Figure 3. Includes Certificate of Conformance.				
NDT734P2R	Boeing Transducer Positioner Part 4 57-54-02 Page 7 Figure 3. Includes Certificate of Conformance.				•
NEC-1062	NDT ENGINEERING CORP. HIGH FREQUENCY PROBE UNSHIELDED 25-500KHZ DIFFERENTIAL, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	AF-5048			
NEC-1062G	NDT ENGINEERING CORP. NEC-1062 PROBE GUIDE. Includes Certificate of Conformance.	AF-5048/G			·
AURFB-5.5MSE/1.5WL	UNIVERSAL FLAT BOTTOM ROTARY PROBE (DELRIN) WITH A 30° COIL ANGLE 5.5mm#j0(0.2165"), 40mm(1.5") WORKING LENGTH 4 PIN FISCHER CONNECTOR, 100KHZ-2MHZ. Includes Test Report and Certificate of Conformance.				
PT.24	SUFACE PROBE 90° DEGREES.063° DROP.100°Ø SHAFT DIAMETER BENT 15° DEGREES,10.0° LONG WITH TRIAX FISCHER CONNECTOR. FREQUENCY S00KH-2MHz. Includes Test Report and Certificate of Conformance.	1R90F101/161 MEG	APN-906-10B/1MHZ		
PT.53	LOW FREQUENCY REFLECTION SPOT PROBE .750"Ø DIAMETER, 2.0" TALL WITH TRIAX FISCHER CONNECTOR. 100Hz-10KHz. Includes Test Report and Certificate of Conformance.	SPO-2572			
PWA75909	ENGINE BLADE PROBE, DIFFERENTIAL 1-4 MHz, ATTACHED CABLE 6.0' FEET LONG WITH 16 PIN LEMO CONNECTOR FOR NOTEC SERIES INSTRUMENTS. DIFFERENTIAL 1-4 MHz. Includes Test Report and Certificate of Conformance.	AF-8001			
SLD-001	SLIDING PROBE, REFLECTION, 1KHz-100KHz, WITH TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformation.	AF-6004			
SPT-001	LOW FREQUENCY REFLECTION SPOT PROBE 500HZ-100KHZ.400"OD, USE WITH NDT396 TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	AF-4011			
SPT-015	LOW FREQUENCY REFLECTION SPOT PROBE, .329" OD, 50-500KHz, TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance	AF-4205			
TBLFC.030-6	BLADE PROBE, .030 THICK, 6" LONG, STRAIGHT, 50-500KHZ, TRIAX FISCHER CONNECTOR, 737 PT 6 57-30-09. Includes test report and Certificate of Conformance.	ATBL030-6			
APN-9375-6	SURFACE PROBE. 90 DEG. 3/8 DROP. 1/8" DIA TUBING. 6" LONG. MICRODOT CONNECTOR. 50-500 kHZ. Includes Test Report and Certificate of Conformance.				
ARR.281SS/1.5WL	RECHII STAINLESS STEEL BOLT HOLE PROBE, 281°Ø, 100K-2MHz, 4 PIN STEP LEMO, 1.5WORKING LENGTH. Includes Test Report and Certificate of Conformance	•	•		
AUR-3.9MSS/125MWL	STAINLESS STEEL ROTARY PROBE 3.9mmØ DIAMETER, 125mm(4.921") WORKING LENGTH SUPPLIED WITH A 4 PIN FISCHER CONNECTOR( MINI ROHMANN) Includes Test Report and Certificate of Conformance	RSM3-9-125			
AF-5144/TF	Rigid Surface Probe Absolute Shielded, 200KHz Center Frequency, .187"Ø Tip, 90°, .250" DROP, 15° Degree Crank, 4.5" long with Triax Fischer Connector. Includes Test Report and Certificate of Conformance. Reference: 610-094-111	312P24			
AF-5218	Rigid Surface Probe Absolute Shielded, 4.5" long, 90°, 350KHz-3MHz, .250" Drop, 15° Degree Crank. 6" Long With Triax fischer Connector. Includes Test Report and Certificate of Conformance.	314P24			
ATPN-925-5.5	RIGID SURFACE PROBE 50-500KHz, 90° DEGREES, .250" DROP 5.5" LONG TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	PAB905502			
AF-5215	CUSTOM EDDY CURRENT EDGE HOLE PROBE, SPLIT END, 200KHz-500KHz, .213"Ø WITH A TRIAX FISCHER CONNECTOR, 4.0" WORKING LENGTH.				
AF-561B	RIGID SURFACE PROBE 50-500KHz, BENT DOWN 90" AT 1.0" FROM THE TIP, .030" DROP, .125"Ø TUBING, 6.0" LONG WITH A TRIAX FISCHER CONNECTOR. Includes Test Report and Certificate of Conformance.	AF-561B			
ATPR-93-5	Rigid Pencil Probe Shielded, Reflection, .187"Ø Diameter Tubing, .300" Drop, 4KHz-100KHz, 5.0" Long with a Triax Fischer Connector. Includes Test Report and Certificate of conformance.	SPC304 1R/Fe			
AURFB250SE/2WL	UNIVERSAL ROTARY FLAT BOTTOM PROBE SUPPLIED WITH A 4 PIN FISCHER CONNECTOR 2.0" WORKING LENGTH 100KHz-2MHz. EXPANDABLE FROM .250". 312"Ø Includes Test Report and Certificate of Conformance.	•			
AURFX187SE/5L	FLEXIBLE ROTARY PROBE 5.0" OVERALL LENGTH WITH COLLAR. EXPANDABLE FROM .187" - 250" DIA PLASTIC HEAD 4 PIN FISCHER CONNECTOR 100KHZ-2MHZ Includes Test Report and Certificate of Conformance	EMFLXY.187-250/5L			
AFNDT-3262AL	Ulympus Style Aluminum multi-hole reference standard. Contains 21 hole sizes; 4.0mm, 4.5mm 5.0mm, 5.5mm, 6.0mm, 6.5mm, 7.0mm, 7.5mm, 8.0mm, 8.5mm, 9.0mm, 9.5mm, 10.0mm, 10.5mm, 11.0mm, 11.2mm, 13.0mm, 14.0mm, 15.0mm and 16.0mm hole diameters. EDM notch = 0.5mm	MHS-21			
ATMH-1.0SE/24WL	MANUAL BOLT HOLE PROBE 50-500KHz UNSHIELDED W/ COLLAR, ABS COIL, TRIAX FISCHER CONNECTOR, 24.0" WORKING LENGTH. Includes Test Report and Certificate of Conformance	•			
AF-4068/4F	LOW FREQUENCY REFLECTION PROBE, 355° Ø ID, 650° Ø OD, 500H2-5KH2 WITH SUPPLIED WITH A 4 PIN LEMO CONNECTOR. REFERENCE: 737 PART 6 55-10-64. Includes Test Report and Certificate of Conformance.	TEK-4067			
AF-4081/4F	UNIBODY LOW FREQUENCY REFLECTION RING PROBE 500Hz-5KHz, 400"Ø ID, .670"Ø OD, SUPPLIED WITH A 4 PIN LEMO CONNECTOR. REFERENCE: 737 PART 6 55-10-64. Includes Test Report and Certificate of Conformance.	RDP.674/2K			
AXPN-92-6BFX	FLEXIBLE SUFACE PROBE .072"Ø OD TIP, BENT 90" DEGREES .200" DROP 6.0" LONG 50-500KHZ SUPPLIED WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MMP902-60FX			
APN-925-6FX/1MHZ	SURFACE PROBE 200KHz-2MHZ 90° DEGREES .250° DROP 6.0° LONG MICRODOT CONNECTOR Includes Test Report and Certificate of Conformance	•			
AF-5265/2MHZ	RIGID SURFACE PENCIL PROBE, ABS. Shielded, Right Angle Shaft, 0.200" in. (5.08 mm) drop bent 15" 1/2" from the tip. 350KHz-3MHz. Includes Test Report and Certificate of Conformance. 610-097-042	314P16	610-097-042		
AF-5266/200K	RIGID SURFACE PENCIL PROBE, ABS Shielded, Right Angle Shaft, 0.200" in. (5.08 mm) drop bent 15° 1/2" from the tip. 20KHz-200KHz., 4.5 " Long. Includes Test Report and Certificate of Conformance. 610-104-031	312P14F	610-104-031		
APN-425-6FX/1MHZ	RIGID SURFACE PROBE, 45° DEGREES, 125° Ø TIP .250° DROP, CURVED, 200KHz-2MHz, 6.0° LONG WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
	STAINLESS STEEL ROTATING SCANNER PROBE 16.4MMØ DIA, 100KHz-2MHz , 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.				
	STAINLESS STEEL ROTATING SCANNER PROBE 16.6MMØ DIA, 100KHz-2MHz , 4 PIN FISCHER CONNECTOR 35MM WORKING LENGTH. Includes Test Report and Certificate of Conformance.			•	
AFS-590AS	90° IN ALUMINUM MINITURE ANGLE BEAM TRANSDUCER 5 MHz .187" X .187", SIDE MOUNT MICRODOT CONNECTOR CASE SIZE: .55"L x .260"W x .450"H. Includes Test Report and Certificate of Conformance.			•	•
	RIGID SURFACE PROBE125"Ø TIP 90° DEGREES .500" DROP, TRIAX FISCHER CONNECTOR 350KHz-3MHz, 5.0" LONG. Includes Test Report and Certificate of Conformance.		•	•	•
	RIGID SURFACE PROBE125"Ø TIP 90° DEGREES .500" DROP, TRIAX FISCHER CONNECTOR 350KHz-3MHz, 12.0" LONG. Includes Test Report and Certificate of Conformance.	RSM4-7-50		•	•
	RIGID SURFACE PROBE, 45° DEGREES, 125" Ø TIP .250° DROP, CURVED, 50-500KHZ 6.0° LONG WITH A MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.			•	
	ADJUSTABLE ROTATING SCANNER PROBE 100KHz-2MHz, SUPPLIED WITH A 4 PIN FISCHER CONNECTOR, 30mm WORKING LENGTH. EXPANDABLE FROM 5.0-6.0mmØ. Includes Test Report and Certificate of Conformance.	URY 5-6M/30WL		•	