

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFC-0540F	Custom 6 inch long handle with pivoting yoke. 10MHz low profile focused transducer with replaceable pencil delay tip.	.	.	.	.
ADL-1025HD	10 MHz .25" DUAL ELEMENT PIEZOCOMPOSITE TRANSDUCER WITH DUAL MICRODOT CONNECTORS OR INTEGRAL CABLE	DA312	DA412	.	.
ADL-525/L00	5 MHz .25" DUAL ELEMENT PIEZOCOMPOSITE TRANSDUCER WITH 00 LEMO INTEGRAL CABLE.. PERSPLEX FACE	.	.	.	.
AFK-UTASW5-12	ULTRASONIC ANGLE BEAM TRANSDUCER KIT. CONSISTS OF A QUANTITY OF 12 5 MHz TRANSDUCERS WITH MICRODOT CONNECTORS FOR INSPECTION OF ALUMINUM SURFACES. Includes Test Report and Certificate of Conformance. Custom fitted waterproof Kit Box Included. Kit Part Numbers Include: AFX-545AT, AFX-560AT, AFX-570AT, AFS-545AT, AFS-560AT, AFS-570AT, AFM-545AT, AFM-560AT, AFM-570AT, AFL-545AT, AFL-560AT, AFL-570AT	.	.	.	.
AFK-UTASW10-12	ULTRASONIC ANGLE BEAM TRANSDUCER KIT. CONSISTS OF A QUANTITY OF 12 10 MHz TRANSDUCERS WITH MICRODOT CONNECTORS FOR INSPECTION OF ALUMINUM SURFACES. Includes Test Report and Certificate of Conformance. Custom fitted waterproof Kit Box Included. Kit Part Numbers Include: AFX-1045AT, AFX-1060AT, AFX-1070AT, AFS-1045AT, AFS-1060AT, AFS-1070AT, AFM-1045AT, AFM-1060AT, AFM-1070AT, AFL-1045AT, AFL-1060AT, AFL-1070AT	.	.	.	.
ABM-5026T-R	13.5" in ALUMINUM 5MHZ TRANSDUCER WITH A 1.33" RADIUS, SUPPLIED WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .500"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
ABM-5021T	45" in ALUMINUM 5MHZ TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .500"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
ABM-5022S	30" in ALUMINUM 5MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .500"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
ABM-5023S	35" in ALUMINUM 5MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .500"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFL-1045AT	45" ALUMINUM, ANGLE BEAM TRANSDUCER 10MHZ. .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	LA-4510T	SU 1045AT	.	.
AFS-1377-1	B777 10 MHz custom L-Wave transducer with a side mount microdot connector, .900" radius 9.0° degrees incident angle. Used on NDT780-A. Includes Test Report and Certificate of Conformance. 777 PART 4 57-50-01	TEK-5828-1	.	.	.
AFS-1377-2	B777 10 MHz custom L-Wave transducer with a side mount microdot connector, .800" radius 7°degrees incident angle. Used on NDT780-B. Includes Test Report and Certificate of Conformance. 777 PART 4 57-50-01	TEK-5828-2	.	.	.
AFS-1377-3	B777 10 MHz custom L-Wave transducer with a side mount microdot connector, 1.05" radius 6.5° degree incident angle. Used on NDT780-C. Includes Test Report and Certificate of Conformance. 777 PART 4 57-50-01.	TEK-5828-3	.	.	.
AFS-1377-4	B777 10 MHz custom L-Wave transducer with a side mount connector, .900" radius 10° degree incident angle. Used on NDT780-D. Includes Test Report and Certificate of Conformance. 777 PART 4 57-50-01	TEK-5828-4	.	.	.
AFS-1377-5	B777 10 MHz custom L-Wave transducer with a side mount microdot connector, .800" radius 7° degree incident angle. Used on NDT780-E. Includes Test Report and Certificate of Conformance. 777 PART 4 57-50-01	TEK-5828-5	.	.	.
AFS-1377-6	B777 10 MHz custom L-Wave transducer 8° degree incident angle with a side mount microdot connector, 1.05" radius used on NDT780-F. Includes Test Report and Certificate of Conformance. 777 PART 4 57-50-01	TEK-5828-6	.	.	.
AFS-1240	45" ALUMINUM 5 MHZ .25" X .25" SIDE MOUNT ANGLE BEAM TRANSDUCER. CASE SIZE: .800"L x .300"W x .400"H MAX WITH MICRODOT CONNECTOR	291-424-600	8/45/5S BPS	.	.
AFC-1215HS	STRAIGHT BEAM CONTACT TRANSDUCER, ELEMENT SIZE .125", 15MHZ. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-470AT	70" IN ALUMINUM 4 MHz .25" X .25" ANGLE BEAM TRANSDUCER. CASE SIZE: .75"L x .37"W x .50"H, WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	RCSM-70-4MHZ-F89	.	.	.
323P	BOEING ULTRASONIC TRANSDUCER SHOE 737 PART 4 53-10-38 FIGURE 3 PAGE 7. Includes Certificate of Conformance.	.	.	.	.
362-002-244	Krautkramer Branson Custom Acrylic Transducer Wedge 35.5", 1.624" (41.25-mm) Radius. Includes Certificate of Conformance.	362-002-244	.	.	.
362-002-245	Krautkramer Branson Custom Acrylic Transducer Wedge 45.6", .812" Radius. Includes Certificate of Conformance.	362-002-245	.	.	.
365G	BOEING TRANSDUCER GUIDE 737 PART 4 71-20-01 PG.4 FIGURE 1 DETAIL II. Includes Certificate of Conformance.	.	.	.	.
4028G	BOEING TRANSDUCER GUIDE 747 57-40-03 FIGURE 2 PAGE 5. MATERIAL: LUCITE. Includes Certificate of Conformance.	.	.	.	.
4028P	BOEING TRANSDUCER POSITIONER 747 57-40-03 FIGURE 1 PAGE 4A. MATERIAL: ALUMINUM. Includes Certificate of Conformance.	.	.	.	.
412B5MHZ35R41FE	CUSTOM 5MHZ 35° TRANSVERSE WAVE TRANSDUCER WITH A 41mm (1.614") RADIUS WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-5002-41M	.	.	.
412B5MHZ35R48FE	CUSTOM 5MHZ 35° TRANSVERSE WAVE TRANSDUCER WITH A 48mm(1.890") RADIUS WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-5002-48M	.	.	.
412B5MHZ45FE	CUSTOM 5MHZ 45° TRANSVERSE WAVE TRANSDUCER WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance. REFERENCE: AIRBUS A300-600 PART 4 54-50-15	412B	412B5MHZ45FE	.	.
53-20-167/2	BAE PROBE RADIUS SHOE, 146-RJ 53-238 53-20-21 PT 4 FIGURE 4&5 PAGE 519 & 512. Includes Test Report and Certificate of Conformance.	.	.	.	.
53-20-169/2	BAE 146-RJ SERIES REFERENCE STANDARD 53-20-21 PT 4 FIGURE 3 PAGES 505. Includes Test Report and Certificate of Conformance.	kSk	.	.	.
AFM-245ST	45" IN STEEL 2.25 MHz .25" X .25" TOP MOUNT ANGLE BEAM TRANSDUCER. CASE SIZE: .750"L x .370"W x .500"H. Includes Test Report and Certificate of Conformance	.	.	.	.
AFM-260ST	60" IN STEEL MINI ANGLE BEAM TRANSDUCER, 2.25MHz .25" x .25" ELEMENT, CASE SIZE: (.750"L x .370"W x .500"H ) TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-0635AGR	5MHZ 40° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH SIDE MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP35LPR	.	.	.
AFS-0636AGR	5MHZ 45° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH END MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP36LPR	.	.	.
AFS-0637AGR	5MHZ 50° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH SIDE MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP37LPR	.	.	.
AFL-1070AT	70° ALUMINUM, ANGLE BEAM TRANSDUCER 10MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0638AGR	5MHZ 55° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH SIDE MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP38LPR	.	.	.
AFS-0639AGR	5MHZ 60° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH SIDE MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP39LPR	.	.	.
53-20-171/2	RADIUSED ULTRASONIC PROBE SHOE USED WITH K5(KAF-525-75) AND REFERENCE STANDARD 53-20-165/1 (BAe 146 Series). Includes Certificate of Conformance.	.	.	.	.
99F57204103000	AIRBUS GUIDE RING A330 PT 4 57-20-16. Includes Test Report and Certificate of Conformance.	.	.	.	.
99F57204104001	AIRBUS SEARCH UNIT GUIDE A330 PT 4 57-20-16. Includes Test Report and Certificate of Conformance.	.	.	.	.
99L57203007000	A380 SEARCH UNIT GUIDE BLOCK; DELRIN(TEFLON), FIGURE:57-11-03-991-026-A. Includes Test Report and Certificate of Conformance.	.	.	.	.
99L57203008000	A380 SEARCH UNIT GUIDE BLOCK; DELRIN(TEFLON), FIGURE:57-11-03-991-027-A. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-0512-4L	5MHz High Damped straight beam transducer skewed 4° to the left attached to a 2.0" inch handle with a total length of 4.0". .125" element with a case diameter of .187" $\phi$ and a case height .500". Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-14005	MINI ANGLE BEAM TRANSDUCER 51° IN STEEL 10MHZ WITH A SIDE MOUNT MICRODOT CONNECTOR, .130" x .187" ELEMENT, CASE SIZE: .354"L(9mm) x .196"(5mm)W x .315"(8mm)H. Includes Test Report and Certificate of Conformance.	SPO 5630	.	.	.
AFC-0512-4R	5MHz High Damped straight beam transducer skewed 4° to the right attached to a 2.0" inch handle with a total length of 4.0". .125" element with a case diameter of .187" $\phi$ and a case height .500". Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-0516	5MHz, .250" $\phi$ element contact transducer(high damped) case size(.700" H x .312" $\phi$ Case) top mount microdot connector. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-0517-4L	10MHz High Damped straight beam transducer skewed 4° to the left attached to a 2.0" inch handle with a total length of 4.0". .125" element with a case diameter of .187" $\phi$ and a case height .500". Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-0517-4R	10MHz High Damped straight beam transducer skewed 4° to the right attached to a 2.0" inch handle with a total length of 4.0". .125" element with a case diameter of .187" $\phi$ and a case height .500". Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-0519	MSW-QC STYLE QUICK CHANGE TRANSDUCER 10MHZ .25" ELEMENT 3/8-32 THREAD. HIGH DAMPED. Includes Test Report and Certificate of Conformance.	389-025-070	.	.	.
AFC-0520	MSW-QC STYLE QUICK CHANGE TRANSDUCER 5MHZ .25" ELEMENT 3/8-32 THREAD. HIGH DAMPED. Includes Test Report and Certificate of Conformance.	KBA6-35, 113-224-591	MSWQC 224-591,234-591	MSWQC 224-591, KBA6-35	TCS-255T-32, V543, A535SRM
AFS-1074-40	SEARCH UNIT 40°, 5MHZ SHEARWAVE... Case size (.35"W x .47"L x .63"H) Top mount connector. (57-53-50-991-008). Includes Test Report and Certificate of Conformance	0545009	TEK-5041-40	.	.
AFC-0529S	GENERAL PURPOSE 5MHZ 1/4" $\phi$ COMPRESSION. STRAIGHT BEAM TRANSDUCER. SIDE MOUNT MICRODOT CONNECTOR, KNURLED CASE SIZE: .750"H x .400" $\phi$ . Includes Test Report and Certificate of Conformance.	GD-0504	.	.	.
AFC-0900RG	CUSTOM STRAIGHT BEAM TRANSDUCER 2.25MHz 1.0" $\phi$ . CASE SIZE:1.625"L x 1.250"W x .810"H WITH A TOP MOUNT BNC CONNECTOR. Includes Test Report.	.	.	.	.
AFC-1012HS	Contact Transducer, 10 MHz, 0.125 in. Element Diameter, Fingertip Case Style, Side Mount Microdot Connector. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-1018-4T	10MHZ .187" $\phi$ ELEMENT, .25" $\phi$ STAINLESS STEEL CASE .400" TALL. WITH A TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	TC4-1810T	.	.	.
AFC-1018-5S	10MHZ .187" $\phi$ ELEMENT, .25" $\phi$ STAINLESS STEEL CASE .500" TALL. WITH AN END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-1018-5T	10MHZ .187" $\phi$ ELEMENT, .25" $\phi$ STAINLESS STEEL CASE .500" TALL. WITH A TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-1018S	10MHZ .187" $\phi$ ELEMENT, .25" $\phi$ STAINLESS STEEL CASE .500" TALL. WITH AN END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-1025H32	Quick fit Screw in Type straight beam transducer, 10MHz .250" $\phi$ Diameter, Top Mounted Microdot Connector, MSW Style, 3/8-32 thread. Includes Test Report and Certificate of Conformance.	A5445-5M	.	.	.
AFC-1025HS	High Damped Contact Transducer, 10 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Right (Side) Microdot Connector (.500" H x .390"OD). Includes Test Report and Certificate of Conformance.	M112-RM	V112-RM	V112RM	.
AFC-1025S	Contact Transducer, 10 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Right Microdot Connector, (.500" H x .375"OD). Includes Test Report and Certificate of Conformance.	SUC 168, A112S-RM	SUC 168, CM1004-S	CG-1002-GP	U8403115, TC-2510S
AFS-1074-60	SEARCH UNIT 60°, 5MHZ SHEARWAVE... Case size (.35"W x .47"L x .63"H) Top mount connector. Includes Test Report and Certificate of Conformance.	TEK-5041-60	.	.	.
AFC-125-6T	5MHZ STRAIGHT BEAM TRANSDUCER, .188" $\phi$ CASE DIAMETER X .600" LONG, TOP MOUNT MICRODOT CONNECTOR. USED WITH NDT6023 AND NDT6023P. Includes Test Report and Certificate of Conformance.	TC6-145T	.	.	.
AFC-150HS	1.0MHz .500" $\phi$ dia. CONTACT (STRAIGHT BEAM) TRANSDUCER HIGH DAMPED ELEMENT, SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	TC-501	.	.	.
AFC-150S	1.0MHz .500" $\phi$ dia. PIEZO-COMPOSITE ELEMENT CONTACT (STRAIGHT BEAM) TRANSDUCER. Includes Test Report and Certificate of Conformance.	V103	M103, 241-043	V103, CM-0108-S-RM	241-043-CR

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFC-1512HS	Contact Transducer, 15 MHz, 0.125 in. Element Diameter, Fingertip Case Style, Side Mount Microdot Connector. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-1525HS	High Damped Contact Transducer, 15 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Right (Side) Microdot Connector (.500" H x .390"OD). Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-1525S	Contact Transducer, 15 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Right Microdot Connector. (.500" H x .375"OD). Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-169	5MHZ STRAIGHT BEAM TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR (.400"H x .375" O.D.), Used with NDT3023P1, NDT3023P2, NDT3023P3. Includes Test Report and Certificate of Conformance.	SUC 169	SUC 169	.	.
AFC-175HS	1.0MHz .750"Ø dia. CONTACT (STRAIGHT BEAM) TRANSDUCER HIGH DAMPED ELEMENT, SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0556	35" in ALUMINUM 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .25H"x.325W" ELEMENT, CASE SIZE: .75"L x .55"H x .43"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0557	45" in ALUMINUM 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .25H"x.325W" ELEMENT, CASE SIZE: .75"L x .55"H x .43"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-2012HS	Contact Transducer, 20 MHz, 0.125 in. Element Diameter, Fingertip Case Style, Side Mount Microdot Connector. Includes Test Report and Certificate of Conformance.	M116-RM	.	.	.
AFC-210HS	Contact Transducer, 2.25 MHz, 1.0 in. Element Diameter, Standard Case Style, Side Microdot Connector. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-221HS	High Damped Videoscan Type Contact Transducer, 2.25 MHz, 1.00"(25.4mm)Ø Element Diameter, Fingertip Case Style, End Mount Microdot Connector. Includes Test Report and Certificate of Conformance.	V104-RM	.	.	.
AFC-225S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 2.25MHz, .25"Ø WITH SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-275HS	Contact Transducer, 2.25 MHz, 0.75 in. Element Diameter, Standard Case Style, Side Microdot Connector. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-3022HS	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER, KNURLED CASE, 2.25MHZ, .25"Ø, .300"Ø DIAMETER by .600" LONG HOUSING. WITH SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-512HDS	STRAIGHT BEAM CONTACT TRANSDUCER .125" DIAMETER 5MHZ HIGH DAMPED WITH SIDE MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	V1091	.	.	.
AFC-512S	5MHz .125" dia FINGER TIP STRAIGHT BEAM TRANSDUCER (VIDEOSCAN TYPE)... Includes Test Report and Certificate of Conformance.	V1091	.	.	.
AFC-518S	FINGERTIP CONTACT TRANSDUCER, 5MHz, .187Ø ELEMENT, .25Ø CASE. END MOUNTED MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	TC5-185S	.	.	.
AFC-525	Contact Transducer, 5 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Right Microdot Connector. (.500" H x .375"OD). Includes Test Report and Certificate of Conformance.	SUC 166	.	.	.
AFC-525-65S	5MHz, 5mm(.25") dia. element high damped side mounted microdot connector. Case size (.395" dia. x .650"H). Includes Test Report and Certificate of Conformance.	2914249	.	.	.
AFC-525-7S	5MHz, 5mm(.25") dia. element high damped side mounted microdot connector. Case size (.395" dia. x .670"H). Includes Test Report and Certificate of Conformance.	K5K	H12845	.	.
AFC-525-8T	5MHZ CONTACT TRANSDUCER, .25 ELEMENT, .375Ø CASE, .800" TALL, TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	SUC 166-8T	SUC 166-8T	.	.
AFC-525H32	Quick fit Screw in Type straight beam transducer, 5MHz, .250"Ø Diameter, Top Mounted Microdot Connector, MSW Style, 3/8-32 thread. Includes Test Report and Certificate of Conformance.	A543S-SM	.	.	.
AFC-525S	Contact Transducer, 5 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Right Microdot Connector, .500" H x .375"OD). Includes Test Report and Certificate of Conformance.	A110S-RM	CF-0502-GP	CM-0504-5	.
AFC-525T-32	5MHz .250" DIA. Alpha Series straight beam transducer. MSWQC Style, 1/4-28 THREAD Used with MSWQCA01105940. Includes Test Report and Certificate of Conformance.	MSWQC250124591	MSWQC250124591	.	.
AFC-537S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 5.0MHz, .375"Ø WITH END MOUNTED MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	57A4268	CF-0503-GP	.	.
AFC-537S-6	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 5.0MHz, .375"Ø .600" H x .500" Ø WITH END MOUNTED MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	TC-375-6	.	.	.
AFC-550B	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 5.0MHz, .500"Ø WITH RIGHT MOUNT BNC CONNECTOR. Includes Test Report and Certificate of Conformance.	A609S-RB	.	.	.
AFC-550BCS	SINGLE ELEMENT FINGER TIP END MOUNT BNC CONTACT TRANSDUCER 5.0MHz, .500"Ø ELEMENT WITH CERAMIC WEAR PLATE. Includes Test Report and Certificate of Conformance.	113-244-043	113-244-043	TCC-505S,	.
AFC5-H237	MSW-QC STYLE KBA QUICK CHANGE SCREW IN TRANSDUCER 2.25MHz, .25"Ø ELEMENT 3/8-32 THREAD. HIGH DAMPED. Includes Test Report and Certificate of Conformance.	KBA222-590	MSWQC	222-590	.
AFL-1075AS	75° ALUMINUM, ANGLE BEAM TRANSDUCER 10MHz .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	SU 1075AS	.	.	.
AFL-445AS	45° ALUMINUM, ANGLE BEAM TRANSDUCER 4MHz .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H ) END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MWB45-4	.	.	.
AFL-460AS	60° ALUMINUM, ANGLE BEAM TRANSDUCER 4MHz .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H ) END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MWB60-4	.	.	.
AFL-470AS	70° ALUMINUM, ANGLE BEAM TRANSDUCER 4MHz .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H ) END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MWB70-4	.	.	.
AFL-545AS	45° ALUMINUM, ANGLE BEAM TRANSDUCER 5MHz .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	LA-455S	SU 545AS	.	.
AFL-545AT	45° ALUMINUM, ANGLE BEAM TRANSDUCER 5MHz .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	LA-455T	SU 545AT	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFL-560AS	60° ALUMINUM, ANGLE BEAM TRANSDUCER 5MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	LA-605S	SU 560AS	.	.
AFL-560AT	60° ALUMINUM, ANGLE BEAM TRANSDUCER 5MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance. 737 Pt4, 57-10-08 & 737 Pt4, 57-10-15	LA-605T	SU 560AT	.	.
AFL-570AS	70° ALUMINUM, ANGLE BEAM TRANSDUCER 5MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H ) END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance. 737 Pt4, 57-10-17	LA-705S	SU 570AS	.	.
AFL-570AT	70° ALUMINUM, ANGLE BEAM TRANSDUCER 5MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance. 737 Pt4, 57-10-05	LA-705T	SU 570AT	.	.
AFIXR-2	90° DEGREE FLEXIBLE SHAFT RIGHT ANGLE PROBE EXTENDER SUPPLIED WITH A MICRODOT CONNECTOR, 2.0" LENGTH. Includes Certificate of Conformance.	SPC-604FX-2	.	.	.
AFM-1045AS	45° ALUMINUM 10 MHZ .25" X .25" SIDE MOUNT MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L x .37" W x .50" H WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	SUM-1045AS	.	.	.
AFM-1060AS	60° IN ALUMINUM 10 MHZ .25" X .25" MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L x .37" W x .50" H WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	SUM-1060AS	.	.	.
AFM-1070AS	SUB-MINITURE 70° ANGLE BEAM TRANSDUCER IN ALUMINUM, 10MHZ .25" X .25" ELEMENT, CASE SIZE: .75" X .37" X .50" WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	SUM-1070AS	.	.	.
AFM-1070AT	SUB-MINITURE 70° ANGLE BEAM TRANSDUCER IN ALUMINUM, 10MHZ .25" X .25" ELEMENT, CASE SIZE: .75" X .37" X .50" WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	57A3087	SUM-1070AT	57A3087	.
AFM-240AT	40° ANGLE BEAM TRANSDUCER IN ALUMINUM, 2.25MHZ .25" X .25" ELEMENT, CASE SIZE: .75" X .37" X .50" WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-245AS	45° IN ALUMINUM MINI ANGLE BEAM TRANSDUCER, 2.25MHZ .25" X .25" ELEMENT, CASE SIZE: (.75" L X .37" W X .50" H ) END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-260AS	60° IN ALUMINUM MINI ANGLE BEAM TRANSDUCER, 2.25MHZ .25" X .25" ELEMENT, CASE SIZE: (.75" L X .37" W X .50" H ) END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	SUM 260AS	.	.	.
AFM-260AT	60° IN ALUMINUM MINI ANGLE BEAM TRANSDUCER, 2.25MHZ .25" X .25" ELEMENT, CASE SIZE: (.75" L X .37" W X .50" H ) TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	SUM 260AT	.	.	.
AFM-270AS	70° ANGLE BEAM TRANSDUCER IN ALUMINUM, 2.25MHZ .25" X .25" ELEMENT, CASE SIZE: .75" X .37" X .50" WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-270AT	70° ANGLE BEAM TRANSDUCER IN ALUMINUM, 2.25MHZ .25" X .25" ELEMENT, CASE SIZE: .75" X .37" X .50" WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-460AT	60° IN ALUMINUM 4 MHZ .25" X .25" ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L X .37" W X .50" H, WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	RCSM-60	.	.	.
AFM-530AT	30° ANGLE BEAM TRANSDUCER IN ALUMINUM, 5MHZ .25" X .25" ELEMENT, CASE SIZE: .75" X .37" X .50" WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-545AD-1	45° ALUMINUM 5 MHZ 1/4" X 1/4" TOP AND SIDE MOUNT TRANSDUCER BUILT IN ONE. TWO MICRODOT CONNECTORS. CASE SIZE: .700" L X .320" W X .620" H. Test Report and Certificate of Conformance.	57A3064TC	.	.	.
AFM-545AS	45° ALUMINUM 5 MHZ .25" X .25" SIDE MOUNT MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L X .37" W X .50" H WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	57A3052	SUM-545AS, A591S-RM	57A3052	PAB-0504-45,
AFM-545AT	45° IN ALUMINUM 5 MHZ .25" X .25" ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L X .37" W X .50" H, WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	57A3064	SUM 545AT, PAB-0504-45	MA-455T	942162
AFM-545ST	45° IN STEEL 5 MHZ .25" X .25" ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L X .37" W X .50" H, WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance...	57A8299	SUM-545ST	57A8299	.
AFM-545TS	45° ANGLE BEAM TRANSDUCER IN TITANIUM, 5MHZ .25" X .25" ELEMENT, CASE SIZE: .75" X .37" X .50" WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MT-455S	.	.	.
ARD-150	1.0MHZ .500"Ø REPLACEABLE DELAY TRANSDUCER. SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = .437". Other lengths available upon request. Includes Test Report and Certificate of Conformance.	.	.	.	.
ARD-350T	3.50MHZ .500"Ø REPLACEABLE DELAY TRANSDUCER WITH .394" LONG DELAY TIP. Includes DRR202 RETAINING RING. Includes Test Report and Certificate of Conformance.	C545-SM	.	.	.
AFS-0600SL	45° IN STEEL 10MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER(LEFT) WITH MICRODOT CONNECTOR, .187" H X .130" W ELEMENT, CASE SIZE: .375" L X .400" H X .230" W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-560AS	60° IN ALUMINUM 5 MHZ .25" X .25" MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L X .37" W X .50" H WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	A592S-RM	A592S	A592S-RM	57A3067
AFM-560AS.	60° IN ALUMINUM 5 MHZ .25" X .25" MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L X .37" W X .50" H WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	57A3067	57A3067	SUM 560AS	.
AFM-560AT	60° IN ALUMINUM 5 MHZ .25" X .25" ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L X .37" W X .50" H, WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	A592S,57A3065	MA-605T, SUM 560AT	PAB-0504-60AI-RM, 389-020-490	A592S-SM, A592S,57A3065
AFS-0600SR	45° IN STEEL 10MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER(RIGHT) WITH MICRODOT CONNECTOR, .187" H X .130" W ELEMENT, CASE SIZE: .375" L X .400" H X .230" W. Includes Test Report and Certificate of Conformance.	.	.	.	.
ASTW5-3	5 STEP ACRYLIC WEDGE, .400", .420", .440", .460", .480", Stretched Acrylic, 1" X 1" Sq, 1" X 5" LONG +/- .002. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-565AT	65° IN ALUMINUM 5 MHZ .25" X .25" TOP MOUNT MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L X .37" W X .50" H WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-570AS	70° ANGLE BEAM TRANSDUCER IN ALUMINUM, 5MHZ .25" X .25" ELEMENT, CASE SIZE: .75" X .37" X .50" WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	A593S-RM	MA-705S	SUM 570AS	A593S-RM
AFM-570AT	70° ANGLE BEAM TRANSDUCER IN ALUMINUM, 5MHZ .25" X .25" ELEMENT, CASE SIZE: .75" X .37" X .50" WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	A593S-SM	SUM-570AT, 389-020-490	A593S-SM	57A3066TC
AFM-550TTI	50° IN TITANIUM 5 MHZ .25" X .25" ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L X .37" W X .50" H, WITH TOP MOUNT MICRODOT CONNECTOR. NOTE: SOUND EXIT POINT .350" FROM THE FRONT OF TRANSDUCER. Includes Test Report and Certificate of Conformance.	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFM-570TS	70° ANGLE BEAM TRANSDUCER in TITANIUM, 5MHz .25" x .25" ELEMENT, CASE SIZE: .75" x .37" x .50" WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MT-705S	.	.	.
AFM-575AS	ANGLE BEAM TRANSDUCER, 5MHz 75° IN ALUMINUM .25" x 25" ELEMENT, SIDE MOUNT MICRODOT CONNECTOR. CASE SIZE: (.75"L x .375"W x .50"H). Includes Test Report and Certificate of Conformance.	ZP-1/4XL/4-10	389-044-140	AL-945180	ZP-1/4XL/4-10
NDT7001P	BOEING LUCITE WEDGE WITH A .315" Ø FLAT BOTTOM HOLE, 2.010" RADIUS FOR A .25" Ø STRAIGHT BEAM TRANSDUCER. USED WITH REFERENCE STANDARD NDT7001.	.	.	.	.
AFM-557TTI	57° IN TITANIUM 5 MHz .25" X .25" ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L X .37" W X .50" H, WITH TOP MOUNT MICRODOT CONNECTOR. NOTE: SOUND EXIT POINT .350" FROM THE FRONT OF TRANSDUCER. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFX-557TTI	57° IN TITANIUM 5MHz .170" X.187"; MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375" L x .375" H x .260" W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-1291	5MHZ 60° IN ALUMINUM .25" X.187" ELEMENT WITH TOP MOUNT MICRODOT CONNECTOR. CASE SIZE: .350"W X .375"L X .750"H. BOEING 737 PART 4 57-10-13, pg.1 USED WITH NDT3166-06 AND NDT3166-07. Includes Test Report and Certificate of Conformance.	TEK-5557/60T	.	.	.
AFS-0640AG	5MHZ 65° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP40LP	.	.	.
AFM-670AT	70° ANGLE BEAM TRANSDUCER in ALUMINUM, 6MHz .25" x .25" ELEMENT, CASE SIZE: .75" x .37" x .50" WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFP-1012/90	10 MHZ 90° .125" Ø diameter focused pencil transducer with a .060" Replaceable tip. Standard microdot connector. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0503-45T	Mini Angle Beam Transducer, 5.0MHz, 0.187" x 0.187" Element, 45° Shear in Aluminum, Top Mount Microdot Connector. Includes Test Report and Certificate of Conformance.	PAB-0503-45	TEK-0503-45AT	.	.
AFS-0503-70S	Mini Angle Beam Transducer, 5.0MHz, 0.187" x 0.187" Element, 70° Shear in Aluminum, Side Mount Microdot Connector. Includes Test Report and Certificate of Conformance.	PAB-0503-70	TEK-0504-70AS,	PD-238-26	PAB-0503-70
AFS-0503-70T	Mini Angle Beam Transducer, 5.0MHz, 0.187" x 0.187" Element, 70° Shear in Aluminum, Top Mount Microdot Connector. Includes Test Report and Certificate of Conformance.	PAB-0503-70	TEK-0503-70AT	.	.
AFS-0503-90SS	Mini Angle Beam Transducer, 5.0MHz, 0.187" x 0.187" Element, 90° Shear in Steel, Side Mount Microdot Connector. Includes Test Report and Certificate of Conformance.	PAB-0503-90-ST-RM	.	.	.
AFS-0672LP	5MHZ 65° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP22LP	.	.	.
AFS-1065	5MHz 70° degree ANGLE BEAM TRANSDUCER. CASE SIZE: .375" L x .325" W x .425" H. Includes Test Report and Certificate of Conformance.	TEK-5056/70	.	.	.
AFS-1299	5MHZ 70° IN ALUMINUM .25" ELEMENT, TOP MOUNT MICRODOT CONNECTOR. CASE DIMENSIONS: .350"W X .375"L X .750"H. BOEING 737 PART 4 57-10-17, pg.2 USED WITH NDT3186 and NDT3187. Includes Test Report and Certificate of Conformance.	TEK-5558/70T	.	.	.
AFS-0504-70ST-SM	70° ANGLE BEAM TRANSDUCER in STEEL, 5MHz .187" x .25" ELEMENT, CASE SIZE(.550"L x .310"W x .675" H) TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PAB-0504-70ST-SM	.	.	.
AFS-0519	CUSTOM BOEING ANGLE BEAM TRANSDUCER, 50°, 5MHz, .187" x.187" ELEMENT WITH TOP MOUNTED MICRODOT CONNECTOR. .550" x .26" x .450" USED WITH NDT596. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0521	CUSTOM ANGLE BEAM TRANSDUCER 5MHZ 45° in Al .25"x.25" ELEMENT. 690"L x .590"H x .300"W WITH END MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0540	CUSTOM SPRING LOADED TRANSDUCER WITH COLLAR FOR C-130 FUSELAGE SP-78 INSPECTION. Includes Test Report and Certificate of Conformance.	HMT-0898	.	.	.
AFS-0641AG	5MHZ 70° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP41LP	.	.	.
AFS-0642AG	5MHZ 75° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP42LP	.	.	.
AFS-0579T	30° ALUMINUM, ANGLE BEAM TRANSDUCER 5MHZ .330"x.25" ELEMENT, CASE SIZE(.750L X .430W X .550"H) TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0590T	30° ALUMINUM, ANGLE BEAM TRANSDUCER 2.25MHZ .330"x.25" ELEMENT, CASE SIZE(.750L X .430W X .550"H) TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0674LP	5MHZ 75° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP24LP	.	.	.
AFS-1324LP	5MHZ or 8MHZ 75° TRANSVERSE BEAM TRANSDUCER IN STEEL WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .400" x .250" x .630". Includes Test Report and Certificate of Conformance(COC)	CEP24LP	.	.	.
ARD-550	5MHZ, .500" Ø(12.7mm) ACTIVE ELEMENT (HIGH DAMPED), REPLACEABLE DELAY TRANSDUCER SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = .437". Other lengths available upon request. Includes Test Report and Certificate of Conformance.	389-024-410	V206-RM	389-024-410	.
AFM-560AD-1	60° ALUMINUM 5 MHz 1/4" x 1/4" TOP and SIDE MOUNT TRANSDUCER BUILT IN ONE. TWO MICRODOT CONNECTORS. CASE SIZE: .700"L x .320"W x .620"H. Includes Test Report and Certificate of Conformance.	57A3065TC	.	.	.
AFS-0504-40AT	60° ANGLE BEAM TRANSDUCER in ALUMINUM, 5MHz .187" x .25" ELEMENT, CASE SIZE(.47" L x .31" W x .55" H) TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PAB-0504-40	.	.	.
AFS-0504-60AS	60° ANGLE BEAM TRANSDUCER in ALUMINUM, 5MHz .25" x .25" ELEMENT, CASE SIZE(.550" L x .310" W x .675" H) SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PAB-0504-60-AL-RM	.	.	.
AFS-0605S-70	CUSTOM 70° SHEAR WAVE TRANSDUCER .125" ELEMENT. CASE SIZE: 6mm L x 20mm H x 8mm W. Per A330 53-30-30. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-560AS	60° in ALUMINUM 5MHz TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	SUSM 560AS,U8550071	SA-605S	.	.
AFS-0620	60° in ALUMINUM 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, STAINLESS STEEL CASE SIZE: .55"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	SUSM 560AT	.	.	.
AFS-0602	60° in ALUMINUM 5MHz SIDE MOUNT MINI ANGLE BEAM TRANSDUCER WITH MICRODOT CONNECTOR, .187" H x .130" W ELEMENT, CASE SIZE: .375"L x .400" H x .200"W. Includes Test Report and Certificate of Conformance.	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-0601	60° IN ALUMINUM 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH MICRODOT CONNECTOR, .187" H x .130" W ELEMENT, CASE SIZE: .375" L x .400" H x .200" W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-5605S	60° IN STEEL 5 MHz .25" X .25" MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L x .37" W x .50" H WITH SIDE MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	A572-RM	SUM 5605S	PAB-0504-60-ST-RM	MS-605S
AFM-5605T	60° IN STEEL 5 MHz .25" X .25" TOP MOUNT MINTURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L x .37" W x .50" H WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	57A8300	SUM-5605T	MS-605T	.
AFS-0504-70AS	70° ANGLE BEAM TRANSDUCER IN ALUMINUM, 5MHz .25" x .25" ELEMENT, CASE SIZE(.550" L x .310" W x .675" H) SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PAB-0504-70-AL-RM	.	.	.
AFS-0635AG	5MHZ 40° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP35LP	.	.	.
AFS-0636AG	5MHZ 45° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP36LP	.	.	.
AFS-0636AGR	5MHZ 45° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH END MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP18LPR	.	.	.
AFS-0637AG	5MHZ 50° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP37LP	.	.	.
AFS-0638AG	5MHZ 55° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP38LP	.	.	.
AFS-0639	5MHZ 60° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP39	.	.	.
AFS-0639AG	5MHZ 60° TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .710" x .370" x .550". Includes Test Report and Certificate of Conformance(COC)	CEP39LP	.	.	.
AFS-0621	70° IN ALUMINUM 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x .187" ELEMENT, STAINLESS STEEL CASE SIZE: .55" L x .45" H x .26" W. Includes Test Report and Certificate of Conformance.	SUSM 570AT	.	.	.
AFM-570AT-1	70° IN ALUMINUM MINIATURE ANGLE BEAM TRANSDUCER, 5MHz, .20" x .20" ELEMENT, CASE SIZE: .75" L x .30" W x .50" H SUPPLIED WITH A TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFXS-570AT	70° IN ALUMINUM 5MHz .160" X .187"; MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL CASE SIZE: .375" L x .375" H x .260" W. Includes Test Report and Certificate of Conformance.	XA-705T-SS	.	.	.
AFS-0604	70° IN ALUMINUM 5MHZ SIDE MOUNT MINI ANGLE BEAM TRANSDUCER WITH MICRODOT CONNECTOR, .187" H x .130" W ELEMENT, CASE SIZE: .375" L x .400" H x .200" W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0603	70° IN ALUMINUM 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH MICRODOT CONNECTOR, .187" H x .130" W ELEMENT, CASE SIZE: .375" L x .400" H x .200" W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-1000A	ULTRASONIC TRANSDUCER 10MHz .100" x .250" ELEMENT, SUPPLIED WITH END MOUNT MICRODOT CONNECTOR. USED WITH NDT1086P-1. Includes Test Report and Certificate of Conformance.	SUS 1020	SUS 1020	TEK-5000-1	.
AFS-1010L	CUSTOM 5MHz SHEAR WAVE(LEFT) TRANSDUCER FOR NDT567, BOEING 757 PT 4 54-50-02 PAGES 1-10. Includes Test Report and Certificate of Conformance.	TEK-5059L	.	.	.
AFS-1010R	CUSTOM 5MHz SHEAR WAVE(RIGHT) TRANSDUCER FOR NDT567, BOEING 757 PT 4 54-50-02 PAGES 1-10. Includes Test Report and Certificate of Conformance.	TEK-5059R	.	.	.
AFS-1025	Panametrics Integral Angle Beam Transducer 5 MHz 70° in Aluminum. .433"x.433"x.236" case: .187"sq.element. stainless steel case. Includes Test Report and Certificate of Conformance. Panametrics Integral Angle Beam Transducer 5 MHz 70° in Aluminum. ....	A5021-RM, U8438004	A5021RM	.	.
AFS-1027	TRANSDUCER, 5MHz .25" (6.35mm) ELEMENT WITH A 3.937" (100mm) RADIUS. REFERENCE: AIRBUS 318/A319/A320/A321 PART 4 57-29-03 PAGE 404. Includes Test Report and Certificate of Conformance.	545336	545336	TEK-5043	.
AFS-1029	ANGLE BEAM TRANSDUCER 45° AL 5MHZ TOP MOUNT MICRODOT CONECTOR. CASE SIZE: .700" L / x .300" W. Includes Test Report and Certificate of Conformance.	TEK-50105-45A	.	.	.
AFS-1031	ANGLE BEAM TRANSDUCER 70° AL 5MHZ TOP MOUNT MICRODOT CONECTOR. CASE SIZE: .700" L / x .300" W. Includes Test Report and Certificate of Conformance.	TEK-50105-70A	.	.	.
AFS-1044	CUSTOM BOEING TRANSDUCER, 5MHz BACK SHOOTER WITH A 1.600" RADIUS AND A MICRODOT CONNECTOR. BOEING 767 PART 4 71-20-01 USED WITH NDT632. Includes Test Report and Certificate of Conformance.	TEK-5072	SUS-632	.	.
AFX-575AT	75° IN ALUMINUM 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .130" x .187" ELEMENT, CASE SIZE: .375" L x .375" H x .260" W. Includes Test Report and Certificate of Conformance.	XA-755T	HS-877-5-75	.	.
AFS-1070	60° IN ALUMINUM 5 MHz .25" X .25" TOP MOUNT MINTURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L x .37" W x .50" H WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	0505555	.	.	.
AFX-580AT	80° IN ALUMINUM 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .130" x .187" ELEMENT, CASE SIZE: .375" L x .375" H x .260" W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFM-590AS	90° IN ALUMINUM 5 MHz .25" X .25" SIDE MOUNT MINTURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L x .37" W x .50" H WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	MWB-09-4	56931	.	.
AFM-590AT	90° IN ALUMINUM 5 MHz .25" X .25" TOP MOUNT MINTURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L x .37" W x .50" H WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	PAB-0504-90AL	SUM 590AT, PAB-0504-90AL	MA-905T	.
AFM-5905S	90° IN STEEL 5 MHz .25" X .25" SIDE MOUNT MINTURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L x .37" W x .50" H WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	A574S-RM	.	.	.
AFM-5905T	90° IN STEEL 5 MHz .25" X .25" TOP MOUNT MINTURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75" L x .37" W x .50" H WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-1074-80	SEARCH UNIT 80°, .25" ELEMENT, 5MHZ SHEAR WAVE. CASE SIZE (.47L x .35W x .62H). Reference: Airbus 57-21-10 A318/A319/A320/A321. Includes Test Report and Certificate of Conformance.	545017	0545017	TEK-5041-80	.
AFS-1080	70° ANGLE BEAM TRANSDUCER IN ALUMINUM, 5MHz .25" x .25" ELEMENT, CASE SIZE: .75" x .37" x .50" WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	0505556	.	.	.
AFS-1089	Custom 65° degree shear wave transducer, 5 MHz, element(.187" x .187"), Top Mount Microdot Connector. Includes Test Report and Certificate of Conformance.	TEK-5535	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-1158	Custom 57° degree shear wave transducer, 5 MHz, element(.187" x.187"), Top Mount Microdot Connector. Includes Test Report and Certificate of Conformance.	TEK-5536	.	.	.
AFS-1162	6 MHz 70° Degree Angle Beam Transducer Case Size .275" x .275" x .630", Top Mount Microdot Connector. Includes Test Report and certificate of Conformance.	SMWB70-6	.	.	.
AFS-1168	5MHz ANGLE BEAM TRANSDUCER WITH A RADIUS OF 2.0" USED NDT6001. Includes Test Report and Certificate of Conformance.	TEK-5023	.	.	.
AFS-1171	6 MHz 45° Degree Angle Beam Transducer Case Size .275" x .275" x .630", Top Mount Microdot Connector. Includes Test Report and certificate of Conformance.	SMWB 45-6	.	SMWB45-6	.
AFS-1172	6 MHz 70° Degree Angle Beam Transducer Case Size .275" x .275" x .630", Top Mount Microdot Connector. Includes Test Report and certificate of Conformance.	SMWB 60-6	.	SMWB60-6	.
AFS-1174	0 degree straight beam contact compression transducer side microdot connector. (15-20mm tall by 10-12.5mm dia.) Acuscan style (medium damped). Includes Test Report and Certificate of Conformance.	A5355-RM	.	A5355-RM	.
AFS-1178	6 MHz 70 Degree Angle Beam Broadband Transducer Case Size .275" x .275" x .630", Top Mount Microdot Connector composite element. Includes Test Report and Certificate of Conformance.	SMWK70-6	.	SMWK70-6	.
AFS-1184	CUSTOM LOW PROFILE TRANSDUCER 5MHz 1.75" RADIUS WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6022. Includes Test Report and Certificate of Conformance.	TEK-5037	.	.	.
AFS-1186	CUSTOM 5MHz RADIUS TRANSDUCER SIDE MOUNT CONNECTOR FOR NDT6012 767 JOINT SUPPORT. Includes Test Report and Certificate of Conformance.	TEK-5038-12	.	.	.
AFS-1187	CUSTOM 5MHz RADIUS TRANSDUCER SIDE MOUNT CONNECTOR FOR NDT6013. Includes Test Report and Certificate of Conformance.	TEK-5038-13	.	.	.
AFS-1188	CUSTOM 5MHz, 1.85" RADIUS TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6014. Includes Test Report and Certificate of Conformance.	TEK-5038-14	.	.	.
AFS-1189	CUSTOM 5MHz, 2.20" RADIUS TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6015. Includes Test Report and Certificate of Conformance.	TEK-5038-15	.	.	.
AFS-1191-1	5MHz ANGLE BEAM TRANSDUCER WITH a RADIUS OF 1.2" USED WITH NDT6038. Includes Test Report and Certificate of Conformance.	TEK-5089-1	.	.	.
AFS-1191-2	5MHz ANGLE BEAM TRANSDUCER WITH a RADIUS OF 1.2" USED WITH NDT6038. Includes Test Report and Certificate of Conformance.	TEK-5089-2	.	.	.
AFS-1194	CUSTOM 5MHz TRANSDUCER WITH 1.4" RADIUS USED WITH NDT6025-1. Includes Test Report and Certificate of Conformance.	TEK-5050-1	.	.	.
AFS-1195	CUSTOM 5MHz TRANSDUCER WITH 1.65" RADIUS USED WITH NDT6025-. Includes Test Report and Certificate of Conformance.	TEK-5050-2	.	.	.
AFS-1196	CUSTOM 5MHz TRANSDUCER WITH 1.620" RADIUS USED WITH NDT6025-3. Includes Test Report and Certificate of Conformance.	TEK-5050-3	.	.	.
AFS-1197	CUSTOM 5MHz TRANSDUCER WITH 1.4" RADIUS USED WITH NDT6025-4. Includes Test Report and Certificate of Conformance.	TEK-5050-4	.	.	.
AFS-1198	CUSTOM 5MHz TRANSDUCER WITH 1.70" RADIUS USED WITH NDT6025-5. Includes Test Report and Certificate of Conformance.	TEK-5050-5	.	.	.
AFS-1199	CUSTOM 5MHz TRANSDUCER WITH 1.930" RADIUS USED WITH NDT6025-6. Includes Test Report and Certificate of Conformance.	TEK-5050-6	.	.	.
AFS-1043	SEARCH UNIT 70°, 5MHz SHEARWAVE. Case size (.35"W x .47"L x .63"H) Top mount connector. Includes Test Report and Certificate of Conformance.	545015	.	.	.
AFS-1209	CUSTOM 5MHz, 1.550" RADIUS TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6031-1. Includes Test Report and Certificate of Conformance.	TEK-5076-1	.	.	.
AFS-1210	CUSTOM 5MHz, 1.880" RADIUS TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6031-2. Includes Test Report and Certificate of Conformance.	TEK-5076-2	.	.	.
AFS-1211	CUSTOM 5MHz, 2.00" RADIUS TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6031-3. Includes Test Report and Certificate of Conformance.	TEK-5076-3	.	.	.
AFS-1212	CUSTOM 5MHz L-WAVE, 1.800" RADIUS TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6031-4. Includes Test Report and Certificate of Conformance.	TEK-5076-4	.	.	.
AFS-1213	CUSTOM 5MHz, 1.500" RADIUS TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6032-1. Includes Test Report and Certificate of Conformance.	TEK-5077-1	.	.	.
AFS-1214	USTOM 5MHz, 1.500" RADIUS L-WAVE TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6032-2. Includes Test Report and Certificate of Conformance.	TEK-5077-2	.	.	.
AFS-1215	CUSTOM 5MHz, 1.850" RADIUS TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6032-3. Includes Test Report and Certificate of Conformance.	TEK-5077-3	.	.	.
AFS-1216	CUSTOM 5MHz, 1.850" RADIUS L-WAVE TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR USED WITH NDT6032-4. Includes Test Report and Certificate of Conformance.	TEK-5077-4	.	.	.
AFS-1224S	55° MINI ANGLE BEAM TRANSDUCER IN ALUMINUM 5MHz .120" x .250"; WITH SIDE MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375"L x .425"H x .325"W. Includes Test Report and Certificate of Conformance.	HS225-5-55	.	HS225-5-55-RM	HS-225-5-55-RM
AFS-1224T	55° MINI ANGLE BEAM TRANSDUCER IN ALUMINUM 5MHz .120" x .250"; WITH TOP MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375"L x .425"H x .325"W. Includes Test Report and Certificate of Conformance.	HS225-5-55	.	HS225-5-55-SM	HS-225-5-55-SM
AFS-1226S	65° MINI ANGLE BEAM TRANSDUCER IN ALUMINUM 5MHz .120" x .250"; WITH SIDE MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375"L x .425"H x .325"W. Includes Test Report and Certificate of Conformance.	HS-225-5-65-AL-RM	.	.	.
AFS-1226S.	65° MINI ANGLE BEAM TRANSDUCER IN ALUMINUM 5MHz .120" x .250"; WITH SIDE MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375"L x .425"H x .325"W. Includes Test Report and Certificate of Conformance.	HS225-5-65	.	HS-225-5-65-RM	HS-225-5-65
AFS-1226T	65° MINI ANGLE BEAM TRANSDUCER IN ALUMINUM 5MHz .120" x .250"; WITH TOP MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375"L x .425"H x .325"W. Includes Test Report and Certificate of Conformance.	HS225-5-65	.	HS225-5-65-AL-SM	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-12275	70" IN ALUMINUM 5MHZ .120" x .250"; SIDE MOUNT MINI ANGLE BEAM TRANSDUCER WITH MICRODOT CONNECTOR. CASE SIZE: .375" L x .425" H x .325" W. Includes Test Report and Certificate of Conformance.	HS225-5-70AL	.	.	.
AFS-1227T	70" IN ALUMINUM 5MHZ .120" x .250"; TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH MICRODOT CONNECTOR. CASE SIZE: .375" L x .425" H x .325" W. Includes Test Report and Certificate of Conformance	HS225-5-70	HS-225-5-70-AL-SM	.	.
AFS-1229T	80" IN ALUMINUM 5MHZ .120" x .250"; TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH MICRODOT CONNECTOR. CASE SIZE: .375" L x .425" H x .325" W. Includes Test Report and Certificate of Conformance	HS225-5-70	HS-225-5-70-AL-SM	.	.
AFS-1202L	CUSTOM 5MHZ TRANSDUCER COMPOUND ANGLE 45 DEGREES IN STEEL. WITH 3.5 INCH HANDLE. REMOVABLE CABLE MOUNT TO MICRODOT CONNECTOR (LEFT) USED WITH NDT3021, 737 Part 4 57-50-01. Includes Test Report and Certificate of Conformance.	SUS921L	SUS921L	.	.
AFS-1202R	CUSTOM 5MHZ TRANSDUCER COMPOUND ANGLE 45 DEGREES IN STEEL. WITH 3.5 INCH HANDLE. REMOVABLE CABLE MOUNT TO MICRODOT CONNECTOR (RIGHT) USED WITH NDT3021, 737 Part 4 57-50-01. Includes Test Report and Certificate of Conformance.	SUS921R	SUS921R	.	.
AFS-12665	5 MHZ ANGLE BEAM TRANSDUCER 45" IN ALUMINUM WITH END MOUNTED MICRODOT CONNECTOR, .150" X .250" ELEMENT. CASE SIZE: .35" W X .375" L X .375" H. Includes Test Report and Certificate of Conformance.	TEK-5548/455	.	.	.
AFS-12685	5 MHZ ANGLE BEAM TRANSDUCER 60" IN ALUMINUM WITH END MOUNTED MICRODOT CONNECTOR, .150" X .250" ELEMENT. CASE SIZE: .35" W X .375" L X .375" H. Includes Test Report and Certificate of Conformance.	TEK-5548/605	.	.	.
AFS-1268T	5 MHZ ANGLE BEAM TRANSDUCER 60" IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR, .150" X .250" ELEMENT. CASE SIZE: .35" W X .375" L X .375" H. Includes Test Report and Certificate of Conformance.	TEK-5548/60T	.	.	.
AFS-1269T	5 MHZ ANGLE BEAM TRANSDUCER 70" IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR, .150" X .250" ELEMENT. CASE SIZE: .35" W X .375" L X .375" H. Includes Test Report and Certificate of Conformance.	TEK-5548/70T	.	.	.
AFS-12705	5 MHZ ANGLE BEAM TRANSDUCER 70" IN ALUMINUM WITH END MOUNTED MICRODOT CONNECTOR, .150" X .250" ELEMENT. CASE SIZE: .35" W X .375" L X .375" H. Includes Test Report and Certificate of Conformance.	TEK-5548/705	.	.	.
AFS-1289	5MHZ TRANSDUCER .25" X .187" TOP MOUNT ELEMENT CASE .350" W X .375" L X .75" H 45°A. Includes Test Report and Certificate of Conformance.	TEK-5557/45T	.	.	.
AFS-1290	5MHZ TRANSDUCER .25" X .187" SIDE MOUNT ELEMENT CASE .350" W X .375" L X .75" H 45°A. Includes Test Report and Certificate of Conformance.	TEK-5557/45S	.	.	.
AFS-1394	CARGOLUX CUSTOM 5MHZ .187", 40" IN ALUMINUM SHEAR WAVE TRANSDUCER WITH A 1.00" RADIUS FOR THE BOEING REFERENCE STANDARD LUG 187-FITTING-SEQUENCE CARRIAGE ATTACHMENT INBOARD TRAILING EDGE FLAP. CASE SIZE: .500" L x .270" W x .350". Includes Test Report...	.	.	.	.
AFS-1292	5MHZ, 60" in Aluminum .25" X .187" ELEMENT SIDE MOUNT .350" W X .375" L X .750" H. REFERENCE: BOEING 737 PART 4 57-10-09, pg.2. Includes Test Report and Certificate of Conformance.	TEK-5557/60S	.	.	.
AFS-1293	CUSTOM BOEING 737 TRANSDUCER, 70" IN ALUMINUM, 5MHZ .250" x .187" ELEMENT, TOP MOUNT MICRODOT CONNECTOR, .350" W x .375" L x .750" H. Includes Test Report and Certificate of Conformance.	TEK-5557/70T	.	.	.
AFS-1294	5MHZ .25" X .187" ELEMENT SIDE MOUNT .350W X .375L X .75H 70°A. Includes Test Report and Certificate of Conformance.	TEK-5557/70S	.	.	.
AFS-0576L	CUSTOM 25" "L" - WAVE TRANSDUCER WITH A 2" COMPOUND ANGLE (BACKSHOOTER) 5.0 MHZ .25" X .25" ELEMENT WITH A 1.65" RADIUS, LEFT SIDE USED WITH NDT3272 Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-1306	60" in ALUMINUM 5MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" X .187" ELEMENT, CASE SIZE: .500" L X .425" H X .300" W. Includes Test Report and Certificate of Conformance.	SMSWSSMHZ60AL	.	.	.
AFS-1308A	CUSTOM 45" in ALUMINUM SEARCH UNIT, 5MHZ .25" ELEMENT. CASE SIZE: .790" L x .360" W x .500" H. Includes Test Report and Certificate of Conformance.	WKS-45-5A	.	.	.
AFS-1313	SONAXIS CUSTOM 45", 8MHZ PIEZOCOMPOSITE TRANSDUCER WITH PIVOTING HANDLE. Includes Test Report and Certificate of Conformance.	CEP13	CEP13	.	.
AFS-1317	8MHZ 40" SHEARWAVE TRANSDUCER IN ALUMINUM PIEZOCOMPOSITE ELEMENT. CASE SIZE: 10mm x 6mm x 15mm. Includes Test Report and Certificate of Conformance(COC)	CEP17	CEP17	.	.
AFS-1318	8MHZ 45" SHEARWAVE TRANSDUCER IN ALUMINUM PIEZOCOMPOSITE ELEMENT. CASE SIZE: 10mm x 6mm x 15mm. Includes Test Report and Certificate of Conformance(COC)	CEP18	CEP18	.	.
AFS-1319	8MHZ 50" SHEARWAVE TRANSDUCER IN ALUMINUM PIEZOCOMPOSITE ELEMENT. CASE SIZE: 10mm x 6mm x 15mm. Includes Test Report and Certificate of Conformance(COC)	CEP19	CEP19	.	.
AFS-1320	8MHZ 55" SHEARWAVE TRANSDUCER IN ALUMINUM PIEZOCOMPOSITE ELEMENT. CASE SIZE: 10mm x 6mm x 15mm. Includes Test Report and Certificate of Conformance(COC)	CEP20	CEP20	.	.
AFS-1321	8MHZ 60" SHEARWAVE TRANSDUCER IN ALUMINUM PIEZOCOMPOSITE ELEMENT. STAINLESS STEEL HOUSING, CASE SIZE: 10mm x 6mm x 15mm. Includes Test Report and Certificate of Conformance(COC)	CEP21	CEP21	.	.
AFS-1322	8MHZ 65" ANGLE BEAM TRANSDUCER IN ALUMINUM PIEZOCOMPOSITE ELEMENT. CASE SIZE: 10mm x 6mm x 15mm. Includes Test Report and Certificate of Conformance(COC)	CEP22	CEP22	.	.
AFS-1322LP	5MHZ 65" TRANSVERSE BEAM TRANSDUCER IN ALUMINUM WITH TOP MOUNTED MICRODOT CONNECTOR. STAINLESS STEEL HOUSING, .25" PIEZOCOMPOSITE ELEMENT. CASE SIZE: .400" X .250" X .630". Includes Test Report and Certificate of Conformance(COC)	CEP22LP	.	.	.
AFS-1323	8MHZ 70" SHEARWAVE TRANSDUCER IN ALUMINUM PIEZOCOMPOSITE ELEMENT. CASE SIZE: 10mm x 6mm x 15mm. Includes Test Report and Certificate of Conformance(COC)	CEP23	CEP23	.	.
AFS-1324	8MHZ 75" SHEARWAVE TRANSDUCER IN ALUMINUM PIEZOCOMPOSITE ELEMENT. CASE SIZE: 10mm x 6mm x 15mm. Includes Test Report and Certificate of Conformance(COC)	CEP24	CEP24	.	.
AFS-0576R	CUSTOM 25" "L" - WAVE TRANSDUCER WITH A 2" COMPOUND ANGLE (BACKSHOOTER) 5.0 MHZ .25" X .25" ELEMENT WITH A 1.65" RADIUS, RIGHT SIDE USED WITH NDT3272 Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-1333/70S	5.0 mhz, 0.250 in. by 0.250 in. element size; 70° degree angle in Steel 0.690 in. lg; 0.590 in. w; 0.330 in with side mount microdot connector. Includes Test Report and Certificate of Conformance.	57A3054	.	.	.
AFS-1336/60S	5.0 mhz, 0.250 in. by 0.250 in. element size; 60° degree angle in Steel with side mount microdot connector. 0.690 in. lg; 0.590 in. w; 0.330 in. Includes Test Report and Certificate of Conformance.	57A3053	.	.	.
AFS-1337	SEARCH UNIT 60", 5MHZ SHEARWAVE... Case size (.35" W x .47" L x .63" H) Top mount microdot connector. Includes Test Report and Certificate of Conformance.	0545013	545013	.	.
AFS-1338/45A	5.0 mhz, 0.250 in. by 0.250 in. element size; 45° degree angle in Aluminum, Top mount microdot connector; 0.690 in. lg; 0.590 in. w; 0.330 in. Includes Test Report and Certificate of Conformance.	57A3064	57A3064	.	.



September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-1339/60A	5.0 mhz, 0.250 in. by 0.250 in. element size; 60° degree angle in Aluminum with top mount microdot connector; 0.690 in. lg; 0.590 in. w; 0.330 in. Includes Test Report and Certificate of Conformance.	57A3065	.	.	.
AFS-1340	SEARCH UNIT 80° in aluminum , 5MHZ ANGLE BEAM. CASE SIZE (470" L x .350" W x .630" H). Includes Test Report and Certificate of Conformance.	0545016	545016	.	.
AFS-1341	SEARCH UNIT 40° IN ALUMINUM, 5MHZ, .25" x .187" ELEMENT, (.35"W x .47"L x .63"H), top mount connector. Includes Test Report and Certificate of Conformance.	545009	545009	.	.
AFS-1342	SEARCH UNIT 35° IN ALUMINUM, 5MHZ, .25" x .187" ELEMENT, (.35"W x .47"L x .63"H), top mount connector. Includes Test Report and Certificate of Conformance.	0105598	545086	0105598	0545086
AFS-1345	SEARCH UNIT 45° IN ALUMINUM, 5MHZ, .25" x .187" ELEMENT, (.35"W x .47"L x .63"H), top mount connector. Includes Test Report and Certificate of Conformance.	545010	545010	0545010	.
AFS-1354/60S	5MHZ 60° IN ALUMINUM .25" ELEMENT, SIDE MOUNT MICRODOT CONNECTOR. CASE DIMENSIONS: .350"W x .375"L x .750"H. BOEING 737 PART 4 Part 4 57-10-09. Includes Test Report and Certificate of Conformance.	TEK-5577/60S	.	.	.
AFS-06105	Custom 5MHz 22-degree shear wave transducer in aluminum, 0.38 inch (9.7 mm) element, 2.0 inch (51mm) radius contact surface with mounted microdot connector. Case dimensions: 0.75"(19.1 mm) x 0.50"12.7 mm) x 0.25"(6.4 mm). Includes Test Report and Certi...	.	.	.	.
AFS-1371	45° IN TITANIUM 5MHZ MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x .187" ELEMENT, CASE SIZE: .375"L x .375"H x .260"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AF-0545	MSW-QC STYLE QUICK CHANGE TRANSDUCER 2.25MHz .25" ELEMENT 3/8-32 THREAD. HIGH DAMPED. Includes Test Report and Certificate of Conformance.	122-591	.	.	.
AF-0546	MSW-QC STYLE QUICK CHANGE TRANSDUCER 10MHz .25" ELEMENT 3/8-32 THREAD. HIGH DAMPED. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-1377	CUSTOM 5MHZ 45° ANGLE BEAM TRANSDUCER WITH A .35mm(1.38") RADIUS WITH TOP MOUNT MICRODOT CONNECTOR. CASE SIZE: .590" x .350" x .470" Includes Test Report and Certificate of Conformance.	412A-45" AI	.	.	.
AFS-1383	SEARCH UNIT 60° , 5MHZ SHEARWAVE... Case size (.35"W x .47"L x .63"H) Top mount connector. Includes Test Report and Certificate of Conformance.	0545013	545013	.	.
AFS-1384	5MHZ, 2 x .25" SQUARE ELEMENT PAINTBRUSH TRANSDUCER USED WITH NDT3023, 737 PART 4 32-10-03 PAGE 7 FIGURE 3. Includes Test Report and Certificate of Conformance.	XAB-6053	TEK-5101	.	.
AFS-1387	NDT SYSTEMS MD-11, 5 MHz .187" x .187" ELEMENT 36° SHEAR WAVE SEARCH UNIT , 5.0" LONG HANDLE WITH MICRODOT CONNECTOR. MD-11 SECTION 2.5 PAGE 1 FIGURE 5.2 Includes Test Report and Certificate of Conformance.	AE06501	AE06501	.	.
AFS-1391	CUSTOM 36 DEGREE 5MHZ SHEARWAVE PAINTBRUSH TRANSDUCER W/1.61"RADIUS, .375"H x .500"W MAX USED WITH NDT615, 767 PT 4 53-80-01. Includes Test Report and Certificate of Conformance. D	SPO-5744	TEK-5060	.	.
AFS-0613S	Custom 5MHz 26-degree shear wave transducer in aluminum, 0.38 inch (9.7 mm) element, 2.0 inch (51mm) radius contact surface with mounted microdot connector. Case dimensions: 0.75"(19.1 mm) x 0.50"12.7 mm) x 0.25"(6.4 mm). Includes Test Report and Certi...	.	.	.	.
AFS-1395/45AS	Miniature Angle Beam Transducer, Side Mount Microdot Connector, 10MHz 45° in Aluminum, 25" x .25" Element. Case Size: .550"L x .300"W x .675" H. Includes Test Report and Certificate of Conformance.	PAB-1004-45-ST-RM	.	.	.
AFS-1395/45AT	Miniature Angle Beam Transducer, Top Mount Microdot Connector, 10MHz 45° in Aluminum, 25" x .25" Element. Case Size: .550"L x .300"W x .675" H. Includes Test Report and Certificate of Conformance.	PAB-1004-45-AL-SM	.	.	.
AFS-1395/45ST	Miniature Angle Beam Transducer, Side Mount Microdot Connector, 10MHz 45° in Steel, 25" x .25" Element. Case Size: .550"L x .300"W x .675" H. Includes Test Report and Certificate of Conformance.	PAB-1004-45-ST-RM	.	.	.
AFS-1395/60AS	Miniature Angle Beam Transducer, Side Mount Microdot Connector, 10MHz 60° in Aluminum, 25" x .25" Element. Case Size: .550"L x .300"W x .675" H. Includes Test Report and Certificate of Conformance.	PAB-1004-60-ST-RM	.	.	.
AFS-1395/60AT	Miniature Angle Beam Transducer, Top Mount Microdot Connector, 10MHz 60° in Aluminum, 25" x .25" Element. Case Size: .550"L x .300"W x .675" H. Includes Test Report and Certificate of Conformance.	PAB-1004-60-AL-SM	.	.	.
AFW-50001	Cusotm Acrylic Wedge, 45° in Al, .25"Ø Transducer Dimensions: .500"Long X .525" Wide X .585" High, 5mm Radius With a 7/16-32 Flat Bottom Hole. Includes Certificate of Conformance.	.	.	.	.
AFS-1395/70AS	Miniature Angle Beam Transducer, Side Mount Microdot Connector, 10MHz 70° in Aluminum, 25" x .25" Element. Case Size: .550"L x .300"W x .675" H. Includes Test Report and Certificate of Conformance.	PAB-1004-70-AL-RM	.	.	.
AFS-1395/70AT	Miniature Angle Beam Transducer, 10MHz 70° in Aluminum, 25" x .25" Element. Case Size: .550"L x .300"W x .675" H. Includes Test Report and Certificate of Conformance.	PAB-1004-70-AL-SM	.	.	.
AFS-1395/90AS	Miniature Angle Beam Transducer, 10MHz 90° Side Mount Microdot Connector in Aluminum, 25" x .25" Element. Case Size: .550"L x .300"W x .675" H. Includes Test Report and Certificate of Conformance.	PAB-1004-90-AL-RM	.	.	.
AF-325HT	3.5MHZ HIGH DAMPED CONTACT TRANSDUCER, .25 ELEMENT, .375Ø CASE O.D., .700" TALL, TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-1395/90AT	Miniature Angle Beam Transducer, 10MHz 90° Top Mount Microdot Connector in Aluminum, 25" x .25" Element. Case Size: .550"L x .300"W x .675" H. Includes Test Report and Certificate of Conformance.	PAB-1004-90-AL-SM	.	.	.
AFS-1396/70AL	5 MHz 70° Degree Angle Beam Transducer in Aluminum. Case Size .275"L x .315"W x .512"H , Side Mount Microdot Connector. Includes Test Report and certificate of Conformance.	W7085MAL	.	.	.
AFS-1398	STAVELY CUSTOM 5MHZ TRANSDUCER 31° IN ALUMINUM WITH .700" RADIUS USED WITH 5B11530001-5. Includes Test Report and Certificate of Conformance.	SPO-4628	.	.	.
AFS-1410CS	30° IN ALUMINUM 5MHZ MINI ANGLE BEAM TRANSDUCER, COMPOSITE ELEMENT BROADBAND WITH SIDE MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-1411CS	45° IN ALUMINUM 5MHZ MINI ANGLE BEAM TRANSDUCER COMPOSITE ELEMENT BROADBAND WITH SIDE MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	.	.	.	.
AFS-1412CS	60° IN ALUMINUM 5MHZ MINI ANGLE BEAM TRANSDUCER COMPOSITE ELEMENT BROADBAND WITH SIDE MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	.	.	.	.
AFS-470AS	70° IN ALUMINUM 4MHZ TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-503	CUSTOM 5MHZ, 10 DEGREES INCIDENT TRANSDUCER FOR THE FORWARD SIDE OF THE LOWER ROW FASTENER HOLE AS WELL AS THE AFT SIDE OF THE AFT UPPER ROW FASTENER HOLE OF NDT3219. CASE SIZE:(.550"Lx.350"Wx.400"H) WITH 1.65" RADIUS. Includes Test Report and Certif...	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-504	CUSTOM 5MHZ TRANSDUCER FOR AFT SIDE OF THE LOWER FASTENER HOLE OF NDT3219. CASE SIZE:(.550"Lx.350"Wx.400"H) WITH 1.65" RADIUS. Includes Test Report and Certificate of Conformance. Reference: 737 part 4 57-10-19 page 1	.	.	.	.
AFS-5050-1	Custom 5 MHz, 22" .187" x .187" element, L-Wave Transducer with a 1.400" Radius used with NDT6025-1. Includes Test Report and Certificate of Conformance.	TEK5050-1	TEK-5050-1	.	.
AFS-270SS	70" in STEEL 2.25MHZ TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	SS-702S	.	.	.
AFS-5050-2	Custom 5 MHz, 20" .187" x .187" element, L-Wave Transducer with a 1.650" Radius used with NDT6025-2. Includes Test Report and Certificate of Conformance.	TEK5050-2	.	.	.
AFS-5050-3	Custom 5 MHz, 24" .187" x .187" element, L-Wave Transducer with a 1.620" Radius used with NDT6025-3. Includes Test Report and Certificate of Conformance.	TEK5050-3	.	.	.
AFS-5050-4	Custom 5 MHz, 24" .187" x .187" element, L-Wave Transducer with a 1.400" Radius used with NDT6025-4. Includes Test Report and Certificate of Conformance.	TEK5050-4	.	.	.
AFS-5050-5	Custom 5 MHz, 24" .187" x .187" element, L-Wave Transducer with a 1.700" Radius used with NDT6025-5. Includes Test Report and Certificate of Conformance.	TEK5050-5	.	.	.
AFS-5050-6	Custom 5 MHz, 18" .187" x .187" element, L-Wave Transducer with a 1.930" Radius used with NDT6025-6. Includes Test Report and Certificate of Conformance.	TEK5050-6	.	.	.
AFS-5053-17	CUSTOM 5MHZ 45° TRANSDUCER 2.30" RADIUS IN ALUMINUM WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-5053-17	.	.	.
AFS-5053-18	CUSTOM 5MHZ 45° TRANSDUCER 2.50" RADIUS IN ALUMINUM WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-5053-18	.	.	.
AFS-5110AT	CUSTOM 5 MHz 75° DEGREE ANGLE BEAM TRANSDUCER, TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-5110T	.	.	.
AFS-5133	CUSTOM L-WAVE TRANSDUCER 13° REFRACTED ANGLE, 10 MHz WITH A 1.950" RADIUS, MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	TEK-5133	.	.	.
AFS-5135	CUSTOM BOEING L-WAVE TRANSDUCER, 10 MHz 9.4° DEGREES With a 1.93" Radius. Case Size: .600"L x .310" W x .400" H. Includes Test Report and Certificate of Conformance.	TEK-5135	.	.	.
AFS-537AS-1.92R	37" in ALUMINUM 5MHZ TRANSDUCER WITH 1.92" RADIUS, END MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	SA-3755-R1.92	.	.	.
AFS-540AT	SMALL 40° ANGLE BEAM TRANSDUCER in ALUMINUM, 5MHZ .187" x .160" ELEMENT, CASE SIZE (.550"L x .26"W x .450"H ) WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-541AS-1.92R	41" in ALUMINUM 5MHZ TRANSDUCER WITH 1.92" RADIUS, END MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	SA-4155-R1.92	.	.	.
AFL-1060AT	60" ALUMINUM, ANGLE BEAM TRANSDUCER 10MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0611S	Custom 5MHz 31-degree shear wave transducer in aluminum, 0.38 inch (9.7 mm) element, 2.0 inch (51mm) radius contact surface with mounted microdot connector. Case dimensions: 0.75"(19.1 mm) x 0.50"(12.7 mm) x 0.25"(6.4 mm). Includes Test Report and Certi...	.	.	.	.
AFS-560AS-1	60" in ALUMINUM 5MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .500"L x .400"H x .26"W (.400" MAX HEIGHT). Includes Test Report and Certificate of Conformance.	SUSM 560AS-1	.	.	.
AFS-560AT	60" in ALUMINUM 5MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	SUSM 560AT	SA-60ST	.	.
AFC-531S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 5.0MHZ, .312"Ø WITH END MOUNTED MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-1018-1	10MHZ LONGITUDINAL BEAM TRANSDUCER .187"Ø DIAMETER ELEMENT, .25"Ø HOUSING 1.0" LONG WITH TOP MOUNTED MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	SPO-5856-1/4-10	.	.	.
AFS-560TT	60" in TITANIUM 5MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFL-1075AS	75° ALUMINUM, ANGLE BEAM TRANSDUCER 10MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance	SU 1075AS	.	.	.
AFS-570AS	70" in ALUMINUM 5MHZ TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	SA-705S	SUSM-570AS	.	.
AFS-570AT	70" in ALUMINUM 5MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	SUSM 570AT	SA-70ST	MPA0517A-TC	.
AFS-766/767-4	CUSTOM 5MHZ ANGLE BEAM TRANSDUCER .25" x .25" ELEMENT. USED WITH NDT766 Outboard Flange of the T-Chord/Lower Surface. Includes Test Report and Certificate of Conformance.REFERENCE: 777 PART 4 57-10-02	TEK766/767-4	.	.	.
AFS-766-3	CUSTOM 5MHZ ANGLE BEAM TRANSDUCER .25" x .25" ELEMENT. USED WITH NDT766 Outboard Flange of the T-Chord/Upper Surface. Includes Test Report and Certificate of Conformance.	TEK-766-3	.	.	.
AFS-767-3	CUSTOM 5MHZ ANGLE BEAM TRANSDUCER .25" x .25" ELEMENT. USED WITH NDT766 Inboard Flange of the T-Chord/Upper Surface. Includes Test Report and Certificate of Conformance.	TEK-767-3	.	.	.
AFS-767-5	CUSTOM 5MHZ ANGLE BEAM TRANSDUCER .25" x .25" ELEMENT. USED WITH NDT766 Inboard Flange of the T-Chord/Lower Surface. Includes Test Report and Certificate of Conformance.	TEK-767-5	.	.	.
AFW25-45S/1.5R	45° IN STEEL LUCITE (PLEXIGLASS) WEDGE WITH 1.5" RADIUS FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD. Includes Certificate of Conformance.	.	.	.	.
412E5MHZ60FE	CUSTOM 5MHZ 60° IN FE TRANSVERSE WAVE BACKSHOOTING TRANSDUCER WITH A SIDE MOUNTED MICRODOT CONNECTOR. CASE SIZE: .690" x .354" x .354 Includes Test Report and Certificate of Conformance. REFERENCE STANDARD: 98A54003077	.	.	.	.
412B5MHZ40R75FE	CUSTOM 5MHZ 40° TRANSVERSE WAVE TRANSDUCER WITH END MOUNT MICRODOT CONNECTOR WITH A 75mm RADIUS. USED WITH AIRBUS REFERENCE STANDARD PART NUMBER 98A54003069 Includes Test Report and Certificate of Conformance. REFERENCE: AIRBUS A300-600 PART 4 54-50-20	.	.	.	.
AFW25-45S/2R	45° IN STEEL LUCITE (PLEXIGLASS) WEDGE WITH 2.0" RADIUS FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD. Includes Certificate of Conformance.	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFW25-60S/1.5R	60° IN STEEL LUCITE (PLEXIGLASS) WEDGE WITH 1.5" RADIUS FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD. Includes Certificate of Conformance.	.	.	.	.
AFW25-60S/2R	60° IN STEEL LUCITE (PLEXIGLASS) WEDGE WITH 2.0" RADIUS FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD. Includes Certificate of Conformance.	.	.	.	.
AFW25-70S/1.5R	70° IN STEEL LUCITE (PLEXIGLASS) WEDGE WITH 1.5" RADIUS FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD. Includes Certificate of Conformance.	.	.	.	.
AFW25-70S/2R	70° IN STEEL LUCITE (PLEXIGLASS) WEDGE WITH 2.0" RADIUS FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD. Includes Certificate of Conformance.	.	.	.	.
AFW-30A	30° LUCITE (PLEXIGLASS) WEDGE FOR .25" Ø SCREW IN TRANSDUCER. 3/8-32 THREAD. Includes Certificate of Conformance.	ABWM4086	.	.	.
AFW-40A	40° LUCITE (PLEXIGLASS) WEDGE FOR .25"Ø SCREW IN TRANSDUCER. 3/8-32 THREAD. Includes Certificate of Conformance.	QCX40 (0105436)	.	.	.
AFW-45S	45° IN STEEL LUCITE (PLEXIGLASS) WEDGE FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD. Includes Certificate of Conformance.	.	.	.	.
AFW-60S	60° IN STEEL LUCITE (PLEXIGLASS) WEDGE FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD. Includes Certificate of Conformance.	.	.	.	.
AFX-1040AT	40° in ALUMINUM 10MHz TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	.	.	.	.
AFX-1045AS	45° in ALUMINUM 10MHz SIDE MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFX-1055AT	55° in ALUMINUM 10MHz TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFX-1060AS	60° in ALUMINUM 10MHz SIDE MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFX-1060AT	60° IN ALUMINUM 10MHz .170" X.187"; MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375" L x .375" H x .260"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFX-260AS	60° IN ALUMINUM 2.25MHZ .160" X.187"; MINI ANGLE BEAM TRANSDUCER WITH END MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375" L x .375" H x .260"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFX-535AS	35° in ALUMINUM 5MHZ MINI ANGLE BEAM TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFX-535AT	35° in ALUMINUM 5MHZ MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W. Includes Test Report and Certificate of Conformance.	HS-877-5-35-AL	.	.	.
AFX-545AT	45° IN ALUMINUM 5MHZ MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .260"W. Includes Test Report and Certificate of Conformance.	A5067	XA-455T,	HS-877-5-45, 946483	A5067-SM
AFX-545ST	45° IN STEEL 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W. Includes Test Report and Certificate of Conformance.	A5015	HS-877-45-5-ST	A5015-5MHZ45	A5015-SM
AFX-550AT	50° in ALUMINUM 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .260"W. Includes Test Report and Certificate of Conformance.	HS-877-5-50-AL	.	.	.
AFX-550TTI	50° IN TITANIUM 5MHZ .170" X.187"; MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375" L x .375" H x .260"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFX-555AT	55° in ALUMINUM 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .170" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .260"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0612S	Custom 5MHz 33-degree shear wave transducer in aluminum, 0.38 inch (9.7 mm) element, 2.0 inch (51mm) radius contact surface with mounted microdot connector. Case dimensions: 0.75" (19.1 mm) x 0.50" (12.7 mm) x 0.25" (6.4 mm). Includes Test Report and Certi...	.	.	.	.
AFX-560AT	60° IN ALUMINUM 5MHZ .170" X.187"; MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375" L x .375" H x .260"W. Includes Test Report and Certificate of Conformance.	A5068	A5068-SM, 57A5068, HS-877-5-60	HS-877, XA605T	946482
AFX-565AT	65° IN ALUMINUM 5MHZ .170" X.187"; MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375" L x .375" H x .260"W. Includes Test Report and Certificate of Conformance...	HS-877-5-65-AL	.	.	.
AFX-570AS	70° IN ALUMINUM 5MHZ .160" X.187"; MINI ANGLE BEAM TRANSDUCER WITH SIDE MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375" L x .375" H x .260"W. Includes Test Report and Certificate of Conformance.....	A5069-RM	.	.	.
AFX-570AT	70° IN ALUMINUM 5MHZ .160" X.187"; MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNTED MICRODOT CONNECTOR. CASE SIZE: .375" L x .375" H x .260"W. Includes Test Report and Certificate of Conformance.	A5069-SM	SX-570AT, HS-877-5-70	HS-877	XA-705T
AFX-570ST	70° IN STEEL 5MHZ .150" X.187", TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	A5013-SM	A5013SM	A5013	.
WS400	Boeing Custom Contact Radius Shoe WS400 with a 0.400" radius. Material: Lucite/Cast Acrylic. 787 Part 4 51-00-23. Includes Certificate of Conformance.	.	.	.	.
AFS-0614S	Custom 5MHz 45-degree shear wave transducer in aluminum, 0.38 inch (9.7 mm) element, contact surface with mounted microdot connector. Case dimensions: 0.75" (19.1 mm) x 0.50" (12.7 mm) x 0.65" (16.5 mm). Includes Test Report and Certificate of Conformance.	.	.	.	.
PT.27	DC-10 ANGLE BEAM TRANSDUCER 60°, 5MHz .187" x .187" ELEMENT. CASE SIZE: .690" x .310" x .560". Includes Test Report and Certificate of Conformance.	294-641	.	.	.
PT.28	DC-10 ANGLE BEAM TRANSDUCER 70°, 5MHz .187" x .187" ELEMENT. CASE SIZE: .690" x .310" x .560". Includes Test Report and Certificate of Conformance.	294-642	.	.	.
ARD-525S	FINGER TIP SINGLE ELEMENT (HIGH DAMPED), REPLACEABLE DELAY TRANSDUCER 5MHZ .250"Ø(6.35mm), WITH SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = .10mm(.394"). Other lengths available upon request. Includes Test Report and Certificate of Conformance.	KSMN	.	.	.
ARD-525	FINGER TIP SINGLE ELEMENT DFR STYLE REPLACEABLE DELAY TRANSDUCER, 5MHZ .250"Ø(6.35mm), WITH SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = .437". Other lengths available upon request. Includes Test Report and Certificate of Conformance.	M201-RM	GRD-0502-HR	V201-RM, 113-124-660	M201-RM
AFX-1401-60	TRANSDUCER, 60° IN STEEL 6MHZ, 3mm(.118") x.4mm(.157") ELEMENT WITH TOP MOUNT MICRODOT CONNECTOR. CASE SIZE: 15mm(.591"L) x (7mm).276"W x 12mm(.472"H). Includes Test Report and Certificate of Conformance.	AM65-3X4-60	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARD-1012	High Damped(Gamma)10MHz .125" Replaceable Delay Transducer with Right Microdot Connector. Includes Test Form Certificate and Certificate of Conformance.	M203-RM	V203-RM		
ARD-1012T	High Damped(Gamma)10MHz .125" Replaceable Delay Transducer with Top Mounted Microdot Connector. Includes Test Form Certificate and Certificate of Conformance.	M203-SM			
ARD-1025	FINGER TIP SINGLE ELEMENT DFR STYLE REPLACEABLE DELAY TRANSDUCER, 10MHZ. 250°Ø(6.35mm), WITH SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = .437". Other lengths available upon request. Includes Test Report and Certificate of Conformance.	M202-RM, 113-126-660	V202-RM	RDG 102, 113-126-660	GRD-1002-HR, F8973
ABM-5021S	45° IN ALUMINUM 5MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .500"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.				
ARD-1025T	FINGER TIP SINGLE ELEMENT DFR STYLE REPLACEABLE DELAY TRANSDUCER, 10MHZ. 250°Ø(6.35mm), WITH TOP MOUNT MICRODOT CONNECTOR. Delay Tip length = .437". Other lengths available upon request. Includes Test Report and Certificate of Conformance.	M202-SM			
ARD-1050-13MM	10MHZ, .472" ELEMENT, 13mm REPLACEABLE DELAY SHOE, HIGH DAMPED BROADBAND CONTACT TRANSDUCER. Includes Test Report and Certificate of Conformance.	PSR13R-10MHZ			
ARD-1525	FINGER TIP SINGLE ELEMENT REPLACEABLE DELAY TRANSDUCER, 15MHZ. 250°Ø(6.35mm), WITH SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = .437". Other lengths available upon request. Includes Test Report and Certificate of Conformance.	V-205RM	TRD-1525	V-205RM	
AFS-1365	GE Angle Beam Transducer 5MHz 35°, 6.35mm (.25") ELEMENT. Case Size: 12.0mm(.472")L x 8.70mm(.343")W x 14.0mm(.551")H, with 30.0mm(1.181") RADIUS. Top Mounted Microdot Connector. Includes Test Report and Certificate of Conformance. REFERENCE: AIRBUS...	WK 545125	545125		
AFC-0525	GENERAL PURPOSE 5MHZ 1/4"Ø COMPRESSION. STRAIGHT BEAM TRANSDUCER. SIDE MOUNT MICRODOT CONNECTOR, KNURLED CASE SIZE: .500"H x .394Ø. Includes Test Report and Certificate of Conformance.	CM0504S			
ARD-2012	High Damped(Gamma) 20MHz .125" Replaceable Delay Transducer with Right Microdot Connector. Includes Test Form Certificate and Certificate of Conformance.	M208-RM, TRD-1220		V208-RM	
ARD-205S	2.0MHZ .500"Ø REPLACEABLE DELAY TRANSDUCER. SIDE MICRODOT CONNECTOR. Delay Tip length = .500". Other lengths available upon request. Includes Test Report and Certificate of Conformance.	MK2S			
ARD-250	2.25MHZ .500"Ø REPLACEABLE DELAY TRANSDUCER. SIDE MICRODOT CONNECTOR. Delay Tip length = .437". Other lengths available upon request. Includes Test Report and Certificate of Conformance.	389-077-490	M207	TRD-502	
ARD-350	3.50MHZ .500"Ø REPLACEABLE DELAY TRANSDUCER WITH Delay Tip length = .437". Other lengths available upon request. Includes Test Report and Certificate of Conformance.	389-024-400			
ARD-350S	3.50MHZ .500"Ø REPLACEABLE DELAY TRANSDUCER WITH END MOUNT MICRODOT CONNECTOR. Delay Tip length = .437". Other lengths available upon request. Includes Test Report and Certificate of Conformance.	389-024-400			
ARD-1512	High Damped(Gamma)15MHz .125" Replaceable Delay Transducer with Right Microdot Connector. Includes Test Form Certificate and Certificate of Conformance.	TRD-1215			
AFS-1074-35	SEARCH UNIT 35°, 5MHZ SHEARWAVE... Case size (.35"W x .47"L x .63"H) Top mount connector. Includes Test Report and Certificate of Conformance	TEK-5041-35			
AFS-1074-70	SEARCH UNIT 70°, 5MHZ SHEARWAVE. Case size (.35"W x .47"L x .63"H) Top mount connector. Includes Test Report and Certificate of Conformance.	0545015	TEK-5041-70		
AFC-1037S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER, MEDIUM DAMPED(ALPHA) 10.0MHZ. .375"Ø WITH SIDE MOUNT MICRODOT CONNECTOR CASE SIZE: .500"DIA x .650"H. Includes Test Report and Certificate of Conformance.				
AFS-1070AT	SMALL 10 MHz 70° TOP MOUNT TRANSDUCER .187"x.187" ELEMENT,CASE SIZE: .26"W x.55" L x .45"H. Includes Test Report and Certificate of Conformance.	SA-7010T	SUSM 1070AT		
AFL-245AT-1	45° IN ALUMINUM ANGLE BEAM TRANSDUCER 2.25MHZ .375"x.375" ELEMENT, CASE SIZE( 1.00 L X .500 W X .625 H )TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	57A3043			
D11	Nova Series High Resolution Fixed Delay 15MHz 0° degree straight beam transducer, side microdot connector. .670"(17.0mm) H x .394"(10mm)Ø, High damped. Includes Test Report and Certificate of Conformance.				
ARD-550/.79	5MHZ, .500"Ø(12.7mm) ACTIVE ELEMENT (HIGH DAMPED), REPLACEABLE DELAY TRANSDUCER SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = .790". Includes Test Report and Certificate of Conformance.	M206RBDLH2-20			
Figure 4.E.-4	Honeywell Positioning Plate and Spacers, 32-49-01 page 4.E.-5. Includes Test Report and Certificate of Conformance.				
412B5MHZ35R80FE	CUSTOM 5MHz 35° TRANSVERSE WAVE TRANSDUCER WITH END MOUNT MICRODOT CONNECTOR WIT A 80mm RADIUS. USED WITH AIRBUS REFERENCE STANDARD PART NUMBER 98A54003096 Includes Test Report and Certificate of Conformance. REFERENCE: AIRBUS A300-600 PART 4 54-50-20				
Holding Block No.1	Honeywell Holding Block No.1, 32-49-01 page 4.E.-3. Includes Test Report and Certificate of Conformance.				
Holding Block No.2	Honeywell Holding Block No.2, 32-49-01 page 4.E.-4. Includes Test Report and Certificate of Conformance.				
MA-455T	45° IN ALUMINUM 5 MHZ .25" X .25" ELEMENT SHEAR WAVE TRANSDUCER 75"L x .37"W x .50"H, WITH TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.				
AFXS-545AS	STAINLESS STEEL, 45° IN ALUMINUM 5MHZ MINI ANGLE BEAM TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375" L x .375" H x .260" W. Includes Test Report and Certificate of Conformance.	A5067			
AFXS-545AT	STAINLESS STEEL, 45° IN ALUMINUM 5MHZ MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375" L x .375" H x .260" W. Includes Test Report and Certificate of Conformance.				
MERC-25-UT-02	QUANTITY OF 3 ULTRASONIC DELRIN (BLACK ACETAL ) GUIDE POSITIONERS, NDT1036-P1, NDT1036-P2 & NDT1036-P4. Includes Certificate of Conformance.				
MERC-26-UT-PF-01	QUANTITY OF 2 ULTRASONIC LUCITE WEDGES. 1.22R & 1.62R Includes Certificate of Conformance.				
NDT298PL	BOEING TRANSDUCER POSITIONER 727 PART 4 32-30-27 PROCEDURE 5 PAGE 9 FIGURE 1. Includes Test Certificate of Conformance.				
NDT298PR	BOEING TRANSDUCER POSITIONER 727 PART 4 32-30-27 PROCEDURE 5 PAGE 8 FIGURE 1. Includes Test Certificate of Conformance.				
NDT567-G1	BOEING GUIDE FOR NDT567, 757 PT4 54-50-02 FIGURE 4 PAGE 9. Includes Certificate of Conformance.				

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
NDT567-G2	BOEING GUIDE FOR NDT567, 757 PT4 54-50-02 FIGURE 4 PAGE 9. Includes Certificate of Conformance.	.	.	.	.
NDT6036CG1	GUIDE FOR NTD6036 BOEING 767 PART 4 57-20-004FIGURE 2 PAGE 7. Includes Certificate of Conformance.	.	.	.	.
NDT6036CG2	GUIDE FOR NTD6036 BOEING 767 PART 4 57-20-004FIGURE 2 PAGE 7. Includes Certificate of Conformance.	.	.	.	.
NDT6036G1	GUIDE FOR NTD6036 BOEING 767 PART 4 57-20-004FIGURE 2 PAGE 7. Includes Certificate of Conformance.	.	.	.	.
NDT6036G2	GUIDE FOR NTD6036 BOEING 767 PART 4 57-20-004FIGURE 2 PAGE 7. Includes Certificate of Conformance.	.	.	.	.
AFW-60T/22R	60° IN TITANIUM LUCITE (PLEXIGLASS) WEDGE, 3/8-32 THREAD WITH A 22mm RADIUS USED WITH A .25"Ø DIAMETER TRANSDUCER WITH A 3/8-32 THREAD. Includes Certificate of Conformance. Reference part number AMS2630C.	.	.	.	.
AFW-60T/29R	60° IN TITANIUM LUCITE (PLEXIGLASS) WEDGE, 3/8-32 THREAD WITH A 29mm RADIUS USED WITH A .25"Ø DIAMETER TRANSDUCER WITH A 3/8-32 THREAD. Includes Certificate of Conformance. Reference part number AMS2630C.	.	.	.	.
AFW-70T/29R	70° IN TITANIUM LUCITE (PLEXIGLASS) WEDGE, 3/8-32 THREAD WITH A 29mm RADIUS USED WITH A .25"Ø DIAMETER TRANSDUCER WITH A 3/8-32 THREAD. Includes Certificate of Conformance. Reference part number AMS2630C.	.	.	.	.
AFW-70T/22R	70° IN TITANIUM LUCITE (PLEXIGLASS) WEDGE, 3/8-32 THREAD WITH A 22mm RADIUS USED WITH A .25"Ø DIAMETER TRANSDUCER WITH A 3/8-32 THREAD. Includes Certificate of Conformance.	.	.	.	.
NDT6063	Reference part number AMS2630C.	.	.	.	.
NDT734G1	Boeing Transducer Guide Part 4 57-54-02 Page 9 Figure 5. Includes Certificate of Conformance.	.	.	.	.
NDT773-G1	BOEING TRANSDUCER GUIDE, 777 PT 4 57-10-04 FIGURE 6 PAGE 20. Includes Certificate of Conformance.	.	.	.	.
MERC-17-UT-PF-01	ULTRASONIC LUCITE FIXTURE. Includes Certificate of Conformance.	.	.	.	.
MERC-20-UT-PF-01	ULTRASONIC LUCITE WEDGES. 2.33R RADIUS. Includes Certificate of Conformance.	120P	.	.	.
AFS-1390HC	90° IN ALUMINUM 5 MHz. .187" X .187" TOP MOUNT MINUTURE ANGLE BEAM TRANSDUCER. CASE SIZE: .690" L x .250" W x .590" H WITH TOP MOUNT MICRODOT CONNECTOR AND 10-32 HELICOIL ATTACHED FOR EXTENSION HANDLE USE. Includes Test Report and Certificate of Conformance.	GV-805	.	.	.
AFXX-560AT	EXTRA SMALL 5MHz 60° MINI ANGLE BEAM TRANSDUCER IN ALUMINUM, .310" L x .250" W. Includes Test Report and Certificate of Conformance.	SSX-605T.310	.	.	.
NRK-35S	CUSTOM NAVY BLOCK. MATERIAL: 304 STAINLESS STEEL. CONTAINING 20 FASTENER HOLES (.156-.750) WITH A TOTAL OF 71 EDM NOTCHES NOTCHES. Includes Test Report and Certificate of Conformance.	.	.	.	.
P6020A	BOEING TRANSDUCER POSITIONER 767 PART 4 57-50-14 PAGE 9 FIGURE 2. Includes Certificate of Conformance.	.	.	.	.
P6020B	BOEING TRANSDUCER POSITIONER 767 PART 4 57-50-14 PAGE 9 FIGURE 2. Includes Certificate of Conformance.	.	.	.	.
P6021A	BOEING TRANSDUCER POSITIONER 767 PART 4 57-50-14 PAGE 10 FIGURE 3. Includes Certificate of Conformance.	.	.	.	.
P6021B	BOEING TRANSDUCER POSITIONER 767 PART 4 57-50-14 PAGE 10 FIGURE 3. Includes Certificate of Conformance.	.	.	.	.
P6021C	BOEING TRANSDUCER POSITIONER 767 PART 4 57-50-14 PAGE 10 FIGURE 3. Includes Certificate of Conformance.	.	.	.	.
PDL 1036	C-130 TRUSS MOUNT UPPER LUG INSPECTION TRANSDUCER, 5MHz, "A" & "B" SMP 515-C INSPECTION PROCEDURE FOR WINGS CHAPTER 57. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-1018-1	10MHZ LONGITUDINAL BEAM TRANSDUCER .187"Ø DIAMETER ELEMENT, .25"Ø HOUSING 1.0" LONG WITH TOP MOUNTED MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFL-560AT-SS	60° ALUMINUM, ANGLE BEAM TRANSDUCER 5MHz .375"x.375" ELEMENT, STAINLESS STEEL HOUSING. CASE SIZE( 1.030 X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-531S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 5.0MHZ, .312"Ø WITH END MOUNTED MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFC-525-75S	5MHZ LONGITUDINAL(STRAIGHT BEAM) TRANSDUCER, .25"Ø ELEMENT, .375"Ø CASE, .750" LONG WITH SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	SUC-706	.	.	.
AFXX-570ST	EXTRA SMALL 5MHz 70° MINI ANGLE BEAM TRANSDUCER IN STEEL, .310" L x .250" W. Includes Test Report and Certificate of Conformance.	XXS-705T.310	.	.	.
AFNDT-2051/HOLDER	CUSTOM HOLDER FOR MISTRAS	.	.	.	.
AFXX-570AT	EXTRA SMALL 5MHz 70° MINI ANGLE BEAM TRANSDUCER IN ALUMINUM, .330" L x .250" W. Includes Test Report and Certificate of Conformance.	XXA-705T.330	.	.	.
AFXX-5455T	EXTRA SMALL 5MHz 45° MINI ANGLE BEAM TRANSDUCER IN STEEL, .310" L x .250" W. Includes Test Report and Certificate of Conformance.	XXS-455T.310	.	.	.
AFS-0503L	5MHZ 28° REFRACTED L WAVE 1.125" R	.	.	.	.
AFS-1268ST	5 MHz ANGLE BEAM TRANSDUCER 60° IN STEEL WITH TOP MOUNTED MICRODOT CONNECTOR, .150" X .250" ELEMENT. CASE SIZE: .35" W X .375" L X .375" H. Includes Test Report and Certificate of Conformance.	TEK-5548/30T	.	.	.
AFS-0504S	5MHZ 28° REFRACTED SHEAR WAVE 1.125" R	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-745AS	SMALL 45° ANGLE BEAM TRANSDUCER in ALUMINUM, 7.5MHz .187" x .187" ELEMENT, CASE SIZE(.550" x .26" x .450") SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-1401-70	TRANSDUCER, 70° in STEEL 6MHz, 3mm(.118") x 4mm(.157") ELEMENT WITH TOP MOUNT MICRODOT CONNECTOR. CASE SIZE: 15mm(.591"L) x (7mm).276"W x 12mm(.472"H). Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-745AT	SMALL 45° ANGLE BEAM TRANSDUCER in ALUMINUM, 7.5MHz .187" x .187" ELEMENT, CASE SIZE(.550" x .26" x .450") TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-760AS	SMALL 60° ANGLE BEAM TRANSDUCER in ALUMINUM, 7.5MHz .187" x .187" ELEMENT, CASE SIZE(.550" x .26" x .450") SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-1175T	70° ANGLE BEAM TRANSDUCER in ALUMINUM, .187" x .187" ELEMENT, TOP MOUNTED MICRODOT CONNECTOR. CASE SIZE: .67"L x .26"W x .33"H. Includes Test Report and Certificate of Conformance. Reference: B767 Part 4 53-50-05. Standard Part number NDT679	389-021-980	.	.	.
AFS-770AS	SMALL 70° ANGLE BEAM TRANSDUCER in ALUMINUM, 7.5MHz .187" x .187" ELEMENT, CASE SIZE(.550" x .26" x .450") SIDE MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-770AT	SMALL 70° ANGLE BEAM TRANSDUCER in ALUMINUM, 7.5MHz .187" x .187" ELEMENT, CASE SIZE(.550" x .26" x .450") TOP MOUNT MICRODOT CONNECTOR. Includes Test Report and Certificate of Conformance.	.	.	.	.
ABM-5024S	50° in ALUMINUM 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x .187" ELEMENT, CASE SIZE: .500"L x .45"H x .26"W. Includes Test Report and Certificate of Conformance.	.	.	.	.
AFS-0513L	35° SHEAR WAVE IN TI, RIGHT SIDE SCANNING, REAR CONNECTOR. MODIFIED VERSION OF AFS-0501L HARDWIRED CABLE	.	.	.	.
AFS-0513R	35° SHEAR WAVE IN TI, RIGHT SIDE SCANNING, REAR CONNECTOR, MODIFIED VERSION OF AFS-0501R HARDWIRED CABLE..	.	.	.	.
SUS 921L	CUSTOM TRANSDUCER COMPOUND ANGLE 45 DEGREES IN STEEL. WITH 3.5 INCH HANDLE. REMOVABLE CABLE MOUNT TO MICRODOT CONNECTOR (LEFT) USED WITH NDT3021, Part 4 57-50-01	AFS-1202L	.	.	.
SUS 921R	CUSTOM TRANSDUCER COMPOUND ANGLE 45 DEGREES IN STEEL. WITH 3.5 INCH HANDLE. REMOVABLE CABLE MOUNT TO MICRODOT CONNECTOR (RIGHT) USED WITH NDT3021, Part 4 57-50-01	AFS-1202R	.	.	.
NDT1086-P1	TRANSDUCER POSITIONER USED WITH SUS 1020 737 PART 4 53-30-05. Includes Certificate of Conformance.	.	.	.	.
NDT1086-P2	TRANSDUCER POSITIONER 737 PART 4 53-30-05. Includes Certificate of Conformance.	.	.	.	.
113-124-660.	5MHz x .250" DFR Style Removable Delay Line Contact Transducer	.	.	.	.
118-440-051.	Delay Lines for DFR model 527-660, 10 pk., .50" long	.	.	.	.
123	BOEING TRANSDUCER POSITIONER FIXTURE 737 PT 4 52-10-01	.	.	.	.
200P	INDONESIA AEROSPACE TRANSDUCER POSITIONER FIXTURE CN-235 PT 4 55-35-03 FIGURE 3	.	.	.	.
202P	INDONESIA AEROSPACE TRANSDUCER POSITIONING FIXTURE CN-235 PT 4 55-31-14 PAGE 7 FIGURE 3	.	.	.	.
204P	INDONESIA AEROSPACE TRANSDUCER POSITIONING FIXTURE CN-235 PT 4 55-30-06 PAGE FIGURE 3	.	.	.	.
209PA	INDONESIA AEROSPACE TRANSDUCER POSITIONER CN-235 PT 4 55-35-03 PAGE 6	.	.	.	.
209PB	INDONESIA AEROSPACE TRANSDUCER POSITIONER CN-235 PT 4 55-35-03 PAGE 6	.	.	.	.
210PA	INDONESIA AEROSPACE TRANSDUCER POSITIONER CN-235 PT 4 55-10-01 PAGE 6 FIGURE 3	.	.	.	.
210PB	INDONESIA AEROSPACE TRANSDUCER POSITIONER CN-235 PT 4 55-10-01 PAGE 6 FIGURE 3	.	.	.	.
53-20-165/2	RADIUSED ULTRASONIC PROBE SHOE USED WITH KSK AND REFERENCE STANDARD 53-20-165/1 (BAe 146 Series)	.	.	.	.
57-54-103C-POS	CUSTOM TRANSDUCER POSITIONER FOR 57-54-103C REFERENCE STANDARD	.	.	.	.
99D57204162000	Airbus A318/A319/A320/A321 Search Unit Guide Assembly 57-29-06-991-003-A. Material: Delrin	.	.	.	.
ABWM-4T-45-COD/1.84	BAE 146 SERIES / AVRO-RJ SERIES 45° DEGREE IN ALUMINUM WEDGE 3/8-32 THREAD WITH A 0.92" RADIUS	.	.	.	.
ABWM-4T-45-COD/1.88	BAE 146 SERIES / AVRO-RJ SERIES 45° DEGREE IN ALUMINUM WEDGE 3/8-32 THREAD WITH A 0.94" RADIUS	.	.	.	.
ABWM-4T-45-COD/2.10	BAE 146 SERIES / AVRO-RJ SERIES 45° DEGREE IN ALUMINUM WEDGE 3/8-32 THREAD WITH A 1.050" RADIUS	.	.	.	.
ADL-518S	HIGH DAMPED DUAL ELEMENT TRANSDUCER 5MHZ .187"Ø, SIDE MOUNT MICRODOT CONNECTOR	KBAS25	113232700	.	.
ADL-525HD	5 MHz .25" DUAL ELEMENT PIEZOCOMPOSITE TRANSDUCER WITH DUAL MICRODOT CONNECTORS. PERSPLEX FACE	.	.	.	.
ADL-525S	HIGH DAMPED DUAL ELEMENT TRANSDUCER 5.0MHZ .250"Ø, WITH 2 SIDE MOUNT MICRODOT CONNECTORS	DHC711-RM	113224700	.	.
ADLH-214	DELAY LINE - POLYSTYRENE(REXOLITE) 0.75"(19mm) LONG.	DLH-214	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ADLH-217	DELAY LINE - POLYSTYRENE(REXOLITE) 1.0"(25.4mm) LONG.	ADLH-217	.	.	.
ADLP-060	Aerofab Delay, tip diameter 0.060 in. for AFP-1512 Series pencil transducers.	DLP-302	.	.	.
ADLP-080	Focused delay for use with V260 Sonopen, tip diameter 0.080 in. used with AFP-1512 (V-260SM, V-260RM) style pencil Transducers.	DLP-3	.	.	.
AF-560AT	SMALL 60° TOP MOUNT TRANSDUCER, ALUMINUM 187"x.25" ELEMENT. CASE SIZE; .400"L x .300"W x .375"H	560AT	.	.	.
AF62-AWS45S	ASW 45° WEDGE IN STEEL	ABWS-6-45	.	.	.
AF62-AWS60S	ASW 60° WEDGE IN STEEL	ABWS-6-60	.	.	.
AF62-AWS70S	ASW 70° WEDGE IN STEEL	ABWS-6-70	.	.	.
AFC-0502	2.25MHZ .375"Ø PIEZO COMPOSITE ELEMENT TOP MOUNT CONNECTOR W/ COSTOM CASE	.	.	.	.
AFC-0503	Longitudinal Wave Transducer,10MHz, 6mm(.25") dia. element medium damped side mounted microdot connector. Knurled Case size (.50 dia. x .670H)	226-000	.	.	.
AFC-0509	MSW-QC STYLE QUICK CHANGE TRANSDUCER 5MHZ .25" ELEMENT 3/8-32 THREAD	224-590	.	.	.
AFC-0510	10MHZ .250" HARDWIRED STRAIGHT BEAM TRANSDUCER WITH BNC CONNECTOR. BOEING 767 PT 4 57-50-07	TEK-5005	.	.	.
AFC-0510F	TRANSDUCER POSITIONING FIXTURE PT 4 57-50-07 FIG 3	TEK-5005F	.	.	.
AFC-0512S	5MHz High Damped straight beam transducer attached to a 2 inch handle with a total length of 4.0" .125" element with a case diameter of .187"Ø and a case height .500".	.	.	.	.
AFC-0514	5MHZ TRANSDUCER, .25" Ø ELEMENT, .275"Ø CASE, FOR POSITIONER NDT3125P	.	.	.	.
AFC-0517S	10MHz High Damped straight beam transducer attached to a 2.0" inch handle with a total length of 4.0" .125" element with a case diameter of .187"Ø and a case height .500".	.	.	.	.
AFC-0521	5MHZ TRANSDUCER QUICK CHANGE EQUIVALENT(234-590)	.	.	.	.
AFC-0522	10 MHz, .25"ELEMENT HIGH DAMPED 3/8-32 THREAD QUICK CHANGE MSWQC STYLE TOP MOUNT CONNECTOR	.	.	.	.
AFC-0522S	10 MHz, .25"ELEMENT HIGH DAMPED 3/8-32 THREAD QUICK CHANGE MSWQC STYLE SIDE MOUNT CONNECTOR	.	.	.	.
AFC-0523	5 MHz, .25"ELEMENT HIGH DAMPED 3/8-32 THREAD QUICK CHANGE MSWQC STYLE TOP MOUNT CONNECTOR	.	.	.	.
AFC-0523S	5 MHz .25"ELEMENT HIGH DAMPED 3/8-32 THREAD QUICK CHANGE MSWQC STYLE SIDE MOUNT CONNECTOR	.	.	.	.
AFC-0524	5MHz High Damped pancake transducer attached to a 2 inch handle. .25" element with a max case height .25"	.	.	.	.
AFC-0527	CONTACT L-WAVE TRANSDUCER 5 MHz .25" ELEMENT, .375" Dia CASE .65" H	.	.	.	.
AFC-0528-710	10MHz .25" diameter element Straight Beam contact transducer. Case Size: 5/16" diameter .700" long with top mounted microdot connector. Medium Damped	.	.	.	.
AFC-0530	5MHZ TOP MOUNT FINGERTIP CONTACT TRANSDUCER, .187"Ø ELEMENT, CASE SIZE: .25"Ø x .625"L. USED WITH NDT6030P. 767 PT 4 57-50-10 PAGE 15.	TEK-5083	.	.	.
AFC-0539	Custom 5MHz .25" diameter piezo-composite straight beam transducer with a convex radius of 6.75". Transducer fitted to custom yolk with handle to microdot connector	.	.	.	.
AFC-0541C	CUSTOM CONVEX TRANSDUCER 20MHz .25" dia. WITH PERMANENT FIXED DELAY SHOE	1ROT20M	.	.	.
AFC-0541R	CUSTOM CONCAVE TRANSDUCER 20MHz .25" dia. WITH PERMANENT FIXED DELAY SHOE	2ROT20M	.	.	.
AFC-0542	Custom 5 MHz, .125"Ø, Sub-miniature Transducer GE SMSWS 214-585. Case Size: .310" x .190" x .280".	214-585	.	.	.
AFC-0544	Stainless Steel MSWS Style Angle Beam Transducer designed for weld inspection. Designed to be used with removavle lucite wedges. 5MHz .25"Ø with microdot connector angled 45°	224-580	.	.	.
AFC-0600G	5MHz .25" dia PZ37 element medium damped. Case size (.437" X .630" knurled).Gamma Series	224-000	.	.	.
AFC-0601G	5MHz .375" dia PZ37 element medium damped. Case size (.530" X .650" knurled).Gamma Series	234-000	.	.	.
AFC-0602G	5MHz .500" dia PZ37 element medium damped. Case size (.650" X .630" knurled).Gamma Series	244-000	.	.	.
AFC-1012H	10MHZ .125"Ø DIAMETER ELEMENT STRAIGHT BEAM TRANSDUCER, .190"Ø HOUSING 1.0" LONG, HARD WIRED TO BNC CONNECTOR, 6.0' LONG.	389-002-190	Y-M-1/8-10	389-002-190	.
AFC-1018-7	10MHZ, .25" element, Straight Beam Transducer, CASE .312" OD X.75"L	SPO-6283	SPO-6283	TC75-1810T-1	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFC-1025-6	10mm DIA. HIGH DAMPED COMPRESSION TRANSDUCER 0 DEGREES. 10 MHz .25" DIA. ELEMENT.(CASE SIZE .393"O.D. x .625"H) KNURLED	K10K	.	.	.
AFC-1025-7T	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 10.0MHZ, .250"Ø WITH TOP MOUNT MICRODOT CONNECTOR CASE SIZE:.375DIA x .700"H	SUC726T	SUC726T	TC8-2510T	.
AFC-1025HST	Contact Transducer, 10 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Topt Microdot Connector..(500" H x .390"OD)	M112-SM	V112-SM	.	.
AFC-1025HT	10MHZ HIGH DAMPED CONTACT TRANSDUCER, .25 ELEMENT, .312Ø CASE O.D., .700" TALL, TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFC-1025KN	GENERAL PURPOSE 10MHZ 1/4" DIA. STRAIGHT BEAM TRANSDUCER. SIDE MOUNT MICRODOT CONNECTOR, KNURLED CASE.	CF-1002-GP	.	.	.
AFC-1025T	Contact Transducer, 10 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Top Microdot Connector..(500" H x .375"OD)	.	.	.	.
AFC-1031S	CONTACT TRANSDUCER 10MHZ .25"Ø ELEMENT. .312" CASEØ, .525" SIDE MOUNT CONNECTOR	.	.	.	.
AFC-1037HS	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER, HIGH DAMPED 10.0MHZ, .375"Ø WITH SIDE MOUNT MICRODOT CONNECTOR CASE SIZE:.500" DIA x .650"H	A127S-RM	.	.	.
AFC-1050S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 10.0MHZ, .500"Ø WITH SIDE MICRODOT CONNECTOR	CM-1008-R-RM	.	.	.
AFC-110S	GENERAL PURPOSE 1.0MHZ 1.0" DIA. STRAIGHT BEAM TRANSDUCER. SIDE MOUNT MICRODOT CONNECTOR.	CF-0108-GP	.	.	.
AFC-1210H	CONTACT TRANSDUCER .125Ø, 10MHZ, HIGH DAMPED	.	.	.	.
AFC-125	STRAIGHT BEAM CONTACT TRANSDUCER, ELEMENT SIZE .125", 5MHZ	.	.	.	.
AFC-218S	HIGH DAMPED CONTACT TRANSDUCER 187" DIAMETER FINGERTIP STYLE CASE WITH SIDE MICRODOT CONNECTOR	SUC 162-TWB	SUC 162-TWB	.	.
AFC-225HS	HIGH DAMPED SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 2.25MHZ, .25"Ø WITH SIDE MOUNT MICRODOT	V133-RM	CF-0202-GP	.	.
AFC-231S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 2.25MHZ, .312"Ø WITH SIDE MOUNT MICRODOT CONNECTOR	72T005	.	.	.
AFC-237S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 2.25MHZ, .375"Ø WITH SIDE MOUNT MICRODOT CONNECTOR	H277100	CF-0203-GP, 113-832-000	57A2275	.
AFC-250GP-S	SINGLE ELEMENT CONTACT TRANSDUCER 2.25MHZ, .500"Ø WITH MICRODOT CONNECTORS	CF-0204-GP	.	.	.
AFC-250HS	HIGH DAMPED SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 2.25MHZ, .500"Ø WITH SIDE MOUNT MICRODOT CONNECTOR	.	.	.	.
AFC-250HT	HIGH DAMPED SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 2.25MHZ, .500"Ø WITH TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFW-500045A	CUSTOM ACRYLIC WEDGE 45" IN ALUMINUM, 1.260"Long X .525" Wide X .460" High. Includes Certificate of Conformance.	.	.	.	.
AFC-250S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 2.25MHZ, .500"Ø WITH SIDE MOUNT MICRODOT CONNECTOR	M106-RM	CF-0204-GP	GRD-0204-HR	.
AFC-250T	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 2.25MHZ, .500"Ø WITH TOP MOUNT MICRODOT CONNECTOR	M106-SM	.	.	.
AFC-255T	CONTACT TRANSDUCER, 5.0MHZ, .25" EL, .312 CASE, TOP MOUNT	TC-255T	.	.	.
AFC-275SB	Contact Transducer, 2.25 MHz, 0.75 in. Element Diameter, Standard Case Style, Right BNC Connector. ACCUSCAN TYPE	A105S-RB	.	.	.
AFC-3110	10MHZ .188Ø 0" .313" O/D .75" LONG PT 4 57-50-04	.	.	.	.
AFC-350S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 3.5MHZ, .500"Ø WITH SIDE MICRODOT CONNECTOR	.	.	.	.
AFC4-375S	5MHZ TRANSDUCER, .375 ELEMENT, SIDE MOUNT CONNECTOR, .400"H CASE	TC4-375S	.	.	.
AFC-5006	CUSTOM 767 PART 4 57-50-05 10MHZ SPRING LOADED LONGITUDINAL WAVE TRANSDUCER. (TEK-5006)	TEK-5006	.	.	.
AFC-5007	CUSTOM 767 PART 4 57-50-05 10MHZ LONGITUDINAL WAVE TRANSDUCER. (TEK-5007)	TEK-5007	.	.	.
AFC-518-4S	5MHZ CONTACT TRANSDUCER .187Ø, .400H, SIDE MOUNT	5702284	.	.	.
AFC-518T	5MHZ TOP MOUNT FINGERTIP CONTACT TRANSDUCER, .187Ø ELEMENT, .25Ø CASE. Used with NDT616P	TC5-185T	SPO-982	.	.
AFC-525-4S	5MHZ CONTACT TRANSDUCER .250Ø, .400H, SIDE MOUNT	57A2214	.	.	.
AFC-525-6T	5MHZ MEDIUM DAMPING STRAIGHT BEAM TRANSDUCER, .25 ELEMENT, .375Ø CASE O.D., .600" TALL, TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFC-525-75T	5MHZ LONGITUDINAL(STRAIGHT BEAM) TRANSDUCER, .25"Ø ELEMENT, .375Ø CASE, .750" LONG WITH TOP MOUNT MICRODOT CONNECTOR.	.	.	.	.



September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFC-525HDS	Contact Transducer, 5 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Side Mounted Microdot Connector (.500" H x .375).	M110-RM	.	.	.
AFC-525HDT	Contact Transducer, 5 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Top Mounted Microdot Connector (.500" H x .390"OD) Knurled Case.	M110-SM	.	.	.
AFC-525HT	5MHZ HIGH DAMPED CONTACT TRANSDUCER, .25 ELEMENT, .312"Ø CASE O.D., .700" TALL, TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFC-525KN	GENERAL PURPOSE 5MHZ 1/4" DIA. STRAIGHT BEAM TRANSDUCER. SIDE MOUNT MICRODOT CONNECTOR, KNURLED CASE.	CF-0502-GP	.	.	.
AFC-525S-1	Contact Transducer, 5 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Right Microdot Connector. (.500" H x .312"OD)	SUC 166-1	6635-01-607-9992	.	.
AFC-525T	Contact Transducer, 5 MHz, 0.25 in. Element Diameter, Fingertip Case Style, Top Microdot Connector (.500" H x .375"OD) KNURLED	A110S-SM	CF-0502-GP	.	.
AFC-525T7	5MHZ MEDIUM DAMPED CONTACT TRANSDUCER, .25 ELEMENT, .312"Ø CASE O.D., .700" TALL, TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFC-537TS	5MHZ .375"Ø THREADED TRANSDUCER MSWQC SERIES	.	.	.	.
AFC-550GP-S	SINGLE ELEMENT CONTACT TRANSDUCER 5.0MHZ, .500"Ø WITH MICRODOT CONNECTORS	CF-0504-GP	.	.	.
AFC-550S	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 5.0MHZ, .500"Ø WITH SIDE MICRODOT CONNECTOR	CM-0508-R-RM	CF-0504-GP, A109S-RM	UT-BT-BC55M	CM-0508-R-RM
AFC-550T	SINGLE ELEMENT FINGER TIP CONTACT TRANSDUCER 5.0MHZ, .500"Ø WITH TOP MICRODOT CONNECTOR	A109S-SM	..	.	.
AFC-5755B	Contact Transducer, 5 MHz, 0.75 in. Element Diameter, Standard Case Style, Right BNC Connector, ACCUSCAN TYPE	A108S-RB	.	.	.
AFC-725HT	7.5MHZ HIGH DAMPED CONTACT TRANSDUCER, .25 ELEMENT, .312"Ø CASE O.D., .700" TALL, TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFC-AWS262	2.25MHZ .625" ELEMENT AWS CASE W/ BNC CONNECTOR, COMPOSITE ELEMENT	.	.	.	.
AFC-C550	5MHZ 1/2" DIA STRAIGHT BEAM COMPOSITE ELEMENT TRANSDUCER SIDE CONNECTOR	RHF 054	RHF 054	.	.
AFC-H225S	2.25MHZ .25"Ø FINGER TIP CONTACT TRANSDUCER	.	.	.	.
AFC-H250S	2.25MHZ .50"Ø FINGER TIP CONTACT TRANSDUCER	.	.	.	.
AFC-H275S	2.25MHZ .70"Ø FINGER TIP CONTACT TRANSDUCER	.	.	.	.
AFC-H525S	5MHZ .25"Ø FINGER TIP CONTACT TRANSDUCER	.	.	.	.
AFC-H550S	5MHZ .50"Ø FINGER TIP CONTACT TRANSDUCER	.	.	.	.
AFC-H575S	5MHZ .75"Ø FINGER TIP CONTACT TRANSDUCER	.	.	.	.
AFC-K15M	1.0 MHz 1.0 inch diameter element straight beam compression transducer used for the inspection of composite materials.	.	.	.	.
AFC-S-1025T	10MHz .25" DIA. ELEMENT MEDIUM DAMPED SCREW IN TRANSDUCER. 3/8"-32 THREAD	389-025-070	.	.	.
AFC-S-250T	SINGLE ELEMENT COMPOSITE FINGER TIP CONTACT TRANSDUCER 2.25MHZ, .500"Ø WITH MICRODOT CONNECTOR,(5/8-24 thread,MSWQC STYLE)	113-591-242	.	.	.
AFC-S-H150	Angle Beam Transducer, 1 MHz, 0.50 in. Element Diameter, Miniature Screw-In Case Style, Straight Microdot Connector. (CentraScan)	C539-SM	A539S-SM	.	.
AFC-S-H250	Benchmark Series Straight Beam Threaded Transducer, 2.25 MHz, 0.50 in. element size, Straight Microdot Connector. MSWQC STYLE	.	C540-SM	.	.
AFC-S-H350	Straight Beam Transducer, 3.5 MHz, 0.50 in. element size, CentraScan Case Style, Straight Microdot Connector	C545-SM	.	.	.
AFC-S-H531	5MHZ SCREW IN HIGH DAMPED STRAIGHT BEAM TRANSDUCER 7/16-32 THREAD, TOP MOUNT CONNECTOR	.	.	.	.
AFC-S-H537	5MHZ 3/8" DIA SCREW IN HIGH DAMPED STRAIGHT BEAM TRANSDUCER 1/2-28 THREAD, TOP MOUNT CONNECTOR	MSWQC	.	.	.
AFC-S-H550	Angle Beam Transducer, 5 MHz, 0.50 in. Element Diameter, Miniature Screw-In Case Style, Straight Microdot Connector. (CentraScan)	C540-SM	MSWQC	.	.
AFC-V550/B	5MHZ CONTACT TRANSDUCER, .050" ELEMENT Ø, RIGHT BNC CONNECTOR	.	.	.	.
AFL-245AT	45° IN ALUMINUM ANGLE BEAM TRANSDUCER 2.25MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFL-245ST	45° IN STEEL ANGLE BEAM TRANSDUCER 2.25MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFL-260AT	60° IN ALUMINUM ANGLE BEAM TRANSDUCER 2.25MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR	.	.	.	.

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFL-260ST	60° IN STEEL ANGLE BEAM TRANSDUCER 2.25MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFL-270AS	70° IN ALUMINUM ANGLE BEAM TRANSDUCER 2.25MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )SIDE MOUNT MICRODOT CONNECTOR	LA-702S	.	..	.
AFL-270AT	70° IN ALUMINUM ANGLE BEAM TRANSDUCER 2.25MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR	LA-702T	.	.	.
AFL-270ST	70° IN STEEL ANGLE BEAM TRANSDUCER 2.25MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFL-545SS	45° STEEL, ANGLE BEAM TRANSDUCER 5MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )SIDE MOUNT	LS-455S	SU 545SS	..	.
AFL-545ST	45° STEEL, ANGLE BEAM TRANSDUCER 5MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT	LS-455T	SU 545ST	..	.
AFL-560ST	60° STEEL, ANGLE BEAM TRANSDUCER 5MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT	LA-605T	SU 560AT	.	.
AFL-570ST	70° STEEL, ANGLE BEAM TRANSDUCER 5MHZ .375"x.375" ELEMENT, CASE SIZE( 1.030L X .500W X .625H )TOP MOUNT TRANSDUCER	LA-705T	SU 570AT	.	.
AFM-1045AT	45° ALUMINUM 10MHZ 1/4" X 1/4" TOP MOUNT TRANSDUCER	SUM-1045AT			
AFM-1045SS	45° STAINLESS STEEL 10MHZ 1/4" X 1/4" SIDE MOUNT TRANSDUCER	SUM 1045SS	SUM-1045SS	.	.
AFM-1045ST	45° STEEL10MHZ 1/4" X 1/4" TOP MOUNT TRANSDUCER	SUM-1045ST		.	.
AFM-1060AT	60° ALUMINUM 10MHZ 1/4" X 1/4" TOP MOUNT TRANSDUCER	SUM-1060AT			
AFM-1070SS	70° STAINLESS 10MHZ 1/4" X 1/4" SIDE MOUNT TRANSDUCER	SUM 1070AS	SUM-1070AS	.	.
AFM-1075AS	75° ALUMINUM 10MHZ 1/4" X 1/4" SIDE MOUNT ANGLE BEAM TRANSDUCER	MA-7510S	SUM 1075AS	.	.
AFM-1075AT	75° ALUMINUM 10MHZ 1/4" X 1/4" TOP MOUNT ANGLE BEAM TRANSDUCER	SUM 1075AT	MA-7510T	.	.
AFM-245AT	45° IN ALUMINUM 2.25 MHz .25" X .25" TOP MOUNT ANGLE BEAM TRANSDUCER. CASE SIZE: .75"L x .37"W x .50"H	.	.	.	.
AFM-245SS	45° IN STEEL 2.25 MHz .25" X .25" SIDE MOUNT ANGLE BEAM TRANSDUCER. CASE SIZE: .75"L x .37"W x .50"H	A561S-RM	.	.	.
AFM-270AD	70° ALUMINUM 2.25 MHz 1/4" X 1/4" TOP and SIDE MOUNT TRANSDUCER BUILT IN ONE. TWO MICRODOT CONNECTORS	.	.	.	.
AFM-540AS	40° IN ALUMINUM 5 MHz .25" X .25" SIDE MOUNT ANGLE BEAM TRANSDUCER. CASE SIZE: .75"L x .37"W x .50"H	MA-405S	.	.	.
AFM-540AT	40° ALUMINUM 5 MHz 1/4" X 1/4" TOP MOUNT TRANSDUCER..	SUM-540AT			
AFM-545SS	45° IN STEEL 5 MHz .25" X .25" SIDE MOUNT MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75"L x .37"W x .50"H WITH MICRODOT CONNECTOR	A571S-RM	SUM-545SS	MS-455S	
AFM-560AT-32	60° ALUMINUM 5 MHz 1/4" X 1/4", TOP MOUNT, .320" MAX HEIGHT TRANSDUCER	MA-605T-32	SUM 560AT-32	.	.
AFM-570AD	70° ALUMINUM 5 MHz 1/4" X 1/4" TOP and SIDE MOUNT TRANSDUCER BUILT IN ONE. TWO MICRODOT CONNECTORS	.	.	.	.
AFM-570AD-1	70° ALUMINUM 5 MHz 1/4" X 1/4" TOP and SIDE MOUNT TRANSDUCER BUILT IN ONE. TWO MICRODOT CONNECTORS. CASE SIZE: .700"L x .320"W x .620"H	.	.	.	.
AFM-570SS	70° IN STEEL 5 MHz .25" X .25" MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75"L x .37"W x .50"H WITH SIDE MICRODOT CONNECTOR	A573S-RM	SUM-570SS	MS-705S	A573SRM
AFM-570ST	70° IN STEEL 5 MHz .25" X .25" TOP MOUNT MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .75"L x .37"W x .50"H WITH MICRODOT CONNECTOR	SUM-570ST	MS-705T		.
AFM-580AT	80° ALUMINUM 5 MHz 1/4" X 1/4" TOP MOUNT TRANSDUCER	.	.	.	.
AFM-650AT	50° ALUMINUM 6 MHz 1/4" X 1/4" TOP MOUNT TRANSDUCER	MA-605T	.	.	.
AFM-670ST	70° STAINLESS 6 MHz 1/4" X 1/4" TOP MOUNT TRANSDUCER	.	.	.	.
AFM-ADH-1	CUSTOM ULTRASONIC TRANSDUCER HOLDER #1 FOR DUAL MICRODOT AFM SERIES TRANSDUCERS FOR 747 PART 4 57-10-09 Pg.4 (AFM-570AD-1, AFM-545AD-1)	.	.	.	.
AFM-ADH-2	CUSTOM ULTRASONIC TRANSDUCER HOLDER #2 FOR DUAL MICRODOT AFM SERIES TRANSDUCERS FOR 747 PART 4 57-10-09 Pg.4 (AFM-570AD-1, AFM-545AD-1)	.	.	.	.
AFNDT-1018AWSDS	DISTANCE / SENSITIVITY (DS) CALIBRATION BLOCK 1018 STEEL..AWS type DS	.	.	.	.
AFNDT-4340DAA19	ASTM DISTANCE AMPLITUDE SET OF 19 4340 CARBON STEEL (CASE INCL) 3/34", 5/64" and 8/64" FLAT BOTTOM HOLES	.	.	.	.
AFNDT-6AL-4VAWSDS	DISTANCE / SENSITIVITY (DS) CALIBRATION BLOCK 6AL-4V TITANIUM..AWS type DS	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFNDT-6AL-4VDAA19	ASTM DISTANCE AMPLITUDE SET OF 19 6AL-4V TITANIUM (CASE INCL) 3/34", 5/64" and 8/64" FLAT BOTTOM HOLES	.	.	.	.
AFNDT-7075AWSDS	DISTANCE / SENSITIVITY (DS) CALIBRATION BLOCK 7075-T6 ALUMINUM..AWS type DS	.	.	.	.
AFNDT-DAC/1018	Used for establishment of primary reference responses for UT examination of welds. Block contains three DAC side-drilled holes at 1.5" deep minimum at diameters between 3/32" and 1/4" depending on the block thickness (T). Hole locations through the ...	.	.	.	.
AFNDT-DAC3	SET OF 3 DAC BLOCKS,(DISTANCE/AREA AMPLITUDE SET) 7075-T6 ALUMINUM...3/64", 5/64", 8/64" FLAT BOTTOM HOLES WITH METAL TRAVEL DISTANCES OF (1/8", 1/4", 1/2", 3/4", 1 1/2", 3")	UT-RC-FBHB-AL-A	.	.	.
AFNDT-DAC7	SET OF 7 DAC BLOCKS,(DISTANCE/AREA AMPLITUDE SET) 7075-T6 ALUMINUM...3/64" FLAT BOTTOM HOLES WITH METAL TRAVEL DISTANCES OF (1/8", 1/4", 1/2", 3/4", 1", 1 1/4", and 1 3/4")	UT-RC-FBHB-AL-A	.	.	.
AFNDT-IIW-01-CASE	Form Fitted Wood Case for IIW Type 1 Calibration Block	.	.	.	.
AFNDT-PSM-5	The PSM-5 Panel is manufactured to Pratt-Whitney P/N TAM 146040 specifications. Smooth Type - the chrome plated strip of the second version is not grit blasted. Sherwin Incorporated is an authorized manufacturer of TAM 146040 panels. PSM-5 Panel proce...	.	.	.	.
AFNDT-ROMPAS-1018-CS	Angle Beam (Rompas), 1018 Carbon Steel. 1/2" (12.5mm) or 1" (25.4 mm) thick, 1" radius opposite 2" radius, with 5/64" diameter side drilled hole (3/4" deep flat bottom hole in 1" thick version).	.	.	.	.
AFP-080/TIP	.080" THREADED DELAY TIP FOR THE AFP SERIES PENCIL TRANSDUCERS	.	.	.	.
AFP-1012	10 MHZ .125" dia focused Straight shaft pencil transducer with a .080" Replaceable tip. Standard microdot connector	HC-398-RDL-L	.	.	.
AFP-1512	15 MHZ .125" dia focused Straight shaft pencil transducer with a .080" Replaceable tip. Standard microdot connector	V260-SM	V260-SM	.	.
AFP-1512/90	15 MHZ 90° SHAFT .125" dia focused pencil transducer with a .060" Replaceable tip. Standard microdot connector	V260-RM	930811	.	.
APPT60	.060" DELAY TIP FOR SONOPEN TYPE PENCIL TRANSDUCERS. 1/4-36 THREAD.	.	.	.	.
APPT80	.080 DELAY TIP FOR PENCIL TRANSDUCERS. 1/4-36 THREAD	U8411019	HAX-398	.	.
AFS-0500L	5MHZ 28° SHEAR WAVE IN TI, 1.97 LEFT SIDE	.	.	.	.
AFS-0500R	5MHZ 28° SHEAR WAVE IN TI, 1.97 RIGHT SIDE	.	.	.	.
AFS-0501L	35° SHEAR WAVE IN TI, 1.97 RIGHT SIDE SCANNING	.	.	.	.
AFS-0501R	35° SHEAR WAVE IN TI, 1.97 RIGHT SIDE SCANNING	.	.	.	.
AFS-0503-45S	STAVELEY 45 DEGREES IN ALUMINUM SHEAR WAVE TRANSDUCER 5MHZ 187" x .187" ELEMENT SIDE MOUNT MICRODOT CONNECTOR	PAB-0503-45	TEK-0503-45AT	.	.
AFS-0506	5MHZ 51° SHEAR WAVE IN ALUMINUM. CASE SIZE .50" W x .80" L x .37" H, REFERENCE STANDARD NDT624	XAB-6056	.	.	.
AFS-0507	5MHZ 32° SHEARWAVE IN ALUMINUM. CASE SIZE .50"X.80" L. HEIGHT TAPERS FROM .20" H FRONT TO .32" H BACK. REFERENCE STANDARD IS NDT624	XAB-6057	.	.	.
AFS-0508	5MHZ BACKSHOOTER IN TI .25" ELEMENT, CASE SIZE .300HX.300WX.500L	.	.	.	.
AFS-0510	CUSTOM TRANSDUCER FOR THE P8 LUG INSPECTION. 5MHZ BACKSHOOTER WITH MAGNETIC PIVOTING HEAD	.	.	.	.
AFS-0511	CUSTOM TRANSDUCER FOR THE P8 LUG INSPECTION. 5MHZ FORWARD SHOOTER WITH MAGNETIC PIVOTING HEAD	.	.	.	.
AFS-0514L	5MHZ 28° SHEAR WAVE IN TI, 1.97 LEFT SIDE, AFT HANDLE, MODIFIED VERSION OF AFS-0500L	.	.	.	.
AFS-0514R	5MHZ 28° SHEAR WAVE IN TI, 1.97 LEFT SIDE, AFT HANDLE. MODIFIED VERSION OF AFS-0500R	.	.	.	.
AFS-0516L	5MHZ 45° SHEARWAVE. SCANS TOWARDS THE LEFT. LOW PROFILE TRANSDUCER	.	.	.	.
AFS-0516R	5MHZ 45° SHEARWAVE. SCANS TOWARDS THE RIGHT. LOW PROFILE TRANSDUCER	.	.	.	.
AFS-0517L	5MHZ 45° SHEARWAVE WITH 34° COMPOUND ANGLE. SCANS TOWARDS THE LEFT. LOW PROFILE TRANSDUCER	.	.	.	.
AFS-0517R	5MHZ 45° SHEARWAVE WITH 34° COMPOUND ANGLE. SCANS TOWARDS THE RIGHT. LOW PROFILE TRANSDUCER	.	.	.	.
AFS-0518L	LEFT SCANNING L-WAVE ULTRASONIC TRANSDUCER	.	.	.	.
AFS-0518R	RIGHT SCANNING L-WAVE ULTRASONIC TRANSDUCER	.	.	.	.
AFS-0520	10 MHz .187x.187 element L-Wave transducer 19 degree incident angle, 1.569R. Case size: .50Lx.26Wx.425H top mount connector	.	.	.	.
AFS-0522	5MHZ 45° CUSTOM TRANSDUCER, AL, 2.9"LX.900"WX1.75"H	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-0524	5 MHz shear wave transducer .25" x .25" square element. 1.025 radius top mount connector. used with NDT3238 ref. standard	.	.	.	.
AFS-0525	5 MHz COMPOUND SHEARWAVE TRANSDUCER USED FOR LEFT SIDE EDM BORE NOTCH ON NDT3242	.	.	.	.
AFS-0526	5 MHz COMPOUND ANGLE SHEARWAVE TRANSDUCER WITH A 2.275 INCH RADIUS. USED TO SCAN NEAR SIDE EDM NOTCH ON NDT3243	.	.	.	.
AFS-0527	5 MHz SHEARWAVE TRANSDUCER USED TO SCAN MID BORE EDM NOTCH ON NDT3242 and NDT3243, 35° INCIDENT ANGLE	.	.	.	.
AFS-0528	42.5° SHEARWAVE TRANSDUCER, 5MHZ OUTER LUG INSPECTION, LOW PROFILE SIDE MOUNT CONNECTOR	.	.	.	.
AFS-0529	33.5° 5MHZ SHEARWAVE TRANSDUCER, NOSE AREA OF LUG, LOW PROFILE SIDE MOUNT TRANSDUCER	.	.	.	.
AFS-0530-4	5MHz 45 deg in steel angle beam transducer. (.500"L x .300"W x .425"H)	.	.	.	.
AFS-0530-6	5MHz 60 deg in steel angle beam transducer. (.500"L x .300"W x .425"H)	.	.	.	.
AFS-0531	CUSTOM ANGLE BEAM TRANSDUCER ..5MHZ 45 DEG. IN ALUMINUM TOP MOUNT CONNECTOR. ...CASE SIZE(.230"L x .350"W x .500"H)	.	.	.	.
AFS-0532	CUSTOM MULTI SHOE TRANSDUCER 45 DEG. IN ALUMINUM 5MHZ. (15, 0, 15, DEGREE OFF SETS)	.	.	.	.
AFS-0536	5MHZ SHEARWAVE TRANSDUCER, 45°, STEEL, .187" x .250" ELEMENT. CASE SIZE .380"Lx.300"Wx.500H,	.	.	.	.
AFS-0537	5MHZ SHEARWAVE TRANSDUCER, 60°, STEEL, .187" x .500" ELEMENT. CASE SIZE, .380"Lx.300"Wx.500H	.	.	.	.
AFS-0538L	CUSTOM SHEARWAVE TRANSDUCER, 5MHZ, LEFT SIDE, FOR NDT6052	.	.	.	.
AFS-0538R	CUSTOM SHEARWAVE TRANSDUCER, 5MHZ, RIGHT SIDE, FOR NDT6052	.	.	.	.
AFS-0539	Custom 5MHz 45 degree shearwave ring transducer which features both right and left scanning directions. Ref. Standard NDT796	.	.	.	.
AFS-0541	Custom 5MHz 75 degree shearwave transducer.	.	.	.	.
AFS-0542	Custom 5MHz 80 degree shearwave transducer.	.	.	.	.
AFS-0543	Custom 10MHz 75 degree shearwave transducer.	.	.	.	.
AFS-0544	Custom 5MHz 80 degree shearwave transducer. A318/A319/A320/A321 Part 4 57-29-11 page 2.	SM55-80	.	.	.
AFS-0545	5MHz 45 deg in aluminum angle beam transducer. (.600"L x .350"W x .45"H). (AP-HP-1/4-5.00-45A)	AP-HP-1/4-5.00-45A	.	.	.
AFS-0546	5MHz 60 deg in aluminum angle beam transducer. (.600"L x .350"W x .45"H). (AP-HP-1/4-5.00-60A)	AP-HP-1/4-5.00-60A	.	.	.
AFS-0547	ANGLE BEAM TRANSDUCER 5MHz 70 degrees in steel with side mount ...microdot connector. Case size(.33"W x .375"L x 75"H)	TEK-5557/7055	.	.	.
AFS-0550	CUSTOM ANGLE BEAM TRANSDUCER 70 DEGREES 58 INC. 5MHz .25"x.160" ELEMENT TOP MOUNT MICRODOT...CASE(.380"L x .300"W x .500"H)...USED WITH NDT784	.	.	.	.
AFS-0551	CUSTOM TRANSDUCER 5MHz .187"x.187" ELEMENT SIDE MOUNT MICRODOT CONNECTOR WITH A 1.70" RADIUS USED WITH NDT3271...CASE(.550"L x .300"W x .450"H)	.	.	.	.
AFS-0553	CUSTOM 10 MHz L-WAVE TRANSDUCER WITH a 3.096" RADIUS. .187" ELEMENT...CASE SIZE(1.0" L x .275"W x .500H)	.	.	.	.
AFS-0554	CUSTOM POTTED HIGH DAMPED 10 MHz L-WAVE TRANSDUCER WITH a 3.096" RADIUS. .187" ELEMENT...CASE SIZE(1.0" L x .275"W x .500H)	.	.	.	.
AFS-0558	CUSTOM MINITURE 70 DEGREE ANGLE BEAM TRANSDUCER TOP MOUNT MICRODOT CONNECTOR...300" L x .260"W x .375"H	.	.	.	.
AFS-0559	CUSTOM 5MHz MINITURE 70 DEGREE IN ALUMINUM ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR.	.	.	.	.
AFS-05605	CUSTOM 5MHz MINITURE 70 DEGREE IN ALUMINUM ANGLE BEAM TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR. CASE SIZE: .500"L x .270"W x .300"H	.	.	.	.
AFS-05615	CUSTOM 5MHz MINITURE 45 DEGREE IN ALUMINUM ANGLE BEAM TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR. CASE SIZE: .500"L x .270"W x .300"H	.	.	.	.
AFS-0562	CUSTOM 5MHz MINITURE 70° DEGREE IN STEEL ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR. CASE SIZE: 310" L x .270"W x .500"H	.	.	.	.
AFS-0563	CUSTOM TRANSDUCER 5MHz 41° IN TITANIUM BACKSHOOTER, .187"x.187" ELEMENT SIDE MOUNT MICRODOT CONNECTOR WITH A 1.70" RADIUS. CASE(.550"L x .260"W x .300"H), USED WITH NDT3271.	.	.	.	.
AFS-0564	CUSTOM TRANSDUCER 5MHz 41° IN TITANIUM, .187"x.187" ELEMENT SIDE MOUNT MICRODOT CONNECTOR WITH A 1.70" RADIUS. CASE(.550"L x .260"W x .375"H), USED WITH NDT3271.	.	.	.	.
AFS-0565	CUSTOM TRANSDUCER 5MHz 25° IN TITANIUM BACKSHOOTER, .187"x.187" ELEMENT SIDE MOUNT MICRODOT CONNECTOR WITH A 1.70" RADIUS. CASE(.550"L x .260"W x .300"H),	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-0566	CUSTOM TRANSDUCER 5MHz 47" IN TITANIUM, .187"x.187" ELEMENT SIDE MOUNT MICRODOT CONNECTOR. CASE:(.550"L x .260"W x.375"H).	.	.	.	.
AFS-0567	CUSTOM TRANSDUCER 5MHz 50" IN TITANIUM, .187"x.187" ELEMENT SIDE MOUNT MICRODOT CONNECTOR. CASE:(.550"L x .260"W x.375"H).	.	.	.	.
AFS-0569	CUSTOM TRANSDUCER 5MHz 38" REFRACTED IN TITANIUM BACKSHOOTER, .187"x.187" ELEMENT SIDE MOUNT MICRODOT CONNECTOR WITH A 1.70" RADIUS. CASE:(.550"L x .260"W x.325"H), USED WITH NDT3271.	.	.	.	.
AFS-0570-1L	CUSTOM ANGLE BEAM TRANSDUCER (LEFT) FOR (.328") DIAMETER FASTENER HOLE'S (0.430") STEP OF REFERENCE STANDARD NDT815	.	.	.	.
AFS-0570-1R	CUSTOM ANGLE BEAM TRANSDUCER (RIGHT) FOR (.328") DIAMETER FASTENER HOLE'S (0.430") STEP OF REFERENCE STANDARD NDT815	.	.	.	.
AFS-0570-2L	CUSTOM ANGLE BEAM TRANSDUCER (LEFT) FOR (0.438" & 0.500") DIAMETER FASTENER HOLE'S (0.430" & 0.590") STEPS OF REFERENCE STANDARD NDT815	.	.	.	.
AFS-0570-2R	CUSTOM ANGLE BEAM TRANSDUCER (RIGHT) FOR (0.438" & 0.500") DIAMETER FASTENER HOLE'S (0.430" & 0.590") STEPS OF REFERENCE STANDARD NDT815	.	.	.	.
AFS-0570-3L	CUSTOM ANGLE BEAM TRANSDUCER (LEFT) FOR (0.642") DIAMETER FASTENER HOLE IN (0.570") STEP OF REFERENCE STANDARD NDT815	.	.	.	.
AFS-0570-3R	CUSTOM ANGLE BEAM TRANSDUCER (RIGHT) FOR (0.642") DIAMETER FASTENER HOLE IN (0.570") STEP OF REFERENCE STANDARD NDT815	.	.	.	.
AFS-0570-4L	CUSTOM ANGLE BEAM TRANSDUCER (LEFT) FOR (0.438") DIAMETER FASTENER HOLE (0.710") STEP OF REFERENCE STANDARD NDT815	.	.	.	.
AFS-0570-4R	CUSTOM ANGLE BEAM TRANSDUCER (RIGHT) FOR (0.438") DIAMETER FASTENER HOLE (0.710") STEP OF REFERENCE STANDARD NDT815	.	.	.	.
AFS-0570-5L	CUSTOM ANGLE BEAM TRANSDUCER (LEFT) FOR (0.625") DIAMETER FASTENER HOLE IN (0.850") STEP OF REFERENCE STANDARD NDT815	.	.	.	.
AFS-0570-5R	CUSTOM ANGLE BEAM TRANSDUCER (RIGHT) FOR (0.625") DIAMETER FASTENER HOLE IN (0.850") STEP OF REFERENCE STANDARD NDT815	.	.	.	.
AFS-0571-1L	Custom Angle Beam Transducer(Left) for B767 Part 4 54-50-15, 5MHz 69" in steel .150" x .187" element, .375" Radius top mount microdot connector.	.	.	.	.
AFS-0571-1R	Custom Angle Beam Transducer(Right) for B767 5MHz 69" in steel .150" x .187" element, .375" Radius top mount microdot connector.	.	.	.	.
AFS-0571-2R	Custom Angle Beam Transducer(Right) for B767 5MHz 67" in steel .150" x .187" element, .325" Radius top mount microdot connector.	.	.	.	.
AFS-0571-3R	Custom Angle Beam Transducer(Right) for B767 5MHz 63" in steel .150" x .187" element, .25" Radius top mount microdot connector.	.	.	.	.
AFS-0571-4L	Custom Angle Beam Transducer(Left) for B767 5MHz 61" in steel .150" x .187" element, .200" Radius top mount microdot connector.	.	.	.	.
AFS-0571-4R	Custom Angle Beam Transducer(Right) for B767 5MHz 61" in steel .150" x .187" element, .200" Radius top mount microdot connector.	.	.	.	.
AFS-0571-5L	Custom Angle Beam Transducer(Left) for B767 5MHz 53" in steel .150" x .187" element, .200" Radius top mount microdot connector. (Left Transducer)	.	.	.	.
AFS-0571-5R	Custom Angle Beam Transducer(Right) for B767 5MHz 53" in steel .150" x .187" element, .200" Radius top mount microdot connector. (Right Transducer)	.	.	.	.
AFS-0571-6L	Custom Angle Beam Transducer(Left) for B767 5MHz 50" in steel .150" x .187" element, .150" Radius top mount microdot connector.	.	.	.	.
AFS-0571-6R	Custom Angle Beam Transducer(Right) for B767 5MHz 50" in steel .150" x .187" element, .150" Radius top mount microdot connector.	.	.	.	.
AFS-0571-7L	Custom Angle Beam Transducer(Left) for B767 5MHz 58" in steel .150" x .187" element, .150" Radius top mount microdot connector. (Left Transducer)	.	.	.	.
AFS-0571-7R	Custom Angle Beam Transducer(right) for B767 5MHz 58" in steel .150" x .187" element, .150" Radius top mount microdot connector. (Right Transducer)	.	.	.	.
AFS-0572-1L	CUSTOM 45° IN STEEL ANGLE BEAM TRANSDUCER (LEFT) FOR (.307") DIAMETER FASTENER HOLE'S (0.340") STEP OF REFERENCE STANDARD NDT6091	.	.	.	.
AFS-0572-1R	CUSTOM 45° IN STEEL ANGLE BEAM TRANSDUCER (RIGHT) FOR (.307") DIAMETER FASTENER HOLE'S (0.340") STEP OF REFERENCE STANDARD NDT6091	.	.	.	.
AFS-0572-2L	CUSTOM 50° IN STEEL ANGLE BEAM TRANSDUCER (LEFT) FOR (.307") DIAMETER FASTENER HOLE'S (0.240") STEP OF REFERENCE STANDARD NDT6092	.	.	.	.
AFS-0572-2R	CUSTOM 50° IN STEEL ANGLE BEAM TRANSDUCER (RIGHT) FOR (.307") DIAMETER FASTENER HOLE'S (0.240") STEP OF REFERENCE STANDARD NDT6092	.	.	.	.
AFS-0572-3L	CUSTOM 60° IN STEEL ANGLE BEAM TRANSDUCER (LEFT) FOR (.307") DIAMETER FASTENER HOLE'S (0.200") STEP OF REFERENCE STANDARD NDT6092	.	.	.	.
AFS-0572-3R	CUSTOM 60° IN STEEL ANGLE BEAM TRANSDUCER (RIGHT) FOR (.307") DIAMETER FASTENER HOLE'S (0.200") STEP OF REFERENCE STANDARD NDT6092	.	.	.	.
AFS-0572-4L	CUSTOM 60° IN STEEL ANGLE BEAM TRANSDUCER (LEFT) FOR (.412") DIAMETER FASTENER HOLE'S (0.200") STEP OF REFERENCE STANDARD NDT6092	.	.	.	.
AFS-0572-4R	CUSTOM 60° IN STEEL ANGLE BEAM TRANSDUCER (RIGHT) FOR (.412") DIAMETER FASTENER HOLE'S (0.200") STEP OF REFERENCE STANDARD NDT6092	.	.	.	.
AFS-0573	CUSTOM 5MHz MINUTURE 45° IN STEEL ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR. CASE SIZE: .310"L x .270"W x .500"H	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-0574	CUSTOM 5MHz MINITURE 60° IN STEEL ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR. CASE SIZE: .310"L x .270"W x .500"H	.	.	.	.
AFS-0577-1	CUSTOM 5MHz 30° .187" X .187" BACK SHOOTING ANGLE BEAM TRANSDUCER FOR THE 767 CF6-80C2 ENGINE STRUTS. USED WITH REFERENCE STANDARD 767 NDT674 54-50-06 PART 4 FIGURE 3	SUS 674-T1	.	.	.
AFS-0577-2	CUSTOM 5MHz, 25° .187" X .187" BACK SHOOTING ANGLE BEAM TRANSDUCER FOR THE 767 CF6-80A/A2 ENGINE STRUTS. USED WITH REFERENCE STANDARD 767 NDT674 54-50-06 PART 4 FIGURE 3	SUS 674-T2	.	.	.
AFS-0735ST	Shear waveTransducer 35° in Steel 5MHz 187"x.187" Element with Top Mounted Microdot Connector. CASE SIZE: .375"L x .500"H x .260"W.	.	.	.	.
AFS-0745ST	Shear waveTransducer 45° in Steel 5MHz 187"x.187" Element with Top Mounted Microdot Connector. CASE SIZE: .375"L x .500"H x .260"W.	.	.	.	.
AFS-0760ST	Shear waveTransducer 60° in Steel 5MHz 187"x.187" Element with Top Mounted Microdot Connector. CASE SIZE: .375"L x .500"H x .260"W.	.	.	.	.
AFS-1000B	ULTRASONIC TRANSDUCER 10MHZ .100X.250 ELEMENT, USED WITH NDT1086-P2	TEK-5000	TEK-5000	XAB-6087	.
AFS-1002-41FE	SHEARWAVE TRANSDUCER, 5MHz, 35 DEGREES SIDE CONNECTOR WITH.1.614"(41MM) RADIUS	TEK-5002-41M	.	.	.
AFS-1002-48FE	SHEARWAVE TRANSDUCER, 5MHz, 35 DEGREES SIDE CONNECTOR WITH.1.890"(48MM) RADIUS	TEK-5002-48M	412A5MHZ35R48FE	.	.
AFS-1012	CUSTOM 10MHZ, 73° SHEAR WAVE TRANSDUCER. BOEING 727 UT INSPECTION FOR 57-10-27.	TEK-5045-73	1073AT	.	.
AFS-1013	SEARCH UNITS 57-21-30 PT 4 FIG 404	TEK-5042S-45	545484	.	.
AFS-1014	SEARCH UNITS 57-21-30 PT 4 FIG 404	TEK-5042-45	54580	.	.
AFS-1015	10MHZ 70° IN ALUMINUM, TOP MOUNT CONNECTOR MAX LENGTH .315" BOEING 737 PART 4. 52-10-02	SUS 1015-10MHZ-70A	SUS 1015	HS7520-10-70A	.
AFS-1020	TWO ELEMENT & SHOW TRANSDUCER WITH SWITCH	TEK-5047	SUS-944	.	.
AFS-1023	SHEARWAVE TRANSDUCER 45 deg. in Al (SS case .433"H x .433"L x .236"W) .connector mounted on bottom(side mount).part 4 57-26-08 fig. 402	TEK-5068-45	.	.	.
AFS-1032SS	Sub Miniature Integral Angle Beam Transducers, Standard Series, 5 MHz, 0.120 in. x 0.250 in.; 45 degree shearwave in Steel, Side Microdot Connector.	HS-225-5-45-ST-RM	.	.	.
AFS-1033SS	Sub Miniature Integral Angle Beam Transducers, Standard Series, 5 MHz, 0.120 in. x 0.250 in.; 60 degree shearwave in Steel, Side Microdot Connector.	HS-225-5-60ST-RM	.	.	.
AFS-1034SS	Sub Miniature Integral Angle Beam Transducers, Standard Series, 5 MHz, 0.120 in. x 0.250 in.; 70 degree shearwave in Steel, Side Microdot Connector.	HS-225-5-70-ST-RM	.	.	.
AFS-1036	CUSTOM 5MHz 45° SHEAR WAVE TRANSDUCER (TEK-5086) .BOEING 767 UT INSPECTION FOR 57-20-04.	TEK-5086	.	.	.
AFS-1045AS	SMALL 10 MHz 45° SIDE MOUNT TRANSDUCER .187"x.187" ELEMENT ,CASE SIZE(.26"Wx.55"Lx.45"H)	SA-4510S	SUSM 1045AS	.	.
AFS-1045AT	SMALL 10 MHz 45° TOP MOUNT TRANSDUCER .187"x.187" ELEMENT ,CASE SIZE(.26"Wx.55"Lx.45"H)	SA-4510T	SUSM 1045AT	.	.
AFS-1045ST	45° in STEEL 10MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	.	.	.	.
AFS-1058	5MHz 35 degree ANGLE BEAM TRANSDUCER	TEK-5056/35	.	.	.
AFS-1059	5MHz 40 degree ANGLE BEAM TRANSDUCER	TEK-5056/40	.	.	.
AFS-1060	5MHz 45 degree ANGLE BEAM TRANSDUCER	TEK-5056/45	.	.	.
AFS-1060AS	SMALL 10 MHz 60° SIDE MOUNT TRANSDUCER .187"x.187" ELEMENT ,CASE SIZE(.26"Wx.55"Lx.45"H)	SA-6010S	SUSM 1060AS	.	.
AFS-1060AT	SMALL 10 MHz 60° TOP MOUNT TRANSDUCER .187"x.187" ELEMENT ,CASE SIZE(.26"Wx.55"Lx.45"H)	SA-6010T	SUSM 1060AT	.	.
AFS-1060ST	60° in STEEL 10MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	.	.	.	.
AFS-1061	5MHz 50 degree ANGLE BEAM TRANSDUCER	TEK-5056/50	.	.	.
AFS-1062	5MHz 55 degree ANGLE BEAM TRANSDUCER	TEK-5056/55	.	.	.
AFS-1063	5MHz 60 degree ANGLE BEAM TRANSDUCER	TEK-5056/60	.	.	.
AFS-1064	5MHz 65 degree ANGLE BEAM TRANSDUCER	TEK-5056/65	.	.	.
AFS-1070AS	SMALL 10 MHz 70° SIDE MOUNT TRANSDUCER .187"x.187" ELEMENT ,CASE SIZE(.26"Wx.55"Lx.45"H)	SA-7010S	SUSM 1070AS	.	.
AFS-1070ST	70° in STEEL 10MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-1077L	CUSTOM ANGLE BEAM TRANSDUCER (LEFT FACING) FOR AIRBUS 57-52-50 PG.403, FIG.402	545042	TEK-5020L	0545042	
AFS-1077R	CUSTOM ANGLE BEAM TRANSDUCER (RIGHT FACING) FOR AIRBUS 57-52-50 PG.403, FIG.402	545041	TEK-5020R	0545041	
AFS-1078-1L	31 DEGREE 5MHz LEFT SCANNING POTTED ANGLE BEAM TRANSDUCER MOUNTED IN A CUSTOM HOUSING 187" DIA ELEMENT TOP MOUNT MICRODOT CONNECTOR. BOEING 777 PART 4. 57-10-04	TEK-5128-1L	.	.	.
AFS-1078-1R	31 DEGREE 5MHz POTTED RIGHT SCANNING ANGLE BEAM TRANSDUCER MOUNTED IN A CUSTOM HOUSING 187" DIA ELEMENT TOP MOUNT MICRODOT CONNECTOR. BOEING 777 PART 4. 57-10-04	TEK-5128-1R	.	.	.
AFS-1078-2L	27 DEGREE 5MHz POTTED LEFT SCANNING ANGLE BEAM TRANSDUCER MOUNTED IN A CUSTOM HOUSING 187" DIA ELEMENT TOP MOUNT MICRODOT CONNECTOR. BOEING 777 PART 4. 57-10-04	TEK-5128-2L	.	.	.
AFS-1078-2R	27 DEGREE 5 MHz POTTED RIGHT SCANNING ANGLE BEAM TRANSDUCER MOUNTED IN A CUSTOM HOUSING 187" DIA ELEMENT TOP MOUNT MICRODOT CONNECTOR. BOEING 777 PART 4. 57-10-04	TEK-5128-2R	.	.	.
AFS-1084B-50M	CUSTOM 5MHz TRANSDUCER WITH A 50mm RADIUS(1.969") AIRBUS 54-40-00, 54-50-23 (BACKSHOOTER)	TEK-5003B-50M	535TS-50R		
AFS-1084B-58M	CUSTOM 5MHz TRANSDUCER WITH A 58mm RADIUS(2.283") AIRBUS 54-40-00, 54-50-23, (BACKSHOOTER)	TEK-5003B-58M	545TS-58R		
AFS-1084B-80M	CUSTOM 5MHz TRANSDUCER WITH A 80mm RADIUS(1.969") AIRBUS 54-40-00, 54-50-23, (BACKSHOOTER)	TEK-5003B-80M	545TS-80R		
AFS-1084F-50M	CUSTOM 5MHz TRANSDUCER WITH A 50mm RADIUS(1.969") AIRBUS 54-40-00, 54-50-23, (FORWARD SOUND PATH)	TEK-5003-50M	535TS-50R		
AFS-1084F-58M	CUSTOM 5MHz TRANSDUCER WITH A 58mm RADIUS(2.283") AIRBUS 54-40-00, 54-50-23, (FORWARD SOUND PATH)	TEK-5003-58M	545TS-58R		
AFS-1084F-80M	CUSTOM 5MHz TRANSDUCER WITH A 80mm RADIUS(3.145") AIRBUS 54-40-00, 54-50-23, (FORWARD SOUND PATH)	TEK-5003-80M	545TS-80R		
AFS-1090	CUSTOM ANGLE BEAM TRANSDUCER 5MHz WITH A 1.260" RADIUS. USED WITH NDT3144 and NDT3145. Boeing NTM 55-10-16 PT4	TEK-5162	.	.	.
AFS-1091	CUSTOM ANGLE BEAM TRANSDUCER 5MHz WITH A 1.30"RADIUS. USED WITH NDT3146. Boeing NTM 55-10-16 PT4	TEK-5163	.	.	.
AFS-1095	5 MHz SHEARWAVE WITH 2.087"RADIUS USED WITH 99D54403005000 HOLDER SUB PART TRANSDUCER(F01200140)	F01200140	TEK-5001-53M	F01200140	
AFS-1110-70	CUSTOM 70 DEGREE 5MHz ANGLE BEAM TRANSDUCER. TOP MOUNT MICRODOT CONNECTOR. BBOEING 777 PART 4. 57-20-03	TEK-5110-70	.	.	.
AFS-1150	CUSTOM 5 MHz SHEAR WAVE TRANSDUCER WITH A 1.40" RADIUS.	TEK-59024	.	.	.
AFS-1151	CUSTOM 5 MHz SHEAR WAVE TRANSDUCER WITH A 1.57" RADIUS.	TEK-59025	.	.	.
AFS-1160	Sub Miniature Integral Angle Beam Transducers, Standard Series, 5 MHz, 0.120 in. x 0.250 in.; 45 degree shearwave in Aluminum, Right Angle Microdot Connector.	HS-225-5-45-AL-RM	U8503124	.	.
AFS-1161	Sub Miniature Integral Angle Beam Transducers, Standard Series, 5 MHz, 0.120 in. x 0.250 in.; 60 degree shearwave in Aluminum, Right Angle Microdot Connector.	HS-225-5-60-AL-RM	U8503053	.	.
AFS-1163	CUSTOM 5MHz LOW PROFILE TRANSDUCER USED FOR NOTCH'S "A" and "B" ON NDT4116	SPO-1883	.	.	.
AFS-1164	CUSTOM 5MHz LOW PROFILE TRANSDUCER USED FOR NOTCH "C" ON NDT4116	SPO-1884	.	.	.
AFS-1165	70° SHEARWAVE 5MHz .187"x.187" ELEMENT .670L X .26W X.33H	.	.	.	.
AFS-1167	CUSTOM 767 STRAIGHT BEAM PANCAKE TRANSDUCER BOEING 57-10-19	TEK-5016	SPO-6148		
AFS-1169	5MHz ANGLE BEAM TRANSDUCER WITH A RADIUS of 2.4" USED NDT6002	TEK-5024	.	.	.
AFS-1170	CUSTOM STRAIGHT BEAM PANCAKE TRANSDUCER WITH HANDLE	TEK-5027	.	.	.
AFS-1175	70 deg. ANGLE BEAM TRANSDUCER in ALUMINUM, .187" x .187" ELEMENT. CASE SIZE: .67"L x .26"W x .33"H.	389-021-980	389-021-980		
AFS-1176-1	CUSTOM 5MHz ANGLE BEAM TRANSDUCER WITH a RADIUS of 2.5" USED NDT6035-1. SIDE MOUNT CONNECTOR.	TEK-5048-1	.	.	.
AFS-1176-2	CUSTOM 5MHz ANGLE BEAM TRANSDUCER WITH a RADIUS of 2.22" USED NDT6035-2. SIDE MOUNT. CONNECTOR	TEK-5048-2	.	.	.
AFS-1177	CUSTOM 5 MHz ANGLE BEAM TRANSDUCER 35° degrees in ALUMINUM WITH END MOUNTED MICRODOT CONNECTOR. USED WITH NDT6034.	TEK-5079	.	.	.
AFS-1183	CUSTOM 5 MHz ANGLE BEAM TRANSDUCER 45° degrees in ALUMINUM, WITH END MOUNTED MICRODOT CONNECTOR. USED WITH NDT6034	TEK-5080	.	.	.
AFS-1185	CUSTOM 5MHz RADIUS TRANSDUCER SIED MOUNT CONNECTOR FOR	TEK-5037-14	.	.	.
AFS-1190	SEARCH UNIT 45°, 10MHZ SHEARWAVE, TOP MOUNT CONNECTOR	0545480	.	.	.
AFS-1192	CUSTOM 5MHz 35° TRANSDUCER IN TITANIUM WITH TOP MOUNT MICRODOT CONNECTOR USED WITH WITH NDT6011P & NDT6011	TEK-5046-2	.	.	.

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-1193	CUSTOM 5MHz 59° TRANSDUCER IN TITANIUM WITH TOP MOUNT MICRODOT CONNECTOR USED WITH WITH NDT6011P & NDT6011	TEK-5046-1	.	.	.
AFS-1200	CUSTOM 767 ANGLE BEAM TRANSDUCER	TEK-5057	.	.	.
AFS-1201	RADIUS TRANSDUCER	TEK-5060	.	.	.
AFS-1203	CUSTOM AIRBUS SEARCH UNIT 5MHz 40 DEGREES IN ALUMINUM TOP MOUNT MICRODOT CONNECTOR WITH Q 34mm (1.339") RADIUS. USED WITH P/N: 99A57004001291, A300-600 57-53-05 PAGE 404 FIGURE 402	545124	.	.	.
AFS-1204	RADIUS TRANSDUCER	TEK-5064	.	.	.
AFS-1205	RADIUS TRANSDUCER	TEK-5065	.	.	.
AFS-1206	60 DEGREE SHEARWAVE TRANSDUCER..SS case .433"H x .433"L x .236"W) ..connector mounted on bottom(side mount)..	TEK-5068-60	.	.	.
AFS-1207	70 DEGREE SHEARWAVE TRANSDUCER..SS case .433"H x .433"L x .236"W) ..connector mounted on bottom(side mount)..	TEK-5068-70	.	.	.
AFS-1208	DOUGLAS DC-10 WING PYLON 45 DEGREE TRANSDUCER WITH A 2.19" RADIUS, .25" x .25" ELEMENT TOP MOUNT MICRODOT CONNECTOR. , 54-10-11 PAGE 635 FIG.603 SHEET 23	.	.	.	.
AFS-1217	CUSTOM 5MHz L-WAVE TRANSDUCER WITH A RADIUS OF 2.5" WITH END MOUNTED MICRODOT CONNECTOR. USED WITH NDT6033-1	TEK-5078-1	.	.	.
AFS-1218	CUSTOM 5MHz L-WAVE TRANSDUCER WITH A RADIUS OF 2.0" WITH END MOUNTED MICRODOT CONNECTOR USED WITH NDT6033-2	TEK-5078-2	.	.	.
AFS-1223	5MHZ 38° ANGLE BEAM TRANSDUCER IN STEEL, MAX HEIGHT OF .400" W/ 1.830" RADIUS	SPO-6223	.	.	.
AFS-1224	5MHZ 38° ANGLE BEAM TRANSDUCER IN STEEL, MAX HEIGHT OF .400" W/ 1.880" RADIUS	SPO-6224	.	.	.
AFS-1225S	Sub Miniature Integral Angle Beam Transducers, Standard Series, 5 MHz, 0.120 in. x 0.250 in.; 60 degree shearwave in Aluminum, Right Angle Microdot Connector.	HS-225-5-60-AL-RM	HS225-5-60	.	.
AFS-1225T	Sub Miniature Integral Angle Beam Transducers, Standard Series, 5 MHz, 0.120 in. x 0.250 in.; 60 degree shearwave in Aluminum, Top Microdot Connector. Case Size: .375"L x .425"H x .325"W	HS225-5-60	HS-225-5-60	HS-225-5-60-AL-SM	.
AFS-1239	EXTRA SMALL 70 DEGREE SHEAR WAVE TRANSDUCER IN ALUMINUM. .5MHz (.130" x .187") ELEMENT..CASE SIZE(.32"L x .42"H x .24"W)	XW570AT	.	.	.
AFS-1267	GE Angle Beam Transducer 5MHz 45°, Ø 5mm (.187") Case Size: 12,5mm x 9,5mm x 15,5mm. Top Mounted Microdot Connector	0508941,WK45 5S	.	.	.
AFS-1272S	Angle Beam Transducer, 5 MHz, 0.25 in. x 0.25 in. Element Size, Integral Case Style, 60 Degree Shear in Steel, Right Microdot Connector.	A572S-RM, U8431046	A572SRM	.	.
AFS-1272T	Angle Beam Transducer, 5 MHz, 0.25 in. x 0.25 in. Element Size, Integral Case Style, 60 Degree Shear in Steel, Top Microdot Connector.	A572S-SM	.	.	.
AFS-1284	70 DEGREE ANGLE BEAM TRANSDUCER 5MHz, CASE SIZE(.375"x.350"x.500") TOP MOUNT CONNECTOR.	TEK-5560T/70A	.	.	.
AFS-1287	60 DEGREE ANGLE BEAM TRANSDUCER 5MHz, CASE SIZE(.375"x.26"x.75")	TEK-5554T/60A	.	.	.
AFS-1288	70 DEGREE ANGLE BEAM TRANSDUCER 5MHz, CASE SIZE(.375"x.26"x.75")	TEK-5555T/70A	.	.	.
AFS-1300-1	CUSTOM 767 ANGLE BEAM TRANSDUCER 767Part 4 57-50-02 Pages 1-10	TEK-5017-1	.	.	.
AFS-1300-2	CUSTOM 767 ANGLE BEAM TRANSDUCER 767Part 4 57-50-02 Pages 1-10	TEK-5017-2	.	.	.
AFS-1300-3	CUSTOM 767 ANGLE BEAM TRANSDUCER 767Part 4 57-50-02 Pages 1-10	TEK-5017-3	.	.	.
AFS-1300-4	CUSTOM 767 ANGLE BEAM TRANSDUCER 767Part 4 57-50-02 Pages 1-10	TEK-5017-4	.	.	.
AFS-1300-5	CUSTOM 767 ANGLE BEAM TRANSDUCER 767Part 4 57-50-02 Pages 1-10	TEK-5017-5	.	.	.
AFS-1300-6	CUSTOM 767 ANGLE BEAM TRANSDUCER 767Part 4 57-50-02 Pages 1-10	TEK-5017-6	.	.	.
AFS-1300-7	CUSTOM 767 ANGLE BEAM TRANSDUCER 767Part 4 57-50-02 Pages 1-10	TEK-5017-7	.	.	.
AFS-1300-8	CUSTOM 767 ANGLE BEAM TRANSDUCER 767Part 4 57-50-02 Pages 1-10	TEK-5017-8	.	.	.
AFS-1300-9	CUSTOM 767 ANGLE BEAM TRANSDUCER 767Part 4 57-50-02 Pages 1-10	TEK-5017-9	.	.	.
AFS-1300-A	TRANSDUCER POSITIONER 767Part 4 57-50-02 Pages 1-10	TEK-5017-A	.	.	.
AFS-1300-B	TRANSDUCER POSITIONER 767Part 4 57-50-02 Pages 1-10..	TEK-5017-B	.	.	.
AFS-1300-C	TRANSDUCER POSITIONER 767Part 4 57-50-02 Pages 1-10	TEK-5017-C	.	.	.



September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-1300-D	TRANSDUCER POSITIONER (ALUMINUM) FOR THE TEK-5017 SERIES TRANSDUCERS. 767Part 4 57-50-02 Pages 1-10	TEK-5017-D	.	.	.
AFS-1300-E	TRANSDUCER POSITIONER 767Part 4 57-50-02 Pages 1-10	TEK-5017-E	.	.	.
AFS-1301-1P	TRANSDUCER POSITIONER	TEK-5008-1P	.	.	.
AFS-1301-2P	TRANSDUCER POSITIONER	TEK-5008-2P	.	.	.
AFS-1302	CUSTOM LOW PROFILE 7.5MHz ANGLE BEAM TRANSDUCER WITH HANDLE. USED TO INSPECT THE CHORD DOUBLER AT THE HINGE BEAM TO LATCH BEAM END FOR THE B777 AIRCRAFT.	TEK-5572	.	.	.
AFS-1302L	CUSTOM LOW PROFILE 7.5MHz ANGLE BEAM TRANSDUCER WITH AN ANGLED HANDLE. USED TO INSPECT THE FIRST 3.5 inches of the HINGE BEAM END FOR THE B777 AIRCRAFT. LEFT SIDE SCANNING	TEK-5572L	.	.	.
AFS-1302R	CUSTOM LOW PROFILE 7.5MHz ANGLE BEAM TRANSDUCER WITH AN ANGLED HANDLE. USED TO INSPECT THE FIRST 3.5 inches of the HINGE BEAM END FOR THE B777 AIRCRAFT. RIGHT SIDE SCANNING	TEK-5572R	.	.	.
AFS-1304	5MHz SHEAR WAVE TRANSDUCER WITH A 35.6mm RADIUS and 39 DEG. INCIDENT ANGLE WITH SIDE MOUNT MICRODOT CONNECTOR. USED WITH RS-502 & RS-502-C.	NA	.	.	.
AFS-1308S	CUSTOM 45° IN STEEL SEARCH UNIT, 5MHz .25" ELEMENT. CASE SIZE: .790" L x .360" W x .500" H. USED WITH 99F57204104001	WK45-5S	.	.	.
AFS-1316	8MHZ 50° SHEARWAVE TRANSDUCER IN ALUMINUM	.	CEP13	.	.
AFS-1326L-I	CUSTOM 45 DEGREE IN ALUMINUM 5MHz (LEFT -INBOARD) TRANSDUCER WITH YOKE USED WITH NDT768	TEK-5510L-I	.	.	.
AFS-1326L-O	CUSTOM 65 DEGREE IN ALUMINUM 5MHz (LEFT -OUTBOARD) TRANSDUCER WITH YOKE USED WITH NDT768	TEK-5510L-O	.	.	.
AFS-1326R-I	CUSTOM 45 DEGREE IN ALUMINUM 5MHz (RIGHT -INBOARD) TRANSDUCER WITH YOKE USED WITH NDT769	TEK-5510R-I	.	.	.
AFS-1326R-O	CUSTOM 65 DEGREE IN ALUMINUM 5MHz (RIGHT -OUTBOARD) TRANSDUCER WITH YOKE USED WITH NDT769	TEK-5510R-O	.	.	.
AFS-1327L-I	CUSTOM 45 DEGREE IN ALUMINUM 5MHz (LEFT -INBOARD) TRANSDUCER WITH YOKE USED WITH NDT771	TEK-5127L-I	.	.	.
AFS-1327L-O	CUSTOM 45 DEGREE IN ALUMINUM 5MHz (LEFT -OUTBOARD) TRANSDUCER WITH YOKE USED WITH NDT771	TEL-5127L-O	.	.	.
AFS-1327R-I	CUSTOM 45 DEGREE IN ALUMINUM 5MHz (RIGHT -INBOARD) TRANSDUCER WITH YOKE USED WITH NDT774	TEK-5127R-I	.	.	.
AFS-1327R-O	CUSTOM 45 DEGREE IN ALUMINUM 5MHz (RIGHT -OUTBOARD) TRANSDUCER WITH YOKE USED WITH NDT774	TEK-5127R-O	.	.	.
AFS-1335	45° TRANSDUCER, STEEL, TOP MOUNT, .25"X.25" ELEMENT, CASE = .500"HX.400"WX.750"L	WK-45-5A	.	.	.
AFS-1343	SEARCH UNIT 50°, 5MHZ SHEARWAVE	0545011	.	.	.
AFS-1344	SEARCH UNIT 55°, 5MHZ SHEARWAVE .250"x.190" element... Case size: (.47" L x .65" H x .33" W)	0545012	0545012	.	.
AFS-1346	CUSTOM 2 ELEMENT RING TRANSDUCER FOR BORE HOLE INSPECTION WITH BOEING REFERENCE STANDARD 55-10-13 PAGE 9 FIGURE 2. TWO MICRODOT CONNECTORS "A" and "B"	TEK-5154	.	.	.
AFS-1346-SC	SEALANT SCRAPER FOR USE WITH AFK-1005.	TEK-5154-SC	.	.	.
AFS-1347	CASA C-212 12" L-WAVE 5MHZ 1.0 RADIUS	.	.	.	.
AFS-1348	SEARCH UNIT 65°, 5MHZ SHEARWAVE... Case size (.35"W x .47"L x .63"H) Top mount connector.	0545014	.	.	.
AFS-1350	MINI ANGLE BEAM TRANSDUCER, 10MHz 45° IN ALUMINUM WITH TOP MOUNT MICRODOT CONNECTOR, .130" x .187" ELEMENT, CASE SIZE: .325" L x .360" H x .250" W	HS-877-45-10-AL-SM	.	.	.
AFS-1351	MINI ANGLE BEAM TRANSDUCER, 10MHz 45° IN ALUMINUM WITH SIDE MOUNT MICRODOT CONNECTOR, .130" x .187" ELEMENT, CASE SIZE: .325" L x .360" H x .250" W	HS-877-45-10-AL-RM	.	.	.
AFS-1352	MINI ANGLE BEAM TRANSDUCER, 10MHz 60° IN ALUMINUM WITH TOP MOUNT MICRODOT CONNECTOR, .130" x .187" ELEMENT, CASE SIZE: .325" L x .360" H x .250" W	HS-877-60-10-AL-SM	.	.	.
AFS-1353	MINI ANGLE BEAM TRANSDUCER, 10MHz 60° IN ALUMINUM WITH SIDE MOUNT MICRODOT CONNECTOR, .130" x .187" ELEMENT, CASE SIZE: .325" L x .360" H x .250" W	HS-877-60-10-AL-RM	.	.	.
AFS-1366	10MHZ 70° SHEAR WAVE TRANSDUCER	PT.26	.	.	.
AFS-1367	5MHZ 75° SHEARWAVE TRANSDUCER AL	AL-945180	.	.	.
AFS-1368	5 MHz, 45 degree shear wave transducer (in aluminum) with top-mounted microdot connector. Case size: 0.5 inch (13 mm) long, 0.35 inch (8.9 mm) wide, and 0.5 inch (13 mm) high.	AP-HP-3/16	.	.	.
AFS-1369	5MHZ 70° SHEARWAVE TRANSDUCER	PAB 0503 70°AL	.	.	.
AFS-1370	5MHZ 40° SHEARWAVE AL TRANSDUCER .187"X.187" ELEMENT CASE SIZE = (.55LX.26WX.350H) SIDE MOUNT CONNECTOR	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-1372	412ASMHZ35AL TRANSVERSE WAVE FROM GELELEC SA (REFER TO CHAPTER 51-42-01 PABE BLOCK 401)	.	.	.	.
AFS-1373	412ASMHZ40AL TRANSVERSE WAVE FROM GELELEC SA (REFER TO CHAPTER 51-42-01 PABE BLOCK 401)	.	.	.	.
AFS-1374	412ASMHZ45AL TRANSVERSE WAVE FROM GELELEC SA (REFER TO CHAPTER 51-42-01 PABE BLOCK 401)	.	.	.	.
AFS-1375	412ASMHZ30AL 30° TRANSVERSE WAVE FROM GELELEC SA (REFER TO CHAPTER 51-42-01 PAGE BLOCK 401). CASE SIZE: .75" LONG x .340" WIDE x 500" HIGH.	412ASMHZ30AL	.	.	.
AFS-1376	5MHZ SHEARWAVE TRANSDUCER, END MOUNT CONNECTOR, AL, CASE DIMS ARE .067"L X .026"WX.033"H	.	.	.	.
AFS-1378	412ASMHZ65AL TRANSVERSE WAVE FROM GELELEC SA (REFER TO CHAPTER 51-42-01 PABE BLOCK 401)	.	.	.	.
AFS-1379	412ASMHZ70AL TRANSVERSE WAVE FROM GELELEC SA (REFER TO CHAPTER 51-42-01 PABE BLOCK 401)	.	.	.	.
AFS-1380	412ASMHZ60AL TRANSVERSE WAVE FROM GELELEC SA (REFER TO CHAPTER 51-42-01 PABE BLOCK 401)	.	.	.	.
AFS-1381	412ASMHZ55AL TRANSVERSE WAVE FROM GELELEC SA (REFER TO CHAPTER 51-42-01 PABE BLOCK 401)	.	.	.	.
AFS-1382	412ASMHZ50AL TRANSVERSE WAVE FROM GELELEC SA (REFER TO CHAPTER 51-42-01 PABE BLOCK 401)	.	.	.	.
AFS-1385	NDT SYSTEMS MD-11 45° REFRACTED SHEAR WAVE SEARCH UNIT , 5" HANDLE, FIGURE 2, SECTION 2-5 FIGURE 5.3	E058814	E058814	.	.
AFS-1386	NDT SYSTEMS, MD-11 60° REFRACTED SHEAR WAVE SEARCH UNIT WITH A 5" HANDLE FIGURE 5, SECTION 2-5 FIGURE 5.4	AE02408	.	.	.
AFS-1388	60° ALUMINUM 5 MHZ 1/4" X 1/4", TOP MOUNT	.	.	.	.
AFS-1389	CUSTOM 45° IN STEEL 5 MHZ .25" X .25" SIDE MOUNT TRANSDUCER USED WITH 4028P (MAX HEIGHT .400") CASE SIZE: (.800"L x .300"W x .400"H)	291-424-600	8/45/5S BPS	.	.
AFS-139270RM	CUSTOM 70 DEGREE IN ALUMINUM SHEARWAVE TRANSDUCER, 3.5MHZ PIEZOCOMPOSITE ELEMENT. SIDE MOUNTED MICRODOT CONNECTOR CASE SIZE: .25" L x .325" W x .500" H, 1/4" ELEMENT	.	.	.	.
AFS-139270SM	CUSTOM 70 DEGREE IN ALUMINUM SHEARWAVE TRANSDUCER, 3.5MHZ PIEZOCOMPOSITE ELEMENT. TOP MOUNTED MICRODOT CONNECTOR CASE SIZE: .25" L x .325" W x .500" H, 1/4" ELEMENT	.	.	.	.
AFS-1392-T1	CUSTOM TRANSDUCER 5MHz 30° in ALUMINUM, .187" x .187" ELEMENT CASE SIZE: .900" L x .400" W x .950" H. BOEING 767 PT 4 54-50-07	SUS676-T1	.	.	.
AFS-1392-T2	CUSTOM TRANSDUCER 5MHz 30° in ALUMINUM, .187" x .187" ELEMENT CASE SIZE: .900" L x .400" W x .950" H. BOEING 767 PT 4 54-50-07	SUS676-T2	.	.	.
AFS-139370RM	CUSTOM 70 DEGREE IN ALUMINUM SHEARWAVE TRANSDUCER, 2.25MHZ PIEZOCOMPOSITE ELEMENT. SIDE MOUNTED MICRODOT CONNECTOR CASE SIZE: .75" L x .500" W x .625" H, 3/8" ELEMENT	.	.	.	.
AFS-139370SM	CUSTOM 70 DEGREE IN ALUMINUM SHEARWAVE TRANSDUCER, 2.25MHZ PIEZOCOMPOSITE ELEMENT. TOP MOUNTED MICRODOT CONNECTOR CASE SIZE: .75" L x .500" W x .625" H, 3/8" ELEMENT	.	.	.	.
AFS-250ST	50° in STEEL 2.25MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	.	.	.	.
AFS-270ST	70° in STEEL 2.25MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	.	.	.	.
AFS-502	SPECIAL RING TRANSDUCER USED ON 787-9-HS-9, NOTCH "C" & 787-9-HS-2 NOTCH "A"	.	.	.	.
AFS-5023T	70° IN ALUMINUM 5MHZ .120" x .187", TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH MICRODOT CONNECTOR. CASE SIZE: .375"L x .400"H x .270"W	.	.	.	.
AFS-502G	DELRIN GUIDE FOR AFS-502	.	.	.	.
AFS-5032-1	CUSTOM LOW PROFILE 5MHz SHEAR WAVE TRANSDUCER 35° IN ALUMINUM WITH A SIDE MOUNTED MICRODOT CONNECTOR.	TEK-5032-1	.	.	.
AFS-5032-2	CUSTOM LOW PROFILE 5MHz SHEAR WAVE TRANSDUCER 35° IN ALUMINUM 2.60" RADIUS WITH A SIDE MOUNTED MICRODOT CONNECTOR.	TEK-5032-2	.	.	.
AFS-5032-3	CUSTOM LOW PROFILE 5MHz SHEAR WAVE TRANSDUCER 35° IN ALUMINUM 2.75" RADIUS WITH A SIDE MOUNTED MICRODOT CONNECTOR.	TEK-5032-3	.	.	.
AFS-5032-4	CUSTOM LOW PROFILE 5MHz SHEAR WAVE TRANSDUCER 35° IN ALUMINUM 2.75" RADIUS (RIGHT) WITH A SIDE MOUNTED MICRODOT CONNECTOR.	TEK-5032-4	.	.	.
AFS-5032-5	CUSTOM LOW PROFILE 5MHz SHEAR WAVE TRANSDUCER 35° IN ALUMINUM (LEFT) WITH A SIDE MOUNTED MICRODOT CONNECTOR.	TEK-5032-5	.	.	.
AFS-5032-6	CUSTOM LOW PROFILE 5MHz SHEAR WAVE TRANSDUCER 35° IN ALUMINUM 2.75" RADIUS (LEFT) WITH A SIDE MOUNTED MICRODOT CONNECTOR.	TEK-5032-6	.	.	.
AFS-5032-7	CUSTOM LOW PROFILE 5MHz SHEAR WAVE TRANSDUCER 35° IN ALUMINUM (RIGHT) WITH A SIDE MOUNTED MICRODOT CONNECTOR.	TEK-5032-7	.	.	.
AFS-5129-T1	BOEING CUSTOM 5MHz TRANSDUCER WITH RADIUS 1.0" LONG TAPERED FOR CLEARANCE.	TEK-5129-T1	.	.	.
AFS-5129-T2	CUSTOM BOEING TRANSDUCER 5 MHz W/ TAPER FROM FRONT TO BACK FOR CLEARANCE WITH END MOUNT MICRODOT CONNECTOR.	TEK-5129-T2	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS-540AS	SMALL 40° ANGLE BEAM TRANSDUCER in ALUMINUM, 5MHz .187" x .160" ELEMENT, CASE SIZE (.550"L x .26"W x .450"H) SIDE MOUNT MICRODOT CONNECTOR...Used for Messier-Dowty service bulletin No. 146-32-174	.	.	.	.
AFS-545AS	SMALL 45° ANGLE BEAM TRANSDUCER in ALUMINUM, 5MHz .187" x .187" ELEMENT, CASE SIZE (.550" x .26" x .450") SIDE MOUNT MICRODOT CONNECTOR	SA-4555	SUSM-545AS	.	.
AFS-545AS-R37M	SMALL 45° ANGLE BEAM TRANSDUCER in ALUMINUM, 5MHz .187" x .187" ELEMENT, CASE SIZE (.50" x .26" x .450") SIDE MOUNT MICRODOT CONNECTOR WITH 37mm(1.457") RADIUS.	SA-4555-R37MM	.	.	.
AFS-545AT	45° in ALUMINUM 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	SA-455T	SUSM-545AT	.	.
AFS-545SS	45° in STEEL 5MHz TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	SS-4555	SUSM-545SS	.	.
AFS-545ST	45° in STEEL 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	SS-455T	SUSM-545ST	.	.
AFS-550ST	50° in STEEL 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	.	.	.	.
AFS-550TTI	50° in TITANIUM 5MHz TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W. NOTE: SOUND EXIT POINT .350" FROM THE FRONT OF TRANSDUCER.	.	.	.	.
AFS-557TTI	57° in TITANIUM 5MHz TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W. NOTE: SOUND EXIT POINT .350" FROM THE FRONT OF TRANSDUCER.	.	.	.	.
AFS-560AT-1	60° in ALUMINUM 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W (.400" MAX HEIGHT)	SUSM 560AT-1	SA-605T-1	.	.
AFS-560SS	60° in STEEL 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	389-021-970	SUSM-560SS	.	.
AFS-560ST	60° in STEEL 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	SS-605T	SUSM-560ST	.	.
AFS-570AS-1	70° in ALUMINUM 5MHz TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W (.400" MAX HEIGHT)	SUSM 570AS-1	.	.	.
AFS-570SS	SMALL 70° SIDE MOUNT TRANSDUCER STEEL	SS-70555	SUSM-570SS	.	.
AFS-570ST	70° in STEEL 5MHz TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	SS-705T	SUSM-570ST	.	.
AFS-575AS	75° in ALUMINUM 5MHz TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .55"L x .45"H x .26"W	SUSM 575AS	SUSM 575AS	.	.
AFS-5825	Custom 5MHz 22° shear wave transducer .375" element. 1.90"(51mm) radius. Case Size: .75"L x .50"W x .25"H. Used with reference standard NDT3195.	TEK-5825	.	.	.
AFS-5826	Custpm 5MHz 31° shear wave transducer .375" element. 2.0"(51mm) radius. Case Size: .75"L x .50"W x .25"H end mounted microdot connector. Used with reference standard NDT3196.	TEK-5826	.	.	.
AFS-5827	Custpm 5MHz 33° shear wave transducer .375" element. 2.0"(51mm) radius. Case Size: .75"L x .50"W x .25"H end mounted microdot connector. Used with reference standard NDT3197.	TEK-5827	.	.	.
AFS-5828	Custpm 5MHz 26° shear wave transducer .375" element. 2.0"(51mm) radius. Case Size: .75"L x .50"W x .25"H end mounted microdot connector. Used with reference standard NDT3197.	TEK-5828	.	.	.
AFS-590AT	90° IN ALUMINUM 5 MHz .187" X .187" TOP MOUNT MINITURE ANGLE BEAM TRANSDUCER. CASE SIZE: .55"L x .260"W x .450"H WITH MICRODOT CONNECTOR	.	.	.	.
AFS-6011P	BOEING 767 TRANSDUCER POSITIONER USED WITH TEKS046-1, TEKS046-2 and NDT6011.	TEK-6011P	.	.	.
AFS-6045-T1/T2	CUSTOM ANGLE BEAM TRANSDUCER FOR B767	XAB-6045-T1/T2	.	.	.
AFS-6058-T1/T2	CUSTOM ANGLE BEAM TRANSDUCER FOR B767	XAB-6058-T1/T2	.	.	.
AFS-6059-T3	CUSTOM ANGLE BEAM TRANSDUCER FOR B767	XAB-6059-T3	.	.	.
AFS-6060-T3	CUSTOM ANGLE BEAM TRANSDUCER FOR B767	XAB-6060-T3	.	.	.
AFS-6224	5MHZ 38° REFRACTED TRANSDUCER	SUS188	SPO-6224	.	.
AFS-670AT	SEARCH UNIT 70° 6MHZ	.	.	.	.
AFS7-132TC	5MHz 70deg in ALUM. ANGLE BEAM TRANSDUCER, .187"sq element ...425"H x .470"L x .260"W TOP MOUNT	HMT 7-132TC	.	.	.
AFS7-221AS	5MHz 45deg in ALUM. ANGLE BEAM TRANSDUCER, .25"sq element ...50"H x .69"L x .33"W SIDE MOUNT	HMT7-421	.	.	.
AFS7-222AS	5MHz 60deg in ALUM. ANGLE BEAM TRANSDUCER, .25"sq element ...50"H x .69"L x .33"W SIDE MOUNT	HMT7-222	.	.	.
AFS7-222AT	5MHz 60deg in ALUM. ANGLE BEAM TRANSDUCER, .25"sq element ...50"H x .69"L x .33"W TOP MOUNT	HMT7-222	.	.	.
AFS7-222SS	5MHz 60deg in STEEL ANGLE BEAM TRANSDUCER, .25"sq element ...50"H x .69"L x .33"W SIDE MOUNT	HMT7-222	.	.	.
AFS7-222ST	5MHz 60deg in STEEL ANGLE BEAM TRANSDUCER, .25"sq element ...50"H x .69"L x .33"W TOP MOUNT	HMT7-222	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFS7-223AS	5MHz 70deg in ALUM. ANGLE BEAM TRANSDUCER, .25"sq element ...50"H x .69"L x .33"W SIDE MOUNT	HMT7-223	.	.	.
AFS7-223AT	5MHz 70deg in ALUM. ANGLE BEAM TRANSDUCER, .25"sq element ...50"H x .69"L x .33"W TOP MOUNT	HMT7-223	.	.	.
AFS7-223SS	5MHz 70deg in STEEL ANGLE BEAM TRANSDUCER, .25"sq element ...50"H x .69"L x .33"W SIDE MOUNT	HMT7-223	.	.	.
AFS7-223ST	5MHz 70deg in STEEL ANGLE BEAM TRANSDUCER, .25"sq element ...50"H x .69"L x .33"W TOP MOUNT	HMT7-223	.	.	.
AFS7-421AS	5MHz 45deg in ALUM. ANGLE BEAM TRANSDUCER, .187"sq element ...45"H x .57"L x .25"W SIDE MOUNT	HMT7-421	.	.	.
AFS7-421AT	5MHz 45deg in ALUM. ANGLE BEAM TRANSDUCER, .187"sq element ...45"H x .57"L x .25"W TOP MOUNT	HMT7-421	.	.	.
AFS7-421SS	5MHz 45deg in STEEL ANGLE BEAM TRANSDUCER, .187"sq element ...45"H x .57"L x .25"W SIDE MOUNT	HMT7-421	.	.	.
AFS7-421ST	5MHz 45deg in STEEL ANGLE BEAM TRANSDUCER, .187"sq element ...45"H x .57"L x .25"W TOP MOUNT	HMT7-421	.	.	.
AFS7-423AS	5MHz 70deg in ALUM. ANGLE BEAM TRANSDUCER, .187"sq element ...45"H x .57"L x .25"W SIDE MOUNT	HMT7-423	.	.	.
AFS7-423AT	5MHz 70deg in ALUM. ANGLE BEAM TRANSDUCER, .187"sq element ...45"H x .57"L x .25"W TOP MOUNT	HMT7-423	.	.	.
AFS7-423SS	5MHz 70deg in STEEL ANGLE BEAM TRANSDUCER, .187"sq element ...45"H x .57"L x .25"W SIDE MOUNT	HMT7-423	.	.	.
AFS7-423ST	5MHz 70deg in STEEL ANGLE BEAM TRANSDUCER, .187"sq element ...45"H x .57"L x .25"W TOP MOUNT	HMT7-423	.	.	.
AFS-760AT	60° TOP MOUNT TRANSDUCER	.	.	.	.
AFS-766/767-2	CUSTOM RADIUS TRANSDUCER L- WAVE 18 DEGREE INCIDENT ANGLE 5MHz .25" ELEMENT WITH TWO SIDE MOUNTED MICRODOT CONNECTORS.	TEK-766/767-2	.	.	.
AFS-766-767-1	CUSTOM RADIUS TRANSDUCER SHEAR WAVE 37 DEGREE INCIDENT ANGLE 5MHz .25" ELEMENT WITH TWO SIDE MOUNTED MICRODOT CONNECTORS.	TEK-766-767-1	.	.	.
AFS-9000L	10MHZ 33° SHEARWAVE TRANSDUCER W/ HANDLE. SOUND PATH DIRECTED TOWARDS THE LEFT	USL 9000	.	.	.
AFS-9000R	10MHZ 33° SHEARWAVE TRANSDUCER W/ HANDLE. SOUND PATH DIRECTED TOWARDS THE RIGHT	USR 9000	.	.	.
AFS-936/MSE	CUSTOM 10 MHz 45° IN STEEL SHEARWAVE TRANSDUCER WITH HANDLE, WITH SWITCH MSE-SWBN65 BUILT INTO HANDLE.	SUS 936/MSE-SWBN65	SUS 936	.	.
AFS-944	SPECIAL 5MHZ TRANSDUCER WITH(2) 60 deg SHOES, LEFT AND RIGHT WITH SWITCH BUILT INTO THE HANDLE	.	.	.	.
AFS-C670AT	COMPOSITE ELEMENT 6MHZ, 70° AL, ..Case .25w x.40L x.43H..piezo size(.125x.190), SUB MINIATURE AGNLE BEAM 3X4MM CRYSTAL	.	.	.	.
AFS-C670ST	6MHZ PIEZOCOMPOSITE ANGLE BEAM TRANSDUCER. 70deg IN STEEL	.	.	.	.
AFS-5587	DUAL 72°, 5MHZ CASONI SHEAR WAVE TRANSDUCER	.	.	.	.
AFW25-23	23 DEGREE LONGITUDINAL LUCITE WEDGE WITH 3/8"-32 THREAD FOR 1/4" ELEMENT THREADED TRANSDUCERS. FOR BELL HELICOPTER 212 MAIN ROTOR GRIP INSPECTION	362-001-210	.	.	.
AFW25-40	40 Degree Lucite Wedge, MSWQC Style used for A330 part 4 57-20-52. Used with MSWQC250124591(AFC-525T-32)	MSWQCA01105940	.	.	.
AFW37-31-TI	WEDGE 31° REFRACTED ANGLE, TI	WFQ-02-31-TI	.	.	.
AFW37-33-TI	WEDGE 33° REFRACTED ANGLE, TI	WFQ-02-33-TI	.	.	.
AFW37-41-TI	WEDGE 41° REFRACTED ANGLE, TI	WFQ-02-41-TI	.	.	.
AFW37-43-TI	WEDGE 43° REFRACTED ANGLE, TI	WFQ-02-43-TI	.	.	.
AFW37-45S	3/8"Ø THREADED WEDGE 45° IN STEEL	AVWM-7T-45	.	.	.
AFW37-60S	3/8"Ø THREADED WEDGE 60° IN STEEL	ABWM-7T-60	.	.	.
AFW37-70A	3/8"Ø THREADED WEDGE 70° IN ALUMINUM	210-852-305	.	.	.
AFW37-70S	3/8"Ø THREADED WEDGE 70° IN STEEL	ABWM-7T-70	.	.	.
AFW-45A	45° IN ALUMINUM LUCITE (PLEXIGLASS) WEDGE FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD	ABTW-06-45	ABTW-06-45	QCX45 (0054277)	.
AFW-45S	45° IN STEEL LUCITE (PLEXIGLASS) WEDGE FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFW-45SA6R	CUSTOM ACRYLIC WEDGE W/ AND AXIAL RADIUS (CONVEX) OF 6" AT 45° IN STEEL, 3/8-32 THREAD	.	.	.	.
AFW-45SC6R	CUSTOM ACRYLIC WEDGE W/ AND CIRCUMFERENTIAL RADIUS (CONVEX) OF 6" AT 45° IN STEEL, 3/8-32 THREAD	.	.	.	.
AFW50-45S	1/2"Ø THREADED WEDGE 45° IN STEEL	ABWM-ST-45	.	.	.
AFW50-60A	1/2"Ø THREADED WEDGE 60° IN ALUMINUM.	.	.	.	.
AFW50-60S	1/2"Ø THREADED WEDGE 60° IN STEEL	ABWM-ST-60	.	.	.
AFW50-70A	1/2"Ø THREADED WEDGE 70° IN ALUMINUM.	.	.	.	.
AFW50-70S	1/2"Ø THREADED WEDGE 70° IN STEEL. USED WITH AFCS-H250 THREADED TRANSDUCER.	ABWM-ST-70	.	.	.
AFW-5A	5" IN ALUMINUM LUCITE (PLEXIGLASS) WEDGE FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD	.	.	.	.
AFW-5S	5" IN STEEL LUCITE (PLEXIGLASS) WEDGE FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD	.	.	.	.
AFW-60A	60" LUCITE (PLEXIGLASS) WEDGE FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD	ABTW-06-60	TCW-60S-.25	ABTW-06-60	QCX60 (0054278)
AFW60-SP2S	60" WEDGE 1.18" RADIUS, DIRECTIONAL TO SOUND PATH. 3/8"-32 FLAT BOTTOM THREADED FOR 1/4"Ø TRANSDUCER	.	.	.	.
AFW60-SP2ST	60" WEDGE 1.18" RADIUS, TRANSVERSE SOUND PATH 3/8-32 FLAT BOTTOM HOLE FOR 1/4"Ø TRANSDUCER	.	.	.	.
AFW60-SP37	60" WEDGE 1.18" RADIUS, DIRECTIONAL TO SOUND PATH. 1/2"-28 FLAT BOTTOM THREADED FOR 3/8"Ø TRANSDUCER	.	.	.	.
AFW60-SP37T	60" WEDGE 1.18" RADIUS, TRANSVERSE SOUND PATH 1/2"-28 FLAT BOTTOM HOLE FOR 3/8"Ø TRANSDUCER	.	.	.	.
AFW-70A	70" LUCITE (PLEXIGLASS) WEDGE FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD	ABTW-06-70	TCW-70S-.25	QCX70 (0054279)	.
AFW-70SA4.063R	CUSTOM ACRYLIC WEDGE WITH AN AXIAL RADIUS (CONVEX) OF 4.063" AT 70° IN STEEL, 3/8-32 THREAD FOR PIPE ID INSPECTION.	.	.	.	.
AFW-70SC4.063R	CUSTOM ACRYLIC WEDGE WITH AN CIRCUMFERENTIAL RADIUS (CONVEX) OF 4.063" AT 70° IN STEEL, 3/8-32 FOR PIPE INSPECTION THREAD	.	.	.	.
AFW937-.812R	90° WEDGE 1/2-28 THREAD W/.812" RADIUS	.	.	.	.
AFW937-.937	90° WEDGE 1/2-28 THREAD W/.937" RADIUS	.	.	.	.
AFW937-.937R	90° WEDGE 1/2-28 THREAD W/.937" RADIUS	.	.	.	.
AFW937-2.062	90° WEDGE 1/2-28 THREAD W/ 2.062" RADIUS	.	.	.	.
AFW937-2.062R	90° WEDGE 1/2-28 THREAD W/ 2.062" RADIUS	.	.	.	.
AFWQ-23A	MSWQC STYLE QUICK FIT WEDGE 23° IN ALUMINUM 3/8-32 THREADED FLAT BOTTOM HOLE.	362-001-210	.	.	.
AFX-1045AT	45° ALUMINUM 10MHZ .187X.187; TOP MOUNT MINI ANGLE BEAM TRANSDUCER	HS-877-10-45-AL-SM	.	.	.
AFX-1045SS	45° STEEL 10MHZ .187X.187; SIDE MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.
AFX-1045ST	45° in STEEL 10MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187"x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W.	.	.	.	.
AFX-1065AT	65° in ALUMINUM 10MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR,.187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	.	.	.	.
AFX-1070AS	70° ALUMINUM 10MHZ .187X.187; SIDE MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.
AFX-1070AT	70° in ALUMINUM 10MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR,.187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	HS-877-10-70-AL-SM	SX-1070AT	XA-7010AT	.
AFX-1070ST	70° in STEEL 10MHZ TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .150"x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W.	.	.	.	.
AFX-260AT	60° ALUMINUM 2.25MHz .187"x.187"; TOP MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.
AFX-290AT	90 deg. ALUMINIUM 2.25MHz .187"x.160" MINI ANGLE BEAM TRANSDUCER TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
AFX-535ST	35° in STEEL 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	XS-35ST	.	.	.
AFX-540AS	40° ALUMINUM 5MHZ .187X.187; SIDE MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFX-540AT	40" in ALUMINUM 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	H5-877-5-40-AL	.	.	.
AFX-540ST	40" in STEEL 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	XS-405T	.	.	.
AFX-545AS	45" in ALUMINUM 5MHZ SIDE MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	A5067	SX 545AS, A5067	XA-455S	A5067-RM
AFX-545AT-2	45" ALUMINUM 5MHZ .187X.187; TOP MOUNT MINI ANGLE BEAM TRANSDUCER..(SIZE RESTRICTION)	SX 545AT-2	SX 545AT-2	.	.
AFX-545SS	45" in STEEL 5MHZ SIDE MOUNT MINI ANGLE BEAM TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	.	.	.	.
AFX-550AS	50" ALUMINUM 5MHZ .187X.187; SIDE MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.
AFX-555AS	55" ALUMINUM 5MHZ .187X.187; SIDE MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.
AFX-557AT	57" in ALUMINUM 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	XA-575T	.	.	.
AFX-560AS	60" in ALUMINUM 5MHZ SIDE MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	.	.	.	.
AFX-560SS	60" in STEEL 5MHZ SIDE MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	A5014-RM	.	A5023-RM	.
AFX-560ST	60" in STEEL 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	A5014-SM	XA-605T	A5014	.
AFX-560TS	5MHZ .187" x .187" 60" IN TITANIUM; SIDE MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.
AFX-560TT	60" TITANIUM 5MHZ .187X.187; TOP MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.
AFX-565AS	65" ALUMINUM 5MHZ .187X.187; SIDE MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.
AFX-567AT	67" in ALUMINUM 5MHZ TOP MOUNT MINI ANGLE BEAM TRANSDUCER WITH TOP MOUNT MICRODOT CONNECTOR, .187" x.187" ELEMENT, CASE SIZE: .375"L x .375"H x .26"W	XA-675T	.	.	.
AFX-570AT-1	70" ALUMINUM 5MHZ (.130"X.187" ELEMENT); TOP MOUNT MICRODOT MINI ANGLE BEAM TRANSDUCER..CASE(.32"L x .24"W x.42"H)	XA-705T-1	.	.	.
AFX-570SS	70" IN STEEL 5MHZ .160" X.187", SIDE MOUNT MINI ANGLE BEAM TRANSDUCER WITH MICRODOT CONNECTOR	A5013-RM	U8438016	.	.
AFX-590AS	90" ALUMINUM 5MHZ .187X.187; SIDE MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.
AFX-590AT	90" ALUMINUM 5MHZ .187X.187; TOP MOUNT MINI ANGLE BEAM TRANSDUCER	.	.	.	.
AFXL-445AS	EXTRA LARGE 4MHz ANGLE BEAM TRANSDUCER 45 DEG WITH SIDE MOUNT CONNECTOR. COMPOSITE ELEMENT	WK 45-4	WK 45-4	.	.
AFXL-460AS	EXTRA LARGE 4MHz ANGLE BEAM TRANSDUCER 60 DEG WITH SIDE MOUNT CONNECTOR. COMPOSITE ELEMENT	WK 60-4	WK 60-4	.	.
AFXL-470AS	EXTRA LARGE 4MHz ANGLE BEAM TRANSDUCER 70 DEG WITH SIDE MOUNT CONNECTOR. COMPOSITE ELEMENT	WK 70-4	.	.	.
AFXL-545SS	EXTRA LARGE 5MHz ANGLE BEAM TRANSDUCER 45 DEG IN STEEL WITH SIDE MOUNT CONNECTOR. PIEZOCOMPOSITE ELEMENT, 8x9mm	MWK-45-5S	.	.	.
AFX-1045AT	45" ALUMINUM 10MHZ .187X.150; TOP MOUNT MINI ANGLE BEAM TRANSDUCER.. CASE(.25"W x .300"L x .300"H)	SSX-1045AT	SSX-1045AT	.	.
AFX-535AT	EXTRA SMALL 35 DEGREE MINI ANGLE BEAM TRANSDUCER(SSX 535AT)	SSX535AT	SSX535AT	.	.
APD-525	5MHz .250" DIA. PERMANENT DELAY TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR.	GD-0505-RM	.	.	.
APD-525-9	5MHz .250" DIA. PERMANENT DELAY TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR	GD-0505-RM	.	.	.
ARD-0550	0.5MHZ .500"Ø REPLACEABLE DELAY TRANSDUCER. SIDE MOUNT MICRODOT CONNECTOR	.	.	.	.
ARD-1050	10MHZ, .500"Ø(12.7mm) ACTIVE ELEMENT (HIGH DAMPED), REPLACEABLE DELAY TRANSDUCER SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = .437". Other lengths available upon request.	.	.	.	.
ARD-1050-9MM	10MHZ, .500 ELEMENT, 9MM REPLACEABLE DELAY SHOE, HIGH DAMPED BROADBAND CONTACT TRANSDUCER	.	.	.	.
ARD-1518	15MHZ, .187"Ø REPLACEABLE DELAY TRANSDUCER	MRD-1501	.	.	.
ARD-2012T	20MHZ, .125Ø REPLACEABLE DELAY TIP TRANSDUCER TOP MOUNT MICRODOT CONNECTOR DFR STYLE	M208-SM	.	.	.
ARD-2025	20MHZ, .250"Ø REPLACEABLE DELAY LINE TRANSDUCER WITH SIDE MOUNT MICRODOT CONNECTOR	T-402-6507	.	.	.
ARD-225	2.25MHz, .250"Ø(6.35mm) ACTIVE ELEMENT (HIGH DAMPED), REPLACEABLE DELAY TRANSDUCER SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = .437". Other lengths available upon request.	GRD-0202-HR 113122660	GRD-0202-HR 113122660	V204-RM	.

September 5, 2019

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
ARD-250/20M	2.25MHZ .500"Ø REPLACEABLE DELAY TRANSDUCER. 20MM LONG DELAY TIP(.797") MICRODOT CONNECTOR	242-591	.	MK2S	.
ARD-325	3.50MHZ .250"Ø REPLACEABLE DELAY TRANSDUCER	.	.	.	.
ARD-325R	3.50MHZ .250"Ø REPLACEABLE DELAY TRANSDUCER, RADIUS TIP	.	.	.	.
ARD-590/20MM	5MHZ, .590"Ø(12.7mm) ACTIVE ELEMENT (HIGH DAMPED), REPLACEABLE DELAY TRANSDUCER SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = 20mm(.790")	PSR5-15R20	.	PSR5-15R20	.
DA312	DA312 Thin Materials Probe - 10 MHz, 0.250" Contact Dia.	0056906	.	.	.
DC-10 FIG603/28WEDGE	CUSTOM TRANSDUCER WEDGE 9 DEGREE INCIDENT ANGLE WITH A 1.80"RADIUS FOR BOTH UPPER AND LOWER ULTRASONIC SCANS, DC-10 54-10-11 FIGURE 603 SHEET 28 PAGE 640	.	.	.	.
DLH-2	Polystyrene 12.7 mm(0.5 in.), Diameter = 14mm (0.551 in.), Length= 12.7 mm(0.5in.)	.	.	.	.
DLR125	RETAINING RING FOR .125" DIA. DELAY LINE TRANSDUCER.	.	.	.	.
DLR-25	DELAY TIP .25	DLH-1	.	.	.
DLT.187-P	Perspex(Lucite) Delay Tip(Standoff) for MRD-1501-HR Transducer.	.	.	.	.
DLT-10M	DELAY TIPS FOR 10mm(.394") DIAMETER DELAY TRANSDUCERS	.	.	.	.
DLT125	DELAY TIPS FOR .125" ARD SERIES TRANSDUCERS	.	.	.	.
DLT25	DELAY TIPS FOR .25" DIAMETER ARD SERIES DELAY TRANSDUCERS	.	.	.	.
DLT25-.25R	MISTRAS CUSTOM DELAY TIPS FOR .25" DIAMETER DELAY TRANSDUCERS WITH .25" RADIUS ON THE TIP.	.	.	.	.
DLT-25/.375CR	MISTRAS CUSTOM DELAY TIPS FOR .25" DIAMETER DELAY TRANSDUCERS WITH .375" CONCAVED RADIUS AT THE TIP.	.	.	.	.
DLT-25CR	MISTRAS CUSTOM DELAY TIPS FOR .25" DIAMETER DELAY TRANSDUCERS WITH .25" CONCAVED RADIUS AT THE TIP.	.	.	.	.
DLT-2MMR	CUSTOM DELAY TIPS 2MM" RADIUS FOR REPLACEABLE DELAY TRANSDUCERS.	.	.	.	.
DLT50	DELAY TIPS FOR .500" ARD SERIES DELAY TRANSDUCERS.	.	.	.	.
DLT5-10	10 DEGREE ANGLE DELAY SHOE, 16.8mmØ	N22YK66438	N22YK66438	.	.
DRR-25	DELAY TIP	DRR-1	.	.	.
DRT90592G	DOWTY AEROSPACE PROPELLERS GUIDE FOR DRT90592	.	.	.	.
ELT TEMPLATE-2	EDDY CURRENT CIRCLE TEMPLATE, 0.201"Ø. 3 HOLE SIZES: .200", .201",.202". MATERIAL: 2024-T351, 0.063"	.	.	.	.
FLN	BOEING CUSTOM LUCITE TRANSDUCER POSITIONER.	.	.	.	.
FLN-2	BOEING LUCITE TRANSDUCER POSITIONER.	.	.	.	.
FREEZE PLUG TP	FREEZE PLUG TRANSDUCER POSITIONER, ALUMINUM	.	.	.	.
FRN	BOEING LUCITE TRANSDUCER POSITIONER	.	.	.	.
HOLDING FIXTURE	LEFT AND RIGHT REAR SPAR MOUNT TOOL MODIFICATION W/ 10 DRILLED HOLES	.	.	.	.
IIW TYPE 1 CASE	IIW TYPE 1 FORM FITTED WOOD PROTECTIVE CARRY CASE	.	.	.	.
IIW-V1-AL	V-1 (A-2) IIW Angle Beam Calibration Block (Metric). Made to British Standard: BS-2704, German Standard: DIN 54-120, Australian Standard AS 2803 and ISO 2400.Thickness of 1" / 25 mm, Height of 4" / 100 mm for straight beam calibration. 4" / 100 mm rad...	V1-AL	.	.	.
K-PEN TIP	GE SERIES K-PEN DELAY TIPS .090" ( WITHOUT GROOVES)	387-003-109	.	.	.
Lucite Wedge 120P	Custom Lucite Wedge for Reference Standard 1. Material: Lucite/Cast Acrylic	120P	.	.	.
MA-705T	70° ANGLE BEAM TRANSDUCER in ALUMINUM, 5MHz .25" x .25" ELEMENT, CASE SIZE(.75" x .37" x .50" ) TOP MOUNT MICRODOT CONNECTOR	.	.	.	.
MBBQCX35-2	Cast Acrylic transducer wedge with a 33 degree sound path, 3/8-32 thread 80mm(3.15") radius	.	.	.	.
MT-PR-DA400	PARKER RESEARCH DA-400 AC/DC MAGNETIC PARTICLE YOKE 115VAC	.	.	.	.

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
MWB 45-4(E)	KRAUTKRAMER 45° ANGLE BEAM TRANSDUCER 8X9 4MHZ	.	.	.	.
MWB 60-4(E)	KRAUTKRAMER 60° ANGLE BEAM TRANSDUCER 8X9 4MHZ	.	.	.	.
NDT3020P1	BOEING PROBE GUIDE 737 PT 6 57-50-06	.	.	.	.
NDT3238P	BOEING POSITIONER	.	.	.	.
NDT3255G	BOEING GUIDE FOR NDT3255	.	.	.	.
NDT4113-5P	ULTRASONIC POSITIONER 55 DEGREE SHEAR WAVE IN STEEL 5.25" CONVEX RADIUS	.	.	.	.
NDT4113-6P	ULTRASONIC POSITIONER 55 DEGREE SHEAR WAVE IN STEEL 6.0" CONVEX RADIUS	.	.	.	.
NDT522P1	Boeing Positioner, 757 PT4 53-80-01..pg. 9 fig 5	.	.	.	.
NDT6045-SC1	Boeing Transducer Guide. Material: Delrin ( Black Acetal). Used with NDT6045 Reference Standard. 767 PART 4 54-50-08 PAGE 15 FIGURE 3	.	.	.	.
NDT6045-SC2	Boeing Transducer Guide. Material: Delrin ( Black Acetal). Used with NDT6045 Reference Standard. 767 PART 4 54-50-08 PAGE 15 FIGURE 3	.	.	.	.
NDT6048P	TRANSDUCER POSITIONER FOR NDT6048	.	.	.	.
NDT6053G	BOEING 767 REFERENCE STANDARD NDT6053 GUIDE. DELRIN	.	.	.	.
NDT6066-P	BOEING POSITIONER (LUG B), LUCITE..PART 4 57-50-11 FIGURE 4 PAGE 12	.	.	.	.
NDT6067-P	BOEING POSITIONER (LUG A), LUCITE. PART 4 57-50-11 FIGURE 4 PAGE 10	.	.	.	.
NDT6068-P	BOEING POSITIONER (LUG D), LUCITE. PART 4 57-50-11 FIGURE 4 PAGE 16	.	.	.	.
NDT6069-P	BOEING POSITIONER (LUG C), LUCITE. PART 4 57-50-11 FIGURE 4 PAGE 14	.	.	.	.
NDT6070-P	BOEING POSITIONER (LUG E), LUCITE. PART 4 57-50-11 FIGURE 4 PAGE 18	.	.	.	.
NDT6071-P	BOEING POSITIONER (LUG F), LUCITE. PART 4 57-50-11 FIGURE 4 PAGE 20	.	.	.	.
NDT6072-P	BOEING POSITIONER (LUG H), LUCITE. PART 4 57-50-11 FIGURE 4 PAGE 22	.	.	.	.
NDT6073-P	BOEING LUCITE POSITIONER (LUG ) LUCITE. USED WITH NDT6073. PART 4 57-50-11 FIGURE 4 PAGE 24	.	.	.	.
NDT6089-G1	BOEING TRANSDUCER GUIDE FOR NDT6090 BAT #3. MATERIAL: ACETAL(DELRIN) 767 PART 4 54-50-15 PAGE 28 FIGURE 8	.	.	.	.
NDT6089-G2	BOEING TRANSDUCER GUIDE FOR NDT6089 BAT #1. MATERIAL: ACETAL(DELRIN)	.	.	.	.
NDT6089-G3	BOEING TRANSDUCER GUIDE FOR NDT6090 BAT #3. MATERIAL: ACETAL(DELRIN) 767 PART 4 54-50-15 PAGE 28 FIGURE 8	.	.	.	.
NDT6089-G4	BOEING TRANSDUCER GUIDE FOR NDT6090 BAT #3. MATERIAL: ACETAL(DELRIN) 767 PART 4 54-50-15 PAGE 28 FIGURE 8	.	.	.	.
NDT6089-G5	BOEING TRANSDUCER GUIDE FOR NDT6090 BAT #3. MATERIAL: ACETAL(DELRIN) 767 PART 4 54-50-15 PAGE 28 FIGURE 8	.	.	.	.
NDT6089-G6	BOEING TRANSDUCER GUIDE FOR NDT6090 BAT #3. MATERIAL: ACETAL(DELRIN) 767 PART 4 54-50-15 PAGE 28 FIGURE 8	.	.	.	.
NDT6090-G1	BOEING TRANSDUCER GUIDE FOR NDT6090 BAT #3. MATERIAL: ACETAL(DELRIN) 767 PART 4 54-50-15 PAGE 28 FIGURE 8	.	.	.	.
NDT6090-G2	BOEING TRANSDUCER GUIDE FOR NDT6090 BAT #3. MATERIAL: ACETAL(DELRIN) 767 PART 4 54-50-15 PAGE 28 FIGURE 8	.	.	.	.
NDT6091G1	NDT6091 REFERENCE STANDARD TRANSDUCER GUIDE. MATERIAL: DELRIN(ACETAL) 767 PART 4 54-50-14 PAGE 26 FIGURE 2.	.	.	.	.
NDT6091G2	NDT6091 REFERENCE STANDARD TRANSDUCER GUIDE. MATERIAL: DELRIN(ACETAL) 767 PART 4 54-50-14 PAGE 26 FIGURE 2.	.	.	.	.
NDT6092G1	NDT6092 REFERENCE STANDARD TRANSDUCER GUIDE. MATERIAL: DELRIN(ACETAL) 767 PART 4 54-50-14 PAGE 27 FIGURE 3	.	.	.	.
NDT6092G2	NDT6092 REFERENCE STANDARD TRANSDUCER GUIDE. MATERIAL: DELRIN(ACETAL) 767 PART 4 54-50-14 PAGE 27 FIGURE 3	.	.	.	.
NDT655G	TRANSDUCER GUIDE	.	.	.	.
NDT656G	TRANSDUCER GUIDE	.	.	.	.



PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
NDT725P1	BOEING TRANSDUCER POSITIONER 777 PT 4 55-17-01	.	.	.	.
NDT725P2	BOEING TRANSDUCER POSITIONER 777 PT 4 55-17-01	.	.	.	.
NDT796G	BOEING TRANSDUCER GUIDE	.	.	.	.
NDT815-G1	DELRIN TRANSDUCER GUIDE FOR REFERENCE STANDARD NDT815	.	.	.	.
NDT815-G2	DELRIN TRANSDUCER GUIDE FOR REFERENCE STANDARD NDT815.	.	.	.	.
NDT815-G3	DELRIN TRANSDUCER GUIDE FOR REFERENCE STANDARD NDT815.	.	.	.	.
NDT815-G4	DELRIN TRANSDUCER GUIDE FOR REFERENCE STANDARD NDT815	.	.	.	.
NDT815-G5	DELRIN TRANSDUCER GUIDE FOR REFERENCE STANDARD NDT815	.	.	.	.
NDT815-G6	DELRIN TRANSDUCER GUIDE FOR REFERENCE STANDARD NDT815	.	.	.	.
NLN	BOEING CAST ACRYLIC POSITIONER	.	.	.	.
NRN	BOEING CAST ACRYLIC POSITIONER	.	.	.	.
PSR5-15R20	5MHZ, .500"Ø(12.7mm) ACTIVE ELEMENT (HIGH DAMPED), REPLACEABLE DELAY TRANSDUCER SIDE MOUNT MICRODOT CONNECTOR. Delay Tip length = (.790")20mm	M206RBDLH2-20	M206-RM	M206RBDLH2-20	.
PT.29A	CUSTOM 45 DEGREE LUCITE WEDGE	.	.	.	.
PT.29B	CUSTOM 11 DEGREE LUCITE WEDGE	.	.	.	.
PT.30	QUICK CHANGE TRANSDUCER 5MHz .25" ELEMENT 3/8-32 THREAD	TAB-052	.	.	.
PT.30a	CUSTOM 45 DEGREE LUCITE SHEAR WAVE WEDGE FOR TITANIUM INSPECTION USED WITH RS.22	AE88901	.	.	.
PT.30b	CUSTOM 20 DEGREE LUCITE "L" WAVE WEDGE WITH 1.220" RADIUS FOR TITANIUM INSPECTION USED WITH RS.22	AE088902	.	.	.
PT.31.1	CUSTOM 45 DEGREE 5MHz .187"x.187" SHEAR WAVE TRANSDUCER WITH HANDLE BENT AT 5 DEGREES AWAY. MICRODOT CONNECTOR.	AE05202	.	.	.
PT.56/A	DC-10 TRANSDUCER INCIDENT ANGLE 8° RADIUS 1.8	.	.	.	.
PT.56/B	DC-10 TRANSDUCER INCIDENT ANGLE 6° RADIUS 2.1	.	.	.	.
PT.56/C	DC-10 TRANSDUCER INCIDENT ANGLE 13° RADIUS 2.25	.	.	.	.
PT.60	TRANSDUCER SHEARWAVE 10MHZ .125ELEMENT, 34°	.	.	.	.
PZT-15MHz	.25" Dia. 15MHz K-81 MATERIAL PIEZOELECTRIC ELEMENT	.	.	.	.
QCX45	45° IN ALUMINUM LUCITE (PLEXIGLASS) WEDGE FOR .25" DIAMETER TRANSDUCER. 3/8-32 THREAD	.	.	.	.
QFW35A/40	35 DEGREE LUCITE WEDGE FOR QUICK FIT TRANSDUCER	QFW35A/40	.	.	.
Radius Shoe 201	Boeing Custom Contact Radius Shoe 201 with a 0.100" radius. Material: Black Delrin(Acetal).	.	.	.	.
Radius Shoe 202	Boeing Custom Contact Radius Shoe 202 with a 0.150" radius. Material: Black Delrin(Acetal).	.	.	.	.
Radius Shoe 203	Boeing Custom Contact Radius Shoe 203 with a 0.200" radius. Material: Lucite/Cast Acrylic.	.	.	.	.
W201	LUCITE WEDGE 45° SHEAR WAVE IN ALUMINUM USED WITH .25" ELEMENT TRANSDUCER (.75"L x .45"W x .37"H)	.	.	.	.
W202	LUCITE WEDGE 60° SHEAR WAVE IN ALUMINUM USED WITH .25" ELEMENT TRANSDUCER (.84"L x .45"W x .44"H)	.	.	.	.
W203	LUCITE WEDGE 70° SHEAR WAVE IN ALUMINUM USED WITH .25" ELEMENT TRANSDUCER (1.0"L x .45"W x .50"H)	.	.	.	.
W-203	LUCITE 70 DEGREE WEDGE MSWQC STYLE	W-203	.	.	.
AFC-1025-75S	10MHZ .250Ø TRANSDUCER, .375Ø	TC8-2510T	SUC-726	.	.
AFC-1050	10MHZ 1/2" STRAIGHT BEAM	.	.	.	.

PART NUMBER	DESCRIPTION	EQUIVALENT	EQUIVALENT	EQUIVALENT	EQUIVALENT
AFC-1210-6	TRANSDUCER, 10MHZ , .188ø X .62 LONG	.	.	.	.
AFC-1210HD-10	10MHZ .125ø ELEMENT, HIGH DAMPED, HARD WIRED TO BNC; .188øX1.0L CASE	.	.	.	.
AFC-1210HD-6	10MHZ .125ø ELEMENT, HIGH DAMPED, HARD WIRED TO BNC; .188øX.60L CASE	.	.	.	.
AFC-2012HT	20MHZ .125ø , TOP MOUNT CONNECTOR	M116-5M	.	.	.
AFC-W2150C	CUSTOM TRANSDUCER	.	.	.	.
AFS-0505B	5MHZ .25" ELEMENT BACKWARD SHOOTING TRANSDUCER	.	.	.	.
AFS-0505F	5MHZ .25" ELEMENT FORWARD SHOOTING TRANSDUCER	.	.	.	.
AFS-0509	35° SHEAR WAVE IN TI, 1.97 RIGHT SIDE SCANNING	.	.	.	.
AFS-0512B	5MHZ .400" ELEMENT BACKWARD SHOOTING TRANSDUCER	.	.	.	.
AFS-0512F	5MHZ .400" ELEMENT FORWARD SHOOTING TRANSDUCER	.	.	.	.
AFS-1028	CUSTOM 22° TRANSDUCER, 5MHZ .25" ELEMENT WITH A 120mm(4.72") RADIUS. REFERENCE: AIRBUS A310 57-51-11 FIGURE 402 PAGE 403. Includes Test Report and Certificate of Conformance.	TEK-5062	545533	.	.
AFS-1301-1F	CUSTOM ANGLE BEAM TRANSDUCER	TEK-5008-1F	.	.	.
AFS-1301-1N	CUSTOM ANGLE BEAM TRANSDUCER	TEK-5008-1N	.	.	.
AFS-1301-2F	CUSTOM ANGLE BEAM TRANSDUCER	TEK-5008-2F	.	.	.
AFS-1301-2N	CUSTOM ANGLE BEAM TRANSDUCER	TEK-5008-2N	.	.	.