



## LUMACHECK DUAL UV & WHITE LIGHT CHECKING

**INTRODUCTION** The LumaCheck Dual UV and White Light Meter has been designed to offer the user the most accurate results and versatile calibration options available on the market.

The LumaCheck is a unique system design, since it is the Sensor that stores the calibration details, not the Instrument itself, meaning that only the Sensor needs to be sent for calibration subject to the standards that your facility operate in accordance with.

This allows the unit of the LumaCheck to be “hot-swapped” with another sensor and remain in continuous use.

- ADVANTAGES**
- + Excellent Results Accuracy.
  - + Dual Sensor.
  - + Interchangeable Sensor allows the LumaCheck to operate continuously.
  - + Lightweight and Compact.
  - + Battery Operated
  - + Ergonomically Designed with Protective Rubber Boot.
  - + Full Colour Programmable Display.
  - + Separate Probe and Separate Cable for convenience and lower replacement costs.



Sensor Head

The LumaCheck not only has a detachable Sensor Head, but also offers a detachable cable too allowing all aspects of the LumaCheck to be interchanged.

If the operator has two Sensors with the LumaCheck, this interchangeability means that operators need not be without a functional light meter during calibration.

The LumaCheck is housed in an extremely robust and high quality casing and as an exclusive Baugh & Weedon design it comes with the guarantee of high quality and renowned calibration services.

## LUMACHECK STANDARD KIT

The LumaCheck comes as a complete kit. It comes with the following as standard:

LumaCheck Unit, Sensor Head, Sensor Cable, Blue Rubber Boot, 2 x Non-Rechargeable AA Batteries, Carry Case, Quick Reference Guide and the LumaCheck Manual.



## SPECIFICATION

<b>GENERAL:</b>	Measuring Range: White Light:	5 lux to 10,000 lux
	UV Light:	0 to 10,000 uW/cm <sup>2</sup>
	Resolution: White Light:	0.1 lux below 10 lux.
	UV Light:	0.15 to 10 μW/cm <sup>2</sup> (micro watts per square centimetre).
	Units: White Light:	Foot Candles (ft-c or fc or lm/ft) or Lux.
	UV Light:	μW/cm <sup>2</sup> (micro watts per square centimetre).
<b>UNIT:</b>	Display:	2.8" (70mm) 320 x 240 pixels colour display. LCD with selectable backlight.
	Screen:	5 readings per second.
	Conversion Rate:	100ms
	Resolution:	Up to 0.1 Lux & 0.1uW/cm <sup>2</sup> (configurable)
	Dimensions:	163mm Long x 80mm Wide x 25mm Deep. With rubber boot on = 168mm Long x 85mm Wide x 30mm Deep.
	Weight:	350g (0.77 pounds) including batteries.
	Power:	2 x 1.5 V AA Alkaline Batteries.
	PC Connectivity:	USB or mains charging capabilities
	IP Standard:	IP54
<b>SENSOR HEAD</b>	Resolution:	Settable in menu system
	Overall Accuracy:	+/- 3% measured against primary standard
	Temperature Coefficient:	less than +/- 0.01%/C (0 to 50C)
	Irradiance range:	UV-A - 0 - 10000 uW/cm <sup>2</sup> , Visible - 0 - 10000 lux
	Spectral range:	UV-A - 315-400nm, Visible - 460-680nm

**NDT Supply.com, Inc.**

7952 Nieman Road  
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125

e-mail: [sales@ndtsupply.com](mailto:sales@ndtsupply.com), [www.ndtsupply.com](http://www.ndtsupply.com)



Document number BR1008: Issue 4

**Baugh & Weedon Ltd.**

Beech Business Park, Tillington Road, Hereford, HR4 9QJ

Tel: +44 (0) 1432 267671 Fax: +44 (0) 1432 359017 Email: [sales@bw-nde.com](mailto:sales@bw-nde.com) [www.bw-nde.com](http://www.bw-nde.com)