


OVERHEAD LAMP MATRIX

Part Number	ASTM E3022	ISO 3059	RRES:90061	AIRBUS AITM6	PRATT & WHITNEY	Nominal Steady-State UV-A Intensity at 15 in (38 cm)	UV-A Coverage at 15 in (38 cm) at minimum 1,200 $\mu\text{W}/\text{cm}^2$	Power Source	Light Source	White Light	Applications
EDGE Series											
EDG-13SBLC	X	X	X	X	X	4,700 $\mu\text{W}/\text{cm}^2$	14.5 x 13 in (37 x 33 cm)	AC power 100-240V 50/60Hz	13 UV-A LEDs	N/A	Industrial, NDT, Clean Room
EDG-13HC	X	X				8,500 $\mu\text{W}/\text{cm}^2$	See Below	AC power 100-240V 50/60 Hz	13 UV-A LEDs	N/A	Industrial, NDT, Clean Room
EDG-13T						8,500 $\mu\text{W}/\text{cm}^2$	16 X 17 in (40.6 X 43.2cm)	AC Power 100-240V 50/60 Hz	13 UV-A LEDs	N/A	Industrial, NDT, Clean Room
EDG-4W						1,400 $\mu\text{W}/\text{cm}^2$ @ 48in. (122cm)	22 X 22 in (56 X 56cm)	AC Power 100-240V 50/60 Hz	4 UV-A LEDs	N/A	Industrial, NDT, Clean Room
PowerMAX											
PM-8B	X	X				0 to 6,500 $\mu\text{W}/\text{cm}^2$	10 X 16 in (25.4 X 40.64cm)	AC power 100-240V 50/60 Hz	8 UV-A LEDs & 2 White LEDs	Y	Industrial, NDT, Clean Room
PM-16B	X	X				0 to 8,500 $\mu\text{W}/\text{cm}^2$	18 X 17 in (45 X 43cm)	AC power 100-240V 50/60 Hz	16 UV-A LEDs & 4 White LEDs	Y	Industrial, NDT, Clean Room

Key Selling Points (EDGE):

- Flexible mounting arms
- Multiple units can be ganged
- 100-240V universal power
- Easy installation



Key Selling Points (PowerMAX):

- ASTM Compliant
- Switchable lighting UV/White
- Dual lighting, covers a large area
- Easy installation



NDT Supply.com, Inc.
 7952 Nieman Road
 Lenexa, KS 66214-1560 USA
 Phone: (913)-685-0675
 Email: sales@ndtsupply.com