

DA750, DA1500 and DA1500-DR

Portable Magnetic Inspection Units

The DA-Series portable power packs are convenient and economical inspection units that are used in a wide range of magnetic particle applications that require only moderate power. They are ideal for large or heavy parts, in-service mobile equipment, or job-site welds.

Advantages & Features

- Selection of AC current or HWDC current by only changing one cable connection.
- Locate defects in any direction using prods, coil wrap or contact clamps.
- Infinitely variable current control.

- Demagnetize your parts in AC by turning the current dial to zero or by passing parts through a coil and slowly withdrawing them while the current is on.
- The optional DA1500-DR comes equipped with an easy-to-read digital LCD display.







DA750 DA1500 DA1500-DR

April 2023 Page **1** of **2**

Specifications

| Unit Comparison Chart | | | | |
|---|--|--|--|--|
| | DA750 | DA1500 | DA1500-DR | |
| Dimensions | 18" x 9.25" x 8" 45.7 x 23.5 x 20.3 cm | 21.5" x 10.5" x 9.5" 54.6 x 26.7 x 24.1 cm | 21.5" x 10.5" x 9.5" 54.6 x 26.7 x 24.1 cm | |
| Weight | 43 lbs. (19.5 kg) | 110 lbs. (49.9 kg) | 110 lbs. (49.9 kg) | |
| Max Output ¹ | 750 Amps AC or HWDC | 1500 Amps AC or HWDC | 1500 Amps AC or HWDC | |
| Cord Length | 20 ft. (6 m) | 20 ft. (6 m) | 20 ft. (6 m) | |
| Duty Cycle | 10% | 10% | 10% | |
| Electrical Requirements ² | 27 A @ 115 VAC 50/60 Hz 14 A @ 230 VAC 50/60 Hz | 45 A @ 230 VAC 50/60 Hz 23 A @ 460 VAC 50/60 Hz | 45 A @ 230 VAC 50/60 Hz 23 A @ 460 VAC 50/60 Hz | |

¹Current ratings based on use of two 15-foot lengths of 4/0 cable (30 feet total) ²Single phase power supply

Accessories and Cables for Start-Up

- 20' Remote Hand Switch Assembly (PN: MA7RC) or 20' Remote Foot Switch Assembly (PN: MA7FC)
- 15' 4/O Cable Set w/Lug & Either Ends (PN: MC1540) or 15' 4/O Cable Set w/Either Ends (PN: MC1541)
- Individual Prod Set (PN: MA7000)
- Dual Horizontal Prod Assembly (PN: MA7001)
- Braided Contact Clamp (PN: MA7003)
- Transport Cart (PN: TR700)

Part Numbers

| | DA750 | DA1500 | DA1500-DR |
|--------|-----------|------------|--------------|
| 115VAC | DA750-115 | - | - |
| 230VAC | DA750-230 | DA1500-230 | DA1500DR-230 |
| 460VAC | - | DA1500-460 | DA1500DR-460 |

NDT Supply.com, Inc. 7952 Nieman Road Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125

e-mail: sales@ndtsupply.com, www.ndtsupply.com



April 2023 Page 2 of 2