

**NDT Supply.com, Inc.**

7952 Nieman Road  
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125

e-mail: [sales@ndtsupply.com](mailto:sales@ndtsupply.com), [www.ndtsupply.com](http://www.ndtsupply.com)



**Black-White**

**Densitometer**





# Black-White Densitometer

## Specification

<b>Main Tech Data</b>	
Density Range	D=0.00—4.00 (DM3010) D=0.00—4.50 (DM3010A) D=0.00—5.00 (DM3011)
Repeatability	$\pm 0.01$
Measuring Error	0.00—2.00 0.02 2.00—4.50 0.05 4.50—5.00 0.08
Power	50 ~ 60Hz, 220V $\pm 10\%$
Power Dissipation	25W
Aperture Size	Dia. 2mm
Display Mode	Three digital display
Sampling Time	0.8 s
Communication Port	RS232 Port
Software	DmCAL PC software
Working Environment	Temperature 0 °C~40 °C, Relative humidity $\leq 85\%$
Dimension	260×265×110 (H×W×L)



Weight	2.7kg
--------	-------

**The Calibration Software Interface**



Standard Configurations	
DM3011 Series Black-White Densitometer	Serial Port Cable
Standard Step Density Tablet	Software CD
Power Line	Quality Certification
Packing Case	Operating Manual, Packaging List