

NDT Supply.com, Inc.
7952 Nieman Road
Lenexa, KS 66214-1560 USA



DT-1308 Lux / Ft-cd Meter offers a Very Rugged Design with Brilliant Backlight Dual Display

Model : DT-1308

DT-1308	Specifications
Display	Multi-function 3-3/4 (3999) digit LCD with Bargraph indicator
Over range indication	LCD displays 'OL'
Spectral response	CIE photopic (CIE human eye response curve)
Measurement Accuracy	± 5%
Temperature coefficient	±0.1% per °C
Sampling rate	13.3 times per second (bargraph); 1.3 times per second (digital display)
Photo detector	Silicon photo-diode with spectral response filter
Peak Hold	Capture light peaks to 10µS
Operating conditions	Temperature: 32 to 104°F (0 to 40°C); Humidity: < 80% RH
Storage conditions	Temperature: 14 to 140°F (-10 to 50°C); Humidity: < 80% RH
Dimensions	6.5 x 3.0 x 1.7" (165 x 76 x 43mm)
Weight	Approx. 14.2 oz. (403g) with battery installed
Power supply	9V battery

Phone: 913-685-0675
Fax: 913-685-1125

e-mail: sales@ndtsupply.com
web: www.ndtsupply.com