

Separate Probe Densitometer

DT-200

- Separate Probe Type Densitometer
- High Accuracy $\pm 0.03 D$
- 10 Points Calibration
- Big Display Screen with backlight
- Extremely wide light range of between 650 Cd/m^2 and $320\,000 \text{ Cd/m}^2$
- Carrying case included



LCNDT®

www.lcndt.net

The DT-200 is a robust, easy to use, separate probe type densitometer for measuring the transmission density of x-ray film. The unit has been designed for using in one-site mobile darkrooms, laboratories and offices.

Specifications:

Range: $650 \text{ Cd/m}^2 - 320\,000 \text{ Cd/m}^2$
Density: $0.00 - 5.00 D^*$
Optical Aperture: 3mm diameter
Probe Temperature compensated
Display: 4 digit LCD
Accuracy: $\pm 0.03 D$
Resolution: $0.01D$
Detector: Silicon photodiode
Power supply: (AA/1.5V)x2-Alkaline Battery
Battery life: 1200 hours (Continuous duty, without illuminated)
Dimensions: $6.7" \times 3.5" \times 2.4"$ (170mm x 90mm x 60mm)
Weight: 1.7 pounds (800g)

Standard Components:

Main unit: 1
Instruction manual (English): 1
Carrying Case: 1

Optional Components:

AGFA Density Strip, 15-step, certified



7952 Nieman Road, Lenexa, KS 66214-1560 USA
Phone: 913-685-0675, Fax: 913-685-1125
www.ndtsupply.com, sales@ndtsupply.com