

PosiTest[®] **HHD**

High voltage Holiday Detector

Detects holidays, porosity, pinholes, leaks,
and other discontinuities using pulse DC



*Optional
handheld wand
with insulated
cable*



DeFelsko[®]
The Measure of Quality

PosiTest® HHD

Features...

Simple

- Easy-to-use with bright, color LCD
- Ready to measure—comes with everything needed for testing
- Audibly and visibly alerts when flaws/holidays are detected
- Lightweight, ergonomic design provides comfortable all-day use, reducing fatigue
- Voltage calculator feature—choose one of 11 international standards, and input the coating thickness to automatically calculate the required test voltage

Durable

- Rugged, environmentally sealed ABS plastic enclosure
- Weatherproof, dustproof, and shockproof
- Included hard shell case with custom foam inserts for superior protection
- Two year warranty

Accurate

- Built-in certified voltmeter (crest meter, jeep meter) displays and regulates the voltage at the electrode
- Long Form Certificate of Calibration included with each instrument
- Conforms to national and international standards including ISO, ASTM, and NACE

Versatile

- A wide range of rolling spring electrodes and wire brushes are available. Custom sizes available upon request.
- Optional handheld wand accessory converts the detector into a wand configuration ideal for testing hard-to-reach areas (suitable for voltages < 15 kV)
- Industry-standard connectors and adaptors for compatibility with nearly all existing electrodes
- User adjustable voltage range from 0.5 – 35kV

Powerful

- Strobe light and loud audible alarms emitted when a holiday is detected. Audio alarm mode can be adjusted for differing environments.
- Removable Smart lithium-ion battery with built-in charge state indicator

Safe

- Press and hold Safety Trigger helps prevent accidental high voltage generation
- 7.6 m (25') ground (earth) cable with locking connector and spring clamp
- Shock proof/creep proof—internally sealed to minimize creep distance to high voltage components. Designed in accordance with IEC 61010-1.



PosiTest HHD with included fan brush

Two Kits available

The PosiTest HHD is available in two kit configurations. The PosiTest HHD Kit features a longer electrode rod, increased battery capacity, Pelican Storm case, and shoulder strap. The PosiTest HHD Basic Kit features a shorter electrode rod, lower battery capacity, and a durable hard shell case.

PosiTest HHD Kit (HHDKIT)

Includes ALL features as shown on left plus...

- Pelican Storm hard shell case with custom foam inserts for maximum protection
- 72 Wh Li-ion battery
- Choice of 50 cm (20") or 13 cm (5") electrode rods
- Shoulder strap

PosiTest HHD Basic Kit (HHDKITB)

Includes ALL features as shown on left plus...

- Hard shell case with custom foam inserts
- 36 Wh Li-ion battery
- 13 cm (5") electrode rod

Specifications	HHDKIT	HHDKITB	
Output Voltage Range	0.5 – 35 kV		
Output Voltage Adjustment	0.5 kV – 1 kV: 10 Volt Steps 1 kV – 35 kV: 100 Volt Steps		
Output Accuracy	±5%		
Pulse Duration	10 µs		
Pulse Repetition Rate	30 Hz		
Coating Thickness Range	up to 20 mm (780 mils) [†]		
Battery Size	72 Wh Li-ion	36 Wh Li-ion	
Typical Battery Life for selected rolling springs @ 10 kV	Ø 12"	40 hrs.	16 hrs.
	Ø 40"	30 hrs.	12 hrs.
Operating Temperature	-20° to 60°C (-4° to 140°F)		

[†] Based on NACE SP0274-2011 recommendations.

Ordering Guide

PosiTest HHD Kit To substitute a Short Electrode Rod, append '-S' to the product code (i.e. HHDKIT-S)	HHDKIT
PosiTest HHD Basic Kit	HHDKITB

KITS COME COMPLETE with Holiday detector, 7.6 m (25') ground (earth) cable with ground clip, Li-ion battery pack with built-in charge state indicator, smart charger with universal AC voltage input, stainless steel fan brush, 50 cm (20") or 13 cm (5") electrode rod with thumb screw, instructions, durable hard shell case, Long Form Certificate of Calibration traceable to NIST, two year warranty

UNIT SIZE:

64 cm x 6.4 cm x 13 cm
(25" x 2.5" x 5")

UNIT WEIGHT:

1.6 kg (3.6 lbs.)
with 72 Wh battery (no electrodes)

Conforms to ASTM D4787/D5162/D6747/D7953/G62,
ISO 29601, NACE SP0188/SP0274/SP0490, AS3894.1

PosiTest[®] HHD

High voltage Holiday Detector

Electrode Options

For a complete list of available electrodes visit www.defelsko.com/hhd



Rolling Spring Electrodes

Rolling Spring Electrodes	
Rolling Spring Coil for 4" pipe (102 mm) OD	HHDSPRING4
Rolling Spring Coil for 6" pipe (152 mm) OD	HHDSPRING6
Rolling Spring Coil for 8" pipe (203 mm) OD	HHDSPRING8
Rolling Spring Coil for 10" pipe (254 mm) OD	HHDSPRING10
Rolling Spring Coil for 12" pipe (304 mm) OD	HHDSPRING12
Rolling Spring Coil for 14" pipe (356 mm) OD	HHDSPRING14
Rolling Spring Coil for 16" pipe (406 mm) OD	HHDSPRING16
Rolling Spring Coil for 20" pipe (508 mm) OD	HHDSPRING20
Rolling Spring Coil for 24" pipe (610 mm) OD	HHDSPRING24
Rolling Spring Coil for 30" pipe (762 mm) OD	HHDSPRING30
Rolling Spring Coil for 36" pipe (914 mm) OD	HHDSPRING36

Custom sizes available upon request

Please Note: Each spring includes two pre-installed spring couplers. A spring connector (HHDCONNECT) is required to attach the PosiTest HHD to the spring couplers. Custom sizes and bulk pricing available. Additional couplers (HHDCOUPLER - 2 pack) are available.



Flat Wire Brush Electrodes

Flat Wire Brush Electrodes	
Flat Brush 51 mm/2"	HHDFLTBRSH2
Flat Brush 152 mm/6"	HHDFLTBRSH6
Flat Brush 203 mm/8"	HHDFLTBRSH8
Flat Brush 305 mm/12"	HHDFLTBRSH12
Flat Brush 610 mm/24"	HHDFLTBRSH24
Flat Brush 914 mm/36"	HHDFLTBRSH36
Flat Brush 1219 mm/48"	HHDFLTBRSH48

Custom sizes available upon request

Fan Brush Electrodes*	
Fan Brush 152 mm/6"	HHDFANBRSH

* PosiTest HHD Kits comes complete with a Fan Brush.

Conductive Rubber Paddle	
Conductive Paddle 102 mm/4"	HHDPADDLE

Use spring and brush electrodes made by other manufacturers with DeFelsko adaptors.

Compatibility Chart	
Model	Adaptor Ordering Code
SPY	not required [†]
PCWI	HHDPCWIADPT
Tinker and Razor	HHDTRADPT
266 & 280	HHD266ADPT

[†] The PosiTest HHD is compatible with SPY coils, brushes, and accessories.

Accessories

PosiTest HHD Verifier standalone voltmeter (crest meter, jeep meter) for verifying the accuracy and operation of ALL pulse type holiday detectors

Handheld Wand with 1.5 m insulated cable converts the detector to a wand-type instrument (for voltages up to 15 kV)

Electrode Rods choose between 13 cm (5") and 50 cm (20") rods

Spring Connectors connect the PosiTest HHD to DeFelsko or SPY rolling spring electrodes

Electrode Adaptors connect to spring and brush electrodes from other manufacturers—choose between PCWI, T&R, and 266/280 adaptors—not required for SPY electrodes (see table on page 3)



PosiTest HHD Verifier

Spring Connector

Handheld Wand

Electrode Adaptors

Features

Control panel with LCD display, strobe alert, and speaker to visibly and audibly detect flaws

Shoulder strap attachment point

Ground (earth) cable socket

Shoulder strap attachment point

Safety trigger

Ergonomic grips for all day comfort

152 mm (6") fan brush

50 cm (20") electrode rod (included with HHDKIT)

PosiTest HHD shown with 50 cm electrode rod

