

Overview

- 2,000, 3,000 or 4,000 Amps
- AC or AC & HWDC or AC & FWDC
- AC Demag, HWDC & Rev. DC Demag Optional
- 12" Coil Standard, larger diameter options
- Coil only option with swivel and part supports.
- 20" Standard Head Opening, 30", 40" options +
- 240V & 440V, 1 Phase, 60 Hz



Features

Frame

- Frame is anodized modular aluminum construction.
- Door Panels are powder coated steel.
- Main tank for liquid collecting is 304 Stainless Steel
- Particle Application: manual gun designed for either water or oil-based products.
- Recirculating Tank: 304 Stainless Steel for liquid mixing, mounted on a removable cart with separate pump for uniform mixing of the inspection media. Recirculating Tanks hold about 20 liters.

Control Panel

- Push buttons with two-hands command for Head-stock clamping.
- Button for test Start
- Warning light for "Exam in program" indication
- Manual switch for magnetization selection (Head Shot or Coil)
- Selector for magnetization / demagnetization
- Potentiometer for the test current adjustment
- Analog ammeter for display of applied current
- Potentiometer for shot time setup



NDT Supply.com, Inc.

7952 Nieman Road
Lenexa, KS 66214-1560 USA



Recycling Tank

- 5 gallons
- 304 Stainless Steel Tank for liquid mixing
- Mounted on cart with separate pump for liquid mixing to keep the best uniformity of the inspection media.