



# The ultrasonic couplant *for better signal with less noise*

## Providing improved signal-to-noise through superior acoustics

For improved signal-to-noise and better penetration with frequencies above 5.0 MHz on:

- Rough surface castings, coarse grain, and small radius curvatures
- Rough fiberglass
- Plastic pipe
- Composites

### PRODUCT DESCRIPTION

Gel viscosity remains in place for overhead and vertical surfaces

Slow drying

Water-soluble, easy clean up

### PACKAGING

- 1 gallon / 3.8 liter cubitainer
- 5 gallon / 19 liter cubitainer

### PRODUCT SPECIFICATIONS

#### Operating Range:

-18° to 224°F (-28° to 107°C)

- **Acoustic Impedance:** 1.95+ g/cm<sup>2</sup>-sec x 10<sup>5</sup>
- **Medium viscosity**
- **Halogens & Sulfur:** Less than 50 ppm
- **pH:** 8.0 nominal at 20°C



**NDT Supply.com, Inc.**  
7952 Nieman Road  
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125  
e-mail: [sales@ndtsupply.com](mailto:sales@ndtsupply.com), [www.ndtsupply.com](http://www.ndtsupply.com)

