

SM-10T Densitometer

Measuring Aperture Measuring Range

0.00 to 5.00 D

Accuracy Repeatability Preview Stage ± 0.02 D ± 0.01 D 2.5"x4"

None

Warm-up time Film Measuring Depth

7.25" (18.42cm)

Portable Power Source (2) 9V Alkaline batteries Included

Desktop Power

9V AC Power Supply

4.5"H (11.4cm) 4.5"W(11.4cm)

Dimensions

11"L (28.0cm)

RS-232 Serial Output (CAT# 5008) Optional

SM-10T CAT# 5009 SM-10TCI CAT# 5008

® is a manufacturer of photographic, graphic arts, and X-ray ESECO - S & equipment. Our products are made and serviced in the USA and backed by over forty years of technical experience. All ESECO products come with a one year No Hassle warranty.

The S SM-10T densitometer assures instant, accurate, and repeatable results that rival the same high standards of more expensive units. Featuring total accuracy of+/- .02 from 0.00 to 5.00 Optical Density and compliant with ANSI / ISO Standard - 5/2.

Low power consuming components and extended battery life features are provided in the automatic "stand-by" mode. For added convenience, it may be operated with the UL/CSA-approved plug-in a/c power adapter furnished with the ? ® SM-10T. The SM-10TCI is available with a serial interface (CAT# 5008). Use the the SM-10TCI model with the ESECO S ® **QC PAL** Software for maximum quality assurance.

> NBS Standard 1009 - Reference Material ID 057901 ANSI / ISO Standard - 5/2

NDT Supply.com, Inc. 7952 Nieman Road Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125 e-mail: sales@ndtsupply.com, www.ndtsupply.com



*** MADE IN USA