



Luxxor® Portable Video Camera

Connects to ANY Hawkeye® Rigid or Flexible Borescope!

When connected to any Hawkeye Borescope, the new Luxxor Portable Video Camera delivers sharp, bright video and still images. Inspection images can be viewed "live," and captured!

LPC



3 Viewing Options:



Portable Video Monitor:
Portable video monitor with image capture PVM-DV



Computer Ready:
USB capture device with software VC-USB2



Sony® Professional Video Monitor:
15" LCD monitor SVM-15

LUXXOR® PORTABLE CAMERA SPECIFICATIONS

Image Sensor	1/4" Color CCD
Lens	Built in - 25mm Borescope coupler lens
Mount	Quick release, ball bearing mount couples borescope securely to the camera. Attaches to any standard 32 mm diameter borescope eyecup
Video Format	NTSC
Resolution	768 x 494 pixels (520 TV lines)
S/N Ratio	48DB +
Min. Illumination	0.2 Lux at F/1.2 (without borescope)
Shutter speed	1/50 - 1/100,000
Working Temperature	-10 to 45 deg C
Power Supply	5 - 12 V DC, 80 mA
Output	Standard cable is RCA composite video, or 12 Pin Hi-ROSE with portable video monitor
Dimensions	Length = 160mm Diameter, handle = 32mm , Diameter, coupler lens = 44.5mm

From the makers of:



PRECISION BORESCOPIES

Made in USA

NDT Supply.com, Inc.
7952 Nieman Road
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125
e-mail: sales@ndtsupply.com, www.ndtsupply.com

