



KOWOLUX LX

NDT Film viewers for X-ray films according to ISO 5580, ASTM E1390





For evaluation of large format NDT X-ray films

KOWOLUX LX series LED film viewer for NDT X-ray films

The KOWOLUX LX viewers are designed for high-end NDT X-ray film evaluation.

A durable, economically designed housing made of stainless steel contains latest series of PowerLEDs providing magnificent white light over the entire control range. A speed controlled cooling fan reduces irritating noise.

KOWOLUX LX 40 / LX 40 plus / LX 60 / LX 90

Viewers with terminal strip for fixing the X-ray film and 4-way blind system for adjustment to any film format.

KOWOLUX LX 14X17 / LX 14X17 plus

Viewers with spot light in the left top corner for evaluating X-ray films with higher density and an attachable masks system.

Housing: stainless steel Screen glass: thermally cured, translucence 92%

g > 0.8Divergence factor: Uniformity factor: $\sigma' > 0.9$ Color temperature: 5,000 K Lifetime of LEDs: > 40,000 h

Control range: < 0.5 ... 100% 88 ... 264 V / 47 ... 63 Hz Power supply:

KOWOLUX LX 40 Article No.: 13 40195

Viewing area: 405 x 430 mm Luminance/ Density: 80,000 cd/m² / 3.9 D

Rated power: 140 W

Dimensions/ Weight: 700 x 100 x 640 mm / 19.0 kg

KOWOLUX LX 40plus Article No.: 13 40700

405 x 430 mm Viewing area: Luminance/ Density: 100,000 cd/m² / 4.0 D

Rated power: 160 W

Dimensions/ Weight: 700 x 130 x 640 mm / 24.0 kg

KOWOLUX LX 60 Article No.: 13 40197

405 x 605 mm Viewing area: Luminance/ Density: 80,000 cd/m² / 3.9 D

Rated power: 200 W

Dimensions/ Weight: 870 x 100 x 640 mm / 24. kg

KOWOLUX LX 90 Article No.: 13 40690

405 x 905 mm Viewing area: 70,000 cd/m² / 3.85 D Luminance/ Density:

450 W Rated power:

Dimensions: 1170 x 100 x 640 mm / 30.0 kg

KOWOLUX LX 14X17 Article No.: 13 40680

Rated power: 200 W

- spot 50 x 50 mm Viewing area: 355 x 430 mm

Luminance/ Density: 70,000 cd/m² / 3.8 D - spot 160,000 cd/m² / 4.2 D

Dimensions/ Weight: 700 x 100 x 640 mm / 11.0 kg

KOWOLUX LX 14X17plus Article No.: 13 40675

Rated power: 230 W

355 x 430 mm - spot 50 x 50 mm Viewing area: - spot 320,000 cd/m² / 4.5 D Luminance/ Density: 160,000 cd/m² / 4.2 D

Dimensions/ Weight: 700 x 130 x 640 mm / 15.0 kg

Scope of supply:

KOWOLUX LX Film viewer complete with:

Foot switch, Power supply cable, Stand feet (vertical stand), Wall mounting kit,

Test Certificate, Certificate of Conformity - LX 14X17 additionally with mask 14x17 inch

Accessories:

LX Set Up-/ Carrying Device Article No.: 13 40199

LX 14X17 Attachment mask for films

Article No.: 13 40681 7x17 inch Article No.: 13 40682 14x17 inch 8x10 inch Article No.: 13 40683 5x 7 inch Article No.: 13 40684 12x15 inch Article No.: 13 40685 10x12 inch Article No.: 13 40686 7x10 inch Article No.: 13 40687 4x15 inch Article No.: 13 40688 14x17 inch with IRIS Ø 4 ... 75 mm at spot Article No.: 13 40689













