

KOWOWET X -very bright, waterproof wet film viewer with no corrosion problems

The KOWOWET X is used for initial viewing of just developed films directly at the processing unit (wall mounting above film processor).

Waterproof cemented glass in plastics housing prevents water and chemicals from penetrating inside the viewer.

With the sealed 2-way-switch viewer can provide permanent light or push button function can be used. The non-corrosive and waterproof plastic housing and the LEDs promise a very long trouble free operation during live span – especially also in mobile laboratories.

KOWOWET X

Viewing area:	135 x 80 mm
Support area:	155 x 100 mm - hardened glass, waterproof cemented in housing
Luminance, max.:	15,000 Cd/m ²
Power:	8 W
Switch:	On / Off or push function
Housing:	plastics / glass – IP 66 according to EN 60529
Mounting:	wall mounting (including mounting material)
Dimensions:	200 x 110 x 60 mm (WxHxD)

KOWOWET X12

Article No. 12 30100

Voltage:	9 ... 34 V DC
Connection:	cable free ends + / -
Weight:	0.6 kg



KOWOWET X230

Article No. 12 30100

Voltage:	9 ... 34 V DC
Power Supply Unit:	100 ... 240 V AC
Connection:	chinch socket for power supply
Weight:	0.5 kg + 0.2 kg

