

LC NDT FV-2014 14" x 17" Industrial LED Film Viewer



The FV-2014 viewer combines the latest electronic technology with a reliable LED driver circuit. The FV-2014 can view film with a density up to 4.0HD and can be operated continuously 24 hours a day.

Features:

- 13" x 16.1" Window size (fits 14" x 17" Film)
- Bright enough to view 4.0 Density Film
- Vertical and Horizontal Electronic Masks
- LED switch control system that allows you to switch on or off areas on the viewer window
- Rugged viewer feet that can support the viewer at any angle or wall mount
- New "Screen Grab" film holder for your convenience
- Low heat output
- Low noise – fan speed varies with temperature
- Low power consumption
- Universal Power Supply – use it anywhere





Mounted on the Wall



Rugged Stand

Specifications:

Max Luminance:	100,000 Cd/m ²
Uniformity:	$g = 0.95$
Diffusion Factor:	$\sigma = 0.95$
Viewer Window:	13" x 16.1" (335 x 410 mm)
Surface Temperature:	Rise $\leq 68^{\circ}\text{F}$ (20°C) After 12 hours continuous maximum luminance
Power:	85 – 264 VAC 47 – 63 Hz. Universal
Dimensions:	20.1" x 16.1" x 2.4" (L x W x H) 51 x 41 x 6 cm
Weight:	18 lbs. (7.4 kg.)
Warranty:	5 years parts, 1 year labor

FV-2014 Kit Includes:

- FV-2014 Film Viewer
- Vertical and Horizontal Electronic Masks
- Foot Switch
- Power Supply
- Power Adapter & Line
- Instruction Manual
- Guarantee
- Inspection Report
- Warranty Card