



LCNDT[®]


PRO UV Series
LCNDT PRO-500 Ultra-High
Intensity LED UV Lamp

Smart & Powerful
Wide beam
High uniformity
As Robust as hammer

ASTM Compliant



NDT Supply.com, Inc.
7952 Nieman Road
Lenexa, KS 66214-1560 USA
Phone: (913)-685-0675
Email: sales@ndtsupply.com




Key Features:

- Ultra-High Intensity Spot: 2" diameter spot > 14,000 uW/cm² @ 15"
- Wide Beam Profile: 10" diameter beam > 1000 uW/cm² @ 15"
- Waterproof and Drop-proof - IP65 Rated and rugged enough for all working environments
- Cool Operation

Standard parts:

- Lamp
- 10 ft. cord
- Power Supply
- Goggles
- Carrying Case
- Certificate of Conformance and a serialized validation report



MODEL	PRO-500
MAX. irradiance at 15" distance	14,000 uW/cm ²
Beam Profile @ 15", Min. 1,000 uW/cm²	10" diameter at min. 1,000 uW/cm ²
Peak Wavelength	365 +/- 5nm
Light Source	1 UV-A LED and 1 white Light LED
Visible Light (UV)	0.5 ft. candles (5 lux)
White Light LED Intensity	163 ft. candles (1800 lux)

Dimensions: 3.3" x 4.7" x 7.9" (D x W x H)

Weight(with battery): 1.9 lbs. (0.85 kg)

Power input: 90V–264V AC / 47-63Hz

Specification: ASTM E3022, ISO 3059

Optional parts:

- Tripod Lamp Holder
- 20 ft. cord
- Heavy Duty Power Supply with Rugged Cable
- Magnetic Stand with 360° Rotation (Not compatible with PRO-500B)
 - The first segment measures 8.85" (225mm), the second measures 6.29" (160mm)