




# LKMT-E3A

## Wireless Battery AC Rotating X Yoke

Integrated design of the probe and lithium battery No need to use a wire connection



### Multi-angle Presentation



Lifting Force:

AC:  $\geq 156.8N(16kg)$




Yoke Weight:

3.85kg( Without power supply)



Protection level:

IP65/IP67



Dual function of black and white light

White light illumination  $\geq 2000$  Lux

Ultraviolet lamp irradiation  $\geq 7000 \mu W/cm^2$

Can display and set remaining power and voltage,  
AC flaw detection mode, point pressing magnetization  
or continuous magnetization working mode, ultraviolet or  
white light illumination mode



Magnetic pole angle can be changed



Magnetic Pole Distance:  
100mm\*100mm



Battery Voltage:  
14.8V/88.8Wh  
Battery Weight  
0.64kg



Working Temperature:  
-10~60°C



Normal operate time 2h

Continuous (Non-Stop) operate time 1h



### Configuration List

Integrated E-type probe 1  
Lithium battery 2  
Lithium battery chargers 2  
Set of auxiliary tools 1  
Instrument protective vest 1  
Instrument carrying case 1  
Fillet weld magnetic feet 4  
Flat-surface pulley magnetic feet 4  
Factory inspection report 1  
User manual 1



NDT Supply.com, Inc.  
7952 Nieman Road  
Lenexa, KS 66214-1560 USA  
Phone: (913)-685-0675  
Email: sales@ndtsupply.com