



- Certificate of Conformance and a serialized validation report
- Focus Spot, Max. UV intensity $> 14,000 \mu$ W/cm² at 15"
- Extreme wide beam profile: 10" diameter of UV-A intensity >1000 $\mu W/cm^2$ at 15"
- Fanless Design no fan But absolutely stay cool
- Li battery Powered Can Easily swapped
- UV intensity will keep the same when battery drops


Super high UV intensity

Make it possible for long distance inspection



PRO UV-500B

Standard parts: Lamp, One Li battery, Charger, Goggles, Carrying case, Serialized Certificates





Dimension(with battery): 3.3" Diameter,
4.7" width, 11.2" height

Weight(with battery): 2.8 lb (1.25 kg)

Power input: 90V–264V AC / 47-63Hz

Specification: ASTM E3022, ISO 3059

Optional parts: High capacity Li battery(4000mAh)

	WODEL	11004-3000
	MAX. irradiance at 15" distance	14,000 uW/cm ²
	Beam Profile @ 15", Min. 1,000 uW/cm ²	10" diameter
	Peak Wavelength	365±5nm
	Light Source	1 UV-A LEDs(4 core) and 1 White LED
	Visible Light	< 0.5 foot-candle (5 lux)
	White Light LED Intensity	163 foot-candle (1800 lux)

http://

MODEL





PRO UV-500B



7952 Nieman Road, Lenexa, KS 66214-1560 USA Phone: 913-685-0675, Fax: 913-685-1125 <u>www.ndtsupply.com</u>, sales@ndtsupply.com