

## INTRODUCTION

The PiX Portable Security Solution from Pacific is designed with a complete focus on the end-user. Every component has a snap-on fit for quick and definitive use in high-pressure environment. The system carries certifications such as Military Standard 810G, 461G for usage in low and high temperature, vibration, and altitude, and is backed by Pacific's ISO 9001:2015 approved quality management system.

The system comes in a portable & rugged pelican case on wheels with custom foam (also available in a backpack solution). The imaging unit consists of an IP67 rated DR with the lowest edge space in the market, a rugged IP 65 PC/Tablet, PiX Security Software, PiX Gold 3.0 Control Box, Dual Energy Module (2.0), Golden XRS source & other accessories (bipod stand, tripod stand etc).

The PiX Security Solution operates with a built-in battery and has both tethered & wireless modes. Our system enables you to capture and display an image in a matter of seconds, allowing you to make rapid decisions under high-pressure situations.



**SATISFIED CLIENTS INCLUDE:**  
 International Airports, Air  
 Force, Forensic Companies  
 & MANY MORE!



## CRITICAL FEATURES

1. Low Edge Space
2. IP 67 Certified Detectors
3. Complete Wireless X-Ray Control
4. Emergency ON/OFF Switch
5. Dual Energy Module
6. Auto-Connect
7. Visual and Audible Alarm
8. Pelican and Backpack Solutions
9. Long Range Image Transfer



**PIX CONTROL BOX**

**BRONZE**

**SILVER**

**GOLD**

**HORIZON**

	PIX CONTROL BOX	BRONZE	SILVER	GOLD	HORIZON
Wireless X-Ray Control	✓	✓	✓	✓	✓
Mounting on X-Ray	✓	✓	✓	✓	✓
Emergency X-Ray Stop	✓	✓	✓	✓	✓
One Pulse Shot	✓	✓	✓	✓	✓
Change Pulses in SW	X	✓	✓	✓	✓
Set Delay Time in SW	X	X	✓	✓	✓
Check X-Ray Battery Level	X	X	✓	✓	✓
Control Dual Energy Box	X	X	✓	✓	✓
Wireless Range (meters)	100	100	300	800	
Size (in)	1.5"x2"x2"	4"x3"x6"	2"x2.5"x7.7"	2"x2.5"x7.7"	
Weight (gms)	40	150	130	150	
IP Rating	IP 65	IP65	IP 67	IP 68	

### DETECTOR SPECIFICATIONS

Item	Unit	Specs
Sensor Type	-	TFT Array
X-Ray convertor (Scintillator)	-	Gadox (Gd <sub>2</sub> O <sub>2</sub> S) & Csl Options Available
Dimension (Wx LxT)	mm	400x465x17
Weight	Kg	(2.9~5) Depending on your application, lead shielding is done
Pixel Pitch	lum	140
Active Pixel Area	mm	358.4x427.3
Active Pixel Resolution	pixels	2500x3052
Limited Resolution	lp/mm	3.57
AD Convertor	bits	16
Data Transfer Interface	-	Wireless: IEEE 802.11 ac/Gigabit Ethernet
X-Ray Generator Interface	-	AED/Line Trigger
Margin of Edge	mm	Bottom: <6, Left: <12 (Optional 3mm & 8mm available)
X-Ray Energy Range	kVp	~450kVp
Battery Performance	-	Over 4 hours (continuous capturing)
Power Consumption	W	45 (DC 12V, 3.75A)
IP Grade	-	IP67
Component	-	Batter Charger, Control Box, Power Supply

*\*Note: Different detector sizes available based on project requirement.*

### TABLET/LAPTOP

**Laptop Option # 1** B360, Intel Core i5-10210U Processor, With Webcam, Microsoft Windows 10 Pro x64 with 8GB RAM, 256GB PCIe SSD, Sunlight Readable Full HD LCD 1400 nits + Touchscreen + Hard tip stylus, US KBD + US Power cord, Membrane Backlit KBD, Wifi + BT, RS232 + VGA, Smart Card Reader, SD Card Reader, RJ45, HDMI, 1 Year Warranty

**Tablet Option** A140 G2, Intel Core i5-10210U Processor 1.6 GHz, (No Webcam), Microsoft Windows 10 Pro x64 with 8GB RAM, 256GB PCIe SSD, Sunlight Readable (LCD+ Touch Screen), US Power Cord, Wifi+BT, Micro SD, LAN, Smart Card reader, 1 Year Warranty

**Laptop Option # 2** S410 G3 Basic, Intel Core i3-8145U Processor 2.1GHz, 14", Microsoft Windows 10 Pro x64 with 4GB RAM, 256GB SSD, STD LCD, US KBD+US Power cord, Membrane KBD, Wifi+BT, SD Card Reader, 1 Year Limited Warranty

### X-RAY GENERATOR SPECIFICATIONS

Power: DeWalt™ 12v Li-Ion Battery  
 Weight: 4.70 lb (2.13 kg) including battery  
 Output Dose: Avg. 3.1 mR/ count, measured 12" from source  
 Pulse rate: 4 Counts per second  
 Counts per charge : 1700 Counts (5100 pulses)  
 Source size: 1 8" (3mm)  
 Mox Photon Energy: 150 kVp  
 Pulse Width: 50 Nanoseconds  
 Beam Angle, 40 Degree standard  
 Current Draw: 6.8 AMPS  
 Max DutyCycle: 100 Counts (300 pulses) per 4 minutes  
 Warranty: 1 Year limited part s, labor, service

*\*Note: 20v Xrs150. Xrs2, Xrs3 Options Also Available*

