

## COMPARATIVE CHART OF COMPLIANT SPECTROLINE® UV-A LED LAMPS

Style	Series	Part Number	Nominal Steady-State UV-A Intensity at 15 in (38 cm)	UV-A Coverage at 15 in (38 cm) at minimum 1,200 µW/cm2	Power Source	
<b>ASTM E3022-18 &amp; RRES 90061 (Rolls-Royce) Compliant Lamps</b>						
Handheld		uVision™ 365	UV-365SBLC	< 5,000	6 in (15 cm) Ø	AC Cord
			UV-365MSBLC	µW/cm2 <	6 in (15 cm) Ø	AC/DC (NiMH Battery)
			UV-365ZSBLC	5,000 µW/cm2	6 in (15 cm) Ø	AC/DC (Li-ion Battery)
			UV-365SBLCR	< 5,000	6 in (15 cm) Ø	AC Cord & Reel
Overhead		EDGE™ 13	EDG-13SBLC	µW/cm2 < 4,700 µW/cm2 5,000 µW/cm2	14.5 x 13 in (37 x 33 cm)	AC Cord
<b>ASTM E3022-18 Compliant Lamps</b>						
Handheld		uVision™ 365	UV-365HC	6,000	6.4 in (16 cm) Ø	AC Cord
			UV-365MHC	µW/cm2	6.4 in (16 cm) Ø	AC/DC (NiMH Battery)
			UV-365ZHC	6,000	7.5 in (19 cm) Ø	AC/DC (Li-ion Battery)
			UV-365HCR	µW/cm2	6.4 in (16 cm) Ø	AC Cord & Reel
		Classic	CLA-100	8,000	6 in (15.25 cm) Ø	AC Cord
			CLA-100Z	µW/cm2	6 in (15.25 cm) Ø	AC/DC (Li-ion Battery)
CLA-150			6,000	7 in (17.78 cm) Ø	AC Cord	
Overhead		PowerMax™ 365	PM-16B	µW/cm2 6,500 µW/cm2	23.6 x 10.63 In (60 x 27 cm)	AC Cord
			PM-32B	5,700 6,500 µW/cm2 µW/cm2	43.3 x 10.63 In (110 x 27 cm)	AC Cord
		EDGE™ 13	EDG-13HC	5,700 8,500 µW/cm2 µW/cm2	24 x 22 in (61 x 56 cm)	AC Cord
Headlamp		CLARITY™ 365	SPN-CLR365-HC	8,000 6,750 µW/cm2 µW/cm2	3 in (8 cm) Ø	Li-ion Battery
			SPN-CLR365-SC	4,500 µW/cm2	4 in (10 cm) Ø	Li-ion Battery
		EagleEye™	EK-3000	4,500 µW/cm2	5.5 in (14 cm) Ø	Li-ion Battery



7952 Nieman Road, Lenexa, KS 66214-1560 USA  
 Phone: 913-685-0675, Fax: 913-685-1125  
[www.ndtsupply.com](http://www.ndtsupply.com), [sales@ndtsupply.com](mailto:sales@ndtsupply.com)

NDT  
 2/23 A16252-8  
 PRINTED IN USA