

## **NANOSERIES**

LED UV-Inspection Flashlight

**IDX 550** 

Spot fluorescent indications in the smallest of spaces.



Rechargeable Batter y



Bright & Uniform Beam



Instant-On Operation



Small Space Inspection

CONVENIENT ON/OFF SWITCH-For easy one-handed operation





NDT Supply.com, Inc. 7952 Nieman Road Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125 e-mail: sales@ndtsupply.com, www.ndtsupply.com





Instant-on operation; lamp reaches full power immediately.

Portable and rugged. Anodized aluminum lamp body minimizes corrosion and stands up to years of heavy use.

Powered by one Lithium Ion (Li-Ion) battery Provides 2.5 Hours of continuous UV-A Light between charges.

MODEL	NOMINAL STEADY-STATE UV-A LIGHT INTENSITY 15 in (nominal value)	Designed upon ASTM E3022-18	UV-A COVERAGE DIAMETER at 15in (38cm) at minimum 1,000  µW/cm²
IDX-550	9,000 μW/cm²	standard Industrial-grade NDT Flaw ultraviolet	5.1in(13cm) dia

① UV intensity reading taken with the Spectro-UV® AccuMAX™ Series meter, and is factory set to the value shown.


## IDX-550


## Nano 365 Series IDX-550 Kit

Comes complete with Nano 365 Series Rechargeable IDX-550 UV-A LED Flashlight, Rechargeable Lithium Ion Battery, 5V Power Adapter, USB Charging Cable, Lanyard, Belt Holster, Safety Glasses (w protective bag) and Storage Box.



CHARACTERISTIC	DESCRIPTION	
Compliance	ASTM E3022-18	
Application	Special for Non-destructive	
	testing (NDT)	
UV led	6W	
Wavelength	365 nm	
Intensity @ 15 in (nominal value)	9,000 μW/cm²	
Li-ion battery capacity	3.7V, 2600 mAh	
Running time	2.5 h	





**DISTRIBUTED** BY:

NDT Supply.com, Inc. 7952 Nieman Road Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125 e-mail: sales@ndtsupply.com, www.ndtsupply.com



