NDT Supply.com, Inc. 7952 Nieman Road Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125 e-mail: sales@ndtsupply.com, www.ndtsupply.com



Tru-Sonic Euro Style Angle Beam Probes

NDT Supply's Tru-Sonic transducers are tuned to provide the best combination of resolution and sensitivity and are well suited for most ultrasonic flaw detection applications. Certification included with all transducers.



Features

- Lemo 00 connectors are standard, but can be ordered with microdot type (M), Subvis (S) or BNC (B) connectors.
- Band width: 50-55% at 6dB
- Sensitivity is equal or better than major name brands
- Certification Included

TATE OF THE PROPERTY OF THE PR	
6	(0)

Model	Frequency (MHz)	Size (mm)	Angle (Degree)
ABE-289-45	2	8 x 9	45
ABE-289-60	2	8 x 9	60
ABE-289-70	2	8 x 9	70
ABE-489-45	4	8 x 9	45
ABE-489-60	4	8 x 9	60
ABE-489-70	4	8 x 9	70
ABE-21416-45	2	14 x 16	45
ABE-21416-60	2	14 x 16	60
ABE-21416-70	2	14 x 16	70
ABE-41416-45	4	14 x 16	45
ABE-41416-60	4	14 x 16	60
ABE-41416-70	4	14 x 16	70
ABE-22022-45	2	20 x 22	45
ABE-22022-60	2	20 x 22	60
ABE-22022-70	2	20 x 22	70
ABE-42022-45	4	20 x 22	45
ABE-42022-60	4	20 x 22	60
ABE-42022-70	4	20 x 22	70