

NDT Supply.com, Inc.

7952 Nieman Road
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125
e-mail: sales@ndtsupply.com, www.ndtsupply.com



Tru-Sonic Euro Style Straight Beam Probes

General purpose medium dampened flaw probes for detection and thickness gauging applications with a combination of a ceramic face and protective membrane. NDT Supply's Tru-Sonic transducers are tuned to provide the best combination of resolution and sensitivity. Certification included with all transducers.

Features



- Lemo connectors standard. Optional microdot type, Subvis or BNC connectors
- Band width: 50-55% at -6Db
- Sensitivity equal or better than major name brands
- Metal housing
- Combination Ceramic Face and Protective Membrane
- Membrane optional for 12 mm, 20 mm, and 24 mm probes
- 0.5 MHz and 1 MHz are Composite Type
- Certification included

Model	Frequency (MHz)	Diameter (mm)	Connector
CRE0.5-24	0.5	24	Lemo 1
CRE1-24	1	24	Lemo 1
CRE2-12	2	12	Lemo 00
CRE2-20	2	20	Lemo 00
CRE2-24	2	24	Lemo 1
CRE4-12	4	12	Lemo 00
CRE4-20	4	20	Lemo 00
CRE4-24	4	24	Lemo 1

