

NDT Supply.com, Inc.

7952 Nieman Road
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125
e-mail: sales@ndtsupply.com, www.ndtsupply.com



Tru-Sonic Mini Angle Beam Probes

NDT Supply's Tru-Sonic transducers are tuned to provide the best combination of resolution and sensitivity and are well suited for most ultrasonic flaw detection applications. Certification included with all transducers.



Features

- 5 MHz Frequency
- Short "X" approach distance improves near surface resolution
- Good resolution & sensitivity
- Good for thin materials and small diameter pipe welds
- Wedge made from "Peek" for superior performance
- Temperature range goes up to 248 °F (120 °C)
- Microdot connector is standard supply, with Lemo 00 or Subvis connectors available on request

Model	Size (in.)	Footprint (in.)	Angle (Degree)
MAB5-2525-45	.25 x .25	.43 x .75	45
MAB5-2525-60	.25 x .25	.43 x .75	60
MAB5-2525-70	.25 x .25	.43 x .75	70
MAB5-1625-45	.16 x .25	.32 x .75	45
MAB5-1625-60	.16 x .25	.32 x .75	60
MAB5-1625-70	.16 x .25	.32 x .75	70

