



# Tru-Sonic USA Style Standard Straight Beam Probes

NDT Supply's Tru-Sonic transducers are tuned to provide the best combination of resolution and sensitivity and are well suited for most ultrasonic flaw detection applications. Available with Right Angle Side Mounted or Top Mounted connectors with optional protective membrane. Certification included with all transducers.

## Features



- Rugged, ergonomic probe housing with frequency color coded ring
- Band Width is between 45 and 60% at – 6dB
- Standard with Right Angle Side Mounted Connector
- Straight Top Mount Connector style optional
- Protective Membrane on Straight Top Mount Connector style optional
- BNC Standard Connector on 1/2" 3/4" and 1" Transducers
- Microdot Connector on 1/4" Transducers
- Lemo or Subvis Connectors are available
- Certification included

## Standard w/ Side Mounted BNC Connector



Model	Frequency (MHz)	Diameter (in.)
CR2-50	2.25	1/2
CR2-75	2.25	3/4
CR2-100	2.25	1
CR5-50	5	1/2
CR5-75	5	3/4
CR5-100	5	1

## Top Mounted BNC Connector

### Standard



Model	Frequency (MHz)	Diameter (in.)
CT2-50	2.25	1/2
CT2-75	2.25	3/4
CT2-100	2.25	1
CT5-50	5	1/2
CT5-75	5	3/4
CT5-100	5	1

### Protective Membrane



Model	Frequency (MHz)	Diameter (in.)
CTP2-75	2.25	3/4
CTP2-100	2.25	1
CTP5-75	5	3/4
CTP5-100	5	1