## XR200 18v-20v X-RAY GENERATOR

150 kVp light duty pulsed X-ray machine



# Golden Engineering Portable X-ray Technology



The redesigned XR200 has a 80 character LCD (20x4), menu based interface and is powered by a DeWalt 18v-20v Li-lon battery

#### **NEW FEATURES**

- Pulse setting up to 999 pulses
- Variable pulse rate (1 pulse per second or slower)
- Set multiple pulse trains
- Select time delay between pulse trains
- Records total life pulses on source
- Two resettable pulse trackers
- Retro-fit existing XR200 X-ray Generators
- Lemo<sup>®</sup> K Series circular connector
- 21 mm Picatinny Rails for mounting accessories
- New hassel-free tripod mount
- 6000 pulses per battery charge
- Battery includes charge indicator

### HIGHLY PORTABLE

- Source with battery is 8% lighter than previous version
- Compact size is 13% smaller in volume
- Battery weighs less than 1 lb (.45 kg)



#### **Dimensions**

Height 5.83" (14.81cm) Width 4.26" (10.82cm) Length 10.69" (27.15cm)



#### **SPECIFICATIONS**

Power:	DeWalt <sup>®</sup> 18v-20v Li-Ion Battery
Weight:	10.7 lb / 4.8 kg (including battery)
Output dose:	Avg. 2.6 mR/pulse measured 12" from source
Pulse rate:	10 pulses per second
Source size:	1/8" (3mm)
Max photon energy:	150 kVp
Pulse width:	50 nanoseconds
Beam angle:	40 degree standard
Current Draw:	9 amps
Max duty cycle:	200 pulses per 4 minutes
Warm up:	NONE Required
Warranty:	1 year limited parts, labor, service



7952 Nieman Road, Lenexa, KS 66214-1560 USA Phone: 913-685-0675, Fax: 913-685-1125 www.ndtsupply.com, sales@ndtsupply.com