

# XRS Graphic Display Series

Making the unseen seen



## Pulsed X-ray Advantages

Penetrating power in a small container

Utilitarian design - DeWalt battery, tripod mounts, picatinny rail, removable top plate

Lightweight - Weighs just 11 lbs

Safety - no radioactive material, minimal leakage, short exposure time

Easy to use - One input variable



**NDT Supply.com, Inc.**

7952 Nieman Road  
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125  
e-mail: [sales@ndtsupply.com](mailto:sales@ndtsupply.com), [www.ndtsupply.com](http://www.ndtsupply.com)



# All-New Graphic Display



Lemo connector above battery for easier access



- Larger text and graphics
- Viewable in direct sunlight
- Colored text and backlight
- Extended temperature range



- Help button – access on-board context-sensitive help



- QR Code - access additional information online

## Integrated Arca Swiss tripod mount



	XR200
Dimensions (with battery)	L: 12.17" (30.91 cm)
(with Picatinny Rails)	W: 4.26" (10.82 cm)
(without key)	H: 5.83" (14.81 cm)
Weight (with battery)	11.0 lbs. (5.0 kg)
Average Output Dose*	3 mR per pulse
Pulse Rate	10 pulses per second
Pulses per Battery charge	6000
Operating Temperature	-4 to 158 °F (-20 to 70 °C)
IP Rating	IP 54

\*Dose measured at 12" (30 cm) from source

 **Golden Engineering**  
Portable X-ray Technology

**Celebrating 50 Years**  
of supplying quality products,  
providing extraordinary service,  
improving portable X-ray technology,  
and being family-owned and operated.