

Announcing the XRS2-MD

Front and Rotational Side beam in one compact unit



Making the unseen seen Versatile and Adaptable

Blue Front beam cap

Compatible with existing accessories
Minimized image edge fade

Gold Side beam cap

Rotates 360°
Operate in tight space



NDT Supply.com, Inc.

7952 Nieman Road
Lenexa, KS 66214-1560 USA



Phone: 913-685-0675, Fax: 913-685-1125
e-mail: sales@ndtsupply.com, www.ndtsupply.com



All-New Graphic Display



Lemo connector above battery for easier access



- Larger text and graphics
- Viewable in direct sunlight
- Colored text and backlight
- Extended temperature range
- Help button – access on-board context-sensitive help
- QR Code - access additional information online

Integrated Arca Swiss tripod mount



Field-Interchangeable Caps



- Adapt to the situation
- Direct X-ray beam **forward** or any angle out the **side**

		XRS2MD
Dimensions	(with battery)	L: 14.42" (36.63 cm)
	(with Picatinny Rails)	W: 4.23" (10.74 cm)
	(without key)	H: 5.28" (13.41 cm)
Weight	(with battery)	8.40 lbs. (3.81 kg)
X-Ray Energy		215 kVe
Average Output Dose*	Forward	1 mR per pulse
	Side	0.4 mR per pulse
Pulse Rate		25 pulses per second
Pulses per Battery charge		10000
Operating Temperature		-4 to 158 °F (-20 to 70 °C)
IP Rating		IP 54

* Dose measured at 12" (30 cm) from source

* screen images simulated

NDT Supply.com, Inc.
7952 Nieman Road
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125
e-mail: sales@ndtsupply.com, www.ndtsupply.com



Golden Engineering
Portable X-ray Technology

50 Years

of supplying quality products, providing extraordinary service, improving portable X-ray technology, and being family-owned and operated.

1" steel