

COMPARATIVE CHART OF COMPLIANT SPECTROLINE® UV-A LED LAMPS

Style	Series	Part Number	Nominal Steady-State UV-A Intensity at 15 in (38 cm)	UV-A Coverage at 15 in (38 cm) at minimum 1,200 µW/cm ²	Power Source	
ASTM E3022-18 & RRES 90061 (Rolls-Royce) Compliant Lamps						
Handheld		uVision™ 365	UV-365SBLC	< 5,000 µW/cm ²	6 in (15 cm) Ø	AC Cord
			UV-365MSBLC	< 5,000 µW/cm ²	6 in (15 cm) Ø	AC/DC (NiMH Battery)
			UV-365ZSBLC	< 5,000 µW/cm ²	6 in (15 cm) Ø	AC/DC (Li-ion Battery)
			UV-365SBLCR	< 5,000 µW/cm ²	6 in (15 cm) Ø	AC Cord & Reel
Overhead		EDGE™ 13	EDG-13SBLC	4,700 µW/cm ²	14.5 x 13 in (37 x 33 cm)	AC Cord
ASTM E3022-18 Compliant Lamps						
Handheld		uVision™ 365	UV-365HC	6,000 µW/cm ²	6.4 in (16 cm) Ø	AC Cord
			UV-365MHC	6,000 µW/cm ²	6.4 in (16 cm) Ø	AC/DC (NiMH Battery)
			UV-365ZHC	8,000 µW/cm ²	7.5 in (19 cm) Ø	AC/DC (Li-ion Battery)
			UV-365HCR	6,000 µW/cm ²	6.4 in (16 cm) Ø	AC Cord & Reel
Handheld		Classic	CLA-100	5,700 µW/cm ²	6 in (15.25 cm) Ø	AC Cord
			CLA-100Z	5,700 µW/cm ²	6 in (15.25 cm) Ø	AC/DC (Li-ion Battery)
			CLA-150	8,000 µW/cm ²	7 in (17.78 cm) Ø	AC Cord
Overhead		PowerMax™ 365	PM-16B	6,500 µW/cm ²	23.6 x 10.63 in (60 x 27 cm)	AC Cord
			PM-32B	6,500 µW/cm ²	43.3 x 10.63 in (110 x 27 cm)	AC Cord
			EDGE™ 13	EDG-13HC	8,500 µW/cm ²	24 x 22 in (61 x 56 cm)
Flashlight		CLARITY™ 365	SPN-CLR365-HC	6,750 µW/cm ²	3 in (8 cm) Ø	Li-ion Battery
			SPN-CLR365-SC	4,500 µW/cm ²	4 in (10 cm) Ø	Li-ion Battery
Headlamp		EagleEye™	EK-3000	4,500 µW/cm ²	5.5 in (14 cm) Ø	Li-ion Battery

