

# NDT Supply.com, Inc.

7952 Nieman Road  
Lenexa, KS 66214-1560 USA



## SC75 CLEANING CONCENTRATE

SC75 is a concentrated semi-aqueous, micro-emulsion solution. It can be used as a pre-wash chemical to remove oil, grease, corrosion and rust, and residue from metal parts. Also, SC75 is an excellent choice for removing heavy oil and water-based paints, ink, and adhesives.

This product has proven itself in hundreds of applications, by removing powder coatings, e-coatings, epoxy systems, oil & water-based paints, adhesives, inks and petroleum-based products. Turpentine products will not harm alloys such as steel, aluminum, copper, magnesium, brass, and most plastic substrates.

### Applications:

- ADHESIVE REMOVAL
- AIRCRAFT STRIPPING
- AUTO RESTORATION
- COATINGS REMOVAL
- CONCRETE RESTORATION
- CYCLINDER STRIPPING
- DEGREASING & RUST REMOVAL
- E-COAT REMOVAL
- FLOOR CLEANING
- FURNITURE STRIPPING
- GRAFFITI REMOVAL
- HOOK STRIPPING
- INK REMOVAL
- ISO POLYUREA
- PAINT OVERSPRAY
- PAINT REMOVAL
- PIGMENT & DYE
- POWDER COAT REMOVAL
- RESIN REMOVAL & RUST REMOVAL
- TANK CLEANING
- TEFLON COATING REMOVAL

Physical Properties	
Appearance:	Yellow Liquid
pH @ 1% solution:	3.5
Odor:	Mild
Foaming action:	Controlled
Solubility in water:	Complete
Rinsing action:	Excellent
Metal Safety:	All Metals
Flash point:	None
Specific Gravity:	1.073
Stability:	Stable

Phone: 913-685-0675  
Fax: 913-685-1125

sales@ndtsupply.com  
www.ndtsupply.com

# NDT Supply.com, Inc.

7952 Nieman Road  
Lenexa, KS 66214-1560 USA



## HANDLING & STORAGE

This product does not pose any fire hazards. Use good industrial hygiene practices such as wearing rubber gloves and an impermeable apron to protect sensitive skin. Chemical safety goggles should be worn to protect eyes. If eye contact occurs, flush with plenty of water for at least 15 minutes and consult a physician. In case of skin contact, wash with soap and water, removing contaminated clothing and shoes. Keep product containers tightly closed when not in use. Store in the original container between 45° and 85°F. When stored as above, shelf life is a minimum of 2 years.