

## North American Standard - I4

- 9.4mm (0.37in) Outer Diameter, 51mm (2in) Length, suitable for hard to reach detection areas
- Top Mounting UHF waterproof Connector

| Frequency | Diameter |       | Models    |             | Probe Specification |      |     |      |    |
|-----------|----------|-------|-----------|-------------|---------------------|------|-----|------|----|
|           |          |       |           |             | Focal Range         |      |     |      |    |
|           | MHz      | mm    | in        | PL          | PH                  | Min  | Max | mm   | in |
| 2.25      | 6        | 0.25  | I4-2.25P6 | I4-2.25P6-H | 10                  | 0.39 | 12  | 0.47 |    |
| 3.5       | 6        | 0.25  | I4-3.5P6  | I4-3.5P6-H  | 11                  | 0.43 | 17  | 0.67 |    |
| 5         | 6        | 0.25  | I4-5P6    | I4-5P6-H    | 12                  | 0.47 | 25  | 0.98 |    |
| 10        | 6        | 0.25  | /         | I4-10P6-H   | 13                  | 0.51 | 45  | 1.77 |    |
| 15        | 3        | 0.125 | /         | I4-15P3-H   | 7                   | 0.28 | 15  | 0.59 |    |
|           | 6        | 0.25  | /         | I4-15P6-H   | 13                  | 0.51 | 50  | 1.97 |    |
| 20        | 3        | 0.125 | /         | I4-20P3-H   | 8                   | 0.31 | 22  | 0.87 |    |
| 25        | 3        | 0.125 | /         | I4-25P3-H   | 10                  | 0.39 | 23  | 0.91 |    |

