



## X0

### Features

- Quick I-PEX Connector (QX)
- Quick I-PEX Bracket
- 5m Cable
- Other cable lengths upon request

Product Code	Probe Description	Frequency	Number Elements	Elevation	Element Pitch	Aperture	External Dimensions		
		F (MHz)	Qty	E (mm)	P (mm)	L (mm)	L (mm)	W (mm)	H (mm)
X0A-001	X0A-2.25M16EFC35-0.5x10-SQX5	2.25	16	10	0.5	8	26	22	9.7
X0A-002	X0A-5M16EFC35-0.5x10-SQX5	5	16	10	0.5	8	26	22	9.7
X0A-003	X0A-7.5M16EFC35-0.5x10-SQX5	7.5	16	10	0.5	8	26	22	9.7
X0A-004	X0A-10M16EFC35-0.5x10-SQX5	10	16	10	0.5	8	26	22	9.7
X0A-005	X0A-10M32EFC35-0.25x10-SQX5	10	32	10	0.25	8	26	22	9.7

Wedge	Description	Wave Type LW/SW	Angle Steel (°)	Cut Angle (°)	Delay Line (mm)	Length L (mm)	Width W (mm)	Front Height H1 (mm)	Back Height H2 (mm)
X0AW-001	X0AW-N60S-IH	S	60	39	0	18	21	13.2	2.4
X0AW-002	X0AW-N55S-IH	S	55	36	0	18	21	13.2	2.4
X0AW-003	X0AW-N45S-IH	S	45	31	0	18	21	13.2	2.4
X0AW-004	X0AW-N60L-IH	L	60	20	0	18	21	9.0	2.4