



X3

Features

- Quick I-PEX Connector (QX)
- Quick I-PEX Bracket
- 2.5m Cable
- Other cable lengths upon request

X3 Series - Sectorial & Linear Scan

Product Code	Probe Description	Frequency	Number Elements	Elevation	Element Pitch	Aperture	External Dimensions		
		F (MHz)	Qty	E (mm)	P (mm)	L (mm)	L (mm)	W (mm)	H (mm)
X3A-001	X3A-2.25M48E-0.8x10-SQX2.5	2.25	48	10	0.8	38.4	45	23	20
X3A-002	X3A-3.5M64E-0.6x10-SQX2.5	3.5	64	10	0.6	38.4	45	23	20
X3A-003	X3A-5M64E-0.6x10-SQX2.5	5	64	10	0.6	38.4	45	23	20
X3A-004	X3A-10M64E-0.6x7-SQX2.5	10	64	7	0.6	38.4	45	23	20

Wedge	Description	Wave Type LW/SW	Angle Steel (°)	Cut Angle (°)	Delay Line (mm)	Length L (mm)	Width W (mm)	Front Height H1 (mm)	Back Height H2 (mm)
X3AW-001	X3AW-0L25	L			25	65	25	25	25
X3AW-002	X3AW-N45S	S	45	31		65	25	41	16.7
X3AW-003	X3AW-N55S	S	55	36		65	25	38.6	11.7
X3AW-004	X3AW-N60S	S	60	39		65	25	36.3	7.5
X3AW-005	X3AW-N45L	L	45	16		65	25	34.4	21
X3AW-006	X3AW-N60L	L	60	20		65	25	43	25

X3-Glider - Compact Linear Scan

Wedge	Description	Wave Type LW/SW	Angle Steel (°)	Cut Angle (°)	Delay Line (mm)	Length L (mm)	Width W (mm)	Front Height H1 (mm)	Back Height H2 (mm)
X3AG-001	X3AG-0L25	L	0		25	66	34.1	25	25