



MMA

Features

- Rectangular, PZT crystal
- Medium damped for medium bandwidth
- European Standard transducer

Frequent Applications

- Castings & Forgings
- Critical Welds
- General Welds
- Machined Parts
- Rail
- Tube & Pipe

Transducer Models

Product Code	Description	Frequency (MHz)	Beam Angle (°)	Crystal Diameter (mm)	Nearfield Length* (mm)	Crystal Diameter (inches)
MMA2-45	Single Shear 2Mhz 45°	2	45	14 x 16	39	0.551 x 0.630
MMA2-60	Single Shear 2Mhz 60°	2	60	14 x 16	39	0.551 x 0.630
MMA2-70	Single Shear 2Mhz 70°	2	70	14 x 16	39	0.551 x 0.630
MMA4-45	Single Shear 4Mhz 45°	4	45	14 x 16	78	0.551 x 0.630
MMA4-60	Single Shear 4Mhz 60°	4	60	14 x 16	78	0.551 x 0.630
MMA4-70	Single Shear 4Mhz 70°	4	70	14 x 16	78	0.551 x 0.630

Size Options				Connector		
Probe Size	Case Dimensions			Type		Position
∅ (inches)	A (mm)	B (mm)	C (mm)	Microdot (D)	Lemo 00 (Z)	Rear (R)
14 x 16	41	22	29	x	x	x