

# DEMAGNETIZING SOLUTIONS

Demagnetizing Equipment & Services

www.demagnetizingsolutions.com • 908.444.MAG1

Using the extremely portable **Pipeline Demagnetizing System**, a high quality weld can be made quickly and efficiently. Tough inspections will be easier to pass. The system has the ability to reverse current through the Demagnetizing Cable without having to re-wrap the cable around the pipe.

The Pipeline Demagnetizing System weighs less than 100 lbs., operates from 110V – 220V and includes the following: Power Controller, Demagnetizing Cable, Gaussmeter, In-line GFCI and Transit Case.



Power Controller DSDC-5	Demagnetizing Cable	Gaussmeter	In-line GFCI	Transit Case
<b>Mode of Operation</b>	<b>Cable Length</b>	<b>Model</b>	<b>Rating</b>	<b>Material</b>
Manual DC 0 – 100%	100 feet	Alpha Labs GM1-ST	Up to 30 AMPS	TTX01 High-Strength Resin
<b>Power Input</b>	<b>Characteristics</b>	<b>Operation</b>	<b>Reset Type</b>	<b>Features</b>
<ul style="list-style-type: none"> <li>• 110V AC – 220V AC</li> <li>• 30 AMPS Max</li> <li>• Single Phase – 50/60 HZ</li> </ul>	<ul style="list-style-type: none"> <li>• Heavy Duty PVC</li> <li>• Built-in Dust Caps</li> <li>• Flexible</li> <li>• UV, Water, Weather &amp; Oil Resistant</li> </ul>	Handheld with Probe	Manual Reset	<ul style="list-style-type: none"> <li>• Retractable Handle</li> <li>• Built-in Wheels</li> </ul>
<b>Operating Temp.</b>	<b>Operating Temp.</b>	<b>Battery</b>	<b>Operating Temp.</b>	<b>Dimensions</b>
-10° – +120° F	-10° – 200° F	9 V Alkaline	-31° – +151° CF	<ul style="list-style-type: none"> <li>• Length – 28 inches</li> <li>• Width – 22 inches</li> <li>• Height – 15 inches</li> </ul>
<b>Weight</b>	<b>Weight</b>	<b>Weight</b>	<b>Weight</b>	<b>Weight</b>
10 pounds	50 pounds	1.5 pounds	2.5 pounds	25 pounds
<b>Power Output</b>				
Full Wave DC				

**NDT Supply.com, Inc.**  
7952 Nieman Road  
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125  
e-mail: [sales@ndtsupply.com](mailto:sales@ndtsupply.com), [www.ndtsupply.com](http://www.ndtsupply.com)

