

Demagnetizing Devices MM HE

MAURER
Classic



NDT Supply.com, Inc.

7952 Nieman Road
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125
e-mail: sales@ndtsupply.com, www.ndtsupply.com



MAURER[®]
MAGNETIC AG

Demagnetizing devices for mobile use

These reliable and dynamic demagnetizing devices are designed to remove residual magnetism; they are particularly suitable for demagnetizing difficult spots.

The demagnetizing depth of these devices is up to 15 mm.

They demagnetize work parts, tools, surfaces and more.

In order to demagnetize a part, the device is moved across the part in a sliding motion.

Characteristics

- **Versatile**
- **Portable**
- **Sturdy, for shop floor use**
- **For surfaces**

	MM HE1	MM HE2
Dimensions W x H x T	88 x 85 x 55 mm	210 x 122 x 140 mm
Maximum field, peak ¹	170 kA/m	320 kA/m
Service cycle	S2, max. 25 min. discontinuous operation	S2, max. 25 min. discontinuous operation
Power supply	230 VAC / 50 Hz / 0.25 A 115 VAC / 60 Hz / 0.5 A	230 VAC / 50 Hz / 3.3 A 115 VAC / 60 Hz / 6.6 A
Weight	0.8 kg	7.4 kg
Protection class IP	41	41

Made in Switzerland 

¹ Divide by 1,41 to obtain RMS value

MM HE1



MM HE2



Magnetizing & Demagnetizing Technology



Maurer Magnetic AG
Industriestrasse 8
CH-8627 Grüningen

Phone +41 44 936 60 40
Fax +41 44 936 60 49

info@maurermagnetic.ch
www.maurermagnetic.ch