TECHNICAL DATA SHEET

Integrity Pillowz™



Integrity Pillowz[™] are made from high temperature resistant Vermiculite Fabric and used in conjunction with Integrity Plugz[™] inspection ports. The Integrity Pillowz[™] add a layer of protection by creating a barrier between the internal pipe and the Integrity Plugz[™] inspection ports. This product is a great solution where there is concern that the cut out insulation is not being put back in under the inspection cover and/or where high temperatures are a concern. Integrity Pillowz[™] can be installed on insulated pipes, tanks, and vessels.

PRODUCT DESCRIPTION

Integrity Pillowz[™] are made from high performing Vermiculite Fabric for extra protection against high temperature applications. Integrity Pillowz[™] can provide temperature resistance up to 1100°F (593.3°C). The Integrity Pillowz[™] also includes a lanyard that integrates with the Integrity Plugz[™] inspection ports to avoid loss. The Integrity Pillowz[™] come standard with a pull handle to make removal simple.

MATERIAL SPECIFICATIONS

MATERIAL(S)

OUTER LAYER
High Temperature
Vermiculite Fabric
INNER LAYER

Fiberglass Fabric INSULATION LAYER

E-Glass Mat Insulation

WEAVE

Vermiculite Fabric (O.L) | 8-H Satin Treated Fiberglass (IS.L) | Plain

THICKNESS

Vermiculite Fabric (O.L.) | 0.070" E-Glass Insulation (IS.L) | 1"

MAXIMUM CONTINUOUS TEMP.

OUTER LAYER Vermiculite Fabric | 1100°F (593.3°C) INNER LAYER

Treated Fiberglass | 1100°F (593.3°C) INSULATION LAYER

E-Glass Insulation 1000°F (537.7°C)

COLOUR

Various

OTHER SPECIFICATIONS

Outer Layer (O.L.) Inner Layer (I.L.) Insulation Layer (IS.L)

VERMICULITE FABRIC (O.L.) E-GLASS (IS.L.)

Meets NFPA 701-1999 Fire Tests for Flame-Resistant Textiles and Films Method 1. Conforms to Mil-DTL24244D(SH), USCG Subpart 164.009, ASTM E84, NRC 1.36

PRODUCT SIZES















NDT Supply.com, Inc. 7952 Nieman Road Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125 e-mail: sales@ndtsupply.com, www.ndtsupply.com

