

Kowolux X6 LED large format viewers



Specifications	KOWOLUX X6	KOWOLUX X6eco
Viewing area:	380 x 270 mm 15 x 10.6 in	380 x 270 mm 15 x 10.6 in
Luminance:	160,000 Cd/m ² *	100,000 Cd/m ² *
for film density:	4.2 D max. **	4.0 D max. **
Rated power:	500 W	340 W
Dimensions	530x330x380 mm 20.9 x 13 x 15 inches	530x330x380 mm 20.9 x 13 x 15 inches
Weight	25 kg 61.7 lbs.	22 kg 48.5 lbs.
Article number:	13 40140	13 40142

Suitable for large format X-ray films with higher density from castings and other complex parts and components
Specification:

- Housing made of stainless steel in ergonomic design
- Interchangeable attachment masks for different film size
- Two potentiometers for brightness control – 0.2 ... 100 percent
- Cooling fan with temperature dependent speed control for low noise level
- Plug-in foot switch – viewer operable without foot switch
- other design features similar to other KOWOLUX X series viewers
- * Luminance approximately 10 percent higher than specified when delivered
- ** according to DIN EN 25580, ISO 5580, ASTM E 1390 max. density
- Life time LEDs: 40,000 h
- Power supply: 100 ... 240 V / 50/60 Hz
- Color temperature: 5,000 K