



## Mi-Glow® 778

Mi-Glow® 778 is Mi-Glow® 800 fluorescent yellow-green particles premixed with liquid Wetting Agent 771 for use in water media. This advanced formulation allows for superior corrosion protection, wetting and particle mobility. It is designed to be used with UV-A light to detect very fine discontinuities in finished products. This material is used in the automotive and aerospace industries on finished component parts, where extra corrosion protection is required.

### Physical Characteristics

Forest green solution with a slight detergent odor.

### Particle Certification

Particles meet or exceed all relevant industry specifications, including but not limited to ASTM E 1444, AMS 3044, MIL-STD-271, NAVSEA 250-1500-1, and NTR-1E. Certification is included with each shipment.

### Particle Color

Fluorescent Yellow-Green

### Average Particle Size

3  $\mu\text{m}$

### AMS Standard

3044

### SAE Sensitivity\*

8

[\*Representative of the number of lines shown on a tool steel ring as defined in SAE AS5282.]

### Temperature Range

32-120°F (0-49°C)

### Related Product Information:

Safety Data Sheet  
Technical Bulletin 267

**Item #**  
FG-3571

**Package Size**  
Case of 4 - 1 Quart Bottles

### NDT Supply.com, Inc.

7952 Nieman Road  
Lenexa, KS 66214-1560 USA

Phone: 913-685-0675, Fax: 913-685-1125  
e-mail: [sales@ndtsupply.com](mailto:sales@ndtsupply.com), [www.ndtsupply.com](http://www.ndtsupply.com)

