## MATERIAL SAFETY DATA SHEET

# **Magnetic Inspection Powder - PARKER RP6 RED**

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION:

CIRCLE SYSTEMS, INC.

479 W. Lincoln, P.O. Box 1228

Hinckley, IL 60520

815-286-3271 / After Hours EMERGENCY RESPONSE: Chem-tel 800-255-3924 Contract# MIS0001649

TRADE NAME: SIRCHEM® DRY POWDER 63 RED (PARKER RP6 RED)

FORMULA: A mixture of iron powder and pigments HMIS Rating: Health 1, Flammability 0, Reactivity 0

2. COMPOSITION, INFORMATION ON INGREDIENTS:

3. HAZARDS IDENTIFICATION:

THRESHOLD LIMIT VALUE:  $10 \text{ mg/m}^3$  for dust

EFFECTS OF OVEREXPOSURE: Slightly dusty material may cause eye, skin, and mucus irritation

4. FIRST AID MEASURES:

EYES: Flush with copious amounts of water INHALATION: Remove subject to fresh air

SKIN: Flush with water INGESTION: Do not induce vomiting. Drink large amounts of water.

SEEK MEDICAL ATTENTION IN ALL CASES

5. FIRE FIGHTING MEASURES:

FLASH POINT (METHOD USED): n.a.

FLAMMABLE LIMITS: n.a.

EXTINGUISHING MEDIA: Graphite, Sodium Chloride

SPECIAL FIRE FIGHTING PROCEDURES: Fog nozzle and fine spray to prevent dusting

UNUSUAL FIRE AND EXPLOSION HAZARDS: Fine dry dust exceeding minimum explosive concentration can explode in presence of ignition.

# 6. ACCIDENTAL RELEASE MEASURES:

Vacuum or carefully sweep up material into container and dispose of according to federal, state, and local regulations.

#### 7. HANDLING AND STORAGE:

Keep material clean and dry until ready to use. Severe dusting in enclosed area may explode from ignition source.

OTHER PRECAUTIONS: Dust-tight wiring, fixtures, etc. recommended. Physical properties may deteriorate if stored in conditions of excessive moisture.

# 8. EXPOSURE CONTROLS, PERSONAL PROTECTION:

VENTILATION REQUIREMENTS: Local exhaust if OSHA limits are exceeded

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT:

EYE: Safety glasses or goggles RESPIRATORY: Recommended - Powder or dust mask if OSHA limits are exceeded

GLOVES: Recommended OTHER CLOTHING & EQUIPMENT: n.a.

### 9. PHYSICAL AND CHEMICAL PROPERTIES:

BOILING POINT: n.a.

VAPOR PRESSURE: n.a.

VAPOR DENSITY (AIR=1): n.a.

SOLUBILITY IN WATER: Negligible

SPECIFIC GRAVITY (H<sub>2</sub>O=1): 2.5

W VOLATILE BY VOLUME: n.a.

EVAPORATION RATE (ETHER=1): n.a.

APPEARANCE & ODOR: Red powder, odorless

# 10. STABILITY AND REACTIVITY:

STABILITY: Stable HAZARDOUS DECOMPOSITION PRODUCTS: n.a. INCOMPATIBILITY: Strong oxidizers HAZARDOUS POLYMERIZATION: Will not occur

#### 11. TOXICOLOGICAL INFORMATION:

TLV (Threshold Limit Value): 10 mg/m<sup>3</sup> for dust

CARCINOGENICITY: Contains no known suspected carcinogens listed with OSHA, IARC, NTP, or ACGIH

### 12. ECOLOGICAL INFORMATION:

No available data.

#### 13. DISPOSAL CONSIDERATIONS:

Vacuum material up and return to container. Dispose of according to federal, state, and local regulations.

### 14. TRANSPORT INFORMATION:

D.O.T. SHIPPING NAME: Not Regulated

D.O.T. Hazard Class: None U.N./N.A. Number: None

Canadian Labels: Not Applicable

### 15. REGULATORY INFORMATION:

TSCA (Toxic Substance Control Act): Components of this product are listed on the TSCA Inventory.

CERCLA (Comprehensive Response Compensation, and Liability Act): NOT Reportable.

SARA TITLE III (Superfund Amendments and Reauthorization Act), SECTION 313 (Reportable Ingredients): No reportable ingredients.

CALIFORNIA PROPOSITION 65: Contains nothing on this list.

#### 16. OTHER INFORMATION:

PREPARED BY: Deborah A. Shreve

TITLE: Vice President/Director of Quality Control

ISSUE DATE: January 15, 2013

SUPERSEDES DATE: January 11, 2012

**DISCLAIMER:** OUR TECHNICAL ADVICE, INFORMATION & STATEMENTS - GIVEN VERBALLY, IN WRITING OR IN THE FORM OF TEST RESULTS - IS OFFERED FOR YOUR GUIDANCE WITHOUT WARRANTY. **NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE**. IT IS THE USER'S RESPONSIBILITY TO TEST THE SUITABILITY OF EACH PRODUCT FOR HIS INTENDED PROCESS AND APPLICATIONS. OUR GUARANTEE IS LIMITED TO THE CONSISTENT QUALITY OF OUR PRODUCTS.



Phone: 913-685-0675, Fax: 913-685-1125 e-mail: sales@ndtsupply.com, www.ndtsupply.com

